

NETWORK ENVIRONMENT SEPARATION

FIELD OF THE PRESENTLY DISCLOSED SUBJECT MATTER

This invention relates to the field of information security and more particularly to the field of network environment separation.

BACKGROUND

Separating between groups of nodes within a communication network, where each group constitutes a separated network environment, is becoming a key element in the field of information security. Consider for example the network architecture illustrated in **Fig. 1**, which shows two Local Area Networks **LAN1** and **LAN2** (LAN- local area network) that are connected over an encrypted Virtual Private Network (VPN) tunnel, established by two access routers (**R1** and **R2**). **LAN1** and **LAN2** can represent, for example, local area networks of the same organization, which are located at different locations on the globe. As can be seen in **Fig. 1** routers **R1** and **R2** on either sides of the network are connected each to a number of nodes. The nodes in **LAN1** and **LAN2** are divided into departments, department **A** (e.g. engineering) and department **B** (e.g. accounting). The nodes which are assigned to department **A** in both **LAN1** and **LAN2** constitute a first network environment and the nodes which are assigned to department **B** in both **LAN1** and **LAN2** constitute a second network environment.

For various reasons it is often advantageous to maintain a clear separation between different departments in the same organization and establish separate network environments, which prevent unauthorized data transfer from one environment to the other. However, while data which is being transferred from one LAN to another can be encrypted, once the data

enters the internal domain of the target LAN it is decrypted and becomes vulnerable to access by unauthorized environments.

Published references considered to be relevant as background to the presently disclosed subject matter are listed below. Acknowledgement of the references herein is not to be inferred as meaning that these are in any way relevant to the patentability of the presently disclosed subject matter.

IEEE Standard for Local and metropolitan area networks Virtual Bridged Local Area Networks: IEEE Std 802.1Q™-2005, IEEE Std 802.1Q-1998, IEEE Std 802.1u™-2001, IEEE Std 802.1v™-2001, and IEEE Std 802.1s™-2002.

SUMMARY

According to an aspect of the presently disclosed subject matter there is provided a separation module: the separation module being operatively connectible to a network device operable to facilitate data communication in a communication network, the separation module being configured to control data communication in the communication network, the separation module being assigned with a network-id associating the separation module with a given network environment; the separation module being further configured to: tag, with the help of the network-id, a data packet received by the network device from a first direction, in order to associate the data packet with the given network environment; and determine whether a tag, associated with a data packet received by the network device from a second direction, is compatible with the assigned network-id, and if it is, remove the tag from the data packet and allow transmission of the data packet.

According to certain embodiments of the presently disclosed subject matter, the separation module is an internal separation module, wherein the first direction is an uplink direction towards the network device and the second direction is a downlink direction away from the network device.

According to certain embodiments of the presently disclosed subject matter, the separation module is an external separation module, wherein the first direction is a downlink direction away from the network device and the second direction is an uplink direction towards the network device.

According to certain embodiments of the presently disclosed subject matter, the separation module comprises a direction determination module configured to adapt the separation module to match one of a first directionality or a second directionality, wherein in the first directionality the first direction is an uplink direction towards the network device and the second direction is a downlink direction away from the network device, and in the second directionality the first direction is a downlink direction away from the network device and the second direction is an uplink direction towards the network device.

According to certain embodiments of the presently disclosed subject matter, the tag is applied to a payload of the data packet.

According to certain embodiments of the presently disclosed subject matter, the separation module according to claim 1 further comprising:

a data-repository for storing the network-id and a processor associated with a tagging module configured to perform the tagging; and a validation module configured to determine whether the tag is compatible with the separation module.

According to certain embodiments of the presently disclosed subject matter, the separation module is incorporated in a security manager; the security manager operatively connected to a network device and to an external network, and being operable to control transmission of data between the network device and the external network; the security manager comprises or otherwise associated with a data repository configured for storing network-ids; the separation module is configured to: receive a data packet, sent via an external separation module in the network device; the data packet comprising

a first tag and a second tag; determine whether the second tag, associated with the data packet, is compatible with any one of network-ids stored in the data repository; if it is, remove the tag from the data packet; and determine whether the first tag, associated with the data packet, is compatible with any one of network-ids stored in the data repository; if it is, remove the tag from the data packet; and allow the transmission of the data packet to the external network.

According to another aspect of the presently disclosed subject matter there is provided a network device configured to control communication of data between nodes associated with one or more network environments; the network device comprising: at least a first separation module and a second separation module, the first separation module being operationally connected to a first node connected to the network device; the first separation module is configured to tag a data packet received from the first node, with the help of a network-id assigned to the first separation module, the tag being indicative of a respective network environment of the first node; and transmit the data packet towards the second separation module.

According to certain embodiments of the presently disclosed subject matter, the second separation module is associated with a second node connected to the network device; the second separation module is configured to: receive the data packet; determine whether the tag associated with the data packet is compatible with the second separation module; and if it is, remove the tag from the data packet and allow transmission of the data packet to the second node.

According to certain embodiments of the presently disclosed subject matter, the second separation module is an external separation module associated with an external communication network connecting the network device to a second network device; the external separation module is configured to: tag the data packet received from the first separation module,

with a second tag, the second tag being indicative of a respective network environment of the network device; and transmit the data packet towards the second network device.

According to another aspect of the presently disclosed subject matter, secure small form-factor pluggable transceiver (SFP) comprising the separation module described above, the SFP being operatively connectible to a network device to facilitate data communication with the network device in a communication network.

According to another aspect of the presently disclosed subject matter there is provided a method of controlling transmission of data in a communication network, the method comprising:

tagging, a data packet received by a network device from a first direction in the communication network; the tagging is performed with the help of a network-id assigned to the network device, the network-id is indicative that the data packet is associated with a given network environment; and determining whether a tag associated with a data packet, received by the network device from a second direction, is compatible with a network-id assigned to a target device, and if it is, removing the tag from the data packet and allowing transmission of the data packet to the target device.

According to certain embodiments of the presently disclosed subject matter, the first direction is an uplink direction towards the network device and the second direction is a downlink direction away from the network device.

According to certain embodiments of the presently disclosed subject matter, the first direction is a downlink direction away from the network device and the second direction is an uplink direction towards the network device.

According to certain embodiments of the presently disclosed subject matter, wherein the network device is connected to a first node and a second node, the method comprising: performing the tagging on a data packet received from a first node connected to the network device; and performing the determining on the data packet being transmitted to a second node connected to the network device; thereby controlling transmission of data between the first node and the second node.

According to another aspect of the presently disclosed subject matter, there is provided a method of controlling transmission of data in a communication network via a network device, the method comprising: receiving from a first node connected to the network device a data packet destined to a second node connected to a second network device; the network and the second network device are connected over a communication network; tagging the data packet received from the first node with a tag being indicative of a respective network environment of the first node; tagging the data packet with a second tag being indicative of a respective network environment of the network device; and transmitting the data packet to the second network device via the communication network; thereby enabling the second network device to determine whether to allow transmission of the data packet.

According to certain embodiments of the presently disclosed subject matter, The method further comprising: receiving a data packet from the second network device destined to a node connected to the network device; the data packet comprising a first tag and a second tag; in case the second tag, associated with the data packet, is compatible with the network device: removing the tag from the data packet; in case the first tag, associated with the data packet, is compatible with the node: removing the tag from the data packet; and allowing transmission of the data packet to the node.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the presently disclosed subject matter and to see how it may be carried out in practice, the subject matter will now be described, by way of non-limiting examples only, with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram schematically illustrating an example of network architecture as known in the art;

Fig. 2 is a functional block diagram schematically illustrating a router and a secure SFP transceiver, in accordance with the presently disclosed subject matter;

Fig. 3 is a functional block diagram schematically illustrating a network environment separation module, in accordance with the presently disclosed subject matter;

Fig. 4 is a functional block diagram schematically illustrating network architecture in accordance with the presently disclosed subject matter;

Fig. 5 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter;

Fig. 6 is a functional block diagram schematically illustrating another network-architecture, in accordance with the presently disclosed subject matter;

Fig. 7 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter;

Fig. 8 is a functional block diagram schematically illustrating another network-architecture, in accordance with the presently disclosed subject matter;

Fig. 9 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter;

Fig. 10 is a functional block diagram schematically illustrating a security manager, in accordance with the presently disclosed subject matter; and

Fig. 11 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter.

DETAILED DESCRIPTION

In the drawings and descriptions set forth, identical reference numerals indicate those components that are common to different embodiments or configurations.

Unless specifically stated otherwise, as apparent from the following discussions, it is appreciated that throughout the specification discussions utilizing terms such as "controlling", "tagging", "allowing", "validating", "determining" or the like, include action and/or processes of a computer that manipulate and/or transform data into other data, said data represented as physical quantities, e.g. such as electronic quantities, and/or said data representing the physical objects.

As used herein, the phrase "for example," "such as", "for instance" and variants thereof describe non-limiting embodiments of the presently disclosed subject matter. Reference in the specification to "one case", "some cases", "other cases" or variants thereof means that a particular feature, structure or characteristic described in connection with the embodiment(s) is included in at least one embodiment of the presently disclosed subject matter. Thus the appearance of the phrase "one case", "some cases", "other cases" or variants thereof does not necessarily refer to the same embodiment(s).

It is appreciated that certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the presently disclosed subject matter, which

are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

In embodiments of the presently disclosed subject matter, fewer, more and/or different stages than those shown in **Fig. 5, Fig. 7, Fig. 9 and Fig. 11** may be executed. In embodiments of the presently disclosed subject matter one or more stages illustrated in **Fig. 5, Fig. 7, Fig. 9 and Fig. 11** may be executed in a different order and/or one or more groups of stages may be executed simultaneously. **Fig. 2, Fig. 3, Fig. 4, Fig. 6, Fig. 8 and Fig. 10** illustrate a general schematic of the system and/or network architecture in accordance with an embodiment of the presently disclosed subject matter. Modules in **Fig. 2, Fig. 3, Fig. 4, Fig. 6, Fig. 8 and Fig. 10** can be made up of any combination of software, hardware and/or firmware that performs the functions as defined and explained herein. The modules in **Fig. 2, Fig. 3, Fig. 4, Fig. 6, Fig. 8, and Fig. 10** may be centralized in one location or dispersed over more than one location. In other embodiments of the presently disclosed subject matter, the system may comprise fewer, more, and/or different modules than those shown in **Fig. 2, Fig. 3, Fig. 4, Fig. 6, Fig. 8, and Fig. 10**.

As mentioned above it is often desirable to create segregated network environments within an organization and thus prevent unauthorized data transfer between different nodes within the organization which are assigned to different network environments. To this end, the teachings of the presently disclosed subject matter includes a secure network separation module which can be incorporated within a network device and which can control transmission of data between different network environments. The secure network separation module disclosed herein is adapted to enable the validation of data packets which are transmitted between different nodes and thereby restrict the unauthorized transmission of data packets between different network environments. The secure network separation module (or in short "separation module") of the presently disclosed subject matter can be incorporated as part of network devices (such as switches, routers, media

converters, advanced telecommunication cards (ATC), etc.) and be configured as a designated programmable module which is write-protected and can be accessed and altered in a secured manner, only by authorized personnel and with special equipment. Particularly, it is configured to be protected from modification of its preprogrammed parameters by remote access via the associated network.

For example, a separation module can be manufactured as a write protected memory device such as a one-time programmable non-volatile memory (OTP NVM) with a high-speed programmable logic (depending on the SFP bandwidth). Alternatively, a separation module can be a reprogrammable memory device which applies a stringent write-protection mechanism, for example a programmable FPGA that only accepts an encrypted binary with a pre-loaded (and burnt) key.

The separation module can be incorporated within a small form-factor pluggable (SFP) transceiver to create a secure SFP. In general an SFP can be plugged into a standard SFP-enabled network device, and used to interface the network device with a fiber optic or copper networking cable to facilitate communication between different nodes in a network. The secure SFP disclosed herein is adapted to facilitate the functionality of the separation module and enable the validation of data packets which are transmitted between different nodes and thereby restrict the unauthorized transmission of data packets between different network environments. The secure SFP can maintain the core structure of previously known SFPs and is therefore compatible with existing network infrastructure equipment.

In the following discussion the presently disclosed subject matter is described with reference to a secure SFP. However, it should be noted that a secure SFP is a non-limiting example and the presently disclosed subject matter contemplates other implementations of a separation module, for

example, in a printed circuit board which can be integrated as part of the network device's motherboard.

It should be also noted that although some aspects of the presently disclosed subject matter are described with reference to wired communication networks, this should not be construed as limiting and the presently disclosed subject matter can be implemented in a wired or wireless communication network and is not limited to any specific type of communication network or protocol.

Fig. 2 is a block diagram schematically illustrating a router and a secure SFP transceiver, in accordance with the presently disclosed subject matter. **Fig. 2** shows router **202** comprising a switching fabric **204** adapted to interconnect and enable data transmission between plurality of secure SFPs (**206_{1-n}**), which are connected to router **202**. **Fig. 2** also shows a detailed view of one secure SFP **210**. Secure SFP **210** comprises a physical interface **212** for physically connecting with an input cable and receiving incoming communication. Physical interface is connected to Phy **214** which can be configured for example to perform analog to digital and digital to analog conversion of incoming and outgoing communication signals, respectively.

According to the presently disclosed subject matter, SFP **210** further comprises a network environment separation module **216** (or in short "separation module") which is configured to control data transmission through SFP **210**. To this end, separation module **216** is preprogrammed with a "network-id" that identifies secure SFP **210** and assigns it to a certain network environment.

Separation module **216** is configured to receive data packets sent by a node to router **202** (uplinked data packets which are sent in the direction of the switching fabric) and based on its respective network-id, tag the data packet in order to indicate the respective network environment of the node. Separation module **216** is further configured to receive data packets

transmitted in the opposite direction i.e. from router **202** (down-linked data packets which are sent away from the switching fabric) and validate, again based on its respective network-id, that the data packets are being transmitted between nodes that are assigned to the same network environment.

In case the tag of a down-linked data packet matches the network-id assigned to the receiving SFP, this means that the node that transmitted the data is assigned to the same network environment assigned to the receiving SFP, and accordingly separation module **216** allows the transmission of the data packet to the requested target. Otherwise, in case the tag of a down-linked data packet does not match the network-id which is assigned to the receiving SFP, this means that the node which transmitted the data and the receiving SFP are assigned to different network environments and accordingly separation module **216** denies transmission of the data packet. The data packet can be discarded or saved for monitoring purposes.

The specific location of separation module **216** within secure SFP **210** may vary, for example in case secure SFP **210** comprises a network interface card (NIC) for storing a MAC address, separation module **216** can be located before or after the NIC card. However, in order to enable to control the transmission of data to the switching fabric, separation module **216** is located before the switching fabric.

Fig. 3 is a functional block diagram schematically illustrating a network environment separation module, in accordance with the presently disclosed subject matter. According to the example illustrated in **Fig. 3** network environment separation module **216** comprises a tagging module **301**, a validation module **303** and a stripping module **305**. Separation module **216** can also comprise a non-volatile computer memory **309** for storing its network-id. In some cases separation module **216** can further comprise a direction determination module **307**. In some configurations different modules described herein with reference to separation module **216** can be distributed

into separate units. Thus, for example, tagging module **301** can be configured in one unit and validation module **303** and stripping module **305** can be configured in a second unit. Separation module **216** can be associated with a processor (e.g. located in SFP **210**) to obtain processing capabilities. A more detailed description of the operations of the different modules in separation module **216** is provided below with reference to **Fig. 5**.

Fig. 4 is a functional block diagram schematically illustrating network architecture in accordance with the presently disclosed subject matter. The network architecture which is illustrated comprises a single router **R3** connected to a plurality of nodes (e.g. computer terminals, computer servers, computer facilities such as printers or fax machines, etc.). The nodes which are connected to router **R3** are assigned to different groups (denoted by the letters **A**, **B** and **C**) each group constituting a different network environment. As mentioned above each group of nodes can correspond, for example, to a different department in the same organization.

As can be seen in **Fig. 4** each node is connected to a respective secure SFP port in router **R3**. In some cases instead of directly connecting each node to router **R3**, part or all of the nodes assigned to the same group can first be connected to one or more intermediate routers which in turn can be connected to router **R3**. In addition, it should be noted that instead of a single router (router **R3**) as disclosed in **Fig. 4**, multiple interconnected routers can be used.

Router **R3** is configured in accordance with the teachings of the presently disclosed subject matter to obtain network environment separation and avoid data transfer between nodes which are assigned to different groups. Secure SFP ports (sSFP₁₋₃) are configured with separation module **216** as described above.

Fig. 5 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter. The operations in **Fig. 5** are described with reference to the network architecture presented in **Fig. 4**.

Consider for example communication of data from a first computer terminal connected to router **R3** to a second computer terminal connected to router **R3**. Initially data packets are transmitted from the first computer terminal to a secure SFP **210** (say **SFP₁**) in router **R3** to which the first computer is connected.

At block **501** a data packet is received in **SFP₁**. As explained above, in order to enable network environment separation between different groups of nodes, each group is assigned with a different network-id that enables to differentiate between data packets transmitted by nodes of different groups. Once the data packet is received in separation module **216** within **SFP₁** the uplinked data packet is tagged with the help of a network-id which is assigned to the respective network environment of the transmitting node (in this case the network-id which is assigned to group A) (block **503**). The network-id can be, stored for example, in **SFP₁** (e.g. in data-repository **309**) which connects the transmitting computer to router **R3**.

The data packet comprises a payload and a header where the payload is the actual data and the header carries metadata which includes the destination and source of the data packet. According to the presently disclosed subject matter, the payload of the data packet can be tagged while the header remains unchanged.

The tagging of an uplinked data packet can be performed by tagging module **301**. Different types of network-ids and different methods can be used for tagging the data packet. For example, a network-id can be a designated header (e.g. the VLAN standard header (802.1Q) can be used for tagging the data packet which is 4 bytes long), wherein the data packet can be tagged by adding the designated header to the payload. In some cases instead or in addition, the data packet can be tagged with the help of a weak encryption (e.g. the network-id being a weak One-Time-Pad encryption with a

fixed key) or a strong encryption (by using a strong encryption model with a matching key).

Once the uplinked data packet is tagged by separation module **216** it is forwarded to switching fabric **202** in router **R3** where it is routed to the secure SFP connecting the target computer terminal to router **R3** (block **505**). Routing can be accomplished based on the information in the data packet header which is left unmodified.

Separation module **216** in the receiving secure SFP is configured to validate that the tag of the data packet is compatible with the network-id which is preprogrammed in the receiving secure SFP (block **507**) and as mentioned above identifies the network environment of to the receiving secure SFP. Validation of the tagging of the data packet can be performed by validation module **303** in separation module **216**.

In some scenarios a single network environment can be allowed to communicate with several different other network environments (referred herein as “affiliated network environments”). In such cases a single separation module **216** can be configured to allow the transmission of data arriving from a plurality of different network environments. As each network environment can be assigned with a predefined network-id, a single separation unit **216** can be provided with information in respect of the affiliated network environments. To this end, data repository **309** can store a list of network-ids assigned to the affiliated network environments. Validation module **303** can be configured, during the validation stage (block **507**), to determine whether tagging of the data packet is compatible with any one of the network-ids of the affiliated network environments, which are stored in data-repository **309**. In cases where the tag of an incoming data packet is compatible with one of the network-ids stored in data repository **309**, the communication of the data packet is allowed.

The manner of validation is dependent on the type of tagging which is used. For example in cases where a designated header has been added to the payload, validation module **303** can simply compare between the designated header attached to the packet and the header which is expected by the receiving secure SFP.

In cases where tagging is more complex, such as some type of encryption, validation module **303** can be configured to check for example, whether the encryption key which is used, is the same encryption key that was assigned to the receiving secure SFP. For example, validation of the data can be performed by attempting to decrypt the encrypted payload. In such cases, separation module **216** can be configured to attempt to decrypt the encrypted payload. In cases where the decryption is successful, the transmission is allowed, and in cases where the decryption fails, transmission of data is denied.

In cases where the validation shows that the tagging of the data packet matches the network-id which is assigned to the receiving SFP (or in some cases any other network-id stored in data repository **309**), the tagging is removed and the stripped data packet is transmitted to the target node e.g. the destination computer terminal (block **509**). Removal of the tag can be accomplished, for example, with the help of stripping module **305** in separation module **216** of the receiving secure SFP. Otherwise, if the validation shows that the tagging of down-linked data packet is not compatible with the network-id assigned to the receiving SFP, the data packet data transmission to the target node is denied (block **511**).

The mechanism described above with reference to **Fig. 5**, enables to enforce network environment separation. For example, since network environment separation is maintained by tagging data packets based on a network-id which is embedded within the SFP port and is not based on an identity of a node enclosed in the data packet's header, a deliberate attempt to

send data from one node to another node in another network environment by altering the sender's address (i.e., a spoofing attack) would fail.

As mentioned above any reference made in the description to a secure SFP is merely by way of a non-limiting example and the presently disclosed subject matter contemplates other implementations of a separation module, for example, in a printed circuit board which can be integrated as part of the network device's motherboard.

Fig. 6 is a functional block diagram schematically illustrating another network-architecture, in accordance with the presently disclosed subject matter. **Fig. 6** shows a similar architecture to one presented earlier in **Fig. 1**. As explained above with reference to **Fig. 1**, **Fig. 6** shows an example of two Local Area Networks **LAN11** and **LAN21** which are connected over an encrypted VPN tunnel, established by two access routers (**R11** and **R21**). **LAN11** and **LAN21** can represent for example local area networks of the same organization which are located at different locations on the globe, connected by a wide-area network (WAN). According to the current example, routers **R11** and **R21** on either sides of the network are connected each to a number of nodes. According to the illustrated example, the nodes in **LAN11** and **LAN21** are divided into two departments, department **A** (e.g. engineering) and department **B** (e.g. accounting).

The nodes in each group can be connected to an intermediate router (not shown) which facilitates the connection to routers **R11** and **R21**. In order to restrict transmission of data between nodes of different groups and maintain network environment separation, SFPs in routers **R11** and **R21** are secure SFPs configured in accordance with the teachings disclosed herein.

Fig. 7 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter. The operations in **Fig. 7** are described with reference to the network architecture presented in **Fig. 6**.

Assume for the sake of example that data is being transmitted from a computer terminal (herein "transmitting computer terminal") in group **A**, in **LAN 11** to a computer terminal in **LAN21**. At block **701** an uplinked data packet is transmitted from the transmitting computer terminal and received by a respective secure SFP **210** in router **R11**. The uplinked data packet is processed by separation module **216** in secure SFP **210** and the uplinked data packet is tagged with the network-id assigned to that secure SFP **210** (block **703**).

As the data packet is targeted to a computer terminal located in another LAN connected over a WAN connection, the data packet is transmitted from the internal secure SFP to an external secure SFP (block **705**). As used herein the term "internal secure SFP" refers to a secure SFP which connects between nodes in the same LAN. Internal secure SFP are described above with reference to **Figs. 4 and 5**. The term "external secure SFP" refers to a secure SFP which connects between a LAN to an external domain such as another LAN, a public network (e.g. Internet), or any kind of shared resources.

In the current example a first external secure SFP connects router **R11** in **LAN11** to a WAN (wide area network) connection (**ESFP₁**) and a second external secure SFP connects router **R21** in **LAN21** to the WAN on the other side (**ESFP₂**). Data packets are forwarded from an internal secure SFP in **LAN11** to an external secure SFP connecting router **R11** to the external network. Note that data packets which are transmitted to an external secure SFP from an internal secure SFP (down-linked data packets) are already tagged the first time by the internal secure SFP.

At block **707** a down-linked data packet which is received by an external secure SFP (**ESFP₁**) is tagged a second time with a second tagging by the external secure SFP. The second tagging is based on a network-id assigned to the external SFP, and identifies the data packet as a data packet which was

sent by an external SFP to an external network. Since the second tagging is assigned only by external secure SFP the data cannot be accessed by other internal SFP unless the second tagging is stripped first. This helps for example to protect against accidental or deliberate transmission of data to the wrong target.

The second tagging can be accomplished for example with the help of an external network-id stored in data-repository **309** accessible to the external secured SFP. After the data is tagged for the second time it is transmitted over the WAN to its destination, in the current example an external secure SFP (**ESFP₂**) in router **R21** (block **709**).

The transmitted data packet is received at an external secured SFP (**ESFP₂**) in router **R21** within **LAN21** (block **711**) where the receiving SFP is configured to validate the second tag (block **713**). In cases where it is determined that the tag of the uplinked data packet is not compatible with the network-id assigned to the external secure SFP (**ESFP₂**) in **LAN21**, transmission of the data packet is denied (block **715**). Otherwise, in cases where it is determined that the tagging of the uplinked data packet is compatible with the external network-id of the external secure SFP (**ESFP₂**), separation module **216** is configured to strip the second tag from the data packet and forward the data packet to its target internal secure SFP, based on the information in the header of the data packet (block **717**).

Note that external secure SFPs and internal secure SFPs are configured differently. Although both types of SFPs perform similar operations, the directionality of the operations is inverted. An internal SFP tags uplinked data packets and strips the tag from down-linked data packets. An external secure SFP tags (with a second tag) down-linked data packets and strips the tag from uplinked data packets.

Thus, in accordance with the presently disclosed subject matter, an external secure SFP and an internal secure SFP are configured differently in

order to be adapted to their respective functionalities. To this end, separation module **216** can optionally comprise a direction determination module **307**. Direction determination module **307** can be configured in accordance with the required functionality of separation module **216** and adapt the directionality of separation module **216**.

In addition or instead of a direction determination module **307** two types of separation modules can be manufactured, an internal separation module and an external separation module. Whereas an internal separation module is configured to tag uplinked data packets and strip down-linked data packets, an external separation module is configured to strip uplinked data packets and tag down-linked data packets. An external secure SFP can comprise an external separation module, and an internal secure SFP can comprise an internal separation module.

Reverting to **Fig. 7**, at block **719** the data packet, now tagged only with a single tagging, is received at the internal secure SFP connected to the target node, where the first tagging of the payload is validated (block **719**).

In case the validation shows that tagging of the down-linked data packet is compatible with the one or more network-ids assigned to the internal secure SFP, the tagging is removed and the stripped data packet is transmitted to the target node (block **723**). This can be accomplished with the help of stripping module **305** in the receiving internal secure SFP. Otherwise, if the validation shows that the tagging of the incoming data packet is not compatible with the network-id assigned to the receiving internal SFP, transmission of data packet to target node is denied (block **721**).

As explained above, in cases where a plurality of affiliated network environments are present, validation module **303** can be configured, during the validation stage (block **713** and block **719**), to determine whether tagging of the data packet is compatible with any one of the network-ids of the affiliated network environments, which are stored in data-repository **309**. In

cases where the tag of an incoming data packet is compatible with one of the network-ids stored in data repository 309 the communication of the data packet is allowed.

Fig. 8 is a block diagram schematically illustrating another type of network architecture, in accordance with the presently disclosed subject matter. **Fig. 8** shows LAN (**LAN23**) divided into two groups, group **A** and group **B** which are both connected to router **R23**. Router **R23** is connected to a de-militarized zone (**DMZ**) via a firewall **FW**. **FW** is also connected to security manager **SM** located within the **DMZ** and to some type of an external shared resource such as a public network (e.g. the Internet), or a shared printer or fax machine.

Firewall **FW** is configured for adding an additional layer of security between the local area network of the organization and an unreliable external resource. Firewall **FW** is configured to enforce a security policy in order to provide better security to the LAN, limiting leakage of information from the LANs to the external resource and the ability to attack the LANs from an external resource (e.g. external networks). To this end, **FW** can operate one or more firewall applications and possibly other security measures, such as intrusion detection and prevention devices, anti-virus and spam filters.

Security manager **SM** is configured to provide additional security in accordance with the presently disclosed subject matter. As illustrated in **Fig. 8** security manager **SM** can be implemented as an independent processing unit, which resides in the **DMZ**. In other cases security manger **SM** can be incorporated as an integral part of **FW**.

Firewall **FW** and security manager **SM** may be, but are not limited to, personal or portable computers, a server computer or any other apparatus having the appropriate processing power for running the required operations and equipped with proper communication facilities and computer memory (including non-transitory computer memory). In general, servers are often

implemented as dedicated server-computers which are characterized by faster CPU, high performance RAM and possibly multiple hard drives and large storage space. Firewall **FW** and security manager **SM** are associated with at least one processor which is configured to manage and control relevant components and operations, and to perform tasks in response to instructions.

Fig. 10 is a functional block diagram schematically illustrating a security manager **SM**, in accordance with the presently disclosed subject matter. **SM** can comprise separation module **216** or similar components including, tagging module **301**, validation module **303** and stripping module **305**. Security manager **SM** also comprises a network-id determination module **1010** and a data repository **1012** for storing addresses of different devices (e.g. nodes and network devices) in the network and their corresponding network-id. Security manager can also comprise a processing unit **1014**. A more detailed description of the operations of the different modules in security manager is provided below with reference to **Fig. 9**.

Fig. 9 is a flowchart illustrating operations performed, in accordance with the presently disclosed subject matter. The operations in **Fig. 9** are described with reference to the network architecture presented in **Fig. 8**.

At block **901** a data packet transmitted from a source external to **LAN23** (e.g. the Internet) is received in security manager **SM**. The data packet is destined to a node in **LAN23**. Security manager **SM** utilizes the destination address of the target node, which is specified in the header of the data packet, to search in data-repository **1012** and locate the respective network-id assigned to the internal secure SFP which is connected to the requested target node. In a similar manner, security manager **SM** identifies the network-id which was assigned to an external secure SFP (**ESFP**) which connects security manger **SM** to router **R23** (block **903**). This can be accomplished with the help of network-id determination module **1010**. Based on the identified network-ids, security manager **SM** tags the incoming data

packet with a first tag (corresponding to target internal-secure-SFP) and a second tagging (corresponding to target external- secure-SFP) (block **905**).

Optionally, **SM** can determine whether an incoming data packet destined to a certain target device is authorized to be sent to the requested target. This can be accomplished for example by **FW**. In case it is determine that the data packet can be forwarded to the requested target (e.g. it does not include malicious content), it can tag the data packet as explained above. Otherwise the transmission of the data can be denied.

The doubly tagged data packet is then transmitted by security manager **SM** to an external secure SFP connected to the target LAN, which is in the current example router **R1** in **LAN23** (block **907**). The data packet is received in the external secure SFP (block **909**) where the SFP determines whether the second tagging of the data packet is in agreement with the network-id which was assigned to the external secure SFP e.g. with the help of validation module **303** (block **911**).

In cases where the validation shows that the second tagging of the incoming data packet is compatible with the network-id assigned to the external secure SFP, the second tagging is removed from the data packet and the data packet is transmitted to the target internal-secure-SFP which is the SFP connected to the target node (block **913**). Removal of the tag can be accomplished with the help of stripping module **305** in the external SFP (**ESFP**). Otherwise, if the validation shows that the tagging of the incoming data packet is not compatible with the network-id assigned to the external secured SFP (**ESFP**) further transmission of the data packet is denied (block **915**).

At block **917** the data packet, now tagged only with the first tag is received by the internal secure SFP (**ISFP** in **Fig. 8**) connected to the target node, where the first tag of the payload is validated e.g. with the help of validating module **303**. In case the validation shows that tagging of the

incoming data packet is compatible with the network-id assigned to the internal secure SFP (**ISFP**), the first tagging is removed from the data packet and the stripped data packet is transmitted to the target node (block **921**). Otherwise, if the validation shows that the tagging of the incoming data packet is not compatible with the network-id assigned to the internal secure SFP, further transmission of the data packet is denied and the data packet is discarded (block **923**).

This configuration of a **DMZ** can help to ensure that only data packets that passed through the **DMZ** (and **FW** in the **DMZ**) are allowed to be transmitted to the requested destination (in this case **LAN23**).

Fig. 11 is a flowchart illustrating operations performed in accordance with the presently disclosed subject matter. The operations in **Fig. 11** are described with reference to the network architecture presented in **Fig. 8** and refer to transmission of data from **LAN23** towards the external resource via security manager **SM**.

At block **1101** a data packet is transmitted from a node and received by the respective internal secure SFP in router **R23**. The uplinked data packet is processed by separation module **216** located in the internal secure SFP (e.g. **ISFP**) and the payload of the outgoing data packet is tagged based on the network-id assigned to the internal secure SFP **210** (block **1103**).

As the data packet is destined to a node located outside of **LAN23** (e.g. connected over the Internet), the data packet is transmitted from the internal secure SFP to an external secure SFP (**ESFP** in **Fig. 8**) which is connected to security manager **SM** in **DMZ** (block **1105**).

As explained above with reference to **Fig. 7** a tagged data packet which is received by an external secure SFP is tagged a second time with a second tagging by the external secure SFP (block **1107**). The second tagging identifies the data packet as a data packet which was sent by an external SFP

to an external resource. After the data is tagged for the second time, it is transmitted to security manager **SM** (block **1109**).

The transmitted data block is received at security manager (block **1111**) where the security manager is configured to validate the second tagging of the data packet e.g. with the help of validation module **303** (block **1113**). To this end, network-id determination module **1010** is used to locate in data repository **1012**, the network-id of the source external secure SFP (**ESFP**). The network-id is used by security manager **SM** to validate the second tagging of the payload.

In cases where it is determined that the second tagging of the payload of the incoming data packet is not compatible with the external network-id assigned to the source external secure SFP (**ESFP**), further transmission of the data packet is denied (block **1115**). Otherwise, in cases where it is determined that the tagging of data packet is compatible with the external network-id of the source external secure SFP (**ESFP**), stripping module in security manager is configured to remove the second tagging from the data packet (block **1117**).

At block **1119** security manager validates the first tagging of the data packet e.g. with the help of validation module **303**. As before network-id determination module **1010** is used to locate in data repository **1012**, the network-id of the source internal secure SFP. The network-id is used by security manager **SM** to validate the second tagging of the payload.

In cases where it is determined that the first tagging of the data packet is not compatible with the internal network-id assigned to the source external secure SFP, further transmission of the data packet is denied (block **1121**). Otherwise, in case it is determined that the first tagging of the data packet is compatible with the internal network-id of the source external secure SFP (**ISFP**), the stripping module in the security manager is configured to remove the first tagging from the payload and forward the data packet to the external resource (block **1123**).

For example, data repository **1012** can comprise data indicating whether data transmitted from a device (e.g. node or network device) associated with a certain network environment is allowed be transmitted to the external network connected to **SM**. Thus, validation performed by validation module **303** includes determining whether the first and second tag identify a devices in a network environment which are allowed to transmit data to the external network.

As explained above, in cases where a plurality of affiliated network environments are present, validation module **303** can be configured, during the validation stage (block **911** and block **917** in **Fig. 9** and **1113** and **1119** in **Fig. 11**), to determine whether tagging of the data packet is compatible with any one of the network-ids of the affiliated network environments, which are stored in data-repository **309**. In cases where the tag of an incoming data packet is compatible with one of the network-ids stored in data repository **309** the communication of the data packet is allowed.

The mechanism described above with reference to **Figs. 8** and **Fig. 11**, enables to enforce restrictions on data communication. For example, since network environment separation is maintained by tagging data packets based on a network-id which is embedded within the SFP port and is not based on an identity of a node enclosed in the data packet's header, a deliberate attempt to send data from an unauthorized node inside **LAN23** to another node located outside **LAN23** by altering the sender's address (i.e., a spoofing attack) would be intercepted by security monitor **SM**.

It will also be understood that the presently disclosed subject matter may be implemented in a suitably programmed computer. Likewise, the presently disclosed subject matter includes a computer program being readable by a computer for executing the method of the presently disclosed subject matter. The presently disclosed subject matter further contemplates a machine-readable memory tangibly embodying a program of instructions

executable by the machine for executing the method of the presently disclosed subject matter. The machine-readable memory includes non-transitory machine-readable computer memory such as for example, CD-ROM, memory device, hard drive, etc.

It is to be understood that the presently disclosed subject matter is not limited in its application to the details set forth in the description contained herein or illustrated in the drawings. The presently disclosed subject matter is capable of other embodiments and of being practiced and carried out in various ways. Hence, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for designing other structures, methods, and systems for carrying out the several purposes of the present presently disclosed subject matter.

CLAIMS:

1. A separation module:

the separation module being operatively connectible to a network device operable to facilitate data communication in a communication network, the separation module being configured to control data communication in said communication network, the separation module being assigned with a network-id associating the separation module with a given network environment; the separation module being further configured to:

tag, with the help of said network-id, a data packet received by the network device from a first direction, in order to associate said data packet with said given network environment; and

determine whether a tag, associated with a data packet received by the network device from a second direction, is compatible with the assigned network-id, and if it is, remove the tag from the data packet and allow transmission of the data packet.

2. The separation module according to claim 1 is an internal separation module, wherein said first direction is an uplink direction towards the network device and said second direction is a downlink direction away from the network device.

3. The separation module according to claim 1 is an external separation module, wherein said first direction is a downlink direction away from the network device and said second direction is an uplink direction towards the network device.

4. The separation module of claim 1 comprising a direction determination module configured to adapt the separation module to match one of a first directionality or a second directionality, wherein in the first directionality said first direction is an uplink direction towards the network device and said second direction is a downlink direction away from the

network device, and in the second directionality said first direction is a downlink direction away from the network device and said second direction is an uplink direction towards the network device.

5. The separation module according to claim 1 wherein said tag is applied to a payload of said data packet.

6. The separation module according to claim 1 is configured as a one time programming device.

7. The separation module according to claim 1 being associated with a plurality of network-ids, each network-id assigned to a respective network environment; said separation module is further configured to determine whether a tag, associated with a data packet received by the network device from said second direction, is compatible with any one of the plurality of the network network-ids, and if it is, remove the tag from the data packet and allow transmission of the data packet.

8. The separation module according to claim 7 comprising a data repository for storing said plurality of network-ids.

9. The separation module according to claim 1 further comprising:

a data-repository for storing said network-id and a processor associated with a tagging module configured to perform said tagging; and a validation module configured to determine whether said tag is compatible with the separation module.

10. A network device configured to control communication of data between nodes associated with one or more network environments; the network device comprising:

at least a first separation module and a second separation module, the first separation module being operationally connected to a first node connected to said network device;

said first separation module is configured to tag a data packet received from said first node, with the help of a network-id assigned to said first separation module, said tag being indicative of a respective network environment of said first node; and transmit said data packet towards said second separation module.

11. The network device according to claim 10, wherein said second separation module is associated with a second node connected to said network device;

said second separation module is configured to:

receive said data packet;

determine whether the tag associated with the data packet is compatible with said second separation module; and if it is,

remove the tag from the data packet and allow transmission of the data packet to said second node.

12. The network device according to claim 10, wherein said second separation module is an external separation module associated with an external communication network connecting said network device to a second network device;

said external separation module is configured to:

tag said data packet received from said first separation module, with a second tag, said second tag being indicative of a respective network environment of said network device; and transmit said data packet towards said second network device.

13. The network device according to claim 12, wherein said second external separation module is configured to:

receive a data packet sent from a second node connected to said second network device; the data packet comprising a first tag and a second tag;

determine whether said second tag, associated with the data packet, is compatible with said external separation module;

if it is, remove the tag from the data packet;

transmit the data packet to said separation module; said separation module is configured to:

determine whether said first tag, associated with the data packet, is compatible with said separation module;

if it is, remove the tag from the data packet; and

transmit said data packet to a node connected to said network device.

14. A secure small form-factor pluggable transceiver (SFP) comprising the separation module of claim 1, the SFP being operatively connectible to a network device to facilitate data communication with said network device in a communication network.

15. The separation module according to claim 1 being incorporated in a security manager;

the security manager operatively connected to a network device and to an external network, and being operable to control transmission of data between said network device and said external network; the security manager comprises or otherwise associated with a data repository configured for storing network-ids;

said separation module is configured to:

receive a data packet, sent via an external separation module in said network device; the data packet comprising a first tag and a second tag;

determine whether said second tag, associated with the data packet, is compatible with any one of network-ids stored in said data repository;

if it is, remove the tag from the data packet; and

determine whether said first tag, associated with the data packet, is compatible with any one of network-ids stored in said data repository;

if it is, remove the tag from the data packet; and

allow the transmission of said data packet to said external network.

16. A method of controlling transmission of data in a communication network, the method comprising:

tagging, a data packet received by a network device from a first direction in said communication network; said tagging is performed with the help of a network-id assigned to said network device, the network-id is indicative that the data packet is associated with a given network environment; and

determining whether a tag associated with a data packet, received by the network device from a second direction, is compatible with a network-id assigned to a target device, and if it is, removing the tag from the data packet and allowing transmission of the data packet to the target device.

17. The method according to claim 16, wherein said first direction is an uplink direction towards the network device and said second direction is a downlink direction away from the network device.

18. The method according to claim 16, wherein said first direction is a downlink direction away from the network device and said second direction is an uplink direction towards the network device.

19. The method according to claim 16, wherein said tagging is performed on a payload of said data packet.

20. The method according to claim 16, wherein said network device is connected to a first node and a second node, the method comprising:

performing said tagging on a data packet received from a first node connected to said network device; and

performing said determining on said data packet being transmitted to a second node connected to said network device; thereby controlling transmission of data between said first node and said second node.

21. A method of controlling transmission of data in a communication network via a network device, the method comprising:

receiving from a first node connected to said network device a data packet destined to a second node connected to a second network device; said network and said second network device are connected over a communication network;

tagging said data packet received from said first node with a tag being indicative of a respective network environment of said first node;

tagging said data packet with a second tag being indicative of a respective network environment of said network device; and transmitting said data packet to said second network device via said communication network;

thereby enabling said second network device to determine whether to allow transmission of said data packet.

22. The method according to claim 21 further comprising:

receiving a data packet from said second network device destined to a node connected to said network device; the data packet comprising a first tag and a second tag;

in case said second tag, associated with the data packet, is compatible with said network device:

removing the tag from the data packet;

in case said first tag, associated with the data packet, is compatible with said node;

removing the tag from the data packet; and

allowing transmission of said data packet to said node.