



(51) International Patent Classification:
F28F 5/00 (2006.01) *F04F 99/00* (2009.01)

(21) International Application Number:
PCT/US2010/061056

(22) International Filing Date:
17 December 2010 (17.12.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/289,955 23 December 2009 (23.12.2009) US

(71) Applicant (for all designated States except US): **ENERGY RECOVERY, INC.** [US/US]; 1717 Doolittle Drive, San Leandro, California 94577 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PINTO, Juan Miguel** [VE/US]; 383 MacArthur Blvd, Apt 219, Oakland, California 94610 (US). **MARTIN, Jeremy G.** [US/US]; 592 Aileen St., Oakland, California 94609 (US). **STOVER, Richard L.** [US/US]; 226 Monte Vista Avenue, Oakland, California 94611 (US).

(74) Agents: **SCHUMANN, James J.** et al.; Fitch, Even, Tabin & Flannery, 120 South LaSalle Street, Suite 1600, Chicago, Illinois 60603-3406 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ROTARY ENERGY RECOVERY DEVICE




FIG. 3

(57) Abstract: A rotary energy recovery device (11) wherein a multi-channel cylindrical rotor (15) revolves with its end faces (32) juxtaposed in sealing relationship with end surfaces (33) of a pair of flanking end covers (19, 21), and wherein inlet and outlet fluid passageways (27, 29) are provided in each end cover. Fluid may be directed into the rotor channels (16) and allowed to exit therefrom in an axial direction parallel to the axis of the rotor; however, rotor revolution is self-driven as a result of the interior design of the channels (16) which extend axially through the rotor and are shaped so that fluid flow therethrough creates a torque.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*