

IDENTIFICATION METHOD AND APPARATUS AND COMPUTER-READABLE STORAGE MEDIUM

5 **Cross-Reference to Related Applications**

[0001] This international application is based upon and claims priority to Chinese Patent Application No. 201810917915.7, filed on August 13, 2018, the entire content of all of which is incorporated herein by reference.

Technical Field

10 [0002] Embodiments of this specification relate to an identification method, and apparatus and computer-readable storage medium.

Technical Background

[0003] With the development of communication technologies and the popularization of electronic payment, people conduct transactions increasingly by electronic payment (such as
15 payment by Alipay™) instead of cash.

[0004] Currently, it is common to use terminals such as mobile phones to complete electronic payment. However, terminals such as mobile phones generally use a payment password for identification or verification during electronic payment. Once a user's mobile phone and payment password are stolen at the same time, the user will suffer economic losses. Therefore, how
20 to better identify a user when the user makes a transaction by electronic payment is a technical problem to be solved.

Summary of the Invention

[0005] An identification method, apparatus and computer-readable storage medium are provided in the embodiments of this specification to better identify a user.

25 [0006] According to a first aspect, an identification method is provided, comprising:

[0007] controlling at least one camera to acquire a face image and an eye image of a target object, wherein the eye image includes an iris feature and/or an eye-print feature; and

[0008] identifying the target object based on the face image and the eye image.

[0009] According to a second aspect, an identification apparatus is provided, comprising:

5 [0010] an acquisition module configured to acquire a face image and an eye image of a target object through at least one camera, wherein the eye image includes an iris feature and/or an eye-print feature; and

[0011] an identification module configured to identify the target object based on the face image and the eye image.

10 [0012] According to a third aspect, an identification device is provided, comprising:

[0013] a processor; and

[0014] a memory configured to store computer executable instructions, wherein the processor performs the following operations when the executable instructions are executed:

15 [0015] controlling at least one camera to acquire a face image and an eye image of a target object, wherein the eye image includes an iris feature and/or an eye-print feature; and

[0016] identifying the target object based on the face image and the eye image.

[0017] According to a fourth aspect, a computer-readable storage medium is provided, wherein one or more programs are stored in the computer-readable storage medium, and the following operations are performed when the one or more programs are executed:

20 [0018] controlling at least one camera to acquire a face image and an eye image of a target object, wherein the eye image includes an iris feature and/or an eye-print feature; and

[0019] identifying the target object based on the face image and the eye image.

[0020] At least one of the afore-mentioned technical solutions used in the embodiments of this specification can achieve the following beneficial effects.

[0021] In the embodiments of this specification, a face image and an eye image of a target object are acquired, and the target object is identified based on an iris feature and/or an eye-print feature in the eye image. Because the target object is verified using multiple factors by combining the face image with the iris feature and/or the eye-print feature in the eye image, a user can be better identified.

Brief Description of the Drawings

[0022] FIG. 1 is a flowchart of an identification method according to an embodiment of this specification;

[0023] FIG. 2 is a flowchart of another identification method according to an embodiment of this specification;

[0024] FIG. 3 is a structural block diagram of an identification apparatus according to an embodiment of this specification; and

[0025] FIG. 4 is a schematic diagram of a terminal according to an embodiment of this specification.

Detailed Description

[0026] The technical solutions in the embodiments of this specification are described clearly and completely below with reference to the accompanying drawings in the embodiments of this specification. Obviously, the described embodiments are some, rather than all, of the embodiments of the present invention. Based on the embodiments in the present invention, all other embodiments obtained by those with ordinary skill in the art without creative efforts belong to the protection scope of the present invention.

[0027] For better understanding of the technical solutions of this application, some concepts involved in this application are first explained below.

[0028] Facial recognition: a biometric recognition technology for identification based on human facial feature information, also commonly referred to as portrait recognition, face recognition.

[0029] Iris: a circular part between the black pupil and the white sclera in the eye, including
5 detail features such as many intersecting spots, thin threads, coronas, stripes, and crypts. Moreover, the iris remains unchanged over one's entire life course after fetal development. These features determine the uniqueness of the iris feature, and also determine the uniqueness of identification. Therefore, the iris feature of the eye can be used as an identifying object of each person.

[0030] Eye-print: this refers to blood vessels, stripes, and other subtle features in the white
10 part of the eye (sclera). Studies show that these detailed features remain unchanged over a long time, and the eye-print feature is unique to each person. Even identical multiples have different eye-prints.

[0031] Liveness detection: this refers to detecting whether a biometric signal obtained by a sensor is from a real living human body. For human face liveness detection, liveness detection
15 technologies are mainly used to ensure that a human face image acquired by a camera comes from the face of a living body, rather than a photo, video, human face mask, or the like.

[0032] The technical solutions according to the embodiments of the present invention are described in detail below with reference to the accompanying drawings.

[0033] The identification method according to the embodiments of this specification can
20 be widely applied in various scenarios, such as payment scenarios, medical scenarios, passenger scenarios, and the like.

[0034] FIG. 1 is a flowchart of an identification method according to an embodiment of this specification. Referring to FIG. 1, the identification method according to an embodiment of this specification may include the following steps.

[0035] In step 110, at least one camera is controlled to acquire a face image and an eye image of a target object, wherein the eye image includes an iris feature and/or an eye-print feature.

[0036] The target object is an object to be identified, and it may be a human being, an animal, or the like. For example, when user A needs to be identified, user A may stand in front of
5 a machine to wait for a camera to acquire a face image and an eye image of user A. In this case, user A is the target object.

[0037] In step 120, the target object is identified based on the face image and the eye image.

[0038] In one embodiment, the target object may be identified based on the face image and the iris feature in the eye image. Optionally, in another embodiment, the target object may be
10 identified based on the face image and the eye-print feature in the eye image.

[0039] Of course, in another embodiment, the target object may be identified based on the face image as well as the iris feature and the eye-print feature in the eye image.

[0040] In the embodiments of this specification, a face image and an eye image of a target object are acquired, and the target object is identified based on an iris feature and/or an eye-print
15 feature in the eye image. Because the target object is verified using multiple factors by combining the face image with the iris feature and/or the eye-print feature in the eye image, a user can be better identified.

[0041] In the embodiments of this specification, the face image and the eye image may be acquired by one camera or by two cameras. In other words, in the case of one camera, the face
20 image and the eye image of the target object may be acquired by the same camera. In the case of two cameras, the face image of the target object may be acquired by one camera, and the eye image of the target object may be acquired by the other camera.

[0042] In the embodiments of this specification, at least one camera can be controlled in various manners to acquire the face image and the eye image of the target object. The manners are
25 described in the following with examples.

[0043] An image acquisition concept is to acquire the face image and the eye image by using rectangular frames. A facial rectangular frame may be used during acquisition of the face image, and a two-eye rectangular frame may be used during acquisition of the eye image. The facial rectangular frame is a rectangular frame outlining the face of the target object, and the two-eye rectangular frame includes rectangular frames outlining the two eyes of the target object, that is, a left-eye rectangular frame and a right-eye rectangular frame. Rectangular frames can be used for alignment with various parts of a body. Therefore, a clear face image and a clear eye image can be obtained when rectangular frames are used for image acquisition, thereby facilitating subsequent identification.

[0044] In one case, the face image and the eye image may be acquired separately. For example, the face image of the target object is acquired first, and then the eye image of the target object is acquired. In this case, the step of acquiring a face image and an eye image of a target object may be specifically: adjusting the at least one camera to acquire the face image of the target object; and adjusting the at least one camera based on the position of a facial rectangular frame of the face image to acquire the eye image of the target object. In this manner, the face image and the eye image of the target object can be acquired quickly by using a facial rectangular frame when the target object does not cooperate.

[0045] In this text, adjusting the camera may be specifically adjusting imaging parameters of the camera, such as a focal length, orientation, exposure time, and the like. An objective of adjusting the camera is to obtain a face image or an eye image of higher resolution and clarity.

[0046] When there is one camera, the aforementioned step of adjusting the at least one camera to acquire the face image of the target object may include: adjusting the camera to obtain the position of the facial rectangular frame of the target object; and acquiring the face image of the target object based on the position of the facial rectangular frame. Correspondingly, the aforementioned step of adjusting the at least one camera based on the position of a facial

rectangular frame of the face image to acquire the eye image of the target object may include: adjusting the camera based on the position of the facial rectangular frame of the face image to obtain the position of a two-eye rectangular frame of the target object; and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

5 **[0047]** In other words, in the case of one camera, the camera can be adjusted to obtain the face image and the eye image of the target object sequentially. Because the face image and the eye image are acquired based on the facial rectangular frame and the two-eye rectangular frame in this process, the high quality of the acquired images can be ensured. At the same time, when the target object does not cooperate during image acquisition, the face image and the eye image can also be
10 obtained quickly by adjusting the camera and using rectangular frames (including the facial rectangular frame and the two-eye rectangular frame).

[0048] When the number of cameras is two, one of the at least one camera may be a first camera for photographing a face, and the other camera may be a second camera for photographing eyes. In this case, the aforementioned step of adjusting the at least one camera to acquire the face
15 image of the target object may include: adjusting the first camera to obtain the position of the facial rectangular frame of the target object; and acquiring the face image of the target object based on the position of the facial rectangular frame. Correspondingly, the aforementioned step of adjusting the at least one camera based on the position of a facial rectangular frame of the face image to acquire the eye image of the target object may include: adjusting the second camera based on the
20 position of the facial rectangular frame to obtain the position of a two-eye rectangular frame of the target object; and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

[0049] In the case of two cameras, the face image and the eye image of the target object may be obtained by adjusting the two cameras. In this process, the face image and the eye image
25 are acquired by special cameras. Therefore, images with higher quality than those in the case of

one camera can be obtained. Because the face image and the eye image are acquired based on the facial rectangular frame and the two-eye rectangular frame in the image acquisition process, the high quality of the acquired images can be ensured. At the same time, when the target object does not cooperate during image acquisition, the face image and the eye image can also be obtained quickly by adjusting the cameras and using rectangular frames (including the facial rectangular frame and the two-eye rectangular frame).

[0050] In another case, the face image and the eye image can be acquired simultaneously. In this case, the step of acquiring a face image and an eye image of a target object may include: adjusting the at least one camera to obtain the position of an initial facial rectangular frame of the target object; and adjusting the at least one camera based on the position of the initial facial rectangular frame to acquire the face image and the eye image of the target object. In other words, in this case, the face image is not acquired when the initial facial rectangular frame appears; instead, the camera is further adjusted to ensure that the face image and the eye image are acquired simultaneously only when the eye image and the face image are both clear enough.

[0051] In the case of one camera, the aforementioned step of adjusting the at least one camera based on the position of the initial facial rectangular frame to acquire the face image and the eye image of the target object may include: adjusting the camera based on the position of the initial facial rectangular frame to obtain the position of a target facial rectangular frame of the target object and the position of a two-eye rectangular frame of the target object; and acquiring the face image of the target object based on the position of the target facial rectangular frame, and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

[0052] In the case of one camera, by adjusting the camera continuously, the face image and the eye image are acquired only when the facial rectangular frame and the two-eye rectangular frame appear at the same time. As such, it can be ensured that the acquired face image and eye image are associated at the same moment.

[0053] In the case of two cameras, the at least one camera includes a first camera for photographing a face and a second camera for photographing eyes, and the aforementioned step of adjusting the at least one camera to obtain the position of an initial facial rectangular frame of the target object may include: adjusting the first camera to obtain the position of the initial facial rectangular frame of the target object. Correspondingly, the aforementioned step of adjusting the at least one camera based on the position of the initial facial rectangular frame to acquire the face image and the eye image of the target object may include: adjusting the first camera based on the position of the initial facial rectangular frame to obtain the position of a target facial rectangular frame of the target object, and acquiring the face image of the target object based on the position of the target facial rectangular frame; adjusting the second camera based on the position of the target facial rectangular frame to obtain the position of a two-eye rectangular frame of the target object; and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

[0054] In the case of two cameras, the face image and the eye image of the target object can be obtained by adjusting the two cameras. In this process, the face image and the eye image are acquired by special cameras. Therefore, images with higher quality than those in the case of one camera can be obtained. Because the face image and the eye image are acquired based on the facial rectangular frame and the two-eye rectangular frame in the image acquisition process, high quality of the acquired images can be ensured. At the same time, when the target object does not cooperate during image acquisition, the face image and the eye image can also be obtained quickly by adjusting the cameras and using rectangular frames (including the facial rectangular frame and the two-eye rectangular frame).

[0055] In the embodiments of this specification, another image acquisition concept is to acquire the face image and the eye image without using rectangular frames. In this case, the camera may be adjusted continuously to ensure that the eye image and the face image are clear enough.

During camera adjustment, similar to the foregoing cases, the face image and the eye image may be acquired separately or simultaneously. When the face image and the eye image are acquired simultaneously, the images are generally required to be of high quality.

[0056] It should be understood that the above descriptions are merely examples of image acquisition methods, which are not intended to be limiting.

[0057] It should also be understood that in the embodiments of this specification, the face may be detected first during the process of determining the facial rectangular frame. The face detection method in this text may be a conventional method based on Haar features and a boost classifier, or a deep learning method based on a transient chaotic neural network (MTCNN). The position of the facial rectangular frame mentioned in this text may be the imaging coordinate position of the facial rectangular frame, and the position of the two-eye rectangular frame mentioned in this text may be the imaging coordinate position of the two-eye rectangular frame.

[0058] FIG. 2 is a flowchart of an identification method according to an embodiment of this specification. Referring to FIG. 2, the identification method according to an embodiment of this specification may include the following steps.

[0059] In step 210, a face image of a target object is acquired, and an iris feature and/or eye-print feature in an eye image of the target object are/is acquired.

[0060] In step 220, it is determined whether the target object is a living body based on the face image and the iris feature and/or the eye-print feature in the eye image.

[0061] The face image may be a single-frame face image or a multi-frame face image. The eye image may be a single-frame eye image or a multi-frame eye image.

[0062] If the face image is a single-frame face image, and the eye image is a single-frame eye image, step 220 of determining whether the target object is a living body based on the eye image and the face image may include: determining whether the target object is a living body based on a difference between a single-frame face image of a living body and a single-frame face image

of a non-living body, and a difference between the iris feature and/or the eye-print feature included in a single-frame eye image of a living body and the iris feature and/or the eye-print feature included in a single-frame eye image of a non-living body.

[0063] In the case of a single-frame face image, the face of a non-living body may have
5 distortions, flaws, or the like. Therefore, by determining whether the face displayed in the single-frame face image has any distortions or flaws, it can be determined whether the target object is a living body. For example, if a single-frame face image has phenomena such as distortions and flaws, it can be directly determined that the target object is a non-living body (for example, a face in a video); if a face displayed in a single-frame face image is intact and has phenomena such as
10 distortions and flaws, the target object can be determined to be a living body, or further detection may be performed in combination with the iris feature and/or the eye-print feature.

[0064] In the case of a single-frame eye image, detail features on the iris (such as spots, thin threads, coronas, stripes, and crypts) or detail features on the eye-print (such as blood vessels and stripes) may be detected to determine whether the target object is a living body. Specifically,
15 if the eye image includes detail features on the iris or detail features on the eye-print, it can be determined that the target object is a living body; if the eye image does not include detail features on the iris or detail features on the eye-print, it can be determined that the target object is a non-living body.

[0065] In the embodiments of this specification, the face image and the eye image may be
20 used in combination, and it is determined whether the target object is a living body by judging the face image and the eye image.

[0066] If the face image is a multi-frame face image, and the eye image is a multi-frame eye image, step 220 of determining whether the target object is a living body based on the eye image and the face image includes: determining that the target object is a living body if there are
25 differences among the multiple frames of the face image; determining that the target object is a

living body if there are differences among the multiple frames of the eye image in terms of the iris feature or the eye-print feature; and determining that the target object is a non-living body if there is no difference between the multiple frames of the eye image in terms of the iris feature or the eye-print feature.

- 5 **[0067]** When the face image and the eye image have multiple frames, the multiple frames of the face image may be compared with each other to determine whether the target object is a living body, and meanwhile, the multiple frames of the eye image are also compared with each other to determine whether the target object is a living body. If there is no difference between the multiple frames of the eye image, it can be determined that the target object is a non-living body.
- 10 Of course, to ensure stringency, the target object may be determined as a non-living body when there is no difference between the multiple frames of the face image and there is also no difference between the multiple frames of the eye image. If there are differences among the multiple frames of the face image or among the multiple frames of the eye image, it can be determined that the target object is a living body.

- 15 **[0068]** In step 230, the target object is identified if the target object is a living body.

- [0069]** In the embodiments of this specification, a face image and an eye image of a target object are acquired, and the target object is identified based on an iris feature and/or an eye-print feature in the eye image. Because the target object is verified using multiple factors by combining the face image with the iris feature and/or the eye-print feature in the eye image, a user can be
- 20 better identified. Meanwhile, before identification of the target object, it is first determined whether the target object is a living body, and identification is performed only when the target object is a living body, thereby ensuring the validity of the identification, preventing others from passing identification using a stolen video or a picture.

- [0070]** The following specifically illustrates identification modes in the embodiments of
- 25 this specification. In the embodiments of this specification, multiple modes may be used for

identification. Specifically, at least one of a face image, the iris feature in an eye image, and the eye-print feature in an eye image may be used for identification. In other words, identification can be performed by combining a face image with the iris feature in an eye image, by combining a face image with the eye-print feature in an eye image, or by using a face image, the iris feature in an eye image, and the eye-print feature in an eye image. Of course, identification may also be performed by combining the iris feature in an eye image with the eye-print feature in an eye image.

[0071] The following specifically describes various identification modes.

[0072] First identification mode: identification based on a face image and the iris feature of an eye image.

10 [0073] In one embodiment of this specification, the eye image may include an iris feature, and in this case, the identifying the target object in step 120 or step 230 may include:

[0074] comparing the acquired face image with face images in a face image library;

[0075] selecting a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold;

[0076] further comparing the iris feature of the acquired eye image with iris features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images; and

20 [0077] identifying the target object successfully if the similarity between an iris feature of an eye image in the eye image library and the iris feature of the acquired eye image is greater than a second threshold.

[0078] This identification mode based on a face image and the iris feature of an eye image can ensure highly precise identification and has a high identification speed.

[0079] Second identification mode: identification based on a face image and the eye-print feature of an eye image.

[0080] In one embodiment of this specification, the eye image comprises an eye-print feature, and the identifying the target object in step 120 or step 230 may include:

[0081] comparing the acquired face image with face images in a face image library;

[0082] selecting a first group of face images from the face image library, the first group of
5 face images being face images whose similarities with the acquired face image are greater than a first threshold;

[0083] further comparing the eye-print feature of the acquired eye image with eye-print features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images; and

10 [0084] identifying the target object successfully if the similarity between an eye-print feature of an eye image in the eye image library and the eye-print feature of the acquired eye image is greater than a third threshold.

[0085] This identification mode based on a face image and the eye-print feature of an eye image can ensure highly precise identification and has a high identification speed.

15 [0086] Third identification mode: identification based on a face image, the iris feature of an eye image, and the eye-print feature of an eye image.

[0087] In one embodiment of this specification, the eye image includes an iris feature and an eye-print feature, and the identifying the target object in step 120 or step 230 includes:

[0088] comparing the acquired face image with face images in a face image library;

20 [0089] selecting a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold;

[0090] further comparing the iris feature of the acquired eye image with iris features of specified eye images in an eye image library, wherein the specified eye images are associated with
25 the face images in the first group of face images;

[0091] selecting a first group of eye images from the specified eye images, the first group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold in the specified eye images;

[0092] comparing the eye-print feature of the acquired eye image with eye-print features
5 of the eye images in the first group of eye images; and

[0093] identifying the target object successfully if the similarity between an eye-print feature of an eye image in the first group of eye images and the eye-print feature of the acquired eye image is greater than a third threshold.

[0094] This identification mode based on a face image, the iris feature of an eye image,
10 and the eye-print feature of an eye image can ensure highly precise identification and effectively avoid false identification.

[0095] Fourth identification mode: identification based on a face image, the eye-print feature of an eye image, and the iris feature of an eye image.

[0096] In one embodiment of this specification, the eye image includes an iris feature and
15 an eye-print feature, and the identifying the target object in step 120 or step 230 includes:

[0097] comparing the acquired face image with face images in a face image library;

[0098] selecting a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold;

[0099] further comparing the eye-print feature of the acquired eye image with eye-print features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images;

[0100] selecting a second group of eye images from the specified eye images, the second group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold in the specified eye images;
25

[0101] comparing the iris feature of the acquired eye image with iris features of the eye images in the second group of eye images; and

[0102] identifying the target object successfully if the similarity between an iris feature of an eye image in the second group of eye images and the iris feature of the acquired eye image is
5 greater than a second threshold.

[0103] This identification mode based on a face image, the eye-print feature of an eye image, and the iris feature of an eye image can ensure highly precise identification and effectively avoid false identification.

[0104] Fifth identification mode: identification based on the iris feature of an eye image
10 and a face image.

[0105] In one embodiment of this specification, the eye image includes an iris feature, and the identifying the target object in step 120 or step 230 includes:

[0106] comparing the iris feature of the acquired eye image with iris features of eye images in an eye image library;

15 [0107] selecting a third group of eye images from the eye image library, the third group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold;

[0108] comparing the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the eye images in the third group of
20 eye images; and

[0109] identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

[0110] This identification mode based on the iris feature of an eye image and a face image has high precision.

[0111] Sixth identification mode: identification based on the eye-print feature of an eye image and a face image.

[0112] In one embodiment of this specification, the eye image includes an eye-print feature, and the identifying the target object in step 120 or step 230 includes:

5 [0113] comparing the eye-print feature of the acquired eye image with eye-print features of eye images in an eye image library;

[0114] selecting a fourth group of eye images from the eye image library, the fourth group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold;

10 [0115] comparing the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the eye images in the fourth group of eye images; and

[0116] identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

15 [0117] This identification mode based on the eye-print feature of an eye image and a face image has high precision.

[0118] Seventh identification mode: identification based on the iris feature of an eye image, the eye-print feature of an eye image, and a face image.

[0119] In one embodiment of this specification, the eye image includes an iris feature and
20 an eye-print feature, and the identifying the target object in step 120 or step 230 includes:

[0120] comparing the iris feature of the acquired eye image with iris features of eye images in an eye image library;

[0121] selecting a third group of eye images from the eye image library, the third group of eye images being eye images having iris features whose similarities with the iris feature of the
25 acquired eye image are greater than a second threshold;

[0122] comparing the eye-print feature of the acquired eye image with eye-print features of the eye images in the third group of eye images;

[0123] selecting a fifth group of eye images from the third group of eye images, the fifth group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold;

[0124] comparing the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the fifth group of eye images; and

[0125] identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

[0126] This identification mode based on the iris feature of an eye image, the eye-print feature of an eye image, and a face image can ensure highly precise identification and effectively avoid false identification.

[0127] Eighth identification mode: identification based on the eye-print feature of an eye image, the iris feature of an eye image, and a face image.

[0128] In one embodiment of this specification, the eye image includes an iris feature and an eye-print feature, and the identifying the target object in step 120 or step 230 includes:

[0129] comparing the eye-print feature of the acquired eye image with eye-print features of eye images in an eye image library;

[0130] selecting a fourth group of eye images from the eye image library, the fourth group of eye images being face images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold;

[0131] comparing the iris feature of the acquired eye image with iris features of the eye images in the fourth group of eye images;

[0132] selecting a sixth group of eye images from the fourth group of eye images, the sixth group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold;

[0133] comparing the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the sixth group of eye images; and

[0134] identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

[0135] This identification mode based on the eye-print feature of an eye image, the iris feature of an eye image, and a face image can ensure highly precise identification and effectively avoid false identification.

[0136] It should be noted that in the various identification modes above, the eye image library and the face image library can be obtained locally or from other storage apparatuses. Eye images in the eye image library may be obtained in advance in various manners, and face images in the face image library may also be obtained in advance in various manners. Specific acquisition manners are not limited in this application.

[0137] Meanwhile, it should be noted that in the various identification modes above, the first threshold, the second threshold, and the third threshold may be set as required. The first threshold may be set to 70 points (100 points in total) or 70%, for example; the first threshold may be set to 72 points or 72%, for example; and the third threshold may be set to 75 points or 75% for example. There is no association among the values of the first threshold, the second threshold, and the third threshold.

[0138] The identification method according to this application can combine face, eye-print, and iris technologies, and the technologies can be applied to non-cooperative identification of users in a face-scanning payment scenario, thereby not only combining face-based and eye-print-based liveness detection technologies, but also using faces, irises, and eye-prints in large-scale user

retrieval. Moreover, retrieval can be implemented in a cascaded manner, thus balancing efficiency and accuracy, and achieving rapid retrieval from a database including millions of faces within a short period of time (such as 1 second).

[0139] FIG. 3 is a structural block diagram of an identification apparatus according to an embodiment of this specification. Referring to FIG. 3, the identification apparatus 300 according to an embodiment of this specification may include an acquisition module 310 and an identification module 320. Here:

[0140] The acquisition module 310 is configured to acquire a face image and an eye image of a target object through at least one camera, wherein the eye image includes an iris feature and/or an eye-print feature.

[0141] The identification module 320 is configured to identify the target object based on the face image and the eye image.

[0142] Optionally, in one embodiment of this specification, the identification module 320 is specifically configured to:

[0143] determine whether the target object is a living body based on the eye image and the face image; and

[0144] identify the target object if the target object is a living body.

[0145] Optionally, in one embodiment of this specification, the acquisition module 310 is specifically configured to: adjust the at least one camera to acquire the face image of the target object; and adjust the at least one camera based on the position of a facial rectangular frame of the face image to acquire the eye image of the target object.

[0146] Optionally, in one embodiment of this specification, the at least one camera is one camera, and the acquisition module 310 is specifically configured to: adjust the camera to obtain the position of the facial rectangular frame of the target object; acquire the face image of the target object based on the position of the facial rectangular frame; adjust the camera based on the position

of the facial rectangular frame of the face image to obtain the position of a two-eye rectangular frame of the target object; and acquire the eye image of the target object based on the position of the two-eye rectangular frame.

[0147] Optionally, in one embodiment of this specification, the at least one camera includes
5 a first camera for photographing a face and a second camera for photographing eyes, and the acquisition module 310 is specifically configured to: adjust the first camera to obtain the position of the facial rectangular frame of the target object; acquire the face image of the target object based on the position of the facial rectangular frame; adjust the second camera based on the position of the facial rectangular frame to obtain the position of a two-eye rectangular frame of the target
10 object; and acquire the eye image of the target object based on the position of the two-eye rectangular frame.

[0148] Optionally, in another embodiment of this specification, the acquisition module 310 is specifically configured to: adjust the at least one camera to obtain the position of an initial facial rectangular frame of the target object; and adjust the at least one camera based on the position of
15 the initial facial rectangular frame to acquire the face image and the eye image of the target object.

[0149] Optionally, the at least one camera is one camera, and the acquisition module 310 is specifically configured to: adjust the camera based on the position of the initial facial rectangular frame to obtain the position of a target facial rectangular frame of the target object and the position of a two-eye rectangular frame of the target object; and acquire the face image of the target object
20 based on the position of the target facial rectangular frame, and acquire the eye image of the target object based on the position of the two-eye rectangular frame.

[0150] Optionally, the at least one camera includes a first camera for photographing a face and a second camera for photographing eyes, and

[0151] the acquisition module 310 is specifically configured to: adjust the first camera to
25 obtain the position of the initial facial rectangular frame of the target object; adjust the first camera

based on the position of the initial facial rectangular frame to obtain the position of a target facial rectangular frame of the target object, and acquire the face image of the target object based on the position of the target facial rectangular frame; adjust the second camera based on the position of the target facial rectangular frame to obtain the position of a two-eye rectangular frame of the target object; and acquire the eye image of the target object based on the position of the two-eye rectangular frame.

[0152] Optionally, in another embodiment of this specification, the face image is a single-frame face image, the eye image is a single-frame eye image, and the identification module 320 is specifically configured to: determine whether the target object is a living body based on a difference between a single-frame face image of a living body and a single-frame face image of a non-living body, and a difference between the iris feature and/or the eye-print feature included in a single-frame eye image of a living body and the iris feature and/or the eye-print feature included in a single-frame eye image of a non-living body.

[0153] Optionally, in another embodiment of this specification, the face image is a multi-frame face image, the eye image is a multi-frame eye image, and the identification module 320 is specifically configured to: determine that the target object is a living body if there are differences among the multiple frames of the face image; determine that the target object is a living body if there are differences among the multiple frames of the eye image in terms of the iris feature or the eye-print feature; and determine that the target object is a non-living body if there is no difference between the multiple frames of the eye image in terms of the iris feature or the eye-print feature.

[0154] Optionally, the eye image includes an iris feature, and the identification module 320 is specifically configured to: compare the acquired face image with face images in a face image library; select a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold; further comparing the iris feature of the acquired eye image with iris features of specified eye

images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images; and identify the target object successfully if the similarity between an iris feature of an eye image in the eye image library and the iris feature of the acquired eye image is greater than a second threshold.

5 **[0155]** Optionally, the eye image includes an eye-print feature, and the identification module 320 is specifically configured to: compare the acquired face image with face images in a face image library; select a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold; further compare the eye-print feature of the acquired eye image with eye-print
10 features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images; and identify the target object successfully if the similarity between an eye-print feature of an eye image in the eye image library and the eye-print feature of the acquired eye image is greater than a third threshold.

[0156] Optionally, the eye image includes an iris feature and an eye-print feature, and the
15 identification module 320 is specifically configured to: compare the acquired face image with face images in a face image library; select a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold; further compare the iris feature of the acquired eye image with iris features of specified eye images in an eye image library, wherein the specified eye images are
20 associated with the face images in the first group of face images; select a first group of eye images from the specified eye images, the first group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold in the specified eye images; compare the eye-print feature of the acquired eye image with eye-print features of the eye images in the first group of eye images; and identify the target object

successfully if the similarity between an eye-print feature of an eye image in the first group of eye images and the eye-print feature of the acquired eye image is greater than a third threshold.

[0157] Optionally, the eye image includes an iris feature and an eye-print feature, and the identification module 320 is specifically configured to: compare the acquired face image with face images in a face image library; select a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold; further compare the eye-print feature of the acquired eye image with eye-print features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images; select a second group of eye images from the specified eye images, the second group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold in the specified eye images; compare the iris feature of the acquired eye image with iris features of the eye images in the second group of eye images; and identify the target object successfully if the similarity between an iris feature of an eye image in the second group of eye images and the iris feature of the acquired eye image is greater than a second threshold.

[0158] Optionally, the eye image includes an iris feature, and the identification module 320 is specifically configured to: compare the iris feature of the acquired eye image with iris features of eye images in an eye image library; select a third group of eye images from the eye image library, the third group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold; compare the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the eye images in the third group of eye images; and identify the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

[0159] Optionally, the eye image includes an eye-print feature, and the identification module 320 is specifically configured to: compare the eye-print feature of the acquired eye image with eye-print features of eye images in an eye image library; select a fourth group of eye images from the eye image library, the fourth group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold; compare the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the eye images in the fourth group of eye images; and identify the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

10 [0160] Optionally, the eye image includes an iris feature and an eye-print feature, and the identification module 320 is specifically configured to: compare the iris feature of the acquired eye image with iris features of eye images in an eye image library; select a third group of eye images from the eye image library, the third group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold; compare the eye-print feature of the acquired eye image with eye-print features of the eye images in the third group of eye images; select a fifth group of eye images from the third group of eye images, the fifth group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold; compare the acquired face image with specified face images in the face image library, wherein the specified face images are associated with the fifth group of eye images; and identify the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

[0161] Optionally, the eye image includes an iris feature and an eye-print feature, and the identification module 320 is specifically configured to: compare the eye-print feature of the acquired eye image with eye-print features of eye images in an eye image library; select a fourth

group of eye images from the eye image library, the fourth group of eye images being face images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold; compare the iris feature of the acquired eye image with iris features of the eye images in the fourth group of eye images; selecting a sixth group of eye images
5 from the fourth group of eye images, the sixth group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold; compare the acquired face image with specified face images in the face image library, wherein the specified face images are associated with the sixth group of eye images; and identify the target object successfully if the similarity between a face image in the specified face images
10 and the acquired face image is greater than a first threshold.

[0162] In the embodiments of this specification, a face image and an eye image of a target object are acquired, and the target object is identified based on an iris feature and/or an eye-print feature in the eye image. Because the target object is verified using multiple factors by combining the face image with the iris feature and/or the eye-print feature in the eye image, a user can be
15 better identified.

[0163] FIG. 4 is a schematic diagram of the hardware of a terminal for implementing the embodiments of the present invention, wherein the terminal may be a mobile terminal.

[0164] The terminal 400 includes, but is not limited to, components such as a radio frequency unit 401, a network module 402, an audio output unit 403, an input unit 404, a sensor
20 405, a display unit 406, a user input unit 407, an interface unit 408, a memory 409, a processor 410, and a power supply 411. Those skilled in the art can understand that the structure of the mobile terminal shown in FIG. 4 does not limit the mobile terminal. The mobile terminal may include more or fewer components than those shown in the figure, or some components may be combined, or a different component deployment may be used. In the embodiments of this specification, the
25 mobile terminal includes, but is not limited to, a mobile phone, a tablet computer, a notebook

computer, a palmtop computer, a vehicle-mounted terminal, a wearable device, a pedometer, and the like.

[0165] The processor 410 is configured to generate prompt information, wherein the prompt information includes a sending location, an amount, and prompt information content;
5 search for another mobile terminal within a preset range of the sending location according to the sending location; and send the prompt information to the another mobile terminal.

[0166] The terminal according to the embodiments of this specification can generate prompt information, wherein the prompt information includes a sending location, an amount, and prompt information content; search for another mobile terminal within a preset range of the sending
10 location according to the sending location; and send the prompt information to the another mobile terminal. The prompt information can be sent anonymously, thereby avoiding the problem of conflicts that occur in face-to-face communication and achieving a notification function, improving safety. Moreover, a small amount of money is attached to the prompt information, which can also attract the attention of the audience, and it is more likely to achieve the information transfer
15 objective.

[0167] It should be noted that in the embodiments of this specification, the radio frequency unit 401 may be used to send and receive information or place a call. Specifically, the receiving and sending of signals involves receiving downlink data from a base station, and then sending it to the processor 410 for processing. In addition, uplink data is sent to the base station. Generally, the
20 radio frequency unit 401 includes, but is not limited to, an antenna, at least one amplifier, a transceiver, a coupler, a low noise amplifier, a duplexer, and the like. In addition, the radio frequency unit 401 may also communicate with a network and other devices through a wireless communication system.

[0168] The mobile terminal provides wireless broadband Internet access for the user through the network module 402, for example, helping the user send and receive emails, browse webpages, access streaming media, and the like.

[0169] The audio output unit 403 can convert audio data, which is received by the radio frequency unit 401 or the network module 402 or stored in the memory 409, into an audio signal and output the audio signal as sound. Moreover, the audio output unit 403 can further provide an audio output (such as a calling reception sound, a message reception sound, and the like) related to a specific function performed by the mobile terminal 400. The audio output unit 403 includes a loudspeaker, a buzzer, a telephone receiver, and the like.

[0170] The input unit 404 is configured to receive audio or video signals. The input unit 404 may include a Graphics Processing Unit (GPU) 4041 and a microphone 4042. The GPU 4041 processes a static picture or image data of a video obtained by an image capture apparatus (such as a camera) in a video capture mode or an image capture mode. A processed image frame may be displayed on the display unit 406. Image frames processed by the GPU 4041 may be stored in the memory 409 (or other storage media) or sent through the radio frequency unit 401 or the network module 402. The microphone 4042 can receive sound and can process the sound to be audio data. The processed audio data may be converted, in telephone call mode, into a format that can be sent to a mobile communication base station through the radio frequency unit 401, and output.

[0171] The mobile terminal 400 further includes at least one sensor 405, such as an optical sensor, a motion sensor, and other sensors. Specifically, the optical sensor includes an ambient light sensor and a proximity sensor. The ambient light sensor can adjust the luminance of a display panel 4061 according to brightness of the ambient light, and the proximity sensor can switch off the display panel 4061 and/or backlight when the mobile terminal 400 is moved to the ear. As a type of motion sensor, an acceleration sensor can detect the magnitude of accelerations in various directions (generally along three axes), can detect the magnitude and direction of gravity when

static, and can be used in functions related to recognizing the attitude of the mobile terminal (such as switching between landscape mode and portrait mode, related games, and magnetometer attitude calibrations) and vibration identification (such as a pedometer and tapping). The sensor 405 may include a fingerprint sensor, a pressure sensor, an iris sensor, a molecule sensor, a gyroscope, a barometer, a hygrometer, a thermometer, an infrared sensor, and the like, which are not described in detail here.

[0172] The display unit 406 is configured to display information input by the user or provide information for the user. The display unit 406 may include a display panel 4061. The display panel 4061 may be configured in the form of a Liquid Crystal Display (LCD), an Organic Light-Emitting Diode (OLED), or the like.

[0173] The user input unit 407 may be configured to receive input digital or character information and generate key signal input related to the user settings and function control of the mobile terminal. Specifically, the user input unit 407 includes a touch panel 4071 and other input devices 4072. The touch panel 4071, also referred to as a touch screen, can collect a touch operation by the user on or near the touch panel (such as an operation by the user on or near the touch panel 4071 using any suitable object or attachment, such as a finger or a stylus). The touch panel 4071 may include two parts: a touch detection apparatus and a touch controller. The touch detection apparatus detects the direction of the user's touch, detects a signal generated by the touch operation, and sends the signal to the touch controller. The touch controller receives touch information from the touch detection apparatus, converts it into touch-point coordinates, sends the coordinates to the processor 410, and receives and executes a command sent by the processor 410. In addition, the touch panel 4071 may be implemented as various types, such as a resistive type, a capacitance type, an infrared type, a surface acoustic wave type, and the like. In addition to the touch panel 4071, the user input unit 407 may further include other input devices 4072. Specifically, the other input devices 4072 may include, but are not limited to, a physical keyboard, a functional key (such as a

volume control key, a switch key, and the like), a track ball, a mouse, and a joystick, which are not described in detail here.

[0174] Further, the touch panel 4071 may cover the display panel 4061. After detecting a touch operation thereon or nearby, the touch panel 4071 transmits the touch operation to the processor 410 to determine the type of touch event. Then, the processor 410 provides a corresponding visual output on the display panel 4061 according to the type of touch event. Although the touch panel 4071 and the display panel 4061 are implemented as two independent parts in FIG. 4 to achieve the input and output functions of the mobile terminal, in some embodiments, the touch panel 4071 and the display panel 4061 may be integrated to achieve the input and output functions of the mobile terminal, which is not specifically limited here.

[0175] The interface unit 408 is an interface for connecting an external apparatus to the mobile terminal 400. The external apparatus may be a wired or wireless headset port, an external power supply (or battery charger) port, a wired or wireless data port, a memory card port, a port for connection to an apparatus having a recognition module, an audio input/output (I/O) port, a visual I/O port, an earphone port, and the like. The interface unit 405 may be configured to receive input (such as data information, electric power, and the like) from the external apparatus, and transmit the received input to one or more components in the mobile terminal 400, or configured to transmit data between the mobile terminal 400 and the external apparatus.

[0176] The memory 409 may be configured to store software programs and various data. The memory 409 may primarily comprise a program storage area and a data storage area. The program storage area can store an operating system, an application program required by at least one function (for example, a sound playing function, an image display function, and the like), etc. The data storage area can store data (such as audio data and an address book) created according to use of the mobile phone, and the like. The memory 409 may include a high-speed random access

memory, and may also include a non-volatile memory, for example, at least one magnetic disk storage device, a flash storage device, or other volatile solid-state storage devices.

[0177] The processor 410 is the control center of the mobile terminal and connects various parts of the whole mobile terminal by using various interfaces and lines. By running or executing
5 a software program and/or module stored in the memory 409, and invoking data stored in the memory 409, the processor 410 performs various functions of the mobile terminal and processes data, thereby performing overall monitoring of the mobile terminal. The processor 410 may include one or more processing units. Preferably, the processor 410 may integrate an application processor and a modem processor. The application processor mainly processes operating systems, user
10 interfaces, application programs, and the like. The modem processor mainly processes wireless communication. It can be understood that the modem processor may not be integrated into the processor 410.

[0178] The mobile terminal 400 may further include a power supply 411 (such as a battery) supplying power to various components. Preferably, the power supply 411 may be logically
15 connected to the processor 410 through a power supply management system, thereby implementing functions such as charging management, discharging management, and power consumption management by using the power supply management system.

[0179] In addition, the mobile terminal 400 includes some functional modules not shown, which are not described in detail here.

20 [0180] Preferably, an embodiment of this specification further provides a mobile terminal, which includes a processor 410, a memory 409, and a computer program that is stored in the memory 409 and operable on the processor 410. When the computer program is executed by the processor 410, the processes of the foregoing identification method embodiments are implemented, and the same technical effect can be achieved. To avoid repetition, the details are not described
25 again here.

[0181] An embodiment of this specification further provides a non-transitory computer-readable storage medium. The computer-readable storage medium stores a computer program. When the computer program is executed by a processor, the processes of any foregoing identification method embodiment can be implemented, and the same technical effect can be achieved. To avoid repetition, the details are not described again here. The computer-readable storage medium is, for example, a Read-Only Memory (ROM), a Random Access Memory (RAM), a magnetic disk, an optical disc, or the like.

[0182] The identification apparatus and terminal according to this application can combine the face, eye-print, and iris technologies, and the technologies can be applied to identification of non-cooperative users in a face-scanning payment scenario, thereby not only combining face-based and eye-print-based liveness detection technologies, but also using faces, irises, and eye-prints in large-scale user retrieval. Moreover, the retrieval can be implemented in a cascaded manner, thus balancing efficiency and accuracy, and achieving rapid retrieval from a database including millions of faces within a short period of time (such as 1 second).

[0183] It should be noted that, the terms "include," "comprise" or any other variations thereof are intended to cover a non-exclusive inclusion, so that a process, method, article or apparatus including a series of elements not only includes those elements, but also includes other elements not expressly listed, or further includes elements inherent to the process, method, article, or apparatus. In the absence of more limitations, an element defined by "including a/an..." does not exclude the presence of other, similar elements in the process, method, article or apparatus including the element.

[0184] According to the foregoing description of the implementations, those skilled in the art can clearly understand that the method in the foregoing embodiments may be implemented by software plus a necessary universal hardware platform, and of course, may also be implemented by hardware. However, in most cases, the former is a better implementation. Based on such an

understanding, the essence of the technical solution of the present invention, or the part making contributions to the prior art, may be embodied in the form of a software product. The computer software product is stored in a storage medium (such as a ROM/RAM, a magnetic disk, or an optical disc), and includes several instructions to enable a terminal (which may be a mobile phone, a computer, a server, an air conditioner, a network device, or the like) to perform the method according to the embodiments of the present invention.

[0185] Specific embodiments of this specification are described above. Other embodiments fall within the scope of the appended claims. In some cases, the actions or steps described in the claims may be performed in a sequence different from the sequence in the embodiment and still achieve the expected result. In addition, the processes depicted in the drawings do not necessarily require the specific sequence shown or a consecutive sequence to achieve the expected result. In some implementations, multi-task processing and parallel processing are also possible or may be advantageous.

[0186] The embodiments of the present invention are described above with reference to the accompanying drawings. However, the present invention is not limited to the foregoing specific implementations. The foregoing specific implementations are merely illustrative and are not restrictive. Under the teaching of the present invention, those with ordinary skill in the art may devise various forms without departing from the objective of the present invention and the protection scope of the claims, and all the forms fall within the protection scope of the present invention.

CLAIMS

1. An identification method, comprising:
controlling at least one camera to acquire a face image and an eye image of a target object,
wherein the eye image comprises an iris feature and/or an eye-print feature; and
5 identifying the target object based on the face image and the eye image.
2. The method of claim 1, wherein the identifying the target object based on the face image
and the eye image comprises:
determining whether the target object is a living body based on the eye image and the face
image; and
10 identifying the target object if the target object is a living body.
3. The method of claim 1, wherein the controlling at least one camera to acquire a face image
and an eye image of a target object comprises:
adjusting the at least one camera to acquire the face image of the target object; and
adjusting the at least one camera based on the position of a facial rectangular frame of the
15 face image to acquire the eye image of the target object.
4. The method of claim 3, wherein the at least one camera is one camera,
the adjusting the at least one camera to acquire the face image of the target object comprises:
adjusting the camera to obtain the position of the facial rectangular frame of the target object; and
acquiring the face image of the target object based on the position of the facial rectangular frame;
20 and
the adjusting the at least one camera based on the position of a facial rectangular frame of the
face image to acquire the eye image of the target object comprises: adjusting the camera based on
the position of the facial rectangular frame of the face image to obtain the position of a two-eye
rectangular frame of the target object; and acquiring the eye image of the target object based on
25 the position of the two-eye rectangular frame.

5. The method of claim 3, wherein the at least one camera comprises a first camera for photographing a face and a second camera for photographing eyes,

the adjusting the at least one camera to acquire the face image of the target object comprises:
adjusting the first camera to obtain the position of the facial rectangular frame of the target object;
5 and acquiring the face image of the target object based on the position of the facial rectangular frame; and

the adjusting the at least one camera based on the position of a facial rectangular frame of the face image to acquire the eye image of the target object comprises: adjusting the second camera based on the position of the facial rectangular frame to obtain the position of a two-eye rectangular
10 frame of the target object; and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

6. The method of claim 1, wherein the controlling at least one camera to acquire a face image and an eye image of a target object comprises:

adjusting the at least one camera to obtain the position of an initial facial rectangular frame
15 of the target object; and

adjusting the at least one camera based on the position of the initial facial rectangular frame to acquire the face image and the eye image of the target object.

7. The method of claim 6, wherein the at least one camera is one camera, and the adjusting the at least one camera based on the position of the initial facial rectangular frame to acquire the
20 face image and the eye image of the target object comprises:

adjusting the camera based on the position of the initial facial rectangular frame to obtain the position of a target facial rectangular frame of the target object and the position of a two-eye rectangular frame of the target object; and

acquiring the face image of the target object based on the position of the target facial
25 rectangular frame, and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

8. The method of claim 6, wherein the at least one camera comprises a first camera for photographing a face and a second camera for photographing eyes,

the adjusting the at least one camera to obtain the position of an initial facial rectangular frame of the target object comprises: adjusting the first camera to obtain the position of the initial facial
5 rectangular frame of the target object; and

the adjusting the at least one camera based on the position of the initial facial rectangular frame to acquire the face image and the eye image of the target object comprises: adjusting the first camera based on the position of the initial facial rectangular frame to obtain the position of a target facial rectangular frame of the target object, and acquiring the face image of the target object based
10 on the position of the target facial rectangular frame; adjusting the second camera based on the position of the target facial rectangular frame to obtain the position of a two-eye rectangular frame of the target object; and acquiring the eye image of the target object based on the position of the two-eye rectangular frame.

9. The method of claim 2, wherein the face image is a single-frame face image, the eye image
15 is a single-frame eye image, and the determining whether the target object is a living body based on the eye image and the face image comprises:

determining whether the target object is a living body based on a difference between a single-frame face image of a living body and a single-frame face image of a non-living body, and a difference between the iris feature and/or the eye-print feature included in a single-frame eye image
20 of a living body and the iris feature and/or the eye-print feature included in a single-frame eye image of a non-living body.

10. The method of claim 2, wherein the face image is a multi-frame face image, the eye image is a multi-frame eye image, and

the determining whether the target object is a living body based on the eye image and the face
25 image comprises:

determining that the target object is a living body if there are differences among the multiple frames of the face image;

determining that the target object is a living body if there are differences among the multiple frames of the eye image in terms of the iris feature or the eye-print feature; and

5 determining that the target object is a non-living body if there is no difference between the multiple frames of the eye image in terms of the iris feature or the eye-print feature.

11. The method of claim 1, wherein the eye image comprises an iris feature, and the identifying the target object comprises:

comparing the acquired face image with face images in a face image library;

10 selecting a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold;

further comparing the iris feature of the acquired eye image with iris features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images; and

15 identifying the target object successfully if the similarity between an iris feature of an eye image in the eye image library and the iris feature of the acquired eye image is greater than a second threshold.

12. The method of claim 1, wherein the eye image comprises an eye-print feature, and the identifying the target object comprises:

20 comparing the acquired face image with face images in a face image library;

selecting a first group of face images from the face image library, the first group of face images being face images whose similarities with the acquired face image are greater than a first threshold;

further comparing the eye-print feature of the acquired eye image with eye-print features of specified eye images in an eye image library, wherein the specified eye images are associated with

25 the face images in the first group of face images; and

identifying the target object successfully if the similarity between an eye-print feature of an eye image in the eye image library and the eye-print feature of the acquired eye image is greater than a third threshold.

13. The method of claim 1, wherein the eye image comprises an iris feature and an eye-print
5 feature, and the identifying the target object comprises:

comparing the acquired face image with face images in a face image library;

selecting a first group of face images from the face image library, the first group of face images
being face images whose similarities with the acquired face image are greater than a first threshold;

further comparing the iris feature of the acquired eye image with iris features of specified eye
10 images in an eye image library, wherein the specified eye images are associated with the face
images in the first group of face images;

selecting a first group of eye images from the specified eye images, the first group of eye
images being eye images having iris features whose similarities with the iris feature of the acquired
eye image are greater than a second threshold in the specified eye images;

15 comparing the eye-print feature of the acquired eye image with eye-print features of the eye
images in the first group of eye images; and

identifying the target object successfully if the similarity between an eye-print feature of an
eye image in the first group of eye images and the eye-print feature of the acquired eye image is
greater than a third threshold.

20 14. The method of claim 1, wherein the eye image comprises an iris feature and an eye-print
feature, and the identifying the target object comprises:

comparing the acquired face image with face images in a face image library;

selecting a first group of face images from the face image library, the first group of face images
being face images whose similarities with the acquired face image are greater than a first threshold;

further comparing the eye-print feature of the acquired eye image with eye-print features of specified eye images in an eye image library, wherein the specified eye images are associated with the face images in the first group of face images;

selecting a second group of eye images from the specified eye images, the second group of
5 eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold in the specified eye images;

comparing the iris feature of the acquired eye image with iris features of the eye images in the second group of eye images; and

identifying the target object successfully if the similarity between an iris feature of an eye
10 image in the second group of eye images and the iris feature of the acquired eye image is greater than a second threshold.

15. The method of claim 1, wherein the eye image comprises an iris feature, and the identifying the target object comprises:

comparing the iris feature of the acquired eye image with iris features of eye images in an eye
15 image library;

selecting a third group of eye images from the eye image library, the third group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold;

comparing the acquired face image with specified face images in a face image library, wherein
20 the specified face images are associated with the eye images in the third group of eye images; and

identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

16. The method of claim 1, wherein the eye image comprises an eye-print feature, and the identifying the target object comprises:

25 comparing the eye-print feature of the acquired eye image with eye-print features of eye images in an eye image library;

selecting a fourth group of eye images from the eye image library, the fourth group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold;

comparing the acquired face image with specified face images in a face image library, wherein
5 the specified face images are associated with the eye images in the fourth group of eye images; and
identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

17. The method of claim 1, wherein the eye image comprises an iris feature and an eye-print feature, and the identifying the target object comprises:

10 comparing the iris feature of the acquired eye image with iris features of eye images in an eye image library;

selecting a third group of eye images from the eye image library, the third group of eye images being eye images having iris features whose similarities with the iris feature of the acquired eye image are greater than a second threshold;

15 comparing the eye-print feature of the acquired eye image with eye-print features of the eye images in the third group of eye images;

selecting a fifth group of eye images from the third group of eye images, the fifth group of eye images being eye images having eye-print features whose similarities with the eye-print feature of the acquired eye image are greater than a third threshold;

20 comparing the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the fifth group of eye images; and

identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

18. The method of claim 1, wherein the eye image comprises an iris feature and an eye-print
25 feature, and the identifying the target object comprises:

comparing the eye-print feature of the acquired eye image with eye-print features of eye images in an eye image library;

selecting a fourth group of eye images from the eye image library, the fourth group of eye images being face images having eye-print features whose similarities with the eye-print feature
5 of the acquired eye image are greater than a third threshold;

comparing the iris feature of the acquired eye image with iris features of the eye images in the fourth group of eye images;

selecting a sixth group of eye images from the fourth group of eye images, the sixth group of eye images being eye images having iris features whose similarities with the iris feature of the
10 acquired eye image are greater than a second threshold;

comparing the acquired face image with specified face images in a face image library, wherein the specified face images are associated with the sixth group of eye images; and

identifying the target object successfully if the similarity between a face image in the specified face images and the acquired face image is greater than a first threshold.

15 19. An identification apparatus, comprising:

an acquisition module configured to acquire a face image and an eye image of a target object through at least one camera, wherein the eye image comprises an iris feature and/or an eye-print feature; and

an identification module configured to identify the target object based on the face image and
20 the eye image.

20. An identification device, comprising:

a processor; and

a memory configured to store computer executable instructions, wherein the processor performs the following operations when the executable instructions are executed:

25 controlling at least one camera to acquire a face image and an eye image of a target object, wherein the eye image comprises an iris feature and/or an eye-print feature; and

identifying the target object based on the face image and the eye image.

21. A computer-readable storage medium, wherein one or more programs are stored in the computer-readable storage medium, and the following operations are performed when the one or more programs are executed:

- 5 controlling at least one camera to acquire a face image and an eye image of a target object, wherein the eye image comprises an iris feature and/or an eye-print feature; and
 identifying the target object based on the face image and the eye image.