(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
11 July 2002 (11.07.2002)

PCT

(10) International Publication Number
WO 02/054240 A2

(51) International Patent Classification[7]: G06F 11/00

(21) International Application Number: PCT/US01/46391

(22) International Filing Date: 3 December 2001 (03.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/751,633 29 December 2000 (29.12.2000) US

(71) Applicant: **TERADYNE, INC.** [US/US]; 321 Harrison Avenue, Boston, MA 02118 (US).

(72) Inventors: **PANIS, Michael, C.**; 21 Warwick Road, No. 3, Brookline, MA 02445 (US). **ROBBINS, Bradford, B.**; 7 Lathrop Road, Wellesley, MA 02482 (US).

(74) Agents: **RUBENSTEIN, Bruce, D.** et al.; Teradyne, Inc., 321 Harrison Avenue, Boston, MA 02118 (US).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ENHANCED LOOPBACK TESTING OF SERIAL DEVICES



(57) Abstract: An instrument for economically yet thoroughly testing serial ports employs a receiver and a transmitter. The receiver can be coupled to a TX line of a serial port for receiving a serial bit stream. The transmitter can be coupled to an RX line of the serial port for generating a serial bit stream. The receiver is coupled to the transmitter for establishing a loopback connection between the TX and RX lines of the serial port. A time distortion circuit and a selector are interposed between the receiver and the transmitter. The time distortion circuit adds predetermined amounts of timing distortion for testing the serial port. The selector selects between the receiver and a direct input, which provides an algorithmic test signal. The algorithmic test signal differs from the input serial bit stream received by the receiver to allow the TX and RX lines to be independently tested.

WO 02/054240 A2