

Process for the manufacture and separation of dinitrile compounds

The present invention relates to a process for the
5 manufacture and separation of dinitrile compounds.

It relates more particularly to a process for the
manufacture and separation of dinitrile compounds from
a medium originating from the hydrocyanation of
10 unsaturated mononitriles.

Dinitrile compounds, such as adiponitrile, are
important chemical intermediates in the manufacture of
numerous compounds. Adiponitrile is in particular a
15 chemical intermediate in the synthesis of various
monomers used in the manufacture of polymers, such as
polyamides.

Furthermore, the process for the synthesis of dinitrile
20 compounds used industrially consists in carrying out a
two-stage hydrocyanation of diolefins, for example of
butadiene.

In a first stage, the synthesis makes it possible to
25 produce unsaturated mononitriles. The latter are used
as starting material in a second stage in order to be
converted to dinitriles by reaction with a molecule of
hydrogen cyanide. Generally, these two stages are
carried out successively with movement of the various
30 streams, such as, for example, the stream of the
catalytic system, between these stages. However, they
can be carried out separately and independently.

The reaction medium resulting from the second stage
35 comprises the dinitriles formed, the unconverted
mononitriles and the catalytic system, as well as
various by-products.

The processes comprise stages for the treatment of this

reaction medium in order, on the one hand, to separate the catalytic system and, on the other hand, to separate the dinitriles from the mononitriles, which will advantageously be recycled.

5

The separation of the catalytic system is generally obtained by separation by settling and/or by liquid/liquid extraction with an extraction solvent, such as hydrocarbons.

10

The organic phase comprising the mononitriles and dinitriles is treated in a distillation stage in order to separate the mononitriles from the dinitriles, on the one hand, and the heavy products, on the other
15 hand. This distillation stage comprises, in current processes, two distillation columns; in a first column, the products with a lower boiling point than that of the dinitriles, such as the mononitriles, are separated and recovered at the column top; the heavy fraction
20 comprising the dinitriles is fed to a second distillation column, making it possible to distil the dinitriles, which are recovered at the column top.

There are several disadvantages to this process,
25 including that of maintaining the dinitrile compounds at a high temperature for a relatively long period of time.

Maintaining the dinitrile compounds at a high
30 temperature promotes the formation of by-products originating from the decomposition of the dinitriles. Thus, in the case of adiponitrile, one by-product, iminocyanocyclopentane (ICCP), is formed in particular. This by-product is very difficult to separate from
35 adiponitrile. In addition, in processes for the conversion of adiponitrile to other compounds, such as, for example, to hexamethylenediamine, the by-products can be converted to other compounds which are difficult to separate. Thus, during the hydrogenation of

adiponitrile to hexamethylenediamine, the ICCP is converted to aminomethylenecyclopentaneamine (AMCPA). These impurities cannot be accepted in processes for the manufacture of polymers, such as polyamide, in particular when the latter are used for the manufacture of textile yarns.

One of the aims of the present invention is to overcome these disadvantages by providing a novel process for the preparation and separation of dinitrile compounds which makes it possible, in particular, to limit and minimize the formation of by-products during the recovery and extraction of the dinitrile compounds formed.

A subject-matter of the present invention is a process for the manufacture and separation of dinitriles from a medium originating from the hydrocyanation of unsaturated mononitriles, characterized in that it consists in

- ▶ feeding the medium comprising the dinitriles to a distillation column at the level of a theoretical plate of the column
- ▶ recovering, at the column top, the compounds with a lower boiling point than that of the dinitriles
- ▶ recovering the intermediate fraction comprising the dinitriles from a theoretical plate situated in a lower part of the column with respect to the plate for feeding the medium comprising the dinitriles
- ▶ recovering the products with a higher boiling point than that of the dinitriles at the column bottom.

According to one characteristic of the invention, the column bottom temperature is less than 200°C, preferably between 140°C and 190°C. Such a column bottom temperature makes it possible to limit the formation of by-products, in particular by thermal

decomposition of the dinitriles. The term "column bottom temperature" is understood to mean the temperature of the liquid phase in the boiler of the column and the wall temperature of the said boiler.

5

Advantageously, the intermediate fraction comprising the dinitriles is recovered without reflux or with a reflux. The reflux ratio can represent from 1 to 6% by weight of the fraction recovered. The reflux can be
10 introduced into the column at the same level as the withdrawal of the said fraction or at a different level.

According to another characteristic of the invention,
15 the dinitrile compounds produced by the process of the invention are compounds of following general formula (I):



20 in which the R radical represents a saturated hydrocarbonaceous radical comprising from 2 to 10 carbon atoms.

The preferred dinitrile compounds of the invention are
25 chosen from the group consisting of adiponitrile, methylglutaronitrile and ethylsuccinonitrile.

The distillation is carried out under an appropriate pressure according to the nature of the dinitrile
30 compounds to be separated, preferably at a pressure of between 1 kPa and 5 kPa.

The distillation of the invention can be carried out in any suitable device, such as a plate column, a packed
35 column or a partition column. The number of theoretical plates of the column is determined according to the nature of the compounds to be treated. Generally, columns exhibiting a number of theoretical plates of between 6 and 20 are suitable for the invention.

The intermediate fraction comprising the dinitrile compounds is withdrawn from the distillation column advantageously in the liquid state or in the vapour state. The fraction collected at the column top
5 comprises, in the case of a hydrocyanation process, the unsaturated mononitriles present in the medium.

The process of the invention makes it possible to recover dinitriles comprising a very low amount of by-
10 products originating from the thermal decomposition of the dinitrile compounds. The dinitriles thus recovered can be subjected to a separation, for example by distillation, to recover, on the one hand, adiponitrile, and, on the other hand, the other
15 dinitriles formed, such as methylglutaronitrile or ethylsuccinonitrile.

Furthermore, the process of the invention makes it possible to obtain dinitrile compounds comprising a
20 very low concentration of impurities while using a single distillation column, that is to say with reduced capital and operating costs in comparison with current plants comprising two columns arranged in series.

25 Other advantages and details of the invention will become more clearly apparent in the light of the description of an implementational example of the process of the invention, given solely by way of illustration and made with reference to the appended
30 figures, in which:

- Figure 1 represents a block diagram of a plant for the separation of dinitriles of the prior art,
- Figure 2 represents a block diagram of an embodiment of a plant for the separation of
35 dinitriles in accordance with the invention.

COMPARATIVE EXAMPLE 1:

With reference to Figure 1, a mixture resulting from a

process for the manufacture of adiponitrile by hydrocyanation of pentenenitriles in the presence of a catalytic system comprising an organometallic complex of nickel and of tritolyl phosphite and of a Lewis acid
5 (ZnCl₂) is fed at 1 to a first distillation column 2 comprising a packing and exhibiting a number of theoretical plates of 6. The column bottom temperature is 161°C and the operating pressure is 2 kPa.

10 A top fraction 5 is withdrawn with a reflux 4. The withdrawn fraction 5 comprises the products exhibiting a boiling point below that of adiponitrile or more generally below those of the dinitriles present in the medium. As is indicated in Table I below, this top
15 fraction is composed mainly of pentenenitriles which have not been converted to dinitriles.

The liquid present at the column bottom circulates in a loop 7 comprising a boiler. A tail fraction 6 is
20 withdrawn at the bottom of column 2 or from this circulation.

This fraction 6 is fed to a second distillation column 8. In the example illustrated, the column 8 is similar
25 to the column 2. The column bottom temperature is 164°C and the pressure is 2 kPa.

Fraction 6 is fed at the level of an intermediate plate of the column 8. The dinitriles, including
30 adiponitrile, are recovered in the form of a top fraction 9, with a reflux 10.

The compounds with a higher boiling point than that of adiponitrile and of the dinitriles present are
35 recovered in the form of a tail fraction 11. As in the column 2, the liquid present in the column bottom is circulated 12 with the presence of a boiler in the circulation loop.

The compositions of the various fractions are shown in Table I below.

5 The residence time of the mixture and in particular of the adiponitrile and the dinitriles is the sum of the residence times in the columns 2 and 8.

The ICCP concentration in the top fraction 9 of the second column 8 is 0.08% by weight.

10

Table I

	Mixture 1	Fraction 5	Fraction 6	Fraction 9	Fraction 11
Pentenitriles (% by weight)	19.6	97.6	0.16	0.17	0
Dinitriles (% by weight)	80	2.4	99.34	99.82	90.99
Heavy compounds (% by weight)	0.4	0	0.5	0.01	9.01
Total stream (kmol/h)	1	0.2	0.8	0.76	0.04

15 The term "heavy compounds" denotes the compounds with a higher boiling point than that of adiponitrile

EXAMPLE 2

20 With reference to Figure 2, a mixture corresponding to that of Example 1 is fed at 13 to an intermediate plate of a packed distillation column 14. This column exhibits 6 theoretical plates and operates under a pressure of 2 kPa with a column bottom temperature of 164°C.

25

The compounds with a lower boiling point than those of the dinitriles present, more particularly than that of

adiponitrile, are recovered in the form of a top fraction 15 with a reflux 16. The composition of this top fraction 15 is shown in Table II below and comprises in particular the unconverted
5 pentenenitriles.

The compounds with a higher boiling point than those of the dinitriles present, more particularly than that of adiponitrile, are recovered at the bottom of column 14 in the form of a fraction 17 with circulation of the
10 liquid at the column bottom through a loop 18 comprising a boiler. The fraction 17 can advantageously be concentrated before being recycled in the loop 18.

The dinitriles, including adiponitrile, are recovered
15 in a fraction 19 by withdrawing from an intermediate plate situated at a lower position with respect to that at which the mixture to be treated is fed 13.

The compositions of the various fractions are shown in
20 Table II below.

The residence time of the mixture and in particular of the dinitriles, including adiponitrile, is of the same order of magnitude as that observed in the column 8 of
25 Example 1. Thus, the process of the invention makes it possible to separate and recover the dinitriles, including adiponitrile, with a residence time of this compound in the distillation column which is lower than that observed in Example 1. This is because the
30 residence time in the column 2 is eliminated with the process of the invention.


The process of the invention makes it possible to recover dinitriles comprising 0.04% by weight of ICCP.
35

Table II

	Mixture 1	Fraction 15	Fraction 19	Fraction 17
Pentenitriles (% by weight)	19.6	97.6	0.17	0
Adiponitrile (% by weight)	80	2.4	99.82	90.99
Heavy compounds (% by weight)	0.4	0	0.01	9.01
Total stream (kmol/h)	1	0.2	0.76	0.04

Claims

1. Process for the manufacture and separation of dinitriles from a medium originating from the hydrocyanation of unsaturated mononitriles, characterized in that it consists in
 - ▶ feeding the medium comprising the dinitriles to a distillation column
 - ▶ recovering, at the column top, the compounds with a lower boiling point than that of the dinitriles
 - ▶ recovering the intermediate fraction comprising the dinitriles from a theoretical plate situated in a lower part of the column with respect to the feed point of the medium comprising the dinitriles, and
 - ▶ recovering, at the column bottom, the products with a higher boiling point than that of the dinitriles.
2. Process according to claim 1, characterized in that the column bottom temperature is less than 200°C, preferably between 140°C and 190°C.
3. Process according to claim 1 or 2, characterized in that the recovery of the intermediate fraction is carried out without reflux.
4. Process according to claim 1 or 2, characterized in that the recovery of the intermediate fraction is carried out with a reflux ratio of between 1 and 6% by weight of the intermediate fraction.
5. Process according to one of the preceding claims, characterized in that the dinitrile compounds are compounds of following general formula (I):



(I)

in which the R radical represents a saturated hydrocarbonaceous radical comprising from 2 to 10 carbon atoms.

- 5 6. Process according to claim 5, characterized in that the dinitriles are chosen from the group consisting of adiponitrile, methylglutaronitrile and ethylsuccinonitrile.
- 10 7. Process according to one of the preceding claims, characterized in that it is carried out under a pressure of between 1 kPa and 5 kPa.
- 15 8. Process according to one of the preceding claims, characterized in that the distillation column is a plate column, a packed column or a partition column.