

LIQUID MENISCUS LENS INCLUDING VARIABLE VOLTAGE ZONES

RELATED APPLICATIONS

5 This application claims priority to Provisional Patent Application U.S. Serial No. 61/387597 which was filed on September 29, 2010 and entitled "LIQUID MENISCUS LENS INCLUDING VARIABLE VOLTAGE ZONES", and as a Continuation in Part Application to Non-Provisional Patent Application U.S. Serial No. 13/095786 which was filed on April 27, 2011 and entitled "ARCUATE LIQUID MENISCUS LENS", as well as Non-Provisional Patent
10 Application U.S. Serial No. 13/149105 which was filed on May 31, 2011 and entitled "LENS WITH CONICAL FRUSTUM MENISCUS WALL", as a Continuation in Part Application, the contents of each of which are relied upon.

FIELD OF USE

 The present invention relates generally to a liquid meniscus lens, more specifically, it
15 includes an arcuate liquid meniscus lens with variable voltage zones on the meniscus wall.

BACKGROUND

 Liquid meniscus lenses have been known in various industries. As discussed more fully below with reference to Figs. 1A and 1B, known liquid meniscus lenses were engineered in cylindrical shapes with a perimeter surface formed by points at a fixed distance from an axis
20 which is a straight line. Known liquid meniscus lenses have been limited to designs with a first interior surface generally parallel to a second interior surface and each perpendicular to a cylindrical axis. Known examples of the use of liquid meniscus lenses include devices such as electronic cameras.

 Traditionally, an ophthalmic device, such as a contact lens and an intraocular lens
25 included a biocompatible device with a corrective, cosmetic or therapeutic quality. A contact lens, for example, can provide one or more of: vision correcting functionality; cosmetic enhancement; and therapeutic effects. Each function is provided by a physical characteristic of

the lens. A design incorporating a refractive quality into a lens can provide a vision corrective function. A pigment incorporated into the lens can provide a cosmetic enhancement. An active agent incorporated into a lens can provide a therapeutic functionality.

More recently, electronic components have been incorporated into a contact lens. Some components can include semiconductor devices. However, physical constraints including the size, shape and control aspects of a liquid meniscus lens have precluded their use in an ophthalmic lens. Generally the cylindrical shape, sometimes referred to as the “hockey puck” shape of liquid meniscus lenses, has not been conducive to something that can work in a human eye environment.

In addition, a curved liquid meniscus lens includes physical challenges that are not necessarily present in a traditional design of a liquid meniscus lens with parallel sidewalls and/or optical windows.

SUMMARY

Accordingly, the present invention provides a liquid meniscus lens. Some preferred embodiments include an arcuate front curve lens and an arcuate back curve lens. The present invention provides for a meniscus wall with physical features conducive for one or both of attraction and repulsion of a liquid contained within the lens and forming a meniscus with another liquid.

According to the present invention, a first optic is proximate to a second optic with a cavity formed therebetween. Preferred embodiments include a first arcuate shaped optic proximate to a second arcuate shaped optic with a cavity formed therebetween. A saline solution and an oil are maintained within the cavity. Application of an electrostatic charge to a meniscus wall generally located in a perimeter area of one or both of the first optic and the second optic changes the physical shape of a meniscus formed between the saline solution and oil maintained within the cavity.

The present invention includes a liquid meniscus lens with variable voltage zones on the meniscus wall. In the current embodiment the meniscus wall is formed into a shape essentially including a frustum of a cone.

DESCRIPTION OF THE DRAWINGS

Fig. 1A illustrates a prior art example of a cylindrical liquid meniscus lens in a first state.

5 Fig. 1B illustrates the prior art example of a cylindrical liquid meniscus lens in a second state.

Fig. 2 illustrates a profile sliced cut away of an exemplary liquid meniscus lens according to some embodiments of the present invention.

10 Fig. 3 illustrates a cross section of a portion of an exemplary arcuate liquid meniscus lens, according to some embodiments of the present invention.

Fig. 4 illustrates additional exemplary aspects of an arcuate liquid meniscus lens.

Fig. 5 illustrates meniscus wall elements within an arcuate liquid meniscus lens, according to some embodiments of the present invention.

15 Fig. 6 illustrates a top down sectional view of a meniscus wall with variable voltage zones, according to some embodiments of the present invention.

Fig. 7 illustrates a top down orthogonal view of a meniscus wall with variable voltage zones showing a position of a liquid meniscus boundary, according to some embodiments of the present invention.

20 Fig. 8 illustrates cross section of a portion of an exemplary arcuate liquid meniscus lens, showing locations of a liquid meniscus boundary on a meniscus wall, according to some embodiments of the present invention.

Fig. 9 illustrates a top down orthogonal view of a meniscus wall with thirty-six voltage zones, according to some embodiments of the present invention.

25 DETAILED DESCRIPTION OF THE INVENTION

The present invention provides for a liquid meniscus lens with at least one of a front curve lens and a back curve lens defining a meniscus cavity of the liquid meniscus lens.

GLOSSARY

In this description and claims directed to the presented invention, various terms may be used for which the following definitions will apply:

5 Contact Angle: The angle at which the oil/saline solution interface, also referred to as the liquid meniscus boundary, meets the meniscus wall. In the case of a linear meniscus wall, the contact angle is measured as the angle between the meniscus wall and the line tangent to the liquid meniscus boundary at the point where the liquid meniscus boundary meets the meniscus wall. In the case of a curved meniscus wall, the contact angle is measured as the angle between the lines tangent to the meniscus wall and the liquid meniscus boundary at the point where they
10 meet.

 Lens: As used herein, a Lens means an article with a front surface and a back surface that is optically transmissive to a predefined range of wavelengths of radiation, such as, by way of example, visible light. A lens may include one or both of a front surface and a back surface which are essentially flat or one or both of a front surface and a back surface which are arcuate
15 in shape.

 Liquid Meniscus Boundary: The arcuate surface interface between the saline solution and the oil. Generally, the surface will form a lens that is concave on one side and convex on the other.

 Meniscus Cavity: The space in an arcuate liquid meniscus lens between the front curve
20 lens and the back curve lens in which oil and saline solution are maintained.

 Meniscus Wall: A specific area on the interior of the front curve lens, such that it is within the meniscus cavity, along which the liquid meniscus boundary moves.

 Optical Zone: as used herein refers to an area of an ophthalmic lens through which a wearer of the ophthalmic lens sees.

25 Sharp: A geometric feature of an internal surface of either a front curve or back curve lens piece sufficient to contain the location of a contact line of two predefined fluids on the optic. The sharp is usually an outside corner rather than an inside corner. From a fluid standpoint it is an angle greater than 180 degrees.

Referring now to Fig. 1A, a cut away view of a prior art lens 100 is illustrated with an oil 101 and a saline solution 102 contained within cylinder 110. The cylinder 110 includes two plates of optical material 106. Each plate 106 includes an essentially flat interior surface 113-114. The cylinder 110 includes an interior surface that is essentially rotationally symmetric. In some prior art embodiments, one or more surfaces may include a hydrophobic coating. Electrodes 105 are also included on or about the perimeter of the cylinder. An electrical insulator may also be used proximate to the electrodes 105.

According to the prior art, each of the interior surfaces 113-114 is essentially flat or planar. An interface surface 112A is defined between the saline solution 102A and the oil 101. As illustrated in Fig. 1A, the shape of the interface 112A is combined with the refractive index properties of the saline solution 102A and the oil 101 to receive incident light 108 through a first interior surface 113 and provide divergent light 109 through a second interior surface 113. The shape of the interface surface between the oil 101 and the saline solution 102 may be altered with the application of an electrical potential to the electrodes 105.

Fig. 1A illustrates a perspective view of the prior art lens illustrated at 100.

Referring now to Fig. 1B, the prior art lens 100 is illustrated in an energized state. The energized state is accomplished by applying voltage 114 across the electrodes 115. The shape of the interface surface 112B between the oil 101 and the saline solution 102 is altered with the application of an electrical potential to the electrodes 115. As illustrated in Fig. 1B, incident light 108B passing through the oil 101 and the saline solution 102B is focused into a convergent light pattern 111.

Referring now to Fig. 2, a cut away view of a liquid meniscus lens 200 with a front curve lens 201 and a back curve lens 202. In various embodiments, the front curve lens 201 and the back curve lens 202 may include an arcuate lens or a substantially flat lens. In some preferred embodiments, the front curve lens 201 and the back curve lens 202 are positioned proximate to each other and form a cavity 210 therebetween. The front curve lens includes a concave arcuate interior lens surface 203 and a convex arcuate exterior lens surface 204. The concave arcuate lens surface 203 may have one or more coatings (not illustrated in Fig. 2). Coatings may include, for example, one or more of electrically conductive materials or electrically insulating materials, hydrophobic materials or hydrophilic materials. One or both of

the concave arcuate lens surface 203 and the coatings are in liquid and optical communication with an oil 208 contained within the cavity 210.

The back curve lens 202 includes a convex arcuate interior lens surface 205 and a concave arcuate exterior lens surface 206. The convex arcuate lens surface 205 may have one or more coatings (not illustrated in Fig. 2). Coatings may include, for example, one or more of electrically conductive materials or electrically insulating materials, hydrophobic materials or hydrophilic materials. At least one of the convex arcuate lens surface 205 and the coatings are in liquid and optical communication with a saline solution 207 contained within the cavity 210. The saline solution 207 includes one or more salts or other components which are ionically conductive and as such may be either attracted to or repulsed by an electric charge.

According to the present invention, an electrically conductive coating 209 is located along at least a portion of a periphery of one or both of the front curve lens 201 and the back curve lens 202. The electrically conductive coating 209 may include gold or silver and is preferably biocompatible. Application of an electrical potential to the electrically conductive coating 209 creates either an attraction or a repulsion of the ionically conductive salts or other components in the saline solution.

The front curve lens 201 has an optical power in relation to light passing through the concave arcuate interior lens surface 203 and a convex arcuate exterior lens surface 204. The optical power may be 0 or may be a plus or minus power. In some preferred embodiments, the optical power is a power typically found in corrective contact lenses, such as, by way of non-limiting example, a power between -8.0 and +8.0 diopters.

The back curve lens 202 has an optical power in relation to light passing through the convex arcuate interior lens surface 205 and a concave arcuate exterior lens surface 206. The optical power may be 0 or may be a plus or minus power. In some embodiments, the optical power is a power typically found in corrective contact lenses, such as, by way of non-limiting example, a power between -8.0 and +8.0 diopters. An optical axis is formed through the back curve lens 202 and the front curve lens 201.

Various embodiments may also include a change in optical power associated with a change in shape of a liquid meniscus 211 formed between the saline solution 207 and the oil. In some embodiments, a change in optical power may be relatively small, such as, for example, a

change of between 0 to 2.0 diopters of change. In other embodiments, a change in optical power associated with a change in shape of a liquid meniscus may be up to about 30 or more diopters of change. Generally, a higher change in optical power associated with a change in shape of a liquid meniscus 211 is associated with a relatively increased lens thickness 213.

5 According to some embodiments of the present invention, such as those embodiments that may be included in an ophthalmic lens, such as a contact lens, a cross cut lens thickness 213 of an arcuate liquid meniscus lens 200 will be up to about 1,000 microns thick. An exemplary lens thickness 213 of a relatively thinner lens 200 may be up to about 200 microns thick. Preferred embodiments may include a liquid meniscus lens 200 with a lens thickness 213 of
10 about 600 microns thick. Generally a cross cut thickness of front curve lens 201 may be between about 35 microns to about 200 microns and a cross cut thickness of a back curve lens 202 may also be between about 35 microns and 200 microns. Typically, a cross-sectional profile includes a defined variance in thickness at different locations in the lens 201.

 According to the present invention, an aggregate optical power is an aggregate of optical
15 powers of the front curve lens 201 the back curve lens 202 and a liquid meniscus 211 formed between the oil 208 and the saline solution 207. In some embodiments, an optical power of the lens 200 will also include a difference in refractive index as between one or more of the front curve lens 201, the back curve lens 202, oil 208 and the saline solution 207.

 In those embodiments that include an arcuate liquid meniscus lens 200 incorporated into
20 a contact lens, it is additionally desirous for the saline 207 and oil 208 to remain stable in their relative positions within the curved liquid meniscus lens 200 as a contact wearer moves. Generally, it is preferred to prevent the oil 208 from floating and moving relative to the saline 207 when the wearer moves, accordingly, an oil 208 and saline solution 207 combination is preferably selected with a same or similar density. Additionally, an oil 208 and a saline solution
25 207 preferably have relatively low miscibility so that the saline 207 and oil 208 will not mix.

 In some preferred embodiments, a volume of saline solution contained within the cavity is greater than the volume of oil contained within the cavity. Additionally, some preferred embodiments include the saline solution 207 in contact with essentially an entirety of an interior surface 205 of the back curve lens 200. Some embodiments may include a volume of oil 208
30 that is about 66% or more by volume as compared to an amount of saline solution 207. Some

additional embodiments may include an arcuate liquid meniscus lens wherein a volume of oil 208 that is about 90% or less by volume as compared to an amount of saline solution 207.

Referring now to Fig. 3, a cutaway of an edge portion arcuate liquid meniscus lens 300 is illustrated. As discussed above, an arcuate liquid meniscus lens 300 includes combined front 5 curve lens 301 and back curve lens 302 components. The front curve lens 301 and back curve lens 302 may be formed with one or more materials that are at least partially transparent. In some embodiments, one or both of the front curve lens 301 and the back curve lens 302 include generally optically clear plastic, such as for example, one or more of: PMMA, Zeonor and TPX.

One or both of the front curve lens 301 and the back curve lens 302 may be fashioned, 10 for example via processes such as one or more of: single point diamond turning lathing; injection molding; digital mirror device free forming.

One or both of the front curve lens 301 and the back curve lens 302 may include a conductive coating 303, as illustrated, the conductive coating 303 extending along a perimeter portion from 309 to 310. In some preferred embodiments, a conductive coating 303 includes 15 gold. The gold may be applied via a sputter process, vapor deposition or other known process. Alternative conductive coating 303 may include, by way of non-limiting example, aluminum, nickel, and indium tin oxide. Generally, the conductive coating 303 will be applied to perimeter areas of one or both of the front curve lens 301 and the back curve lens 302.

In some embodiments, of the present invention, a back curve lens 302 has a conductive 20 coating 304 applied to specific areas. For example, portions about the perimeter of the back curve lens 302 may be coated from a first boundary 304-1 to a second boundary 304-2. The gold coatings may be applied for example via a sputter process or a vapor deposition. In some embodiments, a mask may be used to apply the gold or other conductive material in a predetermined pattern around one or more perimeter portions of a front curve lens 301 or a back 25 curve lens 302. Alternative conductive materials may be applied using various methods and covering varying areas of the back curve lens 302.

In some embodiments, a conductive pass through, such as, for example one or more holes or slots in a back curve lens 302 may be filled with a conductive filler material, such as, for example, a conductive epoxy. The conductive filler may provide electrical communication

to a conductive coating on an interior surface of one or both of the front curve lens 301 and the back curve lens 302.

In another aspect of the present invention, one or both of the front curve lens 301 and the back curve lens 302 may be created from multiple different materials wherein an optical zone
5 generally in a central area of the front curve lens 301 and the back curve lens 302 (not illustrated) may include an optically transparent material and a peripheral zone may include an optically opaque area that includes an electrically conductive material. The optically opaque area may also include one or more of control circuitry and energy sources.

In still another aspect, in some embodiments, an insulator coating 305 is applied to a
10 front curve lens 301. By way of non-limiting example, the insulator coating 305 may be applied in an area from a first region 305-1 and extend to a second region 305-2. Insulators may include, for example, Parylene C™, Teflon AF or other materials with various electrical and mechanical characteristics and electrical resistance.

In some specific embodiments, an insulator coating 305 creates a boundary area to
15 maintain separation between the conductive coating 303 and a saline solution 306 contained in a cavity between the front curve lens 301 and the back curve lens 302. Some embodiments accordingly include an insulator coating 305 patterned and positioned in one or more areas of one or both of the front curve lens 301 and the back curve lens 302 to prevent a positively charged conductor 303 and negatively charged saline solution 306 from coming into contact,
20 wherein contact of a conductor 303 and a saline solution 306 will result in an electrical short. Embodiments may include a positively charged saline solution 306 and a negatively charged conductor 303.

Still other embodiments may allow for a short between a conductor 303 and a saline solution 306 as a reset function of circuitry associated with the operation of the lens 300. For
25 example, a short condition may equalize potential applied to the lens and cause the saline solution 306 and the oil 307 to revert to a default position.

Some preferred embodiments include a conductor 303 that extends from an area 309 on the interior of the cavity 311 to an area 310 external to the cavity 311. Other embodiments may include a channel 312 through the front curve lens or the back curve lens which may be filled
30 with a conductive material 313, such as, for example, a waterproof conductive epoxy. The

conductive material 313 may form or be connected to an electrical terminal external to the cavity. An electrical charge may be applied to the terminal and conducted to the coating via the conductive material 313 in the channel 312.

The thickness of the insulator coating 305 may be varied as a parameter of lens performance. According to the present invention, charged components, including the saline solution 306 and the conductor 303, are generally maintained on either side of the insulator coating 305. The present invention provides for an indirect relationship between the thickness of the insulator coating 305 and an electrical field between the saline solution 306 and the conductor 303, wherein the farther apart the saline solution 306 and the conductor 303 are maintained, the weaker the electrical field will be.

Generally, the present invention provides that electrical field strength may fall off dramatically as insulator coating 305 thickness increases. The closer together the fields are, the more energy that will generally be available to move a spherical liquid meniscus boundary 308. As a distance between the saline solution 306 and conductor 303 increases, the farther apart electrostatic charges of the saline solution 306 and the conductor coating 303 will be and therefore the harder it is to get the spherical meniscus boundary 308 to move. Inversely, the thinner the insulator coating 305, the more susceptible is the lens to defects in an insulator coating 305. Generally, even a relatively small hole in the insulator coating 305 will create an electrical short circuit and the lens will not function in an electrowetting fashion.

In some embodiments, it is desirable to include a saline solution 306 with density that is generally the same density of an oil 307 also contained within the lens 300. For example, a saline solution 306 may preferably include a density that is within 10% of a density of an oil 307 and more preferably the saline solution 306 will include a density within 5% of a density of an oil and most preferably within about 1% or less. In some embodiments, a concentration of salts or other components within the saline solution 306 may be adjusted to adjust the density of the saline solution 306.

According to the present invention, an arcuate liquid meniscus lens 300 will provide a more stable optical quality by limiting movement of the oil 307 in relation to the front curve lens 301 and the back curve lens 302. One method of maintaining stability of movement of the oil 307 in relation to one or both of the arcuate front curve lens 301 and the back curve lens 302

is to maintain a relatively congruent density in the oil 307 and the saline solution 306. In addition, due to the curve design of the interior surfaces of both the front curve lens 301 and the back curve lens 302, the relative depth or thickness of a layer of saline solution 306 is diminished as compared to a traditional cylindrical lens design. In this scenario, the interfacial forces acting on fluids within the cavity may have a relatively greater contribution toward maintaining an unperturbed liquid meniscus boundary. Consequently, the density matching requirement may become more relaxed in such cases. In some embodiments, the relative thinness of the fluid layers further supports the liquid lens boundary

In some preferred embodiments, the saline solution 306 provides a low refractive index as compared to the oil 307 which provides a relatively high refractive index. However, in some embodiments it is possible to include a saline solution 306 with a higher refractive index as compared to the oil 307 which in such cases provides a relatively lower refractive index.

An adhesive 308 may be used to secure the front curve lens 301 and back curve lens 302 in place proximate to each other thereby retaining the oil 307 and saline solution 306 therebetween. The adhesive 308 acts as a seal so that there is no leakage of saline 306 or oil 307 from the curved liquid meniscus lens 300.

Referring now to Fig. 4, a curved liquid meniscus lens 400 is illustrated with a liquid meniscus boundary 401 between the saline solution 406 and oil 407. According to some preferred embodiments, a meniscus wall 405 is defined in the front curve lens 404 by a first angular break in an arcuate wall extending between 402 and 403. The liquid meniscus boundary 401 will move up and down the meniscus wall 405 as charge is applied and removed along one or more conductive coatings or conductive materials 408.

In some preferred embodiments, a conductive coating 403 will extend from an area internal to the cavity 409 holding the saline solution 406 and the oil 407 to an area external to the cavity 409 containing the saline solution 406 and oil 407. In such embodiments, the conductive coating 403 may be a conduit of an electrical charge applied to the conductive coating 403 at a point external to the cavity 409 to an area of the conductive coating within the cavity and in contact with the saline solution 406.

Referring now to Fig. 5, a cut away view of an edge portion of an arcuate liquid meniscus lens 500 is shown with a front curve lens 501 and a back curve lens 502. The arcuate

liquid meniscus lens 500 may be used to contain saline solution 503 and oil 504. The geometry of the arcuate liquid meniscus lens 500 and the characteristics of the saline solution 503 and oil 504 facilitate formation of a liquid meniscus boundary 505 between the saline solution 503 and oil 504.

5 Generally, a liquid meniscus lens may be viewed as a capacitor with one or more of: conductive coatings, insulator coatings, pathways, and materials are present on or through the front curve lens 501 and back curve lens 502. According to the present invention, a shape of a liquid meniscus boundary 505 and therefore a contact angle between the liquid meniscus boundary 505 and the front curve lens 501 change in response to an electrical potential applied
10 to a surface of at least a portion of one or both of the front curve lens 501 and the back curve lens 502.

 According to the present invention, a change in an electrical potential applied to the saline solution via the conductive coatings or materials changes a position of the liquid meniscus boundary 505 along a meniscus wall 506. The movement takes place between a first
15 sharp 506-1 and a second sharp 506-2.

 In preferred embodiments, the liquid meniscus boundary 505 will be at or near the first sharp 506-1 when a first magnitude of electrical potential is applied to the lens, such as, for example, a voltage and current correlating with an unpowered state or resting state.

 Application of a second magnitude of electrical potential, sometimes referred to as a first
20 powered state, may correlate with a movement of the liquid meniscus boundary 505 along the meniscus wall 506 generally in the direction of the second sharp 506-2, causing the shape of the liquid meniscus boundary to change. As discussed further below, according to the present invention, each of multiple sharps included along a meniscus wall may be associated with respective powered states.

25 An applied voltage for transitioning between a first powered state and a second powered state may include, for example, a direct current voltage of between about 5 volts to about 60 volts. In other embodiments an alternating current voltage may also be utilized.

 In some embodiments, the meniscus wall 506 will be a smooth surface in relation to the thickness of the insulator coating. A smooth meniscus wall 506 surface may minimize defects

in the insulator coating. Additionally, because random irregularities in surface texture may result in uneven fluid motion and therefore cause uneven or unpredictable meniscus motion when energizing or de-energizing the lens, a smooth meniscus wall 506 is preferred. In some preferred embodiments, a smooth meniscus wall includes a peak to valley measurement along the meniscus wall 506 in the range of between about 1.25 nanometers to 5.00 nanometers.

In another aspect, in some embodiments, it is desirable for the meniscus wall 506 to be hydrophobic, in which case a defined texture, such as a nano-textured surface, may be incorporated in the design of the arcuate liquid meniscus lens.

In still another aspect, in some embodiments, the meniscus wall 506 may be angled relative to an optical axis of the lens. The angle can range from 0° , or parallel to the optical axis, to at or near 90° , or perpendicular to the optical axis. As illustrated, and in some preferred embodiments, the meniscus wall 506 angle is generally between about 30° and 50° in order for the arcuate liquid meniscus lens to function given the current contact angle between the liquid meniscus boundary 505 and the insulator-coated meniscus wall 506. With the use of different materials or with different optical objectives, such as telescopic vision, the angle of the meniscus wall 506 may be closer to 0° or 90° .

According to the present invention, an angle of a meniscus wall 506 may be designed to accommodate a magnitude of movement along a meniscus wall 506 upon application of a specified electrical voltage. In some embodiments, as meniscus wall 506 angle increases, the ability to change lens power generally decreases within given lens size and voltage parameters. Additionally, if the meniscus wall 506 is at or near 0° relative to the optical axis, the liquid meniscus boundary 505 will be steered nearly straight onto the front optic. Meniscus wall angle is one of several parameters that can be tailored to provide various outcomes in lens performance.

In some preferred embodiments, the meniscus wall 506 is approximately 0.265 mm in length. However, the angle of the meniscus wall 506 together with the size of the overall lens will naturally affect meniscus wall 506 length in various designs.

It may generally be considered that an arcuate liquid meniscus lens 500 will fail if the oil 504 contacts the back curve lens 502. Therefore, in preferred embodiments, the meniscus wall 506 is designed to allow a minimum clearance of 50 microns between the first sharp 506-1 and the back curve lens 502 at its nearest point. In other embodiments, the minimum clearance may

be less than 50 microns, although the risk of lens failure increases as the clearance is reduced. In yet other embodiments, the clearance may be increased to mitigate the risk of lens failure, but the overall lens thickness will also increase which may be undesirable.

In still another aspect of some preferred embodiments of the present invention, the behavior of a liquid meniscus boundary 505 as it travels along a meniscus wall 506 may be extrapolated using Young's Equation. Although Young's Equation defines the balance of forces caused by a wet drop on a dry surface and assumes a perfectly flat surface, the fundamental properties can be applied to the electrowetted lens environment created within the arcuate liquid meniscus lens 500.

A first magnitude of electrical energy may be applied to the lens, such as, for example, when the lens is in an unpowered state. During the application of the first magnitude of electrical energy, a balance of interfacial energies between the oil 504 and saline solution 503 is achieved. Such a state may be referred to herein as a liquid meniscus boundary 505. The oil 504 and meniscus wall 506, and the saline solution 503 and meniscus wall 506, form an equilibrium contact angle between the liquid meniscus boundary 505 and the meniscus wall 506. When a change in magnitude of voltage is applied to the arcuate liquid meniscus lens 500, the balance of interfacial energies will change, resulting in a corresponding change in contact angle between the liquid meniscus boundary 505 and the meniscus wall 506.

The contact angle of the liquid meniscus boundary 505 with the insulator-coated meniscus wall 506 is an important element in the design and function of the arcuate liquid meniscus lens 500 not only due to its role in the Young's Equation in movement of the liquid meniscus boundary 505, but also because the contact angle is used in conjunction with other features of the arcuate liquid meniscus lens 500 to limit meniscus movement.

Discontinuities, such as sharps 506-1 and 506-2, at both ends of the meniscus wall 506 act as boundaries for liquid meniscus 505 movement because it would require a significant change in voltage to effect a large enough change in liquid meniscus contact angle to move the liquid meniscus boundary 505 past one of the sharps. By way of non-limiting example, in some embodiments, a contact angle of the liquid meniscus boundary 505 with the meniscus wall 506 is in the range of 15 to 40° whereas the contact angle of the liquid meniscus boundary 505 with the step 507 below the second sharp 506-2 is perhaps in the range of 90 to 130° and in some preferred embodiments about 110°.

A voltage may be applied to the lens, resulting in movement of the liquid meniscus boundary 505 along the meniscus wall 506 toward the second sharp 506-2. The natural contact angle of the liquid meniscus boundary 505 with the insulator-coated meniscus wall 506 will cause the liquid meniscus boundary 505 to stop at the second sharp 506-2 unless significantly
5 more voltage is supplied.

At one end of the meniscus wall 506, a first sharp 506-1 generally defines one limit beyond which the liquid meniscus boundary 505 will not typically move. In some embodiments, the first sharp 506-1 is constructed as a sharp edge. In other preferred
10 embodiments, the first sharp 506-1 has a defined small radial surface which can be created with less possibility of defect. Conductive, insulator, and other possible desired coatings may not deposit evenly and predictably on a sharp edge, whereas a defined radius edge of the radial surface can be coated more reliably.

In some embodiments, the first sharp 506-1 is constructed at about a 90° angle with a defined radius of about 10 microns. The sharp may also be created with less than a 90° angle.

15 In some embodiments, a sharp with a larger angle than 90° may be used to increase the sturdiness of the sharp, but the design would then take up more lens space.

In various embodiments, a defined radius of a sharp 506-1 506-2 may be in the range of 5 microns to 50 microns. A larger defined radius may be used to improve the reliability of the coatings, but at the cost of using more space within the tight confines of the lens design. In this,
20 as in many other areas of lens design, tradeoffs exist between ease of construction, optimization of lens functions, and minimizing size. A functional, reliable arcuate liquid meniscus lens 500 may be made using a wide range of variables.

In some embodiments, a larger sharp radius may be used in conjunction with an improved surface finish on a side-wall between two adjacent sharps. In some embodiments, it
25 may be desirable that a surface from a first radius (sharp) to a second radius (sharp) be smooth and without discontinuities wherein it is helpful to cut a mold used to fashion a sharp with the same tool. Radii included in a sharp may be cut into a mold tool surface, wherein the mold tool surface radius is larger than the sharp radius. Wherein the mold tool surface is a continuous surface including one or more sharps and a side wall. A larger tool radius may generally relate
30 to a smoother surface finish of a corresponding cut.

A second sharp 506-2, includes a feature designed to limit oil movement when voltage is applied to the arcuate liquid meniscus lens 500. The second sharp 506-2 may also include, in some embodiments a generally pointed end, or in other embodiments, the second sharp 506-2 may include a defined radius of between 5 and 25 microns, most preferred 10 microns. A 10 micron radius performs well as a sharp and can be created using single point diamond turning lathe or injection molding processes.

A vertical, or nearly vertical step 507, extending to a start of the optical area 508 of the front curve lens 501 may be included on a side of the second sharp 506-2 opposing the meniscus wall 506. In some embodiments, the step 507 is 120 microns in height, although it could be in the range of 50 to 200 microns.

In some embodiments, the step 507 may be angled at about 5° from optical axis. In other embodiments, the step 507 angle may be as little as 1° or 2° or may be angled more than 5° . A step 507 that is less angled from optical axis will generally act as a more effective limiter of meniscus movement because it would require a greater change in the contact angle of the liquid meniscus boundary 505 to move off of the meniscus wall 506 and onto the step 507. The transition from the step 507 to the start of the optical area 508 is a 25 micron radius. A larger radius would unnecessarily consume more space within the lens design. A smaller radius is possible and may be implemented if necessary to gain space. The decision to use a defined radius rather than a theoretical sharp in this area as well as others in the lens is based, in part, on the potential move to an injection molding process for lens elements. A curve between the step 507 and the start of the optical area 508 will improve plastic flow during the injection molding process and result in a lens with optimal strength and stress-handling characteristics.

Referring now to Fig. 6, a top down sectional view depicts a meniscus wall 601 with variable voltage zones around the circumference of the meniscus wall 601. According to the present invention, cylinder power, axis and optical power features necessary to correct astigmatism may be produced in a liquid meniscus lens with variable voltage zones around the circumference of a meniscus wall 601. Voltage zones are formed when small gaps 603 are intentionally created or included in a conductive coating 602. Gaps 603 may be formed by a number of techniques such as, by way of non-limiting example, laser milling the gaps 603 after a conductive coating 602 is applied, photomasking prior to applying the conductive coating 602 such that conductive material is not applied in gap 603 areas, and using conductive ink to pad

print a conductive coating 602 only on specific areas. Voltage zones comprised of the conductive coating 602 and gaps 603 extend radially from the meniscus wall to the outer rim of the front curve lens. Electrical connections from a lens driver to voltage zones around the rim of the front curve lens support application of varying magnitudes of electrical potential to different zones. The exemplary lens depicted in Fig. 6 includes two low voltage zones 604 and two high voltage zones 606, separated by four medium voltage zones 605. Fig. 6 is intended to emphasize the voltage zones created by gaps 603 in the conductive coating 602 and is therefore not to scale. The dielectric coating which would be deposited over the conductive coating 602 is not depicted in Fig. 6.

Referring now to Fig. 7, a top down orthogonal view shows a meniscus wall 701 with a first sharp 702, a second sharp 703, and an optical area 708. A position of a liquid meniscus boundary 704 is illustrated when magnitudes of electrical potential have been applied, such as, for example, in a powered state. In high voltage zones 705 where a relatively greater amount of electrical potential has been applied, the liquid meniscus boundary 704 is found generally at or nearest the second sharp 703. The liquid meniscus boundary 704 transitions to a position on the meniscus wall 701 generally mid-way along the wall in medium voltage zones 706. Low voltage zones 707 in which a relatively lesser amount of electrical potential has been applied result in the liquid meniscus boundary 704 positioned relatively closer to the first sharp 702.

When a magnitude of electrical potential is applied to the lens, a saline solution is more strongly attracted to the meniscus wall 701 in areas of stronger electrical potential relative to areas of weaker electrical potential, where attraction of saline solution to the meniscus wall 701 is weaker. In some preferred embodiments, saline solution strongly attracted to a meniscus wall 701 along one axis, such as, for example, an x axis in Fig. 7, and relatively weakly attracted to the meniscus wall 701 along a second perpendicular axis, such as, for example, a y axis in Fig. 7, will cause the liquid meniscus boundary to move and the oil within the meniscus cavity to assume a generally toric shape capable of correcting astigmatism.

The magnitude of electrical potential applied to minimum and maximum voltage zones and the axes at which the minimum and maximum zones are implemented on a meniscus wall 701 within an arcuate liquid meniscus lens may be varied to achieve unique cylinder power and axis combinations for correction of astigmatism. The cylinder power for an astigmatic lens is determined by the magnitude of minimum and maximum electrical potentials applied to voltage

zones along opposing axes around the circumference of a meniscus wall 701. The axis parameter required for astigmatism correction is controlled by the location of minimum and maximum voltage zones on a meniscus wall 701, indicated in Fig. 7 by points 707 and points 705 respectively. A liquid meniscus lens with variable voltage zones around the circumference of the meniscus wall may be designed with various methods of lens stabilization to maintain the correct orientation of the lens axis on the eye for astigmatic correction. Stabilization may be achieved using techniques such as ballasting or more advanced accelerated stabilization designs. The stabilization techniques may be implemented within the arcuate liquid meniscus lens or in a lens that encapsulates the arcuate liquid meniscus lens. Additionally, the orientation of the lens may be dynamically assessed and adjusted, *in situ*, based upon the output of sensing mechanisms on or proximate to the liquid meniscus lens.

Referring now to Fig. 8, a cut away view of an edge portion of an arcuate liquid meniscus lens 800 is shown including a front curve lens 801, a back curve lens 802, saline solution 803, and oil 804. A liquid meniscus boundary 805 is found between the saline solution 803 and oil 804, contacting the front curve lens 801 along a meniscus wall 806. When a first magnitude of electrical energy is applied, such as, for example, an unpowered state or a rest state, the liquid meniscus boundary 805 contacts the meniscus wall 806 at or near a first sharp 807. Application of greater magnitudes of electrical energy, such as, for example, a powered state, cause the liquid meniscus boundary 805 to move and contact the meniscus wall 806 at different points, such as a low voltage point 808, a medium voltage point 809, and a high voltage point 810.

Referring now to Fig. 9, a top down orthogonal view shows an exemplary embodiment with thirty-six (36) voltage zones around the circumference of a meniscus wall 901. The figure includes the meniscus wall 901, a first sharp 902, a second sharp 903, an optical area 904, and thirty-six voltage zones 905. Numbers around the outside of the figure designate axis for the astigmatic lens. The voltage zones, 905-1 through 905-10, indicate an embodiment wherein ten different voltages may be implemented within the thirty-six zones 905. In this exemplary embodiment, zone 905-1 along a ninety degree (90°) axis represents the lowest voltage zones; zones 905-2 through 905-9 have increasing voltages; and zones 905-10 along a one-hundred eighty degree (180°) axis receive the highest voltage. This embodiment supports ten degree

increments of axis correction, although other embodiments may be envisioned with more voltage zones, allowing for more precise astigmatism correction, or with fewer zones.

While the preceding discussion has indicated the correction of astigmatism, it will be apparent to those of skill in the art that other corrections of optical aberrations may be achieved according to the present invention, for example, prism, trefoil, quadrafoil, secondary astigmatism, or other well-defined “higher order” optical aberrations or others not presently described by Zernike polynomials or other analytical treatments.

In the present embodiment, the meniscus wall upon which the variable voltage zones are found generally forms the shape of a conical frustum, a cross section of which shows the meniscus wall to be linear. Examples of a lens including a linear meniscus wall are described in the U.S. Patent Application Serial Number 61,359,548, filed June 29, 2010 and entitled “LENS WITH CONICAL FRUSTUM MENISCUS WALL”.

In some embodiments, variable voltage zones may be included on meniscus walls of varying shapes and designs, such as by way of non-limiting example, a convex torus-segment meniscus wall, a concave torus-segment meniscus wall, a compound linear-convex meniscus wall, a multi-convex meniscus wall, a multi-concave meniscus wall, a multi-segmented linear meniscus wall, and a wall with microchannels.

While the invention has been described with reference to particular embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the scope of the invention.

Therefore, it is intended that the invention not be limited to the particular embodiments disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope and spirit of the appended claims.

Claims

1. An optical lens comprising:
 - a front lens comprising a front lens exterior surface and a front lens interior
5 surface;
 - a back lens comprising a back lens interior surface and a back lens exterior
surface, said back lens positioned proximate to said front lens such that said front lens
interior surface and said back lens interior surface form a cavity therebetween;
 - a volume of saline solution and oil contained within the cavity formed between
10 said front lens interior surface and said back lens interior surface, said volume of saline
solution and oil comprising a meniscus therebetween; and
 - a meniscus wall formed on an area of the interior surface of the front lens, the
meniscus wall comprising a general shape of a conical frustum with multiple voltage
zones formed in one or both of the front lens and back lens and bordering the meniscus
15 formed between the saline solution and oil, wherein at least two of the voltage zones
are capable of receiving a different applied voltage.
2. The optical lens of claim 1 wherein at least one of the front lens and the back
lens is essentially flat.
20
3. The optical lens of claim 1 wherein the front lens and the back lens comprise an
arcuate lens.
4. The optical lens of claim 3 additionally comprising a conductive coating on at
25 least a portion of said meniscus wall.
5. The optical lens of claim 4 wherein the volume of oil is less than the volume of
saline solution contained within the cavity.
- 30 6. The optical lens of claim 5 wherein the volume of oil comprises about 66% or
more by volume as compared to an amount of saline solution.
7. The optical lens of claim 5 wherein the volume of oil comprises about 90% or
less by volume as compared to an amount of saline solution.

35

8. The optical lens of claim 4 wherein the volume of oil comprises a density about equal to a density of the saline solution.
9. The optical lens of claim 4 wherein the volume of oil comprises density within
5 about 10% of a density of the saline solution.
10. The optical lens of claim 4 wherein the volume of oil comprises density within about 5% of a density of the saline solution.
- 10 11. The optical lens of claim 4 wherein the conductive coating extends from an area interior to the cavity to an area external to the cavity.
12. The optical lens of claim 11, wherein the area of conductive coating external to the cavity forms an electrical terminal for providing an electrical potential to the liquid
15 meniscus lens.
13. The optical lens of claim 11 wherein the saline solution and the oil form a meniscus and an application of an electrical potential to the area of conductive coating external to the cavity causes a change in position of contact of the meniscus along the
20 meniscus wall.
14. The optical lens of claim 13 wherein the electrical potential is applied using direct current.
- 25 15. The optical lens of claim 13 wherein the electrical potential comprises between about 5.0 volts to 60.0 volts.
16. The optical lens of claim 15 wherein the electrical potential comprises about 20.0 volts.
30
17. The optical lens of claim 15 wherein the electrical potential comprises about 5.0 volts.
18. The optical lens of claim 13 wherein the electrical potential comprises between
35 about 3.5 volts to about 7.5 volts.

19. The optical lens of claim 5 wherein the front curve lens exterior surface comprises an optical power other than about 0.
20. The optical lens of claim 5 wherein the front curve lens interior surface
5 comprises an optical power other than about 0.
21. The optical lens of claim 5 wherein the back curve lens exterior surface comprises an optical power other than about 0.
- 10 22. The optical lens of claim 5 wherein the back curve lens interior surface comprises an optical power other than about 0.
23. The optical lens of claim 5 additionally comprising a channel through one or both of the front curve lens and the back curve lens and a conductive material filling the
15 channel.
24. The optical lens of claim 23 additionally comprising a terminal in electrical communication with the conductive material filling the channel.
- 20 25. The optical lens of claim 24 wherein application of an electrical potential to the terminal causes a change in the shape of the meniscus.
26. The optical lens of claim 5 additionally comprising an insulator coating along at least a portion of the interior surface of the front curve lens, wherein the insulator
25 coating comprises an electrical insulator.
27. The optical lens of claim 26, wherein the insulator comprises one of Parylene C™ and Teflon AF.
- 30 28. The optical lens of claim 26 wherein the insulator comprises a boundary area to maintain separation between the conductive coating and a saline solution contained in the cavity between the front curve lens and the back curve lens.
29. The optical lens of claim 5 wherein an angle of the conical frustum comprising
35 the meniscus wall comprises between about 30° and 50°.

30. The optical lens of claim 29 additionally comprising a meniscus sharp adjacent to the meniscus wall, said sharp comprising an angular feature for containing the volume of saline solution and oil.
- 5 31. The optical lens of claim 29 wherein the sharp comprises a radial surface portion.
32. The optical lens of claim 30 wherein the radial surface portion comprises a radius in the range of 5 microns to 50 microns.