6 November 2003

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : H04L 27/26 — A2

(11) International Publication Number: **WO 00/49782**

(43) International Publication Date: 24 August 2000 (24.08.00)

(21) International Application Number: PCT/US00/04062

(22) International Filing Date: 17 February 2000 (17.02.00)

(30) Priority Data:
09/252,959 18 February 1999 (18.02.99) US

(71) Applicant: USA DIGITAL RADIO, INC. [US/US]; Suite 202, 8865 Stanford Boulevard, Columbia, MD 21045 (US).

(72) Inventors: PEYLA, Paul, James; 6528 Meadowfield Court, Elkridge, MD 21075 (US). BRONDER, Joseph, Bertram; 10150 Vantage Point Court, New Market, MD 21774 (US).

(74) Agent: LENART, Robert, P.; Eckert Seamans Cherin & Mellott, LLC, 44th floor, 600 Grant Street, Pittsburgh, PA 15219 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
Without international search report and to be republished upon receipt of that report.

162162

(54) Title: A SYSTEM AND METHOD FOR RECOVERING SYMBOL TIMING OFFSET AND CARRIER FREQUENCY ERROR IN AN OFDM DIGITAL AUDIO BROADCAST SYSTEM

G00001



(57) Abstract

The system for recovering symbol timing offset and carrier frequency error from an orthogonal frequency division multiplexed (OFDM) signal includes a receiver circuit for receiving an OFDM modulated signal representing a series of OFDM symbols, and providing a received signal to an output thereof. A peak development circuit is included for developing a signal having a plurality of signal peaks representing symbol boundary positions for each received OFDM symbol, where each of the signal peaks is developed responsive to an amplitude and phase correspondence produced between the leading and trailing portions of each of the received OFDM symbols. The system includes a circuit for enhancing the signal peak detectability, which includes a circuit for additively superimposing and then filtering the signal peaks, to produce an enhanced signal peak having an improved signal-to-noise ratio. A circuit for establishing a temporal position indicative of the symbol boundary position from at least one of the enhance signal peaks output from the signal enhancing module is also provided. Further, a circuit for recovering the received OFDM signal carrier frequency error corresponding to the temporal position is included.