

Fall arrest safety net

Technical field

The present invention relates to a safety net having an attachment device for securing to a construction element particularly for use as a fall arrest apparatus.

5 **Background of the Invention**

When working at elevated positions, in order to protect anyone below the working position, a safety apparatus should be provided to arrest a fall of debris. Typically a safety net may be suspended just below the working height and fastened, for example, to free standing columns or to end-securing fixtures mounted to a wall.

- 10 However for permanent fall arrest protection, for instance in engineering facilities having overhead fittings, maintaining a suspended safety net to span the entire overhead area may not be appropriate due to the construction of the facility, the working height, the obstruction it would cause, or its cost. There is therefore a need for an improved safety apparatus which addresses these drawbacks, is relatively
15 inexpensive to manufacture and easy to install. It is an object of the present invention to address this need or, more generally, to provide an improved safety net.

Disclosure of the Invention

- According to one aspect of the present invention there is provided a safety net assembly for securing an overhead fitting connected to an electrical cable, said
20 assembly comprising: a bag constructed of wire mesh, the bag having an open mouth and a closed end, the bag including a plurality of eyes integral with the wire mesh and spaced circumferentially about the mouth;

- a slit in the wire mesh extending from the open mouth toward the closed end and adapted for receiving the electrical cable, the slit disconnecting a plurality of adjacent
25 wire loops of the mesh;

an elongate line having opposing first and second ends, first and second line portions of the line being disposed adjacent the first and second ends respectively, an intermediate portion of the line located between the first and second line portions, and

a choker fitting having two faces; a plurality openings in the choker fitting which extend
5 between the two faces, an end-securing fixture on the choker fitting, the first portion of the line extending through the eyes for drawing the mouth closed, and wherein either:

(a) the first portion of the line is connected in a ring by the choker fitting with the first end is fixed to the end-securing fixture, and the intermediate portion extends through at least one of the openings in the choker fitting, or

10 (b) a fastener is fixed to the first end of the line for connecting the first end to the end-securing fixture and the intermediate portion extends through at least two of the openings in the choker fitting.

The first portion of the line provides an elongate flexible member, and while the first portion of the line may be continuous, it may alternatively be interrupted by fasteners,
15 links, or the like, connected to adjacent ends of the line and which can be separated so that the ring may be broken as needed in some installations of the net (which are discussed below).

Preferably the intermediate portion extends through the openings in the choker fitting so that a loop in the line protrudes from each of the faces of the choker fitting, each
20 loop spanning between two of the openings. It will be apparent that two openings will be sufficient for connection in this manner, however most preferably the openings include three openings through which the line passes sequentially, the loops being connected through one of the openings. Once the line is tensioned to reduce the size

of the one or more loops this connection serves to effectively lock the line with respect to the choker, while still allowing it to be released by manipulating the line back through the openings.

Preferably the line further comprises a terminal eye formed on the second end of the
5 line. The assembly preferably further comprises a hook fastener received in the terminal eye.

Preferably the two faces of the choker fitting comprise opposing faces of a planar part of the choker fitting, the end-securing fixture comprising a line-receiving aperture having an axis disposed in the plane of the planar part and the first end of the line
10 includes an end-securing fixture thereon, whereby the first portion is received in the line-receiving aperture and the end-securing fixture is sized so as not to pass through the line-receiving aperture.

Preferably the wire mesh bag is formed from a length of wire with fastenings joining portions of the length of wire, the length of wire extending from the closed end toward
15 the mouth and being turned back upon itself to form the eyes at the mouth and corresponding eyes at the closed end, each eye at the mouth being fixed by a respective one of said fastenings to the adjacent eye on either side thereof, and each eye at the closed end being fixed by a respective one of said fastenings to the adjacent eye on either side thereof to form the bag.

20 The fastenings that join two portions of the length of wire and are preferably all of like type, most preferably being ferrules which are crimped or moulded in place.

Preferably the fastenings joining the eyes at the closed end are more closely spaced along the length of wire than the fastenings joining the eyes at the mouth.

In still another aspect the invention provides a method of securing apparatus mounted overhead upon a construction member, the method comprising:

providing a safety net assembly substantially as described above;

introducing the apparatus through the mouth so as to at least partially enclose the
5 apparatus in the wire mesh bag;

manipulating the choker fitting and line to close the mouth;

looping the second portion about the construction member, and

connecting the first portion and the second end by means of a hook fastener.

This invention provides a safety net assembly which is effective and efficient in
10 operational use, providing for ready installation and removal as needed. The net has an overall simple design which minimizes manufacturing costs and maximizes performance. A fall arrest net can be required to absorb significant energy in use, and it has been found that this design offers an ability to spread impact loads. In particular, it is believed that the loops formed about the mouth of the bag provide a
15 degree of movement and avoid highly localised loading stress raisers.

Brief Description of the Drawings

Preferred forms of the present invention will now be described by way of example with reference to the accompanying drawings, wherein:

Fig. 1 is pictorial view of a first exemplary embodiment of the fall arrest safety net assembly of the invention in a collapsed state ready to receive an item of value;

Fig. 2 is a plan view of a web of mesh from which the fall arrest safety net assembly Fig. 1 is formed;

5 Fig. 3 is a plan view of the fall arrest safety net assembly of Fig. 1;

Figs. 4, 5 and 6 are orthogonal end, front and side views respectively of the choker fitting of the fall arrest safety net assembly of Fig. 1;

Fig. 7 is an exploded pictorial view of a second exemplary embodiment of the fall arrest safety net assembly of the invention;

10 Fig. 8 is an exploded pictorial view of a third exemplary embodiment of the fall arrest safety net assembly of the invention;

Fig. 9 is schematic pictorial view of a fourth exemplary embodiment of the fall arrest safety net of the invention, and

Fig. 10 is schematic view of an alternative embodiment of the fall arrest safety net assembly of the invention installed in use.
15

Description of the Preferred Embodiments

Referring to Fig. 1 and 2 of the drawings, a first embodiment of a safety net assembly includes a bag 1 having a narrow closed end 2 and a broader opposing
20 open mouth 3 in which an opening 4 is provided for receiving an apparatus to be secured, such as a light fitting 50 (shown in Fig. 7) mounted overhead on a member

such as a beam 51. A line 33 passes in a ring through the eyes 12 of the mouth 3 and cooperates with a choker fitting 52 to draw together the eyes 12 to close the opening 4. An end of the line 33 is looped around the beam 51 to secure the assembly in place.

5 In the first embodiment illustrated the mesh may be made from a length of wire 5 which may be continuous (i.e. a single length) or discontinuous (for instance, including end-to-end joints) and which provides a degree of flexibility and resilience to the bag 1, allowing it to be expanded in a direction transverse to the lay of the wire so as to accommodate apparatus of varying size, while being readily collapsible.

10 The bag 1 is made from a panel of mesh 10, shown in Fig. 2, which is curved or folded about a longitudinal axis 8; the transversely opposing edges 6, 7 of the mesh 10 are then joined to produce the substantially tapered bag-like form (shown in Fig 1 in its collapsed or relaxed state).

The mesh 10 is a non-woven type in which portions of the length of wire 5 are joined
15 by fastenings in the form of ferrules 9a, 9b, 9c, 9d at nodes of the mesh. The length of wire 5 extends generally longitudinally and is turned back upon itself and joined by ferrules 9c to form eyes 11 at the first edge 23 of the mesh 10, and by ferrules 9d to form the eyes 12 at the longitudinally opposing second edge 22 of the mesh 10. Fastenings in the form of ferrules 9b join the adjacent eyes 12 along the second
20 edge 22 and ferrules 9a join the adjacent eyes 11 along the along the first edge 23.

The mesh 10 may be conveniently manufactured by winding the length of wire 5 between pegs 27 spaced apart in two parallel lines, the lines being spaced apart in the longitudinal direction (relative to the mesh 10). The length of wire 5 is wound about the pegs in a zigzag pattern, alternating in direction when it is turned back

upon itself around each peg 27.

To then form the bag 1 from the mesh 10 of Fig. 2, the mesh 10 is removed from the
 pegs 27 curved about the longitudinal axis 8. Portions 14 and 15 of the outermost
 first edge eyes 11 are then joined by a ferrule (not shown) such that each eye 11 is
 5 fixed by a ferrule to the adjacent eye on either side thereof. In like manner the ends
 16, 17 of the length of wire 5 are joined by a ferrule (not shown) such that each eye
 12 along the second edge 22 is fixed by a ferrule to the adjacent eye on either side
 thereof. In addition a further ferrule (not shown) joins portions 18 and 19 on
 opposing transverse edges of the mesh 10 to form the substantially axisymmetrical
 10 bag 1. As best seen in Fig. 3, all the eyes 11 are joined in a first ring 29 to form a
 closed end of the bag 1. All the eyes 12 are joined in a second ring 30 which forms
 the opening 4.

To produce a bag 1 shaped to taper outwardly from the closed end 2 toward the
 open mouth 3, the transverse dimension of the second edge 22 exceeds that of the
 15 first edge 23. To achieve this, the eyes 12 are larger than the eyes 11 and the
 ferrules 9a joining the eyes 11 are spaced more closely apart (by dimension 24
 measured along the length of wire 5) than the ferrules 9b joining the eyes 12 on the
 second edge 22 (which are spaced by dimension 25 measured along the length of
 wire 5).

20 A first embodiment of the choker fitting 52, shown in detail in Figs 4-6, may be formed
 from a substantially rectangular stainless steel sheet having opposing faces 53, 54.
 On one side of the choker fitting 52 is an end-securing fixture 55 which defines a line-
 receiving aperture 63, while on the opposite side are three circular openings 56, 57, 58
 sized to receive the line 33. The opening 57 may be proximate a corner of the sheet,

with the openings 56, 58 spaced at the same radial distance from opening 57 and at the same distance from their respective orthogonal edges 59, 60. Formed in the choker fitting 52, as by a slitting/pressing operation, the end-securing fixture 55 includes integral U-shaped arms 61, 62 projecting either side from faces 53, 54 and
5 thereby spanning and defining the aperture 63. Formed in this manner the aperture 63 has an axis 64 disposed in the plane of the planar member. Adjacent the innermost arm 62 is a through-extending aperture 65 which is substantially D-shaped. On the front face 53 are textual indicia 80 including an "Expiry date" marking 81 located adjacent a blank area 82 where a date can be permanently marked, by engraving,
10 etching, stamping or the like, to notify users of the end of the working life of the product.

The line 33 has a first end 70 adjacent to which a bead-shaped ferrule or like fitting 71 is fixed. The fitting 71 is disposed in the aperture 65, while the first end 70 extends through the line-receiving aperture 63, the end-securing fixture being larger than the
15 aperture 63 so as to thereby fix the first end the choker fitting 52. A second end 72 of the line 33 opposing the first end 70 includes a terminal eye 73 formed as by an eye splice or by a loop fixed by a ferrule, or like fastener.

A first portion 74 of the line 33 adjacent the first terminal end 70 extends from the end-securing fixture 55 in a ring through the eyes 12 for drawing the mouth 3 closed. A
20 second portion 78 of the line 33 extends from the choker fitting 52 to the second end 72.

An intermediate portion 75 of the line 33 is located between the first and second line portions 74, 78, and passes sequentially through the openings 56, 57 and 58 in the choker fitting. As shown in dashed outline in Fig. 6, a first loop 76 of the line extends

through the openings 57, 58 to protrude from of the face 53, while a second like loop 77 extending between openings 56 and 57 protrudes from the opposing face 54.

The line 3 and the length of wire 5 may be twisted stainless steel wire cables for corrosion resistance. Similarly the other components, such as the ferrules 9a, 9b, 9c, 9d and the hook fastener are also formed of stainless steel.

Fig. 7 shows an exploded view of a second embodiment of the safety net assembly, wherein the bag 101 is assembled from a folded main panel 90 and two like end panels 91. The panels 90, 91 are each formed of a flexible wire mesh, and may each be formed initially each from a respective single length of wire joined at nodes of the mesh by ferrules, or moulded beads etc. The main panel 90 is a rectangular panel folded in a curve and includes rows of eyes 92, 93 along longitudinally opposite transverse edges which, when the panel 90 is folded in a curve as shown are brought together to form opposing sides of the mouth 4, the curved central section of panel 90 forming the closed end 2. The panels 91 have a row of eyes 94 along one edge and are shaped with an arcuate opposing edge complementary to the form of the panel 90. Each end panels 90 is fixed about its peripheral edge, as by ferules or the like, to a long edge of the panel 91, such that the rows of eyes 92, 93, 94 are generally coplanar, the eyes being spaced about the periphery of the mouth 4.

The line 133 and choker 152 shown in Fig. 7 are generally like that of the first embodiment, but with a differing connection between the terminal end 70 of first line portion 74 and the choker 152. A fastener 120, such as a hook fastener, or carabiner with a spring-closed gate, is fixed to the end of the first line section 74, as by a permanent eye 164 formed on the end 70. The wire comprising the eye 164

may pass through an aperture formed in the fastener 12, as shown such that the fastener is permanently fixed to the line. A circular aperture 163 extends between the opposing sides of the choker 152. The fastener 120 is received in the aperture 163 which thus provides the end-securing fixture in this embodiment. In like manner
5 to the first embodiment, the line 33 passes from the choker fitting 152 through the eyes 92, 93, 94 and back to the choker fitting 152, for drawing the mouth 3 of the bag 101 closed.

A third embodiment of the invention is shown in Fig. 8 and includes panels 90, 91, 111 each formed from a flexible wire mesh. The panels 111, like the panels 91 the
10 second embodiment, have a row of eyes 94 along one edge and are shaped with an arcuate opposing edge complementary to the form of the panel 90. The panel 111 further includes a slit 112 in the fabric of the mesh (where adjacent wire loops are disconnected). The slit 112 extends longitudinally down from the row of eyes 94 to an intermediate position in the panel. The end panel 111 is otherwise of like
15 construction to the panels 91 and is fixed about its peripheral edge to a long edge of the panel 91, in like manner to the second embodiment. The line 33 and choker 52 of the third embodiment are generally like that of the first embodiment, but the ring-shaped first portion 74 has a fastener 110 connected in the line 33, allowing the ring to be opened and closed. As shown, the fastener 110 may be a carabiner joining
20 permanent eyes formed in the first portion 74.

In a fourth embodiment the net of the invention, shown in Fig. 9, is formed from a single generally rectangular panel of flexible wire mesh. Like the second and third embodiments, a folded central part of the panel forms the closed end 2 and the opposing short edges of the panel bound the periphery of the open mouth 3, the line
25 33 passing from the choker fitting 52 through the eyes 92, 93 and back to the choker

fitting 52, for drawing the mouth 3 closed. The two halves of the long edge on one side of the panel are connected by join line 115. The two halves 116, 117 of the opposing long edge of the panel are not joined, and define a slit 112 extending from the mouth 3 down one side of the bag toward the closed end 2, in like manner to the third embodiment of Fig. 8.

In use, as best seen in Fig. 10, the components of the light fitting 50 are first introduced through the open mouth 3 thereby substantially enclosing the light fitting in the bag 1. By then manipulating the choker fitting to draw the line through the openings 56, 57, 58 the ring-shaped first line portion 74 is reduced in size to close the mouth 3. The second portion 78 of the line 33 is then looped about the construction member 51. A hook fastener 88 (such as a carabiner having a hinged gate and screw closure) is inserted through the terminal eye 73 and through the ring-shaped first line portion 74 to secure the assembly. When the third embodiment is used a member 113 (such as the power cable shown in phantom in Figs. 9 and 10) which protrudes through the bag may be received in the split 112, while still closing the mouth 3. The fastener 110 is positioned proximate the slit 112 and opened to break open the ring and allow entry of the member 113 into the slit 112. By reconnecting the fastener 110, the mouth can then be drawn closed, to the same degree as the second embodiment, substantially enclosing the light fitting 50.

Aspects of the present invention have been described by way of example only and it should be appreciated that modifications and additions may be made thereto without departing from the scope thereof.

CLAIMS:

1. A fall arrest safety net assembly for securing an overhead fitting connected to an electrical cable, said assembly comprising:
 - a bag constructed of wire mesh, the bag having a an open mouth and a closed end, the bag including a plurality of eyes integral with the wire mesh and spaced circumferentially about the mouth;
 - a slit in the wire mesh extending from the open mouth toward the closed end and adapted for receiving the electrical cable, the slit disconnecting a plurality of adjacent wire loops of the mesh;
 - an elongate line having opposing first and second ends, first and second line portions of the line being disposed adjacent the first and second ends respectively, an intermediate portion of the line located between the first and second line portions, and
 - a choker fitting having two faces; a plurality openings in the choker fitting which extend between the two faces, an end-securing fixture on the choker fitting, the first portion of the line extending through the eyes for drawing the mouth closed, and wherein either:
 - (a) the first portion of the line is connected in a ring by the choker fitting with the first end is fixed to the end-securing fixture, and the intermediate portion extends through at least one of the openings in the choker fitting, or
 - (b) a fastener is fixed to the first end of the line for connecting the first end to the end-securing fixture and the intermediate portion extends through at least two of the openings in the choker fitting.
2. The fall arrest safety net assembly of claim 1 wherein the intermediate portion extends through the openings in the choker fitting so that a loop in the line protrudes from each of the faces of the choker fitting.
3. The fall arrest safety net assembly of claim 1 or claim 2 wherein the openings include three openings through which the line passes sequentially so that a

loop in the line protrudes from each of the faces of the choker fitting.

4. The fall arrest safety net assembly of any one of claims 1 to 3 wherein the line further comprises a terminal eye formed on the second end of the line.
5. The fall arrest safety net assembly of claim 4 wherein the assembly further comprises a hook fastener received in the terminal eye.
6. The fall arrest safety net assembly of any one of claims 1 to 5 wherein the two faces of the choker fitting comprise opposing faces of a planar part of the choker fitting, the end-securing fixture comprising a line-receiving aperture having an axis disposed in the plane of the planar part and the first end of the line includes an end-securing fixture thereon, whereby the first portion is received in the line-receiving aperture and the end-securing fixture is sized so as not to pass through the line-receiving aperture.
7. The fall arrest safety net assembly of claim 1 wherein fastening means are provided in the first portion of the line for opening and re-closing the ring.
8. The fall arrest safety net assembly of any one of claims 1 to 6 wherein the wire mesh bag is formed from a length of wire with fastenings joining portions of the length of wire, the length of wire extending from the closed end toward the mouth and being turned back upon itself to form the eyes at the mouth and corresponding eyes at the closed end, each eye at the mouth being fixed by a respective one of said fastenings to the adjacent eye on either side thereof, and each eye at the closed end being fixed by a respective one of said fastenings to the adjacent eye on either side thereof to form the bag.
9. The fall arrest safety net assembly of claim 8 wherein the fastenings joining the eyes at the closed end are more closely spaced along the length of wire than the fastenings joining the eyes at the mouth.
10. The fall arrest safety net assembly of any one of claims 1 to 9 wherein one of the faces of the choker fitting includes a date marking located adjacent a blank area where a date can be permanently marked.
11. The fall arrest safety net assembly of any one of claims 1 to 10 wherein the

wire mesh bag is formed from a rectangular main mesh panel and a pair of end panels, said plurality of eyes including first and second rows of eyes formed in opposing transverse edges of the main panel, opposing longitudinal edges of the main panel extending between the transverse edges, the end panels comprising third and fourth rows of eyes along an edge of each end panel, wherein each end panel is fixed to a respective one of the longitudinal edges of the main panel.

12. A fall arrest safety net assembly for securing an overhead fitting connected to an electrical cable, said assembly comprising:

a bag constructed of wire mesh, the bag having a closed end and an opposing open mouth, the bag includes a plurality of eyes integral with the wire mesh and spaced circumferentially about the mouth, wire mesh bag is formed from a length of wire with fastenings joining portions of the length of wire, the length of wire extending from the closed end toward the mouth and being turned back upon itself to form the eyes at the mouth and corresponding eyes at the closed end, each eye at the mouth being fixed by a respective one of said fastenings to the adjacent eye on either side thereof, and each eye at the closed end being fixed by a respective one of said fastenings to the adjacent eye on either side thereof to form the bag;

a slit in the wire mesh that is adapted for receiving an electrical cable during installation of the safety net assembly, the slit disconnecting adjacent wire loops of the mesh and extending from the open mouth toward the closed end;

an elongate line having opposing first and second ends, first and second line portions of the line being disposed adjacent the first and second ends respectively, an intermediate portion of the line located between the first and second line portions, and

a choker fitting having two faces between which a plurality of openings extend, and an end-securing fixture on the choker fitting, a terminal eye formed on the second end of the line and a hook fastener received in the terminal eye, wherein the first portion of the line is connectable in a ring, the first portion extending through the eyes for drawing the mouth closed, and the intermediate

portion extending through at least one of the openings in the choker fitting.

13. A method of securing apparatus mounted overhead upon a construction member, the method comprising:

5 providing a fall arrest safety net assembly substantially as claimed in any one of claims 1 to 12;

introducing the apparatus through the mouth so as to at least partially enclose the apparatus in the wire mesh bag;

manipulating the choker fitting and line to close the mouth;

looping the second portion about the construction member, and

10 connecting the first portion and the second end by means of a fastener.

14. A fall arrest safety net assembly for securing an overhead fitting connected to an electrical cable, said assembly comprising:

15 a bag constructed of wire mesh, the bag having an open mouth and a closed end, the bag including a plurality of eyes integral with the wire mesh and spaced circumferentially about the mouth;

a slit in the wire mesh extending from the open mouth toward the closed end and adapted for receiving the electrical cable, the slit disconnecting a plurality of adjacent wire loops of the mesh;

20 an elongate line having opposing first and second ends, first and second line portions of the line being disposed adjacent the first and second ends respectively, an intermediate portion of the line located between the first and second line portions, and

25 a choker fitting having two faces between which at least one opening extends, and an end fixture on the choker fitting, wherein the first portion of the line is connected in a ring by the choker fitting, the first end being fixed to the end fixture, the first portion extending through the eyes for drawing the mouth closed, and the intermediate portion extending through the at least one opening

in the choker fitting.