

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/053367 A3

(51) International Patent Classification⁷: **F16K 51/00**

(21) International Application Number:
PCT/US2003/037735

(22) International Filing Date:
24 November 2003 (24.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/314,728 9 December 2002 (09.12.2002) US

(71) Applicant: **ADVANCED TECHNOLOGY MATERIALS, INC.** [US/US]; Margaret Chappuis, 7 Commerce Drive, Danbury, CT 06810 (US).

(72) Inventor: **TOM, Glenn**; 2 Powderhorn Lane, New Milford, CT 06776 (US).

(74) Agent: **CHAPPUIS, Margaret**; Advanced Technology Materials, Inc., 7 Commerce Drive, Danbury, CT 06810 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: PERMEABLE GAS ASSEMBLY FOR GAS DELIVERY



(57) Abstract: A valve assembly for controlling gas delivery from a higher pressure fluid source to a lower pressure processing tool comprising a valve poppet movably engageable with a valve seating member and a fluid permeable insert positioned between the valve poppet and the valve seating member that is unexposed to flowing fluid when the valve poppet is in a closed position thereby preventing fluid flow through the valve assembly and provides a diffusional path for transfer of all flowing fluid when the valve poppet is in an open position. The permeable insert can be inserted into the sealable and engageable surface of either the valve seat member or the valve poppet.

WO 2004/053367 A3



(88) Date of publication of the international search report:

9 December 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.