

PROCESS AND APPARATUS FOR PRODUCING BIOETHANOL WITHOUT
CO₂ EMISSIONS BY CONVERSION OF SYNGAS OBTAINED FROM THE
THERMAL CONVERSION OF WASTE AT HIGH TEMPERATURE.

DESCRIPTION

The invention regards the field of processes and apparatuses suitable to convert RDF (Refuse Derived Fuel), MSW (Municipal Solid Waste) and similar materials such as plastic residues into products with
5 higher added value by ensuring eco-compatibility in terms of absence of greenhouse gas emissions, and it specifically consists of a process and apparatus for producing bioethanol without CO₂ emissions by converting syngas obtained from the thermal conversion
10 of waste at high temperature.

State of the art

Global warming is forcing the European Union to actuate a strategy for eliminating greenhouse gas (GHG) emissions in Europe by 2050 by looking for alternatives
15 to the use of natural gas or other hydrocarbons.

The conventional way to dispose of municipal, agricultural and industrial waste through incineration is also one of the main sources of greenhouse gas emissions, mainly CO₂, CH₄ and nitrogen oxides. In
20 contrast, the waste can be used as a source of carbon and hydrogen by converting it into a syngas, a mixture of CO, CO₂ and H₂. The processes for such a conversion are known in the art.

For example, patent WO/2018/066013 describes a
25 gasification process through the use of pure oxygen for the conversion of waste into syngas controlling the temperature along the vertical axis of the reactor.

Patent WO/2018/134853 describes a waste conversion process at high temperature for producing syngas, followed by the purification of the syngas and the regulation of the H_2/CO ratio for the purpose of
5 producing methanol.

In both of the cited examples there is an excess of carbon in the matrix of the feed, with respect to the final product, which leaves the process mainly in the form of CO_2 .

10 The further conversion of syngas into the desired products, in particular ethanol, can be performed through different ways.

Patent US9518237 describes a process for converting a syngas into oxygenated hydrocarbon
15 products through anaerobic bioconversion; said hydrocarbon products are in particular ethanol, acetic acid, n-propanol and n-butanol.

Patent US2019/0078121 describes a different method for improving the CO/H_2 composition of the flow of gas
20 available for supplying a microbial production of oxygenated compound.

Finally, in patent document US2019/0323042, the production of ethanol is obtained through anaerobic fermentation from a CO -rich syngas, but this implies
25 that a fraction of carbon is lost as CO_2 whereas the production of CO_2 can only be reduced or avoided as the amount of available H_2 increases.

Therefore, the need remains for a process and apparatus with zero emissions, for producing chemical
30 substances or biofuels such as ethanol, from the carbon contained in municipal solid waste (MSW), agricultural

waste, or in derivatives thereof such as refuse derived fuel (RDF) and industrial waste such as non-recyclable plastic residues.

Refuse derived fuel (RDF) is a sort of fuel
5 produced after the separation of the organic fraction, metals, paper and plastic.

Furthermore, there is a need for a process and apparatus which has zero emissions, in particular in relation to CO₂ emissions.

10 **Aim of the invention**

The aim of the invention is to overcome the limits of the prior art by providing a process and apparatus which are compatible with the guidelines of the regulations aiming at reducing greenhouse gas emissions
15 in the environment to zero and suitable for the conversion of municipal waste, together with other industrial waste, such as non-recyclable plastics, into bioethanol.

Provided solution

20 The provided solution is a process, and the related apparatus, in which the CO₂ emissions are avoided due to the synergistic effect of a fermentation step and a methanation step, also by considering that it is well known that the gasification of such feed
25 implies a greater production of CO and CO₂, so as to produce a syngas which is enriched with extra hydrogen from electrolytic processes and thus maximizing the biological fermentation process for producing ethanol.

List of figures

30 A better understanding of the invention will be had by means of the following detailed description and

with reference to the accompanying drawings, illustrating a preferred embodiment by way of non-limiting examples.

In the drawings:

5 Figure 1 shows a general conceptual diagram of the invention.

Figure 2 shows a block diagram of a preferred embodiment of the invention with introduction of hydrogen upstream and downstream of the fermenter, and
10 with units for refining the raw ethanol and purifying the recovered water.

Figure 3 shows a block diagram of an alternative embodiment of the invention with introduction of hydrogen completely upstream of the fermenter.

15 Figure 4 shows a detailed diagram of a preferred embodiment with introduction of hydrogen upstream and downstream of the fermenter.

Figure 5 is an alternative embodiment with respect to figure 4 in which hydrogen is only introduced
20 upstream of the fermenter.

Detailed description of the invention

The present invention relates to a process for producing raw bioethanol by means of the fermentation of the syngas produced by the thermal conversion of the
25 feed composed of one or more types of waste.

The invention further describes an apparatus for carrying out the aforementioned process.

The process and apparatus described allow the conversion of waste into biofuel such as, for example,
30 ethanol; said waste comprises Municipal Solid Waste (MSW), agricultural waste or derivatives thereof such

as Refuse Derived Fuel (RFD) or even industrial waste, such as non-recyclable plastic waste.

According to a first feature of the invention, the process exploits the availability of hydrogen, produced
5 by electrolysis, to allow the conversion into ethanol of the carbonaceous elements contained in the gasified waste.

The availability of hydrogen produced by electrolysis further allows to avoid any emission of
10 CO₂ into the atmosphere since any carbonaceous elements not converted during the fermentation step are converted into methane through a methanation reaction by simply adding further hydrogen; the methane thus produced can be sent for distribution or recycled to
15 the gasifier to control the waste conversion temperature.


The process developed originates from the consideration that the syngas produced by the high temperature conversion of municipal solid waste,
20 treated or not, or by the thermal conversion of agricultural or industrial waste, has a H₂/CO ratio by volume equal to about 1.

The optimal H₂/CO ratio required to produce ethanol by fermentation is about 2.0 ÷ 2.2 by volume
25 and thus it is obvious that the thermal conversion of waste, such as the above mentioned, which produces a syngas with a lower ratio value than the optimal one, would result into an excess of carbonaceous components which would come out from the process mainly in the
30 form of carbon dioxide.

According to another feature of the invention, it

has been provided that the process comprises a plurality of high temperature waste converters able to produce the syngas and a plurality of electrolysis cells for producing hydrogen and oxygen.

5 By integrating the syngas produced by the converters with the hydrogen (H₂), produced by electrolysis, it is possible to use almost totally all of the carbonaceous component in the form of CO/CO₂ of the syngas for producing ethanol; furthermore, in order
10 to maximize the CO₂ conversion, thus avoiding releasing it into the atmosphere, it is provided that the residual component, still present in the streams downstream of the fermenter, is converted into synthetic methane through the so-called methanation
15 reaction



Advantageously, said methane can be used in the high temperature conversion of the waste for better control of the process and sent at the battery limits
20 for use outside this process.

The block diagrams of the embodiments described can be seen in figures 4 and 5; alternative embodiments of the invention are however possible without altering the inventive concept underlying the invention.

25 Rather, the embodiments described herein aim to provide a complete and exhaustive disclosure which completely transmits the purpose of the invention to the expert skilled in the art.

Therefore, the present invention relates to an
30 eco-compatible process for producing ethanol from waste, through a step of fermentation of the syngas,

said fermentation being optimized by adding extra hydrogen obtained through electrolysis of water whereas the oxygen of the same electrolysis is used as a comburent within the thermal conversion step, allowing
5 to avoid the emission of CO₂ into the atmosphere.

In a preferred but not limiting embodiment, such a process comprises the following main steps:

- High temperature thermal conversion of the waste with production of raw syngas (100);
- 10 • Production of H₂ and O₂ through electrolysis (102);
- Purification of the raw syngas (101);
- Fermentation (103) of the purified syngas for producing raw bioethanol, after the addition of all or part of the hydrogen produced by electrolysis for
15 achieving the optimal H₂/CO ratio required for the fermentation reactions;
- Partial or total conversion of the residual carbon dioxide present in the purge gas from the fermentation into methane (105);
- 20 • Separation (106) of the produced methane from the unconverted carbon dioxide, and recycling of all or part of the methane recovered and all the CO₂ separated to the high temperature thermal conversion step (100);
- 25 • Purification of the raw bioethanol (104) produced by fermentation;

Said main steps can also include some further secondary steps such as:

- Purification of the water (107) obtained from the
30 purification of the raw bioethanol and recycling of the same water to the electrolysis unit.

The secondary steps described above contribute to the optimization of the process in terms of utility consumptions.

In the preferred embodiment described, the step of
5 high temperature conversion of waste to syngas (100) comprises multiple conversion trains, or reactors; more specifically it was chosen to use a minimum of two, preferably three, thermal conversion trains for converting the feed into syngas.

10 Such a solution allows to correctly manage the maintenance period so as to ensure a certain continuity of use; thereby even when a single train is stopped for maintaining the other two trains, are able to work at a greater capacity, thus ensuring a minimum turndown (75-
15 80%) and continuous and almost constant operation for the steps downstream of the thermal conversion.

Furthermore, the operating choice to perform thermal conversion on multiple trains allows to equalize the composition of the various streams of
20 syngas leaving each gasifier before the subsequent purification step; this implies the possibility to modulate the feed with which each gasifier is supplied in order to obtain a raw syngas that is suitable to be treated in the subsequent purification step, increasing
25 the flexibility of the plant.

For example, a flow rate of waste between 8 and 10 t/h was chosen, which is supplied to each individual thermal conversion line for an overall total of 24-30 t/h of convertible waste.

30 The typical composition of the waste is shown in table 1.

ELEMENT	AVERAGE	COMPOSITION	(BY
	WEIGHT)		
C	38 - 42	%wt, wet basis	
H	5 - 6	%wt, wet basis	
N	0.2 - 1	%wt, wet basis	
S	0.2 - 1	%wt, wet basis	
Cl	0.5 - 1	%wt, wet basis	
O	19 - 22	%wt, wet basis	
HUMIDITY	10 - 16	%wt, wet basis	
ASH	15 - 18	%wt, wet basis	

Table 1

Each thermal converter is supplied with pure
 5 oxygen, produced by the electrolysis process (102), as
 a gasifying agent; moreover, there is provided the
 introduction of a certain aliquot of natural gas (CH₄),
 recycled from the methanation step (105) and subsequent
 separation (106), for the purpose of controlling the
 10 temperature profile inside the reactor.

The stream of CO₂ can also advantageously be used
 for inerting the waste supply system thus preventing
 any syngas losses and any air infiltration; in the
 embodiment described it was chosen to use CO₂ as an
 15 inerting agent which is likely to be available within
 the streams that evolve in the process.

It is however possible to use other alternative
 inert gases to CO₂, such as, for example, nitrogen-rich
 streams, for reaching the same purpose of preventing
 20 any syngas losses and any air infiltrations into the
 waste supply system.

For that purpose, it was chosen to add a further amount of hydrogen so as to allow a certain amount of CO₂ to be present downstream of the methanation step, separating it from the methane produced and recirculating it fully to the thermal conversion step (100) as an inerting agent.

Thereby, by performing the fermentation step (103) and the subsequent methanation step (105) so as not to fully convert CO₂, the unconverted amount of carbon dioxide is kept in circulation within the plant, thus achieving optimization and stabilization of all the processing steps.

Each conversion train consists of a conversion reactor which operates at almost atmospheric pressure (max 500 mbarg) and which dispenses syngas at a temperature of 1100-1200°C; said syngas is quickly cooled to 90°C through an evaporative quench which fixes the composition of the syngas obtained at high temperature inside the reactor avoiding triggering collateral reactions responsible for the formation of pollutants such as dioxins and furans.

The invention includes, downstream of the thermal conversion unit (100), a purification step which acts at dual pressure (101), comprising multiple units according to the capacity of the plant, the aim of which is to remove particulate, metals, chlorides, ammonia, COS and H₂S.

In the low-pressure area downstream of the quench, the syngas leaving every gasifier is at a pressure approximately to atmospheric pressure, about between 100-500 mbarg at most; said syngas is routed to an acid

wash column operating at pH 1-3; these conditions allow removing any collected particles and metals from the syngas stream.

The syngas outcoming from the three conversion
5 trains at the outlet of the acid columns is collected together and routed to a common alkaline wash column which neutralizes it by increasing the pH above 7 and reducing any corrosion phenomena on the downstream equipment.

10 A further purification step is carried out by means of a wet electrostatic precipitator (WEP) the aim of which is to remove the collected dust and which is possibly followed by a washing with subcooled water in a column with the aim of further reducing the dust and
15 particulate in the syngas.

At the outlet of the low temperature washing section, a gas storage tank allows handling any flow rate and pressure fluctuations in the syngas; according to the invention the pressure at the gasometer is set
20 at about 40 mbarg.

Before entering the high pressure purification section, the syngas is compressed up to 12 barg through a dedicated compression unit; the pressurized syngas is then sent to an adsorbent bed with the aim of remove
25 the residual dust, particulate and heavy metals.

This operation is followed by a catalyst/adsorbent bed allowing the removal of HCl and a hydrolysis reactor allowing the conversion of COS and HCN into H₂S and NH₃, respectively.

30 The synthesis gas leaving from the hydrolysis reactor is sent to an Hg removal bed and to an H₂S

removal system according to known technologies.

In this sense, the removal of H₂S can be carried out either through a system that allows the transformation of the H₂S into elemental sulfur and then removed as sulfur sludge, or through amine washing.

A typical composition of purified syngas is shown in table 2.

The syngas thus purified can be supplied to the ethanol fermentation section (103).

The data shown in table 2 confirm what has already been mentioned in relation to the H₂/CO ratio which is lower than the optimal ratio for the fermentation step.

ELEMENT	AVERAGE COMPOSITION			
H ₂	40	-	38	%mol
CO	42	-	41	%mol
CO ₂	10	-	12	%mol
N	4	-	4.5	%mol
H ₂ O	4	-	4.5	%mol
PRESSURE	9	-	10	Barg
TEMPERATURE	40	-	45	°C

Table 2

According to the invention, the further hydrogen required to obtain an optimal H₂/CO ratio is supplied by an electrolysis step (102) based on several cells, according to the capacity of the plant, suitable for the production of hydrogen and oxygen.

In a preferred but non-limiting embodiment of the

invention, part of the hydrogen produced by electrolysis is added to the syngas upstream of the fermentation step (103) and the remaining part is added downstream of the fermentation unit (103), before the methanation step (105) with the aim of optimizing both steps in terms of volume and operating conditions of the equipment involved; in an alternative embodiment, the stream of hydrogen produced in the electrolysis is fully added before the fermentation step (103) promoting the maximization of the conversion of CO and CO₂ into ethanol.

In both of the solutions described, the oxygen is sent to the conversion trains to carry out the waste conversion (100).

According to the invention the conversion of CO and CO₂ into ethanol is carried out in a fermentation step (103) in which said conversion is carried out in one or more bioreactors containing a bacterial culture dispersed in a liquid nutrient medium.

As is known an organic stream consisting of single carbon atoms (C₁) and thus comprising one or more of the elements CO and CO₂, in combination with H₂, is converted into ethanol at low temperature 30-40°C and low pressure 3-5 barg.

Therefore, according to the invention, the synthesis gas containing CO, CO₂, added with the H₂ incoming from electrolysis, is bubbled inside the liquid nutrient medium; the conversion causes the formation of dispersed ethanol in the nutrient medium in the aqueous phase and the production of a residual gaseous stream containing unreacted components and CO₂

generated by the biological conversion process during fermentation.

The ethanol concentration in the stream outcoming from the fermentation step is comprised in the range
5 between 3-6 %wt and thus it is required a specific step to separate ethanol from the aqueous phase in order to obtain anhydrous ethanol.

In a preferred embodiment the synthesis gas, in addition with part of the hydrogen produced by
10 electrolysis and therefore having an H_2/CO ratio between 2.0 - 2.2 %vol, is converted into raw ethanol and a purge gas.

In an alternative embodiment, the syngas, in addition with all the hydrogen produced by
15 electrolysis, will have an H_2/CO ratio between 5 - 5.2 %vol thus converting CO and CO_2 into ethanol; according to this operating mode, the CO_2 initially contained in the syngas is converted during the fermentation process with a consequent increase in the yield of ethanol and
20 a minimization of the purge gas stream.

The purge gas produced by the fermentation step is further treated in the methanation step (105) in order to convert the CO_2 still present in the gas into methane preventing emissions into the environment.

25 In the preferred embodiment described, the remaining part of the hydrogen produced by electrolysis (102) is added to the stream of purge gas downstream of the fermentation step (103) in order to make the H_2/C_1 optimal for performing the methanation of the amount of
30 CO_2 still present in the purge gas and with the aim to produce synthetic methane; in the alternative

embodiment described in which the hydrogen produced by electrolysis is fully added before the fermentation step, and thus generating a minimum amount of purge gas, the remaining amount of residue H_2 in the outcoming stream of purge gas at the outlet of the fermenter is sufficient for carrying out the methanation of residual CO and CO_2 without any further addition of fresh H_2 .

According to the invention the methane produced in step 105 is separated from any CO_2 unreacted in step 106, for the purpose of avoiding any emissions of CO_2 into the atmosphere.

As previously said, part of the methane is recycled to the conversion reactors (100) with the aim to control the temperature profile inside the reactors, while the remaining part is sent to other uses or sold externally.

CO_2 is recycled in part to the methanation step (105) and in part to the thermal conversion step (100) as an inerting agent for the waste supply system; in particular in the alternative embodiment described, where the hydrogen from electrolysis (102) is fully added upstream of the fermenter (103), the amount of CO_2 recovered in the separation step (106) is low and not sufficient for inerting the waste supply system.

Therefore in the alternative embodiment described, in addition to the recovered CO_2 , a nitrogen-rich stream deriving from the known CO_2 separation process is used and which corresponds to a sub-product of the same block 106, as shown in fig. 5.

The liquid phase outcoming from the fermenter,

containing diluted ethanol, can be sent to the raw bioethanol, produced by fermentation, purification step (104) for recovering the product; in general this step typically includes the recovery of the biocatalyst, which is recycled again to the fermenter, and an ethanol recovery and purification step, generally carried out by means of several distillation columns, followed by dehydration through molecular sieve filtration in order to comply with the requirements on the residual water.

Therefore, from the purification unit (104) a stream of anhydrous ethanol and a stream of water containing traces of alcohols produced during the fermentation process as sub-products are obtained; generally, such sub-products consist of butanediol, ethyl acetate and other higher alcohols.

Said aqueous stream produced during the distillation step can be routed to a waste water treatment step (107) such as to allow the recycling of the water purified at the electrolysis step (102).

Furthermore, according to the invention, the stream containing the sub-products consisting of butanediol, ethyl acetate and higher alcohols, and also the excess bacteria introduced into the fermenter (103), can be advantageously sent to the thermal conversion step (100); thereby, there is obtained the dual advantage of not dispersing organic components into the environment and further contributing to controlling the thermal conversion in terms of the composition of the raw syngas produced.

Advantageously, the described process allows

producing bioethanol from waste such as RDF, municipal solid waste, plastic residues and the like without introducing CO₂ into the atmosphere; indeed, the synergistic effect of the fermentation step followed by
5 the methanation step of the purge gas produced during fermentation, allows to reduce, or completely break down, the amount of CO₂ in the outlet stream, thus avoiding introduction into the atmosphere.

As mentioned in the embodiments described, the
10 methanation step does not completely remove CO₂ but preserves a certain amount thereof which is however separated downstream of methanation, thus preventing its introduction into the atmosphere; said recovered CO₂ stream is advantageously used to inert the waste
15 supply system, thus preventing any syngas losses and any air infiltrations which would lead to lower conversion yields of the reactor with subsequent imbalances in the fermentation steps.

Claims

1. A process for producing ethanol by anaerobic fermentation of a synthesis gas, characterized in that:
- said syngas is produced by the thermal conversion at high temperature, above 1000°C, of a feed comprising
5 municipal solid waste (MSW), agricultural waste or derivatives thereof such as refused derived fuel (RDF) or even industrial waste such as non-recyclable plastic waste or a combination thereof, and
 - 10 • further hydrogen is added to said syngas, produced by electrolysis so as to balance the H₂/CO ratio to a value equal to at least 2,0 ÷ 2,2 in volume, thus maximizing the conversion of the organic components in the fermentation step so as to avoid the emission
15 of CO₂ into the atmosphere, and wherein said process comprises the following steps:
 - High temperature conversion of the waste with production of raw syngas (100);
 - 20 • Production of H₂ and O₂ through electrolysis (102);
 - Purification of the raw syngas by a purification unit which acts on two pressure levels (101), the purpose of which is the removal of particulate, metals, chlorides, ammonia, COS, and H₂S (101);
 - 25 • Fermentation of the purified syngas for producing raw bioethanol, after the addition of all or part of the hydrogen produced by electrolysis for achieving the optimal H₂/CO ratio required for the fermentation reactions (103);
 - 30 • Partial or total conversion of the residual carbon

dioxide present in the purge gas outcoming from the fermentation into methane (105);

- Separation (106) of the methane produced by unconverted carbon dioxide, and recycling of all or
5 part of the methane recovered and all the CO₂ separated to the thermal conversion step (100).

2. A process according to the preceding claim characterized in that it further includes a step (104) of purifying the raw ethanol produced by fermentation
10 from which a stream of anhydrous ethanol and an aqueous stream containing alcohols and other organic products exit.

3. A process according to the preceding claim characterized in that it further includes a step of
15 purifying the water (107) obtained in the raw ethanol purification step in order to recycle the recovered water to the electrolysis unit.

4. A process according to one or more of the preceding claims characterized in that the high
20 temperature waste conversion step for the production of raw syngas (100) consists of a plurality of converters, providing at least of two trains thereof, preferably three conversion trains.

5. A process according to one or more of the preceding claims characterized in that the step of
25 purifying the syngas produced (101) consists of a plurality of trains depending on the capacity of the plant.

6. A process according to one or more of the preceding claims characterized in that, in the water
30 electrolysis step, several cells are used depending on

the capacity of the plant.

7. A process according to one or more of claims from 1 to 6 characterized in that the hydrogen produced in the electrolysis step (102) is partially added upstream of the fermentation step, thus shifting the H₂/CO ratio to a value between 2.0 and 2.2 %vol, and the remaining part is added downstream of the fermentation step in order to enable the development of methanation reactions (105), thus optimizing the process in terms of volumes and operating conditions of the fermentation and methanation steps.

8. A process according to one or more of claims from 1 to 6 characterized in that the hydrogen produced in the electrolysis step (102) is fully added upstream of the fermentation step, thus shifting the H₂/CO ratio to a value between 5 and 5.2 %vol, maximizing the conversion process of CO and CO₂ into bioethanol.

9. A process according to one or more of the preceding claims characterized in that the oxygen produced by electrolysis is used as a combustive agent in the conversion step for converting waste into syngas.

10. A process according to one or more of the preceding claims characterized in that the fermentation step (103) is carried out in one or more bioreactors, depending on the capacity of the plant, containing a bacterial culture dispersed in a liquid nutrient medium.

11. A process according to one or more of the preceding claims characterized in that an amount of the methane stream produced during methanation (105) and

exiting from the separation step (106) is recycled to the thermal waste conversion step (100) in order to control the conversion temperature of the feed.

12. A process according to one or more of the preceding claims characterized in that the excess bacteria exiting from the fermentation step (103) and the byproducts consisting of butanediol, ethyl acetate, and superior alcohols exiting from the water purification unit (107), are routed to the converter in order to control the conversion of waste in terms of composition of the syngas produced.

13. A process according to one or more of the preceding claims characterized in that the CO₂ outcoming from the separation process (106) is used individually or in a mixture with other streams, consisting of inert substances and which form byproducts of the same separation step (106), for inerting the waste supply system thus preventing any syngas losses and any air infiltration, and allowing an equalization of the conversion yields.

14. An apparatus for producing ethanol by anaerobic fermentation of a synthesis gas characterized in that it includes the conversion into said ethanol of the syngas produced by the thermal conversion of municipal solid waste (MSW), agricultural waste or derivatives thereof such as refused derived fuel (RFD) or even industrial waste such as non-recyclable plastic waste, wherein said process does not imply any CO₂ emission into the atmosphere as it uses electrolysis for the production of further hydrogen to be added to said syngas so as to balance the H₂/CO ratio, thus

maximizing the conversion of the organic components in the fermentation step,
and wherein

said apparatus comprises the following steps:

- 5 • at least one thermal, high temperature waste conversion unit with the production of raw syngas (100) consisting of a plurality of conversion reactors;
- at least one unit for producing H_2 and O_2 by
10 electrolysis (102) consisting of a plurality of electrolysis cells;
- at least one raw syngas purification unit consisting of a plurality of purification trains (101) acting at double stage pressure, low pressure and high
15 pressure, the purpose of said purification trains (101) being to remove particulate, metals, chlorides, ammonia, COS, and H_2S ;
- at least one unit for the fermentation of the purified syngas, consisting of a plurality of
20 bioreactors, for producing raw bioethanol, upon the addition of all or part of the hydrogen produced by electrolysis for achieving the optimal H_2/CO ratio required for the fermentation reactions (103);
- at least one unit for the partial or total
25 conversion of the residual carbon dioxide present in the purge gas from the fermentation into methane (105);
- at least one separation unit (106) for separating the produced methane from unconverted carbon dioxide
30 and a line for recycling both of the streams to the converter;

- at least one recycling line exiting from the separation step (106) and routed to the thermal conversion step (100) for recycling all or part of the methane, exiting from the separation step, as a temperature control vector in the thermal conversion step;
 - at least one recycling line exiting from the separation step (106) and routed to the thermal conversion step (100) for recycling all of the CO₂, recovered in the separation step, as an inerting agent in the thermal conversion step.
15. An apparatus according to claim 14 characterized in that it further includes at least one purification unit (104) for purifying the raw ethanol produced by fermentation from which a stream of anhydrous ethanol and an aqueous stream containing alcohols and other organic products exit.
16. An apparatus according to claims 14 and 15 characterized in that it further includes at least one water purification unit (107) for the aqueous stream produced in the raw ethanol purification step in order to recycle the recovered water to the electrolysis unit.