

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
3 December 2009 (03.12.2009)

PCT

(10) International Publication Number
WO 2009/146277 A1

(51) International Patent Classification:

C08L 27/18 (2006.01) **C09D 127/18** (2006.01)
C08J 3/12 (2006.01) **C09D 5/03** (2006.01)

(21) International Application Number:

PCT/US2009/044516

(22) International Filing Date:

19 May 2009 (19.05.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/057,597 30 May 2008 (30.05.2008) US
 61/100,311 26 September 2008 (26.09.2008) US
 61/145,433 16 January 2009 (16.01.2009) US
 61/145,875 20 January 2009 (20.01.2009) US

(71) **Applicant** (for all designated States except US): **WHIT-FORD CORPORATION** [US/US]; 47 Park Avenue, Elverson, PA 19520 (US).

(72) Inventors; and

(75) **Inventors/Applicants** (for US only): **HARVEY, Leonard, W.** [US/US]; 18 Spring Meadow Drive, Downingtown, PA 19335 (US). **COATES, Michael** [US/US]; 112 Ironstone Lane, Elverson, PA 19520 (US). **WRIGHT, Julie, K.** [GB/GB]; 31 Kennington Park, Widnes, Cheshire WA8 9PE (GB).

(74) **Agent:** **COX, Adam, F.**; Baker & Daniels LLP, 111 East Wayne Street, Suite 800, Fort Wayne, IN 46802 (US).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- with amended claims and statement (Art. 19(1))

(54) Title: BLENDED FLUOROPOLYMER COMPOSITIONS

(57) **Abstract:** Blended fluoropolymer compositions are provided. In one embodiment, a liquid dispersion of a first fluoropolymer is blended with a liquid dispersion of a second fluoropolymer. The first fluoropolymer may be polytetrafluoroethylene (PTFE), such as a low molecular weight PTFE (LPTFE) that has been polymerized via a dispersion or emulsion polymerization process, and which has not been agglomerated, irradiated, or thermally degraded. The LPTFE may be in the form of an aqueous dispersion, having a mean particle size of less than 1.0 microns (μm), with the LPTFE having a first melt temperature (T_m) of 332° C or less. The second fluoropolymer may be a melt processible fluoropolymer (MPF), such as perfluoromethylvinyl ether (MFA), fluorinated ethylene propylene (FEP), or perfluoropropylvinyl ether (PFA), for example, in the form of an aqueous dispersion, and having a mean particle size of less than 1.0 microns (μm). Blending of the dispersions facilitates interaction of the LPTFE and MPF on a submicron level to facilitate intimate blending such that, when the blended fluoropolymer composition is dried, a crystal structure representing a true alloy of the fluoropolymers is formed, having melt characteristics that differ from those of the individual fluoropolymers. The blended fluoropolymer composition may be used to provide a coating having improved impermeability, stain resistance, abrasion resistance, smoothness, and higher contact angles.



WO 2009/146277 A1