

9804469-6
1995 copy!



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01M 4/62, C09D 127/16	A1	(11) International Publication Number: WO 97/32347 (43) International Publication Date: 4 September 1997 (04.09.97)
(21) International Application Number: PCT/EP97/00998 (22) International Filing Date: 27 February 1997 (27.02.97) (30) Priority Data: 8/39672 27 February 1996 (27.02.96) JP (71) Applicant (for all designated States except US): ELF ATOCHEM S.A. [FR/FR]; 4/8, cours Michelet, F-92800 Puteaux (FR). (72) Inventors; and (75) Inventors/Applicants (for US only): OHASHI, Kazuyoshi [JP/JP]; Elf Atochem Japan, Kyoto Technical Center, 1-chome, Awatacho, Chudoji, Shimogyo-ku, Kyoto 600 (JP). MIYAKI, Yoshiyuki [JP/JP]; Elf Atochem Japan, Kyoto Technical Center, 1-chome, Awatacho, Chudoji, Shimogyo-ku, Kyoto 600 (JP). GOTO, Kuniyuki [JP/JP]; Elf Atochem Japan, Kyoto Technical Center, 1-chome, Awatacho, Chudoji, Shimogyo-ku, Kyoto 600 (JP). (74) Agent: TREUIL, Claude; Elf Atochem S.A., Dépt. Propriété Industrielle, Cours Michelet-La Défense 10, F-92091 Paris-La Défense Cédex (FR).	(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(54) Title: BINDERS FOR ELECTRODES AND THEIR PRODUCTION METHOD (57) Abstract The present invention relates to electrodes consisting of an electrode activator and a metallic collector whose adhesion between the activator and the collector is improved. The electrode activator's binder is made of a fluoroplastic grafted with at least one acrylic polymer.		