

Isolated Paste Dispenser

This invention relates to a printing machine for printing a print medium onto a workpiece.

5

Background and Prior Art

Industrial screen-printing machines typically apply print media, such as solder paste or conductive ink, onto a planar workpiece, such as a wafer or circuit board, by applying the print medium (e.g. solder paste) through a pattern of apertures in a screen (sometimes referred to as a foil or a stencil) using an angled blade or squeegee. The print medium is conventionally stored in a cartridge or pot, and is dispensed from the bottom of this by applying pressure to the top, using a pressurised air source. The cartridge is mounted on the print carriage, which also carries the squeegee. Since the print carriage travels along the length (i.e. front to back) of the printing machine, conventionally referred to as the Y direction, the cartridge can dispense to either the front or rear rail of the printing machine. The cartridge is also mounted for movement along the X direction, being normal to the Y axis and in the horizontal plane, relative to the print carriage. In operation therefore, the print carriage is moved to one end of the printing machine, and the cartridge is caused to dispense print medium while travelling along the X direction, so that print medium is dispensed to form an approximately linear bead of medium onto the printing screen. Because of the lack of space available within the printing machine, the cartridge may be rotatable between a horizontal orientation when it is not dispensing, and a vertical orientation for dispensing.

25

The quantity of print medium present in the cartridge can be detected by a sensor, and an operator alerted when the cartridge requires replacement.

There is a problem however that in order to effect replacement of a cartridge, it is necessary to open up the printing machine to obtain access to the cartridge. FIG. 1 schematically shows a known printing machine 1 in a perspective view. The printing machine 1 is substantially cuboid, having an external housing 2 which covers the printing

30

machine 1 to prevent unauthorised access to the interior of the printing machine 1. The housing is mounted on a frame (not visible in FIG. 1), which also supports internal machinery and components. A hood 3 is provided to enable authorised access. This is connected to the remainder of the housing 2 via a hinge 4, so that the hood 3 can be lifted
5 up and rested on top of the housing. To further increase the safety of the printing machine 1, an interlocking system (not shown) may be provided, which must be enabled prior to opening the hood 3.

For safety reasons it is necessary that the printing operation is shut down whenever
10 the hood 3 of the printing machine 1 is opened, including when opened for the purpose of replacing a cartridge. This means that the print cycle is interrupted every time a cartridge is changed, which adds time to, and decreases efficiency of, the print process.

The present invention seeks to overcome this problem.
15

In accordance with the present invention this aim is achieved by providing isolation for the print medium cartridge, such as an isolated chamber which can be opened and accessed without interrupting the print process. In order to enable such a configuration, the cartridge is also separated from the print carriage and carried on a static rail, fixed to the
20 frame of the printing machine. While such an arrangement has the disadvantage that dispensing is only possible at one position, i.e. proximate the front or rear rail, it has been recognised that the advantages offered by this arrangement may outweigh the ability of conventional printing machines to dispense proximate both the front and rear rails of the printing machine.

25

Summary of the Invention

In accordance with a first aspect of the present invention there is provided a printing machine for printing a print medium onto a workpiece, comprising:
30 a frame,
an external housing supported by the frame,
a receptacle for receiving a printing screen in use,

a rail extending at least partially across and over the receptacle,
a shuttle mounted for travel along the rail, and
a cradle adapted to retain a container for print medium, the cradle being mounted on the
shuttle,
5 wherein the rail is statically fixed relative to the frame.

Other specific aspects and features of the present invention are set out in the
accompanying claims.

10 Brief Description of the Drawings

The invention will now be described with reference to the accompanying drawings
(not to scale), in which:

- 15 FIG. 1 schematically shows a perspective view of a closed, known printing machine;
FIG. 2 schematically shows a perspective view of a closed printing machine in accordance
with an embodiment of the present invention;
FIG. 3 schematically shows the printing machine of FIG. 2 with the hood and door removed;
FIG. 4 schematically shows a portion of the printing machine of FIG. 2 with the shuttle at the
20 home position;
FIG. 5 is similar to FIG. 4, with the shuttle moving to a dispensing position;
FIG. 6 is similar to FIG. 5, with the shuttle in a dispensing position;
FIG. 7 schematically shows a perspective view of a closed printing machine in accordance
with a second embodiment of the present invention; and
25 FIG. 8 schematically shows part of the internal configuration of the printing machine of FIG.
7.

Detailed Description of the Preferred Embodiments of the Invention

- 30 An embodiment of the present invention is schematically shown in FIG. 2. This
shows a perspective view of a closed printing machine 10, with an external housing 11
supported on a frame (15, see FIG. 3). A hood 12 provides access the interior of the printing

machine 10. In addition, a separate door 13 is provided, which may be opened by lifting it about a hinge 14 connecting the door 13 to the housing 11.

FIG. 3 shows both schematically and not to scale the printing machine 10 of FIG. 1 from the same viewpoint, though with the hood 12 and door 13 removed for clarity. In addition, and again for clarity, much of the printing machinery, in particular the print carriage, is omitted. The housing 11, and printing machinery and components are supported by frame 15. The internal volume of the printing machine 10 is partially separated into two distinct subvolumes by an internal partition 16: a main volume 17 and a container exchange volume 18, which is smaller than the main volume 17. The main volume 17 accommodates the printing machinery, including a print carriage with squeegee. Chases 22A, 22B are shown within the main volume 17, these chases 22A, 22B provide a receptacle for a printing screen S in use. As is known generally in the art, such chases are movable by actuators (not shown) to adjust the distance therebetween, so that a variety of differently-sized printing screens may be held by the chases 22A, 22B in use. During a printing process, a print carriage (not shown), including a squeegee, travels over the receptacle to act on a stencil S retained within, the direction of travel being parallel to the axes of the chases 22A, 22B, this direction conventionally being referred to as the "Y-direction".

The separation between the main volume 17 and the container exchange volume 18 is only partial since partition 16 includes an aperture 21, which permits communication between the two subvolumes. Passing through the aperture 21 proximate the upper edge thereof is a rail 19. Rail 19 extends at least partially across and over the receptacle, and in this embodiment across substantially the width of the printing machine 10, in a direction conventionally being referred to as the "X-direction". Rail 19 is statically fixed relative to the frame 15.

As will be described in detail below, the rail 19 is provided with a shuttle 23 mounted for travel along the rail 19. A portion of the rail 19, proximate an end thereof and located in the container exchange volume 18, acts both as a "home" position 20 for shuttle 23, in which the shuttle 23 may rest between dispensing actions, and an "exchange" position, in which the print medium container (25, see FIG. 4) may be exchanged, as will be described in more detail below. A cradle 24 is mounted on the shuttle 23 for travel therewith. Cradle 24

is adapted to retain a container for print medium (not shown). This container could for example comprise a cartridge or paste pot. It can be seen that shuttle 23 and cradle 24 are sized so as to fit through the aperture 21, so that they may travel into the main volume 17, and along the length of rail 19.

5

FIG. 4 schematically shows, in a perspective view, a portion of the printing machine 10 of FIG. 2 with the shuttle 23 at the home position. More specifically, FIG. 4 shows the rail 19 with the shuttle 23 mounted thereon, with cradle 24 mounted on the shuttle 23. A paste cartridge 25 is located and securely retained within the cradle 24. The top of cradle 24 is open, so that a pneumatic line (not shown) can be fitted to a pneumatic connector 26 at the top of the paste cartridge 25. Supplying pressurised air through the pneumatic line and connector 26 will cause paste to be dispensed from the lower end of the paste cartridge 25. A printing medium sensor 27 is provided within the container exchange volume 18 so that it is proximate the lower end of a paste cartridge 25 when present in the cradle 24, and when the shuttle 23 is at the home position 20. The printing medium sensor 27 is operative to detect the presence of paste at the lower end of the paste cartridge 25 and output a simple YES / NO signal dependent on the determination of the presence of paste.

The shuttle 23 comprises a wall section 28 at a lateral side of the cradle 24 furthest from the home position 20. The wall section 28 projects from the shuttle 23 towards the front of the printing machine 10, and is dimensioned so as to conform to the aperture 21, and furthermore located so as to align with the partition 16. In this way, when the shuttle 23 is at the home position 20, the cradle 24 is located in the container exchange volume 18 and the wall section 28 aligns with the partition 16 to isolate the container exchange volume 18 from the main volume 17.

The rail 19 is provided with a programmable actuator 29 for moving the shuttle 23 along the rail 19. In this embodiment the rail 19 comprises a linear worm (not shown) selectively rotated by actuator 29, which drives the shuttle 23 along the rail as would be well understood by those skilled in the art. A pneumatic input 30 is provided to the rail 19, which connects to a pneumatic line (not shown) which runs along the rail 19 and connects to the shuttle 23. This pneumatic drive is used to effect vertical movement of the cradle 24

as will be described in more detail below, this vertical direction conventionally being referred to as the “Z-direction”.

When the shuttle 23 is at the home position 20 as shown, so that it is in the
 5 container exchange volume 18, the container exchange volume 18 is isolated from the main
 volume 17. It is possible for an operator to open the door 13 to access the container
 exchange volume 18, remove cartridge 25 from cradle 24 and exchange it with a fresh
 cartridge which can be placed in the cradle 24, all without having to open the hood 12. In
 this way the cartridge can be exchanged without interrupting the printing cycle, in complete
 10 safety for the operator. The need to exchange a cartridge is determined by the output from
 the printing medium sensor 27.

FIG. 5 is a similar view to FIG. 4, however in this case the shuttle 23 is shown moving
 to a dispensing position. Actuator 29 is caused to drive the linear worm to cause the shuttle
 15 23 to move along the rail 19, through aperture 16, out of the container exchange volume 18
 and into the main volume 17. It can be seen that the wall section 28 travels with the shuttle
 23. It should be noted that with the cradle 24 in this configuration, the shuttle 23, cradle 24
 and cartridge 25 can pass over the top of chase 22A (and indeed chase 22B if travel
 continues along the rail 19) to reach a position over the printing screen. However, to
 20 dispense printing medium properly, the cartridge 25 must be closer to the printing screen.
 To achieve this, the cradle 24 is adapted to be vertically movable with respect to the shuttle
 23, so that it can be lowered into a dispensing position. The vertical position of the cradle
 24 is controlled pneumatically, with the pneumatic input 30.

FIG. 6 is a similar view to FIG. 5, with the cradle 24 in its lowered dispensing position.
 The cradle 24 is mounted on shuttle 23 via a linear track 31, which guides the vertical
 motion. For the avoidance of doubt, when the cradle 24 is at this lowered position to
 achieve satisfactory dispensing, it is unable to travel past either chase 22A, 22B without
 collision. Once in this lowered position a dispensing action may commence, during which
 30 the shuttle 23, and hence also cradle 24 and cartridge 25, is moved along the rail 19 by
 driving actuator 29, while pneumatic pressure is applied to pneumatic connector 26, causing
 a bead or line of paste to be dispensed onto the printing screen S (see FIG. 3). Following

completion of dispensing, the pneumatic pressure to pneumatic connector 26 is switched off, the cradle 24 is raised and the shuttle 23 is moved back to the home position 20 by actuator 29. Once the shuttle has reach the home position 20, printing of a workpiece through the printing screen S can be performed as is well-known in the art.

5

Actuator 29 and the pneumatic drive are programmable so as to accommodate the chases 22A, 22B being set at different positions in the X-direction, and in particular to raise or lower the cradle 24 at preselected points of travel of the shuttle 23 along the rail 19. A control processor (not shown) is provided for controlling the actuator 29, the pneumatic supply for cradle 24 and the pneumatic supply for the cartridge 25 as required.

10

FIG. 7 schematically shows a perspective view of a closed printing machine 40 in accordance with a second embodiment of the present invention. The external shape of the printing machine 40 is similar to that of the printing machine 10 shown in FIG. 2, in particular housing 41 is very similar to housing 11. In this embodiment however, hood 42 and its connecting hinge 44 extend across the entirety of the front width of the printing machine 40. A lateral side of the hood 42 is provided with a hatch 43, which is mounted on hood 42 by a hinge 45, to open outwardly.

15

FIG. 8 schematically shows, in perspective view, part of the internal configuration of the printing machine of FIG. 7. In particular, FIG. 8 shows certain major components of the print medium dispensing system. A statically-fixed rail 49 is provided which extends across substantially the entire internal width of the printing machine 40. A shuttle 46 is mounted for travel along the rail 49, so as to traverse a printing screen (not shown) in use. As with the first embodiment, the shuttle 46 carries a cradle 47 for retaining a print medium container (not shown), and a wall section 48 which projects perpendicularly to the rail 49. However, in this second embodiment, the cradle 47 is mounted on a projection 50 of the shuttle 46, which extends past the end of the rail 49 when the shuttle 46 is at an exchange position 51 proximate that end of the rail 49. The rail 49 and hatch 43 are aligned, so that when the shuttle 46 is moved along the rail 49 to the home position 51, the projection 50 abuts against and pushes open the hatch 43 from the inside of the printing machine 40, and passes to the outside of the printing machine 40. The cradle 47 therefore projects through

20

25

30

the hatch 43, and outside the external housing 41. Wall section 48 then aligns with the external lateral surface of the external housing 41, providing at least partial isolation between the interior of the external housing 41 and the cradle 47. In this position, an operator may safely access the cradle to exchange the paste medium container, without
5 interrupting the printing process. It will be apparent to those skilled in the art that a pneumatic line (not shown) will still be attached to the top of the print medium container within cradle 47, and which passes into the interior of the printing machine 40. To accommodate this pneumatic line, the wall section 48 is dimensioned to leave a gap between the wall section 48 and the hood 45, this gap being suitable for receiving the
10 pneumatic line. As shown, the wall section 48 has a shorter dimension along the Z-direction than the hatch 43, so that here a gap is formed above the wall section 48.

It can be seen that with this second embodiment, no internal partition is required. Those skilled in the art will also appreciate that in order to avoid unnecessary opening of the
15 hatch 43, between dispensing actions the shuttle 46 should in general return to a home position 52 located between the exchange position 51 and that part of the rail 49 which overlies the printing screen in use. Movement of the shuttle 46 to the exchange position would only be performed when a paste sensor (not shown) determines that the print medium container is empty.

20 The above-described embodiments are exemplary only, and other possibilities and alternatives within the scope of the invention will be apparent to those skilled in the art. For example, in the embodiment described above, the rails 19, 49 comprise linear worms driven by an actuator 29. Other drive systems are of course possible. Similarly, while the
25 vertical movement of cradles 24, 47 described above uses a pneumatic system, other drive systems, for example electromechanical drive systems, may alternatively be used. While the above-described embodiment shows the use of a paste cartridge, other containers, such as paste pots, and indeed other print media, such as conductive ink, may equally be dispensed.

30

With respect to the second embodiment, shown in FIGs. 7 and 8, the hatch 43 could be opened in a variety of ways, for example by way of a dedicated actuator, or manually opened by an operator.

- 5 It is possible that other equipment could be mounted for travel on the statically-fixed rail either in tandem or independently to the shuttle, such as, for example, a camera or other inspection equipment.

Reference Numerals:

- 1 - Printing machine
- 2 - Housing
- 3 - Hood
- 5 4 - Hinge
- 10, 40 - Printing machine
- 11, 41 - Housing
- 12, 42 - Hood
- 13 - Door
- 10 14, 44 - Hinge
- 15 - Frame
- 16 - Partition
- 17 - Main volume
- 18 - Container exchange volume
- 15 19, 49 - Rail
- 20, 52 - Home position
- 21 - Aperture
- 22A, 22B - Chases
- 23, 46 - Shuttle
- 20 24, 47 - Cradle
- 25 - Paste cartridge
- 26 - Pneumatic connector
- 27 - Printing medium sensor
- 28, 48 - Wall section
- 25 29 - Actuator
- 30 - Pneumatic input
- 31 - Linear track
- 43 - Hatch
- 45 - Hatch hinge
- 30 50 - Projection
- 51 - Exchange position
- S - Screen

Claims

1. A screen printing machine (10, 40) for printing a print medium onto a workpiece, comprising:

a frame (15),
an external housing (11, 41) supported by the frame (15),
a print carriage with squeegee,
a receptacle for receiving a printing screen (S) in use,
a rail (19, 49) extending at least partially across and over the receptacle,
a shuttle (23, 46) mounted for travel along the rail (19, 49), and
a cradle (24, 47) adapted to retain a container (25) for print medium, the cradle (24, 47) being mounted on the shuttle (23, 46),
characterised in that the rail (19, 49) is statically fixed relative to the frame, and a portion of the rail (19, 49) comprises an exchange position (51) for the shuttle (23, 46), at which position a container (25) for printing medium can be placed in or removed from the cradle (24, 47), the container (25) being separated from the print carriage.

2. The printing machine (10) of claim 1, comprising an internal partition (16) which partially separates the interior of the printing machine (10) into a main volume (17) which comprises the receptacle, and a container exchange volume (18) in which the exchange position (51) is located.

3. The printing machine of claim 2, wherein the shuttle (23) comprises a wall section (28), the wall section (28) being provided at a lateral side of the cradle (24), such that when the shuttle (23) is at the exchange position (51), the cradle (24) is located in the container exchange volume (18) and the wall section (28) aligns with the partition (16) to isolate the container exchange volume (18) from the main volume (17).

4. The printing machine (10) of either of claims 2 and 3, wherein the housing (11) comprises a door (13) located proximate the container exchange volume (18), to provide access to the cradle (24) when the shuttle (23) is at the exchange position (51).
5. The printing machine (10, 40) of claim 1, wherein the external housing (11, 41) comprises a hatch (43).
6. The printing machine (40) of claim 5, wherein when the shuttle (46) is at the exchange position (51), the cradle (47) projects through the hatch (43) and outside the external housing (41).
7. The printing machine (40) of claim 6, wherein the shuttle (46) comprises a wall section (48), the wall section (48) being provided at a lateral side of the cradle (47), such that when the shuttle (46) is at the exchange position (51), the cradle (47) is located externally of the external housing (41) and the wall section (48) aligns with the external housing (41) to isolate the cradle (47) from the interior of the housing (41).
8. The printing machine (10, 40) of any of claims 1 to 7, comprising an actuator (29) for moving the shuttle (23, 46) along the rail (19, 49).
9. The printing machine (10, 40) of any of claims 1 to 8, wherein the cradle (24, 47) is movable in a vertical direction relative to the shuttle (23, 46).
10. The printing machine (10, 40) of claim 9, comprising a drive to effect vertical movement of the cradle (24, 47).
11. The printing machine (10, 40) of claim 10, wherein the drive comprises a pneumatic drive.
12. The printing machine (10, 40) of either of claims 10 and 11, wherein the drive is programmable to raise or lower the cradle (24, 47) at preselected points of travel of the shuttle (23, 46) along the rail (19, 49).