

9604132-2
IPD's
copy

THIS SHEET HAS BEEN
REPLACED

94-215 EP

SPECIFICATION

BOARD TO BOARD ELECTRICAL CONNECTORS

Field of the Invention

This invention generally relates to the art of electrical connectors and, particularly, to electrical connectors for coupling first and second printed circuit boards together.

5

Background of the Invention

A variety of electrical connectors have been used to make electrical connections between the circuits on different printed circuit boards. Typically, board to board connectors have both male and female portions or terminals to form an electrical connection between the two circuit boards. Male connector posts or pins typically are coupled to a first circuit board, and the male connector posts mate with female connector receptacles coupled to the second circuit board.

10

15

Board to board connector systems as described above often require two types of connectors to be maintained in inventory in order to afford coupling two printed circuit boards together. However, hermaphroditic connectors have been designed where two identical connectors can be mated to one another in a given orientation. Therefore, only one type of connector needs to be maintained in inventory.

20

25

Problems have been encountered with these types of electrical connector systems, because there is an increasing demand for high density connectors which also allow printed circuit boards to be placed closer together. A high density connector often requires the use of a stamped terminal to reduce the spacing between the



THIS SHEET HAS BEEN
REPLACED

94-215 EP

5 terminals of a given connector. To allow printed circuit boards to be placed closer together in parallel planes, a very low profile board to board connector is required. These demands often result in relatively complicated connector designs.

10 The present invention is directed to providing a simple, efficient and inexpensive high density, low profile hermaphroditic board to board electrical connector which satisfies the needs of the connector industry as is not available in the prior art.

Summary of the Invention

An object, therefore, of the invention is to provide a new and improved electrical connector of the character described above.

15 Another object of the invention is to provide a low profile hermaphroditic electrical connector mounted on the surface of a first printed circuit board and adapted to mate with an identical second connector mounted on the surface of a second printed circuit board to electrically and mechanically couple the first and second circuit boards.

20 In the exemplary embodiment of the invention, the connector includes a housing mounting a plurality of stamped female and male terminals. Each terminal has a surface mounting portion for electrically engaging the respective printed circuit board, a mating portion adapted to mate with the mating portion of the terminal of the opposite gender of the other hermaphroditic connector, and means for holding the terminals in the housing. The invention contemplates that the mating portion of the female terminal include two opposed, spaced apart contact arms. The contact arms and the terminal holding means both project from the mounting portion, with the contact arms



THIS SHEET HAS BEEN
REPLACED

94-215 EP

laterally adjacent the terminal holding means. The mating portion of the male terminal includes a post adapted to be received between the contact arms of the female terminal. The post and the terminal holding means of the male
5 terminal both project from the mounting portion, with the post laterally adjacent the terminal holding means.

As disclosed in the preferred embodiment, the surface mounting portion of the female terminal comprises an elongated generally planar base having opposed stamped
10 edges. One edge is adapted for electrically engaging the respective printed circuit board. The contact arms and the terminal holding means both project from the opposite edge. The contact arms and the terminal holding means are generally planar and coplanar with the base. The terminal
15 holding means is provided by a post generally parallel to the contact arms.

Similarly, the surface mounting portion of the male terminal comprises an elongated generally planar base having opposed stamped edges. One edge is adapted for
20 electrically engaging the respective printed circuit board, and the post and terminal holding means both project from the opposite edge of the base. The post and the terminal holding means are generally planar and coplanar with the base. The terminal holding means is provided by a second
25 post generally parallel to the male terminal post.

Another feature of the invention is to provide a lip projecting from the base portion of the male terminal beneath a shoulder on the respective housing. The lip is engageable with the shoulder to resist lifting of the
30 surface mounting portion off the respective printed circuit board during unmating of the connectors.

Other objects, features and advantages of the invention will be apparent from the following detailed

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

description taken in connection with the accompanying
drawings.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

Brief Description of the Drawings

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

5
10 FIGURE 1 is a vertical section through a pair of hermaphroditic electrical connectors embodying the concepts of the invention, the connectors being surface mounted to a pair of parallel printed circuit boards;

15 FIGURE 2 is a vertical section through the two connectors of Figure 1, with the connectors disconnected and the printed circuit boards removed;

FIGURE 3 is an elevated perspective view of one of the connectors;

20 FIGURE 4 is a top plan view of one of the connectors;

FIGURE 5 is a side elevational view of one of the connectors; and

FIGURE 6 is an end elevational view of one of the connectors.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

Detailed Description of the Preferred Embodiment

Referring to the drawings in greater detail, and first to Figure 1, the invention is embodied in a hermaphroditic electrical connector, generally designated 10. Two connectors 10 are identical in structure, and the connectors are shown in Figure 1 fully mated and coupling a pair of printed circuit boards 12 together in a parallel orientation. Figure 2 shows the two hermaphroditic connectors unmated, and with the circuit boards removed to facilitate the illustration.

More particularly, each hermaphroditic connector 10 includes a one-piece dielectric housing, generally designated 14, that may be unitarily molded of plastic material. A plurality of mounting posts 16 project from the housing for insertion into appropriate mounting holes in the respective circuit board. Each connector mounts a stamped female terminal, generally designated 18, and a stamped male terminal, generally designated 20. The female terminal includes a pair of generally parallel contact arms 22 which define a receptacle 24 therebetween for receiving a contact post 26 of male terminal 20.

Still referring to Figures 1 and 2, female terminal 18 is a stamped metal component with contact arms 22 which form a mating portion and project from one end of an elongated base 28. Terminal holding means in the form of a mounting post 30 projects in the same direction away from one edge 36 of base 28 as contact arms 22. The mounting post is interference fit within a mounting aperture 32 in housing 14 to hold female terminal 18 within the housing. An edge of the base opposite the one edge 36 is provided with a pair of surface mounting portions 38 for electrically coupling to appropriate circuit traces on the respective circuit board. The contact arms and the mounting post are generally planar and coplanar with base



94-215 EP

28. Lastly, a terminal foot 34 projects laterally outwardly of the housing.

5 Male terminal 20 similarly includes an elongated base 40 with contact post 26 defining the mating portion of the terminal. A mounting post 42 projects from the base generally parallel to contact post 26. The mounting post is interference fit within a mounting aperture 44 in housing 14.

10 As with female terminal 18, male terminal 20 is a stamped metal component defining an edge 46 from which contact post 26 and mounting post 42 project. The opposite edge of the base defines a pair of surface mounting portions 48 for engaging appropriate circuit traces on the respective printed circuit board 12. The contact post and
15 the mounting post are generally planar and coplanar with base 40. The male terminal includes a terminal foot 49 projecting laterally of housing 14 at the end of base 40 opposite contact post 26.

20 One or both of the female and male terminals 18 and 20, respectively, are provided with means for resisting lifting of the terminal off of its respective printed circuit board during unmating of the connectors. In the exemplary embodiment, male terminal 20 is provided with a
25 lip 50 which projects laterally away from the contact end of base 40 beneath a shoulder 52 of housing 14. Therefore, upon unmating of the connectors, lip 50 can engage shoulder 52 to resist lifting of the surface mounting portions of the terminal off the respective printed circuit board.

30 Figure 3 shows an elevated perspective view of one of the hermaphroditic electrical connectors 10 according to the invention, and Figures 4-6 show top plan, side elevational and end elevational views, respectively, of the connector. It can be seen that a row of female terminals 18 extend lengthwise of housing 14 generally



THIS SHEET HAS BEEN
REPLACED

94-215 EP

5 parallel to a row of male terminals 20. Figure 3 clearly shows how contact posts 26 of the male terminals project from the housing for insertion between contact arms 22 of female terminals 18 of an identically constructed, hermaphroditic connector.

10 Figures 3 and 4 show how terminal feet 34 of female terminals 18 and terminal feet 49 of male terminals 20 project laterally out of opposite sides of housing 14. Figures 5 and 6 show that a pair of mounting posts 16 depend from the housing for insertion into appropriate mounting holes in the printed circuit board. Lastly, a pair of generally S-shaped "fitting nails", generally designated 56, are mounted at opposite ends of housing 14. As is known in the art, each fitting nail includes a foot
15 portion 58 for surface mounting to a solder pad on the respective circuit board to facilitate securing the connector to the board.

20 It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

This Sheet Has Been Replaced



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

CLAIMS

1. A low profile hermaphroditic electrical connector (10) mounted on the surface of a first printed circuit board (12) and adapted to mate with an identical
5 second connector (10) mounted on the surface of a second printed circuit board (12) to electrically and mechanically couple the first printed circuit board to the second printed circuit board, each connector including:

a housing (14),

10 a plurality of stamped female (18) and male (20) terminals held in said housing, each terminal having a surface mounting portion (38, 48) for electrically engaging the respective printed circuit board, a mating portion (22, 26) adapted to mate with the mating portion of the terminal
15 of the opposite gender of the other hermaphroditic connector, and means (30, 42) for holding said terminal in said housing,

the improvement comprising:

20 the mating portion of said female terminal (18) including two opposed, spaced apart contact arms (22), said contact arms and said terminal holding means (30) both projecting from the mounting portion (38) with the contact arms (22) laterally adjacent the terminal holding means (30); and

25 the mating portion of said male terminal (20) including a contact post (26) adapted to be received between the contact arms (22) of the female terminal (18), said post and said terminal holding means (42) both projecting from the mounting portion (48) with the post
30 (26) laterally adjacent the terminal holding means (42).



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

5 2. The low profile hermaphroditic electrical connector of claim 1 wherein the surface mounting portion of said female terminal (18) comprises an elongated generally planar base (28) having opposed stamped edges (36, 38), one edge (38) providing the surface mounting portion for electrically engaging the respective printed circuit board, and said contact arms (22) and said terminal holding means (30) both projecting from the opposite edge (36).

10 3. The low profile hermaphroditic electrical connector of claim 2 wherein said contact arms (22) and said terminal holding means (30) are generally planar and coplanar with the base (28).

15 4. The low profile hermaphroditic electrical connector of claim 3 wherein said terminal holding means comprises a mounting post (30) generally parallel to said contact arms (22).

20 5. The low profile hermaphroditic electrical connector of claim 1 wherein the surface mounting portion of said male terminal (20) comprises an elongated generally planar base (40) having opposed stamped edges (46, 48), one edge (48) providing the surface mounting portion for electrically engaging the respective printed circuit board, and said contact post (26) and said terminal holding means
25 (42) both projecting from the opposite edge (46).

6. The low profile hermaphroditic electrical connector of claim 5 wherein said contact post (26) and said terminal holding means (42) are generally planar and coplanar with the base (40).



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

7. The low profile hermaphroditic electrical connector of claim 6 wherein said terminal holding means comprises a mounting post (42) generally parallel to said contact post (26).

5

8. The low profile hermaphroditic electrical connector of claim 5 wherein the surface mounting portion of said female terminal (18) comprises an elongated generally planar base (28) having opposed stamped edges (36, 38), one edge (38) providing the surface mounting portion for electrically engaging the respective printed circuit board, and said contact arms (22) and said terminal holding means (30) both projecting from the opposite edge (36).

10

15

9. The low profile hermaphroditic electrical connector of claim 8 wherein said contact arms (22) and said terminal holding means (30) are generally planar and coplanar with the base (28).

20

10. The low profile hermaphroditic electrical connector of claim 9 wherein said terminal holding means comprises a mounting post (30) generally parallel to said contact arms (22).



THIS SHEET HAS BEEN
REPLACED

94-215 EP

5 11. An electrical connector (10) mounted on the surface of a first printed circuit board (12) and adapted to mate with an identical second connector (10) mounted on the surface of a second printed circuit board (12) to electrically and mechanically couple the first printed circuit board to the second printed circuit board, each connector including:

a housing (14),
10 a plurality of female (18) and male (20) terminals held in said housing, each terminal having a surface mounting portion (38, 48) for electrically engaging the respective printed circuit board (12), a mating portion (22, 26) adapted to mate with the mating portion of the terminal of the opposite gender of the other hermaphroditic
15 connector, and means (30, 42) for holding said terminal in said housing,

the improvement comprising:
said surface mounting portion (38, 48) of at least one of the terminals (18, 20) being at least part of
20 a base portion (28, 40) of the terminal, and including a lip (50) projecting from the base portion (40) beneath a shoulder (52) on the respective housing (14) to resist lifting of the surface mounting portion (48) off the respective printed circuit board (12) during unmating of
25 the connectors (10).

12. The hermaphroditic electrical connector of claim 11 wherein said base portion (40) is elongated generally parallel to the respective printed circuit board (12), with the mating portion (26) and said lip (50) being
30 located generally at one end of the base portion.



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

94-215 EP

13. The hermaphroditic electrical connector of claim 12 wherein said lip (50) projects generally parallel to the base portion (40) and the printed circuit board (12).

5 14. The hermaphroditic electrical connector of claim 13 wherein said at least one terminal comprises the male terminal (20) and the mating portion thereof comprises a post (26) projecting generally perpendicular to the elongated base portion (40).

10 15. An electrical connector (10) for mounting on the surface of a printed circuit board (12), the connector including a housing (14) and a plurality of male (20) and female (18) terminals held in the housing, each terminal having a surface mounting portion (48, 38) for electrically
15 engaging the respective printed circuit board, a mating portion (26, 22) adapted to mate with the mating portion of a complementary electrical device, and means (42, 30) for holding the terminal in the housing,

the improvement comprising:

20 said surface mounting portion of the terminal being at least part of a base portion (40) of the terminal, and including

a lip (50) projecting from the base portion (40) beneath a shoulder (52) on the respective housing (14) to
25 resist lifting of the surface mounting portion (48) off the respective printed circuit board (12) during unmating of the connector (10).

30 16. The electrical connector of claim 15 wherein said base portion (40) is elongated generally parallel to the respective printed circuit board (12), with the mating portion (26) and said lip (50) being located generally at one end of the base portion.



THIS SHEET HAS BEEN
REPLACED

94-215 EP

17. The electrical connector of claim 16 wherein said lip (50) projects generally parallel to the base portion (40) and the printed circuit board (12).

This Sheet Has Been Replaced



* C L M S *

THIS SHEET HAS BEEN
REPLACED

94-215 EP

18. The electrical connector of claim 17 wherein said terminal comprises the male terminal (20) and the mating portion thereof comprises a post (26) projecting generally perpendicular to the elongated base portion (40).

This Sheet Has Been Replaced



* C L M S *