

5

TELEVISION PROXIMITY SENSORBACKGROUND OF THE INVENTION

10

Cross Reference to Related Applications

[0001] This application claims priority under 35 U.S.C. § 119(e) to U.S. provisional Application Serial No. 60/313,816, entitled "Television Proximity Sensor",
15 filed August 22, 2001, the contents of which are incorporated by reference herein.

Field of the Invention

[0002] The present invention relates to an apparatus and a method for
20 determining whether a television is on and in near proximity to a sensor, and more particularly an apparatus and a method for determining whether a television audience member is in the same room as a television that is turned on.

Description of the Related Art

25

[0003] Television audience measurement systems are based either on portable devices carried by members of the audience, or on fixed devices placed in the vicinity of a television set. In both these applications, a microphone on the device picks up an audio signal associated with a television program. The usual objective is to determine
30 the program or channel being viewed from an analysis of the audio signal. For example, in one approach, the device computes a "signature" for subsequent matching with a reference signature recorded at a central facility. Alternatively, in a second approach, the device extracts embedded identification codes that have been inserted into the audio stream at the broadcast facility, in order to identify the program.

35

[0004] One of the problems encountered by a portable device is to determine whether the audio signal picked up by the microphone is originating from a nearby television set. The microphone in such devices, being extremely sensitive, can respond to audio signals emitted in a neighboring room. There is a need to disregard such audio
40 and process only the audio emanating from within a room in which the carrier of the

- 5 device is present. In the case of the fixed device, it is essential to determine whether or not the television set is turned on or off.

SUMMARY OF THE INVENTION

10

[0005] In one aspect, the invention provides a television proximity sensor system. The system includes an audio sensor, an analog-to-digital converter, and a digital signal processor. The audio sensor is situated in near proximity to the television. When the television is turned on, the television emits an audio signal, the audio sensor
15 detects the audio signal, the analog-to-digital converter converts the audio signal into a set of digital audio samples, and the digital signal processor processes the set of digital audio samples such that the processor determines that the television is turned on. When the television is turned off, the digital signal processor determines that the television is turned off. The system may also include an amplifier. The amplifier may amplify the
20 detected audio signal and provide the amplified signal to the analog-to-digital converter.

[0006] The processing of the set of digital audio samples may include measuring a first power level of the audio signal at a first frequency, measuring a
25 second power level of the audio signal at a second frequency, measuring a third power level of the audio signal at a third frequency, computing a ratio of the first power level to a sum of the first, second, and third power levels, and comparing the computed ratio to a predetermined first threshold value. When the computed ratio is greater than or equal to the first threshold value, it may be determined that the television is turned on.
30 The digital signal processor may also continuously update the measurements of the first, second, and third power levels and compare the most recent measurement of the first power level to a predetermined second threshold value. When the first power level is greater than or equal to the second threshold value, it may be determined that the television is turned on. When the computed ratio is less than the first threshold value
35 and the first power level is less than the second threshold value, it may be determined that the television is turned off.

5 **[0007]** The digital signal processor may use a sliding Fast Fourier Transform algorithm to detect a presence of an audio signal at the first frequency. The predetermined first threshold value may be substantially equal to 0.9, or it may be substantially greater than or equal to 0.6. The first frequency may be associated with a horizontal scan fly-back transformer used by the television. The horizontal scan fly-back transformer may be associated with a frequency substantially equal to 15.75 kHz. The second and third frequencies may have predetermined spacings from the first frequency.

15 **[0008]** In another aspect, the invention provides an apparatus for determining whether a first television set is turned on, while distinguishing the first television set from other devices such as a radio or a second television set. The apparatus includes receiving means for receiving an analog audio signal, digitizing means for converting the received analog audio signal to a set of digital audio samples, processing means for processing the set of digital audio samples, and

20 determining means for using a result of the processing to determine whether the first television set is turned on. The apparatus may also include amplifying means for amplifying the received analog audio signal. The processing means may include first measuring means for measuring a first power level of the audio signal at a first frequency, second measuring means for measuring a second power level of the audio signal at a second frequency, third measuring means for measuring a third power level of the audio signal at a third frequency, computing means for computing a ratio of the first power level to a sum of the first, second, and third power levels, and first

25 comparing means for comparing the computed ratio to a predetermined first threshold value. When the computed ratio is greater than or equal to the first threshold value, the determining means may determine that the first television set is turned on. The processing means may also include updating means for continuously updating the measurements of the first, second, and third power levels, and second comparing means for comparing the most recent measurement of the first power level to a predetermined second threshold value. When the first power level is greater than or equal to the

30 second threshold value, the determining means may determine that the first television set is turned on. When the first power level is less than the second threshold value and the computed ratio is less than the first threshold value, the determining means may determine that the first television is turned off.

5

[0009] The processing means may also include transforming means for using a sliding Fast Fourier Transform algorithm to detect a presence of an audio signal at the first frequency. The predetermined first threshold value may be substantially equal to 0.9, or it may be substantially than or equal to 0.6. The first frequency may be

10 associated with a horizontal scan fly-back transformer used by the first television. The horizontal scan fly-back transformer may be associated with a frequency substantially equal to 15.75 kHz. The second and third frequencies may have predetermined spacings from the first frequency.

15 [0010] In yet another aspect, the invention provides a method of determining whether a television set is turned on and in near proximity. The method includes the steps of receiving an analog audio signal, converting the received analog audio signal to a set of digital audio samples, processing the set of digital audio samples, and using a result of the processing to determine whether the first television set is turned on and in

20 near proximity. The method may also include the step of amplifying the received analog audio signal. The step of processing may include measuring a first power level of the audio signal at a first frequency, measuring a second power level of the audio signal at a second frequency, measuring a third power level of the audio signal at a third frequency, computing a ratio of the first power level to a sum of the first, second,

25 and third power levels, and comparing the computed ratio to a predetermined first threshold value. When the computed ratio is greater than or equal to the first threshold value, a determination may be made that the television set is turned on and in near proximity.

30 [0011] The step of processing may also include continuously updating the measurements of the first, second, and third power levels, and comparing the most recent measurement of the first power level to a predetermined second threshold value. When the first power level is greater than or equal to the second threshold value, a determination may be made that the television set is turned on and in near proximity.

35 When the first power level is less than the second threshold value and the computed ratio is less than the first threshold value, a determination may be made that the television is turned off or out of proximity.

5 **[0012]** The step of processing may also include the step of using a sliding Fast Fourier Transform algorithm to detect a presence of an audio signal at the first frequency. The predetermined first threshold value may be substantially equal to 0.9, or it may be substantially greater than or equal to 0.6. The first frequency may be associated with a horizontal scan fly-back transformer used by the television. The
10 horizontal scan fly-back transformer may be associated with a frequency substantially equal to 15.75 kHz. The second and third frequencies may have predetermined spacings from the first frequency.

[0013] In still another aspect, the invention provides a method of detecting
15 whether a first television set is turned on, while distinguishing the first television set from other devices such as a radio or a second television set. The method includes the steps of measuring a first power level of an audio signal at a first frequency, measuring a second power level of the audio signal at a second frequency and a third power level of the audio signal at a third frequency, computing a ratio of the first power level to a
20 sum of the first, second, and third power levels, making a first comparison of the ratio to a predetermined threshold ratio value, and making a first determination of whether the first television set is on based on a result of the first comparison. The first frequency is associated with a horizontal scan fly-back transformer used by the first television set. The second and third frequencies have predetermined spacings from the
25 first frequency. The method may also include the steps of using a measured value of the first power level to set a threshold first power value, continuously updating the measurements of the first, second, and third power levels, and making a second comparison of a most recently updated measurement value of the first power level to the threshold first power value when a first determination that the first television set is
30 not on is made. A second determination of whether the first television set is turned on is then made, based on a result of the second comparison.

BRIEF DESCRIPTION OF THE DRAWINGS

35

[0014] Figure 1 is a flowchart illustrating a method of determining whether a television is considered on and in near proximity according to the present invention.

- 5 **[0015]** Figure 2 is a block diagram showing a system for determining whether a television is considered on and in near proximity according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

10

- 15 **[0016]** The present invention is based on the detection of a television display device property to determine whether the television is on. For example, all television sets with Cathode Ray Tube (CRT) displays contain circuitry for scanning an electron beam across the picture tube. The transformers, which generate the required voltage to perform scanning, emit a characteristic audio signal (e.g., transformer buzz). This audio signal permeates the vicinity of a television set. Vibrations of the laminations within the transformer generate the audio. In a television system operating with the NTSC standard, the horizontal scan fly-back transformers emit a 15.75 kHz wave. The presence of this characteristic frequency can be detected from the audio signal picked up by the microphone. This high frequency tone has a fixed intensity for a given television set. It typically does not penetrate through walls, and as a result, only a microphone placed in the same room as the television set can pick up the characteristic frequency. Either an analog phase locked loop or a digital Fast Fourier Transform ("FFT") can be used to detect this signal. Of course, other characteristic signals emitted from a CRT, Liquid Crystal Display (LCD), or other display device may be used.

- 25 **[0017]** Accordingly, as used in this patent application, as applied to a television and a microphone or other appropriate signal detector, the term "in near proximity" is defined as "within the same room and with no physical obstruction, such as a wall, floor, or ceiling, between the television and the detector", and the term "out of proximity" is defined as "not in the same room and with a physical obstruction, such as a wall, floor, or ceiling, between the television and the detector". Thus, the microphone is able to detect the characteristic audio signal for a television that is in near proximity, but the microphone is not able to detect the characteristic audio signal for a television that is out of proximity. When the microphone is attached to a portable device that is being carried by a member of the television audience, determination of whether the television is "in near proximity" or "out of proximity" becomes equivalent to a

- 5 determination of whether the member of the television audience carrying the portable device is in the same room as a television that is turned on.

[0018] If an FFT is used to detect the signal, this can be advantageously embodied in the type of audience measurement system in which “active” embedded
10 codes are detected in the program signal. The extraction of these codes usually involves a spectral analysis of the detected audio using an FFT. The FFT analysis can be easily extended to analyze the frequency neighborhood around the characteristic frequency emitted by the television set. Based on spectral power, the sensed audio can be classified as originating from a television signal or other audio.

15

[0019] The presence of an audio signal at the fly back frequency of 15.75 kHz can be most conveniently detected by means of a “sliding” implementation of the Fast Fourier Transform (hereinafter referred to as “SFFT”). Such an implementation can continuously monitor the spectral power in a neighborhood surrounding the frequency
20 of interest and compute the relative as well as the absolute power of the 15.75 kHz signal. It is noted that in extracting embedded “active” spectral audio codes of the type described in U.S. Patent 6,272,716 (entitled “Broadcast Encoding System and Method” and incorporated herein by reference), the SFFT algorithm is employed.

25 [0020] Referring to Figure 1, a flow chart 100 illustrates a method of determining whether a television is turned on and in near proximity according to one embodiment of the present invention. Referring also to Figure 2, a hardware implementation 200 of a television proximity sensor according to the preferred embodiment of the present invention is shown. In step 105, the audio signal picked up
30 by the microphone 205 is generally amplified by an amplifier 210 and converted into a digital stream by an analog-to-digital converter 215. Then, at step 110, an SFFT is computed using the digital signal processor 220. The digital signal processor 220 includes an internal data memory 225 and an internal program memory 230. The program memory 230 stores the SFFT algorithm, as well as any other algorithms used
35 by the processor 220. The data memory 225 stores data, including the results of performing the SFFT at step 110. In order to compute the Fourier spectrum, a buffer comprising $N_s = 512$ audio samples captured at a 48 kHz sampling rate may be used.

5 The spectral frequency indices ("bins") ranging from 0 to 255 represent frequencies in the range 0 to 24 kHz. The frequency separation between adjacent spectral lines is preferably 93.75 Hz. The horizontal scanning frequency (i.e., 15.75 kHz) corresponds to a bin with index 168. In a typical operating environment, such as a room in a household, the spectral energy in the 15 kHz band is extremely low and is on the order of -60 dB. In order to obtain a relative spectral magnitude of the frequency of interest, the power in bins 160, 164 and 168 is computed at step 115. It is noted that the detection of other characteristic signals would involve the measurement of energy in different bins.

15 **[0021]** Unlike the well-known Fast Fourier Transform, which computes the complete spectrum of a given block of audio, the sliding FFT or SFFT is more useful for computing power in selected frequency bins and constantly updating the spectrum as new audio samples are acquired. Assuming that spectral amplitude $a_0[J]$ and phase angle $\varphi_0[J]$ are known for a frequency with index J for an audio buffer currently stored in the buffer, these values represent the spectral values for the N_s audio samples currently in the buffer. If a new time domain sample v_{N_s-1} is inserted into the buffer to replace the earliest sample v_0 , then the new spectral amplitude $a_1[J]$ and phase $\varphi_1[J]$ for the index J are given by the following equation (Equation 1):

$$\begin{aligned}
 a_1[J] \exp \varphi_1[J] &= a_0[J] \exp \varphi_0[J] \exp \left(-\frac{i2\pi J}{N_s} \right) + \left(v_{N_s-1} \exp \left(\frac{i2\pi J(N_s-1)}{N_s} \right) \right) - \left(v_0 \exp \left(-\frac{i2\pi J}{N_s} \right) \right) \\
 &= (a_0[J] \exp \varphi_0[J] + v_{N_s-1} - v_0) \exp \frac{-i2\pi J}{N_s}
 \end{aligned}$$

Thus, the spectral amplitude and phase values at any frequency with index J in an audio buffer can be computed recursively merely by updating an existing spectrum according to Equation 1. The updated spectral power is $P_J = a_1^2$. Even if all the spectral values (amplitude and phase) were initially set to 0, as new data enters the buffer and old data gets discarded, the spectral values gradually change until they correspond to the actual Fourier Transform spectral values for the data currently in the

5 buffer. In order to overcome certain instabilities that may arise during computation, multiplication of the incoming audio samples by a stability factor usually set to 0.999 and the discarded samples by a factor 0.999^{N_s-1} may be used. The sliding FFT algorithm provides a computationally efficient means of calculating the spectral components of interest for the $N_s - 1$ samples preceding the current sample location
10 and the current sample itself.

[0022] At step 120, in order to detect the presence of a television set that is turned on, or to check if an audio signal picked up by the microphone is associated with

a television set, the ratio $R_n = \frac{P_{168}}{P_{160} + P_{164} + P_{168}}$ is computed for each block of audio

15 indexed by n . When a television set is turned on, this ratio has a value close to 1.0 because $P_{168} \gg P_{160} + P_{164}$. When a television is in the off state, the ratio is close to 0.333 because all three frequency bins have low power values. At step 125, a ratio threshold such as $R_{th} = 0.95$ can then be used to detect the state of the television set. At step 135, when used in conjunction with an “active” embedded audio code-decoding
20 algorithm, the absolute value of P_{168} at an instant of time when an embedded code has been successfully extracted may be used to set an additional reference value P_{th} . Both conditions $R_n > R_{th}$ and $P_{168} > P_{th}$ may be used to determine the state of the television set at a given instant of time. If either of these inequalities is true, then at step 130 it is determined that the television is turned on and in near proximity. If both inequalities
25 are false, then at step 140 it is determined that the television is either turned off or out of proximity. It is noted that the ratio threshold R_{th} can be chosen to be any appropriate value between 0 and 1; for example, R_{th} may be chosen as 0.6, 0.75, or 0.9.

[0023] The use of the ratio threshold as described above in step 125 has the
30 effect of providing an adaptive measure of the television audio spectrum at the frequencies of interest. The use of the absolute power level of bin 168 as described above in step 135 provides a method of mitigating a possible “clipping” effect that may occur if the audio power exceeds the maximum power allowed by the automatic gain control. For example, if a noise spike occurs due to a television program, it is possible
35 that the audio power will reach the maximum possible level, and thus the measurement

- 5 of the power level will be clipped at that maximum level. In such an instance, the ratio R_n may drop below 0.95, because the power levels in P_{160} and P_{164} have risen proportionately as the noise spike. Despite this, the use of the threshold value P_{th} enables the detection of the presence of a television set that is turned on. The threshold value P_{th} can also be adaptive to a particular television, and is not limited to bin 168.
- 10 Rather, the threshold can be applied to whatever bin happens to sustain the maximum power levels for the neighborhood of the frequency of interest, typically 15.75 kHz.

[0024] In a practical implementation, a sequence of R_n and P_{168} values covering a long interval of time (typically on the order of seconds) is examined for determining the presence of a television set that has been turned on. In such a sequence, if a majority of the entries indicate that the television set is turned on, a decision can be made that an active television set is present. Alternatively, an averaging of the ratio and power values captured in the sequence can also be used for decision-making. Several stray effects can occasionally produce spectral energy at 15.75 kHz and averaging the observations over a longer interval results in greater reliability. Yet another factor to be taken into account is the presence of an Automatic Gain Control (AGC) amplifier that may cause a change in the absolute value of P_{168} . If the AGC is software controlled, the reference value P_{th} used for comparison can be varied based on the actual instantaneous gain setting.

25

[0025] An alternative method of detecting whether a television is turned on involves observing a transient effect in the frequency spectrum which is associated with the actual transition from the off state to the on state. When a television has been in the off state and is presently turned on, an audio pulse of energy moves through the frequency spectrum in a "ripple"-like fashion from 0 Hz up to the 15.75 kHz steady-state frequency. Thus, a detection of the frequency ripple acts as an indicator that the television has been turned on.

[0026] The technique described above may be applied to television systems operating with standards other than the NTSC standard, whose horizontal scan fly-back transformer frequency is actually 15.734 kHz. For example, the PAL standard has a horizontal scan fly-back transformer frequency of 15.635 kHz. Line doublers can be

5 used with either the NTSC standard or the PAL standard. The use of a line doubler has the effect of doubling the frequency, to 31.47 kHz in the NTSC case and 31.25 kHz in the PAL case. Digital television includes several formats that are associated with the following frequencies: 15.63 kHz; 26.97 kHz; 27.00 kHz; 28.13 kHz; 31.25 kHz; 31.47 kHz; 33.72 kHz; 33.75 kHz; 44.96 kHz; 45.00 kHz; 62.50 kHz; 67.43 kHz; and
10 67.50 kHz. In each case, the audio is sampled at a rate which is at least double the fly-back frequency. Thus, for example, if a 96 kHz sampling rate is used instead of the 48 kHz rate described above, then any format associated with a fly-back frequency not exceeding 48 kHz may make use of the technique of this invention. In the case of the 67.50 kHz format, the sampling rate is at least 135 kHz.

15

[0027] While the present invention has been described with respect to what is presently considered to be the preferred embodiment, it is to be understood that the invention is not limited to the disclosed embodiments. To the contrary, the invention is intended to cover various modifications and equivalent arrangements included within
20 the spirit and scope of the appended claims. For example, it is to be understood that the invention is applicable to any audio frequency that can reliably be associated with the fact that a television is actually on, such as a motor spin of a video-cassette recorder (VCR), a tray ejection of a VCR, a motor spin of a digital video disk (DVD) player, a modem connected to the television, or static electricity emitted by the television screen.
25 As another example, although a ratio threshold of $R_{th} = 0.95$ is described above, the ratio threshold R_{th} may be set to a lower value such as 0.8 or 0.75 without reducing detection reliability. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

5

What is claimed is:

1. A television proximity sensor system, comprising:
10 an audio sensor disposed in a same room as a television, and configured to detect a predetermined audio signal emitted by the television when the television is on;
an analog-to-digital converter in communication with the audio sensor, and configured to convert the detected audio signal into a set of digital audio samples; and
a digital signal processor in communication with the analog-to-digital converter,
15 and configured to process the set of digital audio samples to determine (i) that the television is turned on, and (ii) that the television is turned off.
2. The sensor system of claim 1, further comprising an amplifier, the amplifier being electrically coupled to the audio sensor, the amplifier being configured to amplify
20 the detected audio signal and to provide the amplified signal to the analog-to-digital converter.
3. The sensor system of claim 1, wherein the digital signal processor is configured to:
25 measure a first power level of the set of digital audio samples at a first frequency;
measure a second power level of the set of digital audio samples at a second frequency;
measure a third power level of the set of digital audio samples at a third frequency;
30 compute a ratio of the first power level to a sum of the first, second, and third power levels;
compare the computed ratio to a predetermined first threshold value; and
when the computed ratio is greater than or equal to the first threshold value, determine that the television is turned on.
- 35 4. The sensor system of claim 3, wherein the digital signal processor is further configured to:

- 5 continuously update the measurements of the first, second and third power levels;
 compare the most recent measurement of the first power level to a predetermined second threshold value;
 when the first power level is greater than or equal to the second threshold value,
10 determine that the television is turned on; and
 when the computed ratio is less than the first threshold value and the first power level is less than the second threshold value, determine that the television is turned off.
5. The sensor system of claim 4, wherein the audio sensor is portable.
- 15 6. The sensor system of claim 3, wherein the digital signal processor is further configured to use a sliding Fast Fourier Transform algorithm to detect a presence of an audio signal at the first frequency.
- 20 7. The sensor system of claim 3, wherein the predetermined first threshold value is equal to substantially 0.9.
8. The sensor system of claim 3, wherein the predetermined first threshold value is greater than or equal to substantially 0.6.
- 25 9. The sensor system of claim 3, wherein the first frequency is associated with a horizontal scan fly-back transformer used by the television.
10. The sensor system of claim 9, wherein the horizontal scan fly-back transformer
30 is associated with a frequency equal to substantially 15.75 kHz.
11. The sensor system of claim 3, wherein the second and third frequencies have predetermined spacings from the first frequency.
- 35 12. The sensor system of claim 3, wherein the audio sensor is portable.
13. The sensor system of claim 1, wherein the audio sensor is portable.

5 14. An apparatus for determining whether a first television set is turned on, while distinguishing the first television set from other devices such as a radio or a second television set, the apparatus comprising:

 receiving means for receiving a predetermined analog audio signal
characteristic of the first television set being on;

10 digitizing means for converting the received analog audio signal to a set of digital audio samples;

 processing means for processing the set of digital audio samples; and

 determining means for using a result of the processing to determine that the first television set is turned on when the processed set of digital audio samples exceeds a
15 predetermined threshold.

15. The apparatus of claim 14, further comprising amplifying means for amplifying the received analog audio signal.

20 16. The apparatus of claim 14, wherein the processing means comprises:

 first measuring means for measuring a first power level of the audio signal at a first frequency;

 second measuring means for measuring a second power level of the audio signal at a second frequency;

25 third measuring means for measuring a third power level of the audio signal at a third frequency;

 computing means for computing a ratio of the first power level to a sum of the first, second, and third power levels; and

 first comparing means for comparing the computed ratio to a predetermined
30 first threshold value,

 wherein when the computed ratio is greater than or equal to the first threshold value, the determining means is configured to determine that the first television set is turned on.

35

17. The apparatus of claim 16, wherein the processing means further comprises:

 updating means for continuously updating the measurements of the first, second, and third power levels; and

- 5 second comparing means for comparing the most recent measurement of the first power level to a predetermined second threshold value,
 wherein when the first power level is greater than or equal to the second threshold value, the determining means is configured to determine that the first television set is turned on; and
- 10 when the first power level is less than the second threshold value and the computed ratio is less than the first threshold value, the determining means is configured to determine that the first television is turned off.
18. The apparatus of claim 17, wherein the receiving means is portable.
- 15 19. The apparatus of claim 16, the processing means further comprising transforming means for using a sliding Fast Fourier Transform algorithm to detect a presence of an audio signal at the first frequency.
- 20 20. The apparatus of claim 16, wherein the predetermined first threshold value is equal to substantially 0.9.
21. The apparatus of claim 16, wherein the predetermined first threshold value is greater than or equal to substantially 0.6.
- 25 22. The apparatus of claim 16, wherein the first frequency is associated with a horizontal scan fly-back transformer used by the first television.
23. The apparatus of claim 22, wherein the horizontal scan fly-back transformer is associated with a frequency equal to substantially 15.75 kHz.
- 30 24. The apparatus of claim 16, wherein the second and third frequencies have predetermined spacings from the first frequency.
- 35 25. The apparatus of claim 16, wherein the receiving means is portable.
26. The apparatus of claim 14, wherein the receiving means is portable.

- 5 27. A method of determining whether a television set is turned on and in near
proximity, the method comprising the steps of:
 receiving an analog audio signal corresponding to a transformer signal of the
television set;
 converting the received analog audio signal to a set of digital audio samples;
10 processing the set of digital audio samples; and
 using a result of the processing to determine whether the television set is turned
on and in near proximity.
- 15 28. The method of claim 27, further comprising the step of amplifying the received
analog audio signal.
- 20 29. The method of claim 27, wherein the step of processing comprises:
 measuring a first power level of the audio signal at a first frequency;
 measuring a second power level of the audio signal at a second frequency;
 measuring a third power level of the audio signal at a third frequency;
 computing a ratio of the first power level to a sum of the first, second, and third
power levels;
 comparing the computed ratio to a predetermined first threshold value; and
 when the computed ratio is greater than or equal to the first threshold value,
25 determining that the television set is turned on and in near proximity.
- 30 30. The method of claim 29, wherein the step of processing further comprises:
 continuously updating the measurements of the first, second, and third power
levels;
30 comparing the most recent measurement of the first power level to a
predetermined second threshold value;
 when the first power level is greater than or equal to the second threshold value,
determining that the television set is turned on and in near proximity; and
 when the first power level is less than the second threshold value and the
35 computed ratio is less than the first threshold value, determining that the first television
is turned off or out of proximity.

- 5 31. The method of claim 30, wherein the step of receiving an analog audio signal corresponding to a transformer signal of the television set comprises detecting the analog audio signal using a portable detecting device.
32. The method of claim 29, the step of processing further comprising the step of
10 using a sliding Fast Fourier Transform algorithm to detect a presence of an audio signal at the first frequency.
33. The method of claim 29, wherein the predetermined first threshold value is equal to substantially 0.9.
- 15 34. The method of claim 29, wherein the predetermined first threshold value is greater than or equal to substantially 0.6.
35. The method of claim 29, wherein the first frequency is associated with a
20 horizontal scan fly-back transformer used by the television set.
36. The method of claim 35, wherein the horizontal scan fly-back transformer is associated with a frequency equal to substantially 15.75 kHz.
- 25 37. The method of claim 29, wherein the second and third frequencies have predetermined spacings from the first frequency.
38. The method of claim 29, wherein the step of receiving an analog audio signal corresponding to a transformer signal of the television set comprises detecting the
30 analog audio signal using a portable detecting device.
39. The method of claim 27, wherein the step of receiving an analog audio signal corresponding to a transformer signal of the television set comprises detecting the analog audio signal using a portable detecting device.
- 35 40. A method of detecting whether a first television set is turned on, while distinguishing the first television set from other devices such as a radio or a second television set, the method comprising the steps of:

- 5 measuring a first power level of an audio signal at a first frequency, the first frequency being associated with a horizontal scan fly-back transformer used by the first television set;
- measuring a second power level of the audio signal at a second frequency and a third power level of the audio signal at a third frequency, the second and third
- 10 frequencies having predetermined spacings from the first frequency;
- computing a ratio of the first power level to a sum of the first, second, and third power levels;
- making a first comparison of the ratio to a predetermined threshold ratio value;
- and
- 15 making a first determination of whether the first television set is turned on based on a result of the first comparison.

41. The method of claim 40, further comprising the steps of:
- using a measured value of the first power level to set a threshold first power
- 20 value;
- continuously updating the measurements of the first, second, and third power levels; and
- when a first determination that the first television set is not turned on is made, making a second comparison of a most recently updated measurement value of
- 25 the first power level to the threshold first power value; and
- making a second determination of whether the first television set is turned on based on a result of the second comparison.

42. The method of claim 41, wherein the step of measuring a first power level of an
- 30 audio signal at a first frequency comprises detecting the audio signal using a portable detecting device.

43. The method of claim 40, wherein the step of measuring a first power level of an
- 35 audio signal at a first frequency comprises detecting the audio signal using a portable detecting device.