

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/076791 A1

(51) International Patent Classification⁷: **F02M 35/024**

(21) International Application Number: PCT/IB02/03574

(22) International Filing Date:
4 September 2002 (04.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
P00200200120 8 March 2002 (08.03.2002) ID

(71) Applicant and

(72) Inventor: **WIJAYA, Heru, Prasanta** [ID/ID]; Graha
Famili D.183, PR. Kali Kendal, Surabaya 60226 (ID).

(74) Agent: **PRIAPANTJA, Cita, Citrawinda**; Biro Oktroi
Roosseno, Kantor Taman A-9, Unit C1 - C2, Jl. Mega
Kuningan, Kuningan, Jakarta 12950 (ID).

(81) Designated States (*national*): AU, BR, CA, CN, IN, JP,
KR, MX, NZ, PH, SG, US, VN.


(84) Designated States (*regional*): Eurasian patent (AM, AZ,
BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE, SK, TR).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **KNOCKED-DOWN AIR FILTER FOR INTERNAL COMBUSTION ENGINE**



(57) **Abstract:** Efficiency leading to saving in transportation is a must at this competitive era. The choice of an automotive vehicle as a transportation means in mining, plantation, and forestry entails a special tactics in order to minimize the operational, maintenance and replacement cost of the air filter used in its internal combustion engines, especially the air filter whose entire parts should be replaced when its clogged filtering medium (7) is replaced. The air filter presently invented is a knocked-down air filter, i.e., an air filter whose part that should be replaced is its filtering medium (7) and inner mesh (6) only which are bound together by lower rubber (5) and upper rubber (8). Its other parts such as lower housing (1), upper housing (9), perforated plate (3) and reinforcing pile (4) are not necessarily replaced. A manually opened and closed locker (11) unite this knocked-down air filter as a single unit.