

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 October 2002 (31.10.2002)

PCT

(10) International Publication Number
WO 02/085573 A1

(51) International Patent Classification⁷: **B24C 7/00**, 1/04

William [GB/SG]; Blk 171, Bukit Batok West Avenue 8,
#20-355, Singapore 650171 (SG).

(21) International Application Number: PCT/SG02/00065

(74) Agent: **DREW & NAPIER LLC**; 20 Raffles Place,
#17-00, Ocean Towers, Singapore 048620 (SG).

(22) International Filing Date: 22 April 2002 (22.04.2002)

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:
200102219-3 21 April 2001 (21.04.2001) SG

(71) Applicant (*for all designated States except US*): **JETSIS INTERNATIONAL PTE LTD** [SG/SG]; 17 Hwa Yew Industrial Building, Mandai Estate, #06-1B, Singapore 729934 (SG).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): **GADD, Michael**,

[Continued on next page]

(54) Title: ABRASIVE FLUID JET SYSTEM



(57) Abstract: The invention provides an abrasive jet system having a high-pressure fluid supply (10) means supplying fluid to a vessel (11) which includes a layer of abrasive slurry and a top layer that contains substantially of fluid over the layer of abrasive slurry. The system also includes a first conduit (14) which leads from the fluid supply means to the top layer of fluid in the vessel and as high-pressure fluid is fed into the vessel, causes displacement of abrasive slurry from a discharge conduit (16). The system further includes a second conduit (21) which connects at different points to the first conduit and the discharge conduit, and including a fluid valve (13) between the operative connection to the first conduit and the discharge conduit, that controls the fluid flow within the second conduit. The fluid valve is closed once the system is pressurised to displace abrasive slurry through the discharge conduit (16) and is opened upon de-pressurization of the system to allow fluid flow from the first conduit (14) to the second conduit and to stop discharge of the abrasive slurry.



WO 02/085573 A1



(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*