

SPECIFICATION

A separable sliding clasp fastener

5 This invention relates to a sliding clasp fastener and more particularly to a separable type of sliding clasp fastener having a separable end stop assembly.

There are known a number of separable sliding clasp fasteners equipped with a separator assembly which comprises a socket member mounted on one of two companion stringers and a pin member mounted on the other stringer, the pin and socket members being releasably interengageable to couple the two stringers. When thus coupling the stringers, a slider functioning to close and open the fastener is brought against the socket member, and then the pin member is inserted through a channel in the slider into the socket member. The slider is thereafter moved along the confronting edges of the stringers to progressively take the fastener into closed disposition. Difficulty has been experienced in such instance with the prior art devices in maintaining the stop assembly in good shape against damage over extended periods of use, such difficulty being encountered particularly with the pin member which is susceptible to wear and rupture at and along its longitudinal edge merging with an integral sleeve portion.

According to the invention, there is provided a separable sliding clasp fastener comprising a pair of companion stringers having a fabric tape and a row of interlocking fastener elements mounted on a longitudinal edge of said tape, a slider having a flanged opening and taking the companion stringers into and out of engagement, and a separable end stop assembly comprising a pin member on one of said companion stringers and a socket member on the other stringer, said socket member having an opening dimensioned to collaterally receive said pin member, each said tape having an end portion raised above the general plane of the tape and anchored within said stop assembly, said pin member having a web integrally formed therewith and tapered such that said web has a thick region extending longitudinally of and adjacent said pin member and a thin region disposed remote from said pin member.

The invention will now be described by way of example with reference to the accompanying drawings, wherein:—

Figure 1 is a fragmentary plan view of a separable sliding clasp fastener provided in accordance with the invention;

55 Figure 2 is a fragmentary plan view of the separable sliding clasp fastener utilized to explain the manner of coupling or uncoupling the two companion stringer;

Figure 3 is an enlarged cross-sectional view taken on the line III-III of Figure 1;

Figure 4 is a fragmentary plan view of one of the two companion stringers having mounted thereon a preferred form of pin member according to the invention;

65 Figure 5 is an enlarged cross-sectional view taken

on the line V-V of Figure 4; and

Figure 6 is an enlarged cross-sectional view taken on the line VI-VI of Figure 4.

Referring now to the drawings and Figure 1 in particular, there is shown a separable sliding clasp fastener 10 which comprises a pair of companion stringers 11, 12 having oppositely disposed fabric tapes 13, 14 and rows of interlocking fastener elements E mounted on the confronting longitudinal beaded edges 13', 14' of the respective tapes 13, 14. The fastener elements E are shown for purposes of illustration to be in the form of a continuous helical coil having a succession of convolutions e each with a coupling head portion e' and are sewn as at 15 to the edge of the respective tape. The two companion stringers 11, 12 are taken into and out of meshing or interlocking engagement with each other by the manipulation of a slider 16 in the well known manner.

85 The stringers 11 and 12 are held together at their one ends by means of a separable end stop assembly generally designated 17 which is disposed to envelop cut-away portions 13'', 14'' of the tapes. The stop assembly 17 is shown for purposes of illustration as applied to the lower ends of the stringers 11, 12, and hence serves as a bottom end stop.

The separable end stop assembly 17 comprises a pin member 18 mounted on one stringer 11 and a socket member 19 mounted on the other stringer 12, the pin and socket members being releasably interengageable to couple the companion stringers 11, 12, in the well known manner.

The socket member 19 has a stud portion 20 extending from below the terminal end convolution e_2 of interlocking element row E to the region of the lower edge of its companion stringer 12. Formed integrally with the stud portion 20 is a socket portion 21 having an abutment 22 extending transversely beyond the beaded edge 14' of stringer 12 and coextensive with the rear end S_1 of the slider 16 such that the latter may be borne against the abutment 22 in the assembled relation of the pin and socket members 18, 19 when inserting the pin 18 into the socket 19 as shown in Figure 2. The socket portion 21 is provided with an opening 23 dimensioned to collaterally receive the pin member 18. Disposed oppositely to and parallel with the stud portion 20 is a similar stud portion 20', the two stud portions 20, 20' being interconnected by a web 24.

115 The pin member 18 extends longitudinally along its companion beaded edge 13' from below the end convolution e_1 to the region of the lower edge of its companion stringer 11. Disposed oppositely to and parallel with the pin member 18 is an L-shaped gripping portion 25 which is disposed to envelop a marginal edge 26 of the cut-away tape portion 13'' and which serves to allow finger-gripping when inserting the pin 18 into the socket 19. The pin 18 and the gripping portion 25 are interconnected by a reinforced web 27. The reinforced web 27 is tapered downwardly toward the gripping portion 25 so that it has a thick region 27a adjacent the pin 18 and a thin region 27b remote from the pin 18 or adjacent the gripping portion 25.

130 The pin member 18 has a bump 32 projecting

transversely slightly beyond the beaded edge 13', the bump 32 having a recess 33 dimensioned to receive the coupling head e' of the end convolution e_2 on stringer 12 in the assembled relation of pin 18 and socket 19.

It will be noted that the separable end stop assembly 17 is preferably made of a plastic material such that all of the various portions discussed of the assembly 17 can be conveniently moulded into the respective desired shapes and fused integrally with the fabric of the stringer tapes 13, 14. Designated at 34 is a reinforcing strip of film attached to the bottom portion of the respective tape 13, (14) over both surfaces thereof, and over which the separable stop assembly 17 are laid.

As shown in Figures 3 and 5, the cut-away marginal portions 13'' and 14'' of the respective tapes are partly raised above the general plane of the tape and anchored within the moulded separator assembly 17 with the total thickness of the stringers 11, 12 (Figure 5) not exceeding the thickness of the pin 18 and the stud 20 of the separator 17. This arrangement provides for strong bondage of the tape 13, (14) and the separator 17.

With this construction of the separable sliding clasp fastener according to the invention, the pin 18 is inserted into a channel S_2 of the slider 16, which has been held in abutted relation to the socket member 19, and thence into the opening 23 of the socket member 19. The insertion of the pin 18 is conveniently done by finger-gripping the integral L-shaped reinforcing portion 25. The pin member 18 advances unobstructedly with respect to the slider because the reinforced web 27 is reduced in thickness as at 27b where it registers with the region of flanged opening S_3 of the slider as shown in Figure 2. The pin member 18 further advances into the opening 23 of the socket member 19 until it comes into fully assembled engagement with the socket member 19 as shown in Figure 1, in which the pin member 18 is firmly retained in place with respect to the socket member 19. Because the web 27 is thickened as at 27a, this marginal portion is reinforced against repeated engaging and disengaging operation of the separator 17.

CLAIMS

1. A separable sliding clasp fastener comprising a pair of companion stringers having a fabric tape and a row of interlocking fastener elements mounted on a longitudinal edge of said tape, a slider having a flanged opening and taking the companion stringers into and out of engagement, and a separable end stop assembly comprising a pin member on one of said companion stringers and a socket member on the other stringer, said socket member having an opening dimensioned to collaterally receive said pin member, each said tape having an end portion raised above the general plane of the tape and anchored within said stop assembly, said pin member having a web integrally formed therewith and tapered such that said web has a thick region extending longitudinally of and adjacent said pin member and a thin region disposed remote from said pin member.

2. A separable sliding clasp fastener as claimed

in claim 1 wherein said pin member is interconnected by said web to an L-shaped gripping portion disposed adjacent said thin region of said web.

3. A separable sliding clasp fastener substantially as herein described with reference to and as illustrated in the accompanying drawings.

Printed for Her Majesty's Stationery Office by The Tweeddale Press Ltd., Berwick-upon-Tweed, 1982.
Published at the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.

transversely slightly beyond the beaded edge 13', the bump 32 having a recess 33 dimensioned to receive the coupling head e' of the end convolution e₂ on stringer 12 in the assembled relation of pin 18 and socket 19.

It will be noted that the separable end stop assembly 17 is preferably made of a plastic material such that all of the various portions discussed of the assembly 17 can be conveniently moulded into the respective desired shapes and fused integrally with the fabric of the stringer tapes 13, 14. Designated at 34 is a reinforcing strip of film attached to the bottom portion of the respective tape 13, (14) over both surfaces thereof, and over which the separable stop assembly 17 are laid.

As shown in Figures 3 and 5, the cut-away marginal portions 13" and 14" of the respective tapes are partly raised above the general plane of the tape and anchored within the moulded separator assembly 17 with the total thickness of the stringers 11, 12. (Figure 5) not exceeding the thickness of the pin 18 and the stud 20 of the separator 17. This arrangement provides for strong bondage of the tape 13, (14) and the separator 17.

With this construction of the separable sliding clasp fastener according to the invention, the pin 18 is inserted into a channel S₂ of the slider 16, which has been held in abutted relation to the socket member 19, and thence into the opening 23 of the socket member 19. The insertion of the pin 18 is conveniently done by finger-gripping the integral L-shaped reinforcing portion 25. The pin member 18 advances unobstructedly with respect to the slider because the reinforced web 27 is reduced in thickness as at 27b where it registers with the region of flanged opening S₃ of the slider as shown in Figure 2. The pin member 18 further advances into the opening 23 of the socket member 19 until it comes into fully assembled engagement with the socket member 19 as shown in Figure 1, in which the pin member 18 is firmly retained in place with respect to the socket member 19. Because the web 27 is thickened as at 27a, this marginal portion is reinforced against repeated engaging and disengaging operation of the separator 17.

CLAIMS

1. A separable sliding clasp fastener comprising a pair of companion stringers having a fabric tape and a row of interlocking fastener elements mounted on a longitudinal edge of said tape, a slider having a flanged opening and taking the companion stringers into and out of engagement, and a separable end stop assembly comprising a pin member on one of said companion stringers and a socket member on the other stringer, said socket member having an opening dimensioned to collaterally receive said pin member, each said tape having an end portion raised above the general plane of the tape and anchored within said stop assembly, said pin member having a web integrally formed therewith and tapered such that said web has a thick region extending longitudinally of and adjacent said pin member and a thin region disposed remote from said pin member.

2. A separable sliding clasp fastener as claimed

in claim 1 wherein said pin member is interconnected by said web to an L-shaped gripping portion disposed adjacent said thin region of said web.

3. A separable sliding clasp fastener substantially as herein described with reference to and as illustrated in the accompanying drawings.

Printed for Her Majesty's Stationery Office by The Tweeddale Press Ltd.,
Berwick-upon-Tweed, 1982.
Published at the Patent Office, 25 Southampton Buildings, London, WC2A 1AY,
from which copies may be obtained.



* C L M S *