

FRESH WATER GENERATION SYSTEM

Technical Field

[0001]

5 The present invention relates to a fresh water generation system.

Background Art

[0002]

10 Patent Literature 1 discloses that a fresh water generation system which performs the steps of: filtering microorganism treatment effluent produced from the waste water which contains organic substances and is to be microbiologically treated, via a primary semi-permeable membrane; mixing the resultant concentrated
15 water into seawater; and filtering the mixed water via a secondary semi-permeable membrane. Those steps allow an osmotic pressure of seawater to be reduced, resulting in the power saving of pump supply needed for the filtration step of the secondary-semi permeable membrane.

20 According to such a fresh water generation system, when a pressure loss of a semi permeable membrane apparatus having primary and secondary semi-permeable membranes reaches a predetermined value, the respective semi-permeable membranes (or reverse osmotic membranes) are chemically cleaned so as to remove microorganisms
25 treating waste water, the microorganisms adhering to the semi-permeable membranes. Herein, the pressure loss of the semi-permeable membrane apparatus represents a value calculated by subtracting a pressure of the concentrated water from a pressure of the injection water in the semi-permeable membrane apparatus.

30 [0003]

 In the meantime, even if a semi-permeable membrane is chemically cleaned, multiple times repeated chemical cleaning gradually increases a pressure loss of the semi-permeable membrane apparatus at the initial operation period just after each chemical

cleaning. This requires replacement of a semi-permeable membrane. Thus, the replacement timing of a semi-permeable membrane is determined, for example, at the time when a pressure loss of the apparatus reaches about 3-fold compared to the initial pressure loss thereof.

[0004]

Alternatively, a low biofouling semi-permeable membrane which prevents microorganisms of treating effluent from adhering to the membrane thereof has been developed recently. Herein, such a low biofouling semi-permeable membrane (for example, TORAY INDUSTRIES, INC.; TML 20 TYPE) is used for a primary semi-permeable membrane (or a semi-permeable membrane in an apparatus of treating waste water), which filters microorganism treating effluent in which microorganisms are easily cultivated; the microorganism treating effluent containing a lot of organic substances compared to seawater.

Citation List

Patent Literature

[0005]

[Patent Literature 1] Japanese Patent No. 4481345

Summary of Invention

Technical Problems to Be Solved by the Invention

[0006]

However, if such a low biofouling semi-permeable membrane is used for a primary semi-permeable membrane, the number of the microorganisms of treating effluent contained in the concentrated water increases. This may cause a drawback that a frequency of the operations for cleaning a secondary semi-permeable membrane (or a semi-permeable membrane in a seawater treatment apparatus) increases. Further, this also increases a frequency of replacing the secondary semi-permeable membrane.

[0007]

For example, if such a low biofouling membrane was used as a primary semi-permeable membrane, the primary and secondary semi-permeable membranes were chemically cleaned every three months in the primary and secondary semi-permeable membrane apparatuses as shown by the arrows "A" in FIG.3. Herein, each arrow "A" in FIG.3 points out reduction in a pressure loss of the semi-permeability apparatus, caused by the chemical cleaning thereof.

[0008]

Accordingly, so many times of the chemical cleaning results in the increased frequency of replacing the semi-permeable membrane, leading to a cost increase. Further, excess amounts of biocide are required to clean the primary and secondary semi-permeable membranes in order to suppress the frequent replacement of the semi-permeable membrane, leading to an inefficient system performance.

[0009]

From the viewpoint of the drawbacks as mentioned above, embodiments of the present invention is directed to the reduction in the frequency of the chemical cleaning and semi-permeable membrane replacement, thereby to provide a fresh water generation system having high efficiency from an economical viewpoint.

Means for Solving the Problems

[0010]

In a first aspect of the present invention, a fresh water generation system is provided, comprising a waste water treatment unit which microbiologically treats waste water containing organic substances; a primary semi-permeable membrane apparatus which separates biotreated water produced by microbiological treatment in the waste water treatment unit into permeated water and concentrated water via a primary semi-permeable membrane; and a secondary semi-permeable membrane apparatus which mixes seawater with the concentrated water of the primary semi-permeable membrane apparatus so as to filter the mixed water via a secondary semi-permeable membrane.

Herein, the primary and secondary semi-permeable membrane

apparatuses respectively house at least one semi-permeable membrane element. The semi-permeable membrane element used in the primary semi-permeable membrane apparatus has a higher microorganism adhesive property than the secondary semi-permeable membrane element.

[0011]

In a second aspect of the present invention, the fresh water generation apparatus comprises a waste water treatment unit which microbiologically treats waste water containing organic substances; a primary semi-permeable membrane apparatus which separates biotreated water produced by microbiological treatment in the waste water treatment unit into permeated water and concentrated water via a primary semi-permeable membrane; and a secondary semi-permeable membrane apparatus which mixes seawater with the concentrated water of the primary semi-permeable membrane apparatus so as to filter the mixed water via the secondary semi-permeable membrane.

Herein, the primary semi-permeable membrane has a higher microorganism adhesive property than the secondary semi-permeable membrane.

[0012]

In the first and second aspects of the present invention, it is preferable to intermittently inject biocide into the effluent treated by microorganisms, or to inject biocide into the mixed water composed of seawater and the concentrated water rejected by the primary semi-permeable membrane apparatus. Further, it is more preferable to increase a frequency of injecting the biocide into the mixed water, an injection amount thereof, or an injection concentration thereof, when the biocide is injected into the effluent treated by microorganisms together with the mixed water composed of seawater and the concentrated water rejected by the primary semi-permeable membrane apparatus.

[0013]

Moreover, it is preferable that the biocide is at least one typed biocide selected from a group of free chlorine based biocide, based biocide, bromine based biocide, an acid, and an alkali.

[0014]

If the biocide is injected, it is preferable not to mix at least a part of the concentrated water rejected by the primary semi-permeable membrane apparatus with seawater which is to be supplied into the secondary semi-permeable membrane apparatus. Further, it is preferable not to supply at least a part of the mixed water composed of seawater and the concentrated water to the secondary semi-permeable membrane.

[0015]

In the first and second aspects of the present invention, it is preferable that at least either of the primary and secondary semi-permeable membranes is a semi-permeable membrane which contains a polyamide or cellulose triacetate as a component thereof. Also, it is preferable that the microorganism is a hydrophobic microorganism.

[0016]

Furthermore, it is preferable that the primary semi-permeable membrane is a semi-permeable membrane which contains cellulose triacetate as a component thereof. Also, it is preferable that the hydrophobic microorganism is a Mycobacterium bacterium.

[0017]

In the first and second aspects of the present invention, it is preferable that a value representing the adhesive property of the microorganisms is equal to a B/F rate which defines a rate of the number of the microorganisms (B) respectively adhering to the primary semi-permeable membrane, the secondary semi-permeable membrane, the primary semi-permeable membrane element or the secondary semi-permeable membrane element against the number of the predetermined microorganisms (F). Herein, it is noted that the predetermined number of the microorganisms is brought into contact with the primary semi-permeable membrane, the secondary semi-permeable membrane, the primary semi-permeable membrane element or the secondary semi-permeable membrane element.

[0018]

Further, it is also preferable that the B/F rate of the primary semi-permeable membrane element is 2-fold or more than the B/F rate of the secondary semi-permeable membrane element. Alternatively, it is preferable that the B/F rate of the primary semi-permeable
5 membrane is 2-fold or more than the B/F rate of the secondary semi-permeable membrane.

[0019]

Further, in the first and second aspects of the present invention, it is preferable to arrange a filter for trapping
10 microorganisms; the filter separating the microorganisms included in the concentrated water rejected by the primary semi-permeable apparatus. Moreover, it is also preferable to arrange an ultrafilter which conducts ultrafiltration of mixed water comprised of seawater and the concentrated water rejected by the primary
15 semi-permeable membrane apparatus, at the period after mixing seawater with the concentrated water rejected by the primary semi-permeable membrane apparatus, and before filtering the mixed water via the secondary semi-permeable membrane.

20 Advantageous Effects of the Invention

[0020]

According to the present invention, the frequency of conducting the chemical cleaning of the semi-permeable membranes included in the whole system and the frequency of replacing the
25 semi-permeable membranes may be reduced. This advantageous effect allows the system to have more economical efficiency.

Brief Description of Drawings

[0021]

30 FIG. 1 is a block diagram showing a schematic construction of a fresh water generation system in an embodiment of the present invention.

FIG. 2 is a graphic diagram showing chemical cleaning timing of each semi-permeable membrane in the fresh water generation system

in an embodiment of the present invention.

FIG.3 is a graphic diagram showing chemical cleaning timing of each semi-permeable membrane in the fresh water generation system of COMPARATIVE EXAMPLE.

5 FIG.4 is a diagram showing a structure of a representative example of a semi-permeable membrane element of a spiral wound type.

Embodiments for Carrying Out the Invention

[0022]

10 Hereinafter, embodiments for carrying out the present invention will be explained in detail in reference to attached drawings. As shown in FIG. 1, a fresh water generation system 1 in an embodiment comprises a waste water treatment unit 3 and a seawater treatment unit 5. The waste water treatment unit 3 treats
15 waste water as raw water, derived from effluent which includes organic substances. The waste water treatment unit 3 comprises a membrane bioreactor (MBR) tank 7 and a primary semi-permeable membrane apparatus 9 having a primary semi-permeable membrane 8. Herein, influent water is transferred to the primary semi-permeable
20 membrane apparatus 9 by a pressure of a first pump 21.

Further, a biocide inlet 12 and a neutralizing agent inlet 15 are arranged between the membrane bioreactor tank 7 and the primary semi-permeable membrane apparatus 9. After biocide has been injected into the treated water of the membrane bioreactor tank
25 7 via the biocide inlet 12, a neutralizing agent is injected via the neutralizing agent inlet 15, thereby to reduce the biocide. Here, the biocide is hypochlorous acid and the neutralizing agent is sodium bisulfite. Accordingly, hypochlorous acid is reduced by sodium bisulfite so as to remove available chlorine. Then, the
30 resultant treated water is transferred to the primary semi-permeable membrane apparatus 9.

Note preferably the biocide is at least one typed biocide selected from a group of free chlorine based biocide such as hypochlorous acid, combined chlorine based biocide such as

chloramines, bromine based biocide such as DBNPA (2,2-dibromo-3-nitrilopropion amide), an acid such as sulfuric acid, and an alkali such as NaOH.

Further, if at least one biocide selected from a group of
5 combined chlorine based biocide, bromine based biocide, an acid and an alkali is used, the treated water to which the selected biocide has been injected may be directly supplied to the primary semi-permeable membrane apparatus 9. In such a case, the primary semi-permeable membrane 8 is not damaged, allowing the treated water
10 to be supplied without injecting the neutralizing agent thereto.
[0023]

The seawater treatment unit 5 comprises an ultrafiltration apparatus 11 having an ultrafiltration membrane (or UF membrane) and a secondary semi-permeable apparatus 13 having a secondary
15 semi-permeable membrane 14. The seawater is transferred to the ultrafiltration apparatus 11 by a pressure of a pump 22. Herein, the treated water of the ultrafiltration apparatus 11 is transferred to the secondary semi-permeable apparatus 13 by a higher pressure of a pump 23 than the pressure of the first pump 21.
20 [0024]

Hereinafter, operation and performance of the fresh water generation system in the present embodiment will be explained.

After the supplied raw water has been contacted with activated sludge in the membrane bioreactor tank 7, the resultant treated water
25 is filtered by a membrane separation unit thereby to separate biotreated water from the activated sludge. Then, the resultant biotreated water is supplied to the primary semi-permeable membrane apparatus 9 located downstream. Herein, a shape of the membrane bioreactor tank 7 is not specifically limited, as long as the
30 membrane bioreactor tank 7 has functions of: decomposing organic substances by the microorganism treatment; performing a solid-liquid separation using a membrane or the like; and hereby obtaining the biotreated water having few solid substances.

For example, the solid-liquid separation is performed by

gravitational sedimentation after the raw water has been treated by microorganisms in the activated sludge, and then the resultant supernatant may be treated by an UF membrane or a microfiltration membrane (or MF membrane) or the like.

5 [0025]

In the primary semi-permeable membrane apparatus 9, the supplied biotreated water is filtered via the primary semi-permeable membrane 8 to be separated into concentrated water and permeated water. Accordingly, the permeated water is obtained as treated
10 water. Then, the concentrated water of the primary semi-permeable membrane apparatus 9 is mixed with the treated water of the ultrafiltration apparatus 11 located in the seawater treatment unit 5.

[0026]

15 On the other hand, seawater is filtered as raw water via a UF membrane of the ultrafiltration apparatus 11 located in the seawater treatment unit 5. Herein, an MF membrane may be used instead of the UF membrane. Further, the ultrafiltration apparatus 11 may be replaced with a sand filter. After the filtrate has been
20 mixed with the above-mentioned concentrated water of the primary semi-permeable membrane apparatus 9, the mixed water is supplied to the secondary semi-permeable membrane apparatus 13.

Herein, it is preferable to inject at least one typed biocide into the mixed water, the biocide being selected from a group of
25 free chlorine based biocide, combined chlorine based biocide, bromine based biocide such as DBNPA, an acid and an alkali, similarly to the primary semi-permeable membrane.

Further, in the case that the biocide is selected from a group of combined chlorine based biocide, bromine based biocide, an acid
30 and an alkali, the mixed water to which the biocide has been injected causes no damage to the secondary semi-permeable membrane 14 even when the mixed water is to be supplied as it is to the secondary semi-permeable membrane apparatus 13. Therefore, it is more preferable to inject no neutralizing agent into the mixed water and

supply the resultant mixed water to the secondary semi-permeable membrane apparatus 13.

[0027]

5 The secondary semi-permeable membrane apparatus 13 treats the supplied mixed water via the secondary semi-permeable membrane 14 to separate the mixed water into concentrated water and permeated water. Accordingly, treated water is obtained from the permeated water.

[0028]

10 Herein, the treated water filtered in the membrane bioreactor tank 7 is intermittently injected with the biocide to sterilize the water.

Note when the biocide is injected via the biocide inlet 12, it is preferable to mix no concentrated water of the primary semi-permeable membrane apparatus 9 into the seawater treatment unit 5. The reason is that when the biocide is injected, it is assumed that a lot of microorganism dead bodies are included in the concentrated water of the primary semi-permeable membrane apparatus 9. Therefore, it is not preferable to supply such contaminated water to the seawater treatment unit 5.

[0029]

25 In the present embodiment, a semi-permeable membrane to which microorganisms more easily (or equally) adhere is used for the primary semi-permeable membrane 8 compared to the secondary semi-permeable membrane 14. This construction facilitates the microorganisms included in the concentrated water of the primary semi-permeable membrane apparatus 9 to be more easily trapped by the primary semi-permeable membrane 8. This results in the decrease in the number of the microorganisms included in the concentrated water.

30 Therefore, the number of microorganisms included in the mixed water which is to be supplied to the secondary semi-permeable membrane apparatus 13 is decreased. This enables the adhesion of the microorganisms to the secondary semi-permeable membrane 14 to

be decreased, resulting in the decrease in the frequency of conducting the chemical cleaning of the secondary semi-permeable membrane 14, and the frequency of replacing the membrane 14.

[0030]

5 The primary semi-permeable membrane 8 and the secondary semi-permeable membrane 14 may be any of semi-permeable membranes as long as each semi-permeable membrane has a desalination function like a reverse osmosis membrane (or RO membrane), a nanofiltration membrane (or NF membrane), and a loose reverse osmosis membrane.
10 Such a semi-permeable membrane may include variety types of membranes such as a hollow fiber membrane, a spiral membrane and a tubular membrane, or a composite membrane composed of an activated layer, a support layer and a substrate.

 Further, a polymer comprising a polyamide such as an aromatic
15 polyamide or cellulose triacetate as a component of the polymer, or a polymer composed of those components may be used for the primary semi-permeable membrane 8 and the secondary semi-permeable membrane 14.

[0031]

20 Here, the semi-permeable membrane made of cellulose triacetate as a main component thereof is particularly great biocide having a high bactericidal effect. Further, when such a semi-permeable membrane is used in combination with a semi-permeable membrane made of a polyamide as a main component thereof, "free
25 chlorine based biocide", which may cause damages to the semi-permeable membrane, may be used without problems. These features allow the above-mentioned biocide to be used for directly sterilizing microorganisms adhering to the semi-permeable membrane.

30 Accordingly, if a membrane which contains cellulose triacetate as a main component thereof (or membrane composed of cellulose triacetate) is applied to the primary semi-permeable membrane 8 that is dare to be designed such that hydrophobic microorganisms (or free microorganism) easily adhere to the membrane,

it is possible to use free chlorine based biocide which sterilizes the microorganisms in a highly effective manner, the microorganisms adhering to the semi-permeable membrane. This construction enables the biofouling effect to be highly increased.

5 [0032]

Further, the primary semi-permeable membrane 8 and the secondary semi-permeable membrane 14 may be composed of a single element, or a plurality of elements. Herein, the element includes a semi-permeable membrane to which raw water is supplied from one side surface of the semi-permeable membrane, and permeated water is obtained from the other side surface of the semi-permeable membrane. The element is constructed such that the membrane area is increased by bundling a lot of separation membrane elements with various shapes. This construction enables a lot of permeated water per unit element to be obtained.

For example, as shown in FIG.4, the spiral wound typed element has a structure in which both of a passage material at the supply side 43 for supplying the raw water 42 to the surface of the separation membrane 41 and a passage material at the permeated side 46 for introducing the permeated water permeated via the separation membrane are wound around a central pipe 45 for collecting and transferring permeated water 44 via a separation membrane 41. Here, the raw water 42 is supplied to the spiral wound typed element, allowing the raw water 42 to be separated into the permeated water 44 and the concentrated water 47.

[0033]

In the fresh water generation system in the above-mentioned embodiment, a low pressure semi-permeable membrane with 1.6 MPa (Toray Industries, Inc., TM720 TYPE: the B/F rate of the adhesive amount of hydrophobic microorganisms is 0.13) is used for the primary semi-permeable membrane 8. A high pressure semi-permeable membrane for desalting seawater with 5.5 MPa (Toray Industries, Inc., TM820 TYPE: the B/F rate of the adhesive amount of hydrophobic microorganisms is 0.13) is used for the secondary semi-permeable

membrane 14.

Here, FIG.2 is a graphic diagram showing fluctuations of pressure losses of the semi-permeable apparatuses when the fresh water generation system having the above-mentioned membranes was operated for one year.

[0034]

In the present invention, the property how easily the microorganisms adhere to the semi-permeable membrane is represented by the B/F rate measured in the following procedure.

After Mycobacterium strain BT12-100 of a hydrophobic microorganism was pre-incubated in the R2A medium, the strain was incubated in the sterilized MS medium that contained a radioisotope of $\text{Na}_2^{35}\text{SO}_4$ for 72 hrs using a rotary shaker (at 200rpm and 28°C). The MS medium comprised mannitol (1.0g), Na_2HPO_4 (0.75g), K_2HPO_4 (0.75g), NH_4Cl (1.0g), $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ (0.01g), $\text{CaCl}_2 \cdot 2\text{H}_2\text{O}$ (0.01g), $\text{FeSO}_4 \cdot 7\text{H}_2\text{O}$ (1mg), $\text{ZnSO}_4 \cdot 7\text{H}_2\text{O}$ (1mg), $\text{MnSO}_4 \cdot 4\text{H}_2\text{O}$ (1mg) per distilled water (1L). Then, a centrifugal separation process and a washing process in which a sterilized MS buffer solution prepared by removing mannitol from the components of the above-mentioned MS medium was used, were repeated twice.

After the processes were repeated, microorganisms were collected and the collected microorganisms were re-suspended in the sterilized MS buffer solution. At that time, the concentration of the microorganisms in the range of 5×10^9 - 10^{10} [cell/mL] was checked in a direct counting method via fluorescent microscope observation after the DAPI staining. If the concentration was out of the range, the concentration thereof was adjusted by again conducting the centrifugal separation process and adding the sterilized MS buffer solution. Then, the disintegration per minute (DPM) of the radioisotope [DPM/mL] in the adjusted microorganism suspension (here, the concentration of the microorganisms at that time was defined as C0 [cell/mL]) was analyzed by a liquid scintillation counter (LSC) (here, the DPM at that time was defined as DPM0 [DPM/mL]).

Next, a B/F rate of the semi-permeable membrane was determined by the following method. First, a bottom part of a sterilized plastic tube with a screw cap was cut off. At the cross-sectional surface of the cut tube, a semi-permeable membrane to be an evaluation target was attached such that a membrane functional layer was placed directed to inside the tube, and then the membrane was fixed thereon. At that time, the membrane area inside the plastic tube was defined as "A" [cm²].

Then, the inside of the plastic tube and the semi-permeable membrane were washed 10 times or more by sterilized pure water or RO permeated water. At that time, no leak of the washing water from the fixed place of the membrane was checked. Then, into the plastic tube, was added predetermined volume of a sterilized MS buffer solution. Then, was further added the microorganism suspension prepared as mentioned above (v [mL]) such that the concentration of the microorganisms was adjusted in the range from 1×10^8 to 5×10^8 [cell/mL]. Here, the liquid volume in the plastic tube was defined as V1 [mL] (herein, setting $v/A = 2.4$ to 2.5).

Next, the resultant plastic tube was sealed by the screw cap, and the microorganisms were incubated for 5 hrs in the rotary shaker (at 200rpm and 28°C). After the incubation, the liquid inside the plastic tube was disposed. The membrane was rinsed with the sterilized MS buffer solution (5.0 mL) twice and taken out. The taken out membrane was immersed in a DPM specific measurement solution and the DPM was analyzed by the LSC similarly to the previous case (herein, the DPM at that time was defined as DPM2 [DPM/mL]).

Next, based on the following equation, a B/F rate was calculated (where "B" represented the number of the microorganisms adhering to the membrane among the free microorganisms having the number of "F").

$$B/F = (DPM2 \times V2) / (DPM0 \times v)$$

[0035]

Further, a B/F rate of the element was determined by the following method. First, raw water to be evaluated was prepared

by adding the above-mentioned microorganism suspension to an MS buffer solution such that the concentration of the microorganisms was adjusted in the range from 1×10^8 to 5×10^8 [cell/mL]. Then, the DPM was analyzed by the LSC similarly to the previous cases (herein, the DPM at that time was defined as DPM0 [DPM/mL]).

The raw water to be evaluated was made to flow at a constant linear speed in the range from 0.4 to 0.5 m/s (for 5 hrs at 25 to 28°C), only at the primary side of the semi-permeable membrane element. In other words, it was set that the raw water flowed without permeating the membrane, while it only contacted with the membrane. After the procedure, the DPM in the raw water was analyzed by the LSC similarly to the previous cases (herein, the DPM at that time was defined as DPM3 [DPM/mL]).

Then, based on the following equation, a B/F rate was calculated.

$$B/F = (DPM0 - DPM3) / (DPM0)$$

[0036]

FIG. 2 is a graphic diagram in which the horizontal axis represents passed months and the vertical axis represents a pressure loss of the semi-permeable membrane. That diagram shows frequencies of the chemical cleaning for the primary semi-permeable membrane 8 and the secondary semi-permeable membrane 14.

As shown in FIG. 2, when the pressure loss of the semi-permeable membrane reached a predetermined value as pointed out by arrows "A", in each of the primary semi-permeable membrane apparatus 9 and the secondary semi-permeable membrane apparatus 13, the respective semi-permeable membranes were chemically cleaned. Herein, each arrow A indicates the lowering in the pressure loss of the semi-permeable membrane apparatus after conducting the chemical cleaning process.

[0037]

As it is apparent compared to the data in COMPARISON EXAMPLE of FIG. 3, conventionally the secondary semi-permeable membrane apparatus 13 required the chemical cleaning 5 times per about every

3 months or less. In contrast, the apparatus 13 only required the chemical cleaning totally 2 times per about every 6 months or more in the present embodiment. That is, according to the present embodiment, it was possible to reduce the frequency of the chemical cleaning for the secondary semi-permeable membrane 14 equal to or less than the half times in the conventional case. This also allowed the frequency of replacing the secondary semi-permeable membrane 14 to be reduced.

[0038]

On the other hand, the primary semi-permeable membrane apparatus 9 required the chemical cleaning every 2 months. This resulted in the increase in the frequency of the chemical cleaning, requiring 6 times per one year, which was more frequent than the conventional case requiring 6 times per one year. However, the frequency of the chemical cleaning in the whole fresh water generation system 1 was 7 times (see FIG. 2). This resulted in a marked reduction of the frequency compared to the frequency of 11 times chemical cleaning in COMPARATIVE EXAMPLE (see FIG. 3).

In the present embodiment, the primary semi-permeable membrane 8 and the secondary semi-permeable membrane 14 were objectively and easily selected by comparing the microorganism adhesive properties based on the B/F rates among the selection candidates.

It should be noted that a semi-permeable membrane with the B/F rate of 0.01 or less may be regarded as a low biofouling membrane (for example, TORAY INDUSTRIES, INC; TML20 TYPE), and distinguished from a general semi-permeable membrane. In this regard, the data of above-mentioned embodiment clearly indicated that when a general biofouling membrane with the B/F rate more than 0.01 was used for the primary semi-permeable membrane 8, it was demonstrated that the frequencies of the chemical cleaning of the secondary semi-permeable membrane 14, and the replacement of the membrane 14 were able to be reduced when compared to the data of COMPARATIVE EXAMPLE shown in FIG.3. Herein, note a low biofouling membrane with the B/F rate

of 0.01 or less was used for the primary semi-permeable membrane 8 in COMPARATIVE EXAMPLE.

[0039]

According to the present embodiment, it is possible to increase the biofouling effect of the secondary semi-permeable membrane 14 by injecting the biocide into the mixed water composed of seawater and the concentrated water separated from the primary semi-permeable membrane apparatus 9.

[0040]

According to the present embodiment, when the biocide is injected into the biotreated water, at least a part of the concentrated water separated from the primary semi-permeable membrane apparatus 9 is not mixed with the seawater to be supplied to the secondary semi-permeable membrane apparatus 13, or at least a part of the mixed water composed of the concentrated water and the seawater is not supplied to the secondary semi-permeable membrane apparatus 13.

This procedure may prevent the concentrated water to which the biocide has been injected thereby to contain a lot of microorganism dead bodies, from being supplied to the secondary semi-permeable membrane apparatus 13. Accordingly, it is possible to suppress the increase in the pressure loss of the secondary semi-permeable membrane apparatus 13 having the secondary semi-permeable membrane 14, the pressure loss being caused by the microorganism dead bodies. Therefore, it is possible to further reduce the frequencies of the chemical cleaning of the secondary semi-permeable membrane 14 and the replacement of the membrane 14.

[0041]

According to the present embodiment, a microorganism trap filter may be arranged, which removes the microorganisms in the concentrated water of the primary semi-permeable membrane apparatus 9 from the above-mentioned concentrated water. This construction may prevent the concentrated water which contains a lot of microorganisms from being supplied to the secondary semi-permeable

membrane apparatus 13. Further, in the present embodiment, at the period after the concentrated water of the primary semi-permeable membrane apparatus 9 has been mixed with seawater and before the resultant mixed water is to be filtered via the secondary
5 semi-permeable membrane 14, the mixed water composed of the concentrated water and the seawater may be treated by the ultrafiltration. This procedure may prevent the concentrated water which contains a lot of microorganisms from being supplied to the secondary semi-permeable membrane apparatus 13.

10 Thus, the above-mentioned construction may suppress the increase in the pressure loss of the secondary semi-permeable membrane apparatus 13 having the secondary semi-permeable membrane 14, the increase in the pressure loss being caused by a lot of microorganisms. Accordingly, it is possible to further reduce the
15 frequencies of the chemical cleaning for the secondary semi-permeable membrane 14 and the replacement of the membrane 14.

Note that a shape of the microorganism trap filter is not specifically limited as long as the microorganism trap filter is able to trap microorganisms.

20 [0042]

The present invention is not limited to the above-mentioned embodiment, and various modifications are possible without departing from the scope of the present invention. For example, in the above-mentioned embodiment, a semi-permeable membrane with
25 the same microorganism adhesive property as the secondary semi-permeable membrane 14 is used for the primary semi-permeable membrane 8. However, besides the above-mentioned membrane, a semi-permeable membrane having the more enhanced microorganism adhesive property than the secondary semi-permeable membrane 14 may
30 be used for the primary semi-permeable membrane 8. For example, it is possible to use the primary semi-permeable membrane 8 having the B/F rate of 0.15, and the secondary semi-permeable membrane 14 having the B/F rate of 0.13. Further, it is possible to use the primary semi-permeable membrane 8 having the B/F rate of 0.13, and

the secondary semi-permeable membrane 14 having the B/F rate of 0.01.
[0043]

As described hereinbefore, if the B/F rates of the primary and secondary semi-permeable membrane 8 and 14 were equal, the frequency of the chemical cleaning of the secondary semi-permeable membrane 14 was able to be set twice per one year.

In contrast, if the B/F rate of the primary semi-permeable membrane 8 is 2-fold or more than the secondary semi-permeable membrane 14, it is possible to reduce the frequencies of the chemical cleaning of the secondary semi-permeable membrane 14 and the replacement of the membrane 14 at most once a year. Thus, for example, it is possible to conduct the maintenance of the secondary semi-permeable membrane 14 by the routine chemical cleaning and routine replacement every one year, leading to the more excellent maintenance performance.

[0044]

Moreover, the waste water treatment unit 3 may first treat raw water at a settling basin before the raw water is supplied to the membrane bioreactor tank 7. Furthermore, the waste water treatment unit 3 is not limited to only use the membrane bioreactor tank 7. That is, after the waste water has been treated by the activated sludge, the waste water treatment unit 3 may settle the activated sludge. Alternatively, the waste water treatment unit 3 may conduct sand filtration for separation, thereby to obtain the biotreated water.

[0045]

The seawater treatment unit 5 may use a microfiltration (or MF) apparatus or sand filtration instead of the ultrafiltration apparatus 11.

List of Reference Signs

[0046]

- 1 Fresh Water Generation System
- 3 Waste Water Treatment Unit

5	Seawater Treatment Unit
8	Primary Semi-Permeable Membrane
9	Primary Semi-Permeable Membrane Apparatus
13	Secondary Semi-Permeable Apparatus
5	14 Secondary Semi-Permeable Membrane
	41 Semi-Permeable Membrane (or Separation Membrane)
	42 Raw Water
	43 Passage Material at Supply Side
	44 Permeated Water
10	45 Central Pipe
	46 Passage Material at Permeated Side
	47 Concentrated Water

Claims

[Claim 1]

A fresh water generation system comprising:

5 a waste water treatment unit which microbiologically treats waste water containing organic substances;

a primary semi-permeable membrane apparatus which separates biotreated water produced by microbiological treatment in the waste water treatment unit into permeated water and concentrated water
10 via a primary semi-permeable membrane; and

a secondary semi-permeable membrane apparatus which mixes seawater with the concentrated water of the primary semi-permeable membrane apparatus so as to filter the mixed water via a secondary semi-permeable membrane, wherein

15 the primary and secondary semi-permeable membrane apparatuses respectively house at least one semi-permeable membrane element, and

the semi-permeable membrane element used in the primary semi-permeable membrane apparatus has a higher microorganism adhesive property than the secondary semi-permeable membrane
20 element.

[Claim 2]

A fresh water generation system comprising:

a waste water treatment unit which microbiologically treats
25 waste water containing organic substances;

a primary semi-permeable membrane apparatus which separates biotreated water produced by microbiological treatment in the waste water treatment unit into permeated water and concentrated water via a primary semi-permeable membrane; and

30 a secondary semi-permeable membrane apparatus which mixes seawater with the concentrated water of the primary semi-permeable membrane apparatus so as to filter the mixed water via the secondary

semi-permeable membrane, wherein

the primary semi-permeable membrane has a higher microorganism adhesive property than the secondary semi-permeable membrane.

5 [Claim 3]

The fresh water generation system according to claim 1 or claim

2, further comprising a biocide inlet, wherein biocide is intermittently injected into the biotreated water by the biocide inlet.

[Claim 4]

5 The fresh water generation system according to claim 1 or claim 2, further comprising a biocide inlet, wherein biocide is injected into mixed water composed of seawater and the concentrated water of the primary semi-permeable membrane apparatus by the biocide inlet.

10 [Claim 5]

 The fresh water generation system according to claim 1 or claim 2, further comprising a biocide inlet which injects biocide into the biotreated water, and a biocide inlet which injects biocide into
15 the mixed water composed of seawater and the concentrated water of the primary semi-permeable membrane apparatus, wherein

 a frequency of injecting the biocide, an amount of the biocide, or a concentration of the biocide injected into the mixed water is
20 larger than those of the biocide injected into the biotreated water.

[Claim 6]

 The fresh water generation system according to claim 3, wherein

 the secondary semi-permeable membrane apparatus is configured
25 so that

 at least a part of the concentrated water of the primary semi-permeable membrane apparatus is not mixed with seawater which is to be supplied to the secondary semi-permeable membrane apparatus; or

30 at least a part of the mixed water composed of the concentrated water and the seawater is not supplied to the secondary semi-permeable membrane.

[Claim 7]

 The fresh water generation system according to claim 1,
35 wherein

at least either of the primary and secondary semi-permeable membranes is a semi-permeable membrane including a polyamide or cellulose triacetate as a component thereof; and

the semi-permeable membrane element used in the primary
5 semi-permeable membrane apparatus has a higher adhesive property of a hydrophobic microorganism than the secondary semi-permeable membrane element.

[Claim 8]

The fresh water generation system according to claim 7,
10 wherein the primary semi-permeable membranes is a semi-permeable membrane including cellulose triacetate as a component thereof.

[Claim 9]

The fresh water generation system according to claim 1,
15 wherein a value of a microorganism adhesive property is equal to a B/F rate which represents the number of the microorganisms (B) respectively adhering to the primary semi-permeable membrane element and the secondary semi-permeable membrane element, against the predetermined number of the microorganisms (F), when the
20 predetermined number of the microorganisms (F) is brought into contact with the primary semi-permeable membrane element and the secondary semi-permeable membrane element.

[Claim 10]

The fresh water generation system according to claim 9,
25 wherein a B/F rate of the primary semi-permeable membrane element is 2-fold or more than a B/F rate of the secondary semi-permeable membrane element.

[Claim 11]

The fresh water generation system according to claim 1 or claim
30 2, further comprising a microorganism trap filter which is configured to remove microorganisms included in the concentrated water of the primary

semi-permeable membrane apparatus, from said concentrated water.
[Claim 12]

The fresh water generation system according to claim 1 or claim 2, further comprising an ultrafiltration apparatus, wherein the
5 ultrafiltration apparatus includes an ultrafilter which is configured to conduct ultrafiltration of mixed water composed of seawater and concentrated water of the primary semi-permeable membrane apparatus, at a period after the concentrated water of the primary semi-permeable membrane apparatus has been mixed with
10 seawater and before the resultant mixed water is to be filtered via the secondary semi-permeable membrane.
[Claim 13]

The fresh water generation system according to claim 2, wherein
15 at least either of the primary and secondary semi-permeable membranes is a semi-permeable membrane including a polyamide or cellulose triacetate as a component thereof; and
the primary semi-permeable membrane has a higher adhesive property of a hydrophobic microorganism than the secondary
20 semi-permeable membrane.
[Claim 14]

The fresh water generation system according to claim 13, wherein the primary semi-permeable membrane is a semi-permeable membrane including cellulose triacetate as a component thereof.
25 [Claim 15]

The fresh water generation system according to claim 2, wherein a value of a microorganism adhesive property is equal to a B/F rate which represents the number of the microorganisms (B) respectively adhering to the primary semi-permeable membrane and
30 the secondary semi-permeable membrane, against the predetermined number of the microorganisms (F), when the predetermined number of the microorganisms (F) is brought into contact with the primary semi-permeable membrane and the secondary semi-permeable membrane.

[Claim 16]

The fresh water generation system according to claim 15, wherein a B/F rate of the primary semi-permeable membrane is 2-fold or more than a B/F rate of the secondary semi-permeable membrane.