

9606787-1

19053

copy

**PROCESSES FOR RECOVERING TOCOTRIENOLS,
TOCOPHEROLS AND TOCOTRIENOL-LIKE COMPOUNDS**

TECHNICAL FIELD OF INVENTION

5 The present invention relates to processes
for obtaining Tocol products, such as tocotrienols,
tocopherols and tocotrienol-like compounds from
biological sources in high yields. More particularly,
this invention relates to processes for stabilizing and
10 recovering Tocol products from plant materials, such as
cereals, grains and grain oils. The Tocol products
recovered according to this invention are useful in
pharmaceutical compositions, food formulations and
dietary supplements. These compositions, formulations
15 and supplements advantageously lower the blood level of
low density lipoproteins and total serum cholesterol in
humans and animals.

BACKGROUND OF THE INVENTION

Hypercholesterolemia is a causative agent of
20 diseases including arteriosclerosis, atherosclerosis,
cardiovascular disease and xanthomatosis. In addition,
high serum cholesterol levels are seen in patients
suffering from diseases including diabetes mellitus,
various liver disorders, such as hepatitis and
25 obstructive jaundice, familial hypercholesterolemia,
acute intermittent prothyria, anorexia nervosa,
nephrotic syndrome and primary cirrhosis. Improvement

This Sheet Has Been Replaced



- 2 -

of lipoprotein profiles has been shown to retard the progression of such diseases, as well as to induce regression of clinically significant lesions in hypercholesterolemic patients.

5 To date, several classes of therapeutic agents have been used in the treatment of hypercholesterolemia. The first class of therapeutics, directed at reducing cholesterol absorption from the blood, include cholestyramine, colestipol, colchicine,
10 neomycin, kanamycin, chloramphenicol, chlortetracycline and β -sitosterol. The utility of such compounds is often limited by serious and frequent side effects, including aberrations in digestive function and malabsorption of essential nutrients. Furthermore,
15 these drugs often induce a decrease in cholesterol absorption and an increase in cholesterol biosynthesis which, in turn, may effectively prevent or lessen the degree of total serum cholesterol reduction.

Agents which block the biosynthesis of
20 cholesterol constitute another class of hypocholesterolemic drugs. Such compounds include mevinnolin, synvinolin, eptastin, CPFB, atomid, methyl clofenapate, Su-13,437, halogenate, benzmalacene, DH-581 and MER-29. The administration of these
25 synthesis blockers often leads to a toxic build-up of cholesterol precursors in blood and tissues.

Other classes of drugs used to treat hypercholesterolemia include those which act upon plasma lipoproteins (i.e., nicotinic acid), bile acid
30 kinetics (i.e., choleic acid), β -adrenergic receptors (i.e., propranolol), endocrine systems (i.e., growth hormones) and those with yet undetermined modes of action (i.e., pyridoxine and inositol).

The reduction of cholesterol level achieved
35 by any of these classes of drugs is variable and rarely

This Sheet Has Been Replaced



exceeds 25%, while the incidence of side effects may significantly limit their use.

As an alternative to pharmaceutical treatment of hypercholesterolemia, surgical procedures, such as partial ileal bypass and manipulation of the digestive tract, have been employed (J. Sabine, Cholesterol, pp. 237-40, Marcel Dekker Inc., New York (1977)). Attendant with such treatments, however, are the risks associated with invasive procedures. Although exercise regimens and dietary intake restrictions have been shown to reduce cholesterol levels, patient compliance with these types of therapy is often sporadic or insufficient to effect clinical improvement.

There is a low incidence of cardiovascular disease in populations consuming large amounts of cereal grains. Soluble and insoluble fibers have, in the past, been viewed as the agents responsible for cholesterol reduction in such populations (see D. Kritchevsky et al., "Fiber, Hypercholesterolemia and Atherosclerosis", Lipids, 13, pp. 366-69 (1978)). More recently, however, the hypocholesterolemic effects of cereal grains have been attributed to natural components of the grains -- tocotrienols ("T₃") and structurally similar compounds, such as tocopherols ("T"). For example, in United States patent 4,603,142, d- α -tocotrienol, isolated from barley extracts, was identified as an inhibitor of cholesterol biosynthesis. See also A. Qureshi et al., "The Structure of an Inhibitor of Cholesterol Biosynthesis Isolated From Barley", J. Biol. Chem., 261, pp. 10544-50 (1986)). Tocotrienols and tocopherols occur naturally in small quantities in plant sources, such as rice bran, palm oil and barley.

Tocotrienols are of special interest as cholesterol lowering agents, because they decrease the



blood level of the low density lipoprotein fraction of cholesterol (LDL-cholesterol) and total serum cholesterol level, while increasing the ratio of the high density lipoprotein fraction of cholesterol (HDL-cholesterol) to LDL-cholesterol. Such effects are clinically significant, because HDL-cholesterol beneficially lowers the risk of heart disease (T. Gordon et al., "High Density Lipoprotein as a Protective Factor Against Coronary Heart Disease", The American Journal of Medicine, 62, pp. 707-14 (1977)).

Efforts to extract tocotrienols and tocotrienol-like compounds, such as tocopherols, from various grains, cereals and oils have resulted in the recovery of relatively small amounts of the desired compounds. For example, Canadian patent 480,484 refers to a method for preparing small amounts of tocopherol concentrates from a by-product of animal and plant oil processing called scum. Yields of tocopherols and tocotrienols according to United Kingdom patent application 2,090,836 are also low. It is believed that enzymes present in biological sources typically destroy tocopherols, tocotrienols and tocotrienol-like compounds during milling, extraction and other conventional processing techniques (see A. Qureshi et al., supra).

Accordingly, the need exists for processes which stabilize biological sources, thereby providing biological sources characterized by an increased content of tocotrienols, tocopherols and tocotrienol-like compounds and facilitating the isolation of tocotrienols, tocopherols and tocotrienol-like compounds from those sources in high yields.



SUMMARY OF THE INVENTION

The present invention solves the problems referred to above by providing processes for recovering T, T₂ and T₃-like compounds ("collectively referred to as Tocol products") from biological sources in high yields. By virtue of the present invention, crude biological materials containing Tocol products are treated to yield natural T, T₂ and T-like compounds, and Tocol-rich products containing them, in commercially feasible amounts, for a variety of uses. By virtue of the processes of this invention, the content of Tocol products in a biological source is enhanced.

The processes of this invention are characterized by a dry heat stabilization stage which stabilizes the biological source. According to one embodiment, this invention is characterized by a two-stage stabilization process, comprising a first dry heat stabilization step, followed by a second wet heat stabilization step.

The processes of this invention advantageously provide biological materials stabilized against enzymes, such as lipases, peroxidases, polyphenol oxidases, lipoxygenases and catalases, which would otherwise degrade the T, T₂ and T₃-like compounds contained therein. Furthermore, the processes of this invention facilitate the release of the T, T₂ and T₃-like compounds contained in the biological source yet constrained therein by interactions, such as hydrogen bonds, covalent bonds, ionic bonds and hydrophobic interactions. And the processes of this invention increase the solubility of the T₁, T₂ and T₃-like compounds contained in the biological source.



Accordingly, T, T₂ and T₃-like compounds are present in and may be recovered from biological materials stabilized according to this invention in higher amounts than those obtained using conventional techniques for processing biological materials or extracting Tocol products therefrom. Such stabilized natural materials, and the natural products recovered therefrom, are useful in the treatment and prevention of diseases attributed to high blood levels of LDL-cholesterol and total serum cholesterol. More particularly, the Tocol-rich products of the present invention are useful in pharmaceutical compositions, food formulations and dietary supplements to lower blood levels of LDL-cholesterol and total serum cholesterol, while increasing the ratio of HDL-cholesterol to LDL-cholesterol in the blood.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic of one embodiment of the processes of the present invention for preparing Tocol-rich stabilized and cooled rice bran from whole rice grain.

Figure 2 is a schematic of one embodiment of the processes of the present invention for extracting Tocol-rich oil from a Tocol-containing grain or other biological source. The products of this process are a Tocol-rich oil and a defatted, cooled biological source in which lysine, cysteine, B vitamins and other temperature sensitive components thereof have been preserved.

Figure 3 is a schematic of one embodiment of the processes of the present invention for treating Tocol-rich oil and separating that oil into refined and bleached rice oil, Tocol-rich products and free fatty acids.



DETAILED DESCRIPTION OF THE INVENTION

Biological source - Any natural or recombinant plant source, microbial source (e.g., bacteria), fungi, yeast, algae, higher plant source, or derivative thereof, which contains tocopherols (T), tocotrienols (T₃) or tocotrienol-like (T₃-like) compounds and which may be effectively stabilized by the processes of the present invention.

Stabilization - A process effective to enhance the content of tocopherols (T), tocotrienols (T₃) or tocotrienol-like compounds (T₃-like compounds) in a biological source by one or a combination of:

- (1) inactivating enzymes which are capable of degrading T, T₃ and T₃-like compounds in that biological source or
- (2) breaking bonds or otherwise interfering with interactions -- such as hydrogen bonds, covalent bonds, ionic bonds and hydrophobic interactions which bind the desired products to proteins, sugars, lipids, carbohydrates, membranes, glycoproteins, or combinations thereof, in the biological source -- which
- retain T, T₃ and T₃-like compounds in that biological source, thus facilitating the release of those desired compounds, or (3) increasing the solubility of the T, T₃ and T₃-like compounds of that biological source beyond that prior to stabilization or beyond the level of solubility of the T, T₃ and T₃-like compounds of a corresponding non-stabilized biological source or of a corresponding non-stabilized biological source treated according to conventional heat treatment processes or conventional stabilization processes. As a result of



stabilization, the content of T, T₂ and T₃-like compounds in a biological source is enhanced. Advantageously, therefore, T, T₂ and T₃-like compounds may be recovered from the stabilized biological source in higher yields than those realized from a corresponding non-stabilized biological source or a corresponding non-stabilized biological source treated according to conventional heat treatment processes or conventional stabilization processes. In a preferred embodiment of this invention, stabilization is effected by treating the biological source with heat.

Tocol or Tocol Products - A mixture of one or more compounds selected from tocopherols (T), tocotrienols (T₂) and tocotrienol-like (T₃-like) compounds.

Tocotrienol-like - Any biologically active compound which is contained in a biological source and (1) which is released, or whose release is facilitated, upon stabilizing that source or (2) whose content in that source is enhanced by stabilizing that source. Such tocotrienol-like compounds include any biologically active compound displaying the biological activity of a tocotrienol which inhibits the synthesis of HMGR as measured by an in vitro HMGR assay, such as that described in A.G. Gornall et al., J. Biol. Chem., 177, pp. 751-66 (1949). Tocotrienol-like compounds include, but are not limited to, trienols that are not tocotrienols and enols that are not trienols, any electron transfer ring compounds, anti-oxidant type compounds and compounds similar to or containing the tocotrienol side chain. Specific examples of T₃-like compounds are ubiquinones, plastoquinones, isoquinones, phylloquinones, unsaturated terpenoids and cyclic and acyclic, saturated and unsaturated isoprenoids.




TRF - A tocotrienol-rich fraction obtained by the stabilization of a biological source. It is characterized by an elution profile on HPLC of the recovered oils on silica columns (C18 columns) using a
5 hexane and isopropanol (99.74:0.34) eluant for an elution time of about .01 to 120 minutes. Detection is carried out by fluorescence monitoring at 295 nm and 330 nm or by monitoring at 280 UV to 295 UV.

Tocol-Rich Product - (1) A stabilized
10 biological source containing Tocol products or (2) Tocol products recovered from a stabilized biological source.

Enhanced - The Tocol content is increased beyond that of the biological source prior to
15 stabilization and, therefore, (1) Tocol products may be recovered from the stabilized source in higher yields than those realized from a corresponding non-stabilized source or a corresponding non-stabilized source treated according to conventional heat treatment
20 or stabilization processes or (2) Tocol products may be more soluble than they were prior to stabilization or more soluble than those of a corresponding non-stabilized source or more soluble than those of a non-stabilized biological source treated according to
25 conventional heat treatment or stabilization process.

The processes of the present invention permit the stabilization of biological sources containing T, T₂ and T₃-like compounds, so that the content of those Tocol products in the source is enhanced. As a result,
30 T, T₂ and T₃-like compounds may be recovered from those stabilized sources in high yields. According to one embodiment of this invention, biological materials are treated by dry heat, using reaction conditions which stabilize the materials without destroying the desired
35 T, T₂ and T₃-like compounds present therein. In a



- 10 -

preferred embodiment for rice bran, or another material having high peroxidase content or a high degree of fines, following this dry heat stabilization step, the biological materials are subjected to a wet heat
5 stabilization step, preferably carried out in sequence in the same apparatus as that used for the dry heat stabilization, under reaction conditions effective to further stabilize the materials without destroying the desired T, T₂ and T₃-like compounds.

10 Following stabilization, the Tocol-rich biological materials may be extracted and the Tocol products recovered therefrom in higher yields than those realized from non-stabilized materials or materials subjected to conventional heat treatment or
15 conventional stabilization processes. In turn, these materials may be processed using conventional methods such as, desolventization, deodorization, degumming, bleaching and refining, to yield an edible, extracted food product. Alternatively, the Tocol-rich products
20 are retained in the biological materials, which are then processed for consumption.

The processes of this invention may be used to treat all types of biological materials including, but not limited to, oats, wheat, rye, barley, brewers'
25 grain, soybean, wheat germ, wheat bran, corn, rice, cottonseed, flax, sesame, amaranth, rice bran, parboiled brown rice, brown rice flour, spit brewers' malt, vegetable oil distillate, fruit concentrate evaporate, barley bran, palm oil, wheat germ oil, rice
30 bran oil, brewers' grain oil, barley oil, coconut oil, cottonseed oil, soybean oil, other plant malts, other cereal grains and other cereal grain oils, plant tissues, leaves, stems, bark, roots, nuts and legumes, or portions thereof. Preferably, the biological source
35 is rice bran.

This Sheet Has Been Replaced



- 11 -

Advantageously, the biological source containing the T, T₂ and T₃-like compounds need not be subjected to any particular mechanical, chemical or enzymatic pre-treatment in order to permit recovery of those desired products. Optionally, however, materials to be treated may be produced, prepared or pre-treated by employing conventional techniques. Such techniques should be those which do not destroy the content of T, T₂ or T₃-like compounds in the biological materials.

10 In accordance with this invention, stabilization of biological materials is carried out using a combination of parameters of: (1) temperature (2) pressure (3) treatment time and (4) moisture in the stabilization apparatus.

15 Generally, during the dry heat or wet heat stabilization stage, conditions are as follows. The pressure should be in the range of about -30 inches Hg to about 10,000 PSI. The preferred pressure for dry heat stabilization is about 2,000 PSI and the preferred
20 pressure for wet heat stabilization is between about 800 and about 2,000 PSI. The temperature should be in the range of about 0°C to about 500°C. The preferred temperature for dry heat stabilization is between about 180°C and about 250°C and the preferred temperature for
25 wet heat stabilization is between about 100°C and about 150°C. The treatment time should be in the range of about 1 second to about 4 hours. The preferred treatment time for dry heat stabilization is between about 20 seconds and about 90 seconds and the preferred
30 treatment time for wet heat stabilization is between about 10 and about 60 seconds. The moisture level should be in the range of about 1% to about 95% -- i.e., the moisture level of the biological material is between about 1% and about 95% by weight. The
35 preferred moisture level for dry heat stabilization is

This Sheet Has Been Replaced

- 12 -

between about 5% and the preferred moisture level for wet heat stabilization is between about 15% and about 30%. It should be understood, however, that the specific choice within a range for a given parameter will depend upon one or more of the other parameters chosen, as well as the type of biological material to be stabilized.

As will be appreciated by a person of ordinary skill in the art, these parameters may be varied in concert from the ranges exemplified herein, while still providing a stabilized biological material. For example, if a desired temperature for stabilization is lower than the range specifically set forth herein, it may be employed in combination with a pressure, treatment time or moisture level greater than those illustrated, in order to stabilize a biological material. Accordingly, the present invention also includes various combinations of the four parameters of temperature, pressure, treatment time and moisture other than those illustrated herein, as long as those combinations result in the production of a stabilized biological material. This invention also contemplates combinations of less than all of these four parameters, as long as those combinations yield a stabilized biological material. The only constraints on such combinations are that the temperature, pressure, treatment time and moisture, or the combination thereof, should not be increased to a level which would result in destruction of the desired Tocol products, decomposition of the non-Tocol containing by-products or unwanted side reactions, such as oxidizing pyrolytic or Maillard reactions. It should also be understood that the optimal treatment conditions for stabilization will depend on factors such as the type and volume of

This Sheet Has Been Replaced

- 13 -

biological material to be treated and the form of the desired end product.

Any form of heat may be used to effect stabilization of the biological material. Accordingly, stabilization may be carried out using any conventional extruder, crop cooker, microwave, polarized microwave or other heating oven or cooker equipment. The choice of specific equipment may vary, depending upon the desired production scale, type of biological material to be treated, throughput, timescale, moisture content, operating environment and availability of electricity, steam and gas. Typically, stabilization may be carried out in any vessel in which provision has been made for the desired temperature, pressure, oxygenation, agitation, moisture and treatment time for the particular biological material. According to preferred embodiments of this invention, stabilization of a biological material is carried out in an Anderson extruder, a Wenger extruder or a polarized microwave apparatus. The use of heat as the agent for stabilizing biological materials may accelerate the oxidation of the desired T_1 , T_2 and T_3 -like compounds present in those materials. Accordingly, heat treatment should preferably be carried out under conditions that minimize or eliminate oxidative effects. Such conditions include the creation of a pressurized vacuum or the use of superheated steam, an inert gas or the evacuation of air in the heating equipment.

Following stabilization, the biological material is characterized by an increased content of Tocol products relative to the content of Tocol products in the starting material -- i.e., it is a Tocol-rich product. The total Tocol content of the stabilized biological material is typically increased



about 100% over that of the non-stabilized starting material. The Tocol content, measured in ppm, may be determined by conventional methods, such as those described in V. Piironen et al., "High Performance
5 Liquid Chromatographic Determination Of Tocopherols And Tocotrienols And Its Application To Diets And Plasma Of Finnish Men", Internat. J. Vit. Nutr. Res., 53, pp. 35-40 (1984) and B. Tan et al., "Separation Of Tocopherol And Tocotrienol Isomers Using Normal- And Reverse Phase
10 Liquid Chromatography", Anal. Biochem., 180, pp. 368-373 (1989).

In a preferred embodiment of this invention, the biological source is a plant material. Typically, the plant materials to be treated in the processes of
15 this invention are first selected and then harvested. Preferably, the plant source chosen contains low concentrations of enzymes, such as lipases, peroxidases, catalases, polyphenol oxidases and lipxygenases, which may begin to degrade the Tocol
20 products once the outer husk of the plant source is removed in the milling process. The concentration of these enzymes in the plant source may be determined, for example, using tributyrin under N₂, at pH 7.5 and 35°C.

25 After harvesting, the plant source is subjected to the process steps illustrated in Figure 1 for preparing Tocol-rich stabilized rice bran from rice whole grain, the most preferred plant source. Preferably, the stabilization process is initiated
30 within as short a time as possible after harvesting, so that enzymes in the unstabilized plant source do not begin to degrade the desired Tocol products. As shown in Figure 1, the first step for plant sources such as, for example, rice, wheat, rye, oats, flax, sesame and
35 amaranth, is to remove the husk, bran coat and germ



- 15 -

from the grain or seed by milling. For example, after removal of husks from whole rice grain, bran is then removed to provide white rice and rice bran products.

Following milling, enzymes present in

5 unstabilized plant sources, such as lipases, peroxidases, catalases, polyphenol oxidases and lipoxxygenases, may become active. In activated form, these enzymes cause the undesired alteration or destruction of the T, T₂ and T₃-like components of the

10 plant material. According to a preferred embodiment of this invention, therefore, plant materials are subjected to stabilization in one or two stages, immediately after milling. In each stage, stabilization is carried out under conditions effective

15 to do one or more of the following: (1) inactivate enzymes capable of destroying the Tocol products contained in the plant material, or (2) break bonds or otherwise interfere with interactions which retain T, T₂ and T₃-like compounds in the material, or

20 (3) increase the solubility of the T, T₂ and T₃-like compounds of that biological source beyond that prior to stabilization or beyond the level of solubility of the T, T₂ and T₃-like compounds of a corresponding non-stabilized biological source or of a corresponding non-

25 stabilized biological source treated according to conventional heat treatment processes or conventional stabilization processes.

When active, enzymes which are capable of destroying the Tocol products contained in the plant

30 material also cause a rapid build-up of free fatty acids (FFA) which in turn, can destroy T₂ and possibly the T₃-like compounds via a radical mechanism. The yield of T, T₂ and T₃-like compounds is optimized when the FFA content in the plant material is reduced to


35 about 4% or less. Preferably, the FFA content is zero.

This Sheet Has Been Replaced

FFA content may be monitored using the official AOCS method Ca Sa-40. Preferably, the FFA content in the plant material after stabilization is the same as that prior to stabilization. Immediate processing of the plant source after milling provides a stabilized product with a low FFA content and a high concentration of T, T₂ and T₃-like compounds.

The dry heat stabilization step typically inactivates lipases and other hydrolytic enzymes in the plant source. The subsequent wet stabilization stage primarily inactivates peroxidases and other oxidative enzymes in the plant source, as well as any other enzymes which become regenerated during storage of the plant source for a time between the dry heat stabilization stage and the wet heat stabilization stage.

The dry heat stabilization step may be carried out in any apparatus that accommodates the desired parameters of temperature, moisture, treatment time and pressure required to inactivate Tocol-destroying enzymes, to permit or facilitate the release of Tocol products from the plant source or to increase the solubility of the Tocol products. During the dry heat stabilization stage, FFA build-up increases with stabilization temperature. Therefore, lower temperatures and a short residence time in the apparatus are preferred. In one embodiment of this invention, a plant source is preferably dry stabilized in an extruder under the preferred parameters of temperature, treatment time, moisture and pressure. Some plant materials, such as grains and cereals, are preferably subjected to microwaving, or other heating, before or after extrusion, to increase the extraction rate and decrease the residence time in the heat providing apparatus, thereby facilitating recovery of



the desired Tocol products. Microwaving before or after extrusion may also aid in rupturing the cells of the plant source and minimizing enzymatic destruction or undesirable alteration of the Tocol products.

5 Since T, T₂ and T₃-like compounds present in plant sources are highly susceptible to oxidation during stabilization, a blanket of superheated steam, an inert gas, such as N₂, or a vacuum is used to protect the plant source from oxygen and, therefore, to
10 prevent high peroxide value (PV) from developing. Superheated steam is preferred, because it is readily available and can also serve as an even source of heat in the apparatus. During stabilization, PV may be monitored using official AOCS method Cd 8-53.

15 When the plant material to be stabilized is rice bran, or another material having high peroxidase content or a high degree of fines, following the dry heat stabilization step, the plant material is preferably further stabilized in a wet heat
20 stabilization step carried out under the preferred parameters of temperature, treatment time, moisture and pressure for wet heat stabilization. This wet heat stabilization step further reduces any residual enzyme activity that may cause destruction of T, T₂ and
25 T₃-like products in the stabilization apparatus. Additionally, the wet heat stabilization step may break bonds or otherwise interfere with interactions which retain T, T₂ and T₃-like compounds in the plant material or it may increase the solubility of the T, T₂ and
30 T₃-like compounds of that biological source beyond that prior to stabilization or beyond the level of solubility of the T, T₂ and T₃-like compounds of a corresponding non-stabilized biological source or of a corresponding non-stabilized biological source treated
35 according to conventional heat treatment processes or



- 18 -

conventional stabilization processes. In order to optimize overall recovery of T, T₂ and T₃-like products, the wet heat stabilization step is preferably carried out immediately following the dry heat stabilization step, in sequence, in the stabilization apparatus. However, depending on how the plant source is stored after dry heat stabilization, the wet heat stabilization can be postponed up to about one month. Optimal conditions for storage are those that do not permit regeneration of enzymes which have been inactivated in the dry heat stabilization step. Such conditions are those of low temperature and low moisture.

In the wet heat stabilization stage, moisture is introduced into the apparatus by means of water mixture, atomizing dispenser or condensing steam. As with the dry heat stabilization stage, wet heat stabilization is also carried out under a blanket of superheated steam, inert gas or vacuum. Superheated steam is preferred.

During wet heat stabilization, FFA build-up in plant material is more responsive to residence time in the stabilization apparatus than to temperature. Typically, the residence time of the plant material is between about 10 and about 500 seconds to minimize the occurrence of enzymatic activity before stabilization is completed. The preferred residence time is typically about 50 seconds, depending on pressure, temperature and moisture. These conditions insure the inactivation of any enzymes which remain active after the first dry heat stabilization stage and further aid in the release of Tocol products contained in the plant material.

Advantageously, collets are formed during the wet heat stabilization step. These serve to facilitate



- 19 -

the extraction of oil and significantly reduce the fine-content of that oil. Fines cause product loss and removing them makes the separation steps more difficult. This second stabilization step thus

5 minimizes the destruction of Tocol products and simplifies their recovery process. As in the dry heat stabilization step, microwaving the plant source before or after extrusion may aid in rupturing the cells of the plant source and minimizing enzymatic destruction

10 of the Tocol products.

In the second stabilization stage, the parameters of temperature, pressure, treatment time and moisture, may be varied in concert from the ranges illustrated herein, while still providing a stabilized

15 plant material. One of ordinary skill in the art can readily select a specific combination of treatment conditions, as long as those conditions are effective to inactivate Tocol-destroying enzymes, interfere with interactions which retain Tocol products in the plant

20 material, or both. In addition, the treatment conditions should not lead to destruction of the desired Tocol products, decomposition of the non-Tocol containing by-products or unwanted side reactions, such as oxidizing pyrolysis and Maillard reactions.

25 After a one or two stage stabilization, the stabilized plant source is cooled. The source may be cooled within tubes using cold water and a cold water blanket or a refrigerant or compressed gas. Preferably, cooling is accomplished with cold water in

30 the tubes of a cooler. The stabilized plant material is placed in the cooler and should be blanketed with an inert gas, such as N_2 , to prevent an increase in peroxide value of the Tocol-containing products. The resulting product is a Tocol-rich stabilized, cooled,

35 plant material. An example of one such product, as

This Sheet Has Been Replaced



- 20 -

shown in Figure 1, is a Tocol-rich stabilized, cooled rice bran.

After stabilization and cooling, further processing of the stabilized plant material is optional. Such processing is desirable when separating oil and Tocol products.

As illustrated in Figure 2, the Tocol products may be recovered from the Tocol-rich stabilized and cooled plant source at low temperatures, such as between about 5°C and 45°C, depending on the specific solvent, using conventional techniques and equipment, such as commercial solvent extraction. Preferably, the extraction is carried out at temperatures at or below about 35°C, as opposed to the temperatures of 50°C to 60°C used in conventional hexane methods. At the low temperatures maintained to recover the Tocol products from the stabilized plant source according to this invention, the yield of T₁, T₂, and T₃-like compounds is maximized. For example, the yield of Tocol products at cold extraction (about 21°C) is much higher than at hot extraction (60°C). Under such conditions, the residual meal of a plant source retains waxes without retaining the desired T₃ products. Waxes are difficult to remove from the T₃ products because they are non-polar compounds and are very similar in structure to T₃. Extraction is preferably conducted in a continuous extraction unit with an organic solvent such as, for example, propane, pentane, butane, hexane, heptane, ethyl alcohol, diethyl ether, ether and ethanol acetate. Extraction may be carried out, for example, in a Rotocal.

For plant sources such as soybean, cottonseed, wheat germ, corn germ and rice bran, the preferred organic solvent is pentane. With pentane, the boiling point is about 35°C and extraction can be

This Sheet Has Been Replaced



- 21 -

carried out at about 25°C, without creating an explosive hazard. With hexane, however, the boiling point is about 60°C and extraction cannot be carried out in a practical manner much below 50°C, without

5 allowing air to enter the extractor and thereby creating the risk of explosion. For extractions conducted at temperatures below about 25°C, other solvents, such as propane, heptane or ethyl alcohol, for example, 95% ethyl alcohol, can also be used.

10 Alternatively, pentane, hexane, heptane or ethyl alcohol, or mixtures thereof, may be used for extraction. The most preferred extraction solvent is a mixture of propane, butane and hexane. Advantageously, when this mixture of solvents is used, the stabilized

15 extraction temperature may be lowered to about 5°C.

Alternatively, a hexane-operating system may be wrapped with pentane or butane. This allows the extraction to be carried out at low temperatures -- down to 40°C with pentane and down to 5°C with butane.


20 In order to retain the Tocot products in the stabilized plant material, extraction is carried out at about 30°C or less for between about 15 to about 40 minutes. To maximize recovery of Tocot products from a stabilized plant material, while retaining the maximum

25 yield of Tocot products in the oil and a considerable quantity of waxes in the meal, extraction is carried out at about 5°C to about 45°C. The extraction time will depend on the material bed formed during extraction. Extraction may also be carried out using

30 supercritical conditions, such as supercritical carbon dioxide. Supercritical carbon dioxide extraction may be carried out under about 5 to about 15,000 PSI pressure at a temperature above about 31.6°C for approximately 1 minute. Preferably, extraction may be

35 carried out using supercritical carbon dioxide under

This Sheet Has Been Replaced



- 22 -

about 10,000 to about 12,000 PSI pressure for about 1 minute, after which the pressure is released.

For certain plant sources, the commercial feasibility of recovering Tocol-rich products at low
5 temperatures is increased if the extraction is preceded by cold pressing the stabilized plant source using a screw press under an inert gas blanket to reduce oil content from about 15-20% down to about 3.5-8.5%. Any remaining oil may then be extracted using cold ethanol,
10 methanol, isopropanol or another organic solvent at a temperature below about 25°C.

The products of extraction of a stabilized plant source are a mixture of solvent and a Tocol-rich oil and an extracted plant source which preferably
15 retains its nutritive value. The oil-solvent mixture is conventionally separated from the meal and solvent by a gravity drain. Then the solvent is evaporated and steam stripped. The recovered oil, depending on the temperature of extraction, contains a low concentration
20 of FFA and waxes and a high concentration of Tocol products. Advantageously, maintenance of cold temperatures during extraction leads to retention of FFA and waxes in the meal, and a high concentration of Tocol products in the oil.

25 Any residual solvent is removed from the extracted plant source using a vapor desolventizer-deodorizer, a flash desolventizer-deodorizer, or an equivalent system, using recirculated superheated vapor in the desolventizer stage to remove more than 95% of
30 the solvent from the extracted plant source. In the deodorizer stage, the system is typically operated in a pressure range of less than about 1 mm to 6 mm Hg. Preferably, the pressure is below about 1 atmosphere in order to remove solvent down to an acceptable level.
35 Preferably, less than 600 ppm solvent remains in the



- 23 -

extracted plant source after the desolventization stage. This assures minimum destruction of valuable products, such as lysine, cysteine, and B-vitamins contained in the meal.

- 5 The desolventized plant source is further cooled by conventional means, for example, by contacting it with air or by cooling with water in the tubes of the cooler. The desolventized extracted meal may be used as an edible source of lysine, cysteine,
- 10 B-vitamins and other essential nutrients. An inert gas, such as nitrogen, can be employed to maintain the mixture of solvents and gases in the apparatus below the explosive limit and also to help remove solvent from the meal. Sparge steam may also be introduced to
- 15 aid in the removal of solvent. Typically, the sparge steam is introduced counter current to the meal in order to remove the solvent to an acceptable level.

- The recovered Tocot-rich oil may also be processed further. For example, the oil may be
- 20 degummed. Degumming may be carried out, for example, by washing the oil with water, thereby dissolving the gummy substances in the water layer. And the oil may be bleached to remove colored bodies. Bleaching techniques involve heating the refined oil together
- 25 with an adsorbent powder, such as natural, or acid-activated bleaching earths, preferably with activated clay (clay to which non-compressible clay has been added as a filtering aid). As a result of bleaching, colored materials are physically adsorbed onto
- 30 activated clay, which is then filtered. Preferably, this step is carried out under vacuum to avoid oxidation of the oil and to improve bleaching efficiency.

- The bleached Tocot-rich oil may then be
- 35 subjected to physical refining techniques, reduced-

This Sheet Has Been Replaced

- pressure molecular distillation (preferably in the range of about 5 μ M Hg to about 6 mm Hg), or both, to provide a distillate containing only the Tocol products and FFA. Physical refinement techniques include low
- 5 pressure, high temperature vacuum distillation. During physical refinement, sparge steam is preferably used to remove the Tocol products and FFA from the oil. When physical refining is employed, molecular distillation is used to separate the FFA from the Tocol fraction.
- 10 Alternatively, either ethanol or methanol may be used to achieve phase separation with the oil. The alcohol can then be distilled off, thereby separating the FFA and Tocol products. Molecular distillation is preferred for recovering the Tocol products.
- 15 The tocopherol-rich fraction, tocotrienol-rich fraction and tocotrienol-like compound-rich fractions may be separated from the Tocol-rich products by any conventional technique used to separate chemical structures, such as supercritical extraction. A
- 20 preferred technique comprises passing the Tocol mixture through a silica gel column. Advantageously, the T_3 or T_3 -like products are retained on the silica gel, while the T products pass through and are collected. The T_3 or T_3 -like compounds may then be recovered by washing
- 25 the silica gel with an organic solvent such as diethyl ether, pentane, hexane, heptane, ethanol, methanol, or combinations thereof. The solvent is then evaporated using conventional means to yield purified T_3 or T_3 -like compounds.
- 30 In addition to a process for recovering Tocol-rich oil from stabilized biological sources, this invention also provides a process which yields a defatted, Tocol-rich stabilized biological source, preferably a plant source. For example, a polar
- 35 medium, such as supercritical CO_2 , may advantageously



- 25 -

be used to remove the oil products from a stabilized plant source while retaining most of the Tocol products in the meal. The operating conditions (i.e., temperature and pressure) can be adjusted to maximize the amount of Tocol retained in the defatted meal. This process may also be used to extract T_2 or T_3 -like compounds from Tocol-rich oil and to break down components of the T_2 fraction or T_3 -like compound fraction.

10 The Tocol-rich products obtained by the processes of this invention are useful in pharmaceutical compositions and food formulations. As used herein, the term "food formulation" refers to any food additive, dietary supplement, foodstuff, or edible composition suitable for consumption by humans and animals. Advantageously, these products are hypcholesterolemic and hypolipidaemic agents.

Pharmaceutical compositions may take the form of tablets, capsules, emulsions, suspensions and powders for oral administration, sterile solutions or emulsions for parenteral administration and sterile solutions for intravenous administration. The pharmaceutical compositions may be administered to humans and animals in a safe and pharmaceutically effective amount to substantially lower the blood level of LDL-cholesterol and total serum cholesterol. Hypercholesterolemic-related diseases which may be treated using such compositions include, but are not limited to, arteriosclerosis, atherosclerosis, xanthomatosis, hyperlipoproteinemias, and familial hypercholesterolemia.

These compositions may also be used to treat hypertension and to increase the production of insulin in Type 2 diabetic patients. In addition, these compositions are useful for prophylactic treatment of



- 26 -

those patients having multiple risk factors for hypercholesterolemia who are as yet asymptomatic.

The pharmaceutical compositions of this invention typically comprise a pharmaceutically effective amount of a Tocol-rich product of this invention and a pharmaceutically acceptable carrier. Therapeutic and prophylactic methods of this invention comprise the step of treating patients in a pharmaceutically acceptable manner with those compositions. As used herein, the term "pharmaceutically effective amount" or "cholesterol-lowering effective amount" refers to an amount effective to lower blood levels of LDL-cholesterol and total serum cholesterol, while increasing the ratio of HDL-cholesterol to LDL-cholesterol in the blood. Alternatively, the term "pharmaceutically effective amount" refers to an amount effective to prevent blood levels of LDL-cholesterol and total serum cholesterol associated with hypercholesterolemia, an amount effective to increase production of insulin in Type 2 diabetic patents or an amount effective to prevent or decrease hypertension.

The pharmaceutical compositions of this invention may be employed in a conventional manner for the treatment and prevention of hypercholesterolemia. Such methods of treatment and prophylaxis and their dosage levels and requirements are well-recognized in the art and may be chosen by those of ordinary skill in the art from available methods and techniques. The dosage and treatment regimens will depend upon factors such as the patient's health status, the severity and course of the patient's hypercholesterolemia or disposition thereto and the judgment of the treating physician.

This Sheet Has Been Replaced



The Tocol-rich products of this invention may also be used in combination with conventional therapeutics used in the treatment or prophylaxis of hypercholesterolemia. Such combination therapies
5 advantageously utilize lower dosages of those conventional therapeutics, thus avoiding possible toxicity incurred when those agents are used as monotherapies.

In food formulations, the Tocol-rich products
10 of this invention may be used in amounts and combined with any biologically acceptable carrier to provide a safe and effective means of substantially lowering blood levels of LDL-cholesterol and total serum cholesterol while increasing the ratio of
15 HDL-cholesterol to LDL-cholesterol. In addition, such food formulations may be used to increase production of insulin in Type 2 diabetics or to prevent or decrease hypertension. The Tocol-rich products of this invention may be combined with any foodstuff to produce
20 such food formulations. Tocol-rich oils obtained by the processes of this invention may be sprayed on foodstuffs, such as cereals. And Tocol-rich oils may be used as a cooking oil or a salad oil. Tocol-rich grains may be used in foodstuffs, such as baked goods,
25 cereals, pastas and soups.

The pharmaceutical compositions and food formulations of this invention may be administered to humans and animals such as, for example, livestock and poultry. Advantageously, livestock and poultry raised
30 on such foodstuffs may, in turn, constitute foodstuffs useful in the treatment or prophylaxis of hypercholesterolemia.

In order that this invention be more fully understood, the following examples are set forth.
35 These examples are for purposes of illustration only,



and are not to be construed as limiting the scope of the invention in any way.


In each example in which the FFA content was determined, it was so done using the official AOCS
5 method Ca Sa-40. The T and T₃ concentrations, recorded in ppm, were determined using the HPLC methods described in V. Piironen et al., "High Performance Liquid Chromatographic Determination Of Tocopherols And Tocotrienols And Its Application To Diets And Plasma Of
10 Finnish Men", Internat. J. Vit. Nutr. Res., 53, pp. 35-40 (1984) and B. Tan et al., "Separation Of Tocopherol And Tocotrienol Isomers Using Normal- And Reverse Phase Liquid Chromatography", Anal. Biochem., 180, pp. 368-373 (1989).

15 Example 1

Raw bran from freshly milled rice was collected in polybag-lined fiber drums and held for 24 hours at ambient temperature (32°C). After 24 hours, the free fatty acid content of the bran had risen to
20 2.4% or 11.0% on an oil basis (the oil comprised 22% w/w of the bran).

At 12-13% moisture, approximately 2,700 lbs. of the bran was fed into the #1 extruder head of a Wenger X-25 single screw extruder at a rate of 15
25 lbs/min. An operating pressure of 300-400 PSI and a discharge temperature of 162°C were maintained. The retention time of the extruder was approximately 30 seconds.

The bran was then ground to a fine powder
30 (approximately 200 mesh). Hexane was added and extraction was performed at room temperature (24°C) for 20 minutes. The hexane/oil mixture was decanted and then the hexane was evaporated under aspiration vacuum. The residual oil was then analyzed by HPLC.



- 29 -

The result of HPLC Tocol analysis is displayed in Table 1.

Example 2

Pre-stabilization and stabilization

5 conditions were as described in Example 1, except that the stabilization apparatus was an Anderson 8 inch single screw expander with a 5/16" x 1" die. At 12-13% moisture, approximately 540 lbs. of the bran was fed into the extruder at a rate of 3.2 lbs/min. No
10 steam or water injection was carried out. The screw rpm was 125, resulting in a discharge temperature of 96°C. The retention time was approximately 50 seconds.

Extraction was performed using the procedure detailed in Example 1.

15 The result of HPLC Tocol analysis is displayed in Table 1.

Example 3


Pre-stabilization and stabilization

conditions were as described in Example 2, except that
20 the stabilization apparatus was fitted with a 1/4" x 1" die to improve collet shape and the bran treated was a sample of approximately 360 lbs. In addition, steam was injected at the fourth bolt hole at a rate of 12 lbs/hr. The screw rpm was 275, resulting in a
25 discharge temperature of 107°C. The retention time was approximately 30 seconds.

Extraction was performed using the procedure detailed in Example 1.

The result of HPLC Tocol analysis is
30 displayed in Table 1.

This Sheet Has Been Replaced



Example 4

Pre-stabilization conditions and sample treated were as described in Example 1, except that the sample size was 2 lbs. No stabilization was carried
5 out.

Extraction was performed using the procedure detailed in Example 1.

The result of HPLC Tocot analysis is displayed in Table 1.

10

Example 5

Pre-stabilization conditions were as described in Example 1, except that the sample size was approximately 1800 lbs.

15 Stabilization was initiated within 5 minutes of bran removal in a Wenger X-25 extruder with a 5/16" x 1" die. The jacketing barrel was cooled with water to 121°C. No steam or water injection was carried out. The operating pressure was 800 PSI. The retention time was about 30 seconds.

20 Extraction was performed with hexane at 60°C until the residual oil weighed less than 1% of the total weight of the bran. The hexane/oil mixture was decanted. Then, the bran was washed with hexane and the combined hexane extracts were evaporated under
25 aspirator vacuum. The residual oil was washed with water to degum and was then analyzed by HPLC.

The FFA content was approximately 4% on an oil basis. The FFA content rose over time.

The result of HPLC Tocot analysis is
30 displayed in Table 1.

This Sheet Has Been Replaced



- 31 -

Example 6

Pre-stabilization and stabilization conditions and the stabilization apparatus were the same as in Example 5.

5 In this example, however, the jacketing barrel was not cooled, resulting in a stabilization temperature of 160°C. The retention time was about 30 seconds.

10 Extraction was performed using the procedure detailed in Example 5, except that the temperature was lowered to 21°C.

The FFA content was approximately 4% on an oil basis. The FFA content did not rise over a two month period.

15 The result of HPLC Tocot analysis is displayed in Table 1. As shown in that table, rice bran stabilized according to this invention produced an oil containing 4179 ppm of Tocot products ($T_1 =$ 2394 ppm and $T_2 =$ 1785 ppm). In contrast, unstabilized
20 rice bran produced an oil containing in the range of 25 ppm Tocot products (see Example 4).

Example 7


Pre-stabilization conditions and stabilization apparatus were the same as in Example 5.

25 Stabilization conditions were the same as Example 6, except that after 6 weeks, the bran was further wet stabilized in the same apparatus using 20% moisture at 113°C.

30 Extraction was performed using the procedure detailed in Example 5.

The FFA content was approximately 4% on an oil basis.

The result of HPLC Tocot analysis is displayed in Table 1.



Example 8

The wax fraction obtained by dewaxing crude rice bran was analyzed by HPLC to determine the amount of Tocol products remaining after the degumming and physical refinement steps.

The result of HPLC Tocol analysis is displayed in Table 1.

TABLE 1

10	<u>Example No.</u>	<u>[T + T₂] in oil</u> <u>(ppm)</u>
	1	331
	2	74
	3	73
	4	26
15	5	2512
	6	4179
	7	2497
	8	338 (T only)

As demonstrated in Table 1:

- 20 -- the ppm of T and T₂ products in the oil was optimized when stabilization was carried out immediately after milling;
- a high temperature dry stabilization stage was far superior to a low temperature dry stabilization stage;
- 25 -- stabilized bran yielded a higher degree of T and T₂ products in the recovered oil than unstabilized bran;
- a delay of 6 weeks between the dry and wet stage stabilizations allowed
- 30



- 33 -

enzymatic activity of the slower acting enzymes, such as the peroxidases to decrease T and T₂ content in the oil.

Example 9

5 The following is a typical protocol for carrying out this invention, using rice bran as the sample biological source.

 Rough rice (paddy rice) from a farm is dried in a commercial-type continuous flow, non-mixing,
10 heated air dryer. Drying is carried out to lower the moisture content of the rice a level of between about 18 and 22 percent to a level between about 10 and 13 percent. The dried rice is then cleaned by removing dust, stones, seeds and sticks by aspiration in a
15 commercial rice cleaning machine, followed by gravity separation in a stoner and particle size separation in a disk grader and a drum separator. The husks are then removed using a rubber roller sheller. Paddy (husks or hulls) were removed using a paddy separator for the
20 first pass, followed by a paddy separator for the second and third passes. The bran is then removed in a friction mill to yield polished rice. The raw bran is then pneumatically conveyed to the extruder or for storage until stabilization.

25 When stabilization is desired, the raw bran is pneumatically conveyed to a filter/sifter to remove residual broken rice. After sifting, the raw bran is pneumatically conveyed to a mixing/tempering hopper tank. The raw bran is conveyed from the discharge of
30 the mixing tank to the extruder inlet valve of a clamped barrel single screw) extruder by a metered screw conveyor feeder. The operating conditions of the extruder are maintained during stabilization in the following range:

35 flow rate: 900-2000 lbs/hr



- 34 -

pressure: 800-2000 PSI
temperature: 135°-180°C
time: 15-90 seconds.

The dry heat stabilized bran is then fed
5 directly into the feed hopper of an expander cooker.
Alternatively, the feed to the cooker may be raw bran
that has been cooled with dry ice. Within that
extruder, the bran is conveyed by a discontinuous worm
shaft toward the discharge plate at a rate of around
10 341 lbs/hr. Water and steam are added through
injection ports in the barrel of the extruder at a rate
of around 38 lbs/hr to completely mix the material and
to raise the moisture level. The ambient temperature
is about -3°C. Flow of the material is controlled by a
15 discharge die plate at a rate of about 341 lbs/hr. The
moisture level is maintained at about 114 lbs/hr and
the temperature is held between about 90° and 135°C for
between about 15 and 90 seconds.

As the bran is extruded through the die
20 plate, the sudden decrease in pressure causes the
liquid water to vaporize. During cooking, enzymes are
denatured and some constituents of the bran are
gelatinized into a fluid paste which binds the
particles together. A compact pellet is formed.
25 Vaporization of water caused breakage within the cells
ideally suited for solvent migration percolation. The
introduction of steam and water during the process
raises the moisture content of the bran to about 22-25
percent. The extruder discharge is then sent
30 downstream at a rate of around 341 lbs/hr. to a
dryer/cooler. Moisture flow was maintained at about 96
lbs/hr and the temperature is kept in the range of 82°C
to 130°C. The discharge from the dryer/cooler is
maintained at a rate of about 341 lbs/hr and at a

This Sheet Has Been Replaced




moisture level of about 30 lb/hr. These conditions allow for storage of the stabilized bran.

The stabilized bran is immersed in hexane in a ratio by weight of about two to one. Typically, about 10-100 g of material can be extracted using this protocol. The hexane is generally heated to about 60°C using a steam table incorporated into an explosion proof vented hood, but other solvents and other temperatures may also be employed. The hexane/oil miscella is removed from the bran by filtration. About 5-6 washings are necessary to bring the oil content of the bran to less than one percent. The defatted bran and the hexane/oil miscella are both desolventized under gentle heating with steam.

If 100-500 lbs. of stabilized bran is to be extracted, it is more practical to use the following protocol. The stabilized bran is fed into a counter-current extractor at a flow rate of about 111 lbs/hour. Fresh hexane is introduced at a rate of around 312 lbs/hr. The fresh solvent temperature is maintained at about 50°C, while the extractor temperature is maintained at around 52°C. The residence time in the extractor is typically around 45 minutes. The product is a defatted bran with an oil content of less than one percent. The hexane/oil miscella exiting the discharge of the extractor is filtered through a plate and frame filter press. The filtered miscella is then pumped to a steam heated still where the hexane is evaporated and collected by a condenser for reuse.

Following extraction and desolventization, crude rice bran oil is typically degummed, dewaxed, bleached and physically refined using steam distillation. Degumming is carried out by a two stage addition under agitation of 2% water by weight and then 0.15% phosphoric acid (85% reagent grade) by weight.



- 36 -

The temperature is held at about 82°C to 88°C for 10 minutes. Then the sludge containing the gums is removed via ultrafugation. (See United States patent 4,049,686). The degummed bran is cooled to about 5°C to 8°C and held for 24 hours. The dewaxed oils form a layer above the waxes which can be decanted using a vacuum pump. Bleaching is carried out according to the official AOCS method 6c 8a-52. Physical refining is carried out in a glass deodorizer at about 250°C and around 3 mm Hg for about 2 hours.

While we have described a number of embodiments of this invention, it is apparent that our basic constructions may be altered to provide other embodiments which utilize the processes and products of this invention. Therefore, it will be appreciated that the scope of this invention is to be defined by the appended claims, rather than by the specific embodiments which have been presented by way of example.

This Sheet Has Been Replaced



CLAIMS

We claim:

1. A process for enhancing the content of Tocol products in a biological source comprising the step of treating said source under conditions effective to stabilize it.

2. The process according to claim 1, further comprising the step of recovering the Tocol products from the stabilized source under conditions which do not destroy said products.

3. The process according to claim 2, further comprising the step of separating the recovered Tocol products into a tocotrienol-rich fraction, a tocopherol-rich fraction and a tocotrienol-like compound-rich fraction.

4. The process according to claim 1, wherein said biological source is stabilized by dry heat stabilization.

5. The process according to claim 1, wherein said biological source is stabilized by dry heat stabilization followed by wet heat stabilization.

6. The process according to claim 4 or 5, wherein said dry heat stabilization is carried out in an apparatus selected from the group consisting of extruders, microwaves, polarized microwaves, heating ovens and cookers.

7. The process according to claim 4 or 5, wherein said dry heat stabilization or said wet heat





- 38 -

stabilization is carried out at a temperature between about 0°C and about 500°C.

8. The process according to claim 7, wherein said dry heat stabilization is carried out at a temperature between about 150° and about 250°C.

9. The process according to claim 7, wherein said wet heat stabilization is carried out at a temperature between about 100°C and about 150°C.

10. The process according to claim 4 or 5, wherein said dry heat stabilization or said wet heat stabilization is carried out for a period of time between about 1 second and about 4 hours.

11. The process according to claim 10, wherein said dry heat stabilization is carried out for a period of time between about 20 seconds and about 90 seconds.

12. The process according to claim 10, wherein said wet heat stabilization is carried out for a period of time between about 10 seconds and about 60 seconds.

13. The process according to claim 4 or 5, wherein said dry heat stabilization or said wet heat stabilization is carried out at a pressure between about -30 inches Hg and about 10,000 PSI.

14. The process according to claim 13, wherein said dry heat stabilization is carried out at a pressure of about 2,000 PSI.



* C L H S *



- 39 -

15. The process according to claim 13, wherein said wet heat stabilization is carried out at a pressure of between about 800 and about 2,000 PSI.

16. The process according to claim 4 or 5, wherein said dry heat stabilization or said wet heat stabilization is carried out so that the moisture level of said biological source is between about 1% and about 95% by weight.

17. The process according to claim 16, wherein said dry heat stabilization is carried out so that the moisture level of said biological source is between about 5% and about 15% by weight.

18. The process according to claim 16, wherein said wet heat stabilization is carried out so that the moisture level of said biological source is between about 15% and about 30% by weight.

19. The process according to claim 4 or 5, wherein said dry heat stabilization is carried out under an inert gas, superheated steam or a vacuum.

20. The process according to claim 4 or 5, wherein said biological source is microwaved prior to or after said dry heat stabilization.

21. The process according to claim 2, wherein said Tocol products are recovered from said stabilized biological source by solvent extraction using an organic solvent.

22. The process according to claim 21, wherein said organic solvent is selected from the group





consisting of hexane, pentane, hexane and mixtures thereof.

23. The process according to claim 2, wherein said Tocol products are recovered from said stabilized biological source by cold pressing the source to obtain an oil containing said products.

24. The process according to any one of claims 1 to 3, wherein said biological source is a plant source.

25. The process according to any one of claims 1 to 3, wherein said biological source is selected from the group consisting of cereal grains, cereal grain oils, cereal brans, leaves, stems, brak, roots, legumes, nuts, microbes, yeasts, fungi and algae.

26. The process according to claim 25, wherein said biological source is selected from the group consisting of oats, oat bran, barley, barley bran, rice and rice bran.


27. A biological source stabilized by the process according to claim 1.

28. A Tocol product recovered by the process according to claim 2.

29. A tocotrienol-rich fraction produced by the process according to claim 3.

30. A tocotrienol-like compound-rich fraction produced by the process according to claim 3.





- 41 -

31. The biological source according to claim 27, said biological source being characterized by a Tocol product content of at least about 100% that of the non-stabilized source.

32. A biological source obtainable by a process comprising the step of treating a biological source containing Tocol products under conditions effective to stabilize said source.

33. A Tocol product obtainable by a process comprising the steps of:

(a) treating a biological source containing Tocol products under conditions effective to stabilize said source; and

(b) recovering the Tocol products from the stabilized source under conditions which do not destroy said products.

34. A tocotrienol-rich fraction obtainable by a process comprising the steps of:

(a) treating a biological source containing Tocol products under conditions effective to stabilize said source;

(b) recovering the Tocol products from the stabilized source under conditions which do not destroy said products; and

(c) separating from the recovered Tocol products a tocotrienol-rich fraction.

35. A tocotrienol-like compound-rich fraction obtainable by a process comprising the steps of:





WO 91/17985

- 42 -

(a) treating a biological source containing Tocol products under conditions effective to stabilize it;

(b) recovering the Tocol products from the stabilized source under conditions which do not destroy said products; and

(c) separating from the recovered Tocol products a tocotrienol-like compound-rich fraction.

36. A pharmaceutical composition for treating or preventing hypercholesterolemic-related diseases comprising a Tocol product according to claim 28 or 33 and a pharmaceutically acceptable carrier.

37. A pharmaceutical composition for treating or preventing hypercholesterolemic-related diseases comprising a biological source according to claim 27 or 32 and a pharmaceutically acceptable carrier.

38. A pharmaceutical composition for treating or preventing hypercholesterolemic-related diseases comprising a tocotrienol-rich fraction according to claim 29 or 34, and a pharmaceutically acceptable carrier.

39. A pharmaceutical composition for treating or preventing hypercholesterolemic-related diseases comprising a tocotrienol-like compound-rich fraction according to claim 30 or 35, and a pharmaceutically acceptable carrier.

40. A foodstuff comprising a Tocol product according to claim 28 or 33.



* C L M S *



41. A feedstuff comprising a biological source according to claim 27 or 32.

42. A feedstuff comprising a tocotrienol-rich fraction according to claim 29 or 34.

43. A feedstuff comprising a tocotrienol-like compound-rich fraction according to claim 30 or 35.

44. A dietary supplement comprising a Tocol product according to claim 28 or 33.

45. A dietary supplement comprising a biological source according to claim 27 or 32.

46. A dietary supplement comprising a tocotrienol-rich fraction according to claim 29 or 34.

47. A dietary supplement comprising a tocotrienol-like compound-rich fraction according to claim 30 or 35.

48. A method for treating or preventing hypercholesterolemic disease in a patient comprising the step of administering to said patient a pharmaceutically effective amount of pharmaceutical composition according to any one of claims 36-39.

49. A method for decreasing the levels of total serum cholesterol and LDL-cholesterol in a human or animal comprising the step of administering to said human or animal a cholesterol-lowering effective amount of a feedstuff according to any one of claims 40-43.



50. The process according to claim 2, wherein said Tocol products are recovered from said stabilized biological source by solvent extraction using a hexane-operating system wrapped with pentane or butane.

This Sheet Has Been Replaced

