9705609-7
RTMP'S COPY

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61M 5/14 — A1

(11) International Publication Number: WO 96/22118

(43) International Publication Date: 25 July 1996 (25.07.96)

(21) International Application Number: PCT/US96/00708

(22) International Filing Date: 18 January 1996 (18.01.96)

(30) Priority Data:
08/375,849 20 January 1995 (20.01.95) US

(60) Parent Application or Grant
(63) Related by Continuation
US 08/375,849 (CIP)
Filed on 20 January 1995 (20.01.95)

(71)(72) Applicants and Inventors: WILSON, Roland, B., Jr. [US/US]; 286 North Wabash Street, P.O. Box 725, Wabash, IN 46992 (US). WILSON, Glenda, A. [US/US]; 286 North Wabash Street, P.O. Box 725, Wabash, IN 46992 (US).

(74) Agent: McNEIL, Michael, B.; Lieli & McNeil, 81 East Hill Street, Wabash, IN 46992 (US).

(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

06 JUL 1998

(54) Title: ANTI-CROSS CONTAMINATION VALVE AND FLUID DELIVERY SYSTEMS USING SAME

(57) Abstract

An anti-cross contamination valve (30) for use in medical fluide delivery systems comprises a valve housing (42) having a first port (34), a second port (35), and a third port (36) that open into a hollow interior (41). A valve body (31) is rotatably mounted within the hollow interior (41) and has at least one fluid passageway therethrough. A knob (32) is attached to the valve body (31) and extends outside of the valve housing (42). At at least one fluid passageway opens the first port (34) to the third port (36) when the valve body (31) is rotated to a first position, and the second port (35) opens to the third port (36) when the valve body (31) is rotated to a second position. In order to prevent the possibility of cross contamination, the valve includes stop barriers (38) and/or a special passageway/port geometry that prevents the possibility of the first port (34) coming into fluid communication with the second port (35), or vice versa.

