



159159

- 1 -



G00002

ELECTRONIC APPARATUS AND TERMINAL

FIELD

Embodiments described herein relate generally to an authentication technique capable of authenticating a plurality of devices by cooperation of the devices.

BACKGROUND

The Global System for Mobile Communications (GSM) is a wireless communication system used for digital cellular telephony. As means having a function of carrying out authentication of a user on the GSM network, and effective accounting management, a Subscriber Identity Module (SIM) is known. As a technique for utilizing the authentication function of the SIM for wireless LAN service, there is an Extensible Authentication Protocol Method for GSM Subscriber Identity Module (EAP-SIM). It should be noted that EAP is a protocol obtained by extending the mechanism of Point-to-Point Protocol (PPP) used in the Internet, and intended for wireless LAN.

Incidentally, in the EAP-SIM, although a protocol is defined between a supplicant corresponding to a data device, and authenticator corresponding to certification authority, this is a protocol corresponding to a configuration having one supplicant and one authenticator.

Accordingly, when a plurality of supplicants are present, although the authenticator needs to execute

the aforementioned authentication operation for each of the supplicants, then each of the plurality of supplicants has to carry out an authentication operation together with the authenticator at independent timing, and it is difficult to assure an effective authentication operation due to, for example, signal conflict, repetition of a duplicate operation, and the like.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exemplary signal delivery/receipt chart showing a procedure in which two supplicants cooperate with each other to execute an authentication operation together with an authenticator according to an embodiment.

FIG. 2 is an exemplary signal delivery/receipt chart showing a procedure in which three supplicants cooperate with each other to execute an authentication operation together with an authenticator according to the embodiment.

FIG. 3 is an exemplary signal delivery/receipt chart showing a procedure in which three supplicants cooperate with each other to execute an authentication operation together with an authenticator according to the embodiment.

FIG. 4 is an exemplary signal delivery/receipt chart showing a procedure in which three supplicants cooperate with each other to execute an authentication

operation together with an authenticator according to the embodiment.

FIG. 5 is an exemplary view for explaining an example in which the authentication system is applied to power supply service for an electric vehicle according to the embodiment.

FIG. 6 is an exemplary signal delivery/receipt chart showing a procedure in which two supplicants cooperate with each other to execute an authentication operation together with an authenticator according to a second embodiment.

FIG. 7 is an exemplary signal delivery/receipt chart showing a procedure in which two supplicants cooperate with each other to execute an authentication operation together with an authenticator according to a third embodiment.

DETAILED DESCRIPTION

In general, according to one embodiment, an electronic device connected to an authentication device through a first communication network, and further connected to another electronic device through a second communication network executes authentication of the electronic device and another electronic device by data delivery/receipt conforming to a predetermined procedure between the electronic device and the authentication device through the first communication network, and data delivery/receipt between the

electronic device and another electronic device through the second communication network.

[First Embodiment]

Hereinafter, this embodiment will be described
5 below in detail with reference to the drawings.

FIG. 1 is an exemplary signal delivery/receipt chart showing a procedure in which two supplicants of this embodiment cooperate with each other to execute an authentication operation together with an
10 authenticator.

In the procedure shown in FIG. 1, an authenticator 1, mobile terminal 2, master supplicant 3, and slave supplicant 4 execute signal delivery/receipt.

The authenticator 1 and mobile terminal 2 can
15 communicate with each other through a GSM (for example, a cellular line). However, the communication system between the authenticator 1 and mobile terminal 2 is not limited to GSM. Further, the mobile terminal 2 has a communication function different from the cellular
20 line, for example, a wireless communication function of a short distance, wireless LAN (WLAN) function or the like, and can also function as an access point (AP).

The master and slave supplicants 3 and 4 each have a SIM function, and function of a wireless LAN slave
25 unit. The master supplicant 3 and slave supplicant 4 can communicate with each other through the wireless LAN. However, the communication system of the master

supplicant 3 and slave supplicant 4 is not limited to the wireless LAN, and it is sufficient if the supplicants 3 and 4 can be connected to each other by any communication system. Accordingly, the master and slave supplicants 3 and 4 can be ascertained as communication devices each of which is provided with a securing function.

Next, a procedure for signal delivery/receipt for authentication will be described below. It should be noted that the signal delivery/receipt procedure will be described in conformity with the specification of IEEE 802.1X to correspond to the two roles of the "supplicant" and "authenticator".

When the mobile terminal 2 and master supplicant 3 are connected to each other through a wireless LAN in a state where the mobile terminal 2 can communicate with the authenticator 1, the master supplicant 3 transmits an EAPOL-Start signal in step S01 to the authenticator 1 through the mobile terminal 2 in accordance with the EAP-SIM authentication procedure.

It should be noted that the mobile terminal 2 bears a function of transferring a signal to/from the master supplicant 3 from/to the authenticator 1 which are different from each other in communication system. Accordingly, in the procedure after this, the operation of the mobile terminal 2 will not be mentioned, and a description will be given on the assumption that the

authenticator 1 and each of the master and slave
supplicants 3 and 4 directly carry out signal
delivery/receipt.

5 In step S02, the authenticator 1 which has
received an EAPOL-Start signal transmits an EAP-
Request/Identity signal to the master supplicant 3, and
master supplicant 3 which has received the signal
transmits an EAP-Response/Identity signal.

10 In step S03, the authenticator 1 which has
received the EAP-Response/Identity signal starts
authentication processing, and transmits an EAP-
Request/SIM/Start signal to the master supplicant 3.
Further, an EAP-Response/SIM/Start signal which is a
response signal to the EAP-Request/SIM/Start signal is
15 received from the master supplicant 3.

In step S04, the authenticator 1 transmits an EAP-
Request/SIM/Challenge signal to the supplicant 3 in
order to carry out authentication for determining
whether or not the master supplicant 3 is a valid
20 device. The master supplicant 3 transmits an EAP-
Response/SIM/Challenge signal which is a response
signal thereto to the authenticator 1.

The authenticator 1 can determine whether or not
the master supplicant 3 is a valid device by analyzing
25 the response signal. For example, it is determined
whether or not the supplicant 3 is a valid device by
analyzing a decryption code included in the response

signal of the master supplicant 3.

When the authenticator 1 can correctly carry out authentication, an EAP-Success signal is transmitted to the master supplicant 3 in step S05. Having received
5 this signal, the master supplicant 3 recognizes that its own device has correctly been authenticated.

Subsequently, an authentication procedure for the slave supplicant 4 will be described below.

When the master supplicant 3 determines that
10 authentication of the slave supplicant 4 has not been carried out yet, the supplicant 3 transmits, in step S06, an EAPOL-Start signal for requesting the authenticator 1 to start authentication processing again within a predetermined time after completion of
15 authentication of its own device to the authenticator 1.

An identifier indicating that the master supplicant transmits the EAPOL-Start signal on behalf of the slave supplicant may be added to the EAPOL-Start
20 signal, or when the master supplicant ascertains an identifier ID of the slave supplicant, the master supplicant may add the identifier ID of the slave supplicant to the EAPOL-Start signal to thereby transmit the signal.

25 The authenticator 1 which has received the EAPOL-Start signal carries out the following determination.

The EAPOL-Start signal has been received from the

same supplicant which has already been authenticated within a predetermined time after the authentication processing of the master supplicant 3, and hence the authenticator 1 determines that the EAPOL-Start signal has been transmitted thereto from the master supplicant on behalf of the slave supplicant.

Alternatively, when an identifier indicating that the signal has been transmitted on behalf of the slave supplicant as described above or an identifier ID (identifier ID of the slave supplicant 4) different from that of the master supplicant 3 is added to the EAPOL-Start signal, the authenticator 1 utilizes the added data to determine that the EAP-Start signal has been transmitted thereto from the master supplicant 3 on behalf of the slave supplicant 4.

Further, when the authenticator 1 has determined that the signal is an EAPOL-Start signal transmitted thereto on behalf of the slave supplicant 4 by any one of the above methods, the authenticator 1 transmits, in step S07, an EAP-Request/Identity signal to which a specific identifier is added.

The specific identifier may be shown by setting a certain specific bit or the specific identifier can be made by making the destination address of the EAP-Request/Identity signal to be transmitted a multicast address or a broadcast address.

Further, when the identifier ID of the slave

supplicant 4 is added to the received EAPOL-Start signal, an EAP-Request/Identity signal a destination address of which is made the identifier ID of the slave supplicant 4 may be transmitted.

5 The master supplicant 3 receives the EAP-Request/Identity signal transmitted from the authenticator 1. When the received EAP-Request/Identity signal corresponds to any one of the following cases, the master supplicant 3 determines
10 that the signal is not addressed to its own device.

 (1) A specific identifier is added to the signal.
 (2) The destination address is not for its own device.
 (3) After the authentication of its own device has been completed, the fact that an EAPOL-Start signal has been
15 transmitted on behalf of the slave supplicant is retained, and an EAP-Request/Identity signal is received within a predetermined time.

 Further, the master supplicant 3 transfers the EAP-Request/Identity signal to the slave supplicant 4.
20 The slave supplicant 4 which has received this signal transmits an EAP-Response/Identity signal to the authenticator 1.

 In steps S08 to S09, the authenticator 1 carries out authentication processing of the slave supplicant 4
25 through the EAP-Request-Response/SIM/Start processing, and EAP-Request-Response/SIM/Challenge processing in the same manner as described above. Further, when the

authentication has been carried out correctly, the authenticator 1 transmits, in step S10, an EAP-Success signal to the master supplicant 3 to notify the supplicant 3 of the completion of the authentication of
5 the slave supplicant 4. The master supplicant 3 transfers the EAP-Success signal to the slave supplicant 4.

In step S11, the authenticator 1 transmits an EAP-Success signal to the master supplicant 3 which has
10 transmitted the EAPOL-Start signal thereto on behalf of the slave supplicant to notify the supplicant 3 of the completion of the authentication of the other supplicant. The authenticator 1 notifies the master supplicant 3 of completion of the authentication by
15 adding, for example, the ID of the supplicant authentication of which has been successfully completed to the signal. Hereby, it is possible for the master supplicant 3 to ascertain the authenticated supplicant, and determine that the supplicant is an authenticated
20 valid device.

Further, it is possible for the authenticator 1 to notify the master supplicant 3 of an encryption key used for the encrypted communication between the authenticator 1 and slave supplicant 4, and also notify
25 the slave supplicant 4 of an encryption key used for the encrypted communication between the authenticator 1 and master supplicant 3. Hereby, it also becomes

possible for the master supplicant 3 and slave supplicant 4 to carry out encrypted communication with each other.

[Variation 1 of First Embodiment]

5 FIG. 2 is an exemplary signal delivery/receipt chart showing a procedure in which three supplicants of the embodiment cooperate with each other to execute an authentication operation together with an authenticator. It should be noted that parts identical
10 to the first embodiment are denoted by reference symbols identical to the first embodiment, and a detailed description of them are omitted.

 In the procedure shown in FIG. 2, an authenticator 1, mobile terminal 2, master supplicant 3, slave
15 supplicant 4, and slave supplicant 5 execute signal delivery/receipt. Further, the master supplicant 3 can directly communicate with slave supplicants 4 and 5.

 The master supplicant 3 carries out its own authentication operation between itself and the
20 authenticator 1. This procedure is identical to steps S01 to S04 of the procedure shown in FIG. 1, and hence a description thereof is omitted.

 When authentication has been carried out correctly, the authenticator 1 transmits, in step S21,
25 an EAP-Success signal to the master supplicant 3. The master supplicant 3 which has received this signal recognizes that its own device has been correctly

authenticated.

Subsequently, an authentication procedure of slave supplicant 4 shown below is executed.

When the master supplicant 3 determines that
5 authentication of slave supplicant 4 has not been
carried out yet, the supplicant 3 transmits, in step
S22, an EAPOL-Start signal for requesting the
authenticator 1 to start authentication processing
again within a predetermined time after completion of
10 authentication of its own device to the authenticator
1.

When the authenticator 1 which has received this
signal determines that this signal is the EAPOL-Start
signal transmitted thereto on behalf of slave
15 supplicant 4, the authenticator 1 transmits an EAP-
Request/Identity signal to the master supplicant 3 in
step S23. The master supplicant 3 receives the EAP-
Request/Identity signal transmitted from the
authenticator 1. The master supplicant 3 transfers the
20 EAP-Request/Identity signal to slave supplicant 4.

In step S24, slave supplicant 4 which has received
this signal transmits an EAP-Response/Identity signal
to the master supplicant 3. The master supplicant 3
transfers the received EAP-Response/Identity signal to
25 the authenticator 1. Subsequently, the authenticator 1
carries out authentication processing of slave
supplicant 4 through the EAP-Request-Request/SIM/Start

processing, and EAP-Request-Response/SIM/Challenge processing. This procedure is identical to that described above, and hence a description thereof is omitted.

5 When authentication has been carried out correctly, the authenticator 1 transmits an EAP-Success signal to slave supplicant 4 in step S25. Further, in step S26, the authenticator 1 transmits an EAP-Success signal to the master supplicant 3 which has transmitted
10 the EAPOL-Start signal thereto on behalf of slave supplicant 4 to notify the master supplicant 3 of the completion of the authentication of slave supplicant 4.

 Subsequently, an authentication procedure of slave supplicant 5 will be described below.

15 When the master supplicant 3 determines that authentication of slave supplicant 5 has not been carried out yet, the supplicant 3 transmits, in step S27, an EAPOL-Start signal for requesting the authenticator 1 to start authentication processing
20 again within a predetermined time after the completion of the authentication of slave supplicant 4 to the authenticator 1.

 When the authenticator 1 which has received this signal determines that this signal is the EAPOL-Start
25 signal transmitted thereto on behalf of slave supplicant 5, the authenticator 1 transmits an EAP-Request/Identity signal to the master supplicant 3 in

step S28. The master supplicant 3 receives the EAP-Request/Identity signal transmitted from the authenticator 1. The master supplicant 3 transfers the EAP-Request/Identity signal to slave supplicant 5.

5 In step S29, slave supplicant 5 which has received this signal transmits an EAP-Response/Identity signal to the master supplicant 3. The master supplicant 3 transfers the received EAP-Response/Identity signal to the authenticator 1. Subsequently, the authenticator 1
10 carries out authentication processing of slave supplicant 5 through the EAP-Request-Request/SIM/Start processing, and EAP-Request-Response/SIM/Challenge processing. This procedure is identical to that described above, and hence a description thereof is
15 omitted.

 When the authentication has been carried out correctly, the authenticator 1 transmits, in step S30, an EAP-Success signal to slave supplicant 5. Further, in step 31, the authenticator 1 transmits an EAP-
20 Success signal to the master supplicant 3 which has transmitted the EAPOL-Start signal thereto on behalf of slave supplicant 5 to notify the supplicant 3 of the completion of the authentication of slave supplicant 5.
[Variation 2 of First Embodiment]

25 FIG. 3 is an exemplary signal delivery/receipt chart showing a procedure in which three supplicants of the embodiment cooperate with each other to execute an

authentication operation together with an authenticator. It should be noted that parts identical to the first embodiment are denoted by reference symbols identical to the first embodiment, and a detailed description of them are omitted.

In the procedure shown in FIG. 3, an authenticator 1, mobile terminal 2, master supplicant 3, slave supplicant 4, and slave supplicant 5 execute signal delivery/receipt. Further, the master supplicant 3 can communicate with slave supplicants 4 and 5 by multihop communication.

Multihop implies a configuration in which a number of supplicants are connected to each other by multistage connection without the intervention of access points. In the multihop communication, supplicants connected to each other and adjacent to each other are configured to be able to communicate with each other, and hence communication is carried out by relay of a plurality of supplicants.

Each of the authentication procedures of the master and slave supplicants 3 and 4 shown in steps S35 to S40 is identical to the processing of steps S21 to S26 shown in FIG. 2, and hence a description thereof is omitted.

Subsequently, an authentication procedure of slave supplicant 5 is executed. When the master supplicant 3 determines that authentication of slave supplicant 5

has not been carried out yet, the supplicant 3 transmits, in step S41, an EAPOL-Start signal for requesting the authenticator 1 to start authentication processing again within a predetermined time after the completion of the authentication of slave supplicant 4 to the authenticator 1.

When the authenticator 1 which has received this signal determines that this signal is the EAPOL-Start signal transmitted thereto on behalf of slave supplicant 5, the authenticator 1 transmits an EAP-Request/Identity signal to the master supplicant 3 in step S42. The master supplicant 3 receives the EAP-Request/Identity signal transmitted from the authenticator 1. The master supplicant 3 transfers the EAP-Request/Identity signal to slave supplicant 4. Slave supplicant 4 receives the EAP-Request/Identity signal transmitted from the master supplicant 3. Slave supplicant 4 transfers the EAP-Request/Identity signal to slave supplicant 5.

Slave supplicant 5 which has received this signal transmits an EAP-Response/Identity signal to slave supplicant 4 in step S43. Slave supplicant 4 which has received this signal transmits the EAP-Response/Identity signal to the master supplicant 3. The master supplicant 3 transfers the received EAP-Response/Identity signal to the authenticator 1.

Thereafter, the master supplicant 3 carries out

communication with slave supplicant 5 through slave
supplicant 4 in the multihop system to execute the EAP-
Request·Response/SIM/Start processing, and EAP-
Request·Response/SIM/Challenge processing. It should
5 be noted that this procedure is identical to that
described previously, and hence a description thereof
is omitted.

When the authentication has been correctly carried
out, the authenticator 1 transmits an EAP-Success
10 signal to the master supplicant 3 in step S44. The
master supplicant 3 transmits the EAP-Success signal to
slave supplicant 4. Slave supplicant 4 transmits the
EAP-success signal to slave supplicant 5. Further, in
step 45, the authenticator 1 transmits an EAP-Success
15 signal to the master supplicant 3 which has transmitted
the EAPOL-Start signal thereto on behalf of slave
supplicant 5 to notify the supplicant 3 of the
completion of the authentication of slave supplicant 5.
[Variation 3 of First Embodiment]

20 FIG. 4 is an exemplary signal delivery/receipt
chart showing a procedure in which three supplicants of
the embodiment cooperate with each other to execute an
authentication operation together with an
authenticator. It should be noted that parts identical
25 to the first embodiment are denoted by reference
symbols identical to the first embodiment, and a
detailed description of them are omitted.

In the procedure shown in FIG. 4, an authenticator 1, mobile terminal 2, master supplicant 3, slave supplicant 4, and slave supplicant 5 execute signal delivery/receipt. Further, the master supplicant 3 can communicate with slave supplicants 4 and 5 by multihop communication.

Each of the authentication procedures of the master and slave supplicants 3 and 4 shown in steps S51 to S56 is identical to the processing of steps S35 to S40 shown in FIG. 3, and hence a description thereof is omitted.

Subsequently, an authentication procedure of slave supplicant 5 is executed. Slave supplicant 4 transmits, in step S57, an EAPOL-Start signal for requesting the authenticator 1 to start authentication processing within a predetermined time after the completion of authentication of its own device to the master supplicant 3. The master supplicant 3 which has received this signal transmits the EAPOL-Start signal to the authenticator 1.

Thereafter, slave supplicant 4 carries out multihop communication with the master supplicant 3 and slave supplicant 5 to execute the EAP-Request-Response/Identity processing, EAP-Request-Response/SIM/Start processing, and EAP-Request-Response/SIM/Challenge processing. It should be noted that this procedure is identical to that of

steps S42 to S44 of FIG. 3, and hence a description thereof is omitted.

Further, in step S61, the authenticator 1 transmits an EAP-Success signal to the master
5 supplicant 3 to notify the supplicant 3 of the completion of the authentication of slave supplicant 5. The master supplicant 3 transmits the EAP-Success signal to the slave supplicant 4.

FIG. 5 is an exemplary view for explaining an
10 example in which the authentication system of the embodiment is applied to power supply service for an electric vehicle.

In a power supply station 10 of FIG. 5, a wall outlet 13, and circuit breaker 14 are provided, and
15 electric power supplied from an electric power company through an electric power transmission line can be supplied to an electric vehicle 16. On the other hand, a user who is an owner of the electric vehicle 16 carries a cellular phone 12 for payment of a charged
20 amount. The cellular phone 12 can communicate with an authenticator 11 through a communication network 15.

When the devices shown in FIG. 5 and devices which have executed the authentication procedure described above are compared with each other, the mobile terminal
25 2 corresponds to the cellular phone, master supplicant 3 corresponds to the wall outlet 13 that can supply power to the electric vehicle 16, and slave supplicant

4 corresponds to the circuit breaker 14 connected to the wall outlet 13.

5 The electric power company measures the total amount of electric power used at the circuit breaker 14, thereby carrying out accounting. In this system, even when a person other than a contractor of the circuit breaker 14 supplies power by using the wall outlet 13, an electric bill is collected from the contractor of the circuit breaker. However, when the
10 actual operation is taken into consideration, a case where a person other than the contractor uses the electric power by using the wall outlet is conceivable. Accordingly, a system in which a user who uses the electric power should pay the electric bill is
15 necessary.

 As a method of solving this problem, application of the aforementioned authentication method is conceivable.

 The wall outlet 13 which is the master supplicant
20 3 is provided with a meter configured to measure the supply amount of electric power. The user brings the cellular phone 12 close to the wall outlet 13, whereby the master supplicant 3 and cellular phone 12 carry out communication with each other. When a credit function
25 is added to the cellular phone in advance, the credit data can be retained in the circuit breaker 14 which is the slave supplicant 4 through the wall outlet 13 which

is the master supplicant 3. It becomes possible for the electric power supplier to charge the user for used electric power on the basis of the credit data and used amount of electric power obtained from the meter.

5 However, concerning the user of the cellular phone 12, notifying the master supplicant 3 and slave supplicant 4 of the credit data without recognizing that the supplicants 3 and 4 are valid devices is problematic in terms of security. Thus, taking the
10 opportunity of the communication between the cellular phone 12 and master supplicant 3, an authenticator possessed by the communication common carrier is used to authenticate the master supplicant 3 and slave
15 supplicant 4, whereby it becomes possible for the user to inform the supplicants of the credit data without anxiety.

 Further, the data is encrypted by the SIM, and hence even when the credit data retained by the slave supplicant 4 is illegally acquired by a third party,
20 the data cannot be inspected.

 By using the technique of authenticating a plurality of devices by cooperation between the devices in the manner described above, it becomes possible to construct a system in which a user of electric power is
25 charged in a service of supplying electric power to electric vehicles 16. It should be noted that the electric power supplying service is only one of

application examples of the present invention, and the present invention can be applied to various services without being limited to the above example.

5 It should be noted that in the example shown in FIG. 5, although the function of the master supplicant 3 is allocated to the wall outlet 13, the allocation is not limited to the example, and the circuit breaker 14 may be allocated to the master supplicant 3.

10 In general, when a plurality of data devices are present, a device corresponding to the master supplicant 3 may be determined in advance. Further, a data device firstly accessed by the mobile terminal 2 may bear the function of the master supplicant 3 without previously determining a device corresponding to the master supplicant 3.

15 [Second Embodiment]

In the first embodiment, authentication has been executed serially in such a manner that after completion of the authentication processing of the master supplicant 3, the authentication processing of the slave supplicant 4 is executed. Conversely, in a second embodiment, authentication of a master supplicant 3, and authentication of a slave supplicant 4 are simultaneously carried out, whereby the communication efficiency in authentication is improved.

20 Accordingly, parts identical to the first embodiment are denoted by reference symbols identical to the first

25

embodiment, and a detailed description of them are omitted.

FIG. 6 is an exemplary signal delivery/receipt chart showing a procedure in which two supplicants of the second embodiment cooperate with each other to execute an authentication operation together with an authenticator. It should be noted that the present invention is not limited to the case where the number of supplicants is two, and can be applied to a case where the number of supplicants is three or more.

In step S65, when the master supplicant 3 has established communication with a mobile terminal 2, the master supplicant 3 transmits an EAPOL-Start signal to an authenticator 1. In step S66, the authenticator which has received this signal transmits an EAP-Request/Identity signal to the master supplicant 3. In step T10, when the master supplicant 3 has received the EAP-Request/Identity signal, the master supplicant 3 transfers the signal to the slave supplicant 4.

The master supplicant 3 stands by for a predetermined time. When the master supplicant has received the EAP-Response/Identity signal transmitted from the slave supplicant 4 within the predetermined time in step T11, the master supplicant 3 generates one EAP-Response/Identity signal formed by aggregating the EAP-Response/Identity signal of its own device, and EAP-Response/Identity signal of the slave supplicant 4

with each other, and transmits the generated signal to the authenticator 1.

As described above, the number of the supplicants is not limited to two, and hence EAP-Response/Identity signals transmitted from two or more slave supplicants 4 are received in some cases. In such a case, one EAP-Response/Identity signal formed by aggregating two or more EAP-Response/Identity signals received within a predetermined time, and the EAP-Response/Identity signal of the master supplicant 3 with each other is generated, and is transmitted to the authenticator 1.

It should be noted that as the method of aggregating a plurality of EAP-Response/Identity signals with each other and aggregating into one EAP-Response/Identity signal, the method provided in, for example, IEEE 802. 11n can be employed. The authenticator 1 which has received the aggregated EAP-Response/Identity signal transmits, in step S68, EAP-Request/SIM/Start data formed by aggregating a plurality of EAP-Request/SIM/Start data items with each other in accordance with the number of aggregation to the master supplicant 3.

The master supplicant 3 which has received this data extracts an EAP-Request/SIM/Start data item corresponding to its own device from the data transmitted thereto, and transfers the received EAP-Request/SIM/Start data to the slave supplicant 4.

Further, after the transfer of the data to the slave supplicant 4, the master supplicant 3 starts a timer or the like to wait for receipt of a response signal.

It should be noted that as the transfer method,
5 the master supplicant 3 may transfer the received EAP-Request/SIM/Start data to the slave supplicant 4 as it is, or may aggregate a plurality of EAP-Request/SIM/Start data items with each other, and may transmit the aggregated EAP-Request/SIM/Start data
10 separately to each of a plurality of slave supplicants 4. Each of the slave supplicants 4 extracts an EAP-Request/SIM/Start data item for its own device from the received data not in accordance with the format of an EAP-Request/SIM/Start signal, and transmits an EAP-Response/SIM/Start signal as a response signal of the
15 received data.

In step T13, when the master supplicant 3 has received EAP-Response/Identity signals transmitted from the slave supplicants 4 within a predetermined time,
20 the master supplicant 3 aggregates EAP-Response/SIM/Start signals from the slave supplicants 4 received before a time-out occurs, and transfers the aggregated signal to the authenticator 1. At this time, random numbers NONCE_MT which are one of the EAP-Response/SIM/Start data items differ from one another
25 in each of the slave supplicants 4.

The authenticator 1 which has received this signal

transmits an aggregated EAP-Request/SIM/Challenge signal to the master supplicant 3 in step S70. Here, a Message Authentication Code (MAC) which is a data element of the EAP-Request/SIM/Challenge signal is generated for each NONCE_MT, and hence differs from each other in each of the slave supplicants 4. Further, the random numbers RAND Challenge which are data elements are data issued from the authenticator 1, and hence are common values.

10 The master supplicant 3 which has received the EAP-Request/SIM/Challenge signal confirms a Message Authentication Code associated with its own device and, when the supplicant 3 determines that the MAC associated with its own device is not appropriate, the
15 supplicant 3 does not transfer the EAP-Request/SIM/Challenge signal to the slave supplicants 4. On the other hand, when it is determined by the master supplicant 3 that the MAC associated with its own device is appropriate, the supplicant 3 transfers
20 the EAP-Request/SIM/Challenge signal to the slave supplicants 4 in step T14. Further, after the transfer of the above signal, the master supplicant 3 starts a timer or the like to wait for receipt of a response signal.

25 The slave supplicant 4 which has received the EAP-Request/SIM/Challenge signal confirms a Message Authentication Code corresponding to its own device

and, when the supplicant 4 determines that the MAC corresponding to its own device is appropriate, the supplicant 4 transmits an EAP-Response/SIM/Challenge signal to the master supplicant 3 in step T15. In step
5 S71, the master supplicant 3 aggregates the EAP-Response/SIM/Challenge signals received before a time-out occurs, and transmits the aggregated signal to the authenticator 1.

Further, in step S72, the authenticator 1
10 transmits an aggregated EAP-Success signal to one of the master and slave supplicants 3 and 4, one of the supplicants being successful in the authentication processing.

It should be noted that like in the case of the
15 first embodiment, the authenticator 1 may notify the supplicants of their encryption keys so that the supplicants for each of which authentication has been completed can carry out encrypted communication with each other.

20 [Third Embodiment]

A third embodiment differs from the second embodiment in using common data to authenticate each supplicant in order to further improve efficiency.

FIG. 7 is an exemplary signal delivery/receipt
25 chart showing a procedure in which two supplicants of the third embodiment cooperate with each other to execute an authentication operation together with an

authenticator. It should be noted that the present invention is not limited to the case where the number of supplicants is two, and can be applied to a case where the number of supplicants is three or more.

5 Steps S75 to S77, and T20 to T21 are identical to steps S65 to S67, and T10 to T11 of FIG. 6, and hence a detailed description of them is omitted.

10 An authenticator 1 which has received an aggregated EAP-Response/Identity signal transmits, in step S78, EAP-Request/SIM/Start data formed by aggregating a plurality of EAP-Request/SIM/Start data items with each other in accordance with the number of aggregation to a master supplicant 3.

15 The master supplicant 3 which has received the EAP-Request/SIM/Start signal transmits an EAP-Response/SIM/Start signal to the authenticator 1 in step S79 without transferring the received signal to a slave supplicant 4.

20 However, EAP-SIM version which is data to be added to the EAP-Response/SIM/Start signal is common to all the related slave supplicants 4. Further, each of NONCE_MT, and AT_SELECTED_VERSION which are parameters of the EAP-Response/SIM/Start signal, is used in common, and is one.

25 The authenticator 1 which has received this signal generates a common Message Authentication Code from the common NONCE_MT and transmits, in step S80, an

EAP-Request/SIM/Challenge signal to which the MAC and one Challenge are added, to the master supplicant 3.

The master supplicant 3 checks the Message Authentication Code transmitted thereto. Further, when
5 the master supplicant 3 determines that the MAC is not appropriate, the supplicant 3 does not transfer the EAP-Request/SIM/Challenge signal to the slave supplicant 4. On the other hand, when it is determined by the master supplicant 3 that the MAC is appropriate,
10 the supplicant 3 transfers the EAP-Request/SIM/Challenge signal to the slave supplicant 4 in step T22.

Each slave supplicant 4 which has received this signal accepts the authentication result obtained by
15 the master supplicant 3 to determine that the Message Authentication Code is appropriate, and returns an EAP-Response/SIM/challenge signal to which SRES response and AT_MAC generated on the basis of RAND are added to the master supplicant 3 in step T23. The master
20 supplicant 3 aggregates return signals from the slave supplicants 4 into one EAP-Response/SIM/Challenge signal, and transmits the aggregated signal to the authenticator 1 in step S81.

The authenticator 1 carries out authentication
25 processing for each supplicant and, when the authenticator 1 determines that all the supplicants are valid supplicants, the authenticator 1 transmits an

EAP-Success signal to the master supplicant 3 in step S82. One SRES response data item indicating success common to all the master and slave supplicants is added to the EAP-Success signal. The master supplicant 3
5 which has received this signal transfers the EAP-Success signal received for each of all the slave supplicants 4 to each of all the slave supplicants 4 in step T24.

Further, like in the cases of the first and second
10 embodiments, the authenticator 1 may notify the supplicants of their encryption keys so that the supplicants for each of which authentication has been completed can carry out encrypted communication with each other.

15 As described above, in step S79, the master supplicant 3 transmits the signal to which one NONCE_MT is added, to the authenticator 1 as a representative of the other supplicants and, in step S80, the authenticator 1 transmits the signal to which one MAC
20 is added, to the master supplicant 3. When the master supplicant 3 determines that the MAC is appropriate, the supplicant 3 transfers the signal to the slave supplicant 4. At this time, the master supplicant 3 has already determined that the authenticator 1 is a
25 valid authenticator, and hence the slave supplicant 4 may not determine the validity of the authenticator 1 again.

As described above, in the third embodiment, common data is used to carry out authentication, whereby it is possible to further improve the communication efficiency in authentication.

5 It should be noted that the slave supplicant 4 may determine the validity of the authenticator 1 again. For example, in step T22, when the master supplicant 3 determines that the MAC is appropriate, the supplicant 3 transfers the signal to the slave supplicant 4. At
10 this time, the signal to which NONCE_MT transmitted from the master supplicant's own device to the authenticator 1 as a parameter, and MAC are added is transferred. The slave supplicant 4 determines the validity of the authenticator 1 by using the data of
15 the NONCE_MT and MAC.

 According to the embodiments described above, it is possible to authenticate a plurality of devices by cooperation of the devices, and hence when authentication is carried out with respect to a system
20 constituted of a plurality of devices, it is possible to obtain an efficient and effective authentication operation.

 It should be noted that in each of the embodiments described above, although the mobile terminal 2 is
25 provided between the master supplicant 3 and authenticator 1, and is provided with a function of carrying out communication through the cellular line

which is a first network, and WLAN which is a second network, the master supplicant 3 may be provided with a function of carrying out communication through the first network and second network without providing the mobile terminal 2.

It should be noted that the communication station described in each of the above-mentioned embodiments can generally be ascertained and configured as an electronic device provided with a communication

function. However, this communication function is not limited to that constituted of hardware such as a communication circuit or the like. For example, part

of the communication function described in each of the embodiments described above can also be constituted of

software. Software can run on a CPU incorporated in a communication circuit, and can also run on a CPU

incorporated in an electronic device connected to a

communication circuit. Further, the communication

circuit can be incorporated in a medium detachable from

the electronic device. That is, the present invention

is not to limit how to configure an electronic device provided with a communication function. Accordingly,

it is also possible to store part of the functions

described in each of the embodiments in a medium such

as a SIM card, SD card or the like. Further, it is

also possible to configure the above part of functions

as an IC chip. Furthermore, it is also possible to

realize the above part of functions by appropriately selecting and combining hardware, software, recording medium, SIM card, SD card, and IC chip.

5 It should be noted that the functions described in each of the embodiments not only can be configured by using hardware, but also can be realized by causing a computer to read a program in which the above functions are described by using software. Further, the functions may be configured by appropriately selecting
10 one of software and hardware.

It should be noted that the present invention is not limited to the aforementioned embodiments as they are and, in the implementation stage, the constituent elements can be modified and embodied within a scope
15 not deviating from the essence of the invention.

While certain embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions. Indeed, the novel embodiments described
20 herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the embodiments described herein may be made without departing from the spirit of the inventions. The accompanying claims and their
25 equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the inventions.

WHAT IS CLAIMED IS:

1. An electronic device connected to an authentication device through a first communication network, and further connected to another electronic device through a second communication network, wherein
5 the electronic device executes authentication of the electronic device and another electronic device by data delivery/receipt conforming to a predetermined procedure between the electronic device and the authentication device through the first communication
10 network, and data delivery/receipt between the electronic device and another electronic device through the second communication network.

2. The electronic device according to claim 1,
15 comprising:

an authentication processing module configured to carry out authentication of the electronic device by data delivery/receipt conforming to a predetermined authentication procedure between the electronic device
20 and the authentication device through the first communication network;

an authentication start processing module configured to, when the electronic device has been authenticated by the authentication device, transmit an
25 authentication start signal configured to start authentication of another electronic device through the first communication network;

an authentication request transfer module configured to, when an authentication request signal is received from the authentication device, determine whether or not the authentication request is an authentication request associated with the electronic device and, when it is determined that the authentication request is not an authentication request associated with the electronic device, transfer the authentication request signal to another electronic device through the second communication network; and

a data relay module configured to thereafter relay data delivered/received in conformity with the predetermined authentication procedure between the authentication device and another electronic device.

3. The electronic device according to claim 2, wherein

data indicating that the authentication start signal is transmitted on behalf of another electronic device is included in the authentication start signal.

4. The electronic device according to claim 2, wherein

a plurality of other electronic devices are connected to the second communication network, and

the electronic device further comprises execution control module configured to cause each of a transmission operation of an authentication start signal configured to start authentication of the other

electronic devices to be executed by the authentication start module, a transfer operation of an authentication request signal to be executed by the authentication request transfer module, and a relay operation of delivery/receipt data to be executed by the data relay module, to be executed for each of the plurality of electronic devices.

5. The electronic device according to claim 4, wherein

10 data indicating that the authentication start signal is transmitted on behalf of one of the other electronic devices is included in the authentication start signal.

6. The electronic device according to claim 4, wherein

15 the plurality of other electronic devices are connected to each other, and the electronic device carries out data delivery/receipt with the plurality of other electronic devices through at least one of the other electronic devices serving as a relay point.

7. The electronic device according to claim 6, wherein

25 data indicating that the authentication start signal is transmitted on behalf of one of the other electronic devices is included in the authentication start signal.

8. The electronic device according to claim 1,

wherein

the electronic device is connected to a plurality of other electronic devices through the second communication network, and

5 the electronic device further comprises
an authentication start processing module configured to transmit an authentication start signal configured to start authentication of the electronic device and the other electronic devices through the
10 first communication network;

an authentication request transfer module configured to, when an authentication request signal is received from the authentication device, transfer the authentication request signal to the plurality of other
15 electronic devices through the second communication network; and

an authentication data delivery/receipt module configured to, regarding delivery/receipt of data for authentication between the authentication device and
20 the other electronic devices, thereafter aggregating data associated with the electronic device, and data items received from the plurality of other electronic devices with each other to transmit the aggregated data to the authentication device, and transmit data from
25 the authentication device to each of the plurality of other electronic devices.

9. The electronic device according to claim 8,

wherein

the authentication data delivery/receipt module
includes

a random number data transmission module
5 configured to transmit a plurality of random number
data items generated in each of the electronic device,
and the plurality of other electronic devices to the
authentication device,

an authentication data receipt module configured
10 to receive a signal including a plurality of
authentication data items generated by the
authentication device in a manner that the
authentication data items correspond to the plurality
of random number data items, and

15 a transmission inhibition module configured to,
when the authentication data corresponding to the
random number data generated in the electronic device
is not valid, inhibit the signal including the
plurality of authentication data items transmitted from
20 the authentication device from being transmitted to the
other electronic devices.

10. The electronic device according to claim 8,
wherein

the authentication data delivery/receipt module
25 includes

a random number data transmission module
configured to transmit one random number data item

generated in the electronic device to the authentication device,

an authentication data receipt module configured to receive one authentication data item generated in the authentication device in a manner that the authentication data item corresponds to the one random number data item, and

a transmission inhibition module configured to, when the authentication data corresponding to the random number data generated in the electronic device is not valid, inhibit the signal transmitted from the authentication device from being transmitted to the other electronic devices.

11. A terminal connected to an authentication device through a first communication network, further connected, through a second communication network, to an electronic device connected to another electronic device through a third communication network, and configured to relay delivery/receipt data between the authentication device and the electronic device, wherein

the electronic device comprises:

an electronic device authentication processing module configured to carry out authentication of the electronic device by data delivery/receipt conforming to a predetermined authentication procedure between the electronic device authentication processing module and

the authentication device through the first communication network;

an authentication start processing module configured to, when the electronic device has been
5 authenticated by the authentication device, transmit an authentication start signal configured to start authentication of another electronic device through the first communication network;

an authentication request transfer module
10 configured to, when an authentication request signal is received from the authentication device, determine whether or not the authentication request is an authentication request associated with the electronic device and, when it is determined that the
15 authentication request is not an authentication request associated with the electronic device, transfer the authentication request signal to another electronic device through the second communication network; and

a data relay module configured to thereafter relay
20 data delivered/received in conformity with the predetermined authentication procedure between the authentication device and another electronic device, and

the authentication device comprises:

25 a first authentication device authentication processing module configured to carry out authentication of the electronic device by data

delivery/receipt conforming to a predetermined authentication procedure between the first authentication device authentication processing module and the electronic device through the first communication network;

a determination module configured to, when an authentication start signal is received from the electronic device after the electronic device has been authenticated, determine whether or not authentication of another electronic device is to be started;

an authentication request module configured to, when it is determined that authentication of another electronic device is to be started, transmit an authentication request signal associated with another electronic device to the electronic device; and

a second authentication device authentication processing module configured to thereafter carry out data delivery/receipt conforming to the predetermined authentication procedure between the second authentication device authentication processing module and the electronic device to authenticate another electronic device.

12. A terminal connected to an authentication device through a first communication network, further connected, through a second communication network, to an electronic device connected to a plurality of other electronic devices through a third communication

network, and configured to relay delivery/receipt data between the authentication device and the electronic device, wherein

the electronic device comprises:

5 an authentication start processing module configured to transmit an authentication start signal configured to start authentication of the electronic device and the other electronic devices through the first communication network;

10 an authentication request transfer module configured to, when an authentication request signal is received from the authentication device, transfer the authentication request signal to the plurality of other electronic devices through the second communication
15 network; and

 an authentication data delivery/receipt module configured to, regarding delivery/receipt of data for authentication between the authentication device and the other electronic devices, thereafter aggregate data
20 associated with the electronic device, and data items received from the plurality of other electronic devices with each other to transmit the aggregated data to the authentication device, and transmit data from the authentication device to each of the plurality of other
25 electronic devices, the authentication device comprises:

 an authentication start signal receipt module

configured to receive an authentication start signal
configured to start authentication of the electronic
device and the plurality of other electronic devices
through the first communication network;

5 an authentication request signal transmission
module configured to transmit an authentication request
signal to the electronic device; and

 an authentication processing module configured to
thereafter execute delivery/receipt of data configured
10 to authenticate the electronic device and the plurality
of other electronic devices between the authentication
processing module and the electronic device, and

 the data for authentication being data formed by
aggregating data associated with the electronic device
15 and data items associated with the plurality of other
electronic devices with each other.