

AUTONOMOUS DOWNHOLE CONVEYANCE SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 61/424,285, filed 17 December 2010 and U.S. Provisional Application No. 61/552,747, filed 28 October 2011.

BACKGROUND OF THE INVENTION

[0002] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

Field of the Invention

[0003] This invention relates generally to the field of wellbore operations. More specifically, the invention relates to an autonomous conveyance system that is used to activate a downhole tool within a wellbore.

General Discussion of Technology

[0004] In the drilling of oil and gas wells, a wellbore is formed using a drill bit that is urged downwardly at a lower end of a drill string. After drilling to a predetermined depth, the drill string and bit are removed and the wellbore is lined with a string of casing. An annular area is thus formed between the string of casing and the surrounding formations.

[0005] A cementing operation is typically conducted in order to fill or “squeeze” the annular area with columns of cement. The combination of cement and casing strengthens the wellbore and facilitates the zonal isolation of the formations behind the casing.

[0006] It is common to place several strings of casing having progressively smaller outer diameters into the wellbore. A first string may be referred to as a conductor pipe or surface casing. Such casing string serves to isolate and protect the shallower, fresh water-bearing aquifers from contamination by any other wellbore fluids. Accordingly, these casing strings are almost always cemented entirely back to the surface. The process of drilling and then cementing progressively smaller strings of casing is repeated several times until the well has reached total depth. In some instances, the final string of casing is a liner, that is, a string of

casing that is not tied back to the surface. The final string of casing, referred to as a production casing, is also typically cemented into place.

[0007] As part of the completion process, the production casing is perforated at a desired level. This means that lateral holes are shot through the casing and the cement column surrounding the casing. The perforations allow hydrocarbon fluids to flow into the wellbore. Thereafter, the formation is typically fractured.

[0008] Hydraulic fracturing consists of injecting viscous fluids (usually shear thinning, non-Newtonian gels or emulsions) into a formation at such high pressures and rates that the reservoir rock parts and forms a network of fractures. The fracturing fluid is typically mixed with a granular proppant material such as sand, ceramic beads, or other granular materials. The proppant serves to hold the fracture(s) open after the hydraulic pressures are released. The combination of fractures and injected proppant increases the flow capacity of the treated reservoir.

[0009] In order to further stimulate the formation and to clean the near-wellbore regions downhole, an operator may choose to "acidize" the formations. This is done by injecting an acid solution down the wellbore and through the perforations. The use of an acidizing solution is particularly beneficial when the formation comprises carbonate rock. In operation, the drilling company injects a concentrated formic acid or other acidic composition into the wellbore, and directs the fluid into selected zones of interest. The acid helps to dissolve carbonate material, thereby opening up porous channels through which hydrocarbon fluids may flow into the wellbore. In addition, the acid helps to dissolve drilling mud that may have invaded the formation.

[0010] Application of hydraulic fracturing and acid stimulation as described above is a routine part of petroleum industry operations as applied to individual hydrocarbon-producing formations (or "pay zones"). Such pay zones may represent up to about 60 meters (100 feet) of gross, vertical thickness of subterranean formation. When there are multiple or layered formations to be hydraulically fractured, or a very thick hydrocarbon-bearing formation (over about 40 meters, or 131 feet), then more complex treatment techniques are required to obtain treatment of the entire target formation. In this respect, the operating company must isolate various zones or sections to ensure that each separate zone is not only perforated, but adequately fractured and treated. In this way the operator is sure that fracturing fluid and/or stimulant is being injected through each set of perforations and into each zone of interest to effectively increase the flow capacity at each desired depth.

[0011] The isolation of various zones for pre-production treatment requires that the intervals be treated in stages. This, in turn, involves the use of so-called diversion methods. In petroleum industry terminology, “diversion” means that injected fluid is diverted from entering one set of perforations so that the fluid primarily enters only one selected zone of interest. Where multiple zones of interest are to be perforated, this requires that multiple stages of diversion be carried out.

[0012] In order to isolate selected zones of interest, various diversion techniques may be employed within the wellbore. Known diversion techniques include the use of:

- Mechanical devices such as bridge plugs, packers, down-hole valves, sliding sleeves, and baffle/plug combinations;
- Ball sealers;
- Particulates such as sand, ceramic material, proppant, salt, waxes, resins, or other compounds;
- Chemical systems such as viscosified fluids, gelled fluids, foams, or other chemically formulated fluids; and
- Limited entry methods.

[0013] These and other methods for temporarily blocking the flow of fluids into or out of a given set of perforations are described more fully in U.S. Pat. No. 6,394,184 entitled “Method and Apparatus for Stimulation of Multiple Formation Intervals”, which issued in 2002.

[0014] The ‘184 patent also discloses various techniques for running a bottom hole assembly (“BHA”) into a wellbore, and then creating fluid communication between the wellbore and various zones of interest. In most embodiments, the BHA includes various perforating guns having associated charges. In most embodiments, the BHA is deployed in the wellbore by means of a wireline extending from the surface. The wireline provides electrical signals to the perforating guns for detonation. The electrical signals allow the operator to cause the charges to detonate, thereby forming perforations.

[0015] The BHA also includes a set of mechanically actuated, axial position locking devices, or slips. The slips are actuated through a “continuous J” mechanism by cycling the axial load between compression and tension. In this way, the slips are re-settable.

[0016] The BHA further includes an inflatable packer or other sealing mechanism. The packer is actuated by application of a slight compressive load after the slips are set within the casing. Along with the slips, the packer is resettable so that the BHA may be moved to

different depths or locations along the wellbore so as to isolate perforations along selected zones of interest.

[0017] The BHA also includes a casing collar locator. The casing collar locator initially allows the operator to monitor the depth or location of the assembly for appropriately detonating charges. After the charges are detonated (or the casing is otherwise penetrated for fluid communication with a surrounding zone of interest), the BHA is moved so that the packer may be set at a desired depth. The casing collar locator allows the operator to move the BHA to an appropriate depth relative to the newly formed perforations, and then isolate those perforations for hydraulic fracturing and chemical treatment.

[0018] Each of the various embodiments for a BHA disclosed in the '184 patent includes a means for deploying the assembly into the wellbore, and then translating the assembly up and down the wellbore. Such translation means include a string of coiled tubing, conventional jointed tubing, a wireline, an electric line or a tractor system attached directly to the BHA. In any instance, the purpose of the bottom hole assembly is to allow the operator to perforate the casing along various zones of interest, and then sequentially isolate the respective zones of interest so that fracturing fluid may be injected into the zones of interest in the same trip.

[0019] The bottom hole assembly and the formation treating processes disclosed in the '184 patent ("ACT-Frac" process) help to expedite the well completion process. In this respect, the operator is able to selectively set the slips and the packer for perforation and subsequent formation treatment. The operator is able to set the BHA at a first location, fracture or otherwise stimulate a formation, release the BHA, and move it to a new level along the wellbore, all without removing the BHA from the wellbore between stages.

[0020] However, as with previously-known well completion processes, the ACT-Frac process requires the use of expensive surface equipment. Such equipment may include a snubbing unit or a lubricator, which may extend as much as 75 feet above the wellhead. In this respect, the snubbing unit or the lubricator must be of a length greater than the length of the perforating gun assembly (or other tool string) to allow the perforating gun assembly to be safely deployed in the wellbore under pressure.

[0021] **Figure 1** presents a side view of a well site **100** wherein a well is being drilled. The well site **100** is using known surface equipment **50** to support wellbore tools (not shown) above and within a wellbore **10**. The wellbore tools may be, for example, a perforating gun or a fracturing plug.

[0022] The illustrative surface equipment **50** first includes a lubricator **52**. The lubricator **52** defines an elongated tubular device configured to receive wellbore tools (or a string of wellbore tools), and introduce them into the wellbore **10**. The lubricator **52** delivers the tool string in a manner where the pressure in the wellbore **10** is controlled and maintained. With readily-available existing equipment, the height to the top of the lubricator **52** can be approximately 100 feet from an earth surface **105**. Depending on the overall length requirements, other lubricator suspension systems (fit-for-purpose completion/workover rigs) may also be used. Alternatively, to reduce the overall surface height requirements, a downhole lubricator system similar to that described in U.S. Pat. No. 6,056,055 issued May 2, 2000 may be used as part of the surface equipment **50** and completion operations.

[0023] A wellhead **70** is provided above the wellbore **10** at the earth surface **105**. The wellhead **70** is used to selectively seal the wellbore **10**. During completion, the wellhead **10** includes various spooling components, sometimes referred to as spool pieces. The wellhead **70** and its spool pieces are used for flow control and hydraulic isolation during rig-up operations, stimulation operations, and rig-down operations.

[0024] The spool pieces may include a crown valve **72**. The crown valve **72** is used to isolate the wellbore **10** from the lubricator **52** or other components above the wellhead **70**. The spool pieces also include a lower master fracture valve **125** and an upper master fracture valve **135**. These lower **125** and upper **135** master fracture valves provide valve systems for isolation of wellbore pressures above and below their respective locations. Depending on site-specific practices and stimulation job design, it is possible that one of these isolation-type valves may not be needed or used.

[0025] The wellhead **70** and its spool pieces may also include side outlet injection valves **74**. The side outlet injection valves **74** provide a location for injection of stimulation fluids into the wellbore **10**. The piping from surface pumps (not shown) and tanks (not shown) used for injection of the stimulation fluids are attached to the injection valves **74** using appropriate fittings and/or couplings.

[0026] The lubricator **52** is suspended over the wellbore **10** by means of a crane arm **54**. The crane arm **54** is supported over the earth surface **105** by a crane base **56**. The crane base **56** may be a working vehicle that is capable of transporting part or all of the crane arm **54** over a roadway. The crane arm **54** includes wires or cables **58** used to hold and manipulate the lubricator **52** into and out of position over the wellbore **10**. The crane arm **54** and crane base **56** are designed to support the load of the lubricator **52** and any load requirements anticipated for the completion operations.

[0027] As an alternative to the crane arm **54** and crane based **56**, a hydraulic suspension system may be used. This is more common for snubbing units.

[0028] In the view of **Figure 1**, the lubricator **52** has been set down over the wellbore **10**. An upper portion of an illustrative wellbore **10** is seen. The wellbore **10** defines a bore **5** that extends from the surface **105** of the earth, and into the earth's subsurface **110**.

[0029] The wellbore **10** is first formed with a string of surface casing **20**. The surface casing **20** has an upper end **22** in sealed connection with the lower master fracture valve **125**. The surface casing **20** also has a lower end **24**. The surface casing **20** is secured in the wellbore **10** with a surrounding cement sheath **25**.

[0030] The wellbore **10** also includes a string of production casing **30**. The production casing **30** is also secured in the wellbore **10** with a surrounding cement sheath **35**. The production casing **30** has an upper end **32** in sealed connection with the upper master fracture valve **135**. The production casing **30** also has a lower end (not shown). It is understood that the depth of the wellbore **10** preferably extends some distance below a lowest zone or subsurface interval to be stimulated to accommodate the length of the downhole tool, such as a perforating gun assembly.

[0031] Referring again to the surface equipment **50**, the surface equipment **50** also includes a wireline **85**. The wireline **85** runs over a pulley and then down through the lubricator **52**, and supports the downhole tool (not shown). To protect the wireline **85**, the wellhead **70** may include a wireline isolation tool **76**. The wireline isolation tool **76** provides a means to guard the wireline **85** from direct flow of proppant-laden fluid injected into the side outlet injection valves **74** during a formation fracturing procedure.

[0032] The surface equipment **50** is also shown with a blow-out preventer **60**. The blow-out preventer **60** is typically remotely actuated in the event of operational upsets. The lubricator **52**, the crane arm **54**, the crane base **56**, the wireline **85**, and the blow-out preventer **60** (and their associated ancillary control and/or actuation components) are standard equipment known to those skilled in the art of well completion.

[0033] It is understood that the various items of surface equipment **50** and components of the wellhead **70** are merely illustrative. A typical completion operation will include numerous valves, pipes, tanks, fittings, couplings, gauges, pumps, and other devices. Further, downhole equipment may be run into and out of the wellbore using an electric line, coiled tubing, or a tractor. Alternatively, a drilling rig or other platform may be employed, with jointed working tubes being used.

[0034] The use of a crane and suspended lubricator add expense and complexity to a well completion operation, thereby lowering the overall economics of a well-drilling project. Further, cranes and wireline equipment present on location occupy needed space. Accordingly, the inventors have conceived of downhole tools that may be deployed within a wellbore without a lubricator and a crane arm. Such downhole tools include a perforating gun and a bridge plug. Such downhole tools are autonomous, meaning that they are not necessarily mechanically controlled from the surface, and do not receive an electrical signal from the surface. Beneficially, such tools may be used for perforating and treating multiple intervals along a wellbore without being limited by pump rate or the need for an elongated lubricator.

[0035] The first patent application describes the design and operation of certain autonomous tools. That application is titled "Assembly And Method For Multi-Zone Fracture Stimulation of A Reservoir Using Autonomous Tubular Units." In the application, a tool assembly is first provided. The tool assembly is intended for use in performing a tubular operation. In one embodiment, the tool assembly comprises an actuatable tool. The actuatable tool may be, for example, a fracturing plug, a bridge plug, a cutting tool, a casing patch, a cement retainer, or a perforating gun.

[0036] The tool assembly preferably self-destructs in response to a designated event. Thus, where the tool is a fracturing plug, the tool assembly may self-destruct within the wellbore at a designated time after being set. Where the tool is a perforating gun, the tool assembly may self-destruct as the gun is being fired upon reaching a selected level or zone of interest.

[0037] The tool assembly also includes a location device. The location device is designed to sense the location of the actuatable tool within a tubular body. The tubular body may be, for example, a wellbore constructed to produce hydrocarbon fluids, or a pipeline for the transportation of fluids.

[0038] The location device senses location within the tubular body based on a physical signature provided along the tubular body. In one arrangement, the location device is a casing collar locator, and the physical signature is formed by the spacing of collars along the tubular body. The collars are sensed by the collar locator. In another arrangement, the location device is a radio frequency antenna, and the physical signature is formed by the spacing of identification tags along the tubular body. The identification tags are sensed by the radio frequency antenna.

[0039] The tool assembly also comprises an on-board controller. The controller is designed to send an actuation signal to the actuatable tool when the location device has recognized a selected location of the tool. The location is again based on the physical signature along the wellbore. The actuatable tool, the location device, and the on-board controller are together dimensioned and arranged to be deployed in the tubular body as an autonomous unit.

[0040] The technology disclosed in the application addresses the autonomous deployment of certain mechanical tools. However, a need remains for an autonomous conveyance system for delivering chemicals or other fluids to a selected location downhole. Further, a need exists for the actuation of other mechanical tools, such as a whipstock without use of an electric line, or even without need of a lubricator and a crane arm.

SUMMARY OF THE INVENTION

[0041] The assemblies described herein have various benefits in the conducting of oil and gas exploration and production activities.

[0042] A delivery assembly for performing a wellbore operation is first disclosed. The delivery assembly is preferably a fluid delivery assembly. The fluid delivery assembly fundamentally includes an elongated fluid container. The fluid container is configured to hold a fluid. The fluid may be a primarily gaseous fluid such oxygen or air. Alternatively, the fluid may be a chemical used for treating or inhibiting waxes, hydrates, or scale along a pipe. Alternatively still, the fluid may be a chemical used for treating a formation, such as an acid or a resin.

[0043] The fluid delivery assembly also includes at least one actuatable tool. The actuatable tool may include a setting tool for setting a set of slips. The slips hold the fluid delivery assembly at a specified location within the wellbore. Alternatively or in addition, the actuatable tool may be a valve having one or more flow ports for releasing fluid from the fluid container. Thus, the fluid delivery assembly may be designed to release fluid from the fluid container in response to an actuation signal when the slips are set.

[0044] The fluid delivery assembly also has a location device. The location device generally senses the location of the actuatable tool within a wellbore. Sensing is based on a physical signature provided along the wellbore. For example, the location device may be a casing collar locator that identifies collars by detecting magnetic anomalies along a casing wall. In this instance, the physical signature is formed by the spacing of collars along a string of casing, with the collars being sensed by the collar locator.

[0045] Alternatively, the location device may be a radio frequency antenna that detects the presence of RFID tags spaced along or within the casing wall. In this instance, the physical signature is formed by the spacing of identification tags along a string of casing, with the identification tags being sensed by the radio frequency antenna.

[0046] In one embodiment, the location device comprises a pair of sensing devices spaced apart along the fluid delivery assembly. The sensing devices represent lower and upper sensing devices. The controller then comprises a clock that determines time that elapses between sensing by the lower sensing device and sensing by the upper sensing device as the assembly traverses across a physical signature marker. The fluid delivery assembly is programmed to determine tool assembly velocity at a given time based on the distance between the lower and upper sensing devices, divided by the elapsed time between sensing. In this way, location of the actuatable tool can be calculated relative to the physical signature provided by downhole markers.

[0047] The fluid delivery assembly further includes an on-board controller. The on-board controller is configured to send an actuation signal to at least one of the at least one actuatable tool when the location device has recognized a selected location of the tool based on the physical signature. Preferably, the on-board controller is part of an electronic module comprising onboard memory and built-in logic.

[0048] In one embodiment, one of the actuatable tools is a detonator. In this instance, the electronic module is configured to send a signal that initiates detonation of the fluid delivery assembly. This may take place when the assembly has reached the specified location. In this instance, detonation of the fluid delivery assembly itself serves to release the fluid. Alternatively, detonation may take place a designated time after the slips have been set and flow ports have opened to release fluids into the wellbore.

[0049] The tool assembly may also include a battery pack for providing power to the location device and the on-board controller.

[0050] The fluid container, the at least one actuatable tool, the location device, the battery pack, and the on-board controller are together dimensioned and arranged to be deployed in the wellbore as an autonomous unit. This means that the tool assembly does not rely upon a signal from the surface to know when to activate the tool. Preferably, the tool assembly is released into the wellbore without a working line. The tool assembly either falls gravitationally into the wellbore, or is pumped downhole. However, a non-electric working line such as slickline may optionally be employed. The slickline may be used to retrieve the fluid delivery assembly after fluid has been released from the fluid container.

[0051] In an alternative embodiment, the delivery system is a solids delivery assembly. In this arrangement, the assembly uses a canister for holding a solid material. The solid material may be, for example, ball sealers or other solids used for diversion. Alternatively, the solid may form a plug for isolation. Alternatively still, the solid may be an ignitable material used for stimulation.

[0052] In this arrangement, the delivery assembly is designed to release the solid from the canister in response to the release signal. In one aspect, the canister is fabricated from a friable material, and the delivery assembly is constructed to self-destruct in response to the actuation signal. In another aspect, the delivery assembly further comprises a perforation gun for perforating a string of casing proximate the selected location. In this instance, one of the at least one actuatable tool comprises the perforating gun, such that perforating charges are fired at the selected location in response to the actuation signal. The controller is programmed to send the release signal before the actuation signal.

[0053] A method for delivering fluid to a subsurface formation is also provided herein. The method first includes releasing a fluid delivery assembly into a tubular body. The tubular body may be a wellbore having a string of casing along its length. The wellbore may be completed for the purpose of producing hydrocarbons from one or more subsurface formations. Alternatively, the wellbore may be completed for the purpose of injecting fluids into one or more subsurface formations, such as for pressure maintenance or sequestration.

[0054] The fluid delivery assembly is designed in accordance with the fluid delivery assembly described above. In this respect, the fluid delivery assembly includes an elongated fluid container, at least one actuatable tool, a location device for sensing the location of one of the at least one actuatable tool within the tubular body based on a physical signature provided along the tubular body, and an on-board controller. The on-board controller is configured to send an actuation signal to an actuatable tool when the location device has recognized a selected location of the tool based on the physical signature.

[0055] The fluid container, the location device, the actuatable tool, and the on-board controller are together dimensioned and arranged to be deployed in the tubular body as an autonomous unit. In one aspect, the fluid delivery assembly further comprises a set of slips for holding the fluid delivery assembly proximate the selected location. In this instance, the actuatable tool includes a setting tool for setting the slips, such that the set of slips is activated in response to the actuation signal.

[0056] The fluid container contains a fluid. The method then includes releasing fluid from the fluid container. Fluid is released at the selected location in response to a release signal.

[0057] The fluid may be air loaded into the chamber at substantially atmospheric pressure. In this instance, releasing fluid creates a “burp” of negative pressure within the wellbore. This may be beneficial when a wellbore is first completed. In this respect, the negative pressure will cause a sudden pull of fluids through perforations in the wellbore. This, in turn, will help clean out perforations and fracture tunnels in the near-wellbore region.

[0058] Alternatively, the fluid may be an acid or a surfactant. This is of benefit, for example, after a wellbore is drilled for cleaning up drilling mud along perforations and fracture tunnels. Other fluids may also be employed for performing other wellbore operations.

[0059] In one embodiment, the fluid delivery assembly is fabricated from a friable material, such as ceramic. In this instance, the fluid delivery assembly is designed to self-destruct in response to a detonation signal. Optionally, the fluid delivery assembly includes a detonator for providing the self-destruction. In this instance, destruction of the fluid delivery assembly causes the fluid container to no longer hold fluid, thereby releasing the fluid. In this way, the detonator may actually be one of the actuatable tools, and the detonation signal is the release signal. Alternatively, the fluid release signal may be sent from the controller prior to the detonation signal.

[0060] In another embodiment, the fluid delivery assembly further includes a valve having one or more flow ports. The on-board controller sends a signal to open the valve, thereby releasing the fluid. This may be done either with or without stopping the fluid delivery assembly using a set of slips. In the former instance, the method further includes sending a signal to open the valve.

[0061] A whipstock assembly is also provided herein. The whipstock assembly is also designed as an autonomous tool that is dimensioned to be received in a wellbore. The whipstock assembly also includes an actuatable tool, a location device, and an on-board controller. However, instead of carrying a fluid container, the whipstock assembly carries a whipstock.

[0062] The whipstock has an elongated concave face. The concave face diverts a milling bit against the surrounding casing in order to form a window. Preferably, the

whipstock is fabricated from a friable material such that the tool assembly self-destructs in response to a signal sent after a designated period of time.

[0063] The actuatable tool for the whipstock assembly is preferably a set of slips. The slips hold the whipstock assembly in place during the formation of the window along a string of casing. The slips are set at the specified or pre-programmed location in response to the actuation signal.

BRIEF DESCRIPTION OF THE DRAWINGS

[0064] So that the present inventions can be better understood, certain drawings, charts, graphs and/or flow charts are appended hereto. It is to be noted, however, that the drawings illustrate only selected embodiments of the inventions and are therefore not to be considered limiting of scope, for the inventions may admit to other equally effective embodiments and applications.

[0065] Figure 1 presents a side view of a well site wherein a well is being completed. Known surface equipment is provided to support wellbore tools (not shown) above and within a wellbore. This is a depiction of the prior art.

[0066] Figure 2 is a side view of an autonomous tool as may be used for wellbore operations. In this view, the tool is a whipstock assembly deployed in a string of production casing. The whipstock assembly is shown in both a pre-actuated position and an actuated position.

[0067] Figure 3 is a side view of an autonomous tool as may be used for wellbore operations, in an alternate embodiment. In this view, the tool is a fracturing plug deployed in a string of production casing. The plug is shown in both a pre-actuated position and an actuated position.

[0068] Figures 4A through 4N present side views of a well site. A lower portion of a wellbore is shown. The wellbore is receiving various autonomous tool assemblies for completing a well.

[0069] Figure 4A is a side view of a well site having a wellbore for receiving autonomous tools. The wellbore is being completed in at least zones of interest "T" and "U."

[0070] Figure 4B is a side view of the well site of Figure 4A. Here, the wellbore has received a first perforating gun assembly, in one embodiment.

[0071] Figure 4C is another side view of the well site of Figure 4A. Here, the first perforating gun assembly has fallen in the wellbore to a position adjacent zone of interest "T."

[0072] Figure 4D is another side view of the well site of Figure 4A. Here, charges of the first perforating gun assembly have been detonated, causing a perforating gun of the perforating gun assembly to fire. The casing along the zone of interest "T" has been perforated.

[0073] Figure 4E is yet another side view of the well site of Figure 4A. Here, fluid is being injected into the wellbore under high pressure, causing the formation within the zone of interest "T" to be fractured.

[0074] Figure 4F1 is another side view of the well site of Figure 4A. Here, the wellbore has received an autonomous fluid delivery assembly, in one embodiment.

[0075] Figure 4F2 is subsequent side view of the well site of Figure 4F1. Here, the flow ports in a fluid container of the fluid delivery assembly have been opened, thereby releasing fluid into the wellbore adjacent the zone of interest "T."

[0076] Figure 4G is another side view of the well site of Figure 4A. Here, a fracturing plug assembly has been released into the wellbore.

[0077] Figure 4H is another side view of the well site of Figure 4G. Here, the fracturing plug assembly has been actuated and set. The fracturing plug assembly is set below zone of interest "U." Of interest, no wireline is needed for setting the plug assembly.

[0078] Figure 4I is yet another side view of the well site of Figure 4A. Here, the wellbore has received a second perforating gun assembly.

[0079] Figure 4J is a side view of the well site of Figure 4I. Here, the second perforating gun assembly has fallen in the wellbore to a position adjacent zone of interest "U." Zone of interest "U" is above zone of interest "T."

[0080] Figure 4K is another side view of the well site of Figure 4I. Here, charges of the second perforating gun assembly have been detonated, causing the perforating gun of the perforating gun assembly to fire. The casing along the zone of interest "U" has been perforated.

[0081] Figure 4L is still another side view of the well site of Figure 4A. Here, fluid is being injected into the wellbore under high pressure, causing the formation within the zone of interest "U" to be fractured.

[0082] Figure 4M1 is yet another side view of the well site of Figure 4A. Here, a second fluid conveyance assembly is being pumped downhole. The fluid conveyance assembly is shown in a pre-actuated position, and is tethered to the surface by means of an optional slickline.

[0083] Figure 4M2 is a subsequent side view of the well site of Figure 4M1. Here, the flow ports in a fluid container of the fluid delivery assembly have been opened, thereby releasing fluid into the wellbore adjacent the zone of interest "U."

[0084] Figure 4M3 is still a subsequent side view of the well site of Figure 4M1. Here, slips holding the fluid delivery assembly in place have been released, and the fluid delivery assembly is being raised back to the surface. A fracturing plug has been detonated below the zone of interest "U."

[0085] Figure 4N provides a final side view of the well site of Figure 4A. The wellbore is now receiving production fluids.

[0086] Figure 5 schematically illustrates a multi-gated safety system for an autonomous wellbore tool, in one embodiment.

[0087] Figure 6 is a flow chart showing steps for a method of delivering fluid to a subsurface formation in a wellbore, in one embodiment. The method includes the autonomous activation of a set of slips and a valve.

[0088] Figure 7 is a flow chart showing steps for a method of forming a window through a string of casing within a wellbore, in one embodiment. The method includes the autonomous activation of a whipstock assembly within a string of production casing.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Definitions

[0089] As used herein, the term "hydrocarbon" refers to an organic compound that includes primarily, if not exclusively, the elements hydrogen and carbon. Hydrocarbons may also include other elements, such as, but not limited to, halogens, metallic elements, nitrogen, oxygen, and/or sulfur. Hydrocarbons generally fall into two classes: aliphatic, or

straight chain hydrocarbons, and cyclic, or closed ring hydrocarbons, including cyclic terpenes. Examples of hydrocarbon-containing materials include any form of natural gas, oil, coal, and bitumen that can be used as a fuel or upgraded into a fuel.

[0090] As used herein, the term “hydrocarbon fluids” refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at processing conditions or at ambient conditions (15° C and 1 atm pressure). Hydrocarbon fluids may include, for example, oil, natural gas, coalbed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

[0091] As used herein, the terms “produced fluids” and “production fluids” refer to liquids and/or gases removed from a subsurface formation, including, for example, an organic-rich rock formation. Produced fluids may include both hydrocarbon fluids and non-hydrocarbon fluids. Production fluids may include, but are not limited to, oil, natural gas, pyrolyzed shale oil, synthesis gas, a pyrolysis product of coal, carbon dioxide, hydrogen sulfide and water (including steam).

[0092] As used herein, the term “fluid” refers to gases, liquids, and combinations of gases and liquids, as well as to combinations of gases and solids, combinations of liquids and solids, and combinations of gases, liquids, and solids.

[0093] As used herein, the term “gas” refers to a fluid that is in its vapor phase at 1 atm and 15° C.

[0094] As used herein, the term “oil” refers to a hydrocarbon fluid containing primarily a mixture of condensable hydrocarbons.

[0095] As used herein, the term “subsurface” refers to geologic strata occurring below the earth's surface.

[0096] As used herein, the term “formation” refers to any definable subsurface region. The formation may contain one or more hydrocarbon-containing layers, one or more non-hydrocarbon containing layers, an overburden, and/or an underburden of any geologic formation.

[0097] The terms “zone” or “zone of interest” refers to a portion of a formation containing hydrocarbons. Alternatively, the formation may be a water-bearing interval.

[0098] For purposes of the present disclosure, the terms “ceramic” or “ceramic material” may include oxides such as alumina and zirconia. Specific examples include bismuth strontium calcium copper oxide, silicon aluminium oxynitrides, uranium oxide, yttrium barium copper oxide, zinc oxide, and zirconium dioxide. “Ceramic” may also include non-oxides such as carbides, borides, nitrides and silicides. Specific examples include titanium carbide, silicon carbide, boron nitride, magnesium diboride, and silicon nitride. The term “ceramic” also includes composites, meaning particulate-reinforced combinations of oxides and non-oxides. Additional specific examples of ceramics include barium titanate, strontium titanate, ferrite, and lead zirconate titanate.

[0099] For purposes of the present patent, the term “production casing” includes a liner string or any other tubular body fixed in a wellbore along a zone of interest.

[0100] The term “friable” means any material that is easily crumbled, powderized, or broken into very small pieces. The term “friable” includes frangible materials such as ceramic.

[0101] The term “millable” means any material that may be drilled or ground into pieces within a wellbore. Such materials may include aluminum, brass, cast iron, steel, ceramic, phenolic, composite, and combinations thereof.

[0102] As used herein, the term “wellbore” refers to a hole in the subsurface made by drilling or insertion of a conduit into the subsurface. A wellbore may have a substantially circular cross section, or other cross-sectional shapes. As used herein, the term “well”, when referring to an opening in the formation, may be used interchangeably with the term “wellbore.”

Description of Selected Specific Embodiments

[0103] The inventions are described herein in connection with certain specific embodiments. However, to the extent that the following detailed description is specific to a particular embodiment or a particular use, such is intended to be illustrative only and is not to be construed as limiting the scope of the inventions.

[0104] It is proposed herein to use tool assemblies for well-completion or other wellbore operations that are autonomous. In this respect, the tool assemblies do not require a wireline and need not otherwise be mechanically tethered or electronically connected to equipment external to the wellbore. The delivery method of a tool assembly may include gravity, pumping, and tractor delivery.

[0105] Various tool assemblies are therefore proposed herein that generally include:

- an actuatable tool;
- a location device for sensing the location of the actuatable tool within a tubular body based on a physical signature provided along the tubular body; and
- an on-board controller configured to send an activation signal to the actuatable tool when the location device has recognized a selected location of the tool based on the physical signature.

The actuatable tool is designed to be actuated to perform a tubular operation in response to the activation signal.

[0106] The actuatable tool, the location device, the on-board controller, and perhaps a battery pack are together dimensioned and arranged to be deployed in a wellbore as an autonomous unit.

[0107] **Figure 2** presents a side view of an illustrative autonomous tool **200** as may be used for wellbore operations. In this view, the tool **200** is a whipstock assembly deployed in a string of production casing **250**. The production casing **250** is formed from a plurality of “joints” **252** that are threadedly connected at collars **254**.

[0108] In **Figure 2**, the whipstock assembly **200** is shown in both a pre-actuated position and an actuated position. The whipstock assembly is shown in a pre-actuated position at **200'**, and in an actuated position at **200''**. Arrow “I” indicates the movement of the whipstock assembly **200'** in its pre-actuated position, down to a location in the production casing **250** where the whipstock assembly **200''** is in its actuated position. The whipstock assembly will be described primarily with reference to its pre-actuated position, at **200'**.

[0109] The whipstock assembly **200'** first includes a whipstock **201**. The whipstock **201** includes an angled and concave face **205**. The concave face **205** is configured to receive a milling bit (not shown) for the formation of a window that will be formed in the casing **250**.

[0110] The whipstock assembly **200'** also includes an actuatable tool. In the preferred arrangement, the actuatable tool is a set of slips **210'**. The slips **210'** ride outwardly from the assembly **200'** along wedges (not shown) spaced radially around the assembly **200'**. The slips **210'** may be urged outwardly along the wedges in response to a shift in a sleeve or other means as is known in the art. The slips **210'** extend radially to “bite” into the casing

250 when actuated, as shown at **201''**. In this manner, the whipstock assembly **200''** is secured in position.

[0111] The whipstock assembly **200'** also includes a setting tool **212**. The setting tool **212** will actuate the slips **210'** and translate them along the wedges to contact the surrounding casing **250**. In this embodiment, the term "actuatable tool" may refer to the slips **210'**, the setting tool **212**, or both together.

[0112] The whipstock assembly **200'** also includes a position locator **214**. The position locator **214** serves as a location device for sensing the location of the tool assembly **200'** within the production casing **250**. More specifically, the position locator **214** senses the presence of objects or "tags" along the wellbore, and generates depth signals in response.

[0113] In the view of **Figure 2**, the objects **254** are the casing collars. This means that the position locator **214** is a casing collar locator, known in the industry as a "CCL." The CCL senses the location of the casing collars **254** as it moves down the production casing **250**. While **Figure 2** presents the position locator **214** as a CCL and the objects **254** as casing collars, it is understood that other sensing arrangements may be employed in the whipstock assembly **200'**. For example, the position locator **214** may be a radio frequency detector, and the objects **254** may be radio frequency identification tags, or "RFID" devices. In this arrangement, the tags may be placed along the inner diameters of selected casing joints **252**, and the position locator **214** will define an RFID antenna/reader that detects the RFID tags. Alternatively, the position locator **214** may be both a casing collar locator and a radio frequency antenna. The radio frequency tags may be placed, for example, every 500 feet or every 1,000 feet to assist a casing collar locator algorithm.

[0114] A special tool-locating algorithm may be employed for accurately tracking casing collars. U.S. Provisional Pat. Appl. No. 61/424,285 filed on December 27, 2010 discloses a method of actuating a downhole tool in a wellbore. This patent application is entitled "Method for Automatic Control and Positioning of Autonomous Downhole Tools."

[0115] The method first includes acquiring a CCL data set from the wellbore. This is preferably done using a traditional casing collar locator. Casing collar locators are run into a wellbore on a wireline or electric line to detect magnetic anomalies along the casing string. The CCL data set correlates continuously recorded magnetic signals with measured depth. More specifically, the depths of casing collars may be determined based on the length and speed of the wireline pulling a CCL logging device. In this way, a first CCL log for the wellbore is formed.

[0116] The method also includes selecting a location within the wellbore for actuation of an actuatable tool. In the whipstock assembly **200'**, the actuatable tool is preferably a set of slips **210** that are part of or are actuated by the setting tool **212**. The actuatable tool may optionally also include an elastomeric sealing element (not shown).

[0117] The method further comprises downloading the first CCL log into a processor. The processor is part of an on-board controller, which in turn is part of an autonomous tool assembly.

[0118] As shown in **Figure 2**, the whipstock assembly **200'** includes an on-board controller **216**. The on-board controller **216** processes the depth signals generated by the position locator **214**. The processing may be in accordance with any of the methods disclosed in U.S. Serial No. 61/424,285. In one aspect, the on-board controller **216** compares the generated signals from the position locator **214** with a pre-determined physical signature obtained for wellbore objects from the prior CCL log.

[0119] The on-board controller **216** is programmed to continuously record magnetic signals as the autonomous tool **200'** traverses the casing collars **254**. In this way, a second CCL log is formed. The processor, or on-board controller **216**, transforms the recorded magnetic signals of the second CCL log by applying a moving windowed statistical analysis. Further, the processor incrementally compares the transformed second CCL log with the first CCL log during deployment of the downhole tool to correlate values indicative of casing collar locations. This is preferably done through a pattern matching algorithm. The algorithm correlates individual peaks or even groups of peaks representing casing collar locations. In addition, the processor is programmed to recognize the selected location in the wellbore, and then send an activation signal to the actuatable wellbore device or tool when the processor has recognized the selected location.

[0120] In some instances, the operator may have access to a wellbore diagram providing exact information concerning the spacing of downhole markers such as the casing collars **254**. The on-board controller **216** may then be programmed to count the casing collars **254**, thereby determining the location of the tool as it moves downwardly in the wellbore.

[0121] In some instances, the production casing **250** may be pre-designed to have so-called short joints, that is, selected joints that are only, for example, 15 feet, or 20 feet, in length, as opposed to the "standard" length selected by the operator for completing a well, such as 30 feet. In this event, the on-board controller **216** may use the non-uniform spacing

provided by the short joints as a means of checking or confirming a location in the wellbore as the whipstock assembly **200'** moves through the production casing **250**.

[0122] In one embodiment, the method further comprises transforming the CCL data set for the first CCL log. This also is done by applying a moving windowed statistical analysis. The first CCL log is downloaded into the processor as a first transformed CCL log. In this embodiment, the processor incrementally compares the second transformed CCL log with the first transformed CCL log to correlate values indicative of casing collar locations.

[0123] In the above embodiments, applying a moving windowed statistical analysis preferably comprises defining a pattern window size for sets of magnetic signal values, and then computing a moving mean $m(t+1)$ for the magnetic signal values over time. The moving mean $m(t+1)$ is preferably in vector form, and represents an exponentially weighted moving average for the magnetic signal values for the pattern windows. Applying a moving windowed statistical analysis then further comprises defining a memory parameter μ for the windowed statistical analysis, and calculating a moving covariance matrix $\Sigma(t+1)$ for the magnetic signal values over time.

[0124] Additional details for the tool-locating algorithm are disclosed in U.S. Provisional Pat. Appl. No. 61/424,285, referenced above. That related, co-pending application is incorporated by reference herein in its entirety.

[0125] In one embodiment, the position locator **214** comprises an accelerometer (not shown). An accelerometer is a device that measures acceleration experienced during a freefall. An accelerometer may include multi-axis capability to detect magnitude and direction of the acceleration as a vector quantity. When in communication with analytical software, the accelerometer allows the position of an object to be determined. Preferably, the position locator would also include a gyroscope. The gyroscope would help maintain the orientation of the fracturing plug assembly **200'** as it traverses the wellbore.

[0126] In any event, the method further includes sending an activation signal. In the arrangement of **Figure 2**, this is done when the on-board controller **216** determines that the whipstock assembly **200'** (or a specific component therein) has arrived at a particular depth adjacent a selected zone of interest. In the example of **Figure 2**, the on-board controller **216** activates the slips **210''** (through the setting tool **212**) to stop the whipstock assembly **200'** from moving and to set the tool **200''** in the production casing **250** at a desired depth or location.

[0127] It is noted that the whipstock assembly **200''** is autonomous, meaning that it is not electrically controlled from the surface for receiving the activation signal.

[0128] Other arrangements for an autonomous tool besides the whipstock assembly **200** may be used. **Figure 3** presents a side view of a fracturing plug assembly **300**. The fracturing plug assembly **300** is also shown within the string of production casing **250**.

[0129] In **Figure 3**, the fracturing plug assembly **300** is shown in both a pre-actuated position and an actuated position. The fracturing plug assembly is shown in a pre-actuated position at **300'**, and in an actuated position at **300''**. Arrow "I" indicates the movement of the fracturing plug assembly **300'** in its pre-actuated position, down to a location in the production casing **250** where the fracturing plug assembly **300''** is in its actuated position. The fracturing plug assembly will be described primarily with reference to its pre-actuated position, at **300'**.

[0130] The fracturing plug assembly **300'** first includes a plug body **310'**. The plug body **310'** will preferably define an elastomeric sealing element **305**. The sealing element **305** is mechanically expanded in response to a shift in a sleeve or other means as is known in the art. In one embodiment, the plug body **305'** is actuated by squeezing the sealing element **305** using a sleeve or sliding ring; in another aspect, the plug body **305'** is actuated by forcing the sealing element **305** outwardly along wedges (not shown).

[0131] The plug body **310'** may also include a set of slips **311**. The slips **311** ride outwardly from the assembly **300'** along wedges (not shown) spaced radially around the assembly **300'**. Preferably, the slips **311** are also urged outwardly along the wedges in response to a shift in the same sleeve or other means as the sealing element **305**. The slips **311** extend radially to "bite" into the casing **250** when actuated, securing the plug assembly **300''** in position. Examples of existing plugs with suitable slip designs are the Smith Copperhead Drillable Bridge Plug and the Halliburton Fas Drill® Frac Plug.

[0132] The fracturing plug assembly **300'** also includes a setting tool **312**. The setting tool **312'** will actuate the sealing element **305** and slips **311** and translate them along the wedges to contact the surrounding casing **250**.

[0133] In the actuated position for the plug assembly **300''**, the plug body **310''** is shown in an expanded state. In this respect, the elastomeric sealing element **305** is expanded into sealed engagement with the surrounding production casing **250**, and the slips **311** are expanded into mechanical engagement with the surrounding production casing **250**. Thus, in the tool assembly **300''**, the plug body **305''** consisting of the sealing element **305** and the

slips **311** defines an actuatable tool. The setting tool **312** may also be considered as part of the actuatable tool.

[0134] As with the whipstock assembly **200** of **Figure 2**, the fracturing plug assembly **300** also includes a position locator **314** and an on-board controller **316**. These serve the same function as the position locator **214** and the on-board controller **216** of **Figure 2**. A special tool-locating algorithm is again employed for accurately tracking casing collars or other tags. An activation signal is sent from the on-board controller **316** to actuate the plug body **310''** at a specified location in the wellbore. In this way, the downhole tool **300** is autonomous, meaning that it is not electrically controlled from the surface for receiving the activation signal.

[0135] Other mechanical devices may be configured as an autonomous tool. Such devices include a bridge plug, a cutting tool, a casing patch, a cement retainer, and a perforating gun. Such autonomous tools are discussed further in U.S. Provisional Pat. Appl. No. 61/348,578 filed on 26 May 2010, referenced and incorporated above.

[0136] A device not described in the application is a fluid container. **Figures 4A** through **4N** demonstrate selected steps for completing a well, including the use of a fluid container, or canister, for delivering fluid to a selected subsurface formation. The fluid container is part of a fluid delivery assembly **410**, shown specifically in **Figures 4F1, 4F2, 4M1, 4M2, and 4M3**.

[0137] **Figures 4A** through **4M** demonstrate the use of various autonomous tools in an illustrative wellbore. First, **Figure 4A** presents a side view of a well site **400**. The well site **400** includes a wellhead **470** and a wellbore **450**. The wellbore **450** includes a bore **405** for receiving the autonomous tool assemblies and other completion equipment. The bore **405** extends from the surface **105** of the earth, and into the earth's subsurface **110**. The wellbore **450** is being completed in at least zones of interest "**T**" and "**U**" within the subsurface **110**.

[0138] The wellbore **450** is first formed with a string of surface casing **420**. The surface casing **420** has an upper end **422** in sealed connection with a lower master fracture valve **425**. The surface casing **420** also has a lower end **424**. The surface casing **420** is secured in the wellbore **450** with a surrounding cement sheath **412**.

[0139] The wellbore **450** also includes a string of production casing **430**. The production casing **430** is also secured in the wellbore **450** with a surrounding cement sheath **414**. The production casing **430** has an upper end **432** in sealed connection with an upper master fracture valve **435**. The production casing **430** also has a lower end **434** proximate a bottom

of the wellbore **450**. It is understood that the bottom or depth of the wellbore **450** extends many thousands of feet below the earth surface **105**.

[0140] The production casing **430** extends through the lowest zone of interest “**T**,” and also through at least one zone of interest “**U**” above the zone “**T**.” A wellbore operation will be conducted that includes perforating each of zones “**T**” and “**U**” sequentially.

[0141] During the completion phase, the wellhead **470** will also include one or more blow-out preventers. The blow-out preventers are typically remotely actuated in the event of operational upsets. In more shallow wells, or in wells having lower formation pressures, the master fracture valves **425**, **435** may be the blow-out preventers. In either event, the master fracture valves **425**, **435** are used to selectively seal the wellbore **450**.

[0142] The wellhead **470** and its components are used for flow control and hydraulic isolation during rig-up operations, stimulation operations, and rig-down operations. The wellhead **470** may include a crown valve **472**. The crown valve **472** is used to isolate the wellbore **400** when downhole tools are placed above the wellhead **470** before being launched into the wellbore **450**. The wellhead **470** further includes side outlet injection valves **474**. The side outlet injection valves **474** are located within fluid injection lines **471**. The fluid injection lines **471** provide a means for the injection of fracturing fluids, weighting fluids, and/or stimulation fluids into the bore **405**, with the injection of the fluids being controlled by the valves **474**.

[0143] The piping from surface pumps (not shown) and tanks (not shown) used for injection of the stimulation (or other) fluids are attached to the valves **474**. Appropriate hoses, fittings and/or couplings (not shown) are employed. The stimulation fluids are then pumped into the production casing **430**.

[0144] It is understood that the various wellhead components shown in **Figure 4A** are merely illustrative. A typical completion operation will include numerous valves, pipes, tanks, fittings, couplings, gauges, and other fluid control devices. These may include a pressure-equalization line and a pressure-equalization valve (not shown) for positioning a tool string above the lower valve **425** before the tool string is dropped into the wellbore **405**. Downhole equipment may be run into and out of the wellbore **450** using an electric line, slick line or coiled tubing. Further, a drilling rig or other platform may be employed, with jointed working tubes being used.

[0145] **Figure 4B** is another side view of the well site **400** of **Figure 4A**. Here, the wellbore **450** has received a first perforating gun assembly **401**. The first perforating gun

assembly **401** is designed to operate in an autonomous fashion, as described more fully in U.S. Provisional Pat. Appl. No. 61/348,578, referenced and incorporated above.

[0146] The perforating gun assembly **401** includes a perforating gun **406**. The perforating gun **406** may be a select fire gun that fires, for example, 16 shots. The gun **406** has associated charges that detonate in order to cause shots to be fired from the gun **406** into the surrounding production casing **430**. Typically, the perforating gun **406** contains a string of shaped charges distributed along the length of the gun **406** and oriented according to desired specifications. The charges are preferably connected to a single detonating cord to ensure simultaneous detonation of all charges. Examples of suitable perforating guns include the Frac Gun™ from Schlumberger, and the G-Force® from Halliburton.

[0147] It can be seen in **Figure 4B** that the perforating gun assembly **401** is moving downwardly in the wellbore **450**, as indicated by arrow “I.” The perforating gun assembly **401** may simply be falling through the wellbore **450** in response to gravitational pull. In addition, the operator may be assisting the downward movement of the perforating gun assembly **401** by applying hydraulic pressure through the use of surface pumps (not shown). Alternatively, the perforating gun assembly **401** may be aided in its downward movement through the use of a tractor (not shown).

[0148] **Figure 4C** is still another side view of the well site **400** of **Figure 4A**. Here, the first perforating gun assembly **401** has fallen in the wellbore **450** to a position adjacent zone of interest “T.” In accordance with the present inventions, the perforating gun assembly **401** includes a locator device **407**. The locator device **407** operates in accordance with locator device **214** described in connection with **Figure 2**. In this respect, the locator device **407** generates signals in response to tags or “downhole markers” placed along the production casing **430**.

[0149] The perforating gun assembly **401** also includes an on-board controller **409**. The on-board controller **409** operates in accordance with on-board controller **216** of **Figure 2**. In this respect, the on-board controller **409** processes the depth signals generated by the position locator **407** using appropriate logic and power units. In one aspect, the on-board controller **409** compares the generated signals with a pre-determined physical signature obtained for the wellbore objects (such as collars **254** of **Figure 2**).

[0150] **Figure 4D** is another side view of the well site **400** of **Figure 4A**. Here, charges of the perforating gun assembly **401** have been detonated, causing the perforating gun **406** to fire. The casing along zone of interest “T” has been perforated. A set of perforations **456T** is shown extending from the wellbore **450** and into the subsurface **110**. While only six

perforations **456T** are shown in the side view, it is understood that additional perforations may be formed, and that such perforations will extend radially around the production casing **430**.

[0151] In addition to the creation of perforations **456T**, the perforating gun assembly **401** is self-destructed. The on-board controller **409** activates a detonating cord that ignites the charge associated with the perforating gun **406** to initiate the perforation of the production casing **430** at a desired depth or location. To accomplish this, the components of the gun assembly **401** are fabricated from a friable material. The perforating gun **401** may be fabricated, for example, from ceramic materials. Upon detonation, the material making up the perforating gun assembly **401** may become part of the proppant mixture injected into fractures in a later completion stage.

[0152] **Figure 4E** is yet another side view of the well site **400** of **Figure 4A**. Here, fluid is being injected into the bore **405** of the wellbore **450** under high pressure. Downward movement of the fluid is indicated by arrows “**F**.” The fluid moves through the perforations **456T** and into the surrounding subsurface **110**. This causes fractures **458T** to be formed within the zone of interest “**T**.”

[0153] It is desirable to place an acid solution into the bore **405** proximate the new perforations **456T** so as to remove carbonate build-up and remaining drilling mud. The acid solution may further be injected into the newly-formed fractures **458T** to stimulate the subsurface **110** for hydrocarbon production. Historically, this has been done simply by injecting a volume of acid solution, or “spotting” the acid solution, into the wellbore, and pumping it down. However, it is desirable to more precisely spot the desired volume of acid. This may be done through the use of a novel fluid delivery assembly.

[0154] **Figures 4F1** and **4F2** provide additional side views of the well site **400** of **Figure 4A**. Here, the wellbore **450** has received a fluid delivery assembly **410**. The fluid delivery assembly **410** includes a fluid container **415**. Preferably, the fluid container **415** is an elongated, cylindrical container for holding a designated volume of fluid.

[0155] The fluid delivery assembly **410** represents yet another autonomous tool. In accordance with the present inventions, the fluid delivery assembly **410** includes a locator device **414**. The locator device **414** operates in accordance with locator device **214** described in connection with **Figure 2**. In this respect, the locator device **414** generates signals in response to tags or “downhole markers” placed along the production casing **430**.

[0156] The fluid delivery assembly **410** also includes an on-board controller **416**. The on-board controller **416** operates in accordance with on-board controller **216** of **Figure 2**. In this respect, the on-board controller **416** processes the depth signals generated by the position locator **414** using appropriate logic and power units. In one aspect, the on-board controller **416** compares the generated signals with a pre-determined physical signature obtained for the wellbore objects, such as casing collars. For example, a CCL log may be run before deploying the autonomous tool in order to determine the spacing of the casing collars. The corresponding depths of the casing collars may be determined based on the speed of the wireline that pulled the CCL logging device.

[0157] It is preferred that the position locator **414** and the on-board controller **416** operate with software in accordance with the locating algorithm discussed above. Specifically, the algorithm preferably employs a windowed statistical analysis for interpreting and converting magnetic signals generated by the casing collar locator.

[0158] The fluid delivery assembly **410** also includes one or more actuatable tools. In the arrangement of **Figures 4F1** and **4F2**, a set of slips **417** is provided as an actuatable tool. The slips **417** are set in response to action of a setting tool **412**. Setting tool **412** may be in accordance with setting tool **212** described above in connection with **Figure 2**. The slips **417** are set in response to an activation signal sent from the on-board controller **416** when the on-board controller **416** determines that the fluid delivery assembly **410** has reached a specified location in the wellbore **450**. Thus, the setting tool **412** may be considered part of the actuatable tool.

[0159] The actuatable tool also includes a valve **411**. The valve **411** is shown as a plurality of flow ports. In the view of **Figure 4F1**, the flow ports of the valve **411** are darkened, indicating that they are closed. In the view of **Figure 4F2**, the flow ports of the valve **411** are lightened, indicating that they are open.

[0160] In **Figure 4F1**, the fluid delivery assembly **410** is in its run-in (pre-actuated) position. The slips, indicated at **417'**, have not been set. In **Figure 4F2**, the fluid delivery assembly **410** is in its set (actuated) position. The slips, indicated at **417''**, have engaged the surrounding casing **430**. This is in response to an actuation signal having been sent from the on-board controller **414** to the setting tool **412** to actuate the slips **417''**.

[0161] It is noted that the use of slips **417** is optional. In one embodiment, the fluid delivery assembly **410** is designed to open the valve **411** when the fluid container **415** reaches the desired subsurface location without the fluid delivery assembly **410** being set.

This embodiment is particularly applicable when the fluid delivery assembly **410** is going all the way to the bottom of the wellbore.

[0162] In one embodiment, the fluid delivery assembly **410** is fabricated from a friable material, such as ceramic. In this instance, the fluid delivery assembly **410** may be designed to self-destruct in response to a designated event such as a period of time after the slips **417** have set or the valve **411** is opened. Optionally, the fluid delivery assembly includes a detonator for providing the self-destruction. In this instance, destruction of the fluid delivery assembly causes the fluid container to no longer hold fluid, thereby releasing the fluid. In this way, the detonator may actually be the actuatable tool, and no slips or valves are needed. Alternatively, the detonator ignites charges that cause the fluid delivery assembly **410** to self-destruct a set time after the fluid has been released from the fluid container **415**.

[0163] **Figure 4G** provides yet another side view of the well site **400** of **Figure 4A**. Here, a new fracturing plug assembly **300'** has been released into the wellbore **450**. The fracturing plug assembly **300'** is falling into the wellbore **450** in response to gravity. Optionally, the fracturing plug assembly **300'** is also being pumped down the wellbore **450**.

[0164] In accordance with the present inventions, the locator device (shown at **314** in **Figure 3**) has generated signals in response to downhole markers placed along the production casing **430**. In this way, the on-board controller (shown at **316** of **Figure 3**) is aware of the location of the fracturing plug assembly **300''**.

[0165] **Figure 4H** is another side view of the well site **400** of **Figure 4A**. Here, the fracturing plug assembly **300''** has been set. This means that the on-board controller **316** has generated signals to activate the setting tool (shown at **312** of **Figure 3**), the plug (shown at **310''** of **Figure 3**) and the slips (shown at **113'**) to set and to seal the plug assembly **300''** in the bore **405** of the wellbore **450**. In **Figure 4H**, the fracturing plug assembly **300''** has been set above the zone of interest "T." This allows isolation of the zone of interest "U" for a next perforating stage.

[0166] **Figure 4I** is another side view of the well site **400** of **Figure 4A**. Here, the wellbore **450** has received a second perforating gun assembly **402**. The second perforating gun assembly **402** may be constructed and arranged as the first perforating gun assembly **401**. This means that the second perforating gun assembly **402** is also autonomous.

[0167] It can be seen in **Figure 4I** that the second perforating gun assembly **402** is moving downwardly in the wellbore **450**, as indicated by arrow "I." The second perforating gun assembly **402** may be simply falling through the wellbore **450** in response to

gravitational pull. In addition, the operator may be assisting the downward movement of the perforating gun assembly **402** by applying hydraulic pressure through the use of surface pumps (not shown). Alternatively, the perforating gun assembly **402** may be aided in its downward movement through the use of a tractor (not shown).

[0168] It can also be seen in **Figure 4I** that the fracturing plug assembly **300**” remains set in the wellbore **450**. The fracturing plug assembly **300**” is positioned above the perforations **456T** and the fractures **458T** in the zone of interest “**T**.” Thus, the perforations **456T** are isolated.

[0169] **Figure 4J** is another side view of the well site **400** of **Figure 4A**. Here, the second perforating gun assembly **402** has fallen in the bore **405** to a position adjacent zone of interest “**U**.” Zone of interest “**U**” is above zone of interest “**T**.” In accordance with the present inventions, the locator device has generated signals in response to downhole markers placed along the production casing **430**. In this way, the on-board controller is aware of the location of the second perforating gun assembly **402**.

[0170] **Figure 4K** is subsequent side view of the well site **400** of **Figure 4A**. Here, charges of the second perforating gun assembly **402** have been detonated, causing the perforating gun of the perforating gun assembly **402** to fire. The zone of interest “**U**” has been perforated. A set of perforations **456U** is shown extending from the wellbore **450** and into the subsurface **110**. While only six perforations **456U** are shown in side view, it is understood that additional perforations are formed, and that such perforations may extend radially around the production casing **430**.

[0171] In addition to the creation of perforations **456U**, the second perforating gun assembly **402** is self-destructed. Any pieces left from the assembly **402** will likely fall to the plug assembly **300**” still set in the production casing **430**.

[0172] It is understood that the order of deploying the fracturing plug assembly **300**’ of (seen in **Figure 4G**) and deploying the second perforating gun assembly **402** (seen in **Figure 4I**) may be reversed. In this way, the fracturing plug assembly **300**” (seen in **Figure 4I**) is not set until after the perforations **456U** (seen in **Figure 4K**) are formed.

[0173] **Figure 4L** is yet another side view of the well site **400** of **Figure 4A**. Here, fluid is being injected into the bore **405** of the wellbore **450** under high pressure. The fluid injection causes the subsurface **110** within the zone of interest “**U**” to be fractured. Downward movement of the fluid is indicated by arrows “**F**.” The fluid moves through the perforations **456U** and into the surrounding subsurface **110**. This causes fractures **458U** to be formed

within the zone of interest “U.” An acid solution may also optionally be circulated into the bore **405** to remove carbonate build-up and remaining drilling mud and further stimulate the subsurface **110** for hydrocarbon production.

[0174] **Figures 4M1, 4M2 and 4M3** provide additional side views of the well site **400** of **Figure 4A**. In **Figure 4M1**, a second fluid conveyance assembly **410** has been placed downhole. The fluid conveyance assembly **410** is shown in a pre-actuated position, and has reached the level of the zone of interest “U.”

[0175] Here, the fluid conveyance assembly **410** is tethered to the surface by means of a slickline. A slickline is shown at **485**. The slickline **485** is provided for the purpose of enabling the operator to retrieve the fluid conveyance assembly **410** after fluid has been delivered to the zone of interest “U.” This is in lieu of using a detonator.

[0176] As an alternative to using a slickline **485**, a tool assembly may be run into the wellbore with a tractor (not shown). This is particularly advantageous in deviated wellbores.

[0177] **Figure 4M2** is a subsequent side view of the well site **400** of **Figure 4M1**. Here, the flow ports in a fluid container **415** of the fluid delivery assembly **410** have been opened. This is the actuated position for the fluid delivery assembly **410**. The flow ports have been opened, thereby releasing fluid into the wellbore adjacent the zone of interest “U.”

[0178] In this process, the treatment fluid is an acid or a surfactant used for cleaning up drilling mud along the perforations **456U** and the fracture tunnels **458U**. Alternatively, the fluid may be air. Opening the fluid container **415** in this instance will create an area of negative pressure that pulls wellbore fluids and drilling mud into the chamber. This, in turn, has an instant cleaning effect for the perforations **456U** and fracture tunnels **458U**.

[0179] **Figure 4M3** is still a subsequent side view of the well site **400** of **Figure 4M1**. Here, the fluid delivery assembly **410** is being raised back to the surface **105**. The wireline **85** is being spooled back to the surface **105**.

[0180] Finally, **Figure 4N** provides a side view of the well site **400** of **Figure 4A** after well completion. Here, the fluid delivery assembly **410** has been removed from the wellbore. In addition, the wellbore **450** is now receiving production fluids. Arrows “P” indicate the flow of production fluids from the subsurface **110** into the wellbore **450** and towards the surface **105**.

[0181] **Figures 4A** through **4N** demonstrate the use of various autonomous tools to fracture and treat a formation. Two separate zones of interest (zones “T” and “U”) have

been treated within an illustrative wellbore **450**. In this example, both the first **401** and the second **402** perforating gun assemblies were autonomous, and the fracturing plug assembly **300** was also autonomous. Further, the fluid delivery assembly **410** was autonomous. However, it is possible to perforate the lowest zone “**T**” using a traditional wireline with a select-fire gun assembly, but then use autonomous perforating gun assemblies to perforate multiple zones above the terminal zone “**T**.”

[0182] It is also possible to deploy the above tools as autonomous tools, that is, tools that are not electrically actuated from the surface, using a slickline. The use of a slickline is shown in **Figures 4M1, 4M2, and 4M3** described above. The fluid delivery assembly may include a fishing neck (not shown) which is dimensioned and configured to serve as the male portion to a mating downhole fishing tool (not shown). The fishing neck **210** allows the operator to retrieve the fluid delivery assembly in the unlikely event that it becomes stuck in the casing.

[0183] It is desirable with autonomous tools, including particularly the perforating gun assemblies **401, 402**, to provide various safety features that prevent the premature actuation or firing of the tool. These are in addition to the locator device and on-board controller described above. Preferably, each autonomous tool utilizes at least two, and preferably at least three, safety gates or “barriers” that must be satisfied before the perforating gun may be “armed” or a tool is detonated or fluid is released or slips or set, depending on the arrangement and function of the tool.

[0184] A safety system is described below in connection with a perforating gun assembly. However, it is understood that the safety system has equal application to other autonomous tools.

[0185] First, one safety check that may be used is a vertical position indicator. This means that the on-board controller will not provide a signal to the select gun to fire until the vertical position indicator confirms that the perforating gun assembly is oriented in a substantially vertical orientation, e.g., within five degrees of vertical. For example, the vertical position indicator may be a mercury tube that is in electrical communication with the on-board controller. Of course, this safety feature only works where the wellbore is being perforated or the tool is being actuated along a substantially vertical zone of interest.

[0186] Another safety check may be a pressure sensor or a rupture disc in electrical communication with the on-board controller. Those of ordinary skill in the art will understand that as the assembly moves down the wellbore, it will experience an increased hydrostatic head. Pressure from the hydrostatic head may be enhanced by using pumps at the surface

(not shown) for pumping the perforating gun assembly downhole. Thus, for example, the pressure sensor may not send (or permit) a signal from the on-board controller to the perforating gun until pressure exceeds, for example, 4,000 psi.

[0187] A third safety check that may be utilized involves a velocity calculation. In this instance, the perforating gun assembly may include a second locator device spaced some distance below the original locator device. As the assembly travels across casing collars, signals generated by the second and the original locator devices are timed. The velocity of the assembly is determined by the following equation:

$$D / (T_2 - T_0)$$

Where: T_0 = Time stamp of the detected signal from the original locator device;

T_2 = Time stamp of the detected signal from a second locator device;
and

D = Distance between the original and second locator devices.

[0188] Use of such a velocity calculation ensures both a depth and the present movement of the perforating gun assembly before the firing sequence can be initiated.

[0189] Still a fourth safety check that may be utilized involves a timer. In this arrangement, the perforating gun assembly may include a button or other user interface that allows an operator to manually “arm” the perforating gun. The user interface is in electrical communication with a timer within the on-board controller. For example, the timer might be 2 minutes. This means that the perforating gun cannot fire for 2 minutes from the time of arming. Here, the operator must remember to manually arm the perforating gun before releasing the perforating gun into the wellbore.

[0190] Yet a fifth safety check that may be employed involves the use of low-life batteries. For example, the perforating gun assembly may be powered with a battery pack, but the batteries are not installed until shortly before the assembly is dropped into a wellbore. This helps to ensure safety during transportation of the tool. In addition, the batteries may have an effective life of, for example, only 60 minutes. This ensures that the assembly’s energy potential is lost at a predictable time in the event that the assembly needs to be pulled.

[0191] The on-board controller and the safety checks for the autonomous tool are part of a safety system. Additional details concerning a safety system are shown in **Figure 5**. **Figure 5** schematically illustrates a multi-gated safety system **500** for an autonomous

wellbore tool, in one embodiment. In the safety system **500** of **Figure 5**, five separate gates are provided. The gates are indicated at **510**, **520**, **530**, **540**, and **550**. Each of these illustrative gates **510**, **520**, **530**, **540**, **550** represents a condition that must be satisfied in order for detonation charges to be delivered to a perforating gun. Stated another way, the gated safety system **500** keeps the detonators inactive while the perforating gun assembly is at the surface or is in transit to a well site.

[0192] Using the gates **510**, **520**, **530**, **540**, **550**, electrical current to the detonators **416** is initially shunted to prevent detonation caused by stray currents. In this respect, electrically actuated explosive devices can be susceptible to detonation by stray electrical signals. These may include radio signals, static electricity, or lightening strikes. After the assembly is launched, the gates are removed. This is done by un-shunting the detonator by operating an electrical switch, and by further closing electrical switches one by one until an activation signal may pass through the safety circuit and the detonators **416** are active.

[0193] In **Figure 5**, a perforating gun is seen at **402**. This is representative of the gun shown at **402** in **Figure 4I**. The perforating gun **402** includes a plurality of shaped charges **412**. The charges are distributed along the length of the gun **402**. The charges **412** are ignited in response to an electrical signal delivered from the controller **516** through electrical lines **535** and to the detonators **416**. The lines **535** are bundled into a sheath **514** for delivery to the perforating gun **412** and the detonators **416**. Optionally, the lines **535** are pulled from inside the tool assembly **402** as a safety precaution until the tool assembly **402** is delivered to a well site.

[0194] The detonators **416** receive an electrical current from a firing capacitor **566**. The detonators **416** then deliver heat to the charges **412** to create the perforations. Electrical current to the detonators **416** is initially shunted to prevent detonation from stray currents. In this respect, electrically actuated explosive devices can be susceptible to detonation by stray electrical signals. These may include radio signals, static electricity, or lightening strikes. After the assembly is launched, the gates are removed. This is done by un-shunting the detonators **416** by operating an initial electrical switch (seen at gate **510**), and by further closing electrical switches one by one until an activation signal may pass through the safety circuit **500** and the detonators **416** are active.

[0195] In the arrangement of **Figure 5**, two physical shunt wires **535** are provided. Initially, the wires **535** are connected across the detonators **416**. This connection is external to the perforating gun assembly **402**. Wires **535** are visible from the outside of the assembly **402**. When the assembly **402** is delivered to the well site, the shunt wires **535** are

disconnected from one another and are connected to the detonators **416** and to the circuitry making up the safety system **500**.

[0196] In operation, a detonation battery **560** is provided for the perforating gun **402**. At the appropriate time, the detonation battery **560** delivers an electrical charge to a firing capacitor **566**. The firing capacitor **566** then sends a strong electrical signal through one or more electrical lines **535**. The lines **535** terminate at the detonators **416** within the perforating gun **402**. The electrical signal generates resistive heat, which causes a detonation cord (not shown) to burn. The heating rapidly travels to the shaped charges **412** along the perforating gun **402**.

[0197] In order to prevent premature actuation, a series of gates is provided. In **Figure 5**, a first gate is shown at **510**. This first gate **510** is controlled by a mechanical pull tab. The tab is pulled as the perforating gun **402** (and other downhole tool components of tool **402**) is dropped into a wellbore. The tab may be pulled manually after the removal of safety pins (not shown). More preferably, the tab is pulled automatically as the gun **402** falls from a wellhead and into the wellbore.

[0198] U.S. Serial No. 61/489,165 describes a perforating gun assembly being released from a wellhead. That application was filed on 23 May 2011, and is entitled "Safety System for Autonomous Downhole Tool." Figure 8 and the corresponding discussion in that co-pending application are incorporated herein by reference.

[0199] When the tab is pulled by the action of gravity upon the tool **402**, the first gate **510** is closed. This causes a command signal to be sent, shown as dashed line **512**. The signal **512** is sent to a fire enabling timer **514**. The timer **514**, in turn, controls a second gate in the safety system **500**.

[0200] Returning to **Figure 5**, the second gate in the safety system **500** is shown at **520**. This second gate **520** represents a timer. More specifically, the second gate **520** is a timed relay switch that shunts the electrical connections to the detonators **416** at all times unless a predetermined time value is exceeded. In one aspect, the timer **514** represents three or more separate clocks. Logic control compares the times kept by each of the three clocks. The logic control averages the three times. Alternatively, the logic control accepts the time of the two closest times, and then averages them. Alternatively still, the logic control "votes" to select the first two (or other) times of the clock that are the same.

[0201] In one aspect, the timer **514** of gate **520** prevents a 2-pole relay **536** from changing state, that is, from shunting the detonators **416** to connecting the detonators **516** to

the firing capacitor **566** for a predetermined period of time. The predetermined period of time may be, for example, 1 to 5 minutes. This is a “fire blocked” state. Thereafter, the electrical switch **520** is closed for a predetermined period of time, such as up to 30 minutes or, optionally, up to 55 minutes. This is a “fire unblocked” state.

[0202] Preferably, the safety system **500** is also programmed or designed to de-activate the detonators **516** in the case that detonation does not occur within a specified period of time. For instance, if the detonators **416** have not caused the charges **412** to fire after 55 minutes, the electrical switch representing the second gate **520** is opened, thereby preventing the relay **536** from changing state from shunting the detonators **416** to connecting the detonators **416** to the firing capacitor **566**. This feature enables the safe retrieval of the gun assembly **402** utilizing standard fishing operations. In any instance, a control signal is provided through dashed line **516** for operating the switch of the second gate **520**.

[0203] As noted, the control system **500** also includes a third gate **530**. This third gate **530** is based upon one or more pressure-sensitive switches. In one aspect, the pressure-sensitive switch **330** is biased by a spring (not shown) to be in the closed (shunted) position. In this manner, the third gate switch **730** is shunted, or closed, during transport and loading. Alternatively, the pressure-sensitive switch is a diaphragms that is designed to puncture or collapse upon exceeding a certain pressure threshold.

[0204] In either design, as the gun assembly **402** falls in the wellbore, hydrostatic pressure increases in the wellbore. Once a predetermined pressure value is exceeded within the wellbore, the gate **530** represented by one or more pressure-sensitive electrical switches closes. This provides a time-delayed unshunting of the detonators **416**.

[0205] In one aspect, the ring (seen in Figure 8 of U.S. Serial No. 61/489,165) provides a mechanical barrier for the actuation of the pressure-activated switches of the third gate **530**. Thus, the third gate **530** cannot close unless the first gate **510** is closed.

[0206] The fourth gate is shown at **540**. This fourth gate **540** represents the program or digital logic that determines the location of the gun assembly **402** as it traverses the wellbore. As discussed above and in the incorporated patent application that is U.S. Provisional Pat. Appl. No. 61/424,285 entitled “Method for Automatic Control and Positioning of Autonomous Downhole Tools,” the logic processes magnetic readings to identify probable casing collar locations, and compares those locations with a previously-downloaded (and, optionally algorithmically processed) casing collar log. The casing collar locations are counted until the desired location within the wellbore is reached. An electrical signal is then delivered that closes the fourth gate **540**.

[0207] The fourth gate **540** is preferably an electronics module. The electronics module consists of an onboard memory **542** and built-in logic **544**, together forming a controller. The electronic module provides a digital safety barrier based on logic and predetermined values of various tool events. Such events may include tool depth, tool speed, tool travel time, and downhole markers. Downhole markers may be Casing Collar Locator (CCL) signals caused by collars and pup joints intentionally (or unintentionally) placed in the completion string.

[0208] In the arrangement of **Figure 5**, a signal **518** is sent when the launch switch representing the first gate **510** is closed. The signal **518** informs the controller to begin computing tool depth in accordance with its operational algorithm. The controller includes a detonator control **542**. At the appropriate depth, the detonator control **542** sends a first signal **544'** to the detonator power supply **560**. In one aspect, the detonator power supply **560** is turned on a predetermined number of minutes, such as three minutes, after the tool assembly **402** is launched.

[0209] It is noted that in an electrically powered perforating gun, a strong electrical charge is needed to ignite the detonators **516**. The power supply (or battery) **560** itself will not deliver that charge; therefore, the power supply **560** is used to charge the firing capacitor **566**. This process typically takes about two minutes. Once the firing capacitor **566** is charged, the current lines **535** may carry the strong charge to the detonators **516**. Line **574** is provided as a power line.

[0210] The controller of the fourth gate **540** also includes a fire control **522**. The fire control **522** is part of the logic. For example, the program or digital logic representing the fourth gate **540** locates the perforating zone by matching a reference casing collar log using real time casing collar information acquired as the tool drops down the well. When the perforating gun assembly **402** reaches the appropriate depth, a firing signal **524** is sent.

[0211] The fire control **522** is connected to a 2-pole Form C fire relay **536**. The fire relay **536** is controlled through a command signal shown at **524**. The fire relay **536** is in a shunting of detonators **516** (or safe) state until activated by the fire control **522**, and until the command path **524** through the second gate **520** is available. In their safe state, the fire relay **536** disconnects the up-stream power supply **560** and shunts down-stream detonators **516**. The relay **536** is activated upon command **524** from the fire control **522**.

[0212] The control system **500** optionally also includes a battery kill timer **546**. The battery kill timer **546** exists in an armed state for, say, up to 60 minutes. When armed, the battery kill timer **546** closes a relay **552** allowing battery pack **554** to power the controller of gate **540**. When necessary to kill the batteries **554**, **560**, battery kill timer **546** opens lower

relay **552'** and closes upper relay **552''**. This allows charge from the power supply **560** to begin dissipating. This, in turn, serves as a safety feature for the system **500**.

[0213] The battery kill timer **546** is also connected to a detonator disconnect relay **572**. This is through a command signal **549**. The disconnect relay **572** is preferably a magnetically latching relay. Therefore, the relay **572** remains in its last-commanded state even when all electrical power is removed from the system **500**.

[0214] The relay **572** resides normally in a closed state. However, if the perforating gun **412** fails to fire after a designated period of time, such as 60 minutes, then a command signal **549** is sent and the relay **572** is opened. Opening the relay **572** prevents a firing charge to be delivered from the capacitor **566** to the shunt wires **535**, thereby serving as another safety feature for the system **500**.

[0215] In another arrangement, the detonator disconnect relay **572** resides normally in an open state. When the tool assembly **200** is dropped, the detonator control **542** sends a command signal **543** to close the relay **572**, thereby allowing electrical current to flow through the relay **572** and towards the detonators **416**. If after a designated period of time, such as 60 minutes, the detonators **416** have not fired, then the battery kill timer **546** sends a separate signal **549** to re-open the relay **572**.

[0216] In the arrangement of **Figure 5**, a command signal **549'** is also shown for "disarming" the power supply **560**. Redundantly, a separate command signal **549''** is optionally directed to the switch **549''**. In a first designated period of time, such as 1 to 5 minutes, the command signals **549'**, **549''** are dormant. The power supply **560** is inactive and the switch **562** remains open. During a second period of time, such as 4 to 60 minutes, the power supply **560** is activated (through command signal **544'** from the detonator control **542**) and the switch **562** is closed (through a related command signal **544''** from the detonator control **542**). During a third designated period of time, such as greater than 30 minutes, or greater than 60 minutes, the power supply **560** is optionally de-activated (using command signal **549'**).

[0217] The controller **216** may be configured to use only one of command signals **549**, **549'**, **549''**, or any two, or none.

[0218] The fifth and final illustrative gate is shown at **550**. This fifth gate **550** relates to the installation of a battery pack **554**. Power is supplied from the battery pack **554** to the controller of the fourth gate **540** only after the battery pack **554** is installed. Without the controller, the firing capacitor cannot deliver electrical signals through the wires **535** and the

detonators **416** cannot be armed. Thus, the battery pack **554** preferably includes a connector that allows the battery pack **554** to be physically disconnected.

[0219] It is noted that relay switches **552'**, **552''** may also be magnetically latching relays. As such, the relays **552**, **552''** maintain their last commanded state after electrical power is removed. Lower relay **552'** controls power to the controller **540**, while the upper relay **552''** is used to discharge the battery **554**. In the pre-configured state, both relays **552'** and **552''** are open. Relay **552''** is closed to power up the controller **540**. When the battery kill timer **546** commands a battery kill action, the relay **552''** is closed by command signal **548**. A short time later, relay **552'** is commanded to the open state, removing electrical power from the controller **540**.

[0220] As an optional feature, a discharge bank **554** may be provided to draw down the electrical power stored in the capacitor **535**. The discharge bank **554** may be, for example, a bleed-down resistor. The discharge bank **554** eliminates any potential source of long-term energy.

[0221] In operation, the battery pack (Gate 5) is installed into the perforating gun **212**. The gun **212** is then released into the wellbore. The ring removal (Gate 1) triggers a pressure-activated switch (Gate 2) rated to remove the detonator shunt at a predetermined pressure value. In addition, the ring removal (Gate 1) activates a timed relay switch (Gate 3) that removes another detonator shunt once the pre-set time expires. At this point the detonators **416** are ready to fire and await the activation signal from the control system (the Gate 4 electronics module). The electronics module monitors the depth of the gun assembly **402**. After the perforating gun assembly **402** has traveled to a pre-programmed depth, the electronics logic (Gate 4) sends a signal that closes a mechanical relay and initiates detonation.

[0222] The safety system **500** may have a built-in safe tool retrieval system in case of misfire. A mechanical relay with a timer may also be activated after the shunt is removed. The timer is programmed to switch the relay after a pre-set period of time has passed, for example, one hour after activation. Once the relay is switched, it shunts the detonators back and locks itself in shunted position. This may be done, for example, by using a magnet. The assembly **402** may be fished out using conventional fishing techniques and the fishing neck.

[0223] In the arrangement of **Figure 5**, a command signal **544''** may be sent to a switch **562**. In a first designated period of time, such as 1 to 5 minutes, the switch **562** remains open. During a second period of time, such as 4 to 60 minutes, the switch is closed. And

during a third designated period of time, such as greater than 30 minutes, the switch is re-opened.

[0224] It is preferred that the autonomous tool be manufactured using non-conductive materials such as ceramic. The use of non-conductive materials increases the safety of the autonomous tool by reducing the risk of stray currents activating the detonators or other tool that is activated in response to an electrical signal.

[0225] A fluid-activated shunt switch can also be incorporated into the safety system **500**. Such a switch shunts the detonators **416** in the event that water enters inside the electronics module. An illustrative fluid-activated shunt switch is shown and described in connection with Figure 9 of U.S. Serial No. 61/489165. Figure 9 and corresponding text is also incorporated herein by reference.

[0226] It is observed that the safety system **500** is applicable not only to autonomous perforating tools, but also to the whipstock assembly **200**, the fracturing plug assembly **300**, and the fluid delivery assembly **410** described above.

[0227] **Figure 6** is a flow chart showing steps for a method **600** of delivering fluid to a subsurface formation, in one embodiment. The method **600** includes the autonomous activation of a fluid conveyance system within a tubular body.

[0228] The method **600** first includes releasing a fluid delivery assembly into a tubular body. This is shown in Box **610**. The tubular body may be a pipeline containing fluids such as hydrocarbon fluids. Alternatively, the tubular body may be a wellbore having a string of casing along its length. The wellbore may be completed for the purpose of producing hydrocarbons from one or more subsurface formations. Alternatively, the wellbore may be completed for the purpose of injecting fluids into one or more subsurface formations, such as for pressure maintenance or sequestration.

[0229] The fluid delivery assembly is designed in accordance with the fluid delivery assembly **410** described above in connection with the **Figure 4** series. In this respect, the fluid delivery assembly includes an elongated fluid container, an actuatable tool, a location device for sensing the location of the autonomous tool within the tubular body based on a physical signature provided along the tubular body, and an on-board controller. The on-board controller is configured to send an actuation signal to an actuatable tool when the location device has recognized a selected location of the autonomous tool based on the physical signature.

[0230] In one aspect, the fluid delivery assembly further comprises a set of slips for holding the fluid delivery assembly proximate the selected location. In this instance, the actuatable tool includes the set of slips, such that the set of slips is activated in response to the actuation signal. A setting tool may be used for setting the slips. In another aspect, the fluid delivery assembly also includes an elastomeric sealing element for sealing the tubular body. In this instance, the actuatable tool further comprises the sealing element, such that the sealing element is also activated in response to the actuation signal.

[0231] The fluid container, the location device, the actuatable tool, and the on-board controller are together dimensioned and arranged to be deployed in the tubular body as an autonomous unit. A battery pack may also be included for powering the on-board controller.

[0232] In the method **600**, the fluid container contains a fluid. The method **600** then includes releasing fluid from the fluid container. This is seen at Box **620**. Fluid is released at the selected location in response to the actuation signal.

[0233] The fluid may be air or other gas loaded into the chamber at substantially atmospheric pressure. In this instance, releasing fluid creates a “burp” of negative pressure within the wellbore. This may be beneficial when a wellbore is first completed. In this respect, the negative pressure will cause a sudden pull of fluids through perforations in the wellbore. This, in turn, will help clean out perforations and fracture tunnels in the near-wellbore region.

[0234] Alternatively, the fluid may be a resin. This may be beneficial where the formation is made up of an unconsolidated sand. Here, the resin may be spotted before a fracturing operation takes place, thereby pushing the resin into the formation and along the fracture tunnels.

[0235] Alternatively, the fluid may be an acid or a surfactant. This is of benefit, for example, after a wellbore is drilled for cleaning up drilling mud along perforations and fracture tunnels.

[0236] Alternatively, the fluid may be a hydrate inhibitor. This is of benefit, for example, after a well has been shut in for a period of time and has entered a cool-down phase.

[0237] Alternatively still, the fluid may be a fluid selected to expedite the swelling of a swellable packer. The fluid may have a pH or a salinity or a temperature or other variable that is specially tuned for expediting the swelling.

[0238] In one embodiment, the fluid delivery assembly is fabricated from a friable material, such as ceramic. In this instance, the fluid delivery assembly is designed to self-destruct in response to a designated event. Optionally, the fluid delivery assembly includes a detonator for providing the self-destruction. In this instance, destruction of the fluid delivery assembly causes the fluid container to no longer hold fluid, thereby releasing the fluid. In this way, the detonator may actually be the actuatable tool.

[0239] In another embodiment, the fluid delivery assembly further includes a valve having one or more ports. The on-board controller sends a signal to open the valve, thereby releasing the fluid. This may be done either with or without stopping the fluid delivery assembly using a set of slips. In the former instance, the method **600** further includes sending a signal to open the valve. This is provided at Box **630**.

[0240] Along with sending a signal to a valve, the method **600** may optionally include sending a signal to a setting tool for a set of slips and, optionally, a sealing element. This is shown at Box **635**. This signal of Box **635** may be sent before, after, or concurrently with sending the signal of Box **630**. In this instance, the actuatable tool of the fluid delivery assembly would comprise the valve as well as the setting tool for the slips and the sealing element.

[0241] After the valve is opened, the fluid delivery assembly may be detonated. Detonation of the fluid delivery assembly is shown at Box **640**. This may be done by a separate signal sent to a detonator. The signal may come from a timer associated with the on-board controller, meaning that the detonator is activated after the passing of a selected period of time. Alternatively, the signal may be an acoustic signal sent through a series of hydraulic pulses from the surface.

[0242] In another embodiment, a signal may be sent from the on-board controller to cause the slips of the fluid delivery assembly to release. This alternative step is shown at Box **645**. In this instance, the fluid delivery assembly may then be retrieved from the wellbore, such as by pulling the tool using a wireline. Thus, the method **600** may further include retrieving the fluid delivery assembly to the surface. This is indicated at Box **655**.

[0243] In one embodiment of the method **600**, the fluid container contains air, but further includes a solid material. Examples of solid material include a biodegradable diverter, an ignitable material, ball sealers, benzoic acid flakes, particulates, or a cellulosic material.

[0244] The method **600** of **Figure 6** is described in terms of using a fluid delivery assembly to deliver fluid to a selected location in a wellbore. The fluid delivery assembly

employs a fluid container. However, the delivery assembly may alternatively be a solids delivery assembly. In this arrangement, the assembly uses a canister for holding a solid material. The solid material may be, for example, ball sealers or other solids used for diversion. Alternatively, the solid may be a plug used zonal for isolation, such as benzoic acid flakes, pecan hulls suspended in gel, hair balls, cotton seeds, wood pulp, and innumerable other examples. Alternatively still, the solid may be an ignitable material used for fracturing or stimulation. An example of ignitable material is the progressively burning propellants used by The GasGun, Inc. of Milwaukie, Oregon. Alternatively still, the solid material may be particulates such as sand or ceramic.

[0245] One material that may be particularly suited for solids delivery using the delivery assembly described herein is BioVert[®]. BioVert[®] is a biodegradable material used by Halliburton as a diverting agent. According to Halliburton literature, BioVert[®] can be used to provide temporary isolation of newly stimulated perforation clusters within a treatment interval. The perforations receiving the early fluid and proppant volumes of the treatment stages can be temporarily isolated, diverting further treatment to additional sets of perforations. The use of BioVert[®] as a diverting material is said to facilitate the treatment of longer intervals, thereby reducing the number of perforating runs and frac plugs required.

[0246] In delivering solids, the delivery assembly is designed to release the solid material from the canister in response to the release signal. In one aspect, the canister is fabricated from a friable material, and the delivery assembly is constructed to self-destruct in response to the actuation signal. The controller may be programmed to send the release signal before the actuation signal.

[0247] In another aspect, the delivery assembly further comprises a perforation gun for perforating a string of casing proximate the selected location. In this instance, one of the at least one actuatable tool comprises the perforating gun, such that perforating charges are fired at the selected location in response to the actuation signal. The controller is programmed to send the release signal before the actuation signal so that ball sealers or other solid is released just before the shaped charges are detonated.

[0248] In yet another aspect, the canister is fabricated from a friable material, and destruction of the canister downhole is in response to the actuation signal. This destruction itself causes a release of the solid material such that the actuation signal and the release signal are the same signal.

[0249] **Figure 7** is a flow chart showing steps for a method **700** of forming a window through a string of casing, in one embodiment. The method **700** involves the autonomous

activation of a whipstock assembly within a wellbore, and the subsequent formation of a window through a string of production casing.

[0250] The method **700** first includes releasing a whipstock assembly into the wellbore. This is shown in Box **710**. The whipstock assembly is constructed in accordance with the whipstock assembly **200** discussed above in **Figure 2**. In this respect, the whipstock assembly generally includes at least one actuatable tool, a whipstock mechanically connected to the actuatable tool, a location device for sensing the location of the actuatable tool within a wellbore based on a physical signature provided along the wellbore, and an on-board controller. The on-board controller is designed to send an actuation signal to one of the at least one actuatable tool when the location device has recognized a selected location of the actuatable tool based on the physical signature.

[0251] In the method **700**, the at least one actuatable tool, the whipstock, the location device, and the on-board controller are together dimensioned and arranged to be deployed in the wellbore as an autonomous unit. A battery pack may be included to power the on-board controller. Preferably, the at least one actuatable tool comprises a setting tool and a set of slips. In this instance, the actuation signal causes the setting tool to set the slips in the wellbore at the selected location.

[0252] The method **700** also includes setting the whipstock assembly at the selected location. This is seen in Box **720**. Setting the whipstock is done in response to the actuation signal, such as by activating the set of slips.

[0253] The method **700** further includes running a milling bit into the wellbore. This is provided at Box **730**. The milling bit is preferably run in at the end of a string of drill pipe. Alternatively, the milling bit may be part of downhole drilling assembly run in on coiled tubing.

[0254] In any event, the method **700** then includes rotating the milling bit in order to form a window through the casing. This is seen at Box **740**. Rotating the milling bit may mean rotating a string of drill pipe with the milling bit connected thereto. Alternatively, rotating the milling bit may mean actuating a downhole drilling assembly at the end of coiled tubing. The window is formed adjacent to the whipstock.

[0255] In one aspect of the method **700**, the at least one actuatable tool comprises a detonator. The method **700** then further comprises sending a detonation signal from the on-board controller to the detonator. This is shown at Box **750**. Sending the detonation signal causes the self destruction of the whipstock assembly after the window has been formed.

[0256] While it will be apparent that the inventions herein described are well calculated to achieve the benefits and advantages set forth above, it will be appreciated that the inventions are susceptible to modification, variation and change without departing from the spirit thereof.

CLAIMS

1. A delivery assembly for performing an autonomous tubular operation comprising:
- an elongated canister;
- 5 at least one actuatable tool;
- a location device for sensing the location of the at least one actuatable tool within a tubular body based on a physical signature provided along the tubular body; and
- an on-board controller configured to send an actuation signal to at least
- 10 one of the at least one actuatable tool when the location device has recognized a selected location of the actuatable tool based on the physical signature;
- wherein:
- the canister, the location device, and the on-board controller are together dimensioned and arranged to be deployed in the tubular body as
- 15 an autonomous unit;
- the delivery assembly is designed to release a material from the canister in response to a release signal; and
- the delivery assembly is constructed to self-destruct in response to the actuation signal.
- 20 2. The delivery assembly of claim 1, wherein the tubular body is (i) a wellbore constructed to produce hydrocarbon fluids, (ii) a wellbore constructed to inject fluids into a subsurface formation, or (iii) a pipeline containing fluids.
3. The delivery assembly claim 1 or 2, wherein:
- the elongated canister is a fluid container; and
- 25 the delivery assembly is designed to release fluid from the fluid container in response to a release signal.
4. The delivery assembly of claim 3, wherein:
- the actuatable tool comprises a detonator, such that activation of the detonator causes a release of fluid from the fluid container at the selected
- 30 location;

the fluid delivery assembly is fabricated from a friable material;
the fluid delivery assembly is designed to self-destruct in response to a detonation signal sent to the detonator; and
the detonation signal is also the release signal.

5 5. The delivery assembly of any one of claims 1 to 3, wherein:
the canister is fabricated from a friable material.

6. The delivery assembly of any one of claims 3 to 5, wherein one or more of
(i) the controller is programmed to send the release signal before the actuation
signal; (ii) when the canister is a fluid container, destruction of the canister causes
10 a release of fluid such that the actuation signal and the release signal are the
same signal; (iii) the material in the elongated canister comprises substantially
solid material and the delivery assembly is designed to release the solid from the
canister in response to the release signal; and (iv) destruction of the canister
causes a release of the solid material such that the actuation signal and the
15 release signal are the same signal.

7. The delivery assembly of claim 6, wherein:
the delivery assembly further comprises a perforation gun for perforating a
string of casing proximate the selected location;
one of the at least one actuatable tool comprises the perforating gun, such
20 that perforating charges are fired at the selected location in response to the
actuation signal; and
the controller is programmed to send the release signal before the
actuation signal.

8. The delivery assembly of claim 6, wherein the solid material comprises ball
25 sealers that are dimensioned to seal perforations.

9. The delivery assembly of any one of claims 1 to 8, further comprising:
a battery pack; and
a multi-gate safety system for preventing premature activation of the at
least one actuatable tool, the safety system comprising control circuitry having

one or more electrical switches that are independently operated in response to separate conditions before permitting the actuation signal to reach the tool.

10. The delivery assembly of claim 9, wherein the multi-gate safety system comprises at least one of:

5 i) a selectively removable battery pack, wherein the control circuitry is configured to operate an electrical switch when the battery pack is installed into the assembly;

10 ii) a mechanical pull-tab, wherein the control circuitry is configured to operate an electrical switch upon removal of the tab from the fluid delivery assembly;

iii) a pressure-sensitive switch that is configured to operate an electrical switch only when a designated hydraulic pressure on the fluid delivery assembly is exceeded;

15 iv) an electrical timer switch that is configured to operate only a designated period of time after deployment of the fluid delivery assembly in the wellbore;

v) a velocity sensor configured to operate an electrical switch only upon sensing that the fluid delivery assembly is traveling a designated velocity; and

20 vi) a vertical sensor configured to operate an electrical switch when the fluid delivery assembly is substantially vertical;

25 wherein operating an electrical switch means either closing such a switch to permit a flow of electrical current through the switch and toward the actuatable tool, or opening such a switch to restrict a flow of electrical current through the switch and toward the actuatable tool.

11. The delivery assembly of any one of claims 1 to 10, further comprising: a whipstock mechanically connected to the actuatable tool wherein:

30 the actuatable tool, the whipstock, the location device, and the on-board controller are together dimensioned and arranged to be deployed in the wellbore as an autonomous unit; and

the actuatable tool is designed to be actuated in response to the actuation signal.

12. The delivery assembly of claim 11, wherein the whipstock assembly further comprises:
an accelerometer in electrical communication with the on-board controller to confirm the selected location of the whipstock assembly.
- 5 13. A method for delivering fluid to a subsurface formation, comprising:
releasing a fluid delivery assembly into a wellbore, the fluid delivery assembly comprising:
an elongated fluid container containing a fluid,
at least one actuatable tool;
10 a location device for sensing the location of the at least one actuatable tool within a tubular body based on a physical signature provided along the tubular body,
and
an on-board controller configured to send an actuation signal to at
15 least one of the at least one actuatable tool when the location device has recognized a selected location of the actuatable tool based on the physical signature;
wherein the fluid container, the location device, the at least one actuatable tool, and the on-board controller are together dimensioned and
20 arranged to be deployed in the wellbore as an autonomous unit; and
releasing fluid from the fluid container at the selected location in response to a release signal.
14. The method of claim 13 or the delivery assembly of claim 1 or 2, wherein:
the location device is a radio frequency antenna; and
25 the signature is formed by the spacing of identification tags along the tubular body, with the identification tags being sensed by the radio frequency antenna.
15. The method of claim 13 or delivery assembly of claim 1, wherein:
the location device is a collar locator; and
30 the signature is formed by the spacing of casing collars along the wellbore, with the collars being sensed by the collar locator.

16. The method or delivery assembly of claim 15, wherein:
the location device comprises a pair of sensing devices spaced apart along
the fluid delivery assembly as lower and upper sensing devices;
the signature is formed by the placement of tags spaced along the
5 wellbore that are sensed by each of the sensing devices;
the controller comprises a clock that determines time that elapses between
sensing by the lower sensing device and sensing by the upper sensing device as
the fluid delivery assembly traverses across a tag; and
the fluid delivery assembly is programmed to determine fluid delivery
10 assembly velocity at a given time based on the distance between the lower and
upper sensing devices, divided by the elapsed time between sensing.

17. The method or delivery assembly of claim 16, wherein a position of the
fluid delivery assembly at the selected location along the wellbore is confirmed by
a combination of (i) location of the fluid delivery assembly relative to the tags as
15 sensed by either the lower or the upper sensing device, and (ii) velocity of the
fluid delivery assembly as computed by the controller as a function of time.

18. The method of any one of claims 13 to 17, wherein:
the fluid delivery assembly is fabricated from a friable material; and
the fluid delivery assembly is designed to self-destruct in response to a
20 detonation signal.

19. The method of claim 19, wherein the at least one actuatable tool
comprises a detonator, such that activation of the detonator causes the self-
destruction of the fluid container; and a release of fluid from the fluid container at
the selected location.

25 20. The method of claim 19, wherein:
the release signal serves to open a valve, thereby releasing fluid from the
fluid container at the selected location; and
the release signal is sent prior to the detonation signal.

21. The delivery assembly of claim 1 or 2 or method of any one of claims 13 to 20, wherein:
- the delivery assembly further comprises a set of slips for holding the location of the delivery assembly proximate the selected location;
- 5 one of the at least one actuatable tool comprises the set of slips, such that the set of slips is activated in response to the actuation signal.
22. The method of claim 21, further comprising:
- sending a signal to release the slips; and
- retrieving the fluid delivery assembly from the wellbore.
- 10 23. The method of claim 22, wherein sending a signal comprises co sending an electrical signal from the on-board controller, or (ii) sending an acoustic signal through hydraulic pulses delivered from a surface.
24. The delivery assembly of claim 1 or 2 or method of claim 21, wherein:
- the fluid delivery assembly further comprises an elastomeric sealing
- 15 element for sealing the tubular body; and
- the actuatable tool further comprises the sealing element, such that the sealing element is also activated in response to the actuation signal.
25. The delivery assembly of claim 1 or 2 or method of any one of claims 13 to 24, wherein the fluid comprises (i) air loaded into the chamber at substantially
- 20 atmospheric pressure, (ii) a resin, (iii) an acid, (iv) a surfactant, (v) a hydrate inhibitor, (vi) oxygen, or (vii) a fluid selected to expedite the swelling of a swellable packer.
26. The delivery assembly of claim 1 or 2 or method of claim 13, wherein:
- the fluid container comprises a valve having at least one port;
- 25 one of the at least one actuatable tool comprises the valve; and
- the valve is configured to open the at least one port in response to the release signal.
27. The method of claim 26, wherein:

the fluid container is fabricated from a friable material; and
the fluid delivery assembly is constructed to self-destruct at the time, or a designated period of time after, the at least one flow port has been opened.

28. The method of any one of claims 13 to 27, wherein:

5 the on-board controller is part of an electronic module comprising on board memory and built-in logic; and

the electronic module is configured to send a signal that initiates detonation of the detonator after the valve has been opened.

29. The method of claim 28, wherein the built-in logic provides a digital safety
10 barrier based on a predetermined value for co assembly depth, (ii) assembly speed, (iii) travel time, (iv) down hole markers, or (v) combinations thereof.

30. The method of any one of claims 13 to 29, wherein the fluid comprises air and a solid material.

31. The method of claim 30, wherein the solid material comprises at least one
15 of a biodegradable diverter, an ignitable material, ball sealers, benzoic acid flakes, particulates, and a cellulosic material.

32. A method for forming a window through a string of casing within a wellbore, comprising:

20 releasing a whipstock assembly into the wellbore, the whipstock assembly comprising:

at least one actuatable tool,

a whipstock mechanically connected to the actuatable tool,

a location device for sensing the location of the actuatable tool within a wellbore based on a physical signature provided along the wellbore, and

25 an on-board controller configured to send an actuation signal to the tool when the location device has recognized a selected location of the actuatable tool based on the physical signature,

wherein the at least one actuatable tool, the whipstock, the location device, and the on-board controller are together dimensioned and arranged to be deployed in the wellbore as an autonomous unit;
setting the whipstock assembly at the selected location in response to the
5 actuation signal; and
the actuatable tool, location device, and the on-board controller are constructed to self-destruct in response to the actuation signal;
running a milling bit into the wellbore; and
rotating the milling bit in order to form a window through the casing
10 adjacent the whipstock.