

(51) International Patent Classification:
H04N 7/26 (2006.01)(21) International Application Number:
PCT/US2013/035809(22) International Filing Date:
9 April 2013 (09.04.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

61/636,566	20 April 2012 (20.04.2012)	US
61/643,100	4 May 2012 (04.05.2012)	US
61/667,371	2 July 2012 (02.07.2012)	US
13/797,458	12 March 2013 (12.03.2013)	US

(71) Applicant: **QUALCOMM INCORPORATED** [US/US];
ATTN: International IP Administration, 5775 Morehouse
Drive, San Diego, California 92121-1714 (US).(72) Inventor: **WANG, Ye-Kui**; 5775 Morehouse Drive, San
Diego, California 92121 (US).(74) Agent: **JOSEPH, Jeffrey R.**; Shumaker & Sieffert, P. A.,
1625 Radio Drive, Suite 300, Woodbury, Minnesota 55125
(US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.



(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))

(54) Title: VIDEO CODING WITH ENHANCED SUPPORT FOR STREAM ADAPTATION AND SPLICING

**FIG. 2A****FIG. 2B**

(57) **Abstract:** Various techniques for enhanced support of stream adaptation and splicing based on clean random access (CRA) pictures are described. Instead of using a flag in the slice header to indicate that a broken link picture is present, a distinct network abstraction layer (NAL) unit type can be used to indicate the presence of a broken link picture. In some implementations, a first distinct NAL unit type may be used to indicate the presence of a broken link picture with leading pictures, while a second distinct NAL unit type indicates the presence of a broken link picture without leading pictures. In some implementations, a third distinct NAL unit type may be used to indicate the presence of a broken link picture with decodable leading pictures.