

DESCRIPTION

**« SYSTEM AND METHOD FOR CHECKING THE MUTUAL POSITION OF
COMPONENTS OF A WORKPIECE AND EQUIPMENT USING SUCH SYSTEM
AND METHOD »**

Technical Field

The present invention relates to a system for checking the mutual position of a second component of a workpiece relative to a first component of the workpiece, the first component being apt to define an axis, comprising a reference system apt to define a reference plane and a main axis perpendicular to the reference plane, and locate the first component of the workpiece so that the axis of the first component is aligned to the main axis, a detection system adapted to define at least a first checking area and a second checking area spaced apart from each other, and detect, at said at least first and second checking areas, quantities indicative of said mutual position of the second component of the workpiece relative to the first component of the workpiece, and a processing unit connected to the detection system, adapted to receive and process such quantities in order to find out information about said mutual position.

The invention also relates to a method for checking the mutual position of a second component of a workpiece relative to a first component of the workpiece, the first component being apt to define an axis, comprising the steps of locating the first component of the workpiece to a reference system apt to define a reference plane and a main axis perpendicular to the reference plane, so that the axis of the first component is aligned to the main axis,

defining at least a first checking area and a second checking area spaced apart from each other, detecting at said at least first and second checking areas quantities indicative of the mutual position, and processing such quantities in order to find out information about the mutual position.

The invention also relates to an assembly equipment and a relative method for assembling two components of a workpiece, that use said system and method, respectively, for checking the mutual position of the same components.

The present invention can be advantageously, but not exclusively, used for checking, for example, axial position of a bearing within a suitable hole of an E-block during the assembly phase, the bearing and the E-block being part of an hard disk, which the description that follows will explicitly refer without loss of generality.

Prior Art

The hard disk storage units or hard disks are devices for storing and recalling data, broadly used in electronic systems, for example computers. Hard disks typically include one or more magnetic read/write heads, each connected to a slider and placed near a surface of a rotating magnetic disk. In the current hard disks, when the magnetic disk is driven into rotation, a thin air cushion forms between said magnetic disk and the slider, enabling the latter to slide over the disk at a distance which is in the range of at most a few tens of nanometers. During such rotation, the magnetic read/write heads can be employed to read/write bits of data within one of the magnetic track on the surface of the magnetic disk.

Each head and the associated slider are part of a so-called Head Gimbal Assembly or HGA, which comprises also a

resilient thin plate, one end thereof carrying the head by means of a joint. At the end opposite with respect to the end carrying the head, each thin plate is connected to one of numerous mutually parallel wings of a support that is
5 called E-block. The assembly of the E-block and all the HGAs is called Head Stack Assembly or HSA and is employed for reading/writing on one face or both faces of one or more magnetic disks. The E-block is equipped with a suitable hole intended for inserting a bearing, through
10 which the HSA is coupled to fixed parts of the hard disk and is able to rotate, for example in response to a moment applied by a motor of the Voice Coil Motor or VCM type, in order to move the magnetic heads on the magnetic tracks.

Inserting the bearing in the suitable hole of the E-
15 block is one of the main phases of a method for assembling an HSA. The greater the precision with which it is carried out, the better and more reliable on a quality level the performance of magnetic read/write heads is. For example, in case the bearing and the hole of the E-block have no end
20 with limit stop intended for defining a wanted axial position, it is appropriate to carry out, during the phase of inserting, a continuous check of the position of a selected surface of the bearing in order to establish the stop of the insertion when the selected surface reaches a
25 wanted height. If the selected surface under check takes a height different from the wanted one, indeed, the proper operation of the HSA inside the hard disk can be compromised. In addition, when the bearing is in the appropriate position inside the E-block, it is advantageous
30 to have information about the attitude of the component. If the axis of the bearing does not coincide, for example it makes a not negligible angle, with the axis of the hole wherein the bearing is inserted, indeed, the rotation of

the components connected through said bearing is not proper and, as a consequence, the magnetic heads risk taking an improper disposition, i.e. position and attitude, with respect to the disk, damaging the reading/writing
5 functions. In addition, the force the bearing applies, while rotating, on the inner walls of the hole, can cause scratching and scraps, or even deformations and breakages of one component or both components, damaging the hard disk and its operation.

10 The U.S. patent number US8203701B2 shows an optoelectronic equipment of the static type for checking the attitude, in terms of roll and pitch angles, and the height of components of workpieces, in particular a bearing housed in the E-block of an assembled HSA, that are
15 fundamental in order to evaluate the attitude of the sliders and, as a consequence, of the read/write magnetic heads. Said equipment comprises a reference system including a floating element apt to reproduce the attitude of the bearing housed in the E-block, an optoelectronic
20 detection device that provides signals indicative of attitude and height of the floating element, and a processing unit that receives the signals of the optoelectronic detection device and processes them for checking the roll and pitch angles and the height of the
25 bearing. In more detail, for checking the roll angle, a detection is carried out at a predetermined checking area of the floating element, whereas, for checking the pitch angle and the height, it is necessary to carry out a detection at a first transversal section, then place the
30 detection device at a second different transversal section, and carry out a distinct detection, both the transversal sections being part of a further predetermined checking

area of the floating element, different from the preceding one.

The known equipment, however, can not be used in checking the mutual position of the components of a workpiece, for example a bearing of an hard disk, in particular in checking the assembly process of the workpiece, for example during the insertion of the bearing in a suitable hole of the E-block of the HSA. Indeed, the known equipment, as it needs procedures for placing and moving detection devices to obtain information about the height of the bearing, does not enable checking in real time the instant position of the bearing in order to control and stop the insertion at the appropriate instant.

15 Disclosure of the Invention

Object of the present invention is to provide a system and a method for checking the mutual position of a second component of a workpiece relative to a first component of a workpiece, such as checking the position of a bearing during the insertion in the suitable hole of an E-block, said system and method being easily and cheaply implemented and ensuring reliable results.

Object of the present invention is also to provide an assembly equipment and the relative method for assembling the components of a workpiece, which have flexibility of use, allow automating and accelerating the process and obtain very reliable results.

These and other objects are achieved by a checking system and a method for checking, and by an assembly 30 equipment and a method for assembling according to the enclosed claims.

A main advantage of the present invention consists in the opportunity of checking the mutual position and, at the

same time, the attitude of components of a workpiece, in particular of having all the information necessary to check also the attitude of said components when the wanted axial position has been reached.

5 These and other objects and advantages of the present invention will become apparent from the detailed description that follows.

Brief Description of the Drawings

10 The present invention is now described with reference to the attached drawings, given by way of non-limiting examples, wherein:

- figure 1 is a schematic view of the longitudinal section of an equipment for assembling components of a workpiece, comprising a checking system according to a preferred embodiment of the present invention, with some details omitted for the sake of simplicity;

15 - figure 2 schematically shows an enlarged longitudinal section along the line II-II of figure 1 of a component of the equipment of figure 1, in particular a checking system according to a preferred embodiment of the present invention, shown in an operating phase;

20 - figure 3 is a perspective view of the component of figure 2, shown in an operating phase different from that illustrated in figure 2;

25 - figure 4 schematically shows a longitudinal section of a checking system according to an alternative embodiment of the present invention.

Best Mode for Carrying Out the Invention

30 Figure 1 shows in a schematic way the section of an equipment **M** for assembling a workpiece with a first component **29** constituted by an E-block provided with a

suitable hole **31** apt to define an axis **E**, and a second component **30** constituted by a bearing designed to allow moving parts to rotate about a rotation axis **C** with respect to stationary parts (figure 3). The equipment **M** comprises a checking system **1** according to the present invention, that includes a base **2** and a reference system **3**, connected to the base **2**, with a reference element or nosepiece **6**. Referring for example to a right-handed Cartesian coordinate system identified by Cartesian axes **X**, **Y** and **Z**, the reference nosepiece **6** is apt to define a reference plane parallel to the Cartesian axes **X** and **Y**, and a main axis **H** perpendicular to the reference plane. The reference nosepiece **6** substantially features cylindrical shape with a through bore **61**, a reference annular surface **63** adapted to locate the E-block **29** so that the axis **E** of the hole **31** of the E-block **29** is aligned to the main axis **H**, and two side openings **62**. A floating element **8** with two opposite longitudinal portions **18** and **19** is partially housed in the reference nosepiece **6** and protrudes from the two side openings **62**, the longitudinal portion **18** and only one side opening **62** being visible in figure 1. A size of the floating element **8**, more specifically the main size in the embodiment shown in figures 1, 2 and 3, extends around a direction parallel to the reference plane, for example parallel to the Cartesian axis **X**, therefore orthogonal to the main axis **H**, and the two side openings **62** feature shape and dimensions such that the floating element **8** is movable with respect to the reference plane and able to assume a position closely related to the position of the bearing **30**.

The equipment **M** comprises also a locking device **4** adapted to lock the E-Block **29** against the reference nosepiece **6**, a positioning device **5** adapted to define a starting position of the second component **30**, for example a

centering element to arrange the bearing **30** so that the rotation axis **C** of the latter is essentially aligned to the axis **E** of the hole **31** of the E-Block **29**, and an insertion device or piston **9** driven by an actuator **10** to thrust the bearing **30** in a direction parallel to the main axis **H** and insert it inside the hole **31** as far as it reaches a wanted axial position.

The checking system **1** comprises also a detection system that includes at least two detection devices, for example a first detection device and a second detection device, intended to cooperate with one of the bearing **30** and a specific component of the checking system **1**, such specific component being adapted to be coupled to the bearing **30**. The checking system **1** is adapted to define at least two checking areas, for example a first checking area and a second checking area, spaced apart from each other. In particular, the first detection device is adapted to define the first checking area and the second detection device is adapted to define the second checking area, said at least two detection devices being intended to operate at the same time, each on the respective checking area. By means of said at least two detection devices cooperating with one of the bearing **30** and the specific component of the checking system **1**, the detection system is adapted to detect, at said at least two checking areas, quantities indicative of the mutual disposition, that is the position and the attitude, of the bearing **30** relative to the E-Block **29**. To be more precise, the detection system is adapted to detect quantities indicative of the position of the bearing **30** relative to the E-Block **29** during the insertion inside the hole **31** and at least as far as the wanted axial position is reached, and quantities indicative of the

attitude of the same bearing **30** in the wanted axial position.

In a preferred embodiment of the invention, for example, the already mentioned specific component consists in the floating element **8**, and the detection system comprises a first and a second detection devices of optoelectronic shadow casting type, only one of them being visible in figure 1, placed each at one of the longitudinal portions **18** and **19** of the floating element **8** and in positions advantageously equidistant from the main axis **H**, the two detection devices being intended to cooperate with the floating element **8**. Alternatively, the specific component can consist in the bearing **30**, as a consequence the first and the second detection devices can be intended to cooperate with the bearing **30**. Each detection device is adapted to define a check optical plane, perpendicular to the reference plane and including one of said first and second checking areas, and is constituted by an optoelectronic emitter **A** and an optoelectronic receiver **B**, to emit and detect, respectively, for example infrared rays (schematically represented in figures 1 and 3 with an area delimited by dotted lines) laying on the check optical plane. In this preferred embodiment, each of the longitudinal portions **18** and **19** of the floating element **8**, as being interposed between one emitter **A** and the related receiver **B**, is intended to partially intercept the emitted rays at the related checking area that corresponds to a section on the related check optical plane of the same longitudinal portion **18**, **19**, and determine a grey area on the related receiver **B**. A processing unit **50** is connected to the detection system, in particular to the receivers **B** to receive and process information concerning the rays they have detected in order to find out information about the

mutual position of the bearing **30** relative to the E-Block **29**, in particular the position of the bearing **30** within the hole **31** of the E-block **29**. The processing unit **50** is also connected to the actuator **10** to send it control signals.

5 As it is schematically illustrated in the enlargement of figure 2, the reference system **3** comprises, besides the reference nosepiece **6**, a sphere **11** and a thrust element **12**, for example a pneumatic cylinder. The reference nosepiece **6** comprises a lower opening **64** wherein the sphere **11** is
10 housed and can slide along the direction parallel to the main axis **H**, the sphere **11** being thrust by the pneumatic cylinder **12** and moving, on turn, the floating element **8** by means of a rest element **16** belonging to the checking system **1**. The floating element **8** is connected to a coupling
15 element, for example a floating nosepiece **17** with a rest surface **67**, adapted to come into contact with the bearing **30** and reproduce the attitude of the latter. In particular, the floating element **8** is tightened by means of a not illustrated screw between the rest element **16** and the
20 floating nosepiece **17**.

Figure 3 shows the floating element **8** suitably shaped. In more detail, in a preferred embodiment of the invention, the floating element **8** is shaped with two converging plane surfaces **81** and **82** which define an edge **83** that lies on a
25 plane, on which the main axis **H** also lies, perpendicular to the check optical plane. The longitudinal portions **18** and **19** comprise also a check surface **84**, opposed to the edge **83**, with two longitudinal borders **86** and **87** and has such an orientation, for example it is conveniently inclined less
30 than 10°, to allow, for restricted values of the angle of rotation about the Cartesian axis **X**, only one of the two longitudinal borders, in figure 3 the longitudinal border **86** pointing to the optoelectronic emitters **A**, to cooperate

with the first and the second optoelectronic detection devices, that is to intercept the infrared rays emitted by the emitters **A**. One of the two longitudinal portions, for example the longitudinal portion **19**, comprises a slot **85**
5 for a guide pin **14** connected to the base **2**.

The equipment **M**, by means of the optoelectronic checking system **1**, enables the check of the instant position of the bearing **30** relative to the E-Block **29**, being said check included in the insertion process, and the
10 check of the roll and pitch angles, respectively defined as rotations about the Cartesian axis **X** and about the Cartesian axis **Y** of the reference plane, perpendicular to the main axis **H**, of the same bearing **30** located at the wanted axial position.

15 A method for checking according to the present invention is described in detail hereinafter, such method employing the optoelectronic checking system **1** of the equipment **M**.

In a preliminary phase of calibration, the check of a
20 master **40**, partially visible in figure 2, is carried out in order to determine the reference values for the subsequent checks. The master **40** is suitably shaped to comprise an external surface **43** that reproduces the theoretical disposition of a positioning surface of the E-block **29**, and
25 an internal surface **47** that reproduces the disposition, that is position, pitch angle and roll angle, of a working surface of the bearing **30** at the wanted axial position within the E-block **29**. The master **40**, at the external surface **43**, is located on the reference annular surface **63**
30 of the reference nosepiece **6**, and locked by the locking device **4**. Then, the pneumatic cylinder **12** thrusts the sphere **11** against the rest element **16**. By means of the already cited tightening of the floating element **8** between

the rest element **16** and the floating nosepiece **17**, the rest surface **67** of the latter comes into contact with the internal surface **47** of the master **40**, so that the floating nosepiece **17** reproduces the attitude of the internal surface **47**. As a consequence, the floating element **8** assumes the attitude of the floating nosepiece **17**, and a position closely related to the position of the master **40**. In particular the position of the edge **83** belonging to the floating element **8** is closely related to the position of the internal surface **47** of the master **40**.

Each emitter **A** emits infrared rays directed towards the related receiver **B**. The longitudinal portions **18** and **19** of the floating element **8** partially intercept the emitted rays and determine a grey area on the receivers **B**. A receiver **B** detects the projection along the direction parallel to the main axis **H** of a section of the longitudinal portion **18**, at the same time the other receiver **B** detects the projection along the same direction of a section of the longitudinal portion **19**. For each section, the relative projection is indicative of a virtual thickness of the corresponding longitudinal portion **18**, **19**, that extends from the projection of the longitudinal border pointing to the optoelectronic emitters **A**, to the projection of the edge **83**, and of a position of the same edge **83**. The virtual thickness detected by the optoelectronic detection device mainly depends on the position of the longitudinal border pointing to the optoelectronic emitters **A**, that depends on the slope of the check surface **84** with respect to the reference plane. Such a slope depends on both the geometric characteristics and the attitude of the floating element **8**, said attitude, as previously said, being that of the internal surface **47** of the master **40**.

The processing unit **50** receives and processes in a known way the results of the detection to obtain information about the position of the edge **83** and about the attitude of the floating element **8**. Reference values, for example equal to zero, can be linked to said position and attitude, that is the pitch angle and the roll angle, of the working surface of the bearing **30** at the wanted axial position within the E-block **29**.

For restricted values of the angle of rotation about the Cartesian axis **X**, detecting both positive variations and negative variation of the roll angle is possible, thanks to the suitable slope of the check surface **84** and to the position of the edge **83**. If the slope of the check surface **84** is such that its two longitudinal borders alternatively intercept the infrared rays emitted by the emitters **A**, and/or the edge **83** has a position different from that previously described, the increase of the detected thickness would not be indicative of the sense of rotation of the floating element **8** about the Cartesian axis **X**. The highlighted expedients, indeed, make the variation of the virtual thickness directly dependent on the sense of rotation of the floating element **8**. Only by way of example, it has to be noted that, with respect to the view of figure 3, a clockwise rotation of the floating element **8** about the Cartesian axis **X** corresponds to a reduction of the virtual thickness (and of the roll angle), whereas a counter-clockwise rotation corresponds to an increase of the virtual thickness (and of the roll angle).

Once the preliminary phase of calibration is finished, the master **40** is taken away from the equipment **M** and the assembly phase occurs, that includes a method for checking according to the present invention.

In this phase, the E-block **29**, at the positioning surface, is located on the reference annular surface **63** of the reference nosepiece **6**, so that the axis **E** of the hole **31** is aligned to the main axis **H**, and locked by the locking device **4**, while the bearing **30**, by means of the centering element **5**, is arranged so that its rotation axis **C** is essentially aligned to the axis **E** of the hole **31**. The insertion piston **9**, driven by the actuator **10**, thrusts the bearing **30** in the direction parallel to the main axis **H**, and makes it move towards the hole **31** and inside it. The pneumatic cylinder **12** thrusts the sphere **11** against the rest element **16** and, by means of the already cited tightening of the floating element **8** between the rest element **16** and the floating nosepiece **17**, the rest surface **67** of the floating nosepiece **17** moves towards the bearing **30**, up to come into contact with the working surface of the latter. The force exerted by the pneumatic cylinder **12** on the sphere **11** is such as to maintain the rest surface **67** of the floating nosepiece **17** in contact with the working surface of the bearing **30**, but not to prevent the advancing movement of the latter. Thus, the floating element **8** assumes a position closely related to an instant position of the bearing **30**, in particular the edge **83** of the floating element **8** assumes a position closely related to an instant position of the working surface of the bearing **30**, variable during the advancement process and generally different from the reference value defined in the preliminary phase of calibration.

Alike the preliminary phase of calibration, one of the two optoelectronic detection devices detects the projection along the direction parallel to the main axis **H** of a section of the longitudinal portion **18**, at the same time the other of the two optoelectronic detection device

detects the projection along the same direction of a section of the longitudinal portion **19**. Each of the two detected projection is indicative of the position of the borders of the floating element **8**, in particular of the edge **83**. The processing unit **50** receives and processes in a known way the values of the upper bounds of the projections detected by the two optoelectronic detection devices in order to obtain information about the position of the edge **83**. On the basis of the value of this position and the reference value defined in the preliminary phase of calibration, the processing unit **50** checks in real time the instant position of the working surface of the bearing **30**, that is it finds out information about the position of the bearing **30** within the hole **31** of the E-block **29**.

The detection and the processing are conveniently carried out in a continuous way during the advancing movement of the bearing **30**, as far as the latter reaches the wanted axial position. When it occurs, in particular the instant position of the working surface of the bearing **30** coincides, for less than an acceptable tolerance, with the wanted axial position, the processing unit **50** sends a stop signal to the actuator **10**, that, as a consequence, stops the advancing movement of the bearing **30**.

At the wanted axial position, the information, acquired during the check of the axial position and that the checking system **1** has available, includes the information necessary to verify also the attitude of the bearing **30**, that is the pitch angle and the roll angle of the working surface of the same bearing **30**. The virtual thickness of the longitudinal portions **18** and **19** detected by the optoelectronic detection devices, indeed, depends on the slope of the check surface **84** with respect to the reference plane, determined by both the geometric

characteristics and the attitude of the floating element **8**, attitude which, in this phase, is that of the working surface of the bearing **30**. The processing unit **50** can then process in a known way the values of the projections
5 detected by the two optoelectronic detection devices in order to obtain information about the pitch angle and the roll angle of the floating element **8** without carrying out further and distinct checking cycles. On the basis of the results of the processing and the reference values defined
10 in the preliminary phase of calibration, the processing unit **50** verifies the proper attitude of the bearing **30**.

Variations can be made to the checking system **1** hitherto described, without departing from the object of the present invention.

15 Components with shape and/or dimensions different from those illustrated can be utilized, in particular the longitudinal portions **18** and **19** of the floating element **8** can be shaped in a different way and show for example the check surface **84** in place of the edge **83** and vice-versa, or
20 the check surface **84** can be characterized by a different slope.

The two detection devices can be allocated each one of the longitudinal portions **18** and **19** and in any position relative to the main axis **H**, otherwise both at only one of
25 the longitudinal portions **18** and **19** and at a certain distance from each other.

Possibly, the checking system **1** can carry out the check of the pitch and roll angles of the working surface of the bearing **30** also during the advancing movement of the
30 bearing **30** along the direction parallel to the main axis **H** and its insertion inside the hole **31** of the E-block **29**.

Figure 4 shows a checking system **1'** in a different embodiment of the present invention. Unlike the previously

described preferred embodiment, in this case the specific component consists in the rest element **16** featuring a checking surface, for example a checking circular surface **65**. The detection system comprises also a third detection
5 device adapted to define a third checking area, the three checking areas being spaced from each other and intended to cooperate with the checking circular surface **65**. In this case, the first, the second and the third detection devices are partially allocated within the lower opening **64** and
10 connected to the processing unit **50**. The three detection devices comprise for example three contact sensors **7** having a touching element or feeler **71** each, adapted to cooperate with, that is to touch, the checking circular surface **65** of the rest element **16**, at the first, the second and the third
15 checking area, substantially a point, and a stem **72** with measuring elastic force, adapted to keep the feelers **71** in contact with the checking circular surface **65**, connected to a transduction device or transducer, not shown in figure. Alternatively, the stems **72** of the three contact sensors **7**
20 can feature measuring pneumatic thrust, to bring the feelers **71** in contact with the checking circular surface **65** following the control signal received, for example, from the processing unit **50**. Preferably, the contact sensors **7** are arranged so that the three checking areas are
25 equidistant from the main axis **H** and their geometrical center of gravity is a point of the main axis **H**. In this different embodiment of the invention, the longitudinal portions **18** and **19** can have dimensions smaller than in the preferred embodiment, as it is shown in figure, for benefit
30 of the total amount of space and of the firmness of the checking system **1'**, although being still partially located each in one of the side openings **62** in order to limit the

movements of the rest surface **67** of the floating nosepiece **17**.

A method for checking according to the present invention, that uses the checking system **1'**, is described
5 in the following.

In the preliminary phase of calibration, the master **40**, at the external surface **43**, is located on the reference annular surface **63** of the reference nosepiece **6**, and locked by the locking device **4**. Similarly to what previously
10 described, the floating nosepiece **17** and, as a consequence, the checking circular surface **65** of the rest element **16**, reproduce the attitude and take a position closely related to the position of the internal surface **47** of the master **40**, corresponding to known pitch angle, roll angle and
15 position of the working surface of the bearing **30** put in the wanted axial position inside the E-block **29**. Each of the three feelers **71** cooperates with the checking circular surface **65** and the related contact sensor **7** provides an indication of the position of the corresponding checking
20 area. The processing unit **50**, in order to obtain information about the position and the attitude of the checking circular surface **65**, processes in a known way the results of the detection, to which it links the reference values, for example equal to zero, corresponding to the
25 known position and attitude, that is the pitch and roll angles, of the working surface of the bearing **30** at the wanted axial position inside the E-block **29**.

Once the preliminary phase of calibration is finished, the master **40** is taken away from the equipment **M**, the E-
30 block **29**, at the positioning surface, is located on the reference annular surface **63** of the reference nosepiece **6** to align the axis **E** of the hole **31** to the main axis **H**, then locked by the locking device **4**. The bearing **30**, by means of

the centering element **5**, is arranged so that its rotation axis **C** is essentially aligned to the axis **E** of the hole **31**, and, by means of the insertion piston **9** driven by the actuator **10**, thrusts along a direction parallel to the main axis **H** towards the hole **31** and inside it. The working surface of the bearing **30** moves towards the floating nosepiece **17** up to the contact with the rest surface **67** of the latter. In this condition, the floating nosepiece **17** and, consequently, the checking circular surface **65** of the rest element **16**, assume a position closely related to the position of the working surface of the bearing **30**. The three feelers **71** cooperate with the check surface **65** and the related transducers **7** give an indication of the axial position of the corresponding checking areas. The processing unit **50** processes in a known way the results of the detection to obtain information about the position of the check surface **65**. Comparing the value of this position with that of the master defined in the preliminary phase of calibration, the processing unit **50** checks in real time the instant position of the working surface of the bearing **30**, that is it finds out information about the position of the bearing **30** within the hole **31** of the E-block **29**.

Similarly to what previously seen, also the checking system **1'** can advantageously carry out in a continuous way the detection and the processing during the advancing movement of the bearing **30**. When the instant position of the working surface of the bearing **30** coincides, for less than an acceptable tolerance, with the wanted axial position, the processing unit **50** sends a stop signal to the actuator **10**, that, as a consequence, stops the advancing movement of the bearing **30**.

Also in this case, as the bearing **30** reaches the wanted axial position, the checking system **1'** can

advantageously supply information about the pitch and roll angles of the working surface of the bearing **30** and verify the accuracy of the attitude, without carrying out further checking cycles.

5 As an alternative, the detection system can comprise a different number of detection devices with respect to what stated hitherto, in other words the detection system of the checking system **1** can comprise further optoelectronic detection devices in addition to the described two, and the
10 detection system of the checking system **1'** can comprise further contact sensors **7** in addition to the described three, or only two contact sensors **7** suitably arranged, for example to define two checking areas in positions similar to those of figure 3.

15 The advantages that derive from the application of the present invention are evident. The checking system **1**, **1'** and the methods according to the invention allow carrying out the check of the position of components of a workpiece, in particular of bearings **30** inside the E-block **29**, without
20 the need of re-arrange the devices of the detection system to carry out distinct checks at different transversal sections, with favorable increase of the mechanical stability of the system and reduction of the detection time. In addition, they allow carrying out the check of the
25 procedure for assembling workpieces having components such as those cited, and automating said checking procedure by means of a suitable equipment **M**.

 The checking systems **1**, **1'**, the methods and the apparatus **M** according to the present invention also allow
30 having the information necessary to verify the accuracy of the attitude of the components, in particular of bearings inside the E-block, without carrying out further and

different checks in addition to those for checking the position.

CLAIMS

1. Checking system (1, 1') for checking mutual position of a second component (30) of a workpiece relative to a first component (29) of the workpiece, the first component (29) being apt to define an axis (E), comprising:

- a reference system (3) apt to define a reference plane and a main axis (H) perpendicular to the reference plane, and locate the first component (29) of the workpiece so that the axis (E) of the first component (29) is aligned to the main axis (H);
- a detection system adapted to define at least a first checking area and a second checking area spaced apart from each other, and detect, at said at least first and second checking areas, quantities indicative of the mutual position of the second component (30) of the workpiece relative to the first component (29) of the workpiece; and
- a processing unit (50) connected to the detection system, adapted to receive and process said quantities in order to find out information about said mutual position;

characterized in that the detection system includes at least a first detection device adapted to define the first checking area, and a second detection device adapted to define the second checking area, said at least first and second detection devices being intended to operate at the same time, each on the respective checking area, and cooperate with one of the second component (30) of the workpiece and a specific component (8, 16) of the checking system (1, 1'), said specific component (8, 16) being adapted to be coupled to the second component (30).

2. Checking system (**1**, **1'**) according to claim 1, wherein the reference system (**3**) comprises a coupling element (**17**) adapted to come into contact with the second component (**30**) of the workpiece, and the specific component consists in a floating element (**8**) connected to the coupling element (**17**), movable with respect to the reference plane and able to assume a position closely related to the position of said second component (**30**), a size of the floating element (**8**) extending around a direction orthogonal to the main axis (**H**), said at least first detection device and second detection device being intended to cooperate with the floating element (**8**).

3. Checking system (**1**, **1'**) according to claim 1 or claim 2, wherein said first detection device and second detection device are placed equidistant from the main axis (**H**).

4. Checking system (**1**) according to any one of the preceding claims, wherein said first detection device and second detection device are of the optoelectronic shadow casting type, each detection device being adapted to define a check optical plane including one of said first and second checking areas.

5. Checking system (**1**) according to claim 4, wherein the floating element (**8**) comprises two converging plane surfaces (**81**, **82**) adapted to define an edge (**83**) lying on a plane passing through the main axis (**H**) and perpendicular to said two check optical planes, and a checking surface (**84**), opposite to the edge (**83**), comprising two longitudinal borders (**86**, **87**), the checking surface (**84**) having such an orientation to allow substantially only one (**86**) of the longitudinal borders to cooperate with said first detection device and second detection device.

6. Checking system (**1'**) according to any one of claims from 1 to 3, comprising a rest element (**16**) featuring a checking

surface (65), the specific component consisting in the rest element (16), and the detection system comprises at least a third detection device adapted to define a third checking area, each of said first, second and third detection
5 devices comprising a contact sensor (7) with a feeler (71), each feeler (71) being adapted to cooperate with the checking surface (65) of the rest element (16), at one of said first, second and third checking areas.

7. Method for checking mutual position of a second
10 component (30) of a workpiece relative to a first component (29) of the workpiece, the first component (29) being apt to define an axis (E), comprising the steps of:

- locating the first component (29) of the workpiece to a reference system (3) apt to define a reference plane
15 and a main axis (H) perpendicular to the reference plane, so that the axis (E) of the first component (29) is aligned to the main axis (H);
- defining at least a first checking area and a second checking area spaced apart from each other;
- 20 – detecting at said at least first and second checking areas quantities indicative of said mutual position; and
- processing such quantities in order to find out information about said mutual position;

25 the method being characterized in that the quantities indicative of the mutual position of the second component (30) of the workpiece relative to the first component (29) of the workpiece are detected at the same time at said first checking area and second checking
30 area.

8. Method according to claim 7, comprising the further steps of:

– defining said mutual position as an axial position of the second component (30) of the workpiece relative to the first component (29) of the workpiece;

– moving the second component (30) of the workpiece with respect to the first component (29) of the workpiece;

wherein the step of detecting and processing the quantities indicative of the axial position of the second component (30) of the workpiece relative to the first component (29) of the workpiece is carried out together with the step of moving the second component (30) of the workpiece, and the reaching of a wanted axial position is checked.

9. Method according to claim 7 or claim 8, comprising the further step of processing said quantities indicative of said mutual position of the second component (30) of the workpiece relative to the first component (29) of the workpiece in order to find out information about the attitude of said second component (30).

10. Method according to any one of claims from 7 to 9, wherein said first component (29) of the workpiece is an E-block with a hole (31) that defines the axis (E), and said second component (30) of the workpiece is a bearing, said mutual position being an axial position of the bearing (30) within the hole (31) of the E-block (29).

11. Assembly equipment (M), to assembly a first component (29) and a second component (30) of a workpiece, comprising:

– a locking device (4) adapted to lock the first component (29) of the workpiece against a reference element (6) of the reference system (3) that defines a reference plane and a main axis (H) perpendicular to the reference plane;

- a positioning device (5) adapted to define a starting position of the second component (30) of the workpiece;
 - an insertion device (9) adapted to cooperate with and
5 move substantially along said main axis (H) the second component (30) of the workpiece; and
 - a checking system (1, 1') for checking mutual position of said first component (29) and second component (30) of the workpiece, according to any one of claims from
10 1 to 6.
12. Method for assembling a first component (29) and a second component (30) of a workpiece, the first component (29) being apt to define an axis (E), comprising the steps of:
- 15 - defining a position of the first component (29) of the workpiece by means of a reference system (3) apt to define a reference plane and a main axis (H) perpendicular to the reference plane, so that the axis (E) of the first component (29) is aligned to the main
20 axis (H);
 - locking the position of the first component (29) of the workpiece;
 - moving the second component (30) of the workpiece towards and inside a hole (31) of the first component
25 (29) of the workpiece substantially along a direction parallel to the main axis (H);
 - checking mutual position of said first component (29) of the workpiece and second component (30) of the workpiece along said direction parallel to the main
30 axis (H) with a method according to claim 8;
 - stopping movement of the second component (30) of the workpiece when it reaches the wanted axial position.