



- (51) International Patent Classification:
F15D 1/02 (2006.01) *G01F 1/50* (2006.01)
- (21) International Application Number:
PCT/US2014/037876
- (22) International Filing Date:
13 May 2014 (13.05.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13/896,947 17 May 2013 (17.05.2013) US
- (71) Applicant (for all designated States except US): CAMERON INTERNATIONAL CORPORATION [US/US];
P.O. Box 1212, Houston, TX 77251 (US).
- (72) Inventor; and
- (71) Applicant (for US only): BROWN, Gregor, J. [GB/GB];
81 Ayr Road, Prestwick, Ayrshire, Scotland KA9 1TF (GB).

- (74) Agent: SCHWARTZ, Ansel, M.; Attorney at Law, 201 N. Craig Street, Suite 304, Pittsburgh, PA 15213 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

- (54) Title: FLOW CONDITIONER AND METHOD FOR OPTIMIZATION




FIG. 1A
PRIOR ART

(57) Abstract: A flow conditioner for a circular pipe having an axis. The flow conditioner includes a plate having a face to be disposed in the circular pipe with the face of the plate perpendicular to the axis of the pipe. The plate has a central circular passage area through which fluid flows surrounded by two or more concentric arrays of segmented annular passages for fluid flow defined by separating and subdividing ligaments, with at least one subdividing ligament having a width different than a width of a second subdividing ligament. There may be at least one array of annular passages having a radial width different than a radial width of a second array of annular passages and at least one subdividing ligament having a width different than a width of a second subdividing ligament. A method of producing an optimized geometry of flow conditioner for a circular pipe having an axis.





TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

5 February 2015