

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/018825 A3

(51) International Patent Classification⁷: **F16L 35/00**

(21) International Application Number:
PCT/US2003/026365

(22) International Filing Date: 22 August 2003 (22.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/405,683 23 August 2002 (23.08.2002) US
10/646,680 22 August 2003 (22.08.2003) US

(71) Applicant: **DRIL-QUIP, INC.** [US/US]; 13550 Hempstead Hwy., Houston, TX 77040 (US).

(72) Inventors: **MILBERGER, Lionel, J.**; 8911 Rock Lane, Houston, TX 77077 (US). **MCCANNA, Jason, C.**; 2850 Wallingford Drive, Apartment 111, Houston, TX 77042 (US).


(74) Agent: **HELMREICH, Loren, G.**; Browning Bushman P.C., 5718 Westheimer, Suite 1800, Houston, TX 77057 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: RISER CONNECTOR



(57) Abstract: A tabular connection (7) is provided for connecting an upper tubular member (10) with a lower tubular member (12). A radially movable latch body (20) is positioned outward of the tabular members. Outer load flanks (25) on the latch body are slidably engageable with inner load flanks (24) on the tubular members. A radially projecting member (32) and a corresponding guide recess (34) are provided for guiding the latch body with respect to one of the tubular members. A safety actuator (30) and corresponding mating surface (38) may also be provided for urging the latch body outward.



Published:

- *with international search report*
- *with amended claims*

Date of publication of the amended claims:

23 September 2004

(88) Date of publication of the international search report:
12 August 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.