

Description

The present invention relates to modular electrical connectors, e.g. connectors commonly referred to as modular phone receptacles or jacks, and to methods of making same.

Modular electrical connectors known as modular phone receptacles or jacks have been known in the art for many years. Although connectors of this type were originally designed in the telecommunications industry and, in particular, for telephones, these connectors have found wide acceptance other than for connecting a telephone to a telephone network. Other common uses include an input/output (I/O) interface with other communications peripheral equipment.

Modular phone jacks are adapted to receive a conventional modular plug. Thus, the jack has a housing with a plug-receiving socket formed therein to receive the plug. The socket is defined by a plug-receiving opening, opposed top and bottom surfaces joined by opposed side surfaces extending from said opening to join a back surface.

A plurality of stamped, metallic elongated conductors are mounted to the housing in some fashion. Each conductor includes a contact portion at one end extending diagonally into the socket, a lead portion at the other end and an intermediate portion between said contact portion and lead portion.

It is advantageous to form the metallic conductors from flat stock. In this manner a plurality of conductors can be stamped at one time. Two examples of modular phone jacks employing flat stamped metallic conductors are disclosed in United States Patent Nos. 4,292,736 and 4,315,664. Both of these patents disclose a one-piece dielectric housing having channels formed in the external surfaces thereof. The channels serve to locate and hold the flat stamped conductors therein.

U.S. Patent No. 4,292,736 discloses a method of producing a one-piece modular phone jack. The method generally comprises:

producing the housing as a one-piece molded part,

manufacturing the conductors as a continuous flat metal strip having a carrier strip with spaced-apart groups of conductors extending in side-by-side co-planar relationship, each group containing the number of conductors required for one of said jack assemblies, positioning the housing adjacent one of the groups of conductors so that the intermediate portions thereof are aligned with said holding and positioning means, moving the conductors normally of their axes towards the housing so that the intermediate portions of the conductors cooperate with said holding and positioning means,

bending first end portions of said conductors to

form the contact portions, and

bending second end portions of said conductors to form the lead portions.

Sometimes, to achieve greater modularity, it is preferred to produce a two-piece modular phone jack assembly. An example of such an assembly employing flat stamped metallic contacts is disclosed in United States Patent No. 4,327,958. Other examples of two-piece designs are disclosed in United States Patent Nos 4,202,593 and 4,274,691.

Typically, two-piece modular phone jack assemblies include a connector housing having a forward end with the plug receiving opening formed therein, two opposed sidewalls, the internal surfaces thereof defining said socket side surfaces, a top wall joining said sidewalls and a rearward end with a rear opening formed therein. A carrier subassembly is mounted through the rear opening of the housing. The subassembly has a dielectric support member to which the conductors are mounted. Means are provided which cooperate between the housing and subassembly to lock the subassembly to the housing. Such a two-piece modular phone jack is disclosed in Technical Digest, Western Electric, No. 74, July 1984, P. 17-18.

Although two-piece assemblies offer some advantages regarding mechanical strength and integrity, it has always been assumed that it is more expensive to manufacture and assemble a two-piece jack assembly as compared with a one-piece jack. This is mainly due to the fact that it has heretofore not been known how to automate such a manufacturing process.

The present invention provides, from one aspect, an improved low cost two-piece modular phone jack assembly of the type described above which is easier to manufacture and assemble. Said carrier subassembly member comprises:

a body portion adjacent said housing sidewalls and top wall and including a forwardly facing surface defining the back surface of the socket,

a base portion having means for receiving and holding the conductor lead portions, and

a conductor mounting portion joining and extending forwardly of said body portion having means formed thereon for positioning and holding the intermediate portions of the conductors which extend generally along the length thereof; whereby a continuously open conductor-receiving pathway is defined between a point within the socket and a point within open slots in the base portion.

The present invention further provides the new and improved method of manufacturing and assembling the modular phone jack assembly described herein comprising producing said support member so that it includes a body portion having a forwardly facing surface defining the back surface of the socket, a base portion having means for

receiving and holding the conductor lead portions and a conductor mounting portion joining and extending forwardly of said body portion and having a forward edge and rearward edge; and bending the first end portions and second end portions of the conductors simultaneously against the forward and rearward edges to form the contact portions and end portions respectively.

One way of carrying out the present invention in both its apparatus and method aspects will now be described by way of example, and not by way of limitation with reference to drawings which show one specific embodiment of a modular phone jack assembly of the present invention and various steps in its manufacture.

In the drawings:

Fig. 1 is a perspective view of the modular phone jack assembly of the present invention mounted on a printed circuit board with a modular plug positioned prior to mating;

Fig. 2 is a side sectional view of the modular phone jack assembly of the present invention;

Fig. 3 is an exploded perspective view of the modular phone jack assembly of the present invention taken from the rear thereof;

Fig. 4 is a plan view of a group of metal conductors used in association with the modular phone jack assembly of the present invention shown attached at both ends to a carrier strip;

Fig. 5 is a top plan view of a support member comprising a part of the modular phone jack assembly of the present invention;

Fig. 6 is a side view of the support member comprising a part of the modular phone jack assembly of the present invention showing the groups of conductors illustrated in Fig. 4 initially mounted at the top thereof;

Fig. 7 is a side view of the support member used in the modular phone jack assembly of the present invention mounted in a manufacturing tool illustrating a first step in the manufacturing process;

Fig. 8 is a view similar to Fig. 7 showing a succeeding step in the manufacturing process; and

Fig. 9 is another view similar to Figs. 7 and 8 illustrating still another succeeding step in the manufacturing process.

Turning now to the drawings, Fig. 1 shows the phone jack assembly of the present invention, generally designated 10, mounted on a printed circuit board 12. The jack assembly 10 is adapted to receive mate with a standard modular phone plug, generally designated 14.

The plug 14 is seen to generally include a housing 16 having a plurality of terminals 18 therein. The terminals 18 are adapted to electrically contact the jack assembly 10 at one end thereof

and the conductors (not shown) of the plug cord 20 at the other end. A manually manipulateable flexible latch 22 is formed on the plug housing 16 to lock and remove the plug 14 from the jack assembly 10.

The jack assembly 10 is of typical dimensions in order to comply with FCC regulation 68.5. As such, the jack assembly 10 has a plug-receiving socket, generally designated 24, formed and defined by a plug-receiving opening 26, opposed top and bottom surfaces, 28 and 30 respectively, which are joined by opposed side surfaces 32 and 34 which extend from said opening 26 to join a back surface 36.

The jack assembly 10 generally includes a connector housing, generally designated 38 which mounts a carrier subassembly, generally designated 40 (see Fig. 3). The carrier subassembly 40 includes a dielectric support member, generally designated 42, which mounts a plurality of stamped, metallic, elongated conductors, generally designated 44.

Looking at Figs. 1 to 3, the housing 38 includes a forward end with the plug receiving opening 26 formed therein. Surrounding opening 26 are two opposed sidewalls 46 and 48 wherein the internal surfaces thereof define the socket side surfaces 32 and 34, respectively, and a top wall 50 and an opposed bottom wall 52.

The front end of the housing 26 has a front mounting face 54 surrounding the plug opening 26. The mounting face 54 has a rearwardly facing surface 55 depending from top wall 50.

As best seen in Fig. 3, a three sided rear shrouded portion 56 extends from the top wall 50 and two side walls 46 and 48 to define the rear opening through which the carrier subassembly 40 is received to be mounted to the housing 38. Formed immediately forward of the shrouded portion 56 is comb structure 58 which is adapted to cooperate with the conductors 44 in a manner which will be described in greater detail hereinafter.

As is best seen in Figs. 1 and 3, the housing 38 has a pair of vertical locating ribs 60, one formed on each sidewall 46 and 48. The ribs 60 are adapted to engage a surface of a panel (not shown) immediately adjacent an opening through which the jack assembly 10 is received to provide a flush mount with the face of 54 of housing 38.

Looking at Fig. 3, guide channels 62 are formed on the interior of the shrouded portion 56 of sidewalls 46 and 48. The guide channels 62 extend forwardly to an opening 64 on each sidewall 46 and 48 which serves to interengage with a portion of the carrier subassembly 40 in a manner which will be described in greater detail hereinafter.

Housing 38 has a slot 66 formed in bottom wall 52 as is seen in Fig. 3. As with opening 64, slot 66

is adapted to interengage with a portion of the carrier subassembly 40 in a manner which will be discussed in greater detail hereinafter.

A pair of depending mounting pegs 68 are formed on the bottom wall 52 of housing 38. Pegs 68 are adapted to be received in suitable apertures (not shown) formed in the printed circuit board 12 in a well known manner to secure the jack assembly 10 thereto.

Turning now to the carrier subassembly 40 and, in particular, the support member 42 in greater detail, the support member 42 is seen to generally comprise a vertical portion 72 housing a rearwardly extending horizontal base portion 74 and a forwardly extending cantilevered top conductor mounting portion 76. The forwardly facing surface of body portion 72 defines the aforementioned back surface 36. The portion 72 also has a pair of side panel portions 78.

The top portion 76 of support member 42 has an upper surface 82 with a plurality of upstanding, staggered locating projections or pins 84. The front end of the top portion 76 has a front edge 86 (Fig. 5) with a plurality of conductor locating fins 88 formed thereat. The conductors 44 are mounted on the upper surface 82 of the top portion 76 so that a portion thereof extends from the front edge 86 to a rear edge 90 (Fig. 6).

A pair of side locking wings 92 are provided on the top portion 76. Locking wings 92 are receivable within guide channels 62 and interengage into openings 64 when the carrier subassembly 40 is mounted to the housing 38.

The base portion 74 has a rearwardly extending staggered contact receiving structure 96 with restricted contact receiving slots 98 formed therein. Each slot 98 has a tapered guide or throat portion 100 formed rearwardly as is best shown in Fig. 5 in order to guide a portion of a conductor 44 therein.

Extending laterally of the base portion 74 are a pair of standoff block portions 102. Block portions 102 underlie the shrouded portion 56 and comprise an extension of sidewalls 46 and 48 when the carrier subassembly 40 is mounted within the housing 38.

To further secure the carrier subassembly 40 into the housing 38, a pair of resilient tabs 104 extend forwardly of the base portion 74. Tabs 104 are adapted to be received within slot 66 in the housing and have hooked portions that engage shoulders (not shown) therein when the carrier subassembly 40 is mounted to the housing 38.

Looking at Fig. 3, each conductor is seen to generally include a contact portion 110, a lead portion 112 and an intermediate portion 114 therebetween. The intermediate portion 114 of each conductor 44 has a pair of spaced apart pilot holes 116 formed therein. The pilot holes 116 of adjacent

conductors 44 are staggered with respect to one another. Locating projections 84 are adapted to be received within pilot holes 116 so as to position the conductor 44 on the support member 42.

Each conductor 44 also includes a stop shoulder 118 formed on the lead portion 112 thereof. The stop shoulder 118 engages the bottom of the contact receiving structure 96 so as to prevent accidental removal of the lead portions 112 due to an upwardly directed pushout force.

When the carrier subassembly 40 is mounted within the housing 38, and held in that position by virtue of the interengagement of locking wings 92 with openings 64 and tabs 104 within slots 66, contact portions 110 of the conductors 44 are positioned and held apart by the comb structure 58. When fully assembled, the jack assembly 10 meets all the required specifications and has all the necessary dimensions to receive a standard modular phone plug 14.

In the past, it was widely accepted that the only reason to have a two-piece jack assembly was to achieve modularity. It was assumed that the manufacturing process and, in particular, the assembly procedure would be more complicated, and, therefore, more costly than a one-piece design.

As with a one-piece design, the conductors 44 are provided in a typical flat stamped metallic strip (not shown) consisting of a plurality of groups 124 of conductors (Fig. 4). Each group 124 of conductors 44 is stamped so that there are a pair of carrier strips 126, one at each end thereof.

The first step is to position a group 124 of conductors on the upper surface 82 of the top portion 76 of support member 42. The conductors 44 are accurately positioned by means of the upstanding projections 84 being received in the corresponding locating or pilot holes 116.

The next step, as best shown in Fig. 7, requires that the support member 42 and the positioned group 124 of conductors 44 are held or received within a suitable tool nest 128. The group 124 of conductors lie on top of an anvil 130 which faces a cutoff punch 132. When the punch 132 is actuated downwardly, the carrier strips 126 are removed while, simultaneously, the tops of the projections 84 are deformed or staked. After deformation, the cross-sectional area of the tops of the projections 84 is larger than the pilot holes 116. In this manner, the intermediate portions 114 of conductors 44 are accurately and permanently positioned and secured to the support member. It is because of this positive positioning that the succeeding steps of the method of production can be produced with a great deal of economy and efficiency.

Turning now to Fig. 8, the support member 42

which has the conductors 44 secured thereto, is positioned within a holding fixture 134. A top forming die 136 is downwardly moveable so that the conductors 44 are formed to produce the bends which divide the intermediate portion 114 from the contact portion 110 and lead portion 112. The contact portion 110 is about the front edge 86 of the top portion 76 while the lead portion 112 is formed about the rear edge 90. The downward bending of both the contact portions 110 and lead portions 112 of all of the conductors 44 occurs simultaneously unlike in the prior art.

After the contact portions 110 and lead portions 112 are initially formed, a second forming operation is performed as is shown in Fig. 9. The top forming die 136 is raised somewhat to allow for adequate clearance for a front forming die 138 and a rear forming die 140. Both forming dies 138 and 140 are moved simultaneously toward the support member 42 so that the contact portions 110 of the conductors 44 are angled rearwardly to their final position and the lead portions 112 are staggered and pushed into their respective contact receiving slots 98.

At the completion of the operation shown in Fig. 9, a finished carrier subassembly 40 is produced. The carrier subassembly 40 is then mounted into the housing 38 in the manner described above.

Because of the accurate and firm positioning of the conductors 44 on the support member 42, many of the manufacturing operations can be performed simultaneously. Many of these operations had to be performed one-at-a-time. Because of the efficiencies enjoyed by the structure of the jack assembly 10, the cost disadvantages of a two-piece assembly disappear. In addition to the manufacturing economies, a vastly superior structure from a mechanical strength point-of-view is produced. The usual concerns regarding the retention of flat conductors to a one-piece housing are eliminated.

It is to be understood that although a printed circuit board mounted jack assembly has been disclosed herein, the present invention could be used for other types of jack assemblies. For example, instead of a printed circuit board, the lead portions of the conductors may be electrically connected to a wire either by crimping or insulation displacement.

Claims

1. A two-piece modular phone jack assembly of the type having a plug-receiving socket (24) formed therein defined by a plug-receiving opening (26), opposed top and bottom surfaces (28,30) joined by opposed side surfaces

(32,34) extending from said opening to join a back surface (36), said jack assembly including a connector housing (38) having a forward end with the plug-receiving opening formed therein, two opposed side walls (46,48), the internal surfaces thereof defining said socket side surfaces, a top wall (50) joining said side walls, and a rearward end with a rear opening formed therein,

a carrier subassembly (40) in said housing mounted through said rear opening, said carrier subassembly having a dielectric support member (42) and a plurality of stamped, metallic elongated conductors (44) mounted on said support member, each conductor including a contact portion (110) at one end extending from said forward end diagonally into the socket, a lead portion (112) at the other end, and an intermediate portion (114) between said contact portion and lead portion, and

means (64),(92),(66),(104) cooperating between said housing and subassembly to lock said subassembly to the housing; whereby said carrier subassembly comprises

a body portion (72) adjacent said housing sidewalls and top wall and including an internal forwardly facing surface defining the back surface of the socket and an external rearwardly facing surface;

a base portion (74) joining the bottom of the body portion having means (96) for receiving and holding the conductor lead portions, said means including open slots (98); and

a conductor mounting portion (76) joining and extending forwardly of said body portion having an internal bottom surface defining the top wall of the socket and an upwardly facing conductor supporting surface (82), said conductor mounting portion having a forward edge supporting the contact portions of the conductors and a rearward edge joined to the top of the body portion supporting the lead portions of the conductors, and further having a plurality of positioning and holding means (84) upstanding from said upwardly facing surface between said edges for positioning and holding the intermediate portions of the conductors which extend generally along the length thereof;

whereby a continuously open conductor-receiving pathway is defined between a point within the socket along said upwardly facing conductor supporting surface and said rearwardly facing surface of said body portion and a point within said open slots in said base portion.

2. The jack assembly of claim 1 wherein the top wall of the housing overlies the conductor

which has the conductors 44 secured thereto, is positioned within a holding fixture 134. A top forming die 136 is downwardly moveable so that the conductors 44 are formed to produce the bends which divide the intermediate portion 114 from the contact portion 110 and lead portion 112. The contact portion 110 is about the front edge 86 of the top portion 76 while the lead portion 112 is formed about the rear edge 90. The downward bending of both the contact portions 110 and lead portions 112 of all of the conductors 44 occurs simultaneously unlike in the prior art.

After the contact portions 110 and lead portions 112 are initially formed, a second forming operation is performed as is shown in Fig. 9. The top forming die 136 is raised somewhat to allow for adequate clearance for a front forming die 138 and a rear forming die 140. Both forming dies 138 and 140 are moved simultaneously toward the support member 42 so that the contact portions 110 of the conductors 44 are angled rearwardly to their final position and the lead portions 112 are staggered and pushed into their respective contact receiving slots 98.

At the completion of the operation shown in Fig. 9, a finished carrier subassembly 40 is produced. The carrier subassembly 40 is then mounted into the housing 38 in the manner described above.

Because of the accurate and firm positioning of the conductors 44 on the support member 42, many of the manufacturing operations can be performed simultaneously. Many of these operations had to be performed one-at-a-time. Because of the efficiencies enjoyed by the structure of the jack assembly 10, the cost disadvantages of a two-piece assembly disappear. In addition to the manufacturing economies, a vastly superior structure from a mechanical strength point-of-view is produced. The usual concerns regarding the retention of flat conductors to a one-piece housing are eliminated.

It is to be understood that although a printed circuit board mounted jack assembly has been disclosed herein, the present invention could be used for other types of jack assemblies. For example, instead of a printed circuit board, the lead portions of the conductors may be electrically connected to a wire either by crimping or insulation displacement.

Claims

1. A two-piece modular phone jack assembly of the type having a plug-receiving socket (24) formed therein defined by a plug-receiving opening (26), opposed top and bottom surfaces (28,30) joined by opposed side surfaces

(32,34) extending from said opening to join a back surface (36), said jack assembly including a connector housing (38) having a forward end with the plug-receiving opening formed therein, two opposed side walls (46,48), the internal surfaces thereof defining said socket side surfaces, a top wall (50) joining said side walls, and a rearward end with a rear opening formed therein,

a carrier subassembly (40) in said housing mounted through said rear opening, said carrier subassembly having a dielectric support member (42) and a plurality of stamped, metallic elongated conductors (44) mounted on said support member, each conductor including a contact portion (110) at one end extending from said forward end diagonally into the socket, a lead portion (112) at the other end, and an intermediate portion (114) between said contact portion and lead portion, and

means (64),(92),(66),(104) cooperating between said housing and subassembly to lock said subassembly to the housing; whereby said carrier subassembly comprises

a body portion (72) adjacent said housing sidewalls and top wall and including an internal forwardly facing surface defining the back surface of the socket and an external rearwardly facing surface;

a base portion (74) joining the bottom of the body portion having means (96) for receiving and holding the conductor lead portions, said means including open slots (98); and

a conductor mounting portion (76) joining and extending forwardly of said body portion having an internal bottom surface defining the top wall of the socket and an upwardly facing conductor supporting surface (82), said conductor mounting portion having a forward edge supporting the contact portions of the conductors and a rearward edge joined to the top of the body portion supporting the lead portions of the conductors, and further having a plurality of positioning and holding means (84) upstanding from said upwardly facing surface between said edges for positioning and holding the intermediate portions of the conductors which extend generally along the length thereof;

whereby a continuously open conductor-receiving pathway is defined between a point within the socket along said upwardly facing conductor supporting surface and said rearwardly facing surface of said body portion and a point within said open slots in said base portion.

2. The jack assembly of claim 1 wherein the top wall of the housing overlies the conductor



mounting portion of the support member.

3. The jack assembly of claim 2 wherein the top wall of said housing has a depending flange (55) spaced forwardly from the forward edge of the conductor mounting portion of the support member, said conductors being received between said forward edge and said depending flange.
4. The jack assembly of any preceding claim wherein said housing further includes a bottom wall (52) joining said side walls, the internal surface of said bottom wall defining the bottom surface of said socket.
5. The jack assembly of claim 4 wherein said cooperating means includes locking members (104) extending forwardly of said base portion having hook means formed on the end thereof and a recess (66) formed in the bottom wall of said housing to receive said locking member, said recess having a shoulder to interengage with said hook means.
6. The jack assembly of any preceding claim wherein said upstanding positioning and holding means includes a plurality of upstanding locating pins (84) formed on the conductor mounting portion of the support member, and the intermediate portions of each conductor has a locating hole (116) to receive a respective pin therein.
7. The jack assembly of claim 6 wherein the holes and pins of adjacent conductors are staggered with respect to each other.
8. The jack assembly of claim 6 or 7 wherein each intermediate portion includes at least two spaced apart locating holes.
9. The jack assembly of claim 6, 7 or 8 including a plurality of fins (88) formed adjacent the forward edge of the conductor mounting portion cooperating with said pins to locate the conductors therebetween.
10. The jack assembly of any preceding claim wherein the housing has a contact comb (58) structure formed thereon, said comb structure having means to receive and separate the ends of the conductor contact portions.
11. The jack assembly of any preceding claim wherein said base portion is generally horizontal and extends rearwardly of said body portion at the bottom thereof and said conductor lead

portions extend downwardly beyond said base portion for connection to circuitry on a printed circuit board.

12. A method of making a modular phone jack assembly as claimed in claim 1 or 8 including the steps of producing said housing as a one-piece molded part,
producing said support member as a one-piece molded part,
manufacturing said conductors as a continuous flat metal strip having a carrier strip (126) with spaced-apart groups (124) of conductors extending in side-by-side coplanar relationship, each group containing the number of conductors required for one of said jack assemblies;
positioning said support member and one of the groups of conductors adjacent one another so that the intermediate portions of the conductors of the group are aligned with said positioning and holding means on said support member,
moving the group of conductors normally of their axes relative to said support member so that said intermediate portions of the conductors cooperate with said positioning and holding means, and
bending the first end portions and the second end portions of the conductors simultaneously against said forward and rearward edges to form the contact portions and lead portions, respectively.
13. The method of claim 12 when claim 12 is dependent upon claim 8, said positioning step including moving said group of conductors relative to the conductor mounting portion so that the locating pins are received within the locating holes.
14. The method of claim 13 including the step of staking the locating pins against the conductors after the positioning step to firmly secure the conductors to the conductor mounting portion of the support member.
15. The method of claim 14 including the step of severing the carrier strip from the conductors, said severing step occurring simultaneously with said staking step.
16. The method of claim 14 wherein said bending step includes a first conductor forming step simultaneously bending the first and second conductor end portions perpendicular relative to said conductor mounting portion and a second conductor forming step simultaneously



moving the first and second conductor end portions towards the body portion whereby the first end portions are angled toward the body portion and said second end portions are secured to said base portion.

Revendications

1. Ensemble de jack de téléphone modulaire, en deux pièces, du type comportant un logement (24) formé à l'intérieur, pour la réception d'une fiche mâle, ce logement étant délimité par une ouverture (26) d'introduction de la fiche mâle, des surfaces opposées supérieure et inférieure (28,30), reliées par des surfaces latérales opposées (32,34) s'étendant à partir de l'ouverture pour rejoindre une surface arrière (36), cet ensemble de jack comportant un boîtier de connecteur (38) ayant une extrémité antérieure dans laquelle est formée l'ouverture d'introduction de la fiche mâle, deux parois latérales opposées (46,48) dont les surfaces internes définissent les surfaces latérales du logement, une paroi supérieure (50) reliant ces parois latérales et une extrémité postérieure dans laquelle est formée une ouverture arrière, un sous-ensemble porteur (40) monté dans le boîtier, à travers son ouverture arrière, ce sous-ensemble porteur comportant un élément support diélectrique (42) et une pluralité de conducteurs métalliques allongés, estampés, (44) montés sur l'élément support, chaque conducteur comportant une portion de contact (110) à une extrémité, cette portion de contact s'étendant à partir de l'extrémité antérieure en diagonale vers et dans le logement, une portion de raccordement (112) à son autre extrémité et une portion intermédiaire (114) entre la portion de contact et la portion de raccordement, et des moyens (64,92,66,104) coopérant entre le boîtier et le sous-ensemble afin de verrouiller ce sous-ensemble dans le boîtier, le sous-ensemble porteur comprenant une portion de corps (72) adjacente aux parois latérales et à la paroi supérieure du boîtier et comportant une surface interne, tournée vers l'avant, définissant la surface arrière du logement, et une surface externe tournée vers l'arrière, une portion de base (74) reliée à la partie inférieure de la portion de corps, comportant des moyens (96) pour recevoir et maintenir les portions de raccordement des conducteurs, ces moyens comportant des rainures ouvertes (98), et une portion (76) de montage des conducteurs reliée à la portion de corps et s'étendant vers l'avant à partir de celle-ci, présentant une surface inférieure interne définissant la paroi supérieure du logement et une surface tournée

vers le haut (82), supportant les conducteurs, cette portion de montage des conducteurs ayant un bord avant supportant les portions de contact des conducteurs et un bord arrière relié au sommet de la portion de corps et supportant les portions de raccordement des conducteurs, et comportant en outre une pluralité de moyens de mise et de maintien en position (84) se dressant vers le haut à partir de la surface tournée vers le haut, entre les deux bords, afin de mettre et maintenir en position les portions intermédiaires des conducteurs qui s'étendent d'une manière générale suivant la longueur de ceux-ci, si bien qu'un trajet de réception des conducteurs, ouvert d'une manière continue, est défini entre un point à l'intérieur du logement, le long de la surface, tournée vers le haut, qui supporte les conducteurs et de la surface de la portion de corps qui est tournée vers l'arrière, et un point à l'intérieur des rainures ouvertes prévues dans la portion de base.

2. Ensemble de jack suivant la revendication 1 caractérisé en ce que la paroi supérieure du boîtier surplombe la portion de montage des conducteurs de l'élément support.
3. Ensemble de jack suivant la revendication 2 caractérisé en ce que la paroi supérieure du boîtier présente une bride en saillie (55) laquelle est espacée vers l'avant du bord avant de la portion de montage des conducteurs de l'élément support, les conducteurs étant logés entre ce bord avant et la bride en saillie.
4. Ensemble de jack suivant l'une quelconque des revendications précédentes caractérisé en ce que le boîtier comporte en outre une paroi inférieure (52) reliant ces parois latérales, la surface interne de cette paroi inférieure définissant la surface inférieure du logement.
5. Ensemble de jack suivant la revendication 4 caractérisé en ce que les moyens coopérant comportent des organes de verrouillage (104) s'étendant vers l'avant à partir de la portion de base, présentant des moyens à crochet formés à leurs extrémités, et un creux (66) formé dans la paroi inférieure du boîtier, afin de recevoir ces organes de verrouillage, ce creux présentant un épaulement coopérant avec les moyens à crochet.
6. Ensemble de jack suivant l'une quelconque des revendications précédentes caractérisé en ce que les moyens de mise et de maintien en position s'étendant vers le haut comportent



une pluralité d'ergots de mise en position (84) s'étendant vers le haut, formés sur la portion de montage des conducteurs de l'élément support, et la portion intermédiaire de chaque conducteur présente un trou de mise en position (116) destiné à recevoir, à l'intérieur, un ergot respectif.

7. Ensemble de jack suivant la revendication 6 caractérisé en ce que les trous et les ergots de conducteurs voisins sont décalés les uns par rapport aux autres.

8. Ensemble de jack suivant l'une quelconque des revendications 6 ou 7 caractérisé en ce que chaque portion intermédiaire comporte au moins deux trous de mise en position espacés l'un de l'autre.

9. Ensemble de jack suivant l'une quelconque des revendications 6, 7 ou 8 caractérisé en ce qu'il comporte une pluralité d'ailettes (88) adjacentes au bord avant de la portion de montage des conducteurs et coopérant avec les ergots afin de loger les conducteurs entre elles.

10. Ensemble de jack suivant l'une quelconque des revendications précédentes caractérisé en ce que sur le boîtier est formée une structure en forme de peigne (58) pour la réception des contacts, cette structure en forme de peigne comportant des moyens pour recevoir et séparer les extrémités des portions de contact des conducteurs.

11. Ensemble de jack suivant l'une quelconque des revendications précédentes caractérisé en ce que la portion de base est généralement horizontale et elle s'étend vers l'arrière à partir de la portion de corps, à la partie inférieure de celle-ci, et les portions de raccordement des conducteurs s'étendent vers le bas au-delà de la portion de base, afin d'être connectées à un circuit sur une carte de circuit imprimé.

12. Procédé de fabrication d'un ensemble de jack de téléphone modulaire suivant la revendication 1 ou 8, caractérisé en ce qu'il comporte les étapes consistant à produire le boîtier sous la forme d'une partie moulée d'une pièce, à produire l'élément support sous la forme d'une partie moulée d'une pièce, à fabriquer les conducteurs sous la forme d'une bande métallique plate continue comportant une bande porteuse (126) avec des groupes (124) de conducteurs, espacés les uns des autres, s'étendant côte-à-côte suivant une disposition coplanaire, chaque groupe contenant le nom-

bre de conducteurs exigés pour l'un des ensembles de jack, à placer l'élément support et l'un des groupes de conducteurs de manière qu'ils soient adjacents l'un à l'autre, de telle façon que les portions intermédiaires des conducteurs du groupe soient alignées avec les moyens de mise et de maintien en position sur l'élément support, à déplacer le groupe de conducteurs perpendiculairement à leurs axes, par rapport à l'élément support, de telle façon que les portions intermédiaires des conducteurs coopèrent avec les moyens de mise et de maintien en position, et à cambrer simultanément les premières portions extrêmes et les secondes portions extrêmes respectivement contre les bords avant et arrière, afin de former les portions de contact et les portions de raccordement.

13. Procédé suivant la revendication 12 lorsque cette revendication 12 est dépendante de la revendication 8, caractérisé en ce que l'étape de mise en position comprend le déplacement du groupe de conducteurs par rapport à la portion de montage des conducteurs de telle façon que les ergots de mise en position viennent se loger dans les trous de mise en position.

14. Procédé suivant la revendication 13 caractérisé en ce qu'il comprend l'étape de refoulement des ergots de mise en position contre les conducteurs, après l'étape de mise en position, afin de fixer fermement les conducteurs à la portion de montage des conducteurs de l'élément support.

15. Procédé suivant la revendication 14 caractérisé en ce qu'il comprend l'étape de séparation de la bande porteuse à partir des conducteurs, cette étape de séparation ayant lieu en même temps que l'étape de refoulement.

16. Procédé suivant la revendication 14 caractérisé en ce que l'étape de cambrage comporte une première étape de formage des conducteurs assurant le cambrage simultané des premières et secondes portions extrêmes des conducteurs perpendiculairement par rapport à la portion de montage des conducteurs, et une seconde étape de formage des conducteurs dans laquelle on déplace simultanément les premières et secondes portions extrêmes des conducteurs vers la portion de corps, de telle façon que les premières portions extrêmes soient inclinées vers la portion de corps et que les secondes portions extrêmes soient fixées à la portion de base.



Patentansprüche

1. Zweistückige Modul-Telefonbuchseineinheit des Typs mit einer in dieser geformten Stekeraufnahmebuchse (24), die von einer Stekeraufnahmeöffnung (26) gebildet ist, Ober- und Unterseite (28,30), die einander gegenüberliegen und durch einander gegenüberliegende Seitenflächen (32,34) verbunden sind, die von der Öffnung ausgehen, um sich an eine rückwärtige Fläche (36) anzuschließen, wobei die Buchseineinheit

ein Verbindergehäuse (38) mit einem vorderen Ende mit der in diesem gebildeten Stekeraufnahmeöffnung, zwei einander gegenüberliegende Seitenwänden (46,48), deren Innenflächen die Buchsenseitenflächen bilden, einer die Seitenwände verbindenden Oberwand (50) und einem hinteren Ende mit einer in diesem gebildeten hinteren Öffnung,

eine Trägeruntereinheit (40) im Gehäuse, die durch die hintere Öffnung montiert ist, wobei die Trägeruntereinheit ein dielektrisches Stützglied (42) und mehrere gestanzte, metallische langgestreckte Leiter (44) besitzt, die an dem Stützglied montiert sind, wobei jeder Leiter einen Kontaktbereich (110) an einem Ende, der sich von dem vorderen Ende diagonal in die Buchse erstreckt, einen Leiterstiftbereich (112) am anderen Ende und einen Zwischenbereich (114) zwischen dem Kontaktbereich und dem Leiterstiftbereich aufweist, und

zusammenwirkende Einrichtungen (64,92,66,104) zwischen dem Gehäuse und der Untereinheit zum Verriegeln der Untereinheit mit dem Gehäuse aufweist, wobei die Trägeruntereinheit

einen Hauptteil (72) angrenzend an die Gehäuseseitenwände und die Oberwand und mit einer nach vorn weisenden, die rückwärtige Fläche der Buchse bildenden Innenfläche und einer rückwärts weisenden Außenfläche,

einen den Boden des Hauptteils verbindenden Basisteil (74) mit einer Einrichtung (96) zum Aufnehmen und Halten der Leiterstiftbereiche, wobei diese Einrichtung offene Schlitz (98) aufweist, und

einen sich an den Hauptteil anschließen und sich von diesem nach vorn erstreckenden Leitermontagebereich (76) mit einer die Oberwand der Buchse bildenden inneren Bodenfläche und einer nach oben weisenden Leiterstützfläche (82) umfaßt, wobei der Leitermontagebereich einen die Kontaktbereiche der Leiter abstützenden vorderen Rand und einen sich an die Oberseite des Hauptteils anschließenden, die Leiterstiftbereiche der Leiter abstützenden hinteren Rand besitzt und ferner

mehrere von der nach oben weisenden Fläche zwischen den Rändern hochstehende Positionier- und Haltermittel (84) zum Positionieren und Halten der mittleren Bereiche der Leiter aufweist, die sich im allgemeinen entlang deren Länge erstrecken,

wobei ein durchgehend offener Leiteraufnahmeweg zwischen einem Punkt in der Buchse entlang der nach oben weisenden Leiterstützfläche und der nach hinten weisenden Fläche des Hauptteils und einem Punkt in den offenen Schlitz im Basisteil gebildet ist.

2. Buchseineinheit nach Anspruch 1, bei der die Oberwand des Gehäuses den Leitermontagebereich des Stützglieds überdeckt.
3. Buchseineinheit nach Anspruch 2, bei der die Oberwand des Gehäuses einen abwärts weisenden Flansch (55) besitzt, der nach vorn mit Abstand vom vorderen Rand des Leitermontagebereichs des Stützglieds angeordnet ist, wobei die Leiter zwischen dem vorderen Rand und dem abwärts weisenden Flansch aufgenommen sind.
4. Buchseineinheit nach einem der vorhergehenden Ansprüche, bei der das Gehäuse ferner eine die Seitenwände verbindende Bodenwand (52) aufweist, wobei die innere Oberfläche der Bodenwand die Bodenfläche der Buchse bildet.
5. Buchseineinheit nach Anspruch 4, bei der die zusammenwirkenden Einrichtungen sich vom Basisteil nach vorn erstreckende Verriegelungsglieder (104) mit an deren Ende gebildeten Haken und eine Ausnehmung (66) in der Bodenwand des Gehäuses zur Aufnahme des Verriegelungsglieds aufweisen, wobei die Ausnehmung eine Schulter für einen wechselseitigen Eingriff mit den Haken besitzt.
6. Buchseineinheit nach einem der vorhergehenden Ansprüche, bei dem die hochstehenden Positionier- und Haltermittel eine Mehrzahl hochstehender Zentrierstifte (84) aufweisen, die auf dem Leitermontagebereich des Stützglieds gebildet sind, und die Zwischenbereiche jedes Leiters eine Zentrieröffnung (116) zur Aufnahme des jeweiligen Stiftes in dieser besitzen.
7. Buchseineinheit nach Anspruch 6, bei der die Öffnungen und Stifte benachbarter Leiter zueinander versetzt sind.
8. Buchseineinheit nach Anspruch 6 oder 7, bei



der jeder Zwischenbereich zumindest zwei beabstandete Zentrieröffnungen aufweist.

9. Buchseneinheit nach Anspruch 6, 7 oder 8, mit einer Mehrzahl von Rippen (88), die am vorderen Rand des Leitermontagebereichs gebildet sind und mit den Stiften zum Zentrieren der Leiter zwischen diesen zusammenwirken.

10. Buchseneinheit nach einem der vorhergehenden Ansprüche, bei der das Gehäuse eine an diesem gebildete Kontaktkammstruktur (58) besitzt, wobei die Kammstruktur Mittel zum Aufnehmen und Trennen der Enden der Leiterkontaktbereiche aufweist.

11. Buchseneinheit nach einem der vorhergehenden Ansprüche, bei der der Basisteil im allgemeinen horizontal ist und sich vom Hauptteil an dessen Boden nach hinten erstreckt und die Leiterstiftbereiche sich über den Basisteil hinaus nach unten für eine Verbindung mit einem Schaltungssystem auf einer gedruckten Leiterplatte erstrecken.

12. Verfahren zur Herstellung einer Modul-Telefonbuchseneinheit nach Anspruch 1 oder 8 mit den Schritten, daß das Gehäuse als ein einstückiges Formteil hergestellt wird,

das Stützglied als ein einstückiges Formteil hergestellt wird,

die Leiter als ein fortlaufendes flaches Metallband mit einem Trägerstreifen (126) mit beabstandeten, in koplanarer Zuordnung nebeneinander verlaufenden Gruppen (124) von Leitern hergestellt werden, wobei jede Gruppe die für eine der Buchseneinheiten benötigte Anzahl von Leitern enthält,

das Stützglied und eine der Leitergruppen aneinander angrenzend positioniert werden, so daß die mittleren Bereiche der Gruppe mit den Positionier- und Haltemitteln am Stützglied ausgerichtet sind,

die Gruppe von Leitern senkrecht zu ihren Achsen in bezug auf das Stützglied bewegt wird, so daß die Zwischenbereiche der Leiter mit den Positionier- und Haltemitteln zusammenwirken, und

die ersten Endbereiche und die zweiten Endbereiche der Leiter gleichzeitig gegen den vorderen und den hinteren Rand gebogen werden, um die Kontaktbereiche bzw. die Leiterstiftbereiche zu bilden.

13. Verfahren nach Anspruch 12, wenn Anspruch 12 von Anspruch 8 abhängig ist, wobei der Positionierschritt ein Bewegen der Gruppe von Leitern in bezug auf den Leitermontagebereich

einschließt, so daß die Zentrierstifte in den Zentrieröffnungen aufgenommen werden.

14. Verfahren nach Anspruch 13 mit dem Schritt, daß die Zentrierstifte gegen die Leiter nach dem Positionierschritt gesteckt werden, um die Leiter sicher am Leitermontagebereich des Stützgliedes festzulegen.

15. Verfahren nach Anspruch 14, mit dem Schritt, daß der Trägerstreifen von den Leitern abgetrennt wird, wobei der Abtrennschritt gleichzeitig mit dem Aufsteckschritt stattfindet.

16. Verfahren nach Anspruch 14, bei dem der Biegeschritt einen ersten Leiterbildeschritt, bei dem gleichzeitig die ersten und die zweiten Leiterendbereiche senkrecht in bezug auf den Leitermontagebereich gebogen werden, und einen zweiten Leiterbildeschritt umfaßt, bei dem gleichzeitig die ersten und die zweiten Leiterendbereiche zum Hauptteil hin bewegt werden, wodurch die ersten Endbereiche zum Hauptteil hin abgewinkelt und die zweiten Endbereiche am Basisteil festgelegt werden.

