

Description

The invention relates to a zoom lens having a focal length variable between a teleposition and a wide angle position for an electronic camera with which still pictures can be picked up, which zoom lens, viewed from the object end, successively comprises a positive first lens group, a second negative lens group which is movable with respect to the first lens group to provide a zooming action, a third lens group and a stationary and positive fourth lens group, the fourth lens group being the main group which has a constant power and the first three lens groups combined constituting a lens system of small power and variable magnification.

U.S. Patent 3.891.304 describes a zoom lens, having the abovementioned four lens groups composition, which is intended to be used in an 8 mm film camera and has a certain degree of distortion correction and a certain resolving power, which are not sufficient for an electronic still picture camera. This is because the human eye is more sensitive to still picture aberrations than for moving picture aberrations.

In an electronic camera a photosensitive film is no longer used for recording the picked-up pictures, but these pictures are electronically recorded in order at a later stage to be reproduced via an electronic display device, such as a television picture display device, or printed. In this camera a so-called electronic image sensor is located in the image plane of the zoom lens, which sensor not only comprises a bidimensional matrix of radiation-sensitive semi-conductor elements, but also electronic circuits coupled to these elements for processing and temporarily storing the picture information which is present in the electrical output signals of the radiation-sensitive elements. The image sensor has a radiation-sensitive surface whose dimensions differ from those of the image plane of a conventional photocamera or those of a conventional film camera. A commonly used electronic image sensor, for example in the form of a so-called charge-coupled device or CCD which is formed as a frame transfer device or FTD such as are used in video camera has an image field diagonal of 11 mm. A zoom lens having a corresponding image field diagonal will have to be used when using such an image sensor in a camera for still pictures.

As compared with a zoom lens for a motion-picture camera, the lens for a still-picture camera should not only have a higher resolving power but it should also be free from distortion to a greater extent. Distortion is to be understood to mean the distortion of the image, for example the so-called barrel or pin-cushion distortion. The human eye can sooner detect a distortion or a poor resolving power in a still picture than in a moving picture.

As is known, an electronic colour image sensor comprises three types of radiation-sensitive elements each being only sensitive to the primary colours red, green and blue, respectively. These elements are juxtaposed in a regular pattern, with the elements of a first type always being surrounded by elements of the two other types. Since the radiation-sensitive elements have a given thickness, a beam portion having the size of a radiation-sensitive element may not only pass through a desired radiation-sensitive element but also through an adjacent element of another colour in the case of oblique incidence of the chief ray of an imaging beam. This might result in a colour shift in the reconstructed picture. It is therefore desirable for the zoom lens to be telecentric at the image end. In fact, the chief ray of a beam imaging a point of the object in a point of the sensor is then always perpendicularly incident on the sensor surface.

It is the object of the present invention to provide a new class of zoom lenses which combine higher resolving power with smaller distortions than known zoom lenses, so that they are specially suitable for use in an electronic camera for still pictures in general and in such cameras with a colour image sensor in particular.

To this end the zoom lens according to the invention is characterized in that the curvatures of the surfaces of the lens elements in the first and second lens groups as well as the positions of the second lens group associated with given focal lengths are such that the sum of the spherical aberration of the first lens group and that of the second lens group is constant throughout the zoom range.

The zoom range is to be understood to mean the range of focal lengths at which the lens can be adjusted.

The spherical aberration referred to in this context is the mutual spherical aberration of the chief rays of the sub-beams entering the zoom lens at different angles. This spherical aberration may also be referred to as the spherical aberration of the image of the entrance pupil, hence the image of the pupil in the object space formed by the the lens groups located in front of this pupil. The said condition implies that the chief rays of all sub-beams pass through one and the same point of the pupil.

It is essential for the zoom lens according to the invention that the distortion of the lens portion comprising the first three lens groups is constant throughout the zoom range from the teleposition to the wide-angle position. The zoom lens may have a telecentric design. It is true that the zoom lenses hitherto known have a very small distortion in the teleposition, but the distortion of these zoom lenses is

considerable in the wide-angle position.

A further advantage of the zoom lens according to the invention, as compared with that described in United States Patent No. 3,891,304, is that the maximum field angle, in the wide-angle position, for which the lens is still sufficiently free from distortion may be larger, for example $2 \times 30^\circ$ for the novel zoom lens and approximately $2 \times 20^\circ$ for the known zoom lens. The field angle is to be understood to mean the angle at which in the object space the chief ray of an obliquely incident beam which is passed by the zoom lens with an acceptable vignetting crosses the optical axis of the lens.

The zoom lens according to the invention is preferably further characterized in that

- in the telemode the rays of the most oblique marginal beam which enters at the angle of acceptance extend at relatively small angles to the normals on the lens elements of both the first and the second lens group, whilst these rays in the second lens group extend close to the optical axis, and the spherical aberrations of the first and second lens groups are small and compensate each other at least for the greater part,
- in the wide-angle mode the rays of the said marginal beam extend at relatively large angles to the normals on the lens elements of both the first and the second lens group, whilst these rays in the second lens group extend at a relatively large distance from the optical axis, and the relatively large positive spherical aberration of the first lens group and the relatively large negative spherical aberration of the second lens group compensate each other to the same extent as in the telemode.

A marginal beam is a beam from the edge of the object. The angle of acceptance is the angle at which the chief ray of the most oblique marginal beam which passes through the zoom lens with an acceptable vignetting crosses the axis of the zoom lens. The angle of acceptance is thus equal to the maximum field angle.

The remaining spherical aberration of the first two lens groups combined may in principle be equal to zero. Then the main group must also be completely corrected for spherical aberration.

However, the zoom lens according to the invention is preferably further characterized in that the constant spherical aberration of the first and second lens groups combined is equal and opposite to that of the main group.

In that case no extra steps have to be taken to render the main group on the one hand and the combination of the first and second lens groups on the other hand free from aberration.

Likewise as in the zoom lens described in United States Patent No. 3,891,304, the third lens group may be movable and then serves as a focus compensator during zooming. In addition to this focus compensator the known zoom lens has a positive stationary lens group between the focus compensation and the main group.

In order to limit the axial and transversal chromatic aberration of the zoom lens, the zoom lens is further characterized in that a lens element of both the first, the second and the fourth lens group is in the form of a doublet.

A doublet is a composite lens element comprising two lens elements having different dispersions which are cemented together directly or via a layer of air and in which the internal surfaces of these lens elements have the same curvature.

The invention will now be described by way of example with reference to the accompanying drawings in which Figs. 1a, 1b and 1c, Figs. 2a, 2b and 2c and Figs. 3a, 3b and 3c show a first, a second and a third embodiment, respectively of the zoom lens, namely in the teleposition, the normal position and the wide-angle position, respectively. Corresponding elements in the Figures have the same reference numerals.

Viewed from the object end, which is on the left-hand side of the drawing, the zoom lens comprises a positive first lens group G_1 , also referred to as front group, consisting of three positive lens elements L_1 , L_2 and L_3 . This group is followed by a movable and negative group G_2 consisting of two negative lens elements L_4 and L_5 . The focal length can be adjusted by moving this group, which is also referred to as the variator group. In Figures 1b, 2b and 3b the variator group is in the intermediate position and the zoom lens has the average or "normal" focal length. Figs. 1a, 2a and 3a show the teleposition in which the variator group is placed in the extreme right position and the focal length of the zoom lens is maximum. The wide-angle position of the zoom lens is shown in Figs. 1c, 2c and 3c. The variator group is then in the extreme left position and the focal length is minimum.

A, for example positive, lens group G_3 which may consist of a single lens element L_6 is arranged behind the variator group. If this lens element is positive, it converts a diverging beam emanating from the variator group into a parallel beam. The lens group G_3 may also be divergent to a small extent.

A beam emanating from the lens group G_3 is focussed in the image plane IP by a fourth lens group G_4 which supplies approximately the total power of the zoom lens in the intermediate zoom position and which is referred to as the main group. The main group may comprise three positive lens elements L_7 , L_8 and L_9 .

The pupil PP' of the zoom lens is in the proximity of the first lens element L_7 of the main group so that the two first lens groups are used rather eccentrically, that is to say, the marginal beams pass through these lens groups at a relatively large distance from the optical axis OO' .

5 The zoom lens according to the invention is satisfactorily corrected for distortion throughout the zoom range. This can be illustrated by tracing the chief ray of the most oblique beam b_1 through the zoom lens in the two extreme situations: the teleposition and the wide-angle position.

10 In the teleposition (Figures 1a, 2a and 3a) the angle of incidence α of the chief ray of the beam b_1 is relatively small, for example 10° . The elements of the front group are traversed maximally eccentrically. The lens elements L_1 , L_2 and L_3 of this group are curved in such a manner that the condition of minimum deviation is substantially complied with per lens element, that is to say, per lens element in the front group the angle at which the chief ray is kinked upon passage through this lens element is small. The positive spherical aberration of the chief ray of the marginal beam b_1 in the front group is relatively small with respect to the chief ray of the central beam b_0 . The lens elements L_4 and L_5 of the variator group G_2 are traversed relatively close to the optical axis in the teleposition and the negative spherical aberration of this lens group is relatively small. It may be ensured that the sum of the small positive and the small negative spherical aberrations compensates the spherical aberration of the main group. In the case of an ideal main group, without spherical aberration, the said sum must also be zero.

15 In the wide-angle position the angle of incidence α of the chief ray of the beam b_1 is considerably larger, for example 30° than in the teleposition. The variator group G_2 is now located close to the front group and the rays of the beam b_1 traverse the elements of the variator group at a relatively large distance from the optical axis. Consequently, a relatively large negative spherical aberration which in itself might cause a large so-called pin-cushion distortion in the image plane IP occurs in this group. This is, however, avoided in that due to the large angle of incidence the chief ray of the beam b_1 no longer traverses the lens elements of the front group G_1 in accordance with the minimum condition of deviation, so that the beam b_1 has a relatively large positive spherical aberration in the front group. This aberration compensates the relatively large negative spherical aberration of the variator group at least for the greater part, so that the resultant aberration is equal to that in the teleposition.

25 Thus it can be achieved that the net spherical aberration of the beam passing through the zoom lens is substantially equal in the teleposition and in the wide-angle position after it has traversed the telescopic lens portion comprising the lens groups G_1 , G_2 and G_3 . In the zoom lens according to the invention the distortion may be kept smaller than approximately 1% in all zoom ranges.

30 Preferably a lens element in both in the front group G_1 , the variator group G_2 and in the main group G_4 is in the form of a doublet. In the embodiments shown in the Figures these are the elements L_1 , L_5 and L_7 . Due to this step the chromatic aberrations can be limited; for example, the transverse colour error may be smaller than approximately 5 microns whilst the longitudinal colour error may be smaller than the depth of field of the zoom lens. Due to the different dispersions of the sub-elements of the said doublets, these elements have a chromatising effect.

35 In the embodiment shown in Figs. 1a, 1b and 1c the lens group G_3 is movable. By automatically adapting the position of this group to that of the variator group G_2 it can be ensured that the diverging beam emanating from the variator group is converted into a parallel beam. Then each sub-beam emanating from the lens portion G_1 , G_2 and G_3 is each time focussed in the image plane IP by the main group G_4 . The movable lens group G_3 is then a focus compensator.

40 In the embodiment shown in Figs. 2a, 2b and 2c the lens group G_3 is stationary. This group can then no longer function as a focus compensator during zooming. In order to achieve that nevertheless a sharp picture is each time formed on the image sensor IS, during zooming of the beam passing through the zoom lens focussing can be detected via the image sensor or a separate focus detection device in the camera of which the zoom lens forms part. The focussing can be re-adjusted with the focus error signal obtained, for example by moving the front group G_1 .

45 The object distance can also be adjusted by axial movement of the front group.

50 An infrared filter F is arranged between the lens element L_7 and the lens element L_8 in the zoom lens shown in Figs. 2a, 2b and 2c.

For a zoom lens according to Figs. 2a, 2b and 2c whose focal length is adjustable between 10 mm and 26 mm and whose F number is equal to F/2.8, the following values apply to the distances d between the surfaces $S_1 \dots S_{23}$, the axial curvatures C , the refractive indices n and the diameters D of the surfaces:

55

EP 0 278 126 B1

		d (mm)	C	n	D (mm)
		s_1	0.000000		53.0
5		2.5000		1.7918	
	L_1	s_2	0.023375		48.0
		10.5000		1.6629	
		s_3	-0.006916		48.0
10		0.2000		1.0000	
	L_2	s_4	0.020235		43.0
		5.6000		1.6229	
		s_5	0.002722		43.0
15		0.2000		1.0000	
	L_3	s_6	0.048035		32.4
		6.2000		1.6940	
		s_7	0.017590		32.4
20		d_1		1.0000	
	L_4	s_8	0.002597		19.0
		1.0000		1.6940	
		s_9	0.146508		12.2
25		5.2000		1.0000	
		s_{10}	-0.031813		11.8
		3.5000		1.7918	
30	L_5	s_{11}	-0.132204		11.8
		1.0000		1.6229	
		s_{12}	0.019499		11.8
35		d_2		1.0000	
	L_6	s_{13}	-0.025002		9.0
		1.2000		1.6229	
			-0.065947		9.0
40		s_{14}			
		9.4102		1.0000	
		s_{15}	-0.020507		10.2
		3.5000		1.7923	
45	L_7	s_{16}	-0.170711		10.2
		1.000		1.7918	
		s_{17}	-0.047777		12.0
		2.8052		1.0000	
50		s_{18}	0.000000		16.0

F		1.0000	1.5187
	S ₁₉	0.000000	16.0
		3.0000	1.0000
	S ₂₀	0.006476	16.0
L ₈		3.0000	1.6229
	S ₂₁	-0.025250	16.0
		1.3156	1.0000
	S ₂₂	0.043493	16.0
L ₉		3.0000	1.6229
	S ₂₃	0.000000	16.0

The pupil PP' is at, for example 3 mm from the lens L₈. This distance can be varied. The distances denoted by d₁ and d₂ in the Table above are variable. The following values for d₁ and d₂ apply to the different zoom distances d_z:

d _z	d ₁ (mm)	d ₂ (mm)
f = 26 mm	9.5360	0.6692
f = 16 mm	5.9749	4.2229
f = 10 mm	1.7391	8.4575

The overall length of this zoom lens is approximately 89.5 mm.

The zoom lens shown in Figs. 3a, 3b and 3c is different from that shown in Figs. 2a, 2b and 2c in that the lens elements L₄ and L₅ are placed closer together and in that the lens element L₆ is arranged behind the pupil PP'.

For a zoom lens as shown in Figs. 3a, 3b and 3c whose focal length is adjustable between 10.5 mm and 25 mm and whose F number can be adjusted between F/4.0 and F/2.8, the following values apply to the distances d between the surfaces S₁...S₂₃, the axial curvatures C, the refractive indices n and the diameters D of the surfaces:

EP 0 278 126 B1

		d (mm)	C	n	D (mm)
			0.000064		52.8
5	L ₁	2.5000		1.7918	
		8.4000	0.016701		49.0
			1.6629		
			-0.005420		49.0
10		0.2000		1.0000	
	L ₂		0.021750		44.0
		5.9000		1.6229	
			0.004915		44.0
15		0.2000		1.0000	
	L ₃		0.036099		35.0
		5.1000		1.6940	
			0.014637		35.0
20		d ₁		1.0000	
	L ₄		0.000000		19.0
		1.2000		1.6940	
			0.128381		12.7
25		4.3000		1.0000	
			-0.043571		12.6
		3.1000		1.7918	
30			-0.115245		12.6
		1.0000		1.6229	
			-0.007312		13.5
		d ₂		1.0000	
35		PP'	0.000000		4.4
		3.5000		1.0000	
	L ₆		-0.008706		9.0
		1.4000		1.6229	
40			-0.055360		9.0
		5.7716		1.0000	
			-0.007096		11.7
		3.3000		1.7923	
45	L ₇		-0.131079		11.7
		1.0000		1.7918	
			-0.031244		14.0
		4.8592		1.0000	
50			0.000000		16.0
		S ₁₈			

55

		d (mm)	C	n	D (mm)
	F	1.0000		1.5187	
5	S ₁₉		0.000000		16.0
		3.000		1.0000	
	S ₂₀		0.009431		17.0
	L ₈	3.0000		1.6229	
10	S ₂₁		-0.017628		17.0
		0.2000		1.0000	
	S ₂₂		0.039210		18.0
15	L ₉	3.0000		1.6229	
	S ₂₃		0.007229		18.0

The following values for d_1 and d_2 apply to the different zoom distances d_z :

	d_z	d_1 (mm)	d_2 (mm)
	$f = 25$ mm	13.0499	3.7591
	$f = 16$ mm	8.5994	8.1989
25	$f = 10.7$ mm	3.8037	12.9857

Claims

1. A zoom lens having a focal length variable between a teleposition and a wide angle position for an electronic camera with which still pictures can be picked up, which zoom lens, viewed from the object end, successively comprises a positive first lens group (G_1), a second negative lens group (G_2) which is movable with respect to the first lens group (2) to provide a zooming action, a third lens group (G_3) and a positive fourth lens group (G_4) which is stationary, the fourth lens group being the main group which has a constant power and the first three lens groups combined constituting a lens system of small power and variable magnification, characterized in that the curvatures of the surfaces of the lens elements in the first and second lens groups (G_1 , G_2) as well as the positions of the second lens group (G_2) associated with given focal lengths of the zoom lens are such that the respective spherical aberration of different chief rays entering the zoom lens at different angles (α) for the combination of the first lens group (G_1) and that of the second lens group (G_2) is constant throughout the zoom range.
2. A zoom lens as claimed in Claim 1, characterized in that
 - in the telemode (Fig. 1a; Fig. 2a; Fig. 3a) the rays of the most oblique marginal beam (b_1) which enters at the angle of acceptance extend at relatively small angles (α) to the normals on the lens elements (L_1 , L_2 , L_3 , L_4 , L_5) of both the first (G_1) and the second lens group (G_2), whilst these rays in the second lens group (G_2) extend close to the optical axis (OO'), and the spherical aberrations of the first and second lens groups (G_1 , G_2) are small and compensate each other at least for the greater part, and in that
 - in the wide-angle mode (Fig. 1c, Fig. 2c, Fig. 3c) the rays of the said marginal beam (b_1) extend at relatively large angles to the normals on the lens elements of both the first and the second lens group (G_1 , G_2), whilst these rays in the second lens group (G_2) extend at a relatively large distance from the optical axis (OO'), and the relatively large positive spherical aberration of the first lens group (G_1) and the relatively large negative spherical aberration of the second lens group (G_2) compensate each other to the same extent as in the telemode.
3. A zoom lens as claimed in Claim 1 or 2, characterized in that the constant spherical aberration of the first and second lens groups (G_1 , G_2) combined is equal and opposite to that of the main group (G_4).



		d (mm)	C	n	D (mm)
	F	1.0000		1.5187	
5			0.000000		16.0
	S ₁₉	3.000		1.0000	
			0.009431		17.0
	S ₂₀	3.0000		1.6229	
10	L ₈		-0.017628		17.0
	S ₂₁	0.2000		1.0000	
			0.039210		18.0
	S ₂₂	3.0000		1.6229	
15	L ₉		0.007229		18.0
	S ₂₃				

The following values for d_1 and d_2 apply to the different zoom distances d_z :

d_z	d_1 (mm)	d_2 (mm)
$f = 25$ mm	13.0499	3.7591
$f = 16$ mm	8.5994	8.1989
$f = 10.7$ mm	3.8037	12.9857

Claims

1. A zoom lens having a focal length variable between a teleposition and a wide angle position for an electronic camera with which still pictures can be picked up, which zoom lens, viewed from the object end, successively comprises a positive first lens group (G_1), a second negative lens group (G_2) which is movable with respect to the first lens group (2) to provide a zooming action, a third lens group (G_3) and a positive fourth lens group (G_4) which is stationary, the fourth lens group being the main group which has a constant power and the first three lens groups combined constituting a lens system of small power and variable magnification, characterized in that the curvatures of the surfaces of the lens elements in the first and second lens groups (G_1 , G_2) as well as the positions of the second lens group (G_2) associated with given focal lengths of the zoom lens are such that the respective spherical aberration of different chief rays entering the zoom lens at different angles (α) for the combination of the first lens group (G_1) and that of the second lens group (G_2) is constant throughout the zoom range.
2. A zoom lens as claimed in Claim 1, characterized in that
 - in the telemode (Fig. 1a; Fig. 2a; Fig. 3a) the rays of the most oblique marginal beam (b_1) which enters at the angle of acceptance extend at relatively small angles (α) to the normals on the lens elements (L_1 , L_2 , L_3 , L_4 , L_5) of both the first (G_1) and the second lens group (G_2), whilst these rays in the second lens group (G_2) extend close to the optical axis (OO'), and the spherical aberrations of the first and second lens groups (G_1 , G_2) are small and compensate each other at least for the greater part, and in that
 - in the wide-angle mode (Fig. 1c, Fig. 2c, Fig. 3c) the rays of the said marginal beam (b_1) extend at relatively large angles to the normals on the lens elements of both the first and the second lens group (G_1 , G_2), whilst these rays in the second lens group (G_2) extend at a relatively large distance from the optical axis (OO'), and the relatively large positive spherical aberration of the first lens group (G_1) and the relatively large negative spherical aberration of the second lens group (G_2) compensate each other to the same extent as in the telemode.
3. A zoom lens as claimed in Claim 1 or 2, characterized in that the constant spherical aberration of the first and second lens groups (G_1 , G_2) combined is equal and opposite to that of the main group (G_4).



4. A zoom lens as claimed in Claim 1, 2 or 3, characterized in that a lens element (L_1 , L_5 , L_7) of both the first (G_1), the second (G_2) and the fourth lens group (G_4) is in the form of a doublet.

Patentansprüche

5

1. Zoom-Objektiv mit einer zwischen einer Telestellung und einer Weitwinkelstellung variierbaren Brennweite für eine elektronische Kamera, mit der stehende Bilder aufgenommen werden können, wobei das Zoom-Objektiv, von der Objektseite aus gesehen, aufeinanderfolgend eine positive erste Linsengruppe (G_1), eine zweite, bezüglich der ersten Linsengruppe (2) zum Verschaffen einer Zoom-Wirkung bewegbare, negative Linsengruppe (G_2), eine dritte Linsengruppe (G_3) und eine feststehende positive vierte Linsengruppe (G_4) umfaßt, wobei die vierte Linsengruppe die Hauptgruppe ist, die konstante Stärke hat, und die ersten drei Linsengruppen zusammen ein Linsensystem niedriger Stärke und veränderlicher Vergrößerung bilden, dadurch gekennzeichnet, daß die Krümmungen der Oberflächen der Linsenelemente in der ersten und der zweiten Linsengruppe (G_1 , G_2) ebenso wie die zu gegebenen Brennweiten des Zoom-Objektivs gehörenden Lagen der zweiten Linsengruppe (G_2) derart sind, daß die jeweilige sphärische Aberration verschiedener in das Zoom-Objektiv unter verschiedenen Winkeln (α) tretender Hauptstrahlen für die Kombination aus der ersten Linsengruppe (G_1) und der zweiten Linsengruppe (G_2) über den gesamten Zoom-Bereich konstant ist.
2. Zoom-Objektiv nach Anspruch 1, dadurch gekennzeichnet, daß
 - im Telebetrieb (Figur 1a; Figur 2a; Figur 3a) die Strahlen des schrägsten Randstrahlenbündels (b_1), das unter dem Akzeptanzwinkel eintritt, relativ kleine Winkel (α) mit den Normalen der Linsenelemente (L_1 , L_2 , L_3 , L_4 , L_5) sowohl der ersten (G_1) als auch der zweiten Linsengruppe (G_2) bilden, während diese Strahlen in der zweiten Linsengruppe (G_2) nahe der optischen Achse (OO') verlaufen und die sphärischen Aberrationen der ersten und der zweiten Linsengruppe (G_1 , G_2) klein sind und einander mindestens zum größeren Teil kompensieren, und daß
 - im Weitwinkelbetrieb (Figur 1c; Figur 2c; Figur 3c) die Strahlen des genannten Randstrahlenbündels (b_1) relativ große Winkel mit den Normalen der Linsenelemente sowohl der ersten als auch der zweiten Linsengruppe (G_1 , G_2) bilden, während diese Strahlen in der zweiten Linsengruppe (G_2) in einem relativ großen Abstand zur optischen Achse (OO') verlaufen und die relativ große positive sphärische Aberration der ersten Linsengruppe (G_1) und die relativ große negative sphärische Aberration der zweiten Linsengruppe (G_2) einander in gleichem Maße wie im Telebetrieb kompensieren.
3. Zoom-Objektiv nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die konstante sphärische Aberration der ersten und der zweiten Linsengruppe (G_1 , G_2) zusammen gleich und entgegengesetzt der der Hauptgruppe (G_4) ist.
4. Zoom-Objektiv nach Anspruch 1, 2 oder 3, dadurch gekennzeichnet, daß ein Linsenelement (L_1 , L_5 , L_7) sowohl der ersten (G_1), der zweiten (G_2) als auch der vierten Linsengruppe (G_4) die Form eines Dubletts hat.

Revendications

1. Objectif à focale variable présentant une distance focale variable entre une téléposition et une position grand-angle, conçu pour une caméra électronique permettant la prise d'images fixes, ledit objectif à focale variable comportant vu du côté d'objet successivement un premier groupe de lentilles positives (G_1), un deuxième groupe de lentilles négatives (G_2) qui est amovible par rapport au premier groupe de lentilles (2) pour effectuer une variation de focale, un troisième groupe de lentilles (G_3) ainsi qu'un quatrième groupe de lentilles positives qui est stationnaire, le quatrième groupe de lentilles étant le groupe principal à puissance constante et l'ensemble constitué des trois premiers groupes de lentilles constituant un système de lentilles à puissance faible et à agrandissement variable, caractérisé en ce que les courbures des surfaces des éléments de lentille du premier et du deuxième groupe de lentilles (G_1 , G_2) aussi bien que les positions du deuxième groupe de lentilles (G_2) associées à certaines distances focales de l'objectif à focale variable sont telles que l'aberration sphérique de rayons principaux différents entrant dans l'objectif à focale variable sous des angles (α) différents est constante sur tout le domaine de variation de focale pour l'ensemble constitué du premier groupe de lentilles (G_1) et du deuxième groupe de lentilles (G_2).



2. Objectif à focale variable selon la revendication 1, caractérisé en ce que

- dans la téléposition (Fig. 1a; Fig. 2a; Fig. 3a), les rayons du faisceau marginal le plus oblique (b_1) qui entre sous l'angle d'acceptation, font des angles (α) relativement petits avec les normales aux éléments de lentille (L_1, L_2, L_3, L_4, L_5) du premier (G_1) aussi bien que du deuxième groupes de lentilles (G_2), alors que dans le deuxième groupe de lentilles (G_2) ces rayons s'étendent tout près de l'axe optique (OO'), et que les aberrations sphériques du premier et du deuxième groupe de lentilles (G_1, G_2) sont faibles et que pour la plus grande partie, elles sont compensées mutuellement, et en ce que
- dans la position grand-angle (Fig. 1c, Fig. 2c, Fig. 3c), les rayons dudit faisceau marginal (b_1) font des angles relativement grands avec les normales aux éléments de lentille du premier aussi bien que du deuxième groupe de lentilles (G_1, G_2), alors que dans le deuxième groupe de lentilles (G_2) ces rayons s'étendent à une distance relativement élevée de l'axe optique (OO'), et que l'aberration sphérique positive relativement élevée du premier groupe de lentilles (G_1) et l'aberration sphérique négative relativement élevée du deuxième groupe de lentilles (G_2) sont mutuellement compensées dans le même degré que dans la téléposition.

3. Objectif à focale variable selon la revendication 1 ou 2, caractérisé en ce que l'aberration sphérique de l'ensemble constitué du premier et du deuxième groupe de lentilles (G_1, G_2) est égale et opposée à celle du groupe principal (G_4).

4. Objectif à focale variable selon la revendication 1, 2 ou 3, caractérisé en ce qu'un élément de lentille (L_1, L_5, L_7) du premier (G_1), aussi bien que du deuxième (G_2) et du quatrième groupe de lentilles (G_4) présente la forme d'un doublet.