

DESCRIPTION

TITLE OF INVENTION

CARRIAGE SYSTEM HAVING TRACK

TECHNICAL FIELD

5 [0001]

The present invention relates to a rail guided vehicle system that conveys, along a rail, an article such as a container, in which various kinds of substrates for the production of semiconductor apparatuses, etc., are contained.

BACKGROUND ART

10 [0002]

A conventional rail guided vehicle system is known to be a rail guided vehicle system that conveys an article such as a FOUP (Front Opening Unified Pod) and that includes an overhead hoist vehicle (so-called OHT) travelling on a rail arranged on a ceiling .

Since such a rail guided vehicle system is often used in a clean room, where the cost
15 of space is expensive, it is necessary to make the rail guided vehicle system smaller. One suggested technique is to make the rail guided vehicle system smaller by shortening the length of a connection rail that connects two main rails. For example, an known technique is to include a forcing guide, configured to force a diverging roller that is used when travelling on the connection rail to shift on the connection rail, in order to shorten the length
20 of the connection rail is known (for example, Patent Citation 1).

[0003]

Here, the case where the vehicle travelling on a N-shaped rail moves from a rail on

which the vehicle is travelling, to another rail is considered as an example. First, the vehicle shifts a diverging roller mechanism to the side on which another rail exists. The diverging roller mechanism is arranged in a travelling unit of the vehicle. Then, the vehicle is guided by a diverging guide, which extends from the rail to the middle of a connection rail, and
5 moves to the connection rail. After this, the diverging roller mechanism is shifted to the opposite side in order for the vehicle to be guided by another diverging guide at the merging side. Here, another diverging guide is arranged in the connection rail and at the position opposite to the diverging guide, with a predetermined offset in between (separating area). In this situation, a forcing guide, which is arranged in the separating area, forces the diverging
10 roller mechanism to be shifted toward another diverging guide. Thus, the travelling unit of the vehicle is guided to another rail.

[0004]

Patent Citation 1: Japanese Laid-Open Patent Application No.2008-126743

DISCLOSURE OF INVENTION

15 TECHNICAL PROBLEM

[0005]

In the above-mentioned technique, the diverging roller mechanism can only be shifted in the separating area, where the diverging guide does not exist. However, even if the forcing guide is used, the length of the separating area needs to be equal or greater than
20 the length that is derived by adding the length of one diverging roller mechanism along the travelling direction, to the travelling length in which the vehicle travels during shifting the diverging roller mechanism.

For example, in order to shorten the connection rail, it is necessary to shorten the separating area by shortening the length of the forcing guide in the travelling direction. However, when shortening the length of the forcing guide, the diverging roller needs to be shifted rapidly unless the vehicle is slowed down. Shifting the diverging roller rapidly might cause abnormal operation because a large amount of stress is applied to the diverging roller. In addition, since the impulsion generated when the diverging roller abuts the forcing guide is large, the vibration of the vehicle and the damage of the diverging roller may occur.

[0006]

As described above, the conventional technique has a limited benefit even if the connection rail can be shortened, and the conventional technique has a technical problem of causing various disadvantages when attempting to shorten the connection rail further.

The present invention was conceived in light of the above-mentioned problem and the problem to be solved is to provide a rail guided vehicle system that can be made smaller by effectively shortening the connection rail.

TECHNICAL SOLUTION

[0007]

A rail guided vehicle system according to the present invention is a rail guided vehicle system that comprises a rail and vehicles. The rail includes a first main rail, a second main rail, and a connection rail that connects the first main rail to the second main rail.

The vehicles travel while being supported and guided by the rail. A vehicle includes a travelling unit, a diverging roller supporting member, and a position stabilizing

roller supporting member. The travelling unit is configured to travel on the rail. The diverging roller supporting member is arranged in the travelling unit. The diverging roller supporting member supports a first diverging roller, and a second diverging roller, that are arranged with a gap in between in a width direction of the travelling unit. The first diverging
5 roller and the second diverging roller shift in the width direction of the travelling unit.

The position stabilizing roller supporting member is arranged in the travelling unit. The position stabilizing roller supporting member supports position stabilizing rollers. The position stabilizing rollers are configured to stabilize a travelling position of the travelling unit such that the position stabilizing rollers do not shift in the width direction of the
10 travelling unit.

The rail includes a first diverging guide, a second diverging guide, and a position stabilizing roller guide. The first diverging guide extends, on one side of the connection rail in the width direction of the connection rail, from the first main rail along an extending direction of the connection rail. The first diverging guide is configured to guide the first
15 diverging roller.

The second diverging guide extends, on another side of the connection rail in the width direction of the connection rail, to the second main rail along the extending direction of the connection rail while having a no-guide zone that does not overlap with the first diverging guide in the extending direction of the connection rail. The second diverging guide is
20 configured to guide the second diverging roller.

The position stabilizing roller guide is arranged in the no-guide zone. The position stabilizing roller guide is configured to guide the position stabilizing rollers in the no-guide

zone. Here, the width direction of the travelling unit means the direction crossing the travelling direction of the vehicle.

[0008]

According to the present invention, the position stabilizing roller guide configured to
5 guide the position stabilizing rollers is arranged in the no-guide zone. The no-guide zone is where the diverging guide of the rail is not provided. By arranging such a position stabilizing roller guide in the no-guide zone, the position stabilizing roller can be guided by the position stabilizing roller guide, and thus the position of the vehicle can be stabilized.

If the position of the vehicle can be stabilized in the no-guide zone, the no-guide
10 zone can be extended to the zone where the first diverging guide and the second diverging guide should be arranged in the conventional techniques. This is the zone where the position of the vehicle should be stabilized by guiding the first diverging roller and the second diverging roller to the first diverging guide and the second diverging guide. Using the present invention, while the no-guide zone has a sufficient length, lengthening of the
15 entirety of the connection rail can be avoided. The preferable movement of the vehicle between the first main rail and the second main rail can be performed, and the shortening of the connection rail can also be realized.

As described above, according to the rail guided vehicle system of the present invention, the system can be made smaller by shortening the connection rail.

20 [0009]

The vehicle may include a main body member and a plurality of bogie truck units that are arranged to rotate in a horizontal direction relative to the main body member. The

travelling unit, the diverging roller supporting member, and the position stabilizing roller supporting member may be arranged in each of the plurality of bogie truck units.

In this structure, since the plurality of bogie truck units are arranged in the vehicle, the vehicle can be larger. Specifically, when the vehicle reaches a curve of the rail, each of the plurality of bogie truck units rotates along the horizontal direction with a different angle from those of other bogie truck units, thus the preferable travelling of the vehicle can be realized.

[0010]

The position stabilizing roller may include a first roller member and a second roller member. The first roller member and the second roller member are attached with a gap in between in the width direction of the travelling unit. The position stabilizing roller guide includes a first roller guide member and a second roller guide member. The first roller guide member extends along the extending direction on one side of the connection rail in the width direction of the connection rail and in the no-guide zone. The first roller guide member is configured to guide the first roller member. The second roller guide member extends along the extending direction on another side of the connection rail in the width direction of the connection rail in the no-guide zone. The second roller guide member is configured to guide the second roller member.

In this structure, in the vehicle reaching the no-guide zone from the first diverging guide, the first roller member is first guided by the first roller guide member. Then, after the vehicle moves across the end of the first roller guide member, the second roller member is guided by the second roller guide member. With the first roller member, the second roller

member, the first roller guide member, and the second roller guide member, the fluctuations in the right and left directions and the mismatches of the position can be inhibited. As a result, the position of the vehicle in the no-guide zone can better be stabilized.

[0011]

5 The rail may be arranged on a ceiling or in the vicinity of the ceiling. The rail includes a first travelling plane portion and a second travelling plane portion at both sides of the lower portion of the rail in the width direction of the rail. The first travelling plane portion and the second travelling plane portion are arranged with a gap in between. The first roller guide member rises in a planar manner from a position closer to the gap of the first travelling plane portion of the connection rail. The second roller guide member rises in a planar manner from a position closer to the gap of the second travelling plane portion of the connection rail. The first roller member and the second roller member are guided by abutting the first roller guide member and the second roller guide member, respectively, from the outer sides of the connection rail in the width direction of the connection rail.

15 In this structure, each of the first roller member and the second roller member is guided by abutting the first roller guide member and the second roller guide member, respectively. Specifically, the first roller member is guided while the first roller guide member abuts the first roller member from the inner side of the connection rail in the width direction of the connection rail. On the other hand, the second roller member is guided while the second roller guide member abuts the second roller member from the inner side of the connection rail in the width direction of the connection rail. Therefore, the position of the vehicle in the no-guide zone can better be stabilized.

[0012]

The rail, which is arranged on a ceiling or in the vicinity of the ceiling, may include a first travelling plane portion and a second travelling plane portion. The first travelling plane portion and the second travelling plane portion are disposed at both sides of the lower
5 portion of the rail. A gap is defined between the first travelling plane portion and the second travelling plane portion.

The rail further includes a first projecting member and a second projecting member. The first projecting member projects toward the gap from the first travelling plane portion in the no-guide zone. The first projecting member extends with a predetermined length along
10 the extending direction of the connection rail. The first projecting member has a first side plane portion at the end side of the first projecting member in a width direction of the first projecting member. The second projecting member projects toward the gap from the second travelling plane portion such that the second projecting member does not overlap with the first projecting member in the extending direction of the connection rail in the no-guide zone.
15 The second projecting member extends a predetermined length along the extending direction of the connection rail. The second projecting member has a second side plane portion at the end side of the second projecting member in a width direction of the second projecting member. The position stabilizing roller supporting member is arranged at the lower side of the travelling unit. The position stabilizing roller supporting member supports the position
20 stabilizing rollers such that the position stabilizing rollers abut the first side plane portion and the second side plane portion.

In this structure, the position stabilizing rollers in the no-guide zone first abut the

first side plane portion that exists at the one side of the connection rail in the width direction of the connection rail. Then, the position stabilizing rollers abut the second side plane portion that exists at another side of the connection rail in the width direction of the connection rail. The travelling position of the vehicle in the no-guide zone is stabilized.

- 5 When the position stabilizing rollers abut the first side plane portion, the position can be better stabilized by a side roller abutting the rail wall at another side. When the position stabilizing rollers abut the second side plane portion, the position can also be better stabilized by a side roller abutting the rail wall at one side.

[0013]

- 10 The position stabilizing rollers may be arranged in line along a travelling direction of the vehicle, in the vicinity of the center portion of the lower side of the travelling unit in the width direction of the travelling unit. The first side plane portion and the second side plane portion are separated from each other by a gap equal to a diameter of the position stabilizing roller in the width direction.

- 15 In this structure, since plural parts of the position stabilizing rollers abut the first side plane portion and the second side plane portion, fluctuations in the right and left directions and the mismatches of the position can be inhibited with a smaller number of the position stabilizing rollers. The travelling position of the vehicle in the no-guide zone is stabilized. The gap between the first side plane portion and the second side plane portion does not have
20 to be exactly equal to the diameter of the position stabilizing roller, as long as the gap and the diameter have almost the same length.

BRIEF DESCRIPTION OF DRAWINGS

[0014]

Fig. 1 is a plan view showing the overall structure of the rail guided vehicle system according to the first embodiment.

Fig. 2 is a side view showing the structure of the vehicle according to the first
5 embodiment.

Fig. 3 is a perspective view showing the transferring operation of the vehicle according to the first embodiment.

Fig. 4 is a perspective view showing the lateral transferring operation of the vehicle according to the first embodiment.

10 Fig. 5 is a plan view showing travelling of the vehicle according to the first embodiment on the connection rail.

Fig. 6 is a cross-sectional view showing the structure of the travelling unit according to the first embodiment together with the rail.

Fig. 7 is a cross-sectional view showing the structure of the travelling unit according
15 to the first embodiment together with the rail.

Fig. 8 is a cross-sectional view showing the structure of the travelling unit according to the first embodiment together with the rail (Part 3).

Fig. 9 is a cross-sectional view showing the structure of the travelling unit according to the first embodiment together with the rail.

20 Fig. 10 is a cross-sectional view showing the structure of the travelling unit of the vehicle according to the comparative example, together with the rail.

Fig. 11 is a plan view showing the zone where the position of the vehicle according

to the comparative example is stable and the zone where the position of the vehicle is unstable.

Fig. 12 is a plan view showing a diverging roller shifting zone for the vehicle according to the comparative example.

5 Fig. 13 is a cross-sectional view showing the structure of the travelling unit of the vehicle according to the second embodiment together with the rail.

Fig. 14 is a side view showing the structure of the travelling unit of the vehicle according to the second embodiment.

10 Fig. 15 is a plan view showing the structure of the travelling plane of the rail according to the second embodiment.

Fig. 16 is a plan view showing the travelling of the vehicle according to the second embodiment on the connection rail.

Fig. 17 is a cross-sectional view showing the structure of the travelling unit of the vehicle according to the second embodiment together with the rail.

15 Fig. 18 is a cross-sectional view showing the structure of the travelling unit of the vehicle according to the second embodiment together with the rail.

EMBODIMENTS

[0015]

20 The embodiments of the present invention will be explained below based on the figures.

<First Embodiment>

First, the overall structure of the rail guided vehicle system according to the first

embodiment will be explained, referring to Fig. 1. Fig. 1 is a plan view showing the overall structure of the rail guided vehicle system according to the first embodiment.

[0016]

In Fig. 1, the rail guided vehicle system according to the present embodiment
5 comprises a rail 100, vehicles 200, and a controller 300.

[0017]

The rail 100 is arranged on a ceiling and made of metal such as aluminum, stainless steel, etc. The rail 100 includes a first main rail 101 and a second main rail 102, and a connection rail 105. The first main rail 101 and the second main rail 102 arranged parallel
10 to each other. The connection rail 105 connects the first main rail 101 to the second main rail 102. Thus, the vehicles 200 travelling on the first main rail 101 can move to the second main rail 102 by travelling on the connection rail 105.

[0018]

A plurality of vehicles 200 are arranged on the rail 100 and can convey FOUPs, as
15 articles to be conveyed, by travelling along the rail 100.

[0019]

In addition, each of the vehicles 200 includes an on-board controller 205. The on-board controller 205 receives conveying instructions from the controller 300, and controls the travelling of the vehicle 200. It should be noted that the on-board controller 205 not
20 only controls the travelling of the vehicle 200, but also has a function of controlling all of the apparatuses included in the vehicle 200.

[0020]

The controller 300 includes an arithmetic circuit, a memory, etc. and is configured to give the conveying instructions to the vehicle 200 via the on-board controller 205.

[0021]

Although not shown in the figure, a shelf (for example, a buffer, a port, etc.) storing the FOUP temporarily and a semiconductor fabricating apparatus are arranged in the location along the rail 100.

[0022]

Next, the further detailed structure of the vehicle 200 will be explained referring to Fig. 2. Fig. 2 is a side view showing the structure of the vehicle according to the first embodiment.

[0023]

In Fig. 2, the vehicle 200 includes a travelling unit 210, a main body member 220, a moving unit 230, a hoist unit 235, a hoist belt 240, and a gripping unit 250. Diverging rollers and position stabilizing rollers, which are described later, are omitted in Fig. 2 for the convenience of this explanation.

[0024]

The vehicle 200 travels along the rail 100 while travelling rollers 215 are rolled by a driving power of the travelling unit 210, e.g., a linear motor. The main body member 220 is suspended on the bottom plane of the travelling unit 210.

20 [0025]

The moving unit 230 is attached to the main body member 220. The moving unit 230 can move to the side (namely, in the right and left directions in Fig. 2) of the rail 100.

The hoist unit 235 is attached to the bottom plane of the moving unit 230.

[0026]

The gripping unit 250 that grips the FOUP is attached to the bottom plane of the hoist unit 235 by the hoist belt 240. The gripping unit 250 can ascend or descend relative to the main body member 220 by winding off or reeling in the hoist belt 240.

[0027]

Next, the method of transferring the FOUP by the vehicle will be explained referring to Figs. 3 and 4. Figs. 3 and 4 are perspective views showing the method of transferring the FOUP by the vehicle according to the first embodiment.

10 [0028]

In Figure 3, when the vehicle 200 transfers the FOUP 400 on the port 510 located right below the rail 100, the vehicle 200 first travels on the rail 100 and stops over the FOUP 400 arranged on the port 510.

[0029]

15 Next, as shown in Fig. 3, the hoist unit 235 winds off the hoist belt 240 and the gripping unit 250 then descends to the location of the FOUP 400. The gripping unit 250 then grips the FOUP 400.

[0030]

20 After the gripping unit 250 grips the FOUP 400, the hoist unit 235 reels the hoist belt 240 so that the gripping unit 250 and the FOUP 400 ascend to the location of the main body member 220. Then, the vehicle 200 travels again on the rail 100 and the FOUP 400 is conveyed.

[0031]

The example shown in Fig. 4 shows the case when the FOUP 400 is arranged at a side buffer 520 located off the side of the rail 100. In this case, after the moving unit 230 moves to the side of the rail 100, the hoist unit 235 winds off the hoist belt 240 and the gripping unit 250 descends to the location of the FOUP 400. With such an operation, it is possible to perform a lateral transfer of the FOUP 400 located off the side of the rail unit 100.

[0032]

Next, the method of travelling on the connection rail by the vehicle according to the present embodiment, and the specific structures of the vehicle and the rail that realize preferable travelling on the connection rail, will be explained referring to Figs. 5 through 9. Fig. 5 is a plan view showing the travelling of the vehicle according to the first embodiment on the connection rail. In addition, Figs. 6 through 9 are cross-sectional views showing the structure of the travelling unit according to the first embodiment together with the rail. Figs. 6 through 9 show the vehicle viewed from the back side of the vehicle in the travelling direction.

[0033]

The operation performed when the vehicle 200 travels from the first main rail 101 to the connection rail 105 and then moves to the second main rail 102 will be explained below, referring to Fig. 5. In the vehicle 200 according to the present embodiment, diverging rollers 610 and position stabilizing rollers 620 are arranged in each of the bogie trucks.

[0034]

As shown in Fig. 5 and Fig. 6, when the vehicle 200a travelling on the first main rail

101 reaches the point where a diverging guide 110a is arranged, the diverging rollers 610 are guided by the diverging guide 110a. A pair of the diverging rollers 610 are supported by a diverging roller supporting member 720 that is configured to shift in the direction crossing the travelling direction of the vehicle 200 (namely, the right and left directions in Fig. 6).

5 Here, the vehicle 200a is about to move to the connection rail 105. The connection rail 105 is located to the left side of the first main rail 101 in the travelling direction. The diverging roller supporting member 720 is shifted to the left side at the point where the diverging guide 110a is arranged. In such a situation, the left side one of the pair of the diverging rollers 610 is positioned to be guided by the diverging guide 110a. In this manner, the vehicle 200 is
10 guided from the first main rail 101 to the connection rail 105.

[0035]

On the other hand, when the vehicle 200 is not guided to the connection rail 105, the diverging roller supporting member 720 is shifted to the right side. In such a situation, the diverging rollers 610 are not guided by the diverging guide 110a at the side of the connection
15 rail 105 but by a diverging guide 110c at the side for travelling straight. Thus, the vehicle 200 is kept travelling on the first main rail 101.

[0036]

As shown in Fig. 5 and Fig. 7, in the vehicle 200b having moved to the connection rail 105 and reaching the point where a position stabilizing roller guide 120a is arranged, the
20 position stabilizing rollers 620 at the left side are guided by the position stabilizing roller guide 120a. A pair of the position stabilizing rollers 620 are supported by the position stabilizing roller supporting member 710, together with a pair of side rollers 650. The

position stabilizing rollers 710 are guided by the position stabilizing roller guide 120a and are configured to stabilize the position of the vehicle.

[0037]

As shown in Fig. 5 and Fig. 8, when the vehicle 200b reaches the point where the position stabilizing roller guide 120b is arranged, the position stabilizing rollers 620 at the right side (namely, the rollers at the side opposite to the side where the rollers that were guided before are arranged) are guided by the position stabilizing roller guide 120b. Although the position stabilizing roller guides 120a and 120b do not overlap with each other in the present embodiment, a zone where both the position stabilizing roller guides 120a and 120b are overlapping may exist.

[0038]

In the zone where the position stabilizing rollers 620 are guided by each of the position stabilizing roller guides 120a and 120b, the diverging roller supporting member 720 is released (namely, the diverging roller supporting member 720 is in the state in which the diverging roller supporting member 720 can be shifted). This is because the diverging guide 110 configured to guide the diverging rollers 610 is not arranged. Therefore, the diverging roller supporting member 720 is shifted to the right side in the zone where the position stabilizing rollers 620 are guided.

[0039]

As shown in Fig. 5 and Fig. 9, when the vehicle 200c reaches the point where the diverging guide 110b exists after passing through the zone where the position stabilizing roller guide 120b exists, the diverging roller supporting member 720 is shifted to the right

side. As a result, the diverging rollers 610 at the right side are guided by the diverging guide 110b. Therefore, the vehicle 200 can move from the connection rail 105 to the second main rail 102.

[0040]

5 The movement of the vehicle from the first main rail 101 to the second main rail 102 can be preferably realized with the rail guided vehicle system according to the present embodiment, since the diverging rollers 610 and the position stabilizing rollers 620 are respectively guided by the diverging guide 110 and the position stabilizing roller guide 120. In the present embodiment, the position stabilizing rollers 620 are guided by the position
10 stabilizing roller guide 120 in the no-guide zone, the no-guide zone being where the diverging guide 110 is not arranged. Therefore, the position of the vehicle 200 can be stabilized even in the no-guide zone.

[0041]

 The rail guided vehicle system that does not include the above-described position
15 stabilizing rollers 620 and the position stabilizing roller guide 120 will be explained, referring to Figs. 10 through 12. Fig. 10 is a cross-sectional view showing the structure of the travelling unit of the vehicle together with the rail, according to the comparative example. Fig. 11 is a plan view showing the zone where the position of the vehicle according to the comparative example is stable, and the zone where the position of the vehicle is unstable.
20 Fig. 12 is a plan view showing a diverging roller shifting zone for the vehicle according to the comparative example.

[0042]

As shown in Fig. 10 and Fig. 11, in the rail guided vehicle system according to the comparative example, the position stabilizing rollers 620 and the position stabilizing roller guide 120 are absent. Thus, in the zone where both side rollers 650 located at the right and left sides abut rail walls (namely, the inner side plane of the rail 100) in the no-guide zone where the diverging guide 110 is absent, the position of the vehicle 200 is stable. However, as shown in Fig. 11, in the no-guide zone where the diverging guide 110 is absent, there is a zone where the rail wall exists only at one side in the travelling direction. In this zone, the side rollers 650 abut only one of the rail walls. Thus, in the above-described zone, since the position cannot be stabilized by the side rollers 650, it is hard to stabilize the position of the vehicle 200. Therefore, in order to realize the stable travelling of the vehicle 200 in the connection rail 105, it is required to lengthen the diverging guide 110.

[0043]

As shown in Fig. 12, if the diverging guide 110 is lengthened in the rail guided vehicle system according to the comparative example, the length of the zone where the diverging rollers 610 are shifted (namely, the no-guide zone where the diverging guide 110 is not arranged) becomes shorter. Therefore, there might be the case in which it is hard for the diverging rollers 610 to be shifted properly. In addition, in such a case, the use of a forcing guide, configured to force the diverging rollers 610 to be shifted, is possible. However, even if the forcing guide is used, the diverging rollers 610 need to be shifted rapidly unless the vehicle 200 is slowed down. Shifting the diverging rollers 610 rapidly might cause abnormal operations because the diverging rollers 610 might receive a large force. In addition, since, if the diverging rollers 610 are rapidly shifted, the impulsion generated when

the diverging rollers 610 abut the diverging guide 110 becomes large, the vibration of the vehicle 200 and/or the damages of the diverging rollers 610 might occur.

[0044]

On the other hand, the rail guided vehicle system according to the present
5 embodiment shown in Figs. 5 through 9 includes the position stabilizing rollers 620 and the position stabilizing roller guide 120. As a result, the no-guide zone, where the diverging guide 110 is not arranged, can be lengthened. Thus, the shifting operation of the diverging rollers 610 can reliably and safely be performed.

[0045]

10 As it can be seen by comparing Fig. 5 with Fig. 11 and Fig. 12, in the rail guided vehicle system according to the present embodiment, while the no-guide zone is longer than that of the rail guided vehicle system according to the comparative example, the lengths of the connection rail 105 are same. Namely, the rail guided vehicle system according to the present embodiment can prevent the connection rail 105 from becoming longer even if the
15 no-guide zone is lengthened. Thus, the connection rail 105 can be shortened even if the no-guide zone is lengthened.

[0046]

As explained above, with the rail guided vehicle system according to the present embodiment, the position stabilizing rollers 620 makes possible the stable travelling on the
20 connection rail. In addition, the position stabilizing rollers 620 make the system smaller by shortening the length of the connection rail 105.

[0047]

<Second Embodiment>

Next, the rail guided vehicle system according to the second embodiment will be explained. Only some of the structures in the second embodiment are different from those of the above-described first embodiment and other structures of the second embodiment are almost the same as those of the first embodiment. Therefore, only the structures that are different from those of the first embodiment will be explained below, and the explanation of structures that are the same as those of the first embodiment will be omitted from the following description accordingly.

[0048]

The structure of the vehicle according to the second embodiment will be explained, referring to Fig. 13 and Fig. 14. Fig. 13 is a cross-sectional view showing the structure of the travelling unit of the vehicle according to the second embodiment together with the rail. Fig. 14 is a side view showing the structure of the travelling unit of the vehicle according to the second embodiment.

[0049]

As shown in Fig. 13, in the vehicle 200 according to the second embodiment, lower position stabilizing rollers 625 are arranged at the lower portion of the travelling unit 210. The lower position stabilizing rollers 625 are fixed so as not to be shifted, and are arranged at the position closer to the lower plane of the rail 100 (namely, the travelling plane on which the travelling unit 210 travels).

[0050]

As shown in Fig. 14, the lower position stabilizing rollers 625 are arranged in line

along the travelling direction of the vehicle 200. Specifically, two lower position stabilizing rollers 625a are arranged longitudinally at the front side of the travelling unit 210a in the travelling direction. In addition, two lower position stabilizing rollers 625b are arranged longitudinally at the back side of the travelling unit 210b in the travelling direction.

5 [0051]

Next, the structure of the rail in the rail guided vehicle system according to the second embodiment will be explained, referring to Fig. 15. Fig. 15 is a plan view showing the structure of the travelling plane of the rail according to the second embodiment.

[0052]

10 As shown in Fig. 15, the rail 100 according to the second embodiment includes a first projecting member 910 and a second projecting member 920 in the travelling plane of the connection rail 105. The first projecting member 910 has a first side plane portion 915. The second projecting member 920 has a second side plane portion 925. As described later, the first side plane portion 915 and the second side plane portion 925 are arranged at the
15 position where they abut the lower position stabilizing rollers 625.

[0053]

The first projecting member 910 is arranged at the right side of the rail 100 in the travelling direction and extends from the vicinity of the diverging point of the first main rail 101 and the connection rail 105, to the middle of the connection rail 105. The second
20 projecting member 920 is arranged to the left side of the rail 100 in the travelling direction and extends from the middle of the connection rail 105 to the vicinity of the merging point of the connection rail 105 and the second main rail 102. The first projecting member 910 and

the second projecting member 920 are arranged at the position where they do not overlap with each other in the travelling direction of the vehicle 200.

[0054]

The length of the gap between the first side plane portion 915 and the second side plane portion 925 in the travelling direction of the vehicle 200 is long enough to change the rotation direction of the lower position stabilizing roller 625. In addition, the length of the gap between the first side plane portion 915 and the second side plane portion 925 in the direction crossing the travelling direction of the vehicle 200 is equal to the diameter of the lower position stabilizing roller 625.

[0055]

Next, the method of travelling on the connection rail 105 by the vehicle 200 according to the second embodiment and the operation of the travelling unit 210 will be explained in detail, referring to Figs. 16 through 18. Fig. 16 is a plan view showing the travelling of the vehicle according to the second embodiment on the connection rail. Fig. 17 and Fig. 18 are cross-sectional views showing the structure of the travelling unit of the vehicle according to the second embodiment together with the rail.

[0056]

The operation that is performed when the vehicle 200a travels from the first main rail 101 to the connection rail 105 and then moves to the second main rail 102 will be explained below. Since the guiding operation and the shifting operation of the diverging rollers 610 are the same as those in the above-described first embodiment, here the operation of the lower position stabilizing rollers 625 that is unique in the second embodiment will be

explained in detail.

[0057]

As shown in Fig. 16 and Fig. 17, in the vehicle 200b reaching the connection rail 105, the lower position stabilizing rollers 625 abut the first side plane portion 915 of the first projecting member 910 when the vehicle 200b moves across the end of the diverging guide 110a. Thus, the position of the vehicle 200 can be stabilized even if the diverging rollers 610 are not guided by the diverging guide 110a. Specifically, the position of the vehicle 200 can be maintained by the abutting portion of the lower position stabilizing rollers 625 and the first side plane portion 915, and by the abutting portion of the side rollers 650 at the left side and the rail wall.

[0058]

As shown in Fig. 16 and Fig. 18, when the vehicle 200b moves across the end of the first projecting member 910, the lower position stabilizing rollers 625 then abut the second side plane portion 925 of the second projecting member 920. Thus, the position of the vehicle 200 can be stabilized even if the diverging rollers 610 are not guided by the diverging guide 110b existing at the side of the second main rail 102. Specifically, the position of the vehicle 200 can be maintained by the abutting portion of the lower position stabilizing rollers 625 and the second side plane portion 925, and by the abutting portion of the side rollers 650 at the right side and the rail wall.

[0059]

As shown in Fig. 16, when the vehicle 200 reaches the second main rail 102 and moves across the end of the second projecting member 920, the diverging rollers 610 are

guided by the diverging guide 110b. Therefore, the position of the vehicle 200 is stabilized even if the lower position stabilizing rollers 625 do not abut the second side plane portion 925.

[0060]

5 As described above, with the lower position stabilizing rollers 625, and the first projecting member 910 and the second projecting member 920, the travelling position of the vehicle 200 can be stabilized even in the zone where the diverging guide 110 does not exist. Therefore, the zone where the diverging guide 110 is arranged can be shortened. By shortening the zone where the diverging guide 110 is arranged, the no-guide zone can be
10 lengthened without changing the length of the connection rail 105. Namely, even if the no-guide zone is lengthened, the connection rail 105 does not become longer due to the lengthening of the no-guide zone. As a result, the connection rail 105 can be shortened.

[0061]

 As described above, with the rail guided system according to the second
15 embodiment, like the above-described first embodiment, the lower position stabilizing rollers 620 enable the travelling on the connection rail to be stable and the system can be made smaller by shortening the length of the connection rail 105.

[0062]

 The present invention is not limited to the above-described embodiment and can be
20 arbitrarily changed without departing from the scope or concept of the invention that can be read from the claims and the entire specification. The rail guided vehicle system including such changes is also within the scope of the present invention.

EXPLANATION OF REFERENCE NUMERALS

[0063]

	100	rail
	101	first main rail
5	102	second main rail
	105	connection rail
	110	diverging guide
	120	position stabilizing roller guide
	200	vehicle
10	210	travelling unit
	215	travelling roller
	220	main body unit
	230	moving unit
	240	hoist belt
15	250	gripping unit
	300	controller
	400	FOUP
	510	port
	520	side buffer
20	610	diverging roller
	620	position stabilizing roller
	625	lower position stabilizing roller

710	position stabilizing roller supporting member
720	diverging roller supporting member
810	connecting shaft
910	first projecting member
5 915	first side plane portion
920	second projecting member
925	second side plane portion

CLAIMS

1. A rail guided vehicle system comprising:

a rail that includes a first main rail, a second main rail, and a connection rail that connects the first main rail to the second main rail, and

5 vehicles that travel while being supported and guided by the rail,

the vehicle including:

a travelling unit configured to travel on the rail;

a first diverging roller and a second diverging roller that are arranged with a gap, the gap being in between the first diverging roller and the second diverging roller in a width
10 direction of the travelling unit;

a diverging roller supporting member arranged in the travelling unit, the diverging roller supporting member supporting the first diverging roller and the second diverging roller such that the first diverging roller and the second diverging roller shift in the width direction of the travelling unit;

15 position stabilizing rollers configured to stabilize a travelling position of the travelling unit; and

a position stabilizing roller supporting member that is arranged in the travelling unit, the position stabilizing roller supporting member supporting the position stabilizing rollers such that the position stabilizing rollers do not shift in the width direction of the travelling
20 unit, and

the rail including:

a first diverging guide that extends, on one side of the connection rail in a width

direction of the connection rail, from the first main rail along an extending direction of the connection rail, the first diverging guide being configured to guide the first diverging roller;

a second diverging guide that extends, on another side of the connection rail in the width direction of the connection rail, to the second main rail along the extending direction of the connection rail while having a no-guide zone that does not overlap with the first diverging guide in the extending direction of the connection rail, the second diverging guide being configured to guide the second diverging roller; and

a position stabilizing roller guide that is arranged in the no-guide zone, the position stabilizing roller guide being configured to guide the position stabilizing rollers in the no-guide zone.

2. The rail guided vehicle system according to claim 1, wherein

the vehicle includes a main body member and a plurality of bogie truck units that are arranged so as to rotate in a horizontal direction of the main body member, and

the travelling unit, the diverging roller supporting member, and the position stabilizing roller supporting member are arranged in each of the plurality of bogie truck units.

3. The rail guided vehicle system according to claim 1, wherein

the position stabilizing roller includes a first roller member and a second roller member, the first roller member and the second roller member being attached with a gap in between in the width direction of the travelling unit, and

the position stabilizing roller guide includes:

a first roller guide member extending along the extending direction on one side of the connection rail in the width direction of the connection rail and in the no-guide zone, the first roller guide member being configured to guide the first roller member and

5 a second roller guide member extending along the extending direction on another side of the connection rail in the width direction of the connection rail and in the no-guide zone, the second roller guide member being configured to guide the second roller member.

4. The rail guided vehicle system according to claim 3, wherein

10 the rail is arranged on a ceiling or in the vicinity of the ceiling, the rail including a first travelling plane portion and a second travelling plane portion at both sides of the lower portion of the rail in the width direction of the rail, the first travelling plane portion and the second travelling plane portion being arranged with a gap in between,

the first roller guide member rises in a planar manner from a position closer to the gap of the first travelling plane portion of the connection rail,

15 the second roller guide member rises in a planar manner from a position closer to the gap of the second travelling plane portion of the connection rail, and

the first roller member and the second roller member are guided by abutting the first roller guide member and the second roller guide member, respectively, from the outer sides of the connection rail in the width direction of the connection rail.

20

5. The rail guided vehicle system according to claim 1, wherein

the rail is arranged on a ceiling or in the vicinity of the ceiling, the rail including a

first travelling plane portion and a second travelling plane portion at the both sides of the lower portion of the rail, the rail having a gap between the first travelling plane portion and the second travelling plane portion,

the rail further including:

5 a first projecting member that projects toward the gap from the first travelling plane portion in the no-guide zone, the first projecting member extending with a predetermined length along the extending direction of the connection rail, the first projecting member having a first side plane portion at the end side of the first projecting member in a width direction of the first projecting member; and

10 a second projecting member that projects toward the gap from the second travelling plane portion in a position that does not overlap with the first projecting member in the extending direction of the connection rail in the no-guide zone, the second projecting member extending with a predetermined length along the extending direction of the connection rail, the second projecting member having a second side plane portion at the end side of the
15 second projecting member in a width direction of the second projecting member, and

the position stabilizing roller supporting member is arranged at the lower side of the travelling unit, the position stabilizing roller supporting member supporting the position stabilizing rollers such that the position stabilizing rollers abut the first side plane portion and the second side plane portion.

20

6. The rail guided vehicle system according to claim 5, wherein

the position stabilizing rollers are arranged in line along a travelling direction of the

vehicle in the vicinity of the center portion of the lower side of the travelling unit in the width direction of the travelling unit, and

the first side plane portion and the second side plane portion are separated from each other with a gap equal to a diameter of the position stabilizing roller in the width direction.

5

7. The rail guided vehicle system according to claim 2, wherein

the position stabilizing roller includes a first roller member and a second roller member, the first roller member and the second roller member being attached with a gap in between in the width direction of the travelling unit, and

10 the position stabilizing roller guide includes:

a first roller guide member extending along the extending direction in the no-guide zone, on one side of the connection rail in the width direction of the connection rail, the first roller guide member being configured to guide the first roller member and

15 a second roller guide member extending along the extending direction in the no-guide zone, on another side of the connection rail in the width direction of the connection rail, the second roller guide member being configured to guide the second roller member.

8. The rail guided vehicle system according to claim 7, wherein

20 the rail is arranged on a ceiling or in the vicinity of the ceiling, the rail including a first travelling plane portion and a second travelling plane portion at both sides of the lower portion of the rail in a width direction of the rail, the first travelling plane portion and the second travelling plane portion being arranged with a gap in between,

the first roller guide member rises in a planar manner from a position closer to the gap of the first travelling plane portion of the connection rail,

the second roller guide member rises in a planar manner from a position closer to the gap of the second travelling plane portion of the connection rail, and

5 the first roller member and the second roller member are guided by abutting the first roller guide member and the second roller guide member, respectively, from the outer sides of the connection rail in the width direction of the connection rail.

9. The rail guided vehicle system according to claim 2, wherein

10 the rail is arranged on a ceiling or in the vicinity of the ceiling, the rail including a first travelling plane portion and a second travelling plane portion at the both sides of the lower portion of the rail, the rail having a gap between the first travelling plane portion and the second travelling plane portion,

the rail further including:

15 a first projecting member that projects toward the gap from the first travelling plane portion in the no-guide zone, the first projecting member extending with a predetermined length along the extending direction of the connection rail, the first projecting member having a first side plane portion at the end side of the first projecting member in a width direction of the first projecting member; and

20 a second projecting member that projects toward the gap from the second travelling plane portion in a position that does not overlap with the first projecting member in the extending direction of the connection rail in the no-guide zone, the second projecting member

extending with a predetermined length along the extending direction of the connection rail,
the second projecting member having a second side plane portion at the end side of the
second projecting member in a width direction of the second projecting member, and

the position stabilizing roller supporting member is arranged at the lower side of the
5 travelling unit, the position stabilizing roller supporting member supporting the position
stabilizing rollers such that the position stabilizing rollers abut the first side plane portion and
the second side plane portion.

10 10. The rail guided vehicle system according to claim 9, wherein the position
stabilizing rollers are arranged in line along a travelling direction of the vehicle in the vicinity
of the center portion of the lower side of the travelling unit in the width direction of the
travelling unit, and

the first side plane portion and the second side plane portion are separated from each
other with a gap equal to a diameter of the position stabilizing roller in the width direction.

15