



(51) International Patent Classification:
G01N 27/64 (2006.01) **B08B 9/32** (2006.01)

(21) International Application Number:
PCT/SG2010/000014

(22) International Filing Date:
19 January 2010 (19.01.2010)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **R2CD HOLDINGS PTE LTD** [SG/SG]; Blk 716, Bedok Reservoir Road, Unit 10-4516, Singapore 470716 (SG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **CHAN, Wai Hoe** [SG/SG]; Blk 716, Bedok Reservoir Road, Unit 10-4516, Singapore 470716 (SG).

(74) Agent: **CHONG, Y., F;** P. O. Box 0399, Psa Building, Singapore 911144 (SG).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: AN AUTO-CLEANING AND AUTO-ZEROING SYSTEM USED WITH A PHOTO-IONIZATION DETECTOR



(57) Abstract: An auto-cleaning and auto-zeroing system (1) comprises a first conduit for flow of ambient gas (16) and a 2nd conduit (22) for flow of ambient air (18). A cleaning chamber (12) removes impurities from ambient air (18). The 1st conduit (20) and 2nd conduit (22) are connected to a valve, operated by the continuous motor, which continuously draws ambient gas (16) or cleaned and filtered ambient air (18) through the system. Cleaned and filtered ambient air (18) enters the ionization chamber (10) to carry out a cleaning (flushing) and a cleaning (ionization) cycle. In this manner, contaminants and pollutants left in the ionization chamber (10) from the measurement of ambient gas (16) are flushed out and removed.

