

STEAM FLOOR MOP

FIELD OF THE INVENTION

This utility model relates to a steam floor mop, and specifically, to a steam cleaning appliance for cleaning work.

BACKGROUND OF THE INVENTION

The current floor cleaning mops are generally classified into two types: one is the traditional floor mop which can be used for the dry cleaning work, and is not suitable to realize a wet cleaning purpose; therefore, its application is limited; the other is the floor cleaning mop having a steam distributing function, with which the water is firstly heated vaporized to generate steam which is then distributed to the floor for the cleaning work so as to realize the effect of high-temperature disinfecting and sterilizing. However the current steam floor mop has the following drawbacks: when in use, the water needs to be provided firstly to the steam generator by powering on the water pump additionally, and then is heated vaporized to generate steam for the cleaning work, this process takes such a long time that its application is inconvenient; in addition, the cleaning work has to be performed repeatedly many times in order to obtain a thorough cleaning effect, it is time-consuming and tiring. The main reasons for the above problems are that: most of the cleaning surface of the current mop is flat, which is bad for the steam distributing to the whole cleaning surface, and thus results in the consequence that the cleaning surface can not be wetted uniformly, some portion of the cleaning surface is too dry while some portion is too wet, and that, the

effect of high-temperature disinfecting and sterilizing can not be realized; moreover, the cleaning cloth serves to cover the floor brush is too smooth without any pattern or stripe that the stains adhered to the floor cannot be cleaned easily.

SUMMARY OF THE INVENTION

In view of the above-described problems, it is an objective of the present utility model to provide a steam floor mop with which the steam can be distributed instantaneously to the floor brush so as to perform the cleaning work by only pushing the handle of the steam floor mop.

It is another objective of the present utility model, to provide a steam floor mop with which the cleaning work can be performed conveniently and is time and labor saving, and the effect of high temperature disinfecting and sterilizing can be realized thoroughly.

To achieve the above objectives, the utility model provides a steam floor mop comprising a handle; a body inside which a manual water pump, a water tank, and a steam generator are provided; and a floor brush connected movably to the body, wherein the manual water pump, the water tank, the steam generator and the floor brush are connected by means of pipes; said handle is connected directly to the piston rod in the manual water pump and serves to manipulate the operation of the manual water pump; and said floor brush is covered by a cleaning cloth.

In accordance with the steam floor mop of the present utility model, a buffer area is provided at a central steam inlet mouth of the floor brush, a plurality of rib stripes is extended from the center of the buffer

area, a plurality of steam distributing grooves is formed between the rib stripes, and a peripheral edge is set around a rim of the floor brush.

In accordance with the steam floor mop of the present utility model, said manual water pump comprises a pump body, the piston rod, a water pump inlet mouth, a water pump outlet mouth, a one-way inlet pump core, and a one-way outlet pump core; and a piston cavity of the pump body is a stepped cavity where a upper cavity of the piston cavity has a larger diameter than the lower cavity of the piston cavity.

In accordance with the steam floor mop of the present utility model, said steam generator comprises a conical shell and a heating core; a water inlet mouth is provided on a bottom end of the heating core, a plurality of electrical heating bodies is die cast in the heating core and a handstand conical cavity is formed inside the heating core, a steam collection room is provided inside the conical shell and is positioned opposite to the conical cavity formed by the inner wall of the shell, a slidable steam separating cover is located between the steam collection room and the heating core, a steam collecting mouth for connecting the conical cavity to the steam collection room is provided at the center of the steam separating cover, a steam exit is provided at a top end of the steam collection room, and a plurality of C-shaped guide rings is set at the water inlet mouth on a bottom end of the heating core.

In accordance with the steam floor mop of the present utility model, said cleaning cloth is matchable with the floor brush and is served to cover tightly the floor brush, and a plurality of #-shaped grilles is formed on the surface of the cleaning cloth.

In accordance with the steam floor mop of the present utility model, the height of the peripheral edge of said floor brush is 0.5-2mm higher than that of the rib stripes.

In accordance with the steam floor mop of the present utility model, said cleaning cloth is in a shape of vest, a pair of fixing straps is extended from a upper portion of the cleaning cloth, a plurality of magic female tapes is affixed on the fixing straps, and a plurality of magic male tapes that can be pasted fixed with the said magic female tapes respectively is affixed on a lower portion of the cleaning cloth.

In accordance with the steam floor mop of the present utility model, a handle cover that can socket with the handle is located on a top end of said body, and the upper end of said handle cover is fixed on the body.

In accordance with the steam floor mop of the present utility model, the one-way inlet pump core and the one-way outlet pump core of said water pump are in a shape of flat cone having a top structure that can be opened after an elastic deformation.

In accordance with the steam floor mop of the present utility model, a steam inlet mouth is also provided on said floor brush, and is connected to the water outlet mouth of the steam generator.

As a result, in accordance with the steam floor mop of the present utility model, by only pushing the handle of the steam floor mop, the steam can be generated and instantaneously distributed to the floor brush so that the cleaning work having an effect of high temperature disinfecting and sterilizing can be realized. It is not needed to power on

the water pump additionally so as to supply water to the steam generator to generate the steam. Besides, a plurality of rib stripes is set on the floor brush, and a plurality of steam distributing grooves is formed between the rib stripes, so that the steam can be distributed uniformly to the whole cleaning surface of the floor brush. In addition, the floor brush is covered tightly by a cleaning cloth having a plurality of #-shaped grills formed thereon, so that the stains adhered to the floor can be cleaned easily. Therefore, by utilizing the steam floor mop of the present utility model, the cleaning work can be performed conveniently and is time and labor saving, the effect of high temperature disinfecting and sterilizing can be realized thoroughly.

BRIEF DISCRIPTION OF THE DRAWINGS

FIG. 1 is a structural view of a steam floor mop of the present utility model;

FIG. 2 is a sectional view of a steam floor mop of the present utility model;

FIG. 3 is a top view of a floor brush for a steam floor mop of the present utility model;

FIG. 4 is a bottom view of the floor brush for the steam floor mop of the present utility model;

FIG. 5 is a perspective view of the floor brush for the steam floor mop of the present utility model;

FIG. 6 is an A-A sectional view of FIG. 3 of the present utility model;

FIG. 7 is an enlarged view of portion B of FIG. 6 of the present utility model;

FIG. 8 is a planar view of a cleaning cloth for a steam floor mop of the present utility model;

FIG. 9 is a perspective view of a water pump for a steam floor mop of the present utility model;

FIG. 10 is a sectional view of FIG. 9 of the present utility model; and

FIG. 11 is a structural view of a steam generator for a steam floor mop of the present utility model.

List of reference numerals:

1	handle	11	handle cover
2	body		
3	floor brush	33	steam inlet mouth
34	buffer area	35	rib strips
36	steam distributing grooves	37	peripheral edge
4	manual water pump	41	piston rod
42	water pump inlet mouth	43	water pump outlet mouth
44	one-way inlet pump core	45	one-way outlet pump core
46	piston cavity	47	pump body
5	water tank		
6	steam generator	61	water inlet mouth
62	steam exit	63	conical shell
64	heating core	65	electrical heating body
66	conical cavity	67	steam collection room

68	steam separating cover	69	steam collecting mouth
641	C-shaped guide ring		
7	cleaning cloth	71	fixing strap
72	magic female tape	73	magic male tape
A	first pipe	B	second pipe
C	third pipe		

DETAILED DESCRIPTION OF THE INVENTION

As shown in FIGS. 1-2, a steam floor mop comprises a handle 1, a body 2 inside which a manual water pump 4, a water tank 5, and a steam generator 6 are provided; and a floor brush 3 connected movably to the bottom end of the body 2, wherein said handle 1 is connected directly to a piston rod 41 in the manual water pump 4, and serves to manipulate the operation of the manual water pump 4; said floor brush 3 is covered with a cleaning cloth 7. A water pump inlet mouth 42 and a water pump outlet mouth 43 are formed at the lower end of said manual water pump 4, wherein said water pump inlet mouth 42 is connected to the water tank 5 by means of a first pipe A; said water pump outlet mouth 43 is connected to a water inlet mouth 61 of the steam generator 6 by means of a second pipe B; a steam exit 62 of the steam generator 6 is connected to the floor brush 3 by means of a third pipe C. During performing the cleaning work using the steam floor mop, by only pushing the handle 1 of the steam floor mop, the piston rod 41 at the top end of the manual water pump 4 is pushed by the handle 1; water is fed into the steam generator 6 by means of the manual water pump 4, and then is heated vaporized to generate steam by the steam generator 6; the generated steam firstly flows

into the floor brush 3 by the third pipe C, and then flows into the cleaning cloth 7 covered on the floor brush 3; the cleaning work having an effect of high temperature disinfecting and sterilizing can be realized by using the steam with the cleaning cloth 7. It is not needed to power on the water pump additionally so as to supply water to the steam generator to generate the steam.

A handle cover 11 that can socket with the handle 1 and serves to limit the moving range of the handle 1 is also located on a top end of the body 2, and the upper end of the handle cover 11 is fixed on the body 2.

As shown in FIGS. 3-7, the floor brush 3 is a fan-shaped brush, a steam inlet mouth 33 is further provided at the floor brush 3, and is connected to the water outlet mouth 62 of the steam generator 6 by means of the third pipe C. A buffer area 34 is provided around the center steam inlet mouth 33 of the floor brush 3 and serves mainly to buffer the pressure and speed of the steam in order to guide smoothly the flow of the steam. A plurality of rib strips 35 is extended from the center of the buffer area 34 and a plurality of steam distributing grooves 36 is formed between the rib stripes. In this way, the steam can be distributed uniformly to the whole cleaning surface of the floor brush, the excessive steam can be vented out and thus the excessive moisture of the cleaning cloth 7 can be avoided. Besides, a peripheral edge 37 is set around the rim of the floor brush 3, and is 0.5-2 mm higher than the rib stripes 35.

As shown in. FIGS. 9-10, the manual water pump 4 comprises a pump body 47, a piston rod 41, a water pump inlet mouth 42, a water pump outlet mouth 43, a one-way inlet pump core 44, and a one-way

outlet pump core 45. A piston cavity 46 of said pump body 47 is a stepped cavity, where the upper cavity has a larger diameter than the lower cavity. The one-way inlet and outlet pump cores 44, 45 are made of elastic material and have a top structure that can be opened after an elastic deformation so as to form a two-layered anti-backpressure apparatus, thereby to against the backpressure of the steam generator 6, and thus to prevent the pump cores from being broken down by the backpressure of the steam generator 6, as well as to control the one-way flow of the water. Namely, the manual water pump 4 can be regarded as a one-way automatic artificial intelligent feed pump, and by pushing the handle 1 of the steam floor mop, the piston rod 41 of the manual water pump 4 can be operated to push automatically the pump water to the steam generator 6.

As shown in FIG. 11, the steam generator 6 comprises a conical shell 63 and a heating core 64, wherein a water inlet mouth 61 is formed at the bottom end of the heating core 64, and a plurality of electrical heating bodies 65 is die cast and a handstand conical cavity 66 is formed inside the heating core 64; a steam collection room 67 is provided inside the conical shell 63 and is positioned opposite to the conical cavity 66; a slidable steam separating cover 68 is located between the steam collection room 67 and the heating core 64, a steam collecting mouth 69 for connecting the conical cavity 66 to the steam collection room 67 is provided at the center of the steam separating cover 68, and a steam exit 62 is provided on the top end of said steam collection room. In addition, a plurality of C-shaped guide rings 641 is set at the water inlet mouth 61 on a bottom end of the heating core 64, and is served to separate the flow

of the water in order to distribute the water uniformly to the whole surface of the heating core.

As shown in FIG. 8, the cleaning cloth 7 is in a shape of vest, a pair of fixing straps 71 is extended from the upper portion of the cleaning cloth 7; a magic female tape 72 is affixed on each of said fixing straps 71, a pair of magic male tapes 73 that can be pasted fixed with the magic female tapes 72 is affixed on a lower portion of the cleaning cloth 7. The size of the cleaning cloth 7 that is matchable with the size of the floor brush is applied to cover the floor brush 3 tightly. A plurality of #-shaped grilles are formed on the surface of the cleaning cloth so that the stains adhered on the floor can be cleaned easily. The cleaning cloth 7 covered at the upper portion of the floor brush 3 is applied to encase the excessive steam and thusly two sides thereof are heated; the cleaning cloth that covered on the lower portion of the floor brush 3 is used for cleaning the floor.

As stated above, a plurality of rib strips 35 is provided at the floor brush and a plurality of steam distributing grooves 36 is formed between the rib stripes 35, so that the steam can be distributed uniformly to each corner of the floor brush, and the humidity can be balanced. As a result, by using the cleaning cloth formed with #-shaped grilles thereon and covering the floor brush 3 tightly, a cleaning work can be performed conveniently and is time and labor saving, and the effect of high temperature disinfecting and sterilizing can be realized.

What is claimed is:

1. A steam floor mop, characterized in that the steam floor mop comprises:

a handle (1);

a body (2) inside which a manual water pump (4), a water tank (5) and a steam generator (6) are provided; and

a floor brush (3) connected slidably to the body,

wherein, the manual water pump (4), the water tank (5), the steam generator (6) and the floor brush (3) are connected by means of pipes; said handle (1) is connected directly to a piston rod (41) in the manual water pump (4) and serves to manipulate the operation of the manual water pump; and said floor brush (3) is covered by a cleaning cloth (7).

2. The steam floor mop according to claim 1, characterized in that a buffer area (34) is provided at a central steam inlet mouth (33) of the floor brush, a plurality of rib stripes (35) is extended from a center of the buffer area (34), a plurality of steam distributing grooves (36) is formed between the rib stripes (35), and a peripheral edge (37) is set around a rim of the floor brush (3).

3. The steam floor mop according to claim 1 or 2, characterized in that said manual water pump (4) comprises a pump body (47), the piston rod (41), a water pump inlet mouth (42), a water pump outlet mouth (43), a one-way inlet pump core (44), and a one-way outlet pump core (45), and a piston cavity (46) of the pump body (47) is a stepped cavity where

a upper cavity of the piston cavity has a larger diameter than a lower cavity of the piston cavity.

4. The steam floor mop according to claim 1 or 2, characterized in that said steam generator (6) comprises a conical shell (63) and a heating core (64); a water inlet mouth (61) is provided on a bottom end of the heating core (64); a plurality of electrical heating bodies (65) is die cast in the heating core (64) and a handstand conical cavity (66) is formed inside the heating core (64); a steam collection room (67) is provided inside the conical shell and is positioned opposite to the conical cavity; a slidable steam separating cover (68) is located between the steam collection room (67) and the heating core (64); a steam collecting mouth (69) for connecting the conical cavity (66) to the steam collection room (67) is provided at a center of the steam separating cover (68); a steam exit (62) is provided at a top end of the steam collection room; and a plurality of C-shaped guide rings (641) is set at the water inlet mouth (61) on a bottom end of the heating core (64).

5. The steam floor mop according to claim 1 or 2, characterized in that said cleaning cloth (7) on the surface of which a plurality of #-shaped grilles is formed is matchable with the floor brush (3) and is served to cover tightly the floor brush (3).

6. The steam floor mop according to claim 1 or 2, characterized in that the height of the peripheral edge (37) of said floor brush (3) is 0.5 to 2 mm higher than that of the rib stripes (35).

7. The steam floor mop according to claim 5, characterized in that said cleaning cloth (7) is in a shape of vest; a pair of fixing straps (71) is

extended from a upper portion of the cleaning cloth (7); a plurality of magic female tapes (72) is affixed on the fixing straps (71); and a plurality of magic male tapes (73) that can be pasted fixed with the said magic female tapes (72) respectively is affixed on a lower portion of the cleaning cloth (7).

8. The steam floor mop according to claim 1 or 2, characterized in that a handle cover (11) that can socket with the handle (1) is located on a top end of said body (1) [*sic*, "(2)"], and a upper end of said handle cover (11) is fixed on the body (1) [*sic*, "(2)"].

9. The steam floor mop according to claim 1 or 2, characterized in that the one-way inlet pump core (44) and the one-way outlet pump core (45) of said water pump (2) [*sic*, "(4)"] are in a shape of flat cone having a top structure that can be opened after an elastic deformation.

10. The steam floor mop according to claim 1 or 2, characterized in that a steam inlet mouth (33) is also provided on said floor brush (3) and is connected to the water outlet mouth (62) of the steam generator (6).