

(51) International Patent Classification:
G06F 1/12 (2006.01)(21) International Application Number:
PCT/US2012/047756(22) International Filing Date:
20 July 2012 (20.07.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/509,971 20 July 2011 (20.07.2011) US(71) Applicant (for all designated States except US): **AVIAT NETWORKS, INC.** [US/US]; 5200 Great America Parkway, Santa Clara, CA 95054 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **MIHELIC, Janez** [US/US]; 5200 Great America Parkway, Santa Clara, CA 95054 (US).(74) Agents: **KLOKE, Daniel, C.** et al.; Sheppard, Mullin, Richter & Hampton LLP, 379 Lytton Avenue, Palo Alto, CA 94301 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: SYSTEMS AND METHODS OF NETWORK SYNCHRONIZATION




FIG. 5

(57) Abstract: An exemplary method of synchronizing a master clock and a slave clock comprises transmitting a plurality of packets between a master device and a slave device, calculating a first skew between a first pair of the plurality of packets at the slave device and a second skew between the first pair at the master device, calculating a ratio between the first skew and the second skew, providing a slave clock frequency correction to the slave device, calculating a first packet trip delay using a time that the master device initiates sending a packet to the slave device, a time the master device receives a response from the slave device, a corrected time the slave device receives the packet, and a corrected time the slave device initiates sending the response, calculating a first offset based on the first packet trip delay, and providing the first offset to the slave device.