

CLAIMS

1. A method for receiving a paging message, comprising:

determining, by a terminal device, a paging starting moment according to a
5 paging cycle of the terminal device and UE_ID of the terminal device and
determining a paging receiving duration of the paging message indicated by
information in a system message received from an access network device; and

receiving, by the terminal device, the paging message according to the paging
starting moment and the paging receiving duration.

10

2. The method of claim 1, wherein the paging message is transmitted by an access
network device in a manner of beam scanning according to the paging starting
moment and a paging transmitting duration, and the paging receiving duration is more
than or equal to the paging transmitting duration.

15

3. The method of claim 1 or 2, wherein determining, by the terminal device, the
paging starting moment and the paging receiving duration comprises:

determining, by the terminal device, the paging starting moment and the
paging receiving duration according to a paging cycle of the terminal device.

20

4. The method of claim 3, wherein the paging cycle comprises a first period and a
second period, the first period is a period in which the terminal device continuously
listens for the paging message, the second period is a period in which the terminal
device is in a sleep state, and

25

wherein determining, by the terminal device, the paging receiving duration
according to the paging cycle of the terminal device comprises:

determining, by the terminal device, a duration of the first period as the paging
receiving duration,

30

wherein the paging cycle is N times the duration of the first period, N being a
positive integer larger than 1.

5. The method of claim 4, wherein receiving, by the terminal device, the paging
message according to the paging starting moment and the paging receiving duration

comprises:

at the paging starting moment, starting, by the terminal device, a first timer, and simultaneously starting continuously listening, by the terminal device, for the paging message in the first period, a timing period of the first timer being the paging

5 cycle;

in case that the paging message is not heard by the terminal device in the first period, entering, by the terminal device, the sleep state; and

responsive to determining, by the terminal device, timeout of the first timer, restarting continuously listening, by the terminal device, for the paging message.

10

6. The method of claim 4, wherein receiving, by the terminal device, the paging message according to the paging starting moment and the paging receiving duration comprises:

continuously listening, by the terminal device, for the paging message in the first period from the paging starting moment;

15

in case that the paging message is not heard by the terminal device in the first period, at an ending moment of the first period, starting, by the terminal device, a second timer and simultaneously entering, by the terminal device, the sleep state, a timing period of the second timer being a duration of the second period; and

20

responsive to determining, by the terminal device, timeout of the second timer, restarting continuously listening, by the terminal device, for the paging message.

7. The method of any one of claims 4-6, wherein the paging message is started, from the paging starting moment, to be transmitted by the access network device in the manner of beam scanning by means of L paging beams, any two of the L paging beams correspond to different paging transmitting durations, and the duration of the first period is more than or equal to a maximum value of paging transmitting durations corresponding to the L paging beams, L being a positive integer more than or equal to 2.

25
30

8. The method of claim 7, wherein a value of L is 2, a paging transmitting duration corresponding to one of the two paging beams is a cell-specific continuous listening duration of a cell where the terminal device is located or a preset duration, and a

paging transmitting duration corresponding to another of the two paging beams is a terminal device specific continuous listening duration of the terminal device.

9. The method according to claim 2 or 3, further comprising:

5 transmitting, by the terminal device, a response message configured to indicate that the paging message is successfully received, to the access network device; and
 when the terminal device receives an acknowledgment message for the response message from the access network device, starting, by the terminal device, a third timer, and simultaneously entering, by the terminal device, a sleep state; or, at a
10 moment of K time units after the acknowledgment message is received, starting, by the terminal device, the third timer, and simultaneously entering, by the terminal device, the sleep state, K being a positive integer more than or equal to 1.

10. A terminal device, comprising:

15 a determination module, configured to determine a paging starting moment and a paging receiving duration of a paging message according to a paging cycle of the terminal device and UE_ID of the terminal device, wherein the UE_ID is included in the paging message; and
 a transceiver module, configured to receive the paging message according to
20 the paging starting moment and the paging receiving duration.

11. The terminal device of claim 10, wherein the paging message is transmitted by an access network device in a manner of beam scanning according to the paging starting moment and a paging transmitting duration, and the paging receiving duration is more
25 than or equal to the paging transmitting duration.

12. The terminal device of claim 10 or 11, wherein, in terms of determining the paging starting moment and the paging receiving duration, the determination module is specifically configured to:

30 determine the paging starting moment and the paging receiving duration according to a paging cycle of the terminal device.

13. The terminal device of claim 12, wherein the paging cycle comprises a first

period and a second period, the first period is a period in which the terminal device continuously listens for the paging message, the second period is a period in which the terminal device is in a sleep state, and

in terms of determining the paging receiving duration according to the paging cycle of the terminal device, the determination module is configured to:
determine a duration of the first period as the paging receiving duration.

14. The terminal device of claim 13, wherein, in terms of receiving the paging message according to the paging starting moment and the paging receiving duration, the transceiver module is configured to:

at the paging starting moment, start a first timer, and simultaneously start continuously listening for the paging message in the first period, a timing period of the first timer being the paging cycle; and

in case that the paging message is not heard in the first period, cause the terminal device to enter the sleep state,

wherein the determination module is further configured to, responsive to determining timeout of the first timer, cause the transceiver module to restart continuously listening for the paging message.

15. The terminal device of claim 13, wherein, in terms of receiving the paging message according to the paging starting moment and the paging receiving duration, the transceiver module is configured to:

continuously listen for the paging message in the first period from the paging starting moment; and

in case that the paging message is not heard in the first period, at an ending moment of the first period, start a second timer, and simultaneously cause the terminal device to enter the sleep state, a timing period of the second timer being a duration of the second period,

wherein the determination module is further configured to, responsive to determining timeout of the second timer, cause the terminal device to restart continuously listening for the paging message.

16. The terminal device of any one of claims 13-15, wherein the paging cycle is N

times the duration of the first period, N being a positive integer larger than 1.

17. The terminal device of any one of claims 13-16, wherein the paging message is started to be transmitted by the access network device from the paging starting moment in the manner of beam scanning by means of L paging beams, any two of the L paging beams correspond to different paging transmitting durations, and the duration of the first period is more than or equal to a maximum value of paging transmitting durations corresponding to the L paging beams, L being a positive integer more than or equal to 2.

18. The terminal device of claim 17, wherein a value of L is 2, a paging transmitting duration corresponding to one of the two paging beams is a cell-specific continuous listening duration of a cell where the terminal device is located or a preset duration, and a paging transmitting duration corresponding to another of the two paging beams is a terminal device specific continuous listening duration of the terminal device.

19. The terminal device of any one of claims 13-18, wherein the transceiver module is further configured to:

receive a system message from the access network device, the system message comprising information configured to indicate the duration of the first period.

20. The terminal device of claim 11 or 12, wherein the transceiver module is further configured to:

transmit a response message, configured to indicate that the paging message is successfully received, to the access network device; and

upon receiving an acknowledgment message for the response message from the access network device, start a third timer, and simultaneously cause the terminal device to enter a sleep state; or at a moment of K time units after the acknowledgment message is received, start the third timer, and simultaneously cause the terminal device to enter the sleep state, K being a positive integer more than or equal to 1.