MAST SYSTEM AND METHOD

TECHNOLOGICAL FIELD

The presently disclosed subject matter relates to systems and methods for underwater vehicles.

BACKGROUND

A variety of systems and methods for underwater vehicles are known.

Some types of underwater vehicles, for example some submarines, include a vertical structure amid-ships, commonly referred to as a "sail" or "fin", which houses retractable periscopes and the like, and allow the periscope to break surface while the underwater vehicle including the "sail" are still submerged at a short depth from the sea surface.

An example of mast system can be found in document DE3716536, which forms the basis for claim 1.

GENERAL DESCRIPTION

According to at least an aspect of the presently disclosed subject matter, there is provided a mast system for use with an underwater vehicle, comprising:

a support base defining a base axis;

a mast arm defining a longitudinal axis, and comprising a free longitudinal mast end and a mast mounting portion longitudinally spaced from said mast end;

a mast payload bay provided at said mast end, configured for supporting a payload therein;

the mast arm being mounted to the support base via said mast mounting portion, and the mast arm being selectively deployable with respect to the support base at least between a retracted configuration, in which said mast end is at a first spacing with respect to said mast mounting portion, and an extended configuration, in which said mast end is at a second spacing with respect to said

mast mounting portion, wherein said second spacing is greater than said first spacing,

wherein the mast system is configured for operating in a marine environment.

In at least one example the mast system further comprises a pressure vessel, wherein said payload bay is selectively reversibly retractable into said pressure vessel to enable isolating a payload bay pressure from an ambient pressure outside of said pressure vessel.

Additionally or alternatively, for example, said mast arm comprises a plurality of longitudinally movable nested telescopic sections between said mast end and said mast mounting portion.

Additionally or alternatively, for example, the mast system comprises a first drive unit for selectively driving said mast end longitudinally away from said mast mounting to provide said extended configuration, and for selectively driving said mast end longitudinally towards said mast mounting to provide said retracted configuration.

Additionally or alternatively, for example, said mast arm is pivotably mounted to said support base about a pivot axis via said mast mounting portion, said pivot axis being orthogonal to said longitudinal axis. For example, said mast arm is reversibly pivotably movable with respect to said support base about said pivot axis between a stowed position and a deployed position. For example, the mast system comprises a second drive unit for selectively pivoting said mast arm about said pivot axis from said stowed position to said deployed position, and for selectively pivoting said mast arm about said pivot axis from said deployed position to said stowed position. Additionally or alternatively, for example, in said stowed position, said mast arm is in said retracted configuration, and wherein in said deployed position said mast arm is selectively deployable to said extended configuration. Additionally or alternatively, for example, in said stowed position, said longitudinal axis is parallel to said base axis, and wherein in said deployed position said longitudinal axis is orthogonal to said base axis. Additionally or alternatively, for example, said pivot axis is orthogonal to said base axis.

Additionally or alternatively, for example, said payload bay is pivotable about said longitudinal axis, at least in said extended configuration.

Additionally or alternatively, for example, said pressure vessel comprises a closable payload housing, and wherein said payload bay is selectively reversibly

retractable into said payload housing between a housed configuration and an exposed configuration.

Additionally or alternatively, for example, in said housed configuration, fluid communication is prevented between said payload bay and an outside of said mast system.

Additionally or alternatively, for example, said pressure vessel comprises a bulkhead arrangement, wherein in said housed configuration said payload housing is configured for sealing with respect to said bulkhead arrangement to prevent fluid communication between said payload bay and an outside of said mast system, and wherein in said exposed configuration said payload housing is configured for being unsealed with respect to said bulkhead arrangement and to provide fluid communication between said payload bay and an outside of said mast system. For example, said bulkhead arrangement is fixed to the payload bay.

For example, said bulkhead arrangement comprises an outer facing bulkhead at an outer longitudinal end of said payload bay, said bulkhead configured for preventing fluid communication between said payload bay and an outside of said mast system in a longitudinal outward direction through said bulkhead, said bulkhead further comprising a bulkhead sealing perimeter configured for sealing with respect to said payload housing in said housed configuration. For example, the mast system further comprises an auxiliary payload bay projects outwardly from said bulkhead, said auxiliary payload bay being in communication with said payload bay.

For example, said payload housing comprises a chamber configured for accommodating therein said payload bay in said housed configuration, said chamber having a chamber opening configured to allow said payload bay to be selectively and reversibly retracted with respect to said payload housing, said opening comprising a housing sealing perimeter for reversibly sealing with respect to said bulkhead sealing perimeter in said housed configuration. For example, said bulkhead is disc-shaped and wherein said payload housing comprises a lateral peripheral wall having a payload housing axis parallel to said longitudinal axis, and defining said chamber opening and a closed end at respective opposite longitudinal ends of said lateral peripheral wall. For example, said lateral peripheral wall is a tubular wall.

Additionally or alternatively, for example, the mast system comprises an inflatable seal arrangement for selectively sealing and for selectively unsealing said bulkhead with respect to said payload housing.

Additionally or alternatively, for example, said pressure vessel is configured for enabling the payload bay to have a said payload bay pressure isolated from an outside of said mast system, in said housed configuration.

Additionally or alternatively, for example, said pressure vessel maintains said payload bay pressure constant in said housed configuration.

Additionally or alternatively, for example, said pressure vessel operates to maintain said payload bay pressure at below a threshold value, in said housed configuration. For example, said threshold value is a gauge pressure of 1 bar or less. For example, said threshold value is a gauge pressure of 1 bar or less, while an outside ambient pressure is under a gauge pressure of more than 5bar.

Additionally or alternatively, for example, said payload bay is in said housed configuration concurrent with said mast arm being in said retracted configuration.

Additionally or alternatively, for example, said payload bay is in said exposed configuration at least concurrent with said mast arm being in said extended configuration.

Additionally or alternatively, for example, said payload housing is fixedly mounted to said mast mounting portion and is pivotably movable with said mast mounting portion about said pivot axis.

Additionally or alternatively, for example, said mast arm comprises a lumen.

Additionally or alternatively, for example, the mast system, further comprises a plurality of cables providing at least one of power transmission and data transmission between said payload bay and an outside of said mast system. For example, the mast system further comprises a cable management system, configured to enabling the cables to remain anchored to the payload bay irrespective of whether said mast arm is in said stowed position or in said deployed position, and irrespective of whether said mast arm is in said retracted configuration or in said extended configuration. For example, said cable management system is comprised in said support base. For example said cables are routed through a center of said mast arm.

Additionally or alternatively, for example, in said deployed position, said longitudinal axis is vertical.

Additionally or alternatively, for example, in said stowed position, said longitudinal axis is horizontal.

Additionally or alternatively, for example, in said retracted configuration and said stowed position, said mast system fits into a predetermined geometrical envelope. For example, in said extended configuration and said deployed position, said payload bay extends from said geometrical envelope by more than 2m. For example said extended configuration and said deployed position, said payload bay extends from said geometrical envelope by at least 3m. For example said geometrical envelope conforms to, or is configured for being mounted within, a hull compartment of an underwater vehicle. For example, said mast system in said extended configuration and said deployed position comprises a center of gravity that is below a centerline of the underwater vehicle.

For example, when installed in the underwater vehicle, the mast system is configured to optimize performance of the underwater vehicle when the mast arm is fully stowed, and for minimizing exposure of the vessel when the mast arm is fully deployed.

According to an aspect of the presently disclose subject matter there is provided a mast system for use with an underwater vehicle, comprising:

a support base defining a base axis;

a mast arm defining a longitudinal axis, and comprising a free longitudinal mast end and a mast mounting portion longitudinally spaced from said mast end;

a mast payload bay provided at said mast end, configured for supporting a payload therein;

the mast arm being mounted to the support base via said mast mounting portion, and the mast arm being selectively deployable with respect to the support base between a retracted configuration, in which said mast end is at a first spacing with respect to said mast mounting portion, and an extended configuration, in which said mast end is at a second spacing with respect to said mast mounting portion, wherein said second spacing is greater than said first spacing,

wherein said payload bay is selectively reversibly retractable into said pressure vessel to enable isolating a payload bay pressure from an ambient pressure outside of said pressure vessel.

For example, the mast system is configured for operating in a marine environment.

For example, when installed in the underwater vehicle, the mast system is configured to optimize performance of the underwater vehicle when the mast arm is fully stowed, and for minimizing exposure of the vessel when the mast arm is fully deployed.

According to an aspect of the presently disclose subject matter there is also provided an underwater vehicle comprising the mast system as defined herein, in particular as defined above. For example, said underwater vehicle is an unmanned underwater vehicle.

According to an aspect of the presently disclose subject matter there is also provided a method for selectively exposing a payload to an atmospheric environment, comprising

(a) providing an underwater vehicle comprising the mast system as defined herein, in particular as defined above;

(b) operating the mast system to deploy the mast arm at least to the extended configuration while a remainder of the mast system is submerged.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, examples will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 illustrates in isometric view a first example of the mast system, in which the mast arm is in the retracted configuration and in the stowed position.

Fig. 2 illustrates in side view the first example of the mast system, in which the mast arm is in the retracted configuration and in the stowed position.

Fig. 3 illustrates in side view the first example of the mast system, in which the mast arm is in the retracted configuration and in the deployed position.

Fig. 4 illustrates in side view the first example of the mast system, in which the mast arm is in the extended configuration and in the deployed position.

Fig. 5(a) and **Fig. 5(b)** illustrate, in top view and side view respectively, the first example of the mast system accommodated within a hull compartment, in which the mast arm is in the retracted configuration and in the stowed position within the hull compartment.

Fig. 7 illustrates in cutaway isometric cross-sectional view the first example of the mast system accommodated within a hull compartment, in which the mast arm is in the retracted configuration and in the stowed position; **Fig. 7(a)** shows a detail view of part of the example of Fig. 7.

Fig. 8 illustrates in side view an example of an underwater vehicle in which the first example of the mast system is accommodated in a hull compartment therein.

DETAILED DESCRIPTION

Referring to Figs. 1 to 7, a mast system, according to a first example of the presently disclosed subject matter, generally designated **100,** comprises a support base **200,** a support arm **300,** and a payload bay **400.** Herein, the mast system **100** can be interchangeably referred to as a mast assembly.

As will become clearer hereinbelow, in this example, the mast system **100** is configured for selectively retracting and selectively extracting the payload bay with respect to a pressure vessel, such that when retracted therein, the payload bay is pressure-isolated for the outside of the mast system, in particular from the outside of the pressure vessel.

The mast system **100** at least in this example is configured for operating in a marine environment, for example the sea, and at least in this example the mast system **100** is configured for operating at sea depths of more than 50m.

The term "sea" also refers to, and is used herein interchangeably with, other bodies of water, for example ocean, rivers, lakes, reservoirs, etc.

The mast system **100** at least in this example is configured for operating within a predetermined range of air temperatures, and at least in this example this air temperature range is between -20°C to +50°C, though in alternative variations of this example the air temperature range can be different.

The mast system **100** at least in this example is configured for operating within a predetermined range of sea temperatures, and at least in this example this sea

temperature range has an upper limit of +32°C, though in alternative variations of this example the sea temperature range can be different.

Furthermore, at least in this example, the mast system **100** is configured for use with an underwater vehicle. Referring also to Fig. 8, an example of such an underwater vehicle, generally designated **600** (also referred to interchangeably herein as a submersible vehicle, or as a submersible vessel, or as an underwater vessel) is configured for operating when submerged, and can take many different forms. In this example, the underwater vehicle **600** is unmanned and self propelled, comprising a suitable underwater propulsion system **610,** and a suitable underwater maneuvering system in the form of vanes **606, 607.** The underwater vehicle **600** comprises a pressure hull **602,** in this example torpedo-shaped including a nose section **601,** a tail section **605,** and an intermediate section **630.** The intermediate section **630** of the hull **602** includes a hull compartment **603,** configured for accommodating therein the mast system **100.** The underwater vehicle **600** further comprises hull doors **609** on the upper side of the pressure hull **602.** The hull doors **609** are configured for selectively opening, at least when the underwater vehicle **600** is submerged, exposing the hull compartment **603,** and thus exposing the mast system **100,** to the surrounding marine environment **ME**. Referring to Fig. 1, a powered hull door drive mechanism **620** is provided for selectively opening and for selectively closing the hull doors **609.**

Referring again to Figs. 1 to 3 in particular, the support base **200** is configured for mounting and securing the system **100** to the underwater vehicle **600,** in particular the hull compartment **603,** and comprises support brackets **220** that affix the mast system **100** to the hull compartment **603.** For convenience, a base axis **BA** can be defined for the support base **200,** the base axis **BA** passing near to the geometric center of the support brackets **220,** and being parallel to the centerline **CL** (see Fig. 8) of the underwater vehicle **600.**

Referring again to Figs. 1 to 4 in particular, the mast arm **300** is elongate, defining a longitudinal axis **LA**, and comprises a free longitudinal mast end **310** and a mast mounting portion **320.**

The mast arm **300** is mounted to the support base **200** via the mast mounting portion **320,** and the mast arm **300** is selectively deployable (in particular at least extendible) with respect to the support base **200** between a retracted configuration (see Figs 1, 2 and 3), and an extended configuration (see Fig. 4). The mounting portion **320** is longitudinally spaced from the mast end **310,** and this spacing varies according to the

configuration of the mast arm **300,** i.e., between the retracted configuration and the extended configuration.

As best seen in Fig. 4, the mast payload bay **400** is provided at the mast end **310.** The mast payload bay **400** is configured for supporting and/or accommodating a payload (not shown) therein, and thus comprises one or more payload chambers and is optionally in communication with an auxiliary payload bay **450,** best seen in Fig. 7. As will become clearer herein, and referring to Fig. 4, the payload bay **400** (as well as the auxiliary payload bay **450**) is configured to carry therein any desired payload, for example in the form of devices and/or materials and/or systems, that can be fitted within the payload bay **400** (and/or in the auxiliary payload bay **450**) and that it is desired to expose to the atmosphere **AT** at least while the underwater vehicle **600** is submerged in the marine environment **ME,** albeit in this example submerged in the marine environment **ME** only a few meters below the water surface **WA**. For example, one such auxiliary payload bay **450** is in fluid communication with the payload bay **400.** In this example, the auxiliary payload bay **450** is hemispherically shaped, and capped by a hemispherical shell **455.**

In this example, the payload bay **400** is pivotable about the longitudinal axis **LA,** at least when the mast arm **300** is in the deployed position and in the extended configuration. This confers a panning capability to the payload bay **400** in azimuth. Referring to Figs. 4 and 6, such pivoting can comprise, for example, a clockwise rotation **CW** and/or a counterclockwise rotation **CCW,** with respect to an angular datum **DAT,** through a maximum permitted angular range. For example, such an angular range can be ±175° with respect to angular datum **DAT**. For example, angular datum **DAT** can be parallel to the centerline **CL** of the underwater vehicle **600** or to the base axis **BA**. Referring to Fig. 7, a mast arm drive unit **560,** for example in the form of a panning mechanism, is provided to selectively drive pivoting of the payload bay **400** about the longitudinal axis **LA**. In this example, the mast arm drive unit **560** is configured for pivoting the payload bay **400** about the longitudinal axis **LA** at a desired angular speed, for example **4**rpm. In this example, the mast arm drive unit **560** is also configured for providing rotational position feedback regarding the angular position of the payload bay **400** about the longitudinal axis **LA** with respect to the angular datum **DAT**. For example, such rotational position feedback can have an accuracy of at least 0.1°.

In alternative variations of this example, the payload bay **400** is additionally or alternatively pivotable about a tilt axis orthogonal to the longitudinal axis **LA**, at least when the mast arm **300** is in the deployed position and in the extended configuration, conferring a full or partial tilt capability to the payload bay **400** in elevation.

Referring to Fig. 3, in the retracted configuration, the mast end is at a first spacing **S1** with respect to the mast mounting portion **320.** Referring to Fig. 4, in the extended configuration, the mast end **310** is at a second spacing **S2** with respect to the mast mounting portion **320.** Clearly, the second spacing **S2** is greater than the first spacing **S1.**

As best seen in Figs. 4 and 7, the mast arm **300** comprises a plurality of longitudinally movable nested telescopic sections **350,** provided between the mast end **310** and the mast mounting portion **320.** The telescopic sections **350** are, in this example, generally tubular with circular transverse cross-section, although in alternative variations of this example the respective telescopic elements can have other cross-sections, for example rectangular, in which free relative rotation between the telescopic elements about the longitudinal axis **LA** is naturally prevented.

Thus, the mast arm **300** comprises a lumen **380,** running through the center of the telescopic sections **350.**

Referring in particular to Fig. 1, in this example the mast arm **300** is pivotably mounted to the support base **200** about a pivot axis **PA** via the mast mounting portion **320.** In particular, the mast mounting portion **320** is pivotably mounted to the support brackets **220** with respect to the pivot axis **PA,** via bearing arrangement **230.** The pivot axis **PA** is orthogonal to the longitudinal axis **LA.** The mast arm **300** is pivotably movable with respect to the support base **200** about the pivot axis **PA** within an angular range. In this example, the angular range is 90°, allows the arm **300** to be selectively pivoted about the pivot axis **PA** between a stowed position, illustrated in Figs. 1 and 2, and a deployed position, illustrated in Figs. 3 and 4. A first angular stop **242** is provided on the support base **200** to define the angular position of the arm **300** in the stowed position, and a second angular stop **244** is provided on the support base **200** to define the angular position of the arm **300** in the deployed position.

In alternative variations of this example and in other examples, the mast arm is fixedly mounted to the support base with the longitudinal axis **LA** in a vertical

orientation, and thus the respective mast arm is deployed and stowed only by extending and retracting, respectively, the mast arm.

In this example, and referring to Figs. 1 and 2, in the stowed position, the longitudinal axis **LA** is parallel to the base axis **BA**, while referring to Figs. 3 and 4, in the deployed position longitudinal axis **LA** is orthogonal to the base axis **BA**. Furthermore, in this example, the pivot axis **PA** is orthogonal to the base axis. **BA**, and pivot axis **PA** is also orthogonal to the longitudinal axis **LA**.

Furthermore, in operation of the mast system **100,** particularly when installed in the underwater vehicle **600,** the longitudinal axis **LA** is vertical when the mast arm **300** is in the deployed position, and the longitudinal axis **LA** is horizontal when the mast arm **300** is in the stowed position.

In this example, the mast system **100** can also accommodate a plurality of cables, for example electrical cables and/or fiber optic cables, for providing power transmission and/or data transmission between payload bay **400** and an outside of the mast system **100,** for example the underwater vehicle **600.** For example, such cables can routed through a center of mast arm **300.**

Thus, optionally, the mast system **100** can be provided with a cable management system (not shown), configured for enabling such cables to remain anchored to the payload bay **400** irrespective of whether said mast arm **300** is in the stowed position or in the deployed position, and irrespective of whether the mast arm **300** is in said retracted configuration or in the extended configuration. For example, such a cable management system can be comprised in the support base **200.**

The mast system **100** comprises first drive unit **510** for selectively extending and retracting the mast arm **300,** and a second drive system **530** for selectively stowing and deploying the mast arm **300.**

Referring in particular to Fig. 7, the first drive unit **510** is configured for selectively extending the mast arm **300** to the extended configuration, and for selectively retracting the mast arm to the retracted configuration. Thus, the drive unit **510** operates to selectively drive the mast end **310** longitudinally away from the mast mounting **320** to provide said extended configuration, and to selectively drive the mast end **310** longitudinally towards the mast mounting portion **320** to provide the retracted configuration.

In this example, the first drive unit **510** comprises a chain **512** (which in alternative variations of this example, can be replaced with a cable or the like) which passes around a pulley sprocket **514** that is driven by a motor **516,** such as an electric motor for example. The chain **512** is fixedly connected to the outermost telescopic section **350A** closest to the mast end **310,** and in this example the chain **512** is in the form of an endless loop. In operation of the first drive unit **510** to selectively extend the mast arm **300** to the extended configuration, the motor **516** turns the pulley sprocket **514** in one direction, and the chain **512** is moved to urge the outermost telescopic section **350A** outwards, away from the mast mounting portion **320.** Conversely, operation of the first drive unit **510** to selectively retract the mast arm **300** to the retracted configuration, the motor **516** turns the pulley sprocket **514** in the opposite direction, and the chain **512** is moved to urge the outermost telescopic section **350A** inwards, towards the mast mounting portion **320,** so that the telescopic sections are urged to telescope within each other. Referring also to Fig. 2, a drive housing **519** is provided to house at least parts of the drive unit **510,** and in particular comprises an extended housing portion **518** for accommodating changes in length of the chain **512** as the arm is extended between the extended configuration and the retracted configuration.

Referring to Figs. 2 and 3 in particular, the second drive unit **520** is configured for selectively pivoting the mast arm **300** about the pivot axis **PA** from the stowed position to the deployed position, and for selectively pivoting the mast arm **300** about the pivot axis **PA** from the deployed position to the stowed position.

In this example, and referring to Figs. 2 and 3, the second drive unit **520** comprises an extendible configured for providing a linear force as the jack is extended or retracted. The jack **522** includes an inner rod **521** (pivotably mounted to the mast arm **300**) reciprocally mounted to an outer cylinder **523** (pivotably mounted to the support base **200**). The inner rod **521** can be extended or retracted with respect to the outer cylinder in many different ways, for example electrically or hydraulically, and optionally can employ a screw thread.

While in this example the first drive unit **510** and the second drive unit **520** can each be operated independently of one another, in practice operation of the two drive units can be, and is, linked. In alternative variations of this example, the two drive units are incorporated into a single drive unit which operates in a manner corresponding to such operational linkage.

In any case, for example, such operational linkage can be useful in avoiding potentially damaging the mast system **100.** For example, such linking includes not permitting the first drive unit **510** to extend the mast arm **300** from the retracted configuration when the mast arm **300** is in the stowed position, and not permitting the second drive unit **520** to pivot the mast arm **300** to the stowed position when the mast arm **300** is in the extended configuration.

Thus, in the stowed position, the mast arm **300** is constrained to be in the retracted configuration, while in the deployed position the mast arm **300** is selectively deployable to the extended configuration, and selectively retractable to the retracted configuration.

For example, such operational linking can be useful in providing full deployment or full stowage of the mast system **100** in a rapid manner. Such a feature can be useful, for example, when it is desired to limit the exposure time of the payload bay **400** above the water surface **WS**, or when an emergency situation requires the mast system **100** to be brought into fill stowage quickly. Such operational linking can include operating the two drive units in rapid succession in order to switch between the full stowage of the mast system **100,** comprising the retracted configuration in the stowed position illustrated in Fig. 1, and the full deployment of the mast system **100,** comprising the extended configuration in the deployed position illustrated in Fig. 4. Thus, for providing full deployment starting with the mast system **100** fully stowed (Fig. 1), the second drive unit **520** is first operated to pivot the mast arm **300** to the deployed position from stowed position, while the mast arm **300** is in the retracted configuration (Fig. 2); once the deployed position is attained, the second drive unit **520** ceases operation, and the first drive unit **510** is automatically operated to extend the mast arm **300** to the extended configuration (Fig. 4).

Conversely, for providing full stowage starting with the mast system **100** fully deployed (Fig. 4), the first drive unit **510** is first operated to retract the mast arm **300** to the retracted configuration (Fig. 3); once the retracted configuration is attained, the first drive unit **510** ceases operation, and the second drive unit **520** is then automatically operated to pivot the mast arm **300** to the stowed position from deployed position, while the mast arm **300** is in the retracted configuration (Fig. 2).

Another safety feature can include linking operation of the two drive units to operation of the hull doors **609,** in particular the powered hull door drive mechanism **620.** For example sensors can be provided that sense whether the hull doors **609** are fully open

or fully closed. These sensors can be operatively linked to the first drive unit **510** and the second drive unit **520** (for example via a control computer in the vehicle **600** or comprised in the mast system **100**), and operation of the two drive units to provide full deployment is not permitted when the sensors indicate that the hull doors **609** are not fully open. Similarly, powered operation of the hull doors (to selectively open or to selectively close the hull doors **609**) via the powered hull door drive mechanism **620** can also be linked to operation of the mast system **100,** and thus the hull doors can be prevented from closing when the mast system **100** is not fully stowed.

In this example, the mast system **100** is configured for providing feedback regarding whether the mast arm **300** is in the retracted configuration or in the extended configuration. For example, suitable sensors can be provided that provide sensor outputs that indicate whether the mast arm **300** is fully extended in the extended configuration or fully retracted in the retracted configuration. Such sensors can be operatively connected to one or both of the drive units **510, 520,** and/or to the operating mechanism of the hull doors **609,** for example, directly or via a control computer in the vehicle **600** or comprised in the mast system **100.**

In this example, the mast system **100** is also configured for providing feedback regarding whether the mast arm is in the stowed position or in the deployed position. For example, the first angular stop **242** and the second angular stop **244** can each comprise a respective contact sensor, that senses when the mast arm **300** is in contact therewith, and sensor outputs from these sensors can therefore indicate when the mast arm is in the stowed position or in the deployed position. Such sensors can be operatively connected to one or both of the drive units **510, 520,** and/or to the operating mechanism of the hull doors **609,** for example, directly or via a control computer in the vehicle **600** or comprised in the mast system **100.**

As mentioned above, in this example, and referring to Figs. 1 to 4, the mast system **100** is configured for selectively retracting and selectively extracting the payload bay **400** with respect to a pressure vessel **490,** such that when retracted therein, the payload bay **400** is pressure-isolated for the outside of the mast system, in particular from the environment outside of the pressure vessel **490.**

Thus, the mast system **100** comprises a pressurisable pressure vessel **490.** The pressure vessel **490** comprises a selectively closable and sealable payload housing **480,** wherein payload bay **400** is selectively reversibly retractable with respect to the payload

housing **480.** Thus, the payload bay **400** is selectively retractable into the payload housing **480** to provide a housed configuration, and the payload bay **400** is selectively extractable from the payload housing **480** to provide an exposed configuration. In this example, in the housed configuration, the pressure vessel **490** prevents fluid communication and/or pressure communication between the payload bay **400** and an outside of the mast system **100,** in particular the marine environment.

As best seen in Fig. 4, and Fig. 7, the pressure vessel **490** also comprises a bulkhead arrangement **440,** provided with the payload bay **400.** The payload housing **480** is configured for sealing with respect to this bulkhead arrangement **440** to prevent fluid communication and/or pressure communication between the payload bay **400** and an outside of the mast system **100.** On the other hand, in the exposed configuration the payload housing **480** is configured for being unsealed with respect to the bulkhead arrangement **440,** and to provide fluid communication and/or pressure communication between the payload bay **400** and the outside of the mast system **100.**

In this example, the bulkhead arrangement **440** comprises an outer-facing bulkhead **442** at an outer longitudinal end of the payload bay **400.** The bulkhead **442** is configured for preventing fluid communication between the payload bay **400** and an outside of the mast system **100** in a longitudinal outward direction **D1** through the bulkhead **440.** The bulkhead **442** further comprises a bulkhead sealing perimeter **443** configured for sealing with respect to the payload housing **480** in the housed configuration. In this example, the bulkhead sealing perimeter **443** is in the form of a sealing surface on or near the other edge **449** of the bulkhead **442.**

Referring to Figs. 4, 7 and 7(a) in particular, the payload housing **480** comprises a chamber **485** configured for accommodating therein the payload bay **400** when in the housed configuration. The chamber **485** has a chamber opening **486,** configured to allow the payload bay **400** to be selectively retracted into and to be selectively extracted from the payload housing **480,** and the opening comprises a housing sealing perimeter **488** for sealing with respect to the bulkhead sealing perimeter **443,** in said housed configuration.

In this example, the payload housing **480** is fixedly mounted to the mast mounting portion **320,** while the bulkhead **442** is fixedly mounted to the payload bay **400.** Thus the payload housing **480** is pivotably movable with the mast mounting portion **320** about the pivot axis **PA** as the mast arm **300** is pivoted between the stowed

position and the deployed position. Furthermore, the payload housing **480** remains fixed with the mast mounting portion **320,** whether the mast arm **300** is in the extended configuration or in the retracted configuration. On the other hand the bulkhead **442** is brought into alignment with the payload housing **400** in the retracted configuration, and the bulkhead **442** is longitudinally spaced from the payload housing **400** in the extended configuration.

Thus, the payload bay **400** is in the housed configuration concurrent with the mast arm **300** being in the retracted configuration, and, the payload bay **400** is in the exposed configuration at least concurrent with the mast arm **300** being in the extended configuration.

In this example, the bulkhead **442** is generally disc-shaped, and the payload housing **480** comprises a lateral peripheral wall in the form of tubular wall **481** having a payload housing axis parallel to the longitudinal axis **LA**. The tubular wall **481** defines the chamber opening **486** at one longitudinal end of the tubular wall **481,** and has a closed end **483** at the opposite longitudinal end of the tubular wall **481.**

In this example, and referring in particular to Fig. 7(a), an inflatable seal arrangement **470** is provided, configured for selectively sealing and for selectively unsealing the bulkhead **442** with respect to the payload housing **480** when aligned therewith in the retracted configuration. The inflatable seal arrangement **470** comprises a selectively inflatable and deflatable annular seal body **472,** accommodated in and fixed to an annular recess **473** provided near the opening **486.** The seal body **472** comprises a seal lumen **477,** in fluid communication with a hydraulic system **499** that is configured for selectively providing a desired hydraulic pressure to the seal lumen sufficient for inflating the seal body **472,** and for selectively relieving hydraulic pressure at the seal lumen sufficient for deflating the seal body **472.**

The seal body **472** has an outer facing seal face **475** that provides the housing sealing perimeter **488.** When the seal body **472** is in the inflated state, the seal face **475** is configured to press against the bulkhead sealing perimeter **443,** thereby sealing the chamber **485** from the outside of the mast system **100,** in particular from the outside of the pressure vessel **490.**

Sealing of the pressure vessel **490** occurs at the retracted configuration, and is carried out as follows. With the mast arm **300** in the retracted configuration, the bulkhead **442** is aligned with the payload housing **480** so that the payload bay is in the

housed configuration. At this point, the seal face **475** is also aligned with the bulkhead sealing perimeter **443,** but a small gap **G** is provided therebetween to facilitate this alignment. When aligned, the hydraulic system **499** provides hydraulic pressure to the seal lumen **477,** inflating the seal body **472,** and causing the seal face **475** to press against the bulkhead sealing perimeter **443** and thus close the gap **G**, thereby sealing the chamber **485** from the outside of the mast system **100,** in particular from the outside of the pressure vessel **490.** Hydraulic pressure can be maintained via valve **498.** For unsealing the pressure vessel **490,** a reverse procedure is applied: the hydraulic system **499** relieves hydraulic pressure of the seal lumen **477,** deflating the seal body **472,** and causing the seal face **475** come away from the bulkhead sealing perimeter **443,** thereby reopening the gap **G** and unsealing the chamber **485.**

The pressure vessel **490,** when in the housed configuration and sealed, provides a payload bay pressure to the payload bay **400** that is isolated from an outside of the mast system. Essentially, the payload housing **480,** when closed with the bulkhead **442,** operates as a pressurized vessel with respect to the payload bay **400** for isolating the payload bay pressure from an outside of the mast system **100,** in the housed configuration.

By isolating the payload bay pressure from the ambient pressure of an outside of the mast system **100,** it is possible to provide and maintain the payload bay pressure at below a threshold value, even where the ambient pressure outside of the pressure vessel **490** is much greater and/or is variable. For example, such a threshold value can be a gauge pressure of 1 bar or less, even while the outside of mast system **100,** in particular of the pressure vessel **490,** is subject to a gauge pressure of for example 5bar or more.

By isolating the payload bay pressure from the outside ambient pressure, in particular the outside marine ambient pressure, it is possible to protect the payload that is accommodated within the payload bay **400** from adverse effects of high pressure applied by the outside marine environment **ME**. It is therefore only necessary to ensure that the payload is capable of withstanding the relatively modest pressure defined by the above mentioned threshold value. This feature of payload bay pressure isolation can be of particular use where the payload only requires to be exposed to the atmospheric environment **AT** in the exposed configuration of the payload bay **400,** and where there is no need to expose the payload to marine conditions consistent with a pressure greater than the threshold value. This is particular more so the case where the payload would be

damaged if exposed to pressures greater than the threshold value, and would otherwise require each item of the payload to be protected against exposure to such marine conditions.

Referring again to Fig. 8, when the mast system **100** is fully stowed, i.e., with the mast arm **300** in the retracted configuration and in the stowed position, the mast system **100** fits into a predetermined geometrical envelope **GE**. This geometrical envelope **GE** is such as to enable the mast system **100** to be fitted within the hull compartment **603** of the underwater vessel **600,** without affecting the drag characteristics of the underwater vehicle **600.** For example, the geometrical envelope **GE** conforms to, or is configured for being mounted within, the hull compartment **609** of an underwater vehicle **600.**

Thus, for example, when installed in the underwater vehicle **600**, the mast system **100** is configured to optimize performance of the underwater vehicle when the mast arm is fully stowed, and for minimizing exposure of the vessel when the mast arm is fully deployed.

When the mast system **100** is fully deployed, with the mast arm **300** in the extended configuration and in the deployed position, the payload bay **400** extends from the geometrical envelope **GE** by for example more than 2m, for example at least up to 3m or more.

For example the mast system **300** is configured such the mast system **100** is fully deployed, with the mast arm **300** in the extended configuration and in the deployed position, the mast system **100** comprises a center of gravity that is below the centerline **CL** of the underwater vehicle **600.**

The mast system **100** can be used as follows, for example, for exposing a payload (carried by the payload bay **400** and/or the auxiliary payload bay **450**) to atmospheric environment while a majority of the remainder of the mast system **100** remains submerged together with the underwater vehicle **600.**

First the underwater vehicle **100** transports the desired payload, accommodated in the payload bay **400** and/or the auxiliary payload bay **450,** to a desired location. At least a part of this transportation can occur with the underwater vehicle **600** submerged, at any desired depth, for example more than 50m, which can minimize risk of detection of the underwater vessel **600,** for example.

It is to be noted that in order to isolate the payload bay pressure from the marine environment pressure, particularly at such depths, and to maintain constant the payload bay pressure, a pressurization procedure is first conducted for the payload bay, typically at the start of a mission, or at least well before it is intended to submerge the vehicle **600** at pressure greater than the threshold value.

In the pressurization procedure, the pressure vessel **490** is unsealed, with the mast arm **300** in the deployed position and at least partially extended from the retracted configuration, such that the payload housing is at a water depth providing a water pressure corresponding to the threshold value or less. Under these conditions the payload housing is filled with water at this pressure, and the mast arm is then returned to the retracted configuration and stowed position, in which the payload bay **400** is in the housed configuration within the payload housing **480** and the opening **486** is closed by the bulkhead **442.** Then the pressure vessel **490** is sealed by the inflatable seal system **470,** trapping therein water at a water pressure corresponding to the threshold value or less. In this manner, the payload in the payload bay is exposed to this pressure within the pressure vessel **490.** Thereafter, until the pressure vessel is unsealed, the pressure within the pressure vessel **490** remains constant, irrespective of the depth of the underwater vehicle **600,** at least for a range of depths over 50m.

When the underwater vessel **600** is at the required location for the aforementioned atmospheric exposure of the payload, the underwater vehicle **600** attains a water depth corresponding at least to the pressure in the pressure vessel, i.e., at or less than the threshold value. For example such a depth can be about 2m. The hull doors **609** are opened, and the mast arm **300** is pivoted to the deployed position, and this is followed by unsealing of the pressure vessel **490** and extension of the mast arm to the extended configuration of Fig. 4. For example, for an axial length of the mast arm **300** including the payload bay **400** and cap **455** of about 3m or 4m, for example, the top 1m or 2m thereof including the payload bay **400** and dome **455** are above the water surface **WS**. At this point, the payload in the payload bay **400** is exposed to the atmospheric environment.

When it is desired to terminate such exposure, the reverse procedure is implemented, whereupon the mast arm **300** is retracted to the retracted configuration under the water surface at this depth, and the payload bay **400** sealed within the pressure vessel **490** at a pressure corresponding to this depth. The mast arm **300** is then pivoted

to the stowed configuration and the hull doors closed. The underwater vehicle can then travel to a different location.

In the method claims that follow, alphanumeric characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any particular order of performing the steps.

Finally, it should be noted that the word "comprising" as used throughout the appended claims is to be interpreted to mean "including but not limited to".

CLAIMS

1. A mast system (100, 300) for use with an underwater vehicle (100, 600), comprising: a support base (200) defining a base axis; a mast arm (25, 300, 30) defining a longitudinal axis, and comprising a free longitudinal mast end (310) and a mast mounting portion (320) longitudinally spaced from said mast end (310); a mast payload bay (400) provided at said mast end (310), configured for supporting a payload therein; a pressure vessel (490), wherein said payload bay (400) is selectively reversibly retractable into said pressure vessel (490) to enable isolating a payload bay (400) pressure from an ambient pressure outside of said pressure vessel (490); said pressure vessel (490) comprising a payload housing (400, 480) fixedly mounted to said mast mounting portion (320); the mast arm (25, 300, 30) being mounted to the support base (200) via said mast mounting portion (320), and the mast arm (25, 300, 30) being selectively deployable with respect to the support base (200) at least between a retracted (10) configuration, in which said mast end (310) is at a first spacing (S2) with respect to said mast mounting portion (320), and an extended configuration, in which said mast end (310) is at a second spacing (S2) with respect to said mast mounting portion (320), wherein said second spacing (S2) is greater than said first spacing (S2), wherein the mast system (100, 300) is configured for operating in a marine environment (30); and wherein said mast arm (25, 300, 30) is pivotably mounted to said support base (200) about a pivot axis via said mast mounting portion (320), said pivot axis being orthogonal to said longitudinal axis.

2. The mast system (100, 300) according to claim 1, wherein said mast arm (25, 300, 30) comprises a plurality of longitudinally movable nested telescopic sections (350) between said mast end (310) and said mast mounting portion (320).

3. The mast system (100, 300) according to claim 2, wherein said mast arm (25, 300, 30) is reversibly pivotably movable with respect to said support base (200) about said pivot axis between a stowed (20) position and a deployed position.

4. The mast system (100, 300) according to claim 3, comprising a first drive unit (510, 520) for selectively driving said mast end (310) longitudinally away from said mast mounting (30, 320) to provide said extended configuration, and for selectively driving said mast end (310) longitudinally towards said mast mounting (30, 320) to provide said retracted (10) configuration, and comprising a second drive unit (510, 520) for selectively pivoting said mast arm (25, 300, 30) about said pivot axis from said stowed (20) position to said deployed position, and for selectively pivoting said mast arm (25, 300, 30) about said pivot axis from said deployed position to said stowed (20) position.

5. The mast system (100, 300) according to any one of claims 3 to claim 4, including at least one of the following: - wherein in said stowed (20) position, said mast arm (25, 300, 30) is in said retracted (10) configuration, and wherein in said deployed position said mast arm (25, 300, 30) is selectively deployable to said extended configuration; - wherein in said stowed (20) position, said longitudinal axis is parallel to said base axis, and wherein in said deployed position said longitudinal axis is orthogonal to said base axis; - wherein said pivot axis is orthogonal to said base axis.

6. The mast system (100, 300) according to any one of claims 1 to 5, wherein said payload bay (400) is pivotable about said longitudinal axis, at least in said extended configuration.

7. The mast system (100, 300) according to any one of claims 1 to 5, wherein said payload housing (400, 480) is closeable, and wherein said payload bay (400) is selectively reversibly retractable into said payload housing (400, 480) between a housed configuration and an exposed configuration, and wherein in said housed configuration, fluid communication is prevented between said payload bay (400) and an outside of said mast system (100, 300).

8. The mast system (100, 300) according to claim 7, wherein said pressure vessel (490) comprises a bulkhead (440, 442) arrangement, wherein in said housed configuration said payload housing (400, 480) is configured for sealing with respect to said bulkhead (440, 442) arrangement to prevent fluid communication between said payload bay (400) and an outside of said mast system (100, 300), and wherein in said exposed configuration said payload housing (400, 480) is configured for being

unsealed with respect to said bulkhead (440, 442) arrangement and to provide fluid communication between said payload bay (400) and an outside of said mast system (100, 300).

9. The mast system (100, 300) according to claim 8, wherein said bulkhead (440, 442) arrangement is fixed to the payload bay (400).

10. The mast system (100, 300) according to any one of claims 7 to 9, wherein said bulkhead (440, 442) arrangement comprises an outer facing bulkhead (442) at an outer longitudinal end of said payload bay (400), said bulkhead (440, 442) configured for preventing fluid communication between said payload bay (400) and an outside of said mast system (100, 300) in a longitudinal outward direction through said bulkhead (440, 442), said bulkhead (440, 442) further comprising a bulkhead sealing perimeter (443) configured for sealing with respect to said payload housing (400, 480) in said housed configuration.

11. The mast system (100, 300) according to claim 10, including at least one of the following: - further comprising an auxiliary payload bay (450) projects outwardly from said bulkhead (440, 442), said auxiliary payload bay (450) being in communication with said payload bay (400); - wherein said payload housing (400, 480) comprises a chamber (485) configured for accommodating therein said payload bay (400) in said housed configuration, said chamber (485) having a chamber opening (486) configured to allow said payload bay (400) to be selectively and reversibly retracted (10) with respect to said payload housing (400, 480), said opening (486) comprising a housing sealing perimeter (488) for reversibly sealing with respect to said bulkhead sealing perimeter (443) in said housed configuration; - wherein said payload housing (400, 480) comprises a chamber (485) configured for accommodating therein said payload bay (400) in said housed configuration, said chamber (485) having a chamber opening (486) configured to allow said payload bay (400) to be selectively and reversibly retracted (10) with respect to said payload housing (400, 480), said opening (486) comprising a housing sealing perimeter (488)

for reversibly sealing with respect to said bulkhead sealing perimeter (443) in said housed configuration, and, wherein said bulkhead (440, 442) is disc-shaped and wherein said payload housing (400, 480) comprises a lateral peripheral wall having a payload housing (400, 480) axis parallel to said longitudinal axis, and defining said chamber opening (486) and a closed end (483) at respective opposite longitudinal ends of said lateral peripheral wall; - wherein said payload housing (400, 480) comprises a chamber (485) configured for accommodating therein said payload bay (400) in said housed configuration, said chamber (485) having a chamber opening (486) configured to allow said payload bay (400) to be selectively and reversibly retracted (10) with respect to said payload housing (400, 480), said opening (486) comprising a housing sealing perimeter (488) for reversibly sealing with respect to said bulkhead sealing perimeter (443) in said housed configuration, and, wherein said bulkhead (440, 442) is disc-shaped and wherein said payload housing (400, 480) comprises a lateral peripheral wall having a payload housing (400, 480) axis parallel to said longitudinal axis, and defining said chamber opening (486) and a closed end (483) at respective opposite longitudinal ends of said lateral peripheral wall, and, wherein said lateral peripheral wall is a tubular wall (481); - comprising an inflatable seal arrangement for selectively sealing and for selectively unsealing said bulkhead (440, 442) with respect to said payload housing (400, 480).

12. The mast system (100, 300) according to any one of claims 7 to 11, including at least one of the following: - wherein said pressure vessel (490) is configured for enabling the payload bay (400) to have a said payload bay (400) pressure isolated from an outside of said mast system (100, 300), in said housed configuration; - wherein said pressure vessel (490) maintains said payload bay (400) pressure constant in said housed configuration; - wherein said pressure vessel (490) operates to maintain said payload bay (400) pressure at below a threshold value, in said housed configuration; - wherein said pressure vessel (490) operates to maintain said payload bay (400) pressure at below a threshold value, in said housed configuration, and, wherein said threshold value is a gauge pressure of 1 bar or less; - wherein said pressure vessel (490) operates to maintain said payload bay (400) pressure at below a threshold value, in said housed configuration, and, wherein said threshold value is a gauge pressure of 1 bar or less, while an outside ambient pressure is under a gauge pressure of more than 5bar;

wherein said payload bay (400) is in said housed configuration concurrent with said mast arm (25, 300, 30) being in said retracted (10) configuration; - wherein said payload bay (400) is in said exposed configuration at least concurrent with said mast arm (25, 300, 30) being in said extended configuration; - wherein said payload housing (400, 480) is fixedly mounted to said mast mounting portion (320) and is pivotably movable with said mast mounting portion (320) about said pivot axis.

13. The mast system (100, 300) according to any one of claims 1 to 12, including at least one of the following: - wherein said mast arm (25, 300, 30) comprises a lumen (380); - further comprising a plurality of cables providing at least one of power transmission and data transmission between said payload bay (400) and an outside of said mast system (100, 300); - further comprising a plurality of cables providing

at least one of power transmission and data transmission between said payload bay (400) and an outside of said mast system (100, 300), and, further comprising a cable management system (100), configured to enabling the cables to remain anchored to the payload bay (400) irrespective of whether said mast arm (25, 300, 30) is in said stowed (20) position or in said deployed position, and irrespective of whether said mast arm (25, 300, 30) is in said retracted (10) configuration or in said extended configuration; - further comprising a plurality of cables providing at least one of power transmission and data transmission between said payload bay (400) and an outside of said mast system (100, 300), and, further comprising a cable management system (100), configured to enabling the cables to remain anchored to the payload bay (400) irrespective of whether said mast arm (25, 300, 30) is in said stowed (20) position or in said deployed position, and irrespective of whether said mast arm (25, 300, 30) is in said retracted (10) configuration or in said extended configuration, and, wherein said cable management system (100) is comprised in said support base (200); - further comprising a plurality of cables providing at least one of power transmission and data transmission between said payload bay (400) and an outside of

said mast system (100, 300), and, wherein said cables are routed through a center of said mast arm (25, 300, 30); - wherein in said deployed position, said longitudinal axis is vertical; - wherein in said stowed (20) position, said longitudinal axis is horizontal; - wherein in said retracted (10) configuration and said stowed (20) position, said mast system (100, 300) fits into a predetermined geometrical envelope; - wherein in said retracted (10) configuration and said stowed (20) position, said mast system (100, 300) fits into a predetermined geometrical envelope, and, wherein in said extended configuration and said deployed position, said payload bay (400) extends from said geometrical envelope by more than 2m or by at least 3m; - wherein in said retracted (10) configuration and said stowed (20) position, said mast system (100, 300) fits into a predetermined geometrical envelope, and, wherein said geometrical envelope conforms to, or is configured for being mounted within, a hull compartment (603, 609) of an underwater vehicle (100, 600); - wherein in said retracted (10) configuration and said stowed (20) position, said mast system (100, 300) fits into a predetermined geometrical envelope, and, wherein said geometrical envelope conforms to, or is configured for being mounted within, a hull compartment (603, 609) of an underwater vehicle (100, 600), and, wherein said mast system (100, 300) in said extended configuration and said deployed position comprises a center of gravity that is below a centerline of the underwater vehicle (100, 600).

14. An underwater vehicle (100, 600) comprising the mast system (100, 300) as defined in any one of claims 1 to 13, and wherein optionally said vehicle (600) is an unmanned underwater vehicle (100, 600).

15. A method for selectively exposing a payload to an atmospheric environment (30), comprising: (a) providing a mast system (100, 300) as defined in any one of claims 1 to 13; (b) operating the mast system (100, 300) to deploy the mast arm (25, 300, 30) at least to the extended configuration while a remainder of the mast system (100, 300) is submerged.