



- (51) International Patent Classification:
F16H 55/30 (2006.01)
- (21) International Application Number:
PCT/US2012/063610
- (22) International Filing Date:
5 November 2012 (05.11.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/555,350 3 November 2011 (03.11.2011) US
- (71) Applicant (for all designated States except US): **BARDEX CORPORATION** [US/US]; 6338 Lindmar Drive, Goleta, CA 93116 (US).
- (72) Inventors; and
- (71) Applicants (for US only): **MILLER, Thomas** [US/US]; 6338 Lindmar Drive, P.O. Box 1068, Goleta, CA 93116 (US). **GILPIN, James** [US/US]; 6338 Lindmar Drive, P.O. Box 1068, Goleta, CA 93116 (US).
- (74) Agents: **McCOY, Michael, S.** et al.; Fulbright & Jaworski L.L.P., Fulbright Tower, 1301 McKinney, Suite 5100, Houston, TX 77010-3095 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR MANIPULATING CHAIN SEGMENTS




FIG. 2

(57) Abstract: A chain wheel designed to haul in, pay out and/or guide a mooring chain that includes multiple chain sizes. In one configuration, the chain wheel is a dual chain wheel that includes pockets sized to support a larger chain size and pockets sized to support a smaller chain size. The pockets include flat surfaces that support links of the chain as it passes over the chain wheel. The chain wheel also includes whelps designed to support and guide chain segments into proper alignment with the chain wheel.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG). (88) Date of publication of the international search report:
17 July 2014

Published:

— with international search report (Art. 21(3))