

encrypted data by re-encrypting the ciphertext received from the first user device without decryption by the re-encryption key in the storage means; and

5 a means (43) that transmits the obtained re-encrypted data to the second user device, wherein

the re-encryption key is generated based on a first private key corresponding to the public key for encryption, public information for generating a re-encryption key corresponding to the second private key, and a first random
10 number generated by the re-encryption key generator.

~~20. The re-encryption device according to claim 19, wherein~~

~~the re-encryption key is generated independently of the ciphertext data before re-encryption.~~

15 2021. A program executed by a processor of a re-encryption key generator (30) that generates a re-encryption key to obtain re-encrypted data that can be decrypted by a second private key of a second user device after ciphertext data obtained by encrypting plaintext data
20 by a public key for encryption of a first user device is re-encrypted without decryption and stored in a non-transitory computer-readable storage medium (M3), the program comprising:

a first program code causing the processor to perform
25 processing to write a first private key corresponding to the public key for encryption into a first storage means (31) of the re-encryption key generator;

a second program code causing the processor to perform the processing to write public information for generating a
30 re-encryption key corresponding to the second private key into a second storage means (32) of the re-encryption key generator;

a third program code causing the processor to perform processing (36) to generate a first random number; and

a fourth program code causing the processor to perform processing (34) to generate the re-encryption key based on
5 the first private key, the public information for generating a re-encryption key, and the first random number.

~~22. The program according to claim 21, wherein
the processor is caused to perform the processing to
10 generate the re-encryption key independently of the
ciphertext data before re-encryption.~~

~~21~~²³. A program executed by a processor of a re-encryption device (40) capable of communicating with a re-encryption key generator (30) that generates a re-encryption key to obtain re-encrypted data that can be
15 decrypted by a second private key of a second user device after ciphertext data obtained by encrypting plaintext data by a public key for encryption of a first user device is re-encrypted without decryption and stored in a non-
20 transitory computer-readable storage medium, the program comprising:

a first program code causing the processor to perform processing to write the re-encryption key received from the re-encryption key generator into a storage means (41) of
25 the re-encryption device;

a second program code causing the processor to perform processing (44) to obtain the re-encrypted data by re-encrypting the ciphertext data received from the first user device by the re-encryption key in the storage means
30 without decryption; and

a third program code causing the processor to perform processing (43) to transmit the obtained re-encrypted data to the second user device, wherein

the re-encryption key is generated based on a first private key corresponding to the public key for encryption, public information for generating a second re-encryption key corresponding to the second private key, and a first
5 random number generated by the re-encryption key generator.

| 2224. A program executed by a processor of an encryption device (20) capable of communicating with a re-encryption device (40) that uses a re-encryption key to obtain re-encrypted data that can be decrypted by a second
10 private key of a second user device after ciphertext data obtained by encrypting plaintext data by a public key for encryption of a first user device is re-encrypted without decryption and stored in a non-transitory computer-readable storage medium (M2), the program comprising:

15 a first program code causing the processor to perform processing (22) to write the public key for encryption into a storage means (21) of the encryption device;

 a second program code causing the processor to perform processing (24) to obtain the ciphertext data by encrypting
20 the plaintext data using the public key for encryption in the storage means; and

 a third program code causing the processor to perform processing (22) to transmit the obtained ciphertext data to the re-encryption device, wherein

25 the re-encryption key is generated based on a first private key corresponding to the public key for encryption, public information for generating a re-encryption key corresponding to the second private key, and a first random number generated by a re-encryption key generator that
30 generates the re-encryption key.

| 2325. A program executed by a processor of a decryption device (50) that decrypts re-encrypted data obtained from the re-encryption device after obtaining the

re-encrypted data that can be decrypted by a second private key of a second user device after ciphertext data obtained by encrypting plaintext data by a public key for encryption of a first user device is re-encrypted by a re-encryption
5 device (40) based on a re-encryption key without decryption and stored in a non-transitory computer-readable storage medium (M5), the program comprising:

a first program code causing the processor to perform processing (53) to write the second private key into a
10 storage means (51) of the decryption device; and

a second program code causing the processor to perform processing (54) to obtain the plaintext data by decrypting the re-encrypted data based on the second private key in the storage means after receiving the re-encrypted data
15 from the re-encryption device, wherein

the re-encryption key is generated based on a first private key corresponding to the public key for encryption, public information for generating a re-encryption key corresponding to the second private key, and a first random
20 number generated by a re-encryption key generator that generates the re-encryption key.

~~26. The program according to any one of claims 23 to 25, wherein~~
~~the re encryption key is generated independently of~~
25 ~~the ciphertext data before re encryption.~~