

FUEL COMPOSITIONS

Field of the Invention

This invention relates to additives for use in a fuel for a spark-ignition internal combustion engine. In particular, the invention relates to additives for use in increasing the octane number of a fuel for a spark-ignition internal combustion engine. The invention further relates to fuels for a spark-ignition internal combustion engine comprising the octane-boosting additives.

Background of the Invention

Spark-ignition internal combustion engines are widely used for power, both domestically and in industry. For instance, spark-ignition internal combustion engines are commonly used to power vehicles, such as passenger cars, in the automotive industry.

Combustion in spark-ignition internal combustion engines is initiated by a spark which creates a flame front. The flame front progresses from the spark-plug and travels across the combustion chamber rapidly and smoothly until almost all of the fuel is consumed.

Spark-ignition internal combustion engines are widely thought to be more efficient when operating at higher compression ratios, *i.e.* when a higher degree of compression is placed upon the fuel/air mix in the engine prior to its ignition. Thus, modern, high performance spark-ignition internal combustion engines tend to operate at high compression ratios. Higher compression ratios are also desired when an engine has a high degree of supplemental pressure boosting to the intake charge.

However, increasing the compression ratio in an engine increases the possibility of abnormal combustion including that of auto-ignition, particularly when the engine is pressure-boosted. A form of auto-ignition occurs when the end gas, typically understood to be the unburnt gas between the flame front and combustion chamber walls/piston, ignites spontaneously. On ignition, the end gas burns rapidly and prematurely ahead of the flame front in the combustion chamber, causing the pressure in the cylinder to rise sharply. This creates the characteristic knocking or pinking sound and is known as “knock”, “detonation” or “pinking”. In some cases, particularly with pressure-boosted engines, other forms of auto-ignition can even lead to destructive events known as “mega-knock” or “super-knock”.

Knock occurs because the octane number (also known as the anti-knock rating or the octane rating) of the fuel is below the anti-knock requirement of the engine. Octane number is a standard measure used to assess the point at which knock will occur for a given fuel. A higher octane number means that a fuel/air mixture can withstand more compression before auto-ignition of the end gas occurs. In other words, the higher the octane number, the better the anti-knock properties of a fuel. Whilst the research octane number (RON) or the motor octane number (MON) may be used to assess the anti-knock performance of a fuel, in recent literature more weight is being given to the RON as an indicator of a fuel's anti-knock performance in modern automotive engines.

Accordingly, there is a need for fuels for spark-ignition internal combustion engines which have a high octane number, *e.g.* a high RON. There is a particular need for fuels for high compression ratio engines, including those utilising a high degree of supplemental pressure boosting to the intake charge, to have a high octane number so that higher engine efficiency may be enjoyed in the absence of knock.

In order to increase the octane number, octane improving additives are typically added to a fuel. Such additisation may be carried out by refineries or other suppliers, *e.g.* fuel terminals or bulk fuel blenders, so that the fuel meets applicable fuel specifications when the base fuel octane number is otherwise too low.

Organometallic compounds, comprising *e.g.* iron, lead or manganese are well-known octane improvers, with tetraethyl lead (TEL) having been extensively used as a highly effective octane improver. However, TEL and other organometallic compounds are generally now only used in fuels in small amounts, if at all, as they can be toxic, damaging to the engine and damaging to the environment.

Octane improvers which are not based on metals include oxygenates (*e.g.* ethers and alcohols) and aromatic amines. However, these additives also suffer from various drawbacks. For instance, N-methyl aniline (NMA), an aromatic amine, must be used at a relatively high treat rate (1.5 to 2 % weight additive / weight base fuel) to have a significant effect on the octane number of the fuel. NMA can also be toxic. Oxygenates give a reduction in energy density in the fuel and, as with NMA, have to be added at high treat rates, potentially causing compatibility problems with fuel storage, fuel lines, seals and other engine components.

Effort has been made to find alternative non-metallic octane improvers to NMA.

GB 2 308 849 discloses dihydro benzoxazine derivatives for use as anti-knock agents. However, the derivatives provide a significantly smaller increase in the RON of a fuel than is provided by NMA at similar treat rates.


Accordingly, there remains a need for additives for a fuel for a spark-ignition internal combustion engine that are able to achieve anti-knock effects, e.g. at least comparable anti-knock effects to NMA, while mitigating at least some of the problems highlighted above.

Summary of the Invention

Surprisingly, it has now been found that an additive having a chemical structure comprising a 6-membered aromatic ring sharing two adjacent aromatic carbon atoms with a 6- or 7-membered saturated heterocyclic ring, the 6- or 7-membered saturated heterocyclic ring comprising a nitrogen atom directly bonded to one of the shared carbon atoms to form a secondary amine and an atom selected from oxygen or nitrogen directly bonded to the other shared carbon atom, the remaining atoms in the 6- or 7-membered heterocyclic ring being carbon, provides a substantial increase to the octane number, particularly the RON, of a fuel for a spark-ignition internal combustion engine.

Accordingly, the present disclosure provides a fuel composition for a spark-ignition internal combustion engine, the fuel composition comprising an additive having a chemical structure comprising a 6-membered aromatic ring sharing two adjacent aromatic carbon atoms with a 6- or 7-membered saturated heterocyclic ring, the 6- or 7-membered saturated heterocyclic ring comprising a nitrogen atom directly bonded to one of the shared carbon atoms to form a secondary amine and an atom selected from oxygen or nitrogen directly bonded to the other shared carbon atom, the remaining atoms in the 6- or 7-membered heterocyclic ring being carbon (hereinafter described as an “octane-boosting additive”).

Also provided is a fuel composition for a spark-ignition internal combustion engine, the fuel composition comprising an octane-boosting additive having the formula:



where: R_1 is hydrogen;


R_2 , R_3 , R_4 , R_5 , R_{11} and R_{12} are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

R_6 , R_7 , R_8 and R_9 are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

X is selected from $-O-$ or $-NR_{10}-$, where R_{10} is selected from hydrogen and alkyl groups; and

n is 0 or 1.

In one aspect, the present disclosure provides a fuel composition for a spark-ignition internal combustion engine, the fuel composition comprises an additive having the formula:



where: R_1 is hydrogen;

R_2 , R_3 , R_4 , R_5 , R_{11} and R_{12} are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;


R_6 , R_7 , R_8 and R_9 are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

X is selected from $-O-$ or $-NR_{10}-$, where R_{10} is selected from hydrogen and alkyl groups; and

n is 0 or 1;

wherein at least one of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} is selected from a group other than hydrogen.

In one aspect, the present disclosure provides a fuel composition for a spark-ignition internal combustion engine, the fuel composition comprising an additive of the




In another aspect, the present disclosure provides a process for producing a fuel composition of the present disclosure, the process comprising the step of combining a fuel for a spark-ignition internal combustion engine with an octane-boosting additive described herein.

In another aspect, the present disclosure provides the use of an octane-boosting additive described herein in a fuel for a spark-ignition internal combustion engine. In another aspect, the present disclosure provides the use of an octane-boosting additive described herein for increasing the octane number of a fuel for a spark-ignition internal combustion engine. In a further aspect, the present disclosure provides the use of an additive described herein for improving the auto-ignition characteristics of a fuel, *e.g.* by reducing the propensity of the fuel for at least one of auto-ignition, pre-ignition, knock, mega-knock and super-knock, when used in a spark-ignition internal combustion engine.

In another aspect, the present disclosure provides a method for increasing the octane number of a fuel for a spark-ignition internal combustion engine, said method comprising blending an additive described herein with the fuel. In another aspect, the present disclosure provides a method for improving the auto-ignition characteristics of a fuel, *e.g.* by reducing the propensity of a fuel for at least one of auto-ignition, pre-ignition, knock, mega-knock and super-knock, when used in a spark-ignition internal combustion engine, said method comprising blending an octane-boosting additive described herein with the fuel.

In yet another aspect, there is provided a use of an additive in a fuel for a spark-ignition internal combustion engine or for increasing the octane number of a fuel for a spark-ignition internal combustion engine, wherein the additive is of the formula :

4b



wherein R₁, R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁, R₁₂, X, and n are as defined in any of claims 1 to 11, or the additive is 3,4-dihydro-2H-benzo[b][1,4]oxazine or 2,3,4,5-tetrahydrobenzo[b][1,4]oxazepine.

5

Brief Description of the Figures

Figures 1a-c show graphs of the change in octane number (both RON and MON) of fuels when treated with varying amounts of an octane-boosting additive described herein. Specifically, Figure 1a shows a graph of the change in octane number of an E0 fuel having a RON prior to additisation of 90; Figure 1b shows a graph of the change in octane number of an E0 fuel having a RON prior to additisation of 95; and Figure 1c shows a graph of the change in octane number of an E10 fuel having a RON prior to additisation of 95.

10

Figures 2a-c show graphs comparing the change in octane number (both RON and MON) of fuels when treated with octane-boosting additives described herein and N-methyl aniline. Specifically, Figure 2a shows a graph of the change in octane number of an E0 and an E10 fuel against treat rate; Figure 2b shows a graph of the change in octane number of an E0 fuel at a treat rate of 0.67 % w/w; and Figure 2c shows a graph of the change in octane number of an E10 fuel at a treat rate of 0.67 % w/w.

Detailed Description of the Invention


Octane-boosting additive

The present invention provides a fuel composition for a spark-ignition internal combustion engine, said fuel composition comprising an octane-boosting additive.

The octane-boosting additive has a chemical structure comprising a 6-membered aromatic ring sharing two adjacent aromatic carbon atoms with a 6- or 7-membered otherwise saturated heterocyclic ring, the 6- or 7-membered saturated heterocyclic ring comprising a nitrogen atom directly bonded to one of the shared carbon atoms to form a secondary amine and an atom selected from oxygen or nitrogen directly bonded to the other shared carbon atom, the remaining atoms in the 6- or 7-membered heterocyclic ring being carbon (referred to in short as an octane-boosting additive described herein). As will be appreciated, the 6- or 7- membered heterocyclic ring sharing two adjacent aromatic carbon atoms with the 6-membered aromatic ring may be considered saturated but for those two shared carbon atoms, and may thus be termed “otherwise saturated.”

Alternatively stated, the octane-boosting additive used in the present invention may be a substituted or unsubstituted 3,4-dihydro-2H-benzo[b][1,4]oxazine (also known as benzomorpholine), or a substituted or unsubstituted 2,3,4,5-tetrahydro-1,5-benzoxazepine. In other words, the additive may be 3,4-dihydro-2H-benzo[b][1,4]oxazine or a derivative thereof, or 2,3,4,5-tetrahydro-1,5-benzoxazepine or a derivative thereof. Accordingly, the additive may comprise one or more substituents and is not particularly limited in relation to the number or identity of such substituents.

Preferred additives have the following formula:



where: R_1 is hydrogen;

$R_2, R_3, R_4, R_5, R_{11}$ and R_{12} are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

R_6, R_7, R_8 and R_9 are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

X is selected from $-O-$ or $-NR_{10}-$, where R_{10} is selected from hydrogen and alkyl groups; and

n is 0 or 1.

In some embodiments, $R_2, R_3, R_4, R_5, R_{11}$ and R_{12} are each independently selected from hydrogen and alkyl groups, and preferably from hydrogen, methyl, ethyl, propyl and butyl groups. More preferably, $R_2, R_3, R_4, R_5, R_{11}$ and R_{12} are each independently selected from hydrogen, methyl and ethyl, and even more preferably from hydrogen and methyl.

In some embodiments, R_6, R_7, R_8 and R_9 are each independently selected from hydrogen, alkyl and alkoxy groups, and preferably from hydrogen, methyl, ethyl, propyl, butyl, methoxy, ethoxy and propoxy groups. More preferably, R_6, R_7, R_8 and R_9 are each independently selected from hydrogen, methyl, ethyl and methoxy, and even more preferably from hydrogen, methyl and methoxy.

Advantageously, at least one of $R_2, R_3, R_4, R_5, R_6, R_7, R_8, R_9, R_{11}$ and R_{12} , and preferably at least one of R_6, R_7, R_8 and R_9 , is selected from a group other than hydrogen. More preferably, at least one of R_7 and R_8 is selected from a group other than hydrogen. Alternatively stated, the octane-boosting additive may be substituted in at least one of the positions represented by $R_2, R_3, R_4, R_5, R_6, R_7, R_8, R_9, R_{11}$ and R_{12} , preferably in at least one of the positions represented by R_6, R_7, R_8 and R_9 , and more preferably in at least one of the positions represented by R_7 and R_8 . It is believed that the presence of at least one

group other than hydrogen may improve the solubility of the octane-boosting additives in a fuel.

Also advantageously, no more than five, preferably no more than three, and more preferably no more than two, of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} are selected from a group other than hydrogen. Preferably, one or two of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} are selected from a group other than hydrogen. In some embodiments, only one of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} is selected from a group other than hydrogen.

It is also preferred that at least one of R_2 and R_3 is hydrogen, and more preferred that both of R_2 and R_3 are hydrogen.


In preferred embodiments, at least one of R_4 , R_5 , R_7 and R_8 is selected from methyl, ethyl, propyl and butyl groups and the remainder of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} are hydrogen. More preferably, at least one of R_7 and R_8 are selected from methyl, ethyl, propyl and butyl groups and the remainder of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} are hydrogen.


In further preferred embodiments, at least one of R_4 , R_5 , R_7 and R_8 is a methyl group and the remainder of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} are hydrogen. More preferably, at least one of R_7 and R_8 is a methyl group and the remainder of R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} and R_{12} are hydrogen.

Preferably, X is -O- or -NR₁₀-, where R₁₀ is selected from hydrogen, methyl, ethyl, propyl and butyl groups, and preferably from hydrogen, methyl and ethyl groups. More preferably, R₁₀ is hydrogen. In preferred embodiments, X is -O-.

n may be 0 or 1, though it is preferred that n is 0.


Octane-boosting additives that may be used in the present invention include:






5

Preferred octane-boosting additives include:



A mixture of additives may be used in the fuel composition. For instance, the fuel composition may comprise a mixture of:



It will be appreciated that references to alkyl groups include different isomers of the alkyl group. For instance, references to propyl groups embrace n-propyl and i-propyl groups, and references to butyl embrace n-butyl, isobutyl, sec-butyl and tert-butyl groups.

Fuel composition

The octane-boosting additives described herein are used in a fuel composition for a spark-ignition internal combustion engine. It will be appreciated that the octane-boosting additives may be used in engines other than spark-ignition internal combustion engines, provided that the fuel in which the additive is used is suitable for use in a spark-ignition internal combustion engine. Gasoline fuels (including those containing oxygenates) are typically used in spark-ignition internal combustion engines. Commensurately, the fuel composition according to the present invention may be a gasoline fuel composition.

The fuel composition may comprise a major amount (*i.e.* greater than 50 % by weight) of liquid fuel ("base fuel") and a minor amount (*i.e.* less than 50 % by weight) of octane-boosting additive described herein, *i.e.* an additive having a chemical structure comprising a 6-membered aromatic ring sharing two adjacent aromatic carbon atoms with a 6- or 7-membered saturated heterocyclic ring, the 6- or 7-membered saturated heterocyclic ring comprising a nitrogen atom directly bonded to one of the shared carbon atoms to form a secondary amine and an atom selected from oxygen or nitrogen directly bonded to the other shared carbon atom, the remaining atoms in the 6- or 7-membered heterocyclic ring being carbon.

Examples of suitable liquid fuels include hydrocarbon fuels, oxygenate fuels and combinations thereof.

Hydrocarbon fuels that may be used in a spark-ignition internal combustion engine may be derived from mineral sources and/or from renewable sources such as biomass (*e.g.* biomass-to-liquid sources) and/or from gas-to-liquid sources and/or from coal-to-liquid sources.

Oxygenate fuels that may be used in a spark-ignition internal combustion engine contain oxygenate fuel components, such as alcohols and ethers. Suitable alcohols include straight and/or branched chain alkyl alcohols having from 1 to 6 carbon atoms, *e.g.* methanol, ethanol, n-propanol, n-butanol, isobutanol, tert-butanol. Preferred alcohols include methanol and ethanol. Suitable ethers include ethers having 5 or more carbon atoms, *e.g.* methyl tert-butyl ether and ethyl tert-butyl ether.

In some preferred embodiments, the fuel composition comprises ethanol, *e.g.* ethanol complying with EN 15376:2014. The fuel composition may comprise ethanol in an amount of up to 85 %, preferably from 1 % to 30 %, more preferably from 3 % to 20 %, and even more preferably from 5 % to 15 %, by volume. For instance, the fuel may contain ethanol in an amount of about 5 % by volume (*i.e.* an E5 fuel), about 10 % by volume (*i.e.* an E10 fuel) or about 15 % by volume (*i.e.* an E15 fuel). A fuel which is free from ethanol is referred to as an E0 fuel.

Ethanol is believed to improve the solubility of the octane-boosting additives described herein in the fuel. Thus, in some embodiments, for instance where the octane-boosting additive is unsubstituted (*e.g.* an additive in which R₁, R₂, R₃, R₄, R₅, R₆, R₇, R₈ and R₉ are hydrogen; X is -O-; and n is 0) it may be preferable to use the additive with a fuel which comprises ethanol.

The fuel composition may meet particular automotive industry standards. For instance, the fuel composition may have a maximum oxygen content of 2.7 % by mass.

The fuel composition may have maximum amounts of oxygenates as specified in EN 228, *e.g.* methanol: 3.0 % by volume, ethanol: 5.0 % by volume, iso-propanol: 10.0 % by volume, iso-butyl alcohol: 10.0 % by volume, tert-butanol: 7.0 % by volume, ethers (*e.g.* having 5 or more carbon atoms): 10 % by volume and other oxygenates (subject to suitable final boiling point): 10.0 % by volume.

The fuel composition may have a sulfur content of up to 50.0 ppm by weight, *e.g.* up to 10.0 ppm by weight.

Examples of suitable fuel compositions include leaded and unleaded fuel compositions. Preferred fuel compositions are unleaded fuel compositions.

In embodiments, the fuel composition meets the requirements of EN 228, *e.g.* as set out in BS EN 228:2012. In other embodiments, the fuel composition meets the requirements of ASTM D 4814, *e.g.* as set out in ASTM D 4814-15a. It will be

appreciated that the fuel compositions may meet both requirements, and/or other fuel standards.

The fuel composition for a spark-ignition internal combustion engine may exhibit one or more (such as all) of the following, *e.g.*, as defined according to BS EN 228:2012: a
5 minimum research octane number of 95.0, a minimum motor octane number of 85.0 a maximum lead content of 5.0 mg/l, a density of 720.0 to 775.0 kg/m³, an oxidation stability of at least 360 minutes, a maximum existent gum content (solvent washed) of 5 mg/100 ml, a class 1 copper strip corrosion (3 h at 50 °C), clear and bright appearance, a maximum olefin content of 18.0 % by weight, a maximum aromatics content of 35.0 % by weight,
10 and a maximum benzene content of 1.00 % by volume.

The fuel composition may contain the octane-boosting additive described herein in an amount of up to 20 %, preferably from 0.1 % to 10 %, and more preferably from 0.2 % to 5 % weight additive / weight base fuel. Even more preferably, the fuel composition contains the octane-boosting additive in an amount of from 0.25 % to 2 %, and even more
15 preferably still from 0.3 % to 1 % weight additive / weight base fuel. It will be appreciated that, when more than one octane-boosting additive described herein is used, these values refer to the total amount of octane-boosting additive described herein in the fuel.

The fuel compositions may comprise at least one other further fuel additive.

Examples of such other additives that may be present in the fuel compositions
20 include detergents, friction modifiers/anti-wear additives, corrosion inhibitors, combustion modifiers, anti-oxidants, valve seat recession additives, dehazers/demulsifiers, dyes, markers, odorants, anti-static agents, anti-microbial agents, and lubricity improvers.

Further octane improvers may also be used in the fuel composition, *i.e.* octane improvers which are not octane-boosting additives described herein, *i.e.* they do not have a
25 chemical structure comprising a 6-membered aromatic ring sharing two adjacent aromatic carbon atoms with a 6- or 7-membered saturated heterocyclic ring, the 6- or 7-membered saturated heterocyclic ring comprising a nitrogen atom directly bonded to one of the shared carbon atoms to form a secondary amine and an atom selected from oxygen or nitrogen directly bonded to the other shared carbon atom, the remaining atoms in the 6- or 7-
30 membered heterocyclic ring being carbon.

Examples of suitable detergents include polyisobutylene amines (PIB amines) and polyether amines.

Examples of suitable friction modifiers and anti-wear additives include those that are ash-producing additives or ashless additives. Examples of friction modifiers and anti-wear additives include esters (*e.g.* glycerol mono-oleate) and fatty acids (*e.g.* oleic acid and stearic acid).

5 Examples of suitable corrosion inhibitors include ammonium salts of organic carboxylic acids, amines and heterocyclic aromatics, *e.g.* alkylamines, imidazolines and tolyltriazoles.

10 Examples of suitable anti-oxidants include phenolic anti-oxidants (*e.g.* 2,4-di-tert-butylphenol and 3,5-di-tert-butyl-4-hydroxyphenylpropionic acid) and aminic anti-oxidants (*e.g.* para-phenylenediamine, dicyclohexylamine and derivatives thereof).

Examples of suitable valve seat recession additives include inorganic salts of potassium or phosphorus.

15 Examples of suitable further octane improvers include non-metallic octane improvers include N-methyl aniline and nitrogen-based ashless octane improvers. Metal-containing octane improvers, including methylcyclopentadienyl manganese tricarbonyl, ferrocene and tetra-ethyl lead, may also be used. However, in preferred embodiments, the fuel composition is free of all added metallic octane improvers including methyl cyclopentadienyl manganese tricarbonyl and other metallic octane improvers including *e.g.* ferrocene and tetraethyl lead.

20 Examples of suitable dehazers/demulsifiers include phenolic resins, esters, polyamines, sulfonates or alcohols which are grafted onto polyethylene or polypropylene glycols.

Examples of suitable markers and dyes include azo or anthraquinone derivatives.

25 Examples of suitable anti-static agents include fuel soluble chromium metals, polymeric sulfur and nitrogen compounds, quaternary ammonium salts or complex organic alcohols. However, the fuel composition is preferably substantially free from all polymeric sulfur and all metallic additives, including chromium based compounds.

30 In some embodiments, the fuel composition comprises solvent, *e.g.* which has been used to ensure that the additives are in a form in which they can be stored or combined with the liquid fuel. Examples of suitable solvents include polyethers and aromatic and/or aliphatic hydrocarbons, *e.g.* heavy naphtha *e.g.* Solvesso (Trade mark), xylenes and kerosene.

Representative typical and more typical independent amounts of additives (if present) and solvent in the fuel composition are given in the table below. For the additives, the concentrations are expressed by weight (of the base fuel) of active additive compounds, *i.e.* independent of any solvent or diluent. Where more than one additive of each type is present in the fuel composition, the total amount of each type of additive is expressed in the table below.

	Fuel Composition	
	Typical amount (ppm, by weight)	More typical amount (ppm, by weight)
Octane-boosting additives	1000 to 100000	2000 to 50000
Detergents	10 to 2000	50 to 300
Friction modifiers and anti-wear additives	10 to 500	25 to 150
Corrosion inhibitors	0.1 to 100	0.5 to 40
Anti-oxidants	1 to 100	10 to 50
Further octane improvers	0 to 20000	50 to 10000
Dehazers and demulsifiers	0.05 to 30	0.1 to 10
Anti-static agents	0.1 to 5	0.5 to 2
Other additive components	0 to 500	0 to 200
Solvent	10 to 3000	50 to 1000

In some embodiments, the fuel composition comprises or consists of additives and solvents in the typical or more typical amounts recited in the table above.

Fuel compositions of the present invention may be produced by a process which comprises combining, in one or more steps, a fuel for a spark-ignition internal combustion engine with an octane-boosting additive described herein. In embodiments in which the fuel composition comprises one or more further fuel additives, the further fuel additives may also be combined, in one or more steps, with the fuel.

In some embodiments, the octane-boosting additive may be combined with the fuel in the form of a refinery additive composition or as a marketing additive composition. Thus, the octane-boosting additive may be combined with one or more other components (*e.g.* additives and/or solvents) of the fuel composition as a marketing additive, *e.g.* at a

terminal or distribution point. The octane-boosting additive may also be added on its own at a terminal or distribution point. The octane-boosting additive may also be combined with one or more other components (*e.g.* additives and/or solvents) of the fuel composition for sale in a bottle, *e.g.* for addition to fuel at a later time.

5 The octane-boosting additive and any other additives of the fuel composition may be incorporated into the fuel composition as one or more additive concentrates and/or additive part packs, optionally comprising solvent or diluent.

 The octane-boosting additive may also be added to the fuel within a vehicle in which the fuel is used, either by addition of the additive to the fuel stream or by addition of
10 the additive directly into the combustion chamber.

 It will also be appreciated that the octane-boosting additive may be added to the fuel in the form of a precursor compound which, under the combustion conditions encountered in an engine, breaks down to form an octane-boosting additive as defined herein.

15 Uses and methods

 The octane-boosting additives disclosed herein are used in a fuel for a spark-ignition internal combustion engine. Examples of spark-ignition internal combustion engines include direct injection spark-ignition engines and port fuel injection spark-ignition engines. The spark-ignition internal combustion engine may be used in
20 automotive applications, *e.g.* in a vehicle such as a passenger car.

 Examples of suitable direct injection spark-ignition internal combustion engines include boosted direct injection spark-ignition internal combustion engines, *e.g.* turbocharged boosted direct injection engines and supercharged boosted direct injection engines. Suitable engines include 2.0L boosted direct injection spark-ignition internal
25 combustion engines. Suitable direct injection engines include those that have side mounted direct injectors and/or centrally mounted direct injectors.

 Examples of suitable port fuel injection spark-ignition internal combustion engines include any suitable port fuel injection spark-ignition internal combustion engine including
e.g. a BMW 318i engine, a Ford 2.3L Ranger engine and an MB M111 engine.

30 The octane-boosting additives disclosed herein may be used to increase the octane number of a fuel for a spark-ignition internal combustion engine. In some embodiments, the octane-boosting additives increase the RON or the MON of the fuel. In preferred

embodiments, the octane-boosting additives increase the RON of the fuel, and more preferably the RON and MON of the fuel. The RON and MON of the fuel may be tested according to ASTM D2699-15a and ASTM D2700-13, respectively.

Since the octane-boosting additives described herein increase the octane number of a fuel for a spark-ignition internal combustion engine, they may also be used to address abnormal combustion that may arise as a result of a lower than desirable octane number. Thus, the octane-boosting additives may be used for improving the auto-ignition characteristics of a fuel, *e.g.* by reducing the propensity of a fuel for at least one of auto-ignition, pre-ignition, knock, mega-knock and super-knock, when used in a spark-ignition internal combustion engine.

Also contemplated is a method for increasing the octane number of a fuel for a spark-ignition internal combustion engine, as well as a method for improving the auto-ignition characteristics of a fuel, *e.g.* by reducing the propensity of a fuel for at least one of auto-ignition, pre-ignition, knock, mega-knock and super-knock, when used in a spark-ignition internal combustion engine. These methods comprise the step of blending an octane-boosting additive described herein with the fuel.


The methods described herein may further comprise delivering the blended fuel to a spark-ignition internal combustion engine and/or operating the spark-ignition internal combustion engine.

The invention will now be described with reference to the following non-limiting examples.


Examples

Example 1: Preparation of octane-boosting additives


The following octane-boosting additives were prepared using standard methods:




OX1




OX2




OX3




OX4




OX5




OX6




OX7




OX8




OX9




OX10




OX11




OX12




OX13




OX14




OX15




OX16



OX17



OX18



OX19

Example 2: Octane number of fuels containing octane-boosting additives

The effect of octane-boosting additives from Example 1 (OX1, OX2, OX3, OX5, OX6, OX8, OX9, OX12, OX13, OX17 and OX19) on the octane number of two different base fuels for a spark-ignition internal combustion engine was measured.

5 The additives were added to the fuels at a relatively low treat rate of 0.67 % weight additive / weight base fuel, equivalent to a treat rate of 5 g additive / litre of fuel. The first fuel was an E0 gasoline base fuel. The second fuel was an E10 gasoline base fuel. The RON and MON of the base fuels, as well as the blends of base fuel and octane-boosting additive, were determined according to ASTM D2699 and ASTM D2700, respectively.

10 The following table shows the RON and MON of the fuel and the blends of fuel and octane-boosting additive, as well as the change in the RON and MON that was brought about by using the octane-boosting additives:

Additive	E0 base fuel				E10 base fuel			
	RON	MON	Δ RON	Δ MON	RON	MON	Δ RON	Δ MON
-	95.4	86.0	n/a	n/a	95.4	85.2	n/a	n/a
OX1	-	-	-	-	97.3	86.3	1.9	1.1
OX2	97.7	87.7	2.3	1.7	97.8	86.5	2.4	1.3
OX3	97.0	86.7	1.6	0.7	97.1	85.5	1.7	0.3
OX5	97.0	86.5	1.6	0.5	97.1	85.5	1.7	0.3
OX6	98.0	87.7	2.6	1.7	98.0	86.8	2.6	1.6
OX8	96.9	86.1	1.5	0.1	96.9	85.7	1.5	0.5
OX9	97.6	86.9	2.2	0.9	97.6	86.5	2.2	1.3
OX12	97.4	86.3	2.0	0.3	97.3	86.1	1.9	0.9
OX13	97.9	86.5	2.5	0.5	97.7	86.1	2.3	0.9
OX17	97.5	86.4	2.1	0.4	97.4	86.4	2.0	1.2
OX19	97.4	86.1	2.0	0.1	97.6	85.9	2.2	0.7

15 It can be seen that the octane-boosting additives may be used to increase the RON of an ethanol-free and an ethanol-containing fuel for a spark-ignition internal combustion engine.

Further additives from Example 1 (OX4, OX7, OX10, OX11, OX14, OX15, OX16 and OX18) were tested in the E0 gasoline base fuel and the E10 gasoline base fuel. Each
 20 of the additives increased the RON of both fuels, aside from OX7 where there was insufficient additive to carry out analysis with the ethanol-containing fuel.

Example 3: Variation of octane number with octane-boosting additive treat rate

The effect of an octane-boosting additive from Example 1 (OX6) on the octane number of three different base fuels for a spark-ignition internal combustion engine was measured over a range of treat rates (% weight additive / weight base fuel).

5 The first and second fuels were E0 gasoline base fuels. The third fuel was an E10 gasoline base fuel. As before, the RON and MON of the base fuels, as well as the blends of base fuel and octane-boosting additive, were determined according to ASTM D2699 and ASTM D2700, respectively.

10 The following table shows the RON and MON of the fuels and the blends of fuel and octane-boosting additive, as well as the change in the RON and MON that was brought about by using the octane-boosting additives:

15

20

25

30

	Additive treat rate (% w/w)	Octane number			
		RON	MON	Δ RON	Δ MON
E0 90 RON	0.00	89.9	82.8	0.0	0.0
	0.20	91.5	83.5	1.6	0.7
	0.30	92.0	83.6	2.1	0.8
	0.40	92.5	83.8	2.6	1.0
	0.50	92.9	83.8	3.0	1.0
	0.67	93.6	84.2	3.7	1.4
	1.01	94.7	85.0	4.8	2.2
	1.34	95.9	85.4	6.0	2.6
	10.00	104.5	87.9	14.6	5.1
E0 95 RON	0.00	95.2	85.6	0.0	0.0
	0.10	95.9	85.8	0.7	0.2
	0.20	96.4	86.3	1.2	0.7
	0.30	96.6	86.8	1.4	1.2
	0.40	97.1	86.6	1.9	1.0
	0.50	97.3	87.0	2.1	1.4
	0.60	97.5	86.8	2.3	1.2
	0.70	97.8	86.8	2.6	1.2
	0.80	98.0	87.3	2.8	1.7
	0.90	98.5	86.8	3.3	1.2
	1.00	98.7	86.9	3.5	1.3
	10.00	105.7	88.7	10.5	3.1
E10 95 RON	0.00	95.4	85.1	0.0	0.0
	0.10	95.9	85.2	0.5	0.1
	0.20	96.3	86.3	0.9	1.2
	0.30	96.8	86.3	1.4	1.2
	0.40	96.9	85.8	1.5	0.7
	0.50	97.3	85.9	1.9	0.8
	0.60	97.4	85.9	2.0	0.8
	0.70	97.9	86.0	2.5	0.9
	0.80	98.2	86.8	2.8	1.7
	0.90	98.7	86.3	3.3	1.2
	1.00	98.8	86.5	3.4	1.4
	10.00	105.1	87.8	9.7	2.7

Graphs of the effect of the octane-boosting additive on the RON and MON of the three fuels are shown in Figures 1a-c. It can be seen that the octane-boosting additive had a significant effect on the octane numbers of each of the fuels, even at very low treat rates.

Example 4: Comparison of octane-boosting additive with N-methyl aniline

The effect of octane-boosting additives from Example 1 (OX2 and OX6) was compared with the effect of N-methyl aniline on the octane number of two different base fuels for a spark-ignition internal combustion engine over a range of treat rates (% weight additive / weight base fuel).

The first fuel was an E0 gasoline base fuel. The second fuel was an E10 gasoline base fuel. As before, the RON and MON of the base fuels, as well as the blends of base fuel and octane-boosting additive, were determined according to ASTM D2699 and ASTM D2700, respectively.

A graph of the change in octane number of the E0 and E10 fuels against treat rate of N-methyl aniline and an octane-boosting additive (OX6) is shown in Figure 2a. The treat rates are typical of those used in a fuel. It can be seen from the graph that the performance of the octane-boosting additives described herein is significantly better than that of N-methyl aniline across the treat rates.

A comparison of the effect of two octane-boosting additives (OX2 and OX6) and N-methyl aniline on the octane number of the E0 and E10 fuels at a treat rate of 0.67 % w/w is shown in Figures 2b and 2c. It can be seen from the graph that the performance of octane-boosting additives described herein is significantly superior to that of N-methyl aniline. Specifically, an improvement of about 35 % to about 50 % is observed for the RON, and an improvement of about 45 % to about 75 % is observed for the MON.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Every document cited herein, including any cross referenced or related patent or application, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document

conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and
5 modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope and spirit of this invention.

10

15


20

25

30

Claims:

1. A fuel composition for a spark-ignition internal combustion engine, the fuel composition comprises an additive having the formula:



5

where: R₁ is hydrogen;

R₂, R₃, R₄, R₅, R₁₁ and R₁₂ are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

- 10 R₆, R₇, R₈ and R₉ are each independently selected from hydrogen, alkyl, alkoxy, alkoxy-alkyl, secondary amine and tertiary amine groups;

X is selected from -O- or -NR₁₀-, where R₁₀ is selected from hydrogen and alkyl groups; and

n is 0 or 1;

- 15 wherein at least one of R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁ and R₁₂ is selected from a group other than hydrogen.

2. A fuel composition according to claim 1, wherein R₂, R₃, R₄, R₅, R₁₁ and R₁₂ are each independently selected from hydrogen and alkyl groups, preferably from hydrogen, methyl, ethyl, propyl and butyl groups, more preferably from hydrogen, methyl and ethyl, and even more preferably from hydrogen and methyl.


20


3. A fuel composition according to claim 1 or claim 2, wherein R₆, R₇, R₈ and R₉ are each independently selected from hydrogen, alkyl and alkoxy groups, preferably from hydrogen, methyl, ethyl, propyl, butyl, methoxy, ethoxy and propoxy groups, more preferably from hydrogen, methyl, ethyl and methoxy, and even more preferably from hydrogen, methyl and methoxy.

25

4. A fuel composition according to any of claims 1 to 3, wherein at least one of R₆, R₇, R₈ and R₉ is selected from a group other than hydrogen.


5. A fuel composition according to any of claims 1 to 4, wherein no more than five, preferably no more than three, and more preferably no more than two, of R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁ and R₁₂ are selected from a group other than hydrogen.
- 5 6. A fuel composition according to any of claims 1 to 5, wherein at least one of R₂ and R₃ is hydrogen, and preferably wherein R₂ and R₃ are hydrogen.
7. A fuel composition according to any of claims 1 to 6, wherein at least one of R₄, R₅, R₇ and R₈ is selected from methyl, ethyl, propyl and butyl groups and the remainder of R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁ and R₁₂ are hydrogen, and preferably wherein at least
- 10 one of R₇ and R₈ are selected from methyl, ethyl, propyl and butyl groups and the remainder of R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁ and R₁₂ are hydrogen.
8. A fuel composition according to claim 7, wherein at least one of R₄, R₅, R₇ and R₈ is a methyl group and the remainder of R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁ and R₁₂ are hydrogen, and preferably wherein at least one of R₇ and R₈ is a methyl group and the
- 15 remainder of R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁ and R₁₂ are hydrogen.
9. A fuel composition according to any of claims 1 to 8, wherein X is -O- or -NR₁₀-, where R₁₀ is selected from hydrogen, methyl, ethyl, propyl and butyl groups, preferably from hydrogen, methyl and ethyl groups, and even more preferably is hydrogen.
10. A fuel composition according to any of claims 1 to 9, wherein X is -O-.
- 20 11. A fuel composition according to any of claims 1 to 10, wherein n is 0.
12. A fuel composition according to any preceding claim, wherein the additive is selected from:






5

and preferably from:




13. A fuel composition for a spark-ignition internal combustion engine, the fuel

composition comprising an additive of the formula



or




- 5 14. A fuel composition according to any preceding claim, wherein the additive is present in the fuel composition an amount of up to 20 %, preferably from 0.1 % to 10 %, more preferably from 0.2 % to 5 %, even more preferably from 0.25 % to 2 %, and even more preferably still from 0.3 % to 1 %, weight additive / weight base fuel.

15. A fuel composition according to any preceding claim, further comprising ethanol present in the fuel composition in an amount of up to 85 %, preferably from 1 % to 30 %, more preferably from 3 % to 20 %, and even more preferably from 5 % to 15 %, by volume.

5 16. A process for producing a fuel composition of any of claims 1 to 15, the process comprising combining a fuel for a spark-ignition internal combustion engine with an additive as defined in any of claims 1 to 13.

17. Use of an additive in a fuel for a spark-ignition internal combustion engine or for increasing the octane number of a fuel for a spark-ignition internal combustion engine,

10 wherein the additive is of formula :




wherein R₁, R₂, R₃, R₄, R₅, R₆, R₇, R₈, R₉, R₁₁, R₁₂, X, and n are as defined in any of claims 1 to 11, or

the additive is 3,4-dihydro-2H-benzo[b][1,4]oxazine or 2,3,4,5-

15 tetrahydrobenzo[b][1,4]oxazepine.


18. Use of an additive for improving the auto-ignition characteristics of a fuel, *e.g.* by reducing the propensity of a fuel for at least one of auto-ignition, pre-ignition, knock, mega-knock and super-knock, when used in a spark-ignition internal combustion engine, wherein the additive is of formula .



wherein R_1 , R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} , R_{12} , X , and n are as defined in any of claims 1 to 11, or

the additive is 3,4-dihydro-2*H*-benzo[*b*][1,4]oxazine or 2,3,4,5-tetrahydrobenzo[*b*][1,4]oxazepine.


- 5 19. A method for increasing the octane number of a fuel for a spark-ignition internal combustion engine, said method comprising blending an additive with the fuel, wherein the additive is of formula:



- 10 wherein R_1 , R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} , R_{12} , X , and n are as defined in any of claims 1 to 11, or;

the additive is 3,4-dihydro-2*H*-benzo[*b*][1,4]oxazine or 2,3,4,5-tetrahydrobenzo[*b*][1,4]oxazepine.

20. A method for improving the auto-ignition characteristics of a fuel, *e.g.* by reducing the propensity of a fuel for at least one of auto-ignition, pre-ignition, knock, mega-knock
15 and super-knock, when used in a spark-ignition internal combustion engine, said method comprising blending an additive with the fuel, wherein the additive is of formula:



wherein R_1 , R_2 , R_3 , R_4 , R_5 , R_6 , R_7 , R_8 , R_9 , R_{11} , R_{12} , X , and n are as defined in any of claims 1 to 11, or

- 20 the additive is 3,4-dihydro-2*H*-benzo[*b*][1,4]oxazine or 2,3,4,5-tetrahydrobenzo[*b*][1,4]oxazepine.