

MAGNETIC DISK DEVICE

[Detailed Description of the Invention]
[0001]

[Technical Field to which the Invention Pertains]

The present invention relates to a technique for preventing a data loss as a result of deletion of data on adjacent tracks that may occur when data on a given track is written repeatedly in a magnetic disk device.

[0002]

[Prior Art]

In recent years, as magnetic disk devices achieve widespread use not only in the field of computer technology but also in another application such as hard disk recorders in place of video tape recorders, the need to increase capacity of the magnetic disk devices, which are random-accessible large-capacity storage units, grows increasingly.

[0003]

Fig. 2 shows a mechanism of a typical magnetic disk device. The disk device comprises: magnetic disks 201 each of which consists of a disk of a non-magnetic material such as glass on which a magnetic layer is laminated; write heads for writing data to the magnetic disks; and read heads for reading data from the magnetic disks. Typically, pairs of one write head and one read head constitute an integrated magnetic head construction 202. The magnetic disks 201 are held on a single spindle 203. The heads 202

whose number corresponds to the number of surfaces of the magnetic disks are attached to arms 204. The arms 204 are configured so that they can be moved onto the disk surfaces by a VCM (voice coil motor) 205.

[0004]

In the magnetic disk device, data is written and read on areas disposed on the disks as concentric circles, which are called tracks. Fig. 3 shows the placement of the tracks 302 on the magnetic disk 301. The tracks 302 are disposed so that they are typically spaced uniformly from each other by a track pitch 303 and each track 302 consists of servo areas where information that is needed for positioning the heads and data areas to/from which a user can write/read data. Further, each data area can be divided into minimum accessible units called sectors.

[0005]

Fig. 4 shows basic components required for writing/reading data on/from the magnetic disk device.

When the data is written, the data is sent from a host computer 401 to a hard disk controller (HDC) 402. The HDC 402 determines an address or the head, track and sector number to which the data is written and issues a command to a servo controller 404 to move a write head 407 to a specified sector position. Based on servo information that is written on the magnetic disk 409 and obtained via a R/W amplifier 406 and a R/W channel 405, the servo controller 404 moves the write head to the track in which the desired sector resides.

[0006]

The HDC 402 outputs the write data to the R/W channel 405 in synchronization with the sector specified on the track of the rotating magnetic disk 409. The write data is encoded into a format suitable for writing in the R/W channel 405 and the R/W amplifier 406 and, then, the encoded write data is written on the magnetic disk 409 by a write head 407. Here, it is to be noted that the data from the host computer is typically stored in a data buffer 403 once and, then, sent from the data buffer 403 to the R/W channel when the writing is ready.

[0007]

Also when the data is read, the head is positioned on the track where the desired sector resides in a manner similar to the one when the data is written. After the

head has been positioned, the data is read from the magnetic disk 409 by a read head 408 in synchronization with the specified sector, the read waveform is decoded into the original data by the R/W amplifier 406 and the R/W channel 405 and, then, the decoded data is sent to the HDC 402. Finally, the HDC 402 outputs the data to the host computer.

[0008]

The data is written or read in the procedure described above. The addresses specified by the host computer when it accesses the magnetic disk device are called logical addresses, which are not always the same as physical addresses or actual addresses on the disk. A MPU 410 calculates the corresponding physical addresses from the logical addresses specified by the host computer 401 and the actual write/read operation is performed on the addresses. When the magnetic disk device is accessed sequentially, the data is written or read in the order of logical addresses.

[0009]

In order to meet the requirement for increasing the storage capacity in the magnetic disk device configured as described above, various attempts are made to improve a recording density such as by increasing a track recording density of the disk, which is a density in the

circumferential direction, or by reducing the track width as well as the track pitch to increase the track density.

[0010]

Fig. 5 shows a structural schematic view of the write head. When a coil 503 is energized, a magnetic field is generated between a floating upper surface portion 504 of a head of an upper pole piece 502 and a lower pole piece 501 and, then, as this magnetic field magnetizes the magnetic disk surface, the data is written. However, under the circumstance that track width becomes narrower so as to increase the recording density as described above, as the tip portion of the write head becomes narrower, the tip portion may be saturated by the magnetic field. As a result, the magnetic field may not only be generated at the floating upper surface portion 504 as it should be, but also be leaked from side surfaces 505. Further, when the track pitch is narrow, this leakage magnetic field from the side surfaces may be spread to adjacent tracks. Since the leakage magnetic field is weaker than the main write magnetic field to write the data, even if the leakage magnetic field is spread to the adjacent tracks, the data on the adjacent tracks may not be affected immediately. However, as the adjacent tracks are exposed to the leakage magnetic field multiple times, the data on the adjacent tracks may be deleted little by little and, eventually, the

data may become unreadable.

[0011]

In order to avoid the data loss on the adjacent tracks due to the leakage magnetic field, in view of the parts constituting the magnetic disk device, examples of the measures include: (1) to increase a coercive force of the magnetic disk so that the data may be not liable to be deleted even if there is the leakage magnetic field from the adjacent tracks; and (2) to configure the write head such that the leakage magnetic field may not be liable to be generated.

[0012]

Further, in view of usage of the device so as to prevent the occurrence of the deletion of the adjacent tracks due to the leakage magnetic field, other examples of the measures include: (3) to reduce the amount of the leakage magnetic field to which the adjacent tracks are exposed by increasing the track pitch; and (4) to reduce the amount of the leakage magnetic field itself by adjusting the magnitude of the current applied to the write head when the data is written or an amount of overshoot of the write current waveform.

[0013]

Further, in a prior art example, under the circumstance where it is required to increase the track

density TPI so that the recording density of the recording media can be improved and, due to the high TPI, both new and old versions of the write data may coexist together in a unitary storage area, an improvement has been proposed wherein incorrect data that may result from reading the old data can be inhibited (for example, see patent document 1).

[0014]

Still further, in another prior art example, paying attention to the high correlation of a failure frequency of storage units with the number of accesses and total energizing time, a technique has been proposed for storing an operation history of a main storage unit every time the main storage unit is operated and, based on this operation history, determining the possibility that the failure may occur in the main storage unit (for example, see patent document 2).

[0015]

[Patent Document 1]

Japanese Patent Laid-open No 2001-338468

[0016]

[Patent Document 2]

Japanese Patent Laid-open No. 2001-350596

[0017]

[Problem to be Solved by the Invention]

Although the methods for inhibiting the data loss in

the adjacent tracks due to the leakage magnetic field have been proposed as described above, if the coercive force of the disk is increased as discussed in item (1), the data on the adjacent tracks becomes less liable to be deleted but it also becomes difficult to overwrite the data as it should be and thus the overwrite characteristic is degraded, which may result in a poor error rate of the data that should be overwritten. On the other hand, with regard to item (2), the construction of the write head that is effective in inhibiting the leakage magnetic field has not been sufficiently apparent up to the present and this problem should be addressed in the future.

[0018]

Further, if the measure described in item (3) is adopted, in order to ensure the storage capacity per disk, the track recording density must be increased in proportion to the track pitch, but the higher track recording density may allow resolution and S/N ratio of the readout waveform to be reduced and, therefore, the error rate may be degraded. Still further, with regard to the setting of the write current value and the adjustment of the overshoot of the write current as discussed in item (4), if such measures are taken so that the leakage magnetic field will not occur or, more specifically, if the write current value is set to a smaller value or the amount of overshoot is

reduced, the data itself may be written insufficiently and, consequently, the error rate may be degraded just as in the case described with regard to item (1).

[0019]

Still further, although the improvement measures against the failure of the data written on the storage media have been proposed in patent documents 1 and 2 as described above, these measures do not address the data loss on the adjacent tracks due to the leakage magnetic field and, moreover, these measures do not take refresh process of the written data into consideration.

[0020]

It is an object of the present invention to provide a magnetic disk device in which even under circumstances where a leakage magnetic field deletes data on adjacent tracks little by little, such deletion can be compensated to refresh the data so that data errors can be prevented from occurring.

[0021]

[Means for Solving the Problems]

In order to solve the problems described above, the present invention mainly adopts a configuration as described below.

According to a first aspect of the present invention, there is provided a magnetic disk device comprising: a

magnetic disk for recording data; a magnetic head for writing or reading the data on or from the magnetic disk; and a write and read circuit, connected to the magnetic head, for writing or reading the data; wherein the data is written or read to or from a plurality of tracks in the form of concentric circles disposed on the magnetic disk; and wherein the number of write of data on a given track is acquired and it is detected that the number of write reaches a predetermined number, and based on the detection, data on tracks adjacent to the given track is read out once and, then, the read-out data is rewritten to the adjacent tracks.

[0022]

According to a second aspect of the present invention, there is provided a magnetic disk device comprising: a magnetic disk for recording data; a magnetic head for writing or reading the data on or from the magnetic disk; and a write and read circuit, connected to the magnetic head, for writing or reading the data; wherein the data is written or read to or from a plurality of tracks in the form of concentric circles disposed on the magnetic disk; and wherein all tracks on the magnetic disk are divided into a plurality of areas, the number of write of data on even-numbered physical tracks in the divided areas is acquired and it is detected that the number of

write reaches a predetermined number, and based on the detection, data on odd-numbered physical tracks in the divided areas is read out once and, then, the read-out data is rewritten on the odd-numbered tracks.

[0023]

According to a third aspect of the present invention, there is provided a magnetic disk device comprising: a magnetic disk for recording data; a magnetic head for writing or reading the data on or from the magnetic disk; and a write and read circuit, connected to the magnetic head, for writing or reading the data; wherein the data is written or read to or from a plurality of tracks in the form of concentric circles disposed on the magnetic disk; and wherein all tracks on the magnetic disk are divided into a plurality of areas, the number of write of data on odd-numbered physical tracks in the divided areas is acquired and it is detected that the number of write reaches a predetermined number, and based on the detection, data on even-numbered physical tracks in the divided areas is read out once and, then, the read-out data is rewritten on the even-numbered tracks.

[0024]

Still further, the magnetic disk device may be configured such that, when the data is written on the tracks, the data is written on alternate physical tracks

and every other track is skipped and, after the data is written on half of all the tracks, the data is written on the skipped tracks.

[0025]

By adopting the configuration described above, according to the present invention, even under circumstances where a leakage magnetic field deletes data on adjacent tracks little by little, such deletion can be compensated so as to prevent data errors from occurring.

[0026]

[Mode for Carrying out the Invention]

First, measures for preventing a data loss in a magnetic disk device according to the present invention or, more specifically, a data loss in adjacent tracks due to a leakage magnetic field will be described briefly. Since inhibiting the data loss itself on the adjacent tracks due to the leakage magnetic field has limitations as described above, according to an embodiment of the present invention, even under circumstances where the leakage magnetic field occurs to delete the data on the adjacent tracks little by little, such deletion can be compensated so that data errors can be prevented from occurring in a magnetic disk device.

[0027]

To that end, when the number of data write on a

magnetic disk surface reaches the predetermined number, on the assumption that it may be possible that data on a track adjacent to the track in question is about to be deleted, the data is refreshed or, more specifically, the data written on the magnetic disk surface is read out once and, then, rewritten on the same track.

[0028]

Fig. 6 is a diagram showing an example of a correspondence between physical track numbers and logical track numbers on a magnetic disk. Fig. 7 is a diagram showing another example of a correspondence between physical track numbers and logical track numbers on a magnetic disk. According to this embodiment, when data is written on a magnetic disk surface, it is defined in advance that the data is written on alternate physical tracks. More specifically, the physical track numbers are associated with the logical track numbers as shown in Fig. 6, wherein the logical track numbers indicate order when the magnetic disk device is actually used.

[0029]

When the physical track numbers are associated with the logical track numbers as shown in Fig. 6, the data is written on the magnetic disk surface in the order of 0, 2, 4, ... of the physical track numbers. In the case in which there are $2n$ tracks in all shown in Fig. 6, when up to half

of the capacity is used or not more than n tracks are used, the data is not written on adjacent tracks and, therefore, even when the data is written repeatedly, there is no possibility that the adjacent tracks are deleted by the leakage magnetic field and it is not necessary to refresh the data.

[0030]

As another method for assigning the logical track numbers to alternate tracks, the method shown in Fig. 7 can also be adopted as an embodiment of the present invention. Further, the number of write on each magnetic disk may be recorded for both even- and odd-numbered physical tracks separately. In this case, for example, when the number of write on the even-numbered physical tracks reaches the predetermined number, it is needed only to refresh the data on the odd-numbered physical tracks and, conversely, when the number of write on the odd-numbered physical tracks reaches a predetermined number, it is needed only to refresh the data on the even-numbered physical tracks and, consequently, the time required to refresh the data can be reduced.

[0031]

The refresh of the data must be performed while the operation in response to commands from the host is not performed. Therefore, in terms of the operation in

response to the commands from the host, it is time-wise difficult to refresh the data on all disk surfaces at a time. Thus, according to this embodiment, each disk surface is divided into several areas as shown in Fig. 8 and the number of write of the data for each area is recorded and, then, it is determined whether or not a refreshing operation is needed for each area.

[0032]

In other words, it is a concept of the present invention that the number of write for each track is monitored so as to refresh the data on the tracks adjacent to the monitored tracks and, further, the data is recorded on alternate physical tracks and, after half of all the tracks have been occupied, the data is written on the tracks that have been skipped. More specifically, considering the fact that the concept described above is not practical in terms of memory management because an enormous number of tracks must be managed, the magnetic disk surfaces are divided into areas and the number of write and the refresh of the data is managed for each area. In this case, it is needed only to refresh the data on the restricted number of tracks and, therefore, it can be avoided that the areas that are still not needed to be refreshed may be refreshed uselessly and, consequently, the time required for refreshment can be reduced.

[0033]

Fig. 9 is a diagram showing a state in which the number of write on both even- or odd-numbered physical tracks is recorded on a memory for each area on a given magnetic disk surface according to this embodiment. In the following description, it is assumed that the tracks are designated by the physical track numbers, even unless explicitly stated. In a specific example shown in Figs. 8 and 9, in which one disk surface may be divided into about 10 areas, if one magnetic disk surface includes 40,000 - 50,000 tracks in all, each area should include 4000 - 5000 tracks. In Fig. 9, even [1] refers to a variation indicating the number of write on even-numbered physical tracks residing in the area number 1 and this value is recorded on the memory as, for example, even [1] 900. Here, although the number of write is not always equal among all even-numbered tracks in the area number 1, it may be reasonable to record the maximum value of the number of write on any one track in the area number 1.

[0034]

The magnetic disk device having a plurality of magnetic disk surfaces is provided with the tables as shown in Fig. 9 as many as the magnetic disk surfaces. The number of write on the even-numbered tracks in the area y is stored in even [y] and the number of write on the odd-

numbered tracks in the area y is stored in odd [y]. When the magnetic disk device is shipped, all these values are 0. [0035]

Since the values in the tables shown in Fig. 9 must be held even while the magnetic disk device is de-energized, these values are recorded, for example, in a Flash memory or on the magnetic disk surface. However, as these values of the number of write are read or updated frequently while the magnetic disk device is in operation, it is preferable that these values reside on a memory such as a RAM that can be read and written at high speed.

[0036]

In this case, when the magnetic disk device is activated, the values of the number of write up to the previous time that have been recorded in the non-volatile memory are read and, then, the values are put on the RAM and, then, while the magnetic disk device is in operation, the values on the RAM are read or updated. Then, before the magnetic disk device is de-energized, the values on the RAM are rewritten in the non-volatile memory. Since there is a possibility that the magnetic disk device is de-energized suddenly, it is preferable to save the values on the RAM to the non-volatile memory not only at the moment when the magnetic disk device is turned off but also from time to time.

[0037]

Next, a procedure for refreshing data according to the embodiment of the present invention will be described. Fig. 1 shows a procedure for determining whether a data refresh process is needed or not when data is written on a track x and a procedure after the refresh process is performed. Here, it is assumed that the track x belongs to an area y in the following description.

[0038]

First, in step 101, it is determined whether even-numbered or odd-numbered the track x is. The following description will be given on the assumption that the track x is even-numbered. Next, in step 102, it is determined whether or not the data has been written on adjacent tracks. If $\text{odd}[y] = 0$, or if the data has not been written at all on odd-numbered tracks in the area y, no matter how many times the data is written on the even-numbered tracks, since it is not necessary to consider a possibility that the data on the adjacent tracks is deleted by a leakage magnetic field and the number of write on the even-numbered tracks is insignificant, the process proceeds to step 103 and the value of $\text{even}[y]$ is always 1. If $\text{odd}[y]$ is not 0, or if the data has already been written on the odd-numbered tracks, the process proceeds to step 104 and the value of $\text{even}[y]$ is incremented by 1 (the number of write on the

even-numbered tracks in the area y is incremented by 1).

[0039]

If the value of even [y] is updated, since there is a possibility that the number of write on the even-numbered tracks reaches the value at which the refresh is required, the number of write on the even-numbered tracks is determined in step 105 in this embodiment. More specifically, in this case, it is determined whether the number of write on the even-numbered tracks reaches a threshold value p at which the refresh is needed. If the value of even [y] is less than the threshold value p, it is determined that the refresh is not needed and the process is ended (106). However, if the value of even [y] is not less than the threshold value p, it is determined that there is a possibility that the refresh is needed and the process continues.

[0040]

When the number of write on the even-numbered tracks in the area y reaches the threshold value p, the refresh process may be performed at once but, alternatively, another procedure shown in step 107 (see steps in a dotted box in Fig. 1) may be taken wherein the data on the odd-numbered tracks in the area y, which has been written temporarily to refresh the data, is read out once (108) and, then, if the number of retry attempts exceeds a

predetermined value, it is determined that the data is about to be deleted actually (109) and the data is rewritten. In a typical magnetic disk device, if the data is not read properly in the first read operation, the retry attempts are performed to read the data in the same portion repeatedly up to a few tens or a hundred times until the data is read properly and, then, if the data has not been failed completely, the data may often be read by the retry attempts.

[0041]

In Fig. 1, when the data on the odd-numbered tracks in the area y in question is read, if the number of retry attempts reaches a predetermined value q, it is determined that the data in the area becomes less readable in actuality in step 109. Then, if it is determined that the data must be rewritten, the data is rewritten in step 110 (the data on all the odd-numbered tracks in the area y is rewritten). If the number of retry attempts is small and it is determined that the refresh is not needed yet, the data is not rewritten. In the case where the data is not rewritten, it is preferable that the data that has been read once is stored on a high-speed memory such as RAM temporarily until it is determined whether the data must be rewritten so that it would not be necessary to read the data in the area in question that has been read once again

(so that it would not be necessary to repeat step 108) when it would be determined that the data must be rewritten actually (for example, when the threshold value p is reached in step 105).

[0042]

When the process shown in step 107 is not performed, it will be more cost effective if the refresh is performed, not by the procedure in which all the data in the area to be refreshed is read out once and then rewritten, but by the procedure in which the data is read and then written at once by small blocks (for example, by 100 tracks/block instead of 4000 - 5000 tracks/area) repeatedly, because it is not necessary to prepare the large-capacity memory to store the read data until it is rewritten in the latter case.

[0043]

If it is determined that the data must be refreshed in step 109 and the rewrite is performed actually in step 110, the number of write on the even-numbered tracks can be reset to 1 (111).

[0044]

On the other hand, in the case where the number of write exceeds the threshold value p but it is determined that the refresh is still not needed in step 109 and the rewrite process is not performed, when the data is written

on the even-numbered tracks in the area y in question next time, it will be determined that the refresh is needed again. Here, the checking procedure by reading the data before rewriting as shown in step 107 may be performed. More specifically, the procedure in which the refresh process is not performed soon after the number of write reaches the threshold value p but it is determined whether the refresh is needed or not after the data is read out once may be adopted. In this case, if the value of even [y] remains unchanged, even [y] is always not less than p until the data in the area in question is refreshed and, therefore, every time when the data is written on the even-numbered tracks in the area in question at least once, the read checking procedure for determining whether the refresh is needed must be performed inevitably.

[0045]

It typically does not happen that the data on a track, which has been able to be read without problems, becomes unreadable suddenly after one write operation on the adjacent tracks. It therefore seems to be no problem that it is not determined whether the refresh operation is needed or not for the predetermined number of times after the read checking procedure is performed (in step 109) once.

[0046]

Therefore, after it is determined whether the

refresh is needed or not once in steps 108 and 109, the process is configured so that the read operation to check whether the refresh is needed or not is not performed until the write operation is performed over r times. Such configuration is implemented in step 112. As shown in step 112, by subtracting r from the value of even $[y]$ in advance, the condition even $[y] \geq p$ is not satisfied in step 105 until the data is written on the even-numbered tracks in the area y over r times. Therefore, the read checking procedure to determine whether the refresh is needed or not is not performed meanwhile. This inhibits that the read checking procedure (108) to determine whether the refresh is needed or not is performed too frequently. More specifically, assuming that $p = 1000$ in step 105 and $r = 100$ in step 112, even $[y] = 1000 - 100 = 900$ is obtained in step 112 and even $[y] = 900$ is obtained in step 104. Therefore, the condition even $[y] \geq p$ is not satisfied in step 105 while the data is written on the even-numbered tracks over 100 times and, consequently, it is not necessary to read the odd-numbered tracks in the area y (step 108) meanwhile.

[0047]

Since optimal values for p , q and r as described above may vary depending on the combination of the magnetic disks and heads used actually or the write current value,

it is preferable that the values of p, q and r may be variable parameters defined separately for each disk surface or each area.

[0048]

In Fig. 1, if the track x is an odd-numbered track, the process goes from step 101 to step 113 but, after that, the process is similar to the one described with reference to the left side of Fig. 1, although the even-numbered tracks are substituted by the odd-numbered tracks.

[0049]

As described above, the present invention principally provides the configuration and functions or operations as follows: That is, the number of write is counted and, if the number of write exceeds a predetermined number, the refresh operation to read once and then write the data is performed. Here, logical track numbers are assigned to alternate physical tracks and the number of write is counted separately for even-numbered and odd-numbered physical tracks.

[0050]

By adopting such configuration, it is needed only to refresh the data on either the even-numbered or the odd-numbered physical tracks and, therefore, the time required to refresh the data can be reduced. Further, since the logical track numbers are assigned alternately, the

phenomenon in which the adjacent tracks are deleted does not occur until half of the capacity of the entire magnetic disk is used.

[0051]

Still further, by dividing the disk surfaces of the recording media into a plurality of areas and counting the number of write for each of the plurality of areas, the data subject to the refresh operation can be restricted and the time required for the refresh operation can be saved.

[0052]

[Effect of the Invention]

According to the present invention, the phenomenon in which the data is deleted by the leakage magnetic field from the side surfaces of the write head can be prevented until half of the entire capacity of the magnetic disk is used.

[0053]

Further, when it is necessary to refresh the data after more than half of the entire capacity has been used, the data can be recovered for a shorter time and more effectively.

[Brief Description of the Drawings]

[Fig. 1]

Fig. 1 is a flow chart illustrating a procedure for refreshing data when the data is written on a track x in an

area y on a magnetic disk surface in a magnetic disk device according to an embodiment of the present invention.

[Fig. 2]

Fig. 2 is a diagram schematically showing a mechanism of a typical magnetic disk device.

[Fig. 3]

Fig. 3 is a conceptual diagram showing placement of tracks on a typical magnetic disk.

[Fig. 4]

Fig. 4 is a diagram showing a configuration required for reading and writing the data in a typical magnetic disk device.

[Fig. 5]

Fig. 5 is a diagram schematically showing a structure of a write head in a typical magnetic disk device.

[Fig. 6]

Fig. 6 is a drawing showing an example of a correspondence between physical track numbers and logical track numbers on a magnetic disk.

[Fig. 7]

Fig. 7 is a drawing showing another example of a correspondence between physical track numbers and logical track numbers on a magnetic disk.

[Fig. 8]

Fig. 8 is a diagram showing an exemplary

configuration in which a magnetic disk surface is divided into a plurality of areas according to this embodiment.

[Fig. 9]

Fig. 9 is a diagram showing a state in which the number of write on both even- or odd-numbered physical tracks is recorded on a memory for each area on a given magnetic disk surface according to this embodiment.

[Explanation of Reference Numerals]

201 Magnetic disk

202 Magnetic head

203 Spindle

204 Arm

205 VCM

301 Magnetic disk

302 Tracks on magnetic disk

303 Track pitch

401 Host computer

402 HDC

403 Data buffer

404 Servo controller

405 R/W channel

406 R/W amplifier

407 Write head

408 Read head

409 Magnetic disk

410 MPU

501 Write head lower magnetic pole piece

502 Write head upper magnetic pole piece

503 Write head coil

504 Write head floating upper surface portion

505 Write head side surface portions

601, 701 Track on magnetic disk

Fig. 1

101: Track x = even numbered

108: Read data on odd-numbered tracks in area y

109: the number of retry $\geq q$

110: Write data on odd-numbered tracks in area y

エリア y の偶数トラックをリード: A: Read data on even-numbered tracks in area y

リトライ発生数 $\geq q$: Write data on even-numbered tracks in area y

Fig. 3

データ: Data

サーボ: Servo

トラックピッチ: Track pitch

Fig. 4

401: Host computer

403: Data buffer

404: Servo controller

405: R/W channel

406: R/W amplifier

Fig. 6

物理トラック番号: Physical track number

論理トラック番号: Logical track number

Fig. 8

エリア番号: Area number

Fig. 9

エリア番号: Area number

物理偶数トラックライト回数: Number of write on even-numbered
physical tracks

物理奇数トラックライト回数: Number of write on odd-numbered
physical tracks

[What is Claimed is]

[Claim 1]

A magnetic disk device comprising:
a magnetic disk for recording data;
a magnetic head for writing or reading the data on
or from the magnetic disk; and
a write and read circuit, connected to the magnetic
head, for writing or reading the data;
wherein the data is written or read to or from a
plurality of tracks in the form of concentric circles
disposed on the magnetic disk; and
wherein the number of write of data on a given track
is acquired and it is detected that the number of write
reaches a predetermined number, and
based on the detection, data on tracks adjacent to
the given track is read out once and, then, the read-out
data is rewritten to the adjacent tracks.

[Claim 2]

A magnetic disk device comprising:
a magnetic disk for recording data;
a magnetic head for writing or reading the data on
or from the magnetic disk; and
a write and read circuit, connected to the magnetic

head, for writing or reading the data;

wherein the data is written or read to or from a plurality of tracks in the form of concentric circles disposed on the magnetic disk; and

wherein all tracks on the magnetic disk are divided into a plurality of areas,

the number of write of data on even-numbered physical tracks in the divided areas is acquired and it is detected that the number of write reaches a predetermined number, and

based on the detection, data on odd-numbered physical tracks in the divided areas is read out once and, then, the read-out data is rewritten on the odd-numbered tracks.

[Claim 3]

A magnetic disk device comprising:

a magnetic disk for recording data;

a magnetic head for writing or reading the data on or from the magnetic disk; and

a write and read circuit, connected to the magnetic head, for writing or reading the data;

wherein the data is written or read to or from a plurality of tracks in the form of concentric circles disposed on the magnetic disk; and

wherein all tracks on the magnetic disk are divided

into a plurality of areas,

the number of write of data on odd-numbered physical tracks in the divided areas is acquired and it is detected that the number of write reaches a predetermined number, and

based on the detection, data on even-numbered physical tracks in the divided areas is read out once and, then, the read-out data is rewritten on the even-numbered tracks.

[Claim 4]

A magnetic disk device according to claim 2, wherein, when the read-out data is rewritten on the odd-numbered tracks, the number of write on the even-numbered physical tracks is cleared.

[Claim 5]

A magnetic disk device according to claim 3, wherein, when the read-out data is rewritten on the even-numbered tracks, the number of write on the odd-numbered physical tracks is cleared.

[Claim 6]

A magnetic disk device according to any one of claims 1 to 5, wherein, when data is written on the tracks, the data is written on alternate physical tracks and every other track is skipped and, after the data is written on half of all the tracks, the data is written on the skipped

tracks.

[Claim 7]

A magnetic disk device according to any one of claims 1 to 6, wherein, when it is detected that the number of write reaches the predetermined number, the data to be rewritten is read and, then, if the number of retry for the data reaches a predetermined value, the data is rewritten.