

PATENT SPECIFICATION

(11) 1 540 583

1 540 583

- (21) Application No. 26485/75 (22) Filed 21 June 1975
(21) Application No. 7366/76 (22) Filed 20 March 1975
(62) Divided out of No. 1540582
(23) Complete Specification filed 9 March 1976
(44) Complete Specification published 14 Feb. 1979
(51) INT CL² G01N 23/06 G01T 1/20
(52) Index at acceptance

H4F D12X D18K D18X D27K D27L D27M D30K D53D
D56X D83B L

(72) Inventor CHRISTOPHER ARCHIBALD GORDON LE-MAY

(54) IMPROVEMENTS IN OR RELATING TO RADIOGRAPHY



(71) We, E.M.I. LIMITED, a British Company of Blyth Road, Hayes, Middlesex, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

The present invention relates to radiographic apparatus of the kind arranged to provide a representation of the variation of absorption with position across a planar slice of a body with respect to penetrating radiation.

In our co-pending Patent Application No. 41191/73 (Serial No. 1,478,124) there is described an apparatus for that purpose which includes a source of penetrating radiation arranged to provide a fan-shaped spread of radiation lying in the plane of the slice. Suitable collimators are provided to define a plurality of pencil beams from that spread and an array of detectors is arranged to measure the intensity of each of those beams after passage through the body. The detectors are required to provide output signals indicative of the absorption suffered by the radiation over a large number of paths through the body. For that purpose the source and detectors are reciprocated in the plane of the slice and orbited about a common axis normal to that plane. The output signals are processed by any suitable method, for example the convolution method described in co-pending application No. 19528/73 (Serial No. 1,471,531), to provide the desired representation.

Further developments of the apparatus are described in our co-pending application No. 26811/73 (Serial No. 1,475,303) and in application No. 4562/74 (Serial No. 1,493,594). According to those specifications the fan-shaped spread of radiation subtends an angle sufficient to include the whole region of interest in the plane of the slice so that a complete scan

can be effected solely by orbiting the source and detectors about the common axis.

It is an object of the present invention to provide an alternative apparatus for the same purpose.

According to the invention there is provided an apparatus for examining a body by means of penetrating radiation including a source means arranged to irradiate the body with a planar spread of said radiation originating from a position outside the body, detector means arranged to detect the radiation to provide output signals, relating to absorption of the radiation by the body, for processing to provide a representation of the distribution of absorption in a substantially planar section of the body and scanning means arranged to scan the planar spread of radiation in relation to the body so as to irradiate the said section along a plurality of beam paths passing through the body from a plurality of positions of the origin of the radiation wherein said detector means comprises a plurality of detector devices of which a predetermined plurality, less than the first mentioned plurality, are irradiated by the said spread at any time and wherein the scanning means is arranged to traverse the spread of radiation along the detector devices.

According to an optional feature of the invention the detector devices are interconnected in groups in each of which not all devices are irradiated at any time so that the outputs of all devices in any group are provided as one output channel for the said processing.

In order that the invention may be clearly understood and readily carried into effect examples thereof will now be described with reference to the accompanying drawings of which:

Figure 1a and 1b show in simplified form, in end and side elevation respectively, an apparatus incorporating the invention.

50

55

60

65

70

75

80

85

90

Figure 2 shows a detector arrangement for one example of the invention,

Figure 3 shows an arrangement for an alternative embodiment of the invention and,

Figure 4 shows in block diagrammatic form a circuit used for processing data derived from the apparatus.

The apparatus is shown in a simplified form in end elevation in Figure 1a and in side elevation in Figure 1b and comprises a rotary member 1, which is rotatable about an aperture 2 in which the body 3 of a patient to be examined can be inserted. The body 3 shown in transverse section is supported on a suitably shaped bed 4 also shown in transverse section. A material 5 having an absorption to the radiation similar to body tissue is positioned between the body 3 and the bed 4 to substantially exclude air from the gap therebetween and is extended partly about the body to provide an approximately circular cross-section to the radiation. The body is retained firmly in the desired position by means such as a restraining strap 6. If desired a more rigid arrangement such as that shown in our co-pending application No. 41191/73 (Serial No. 1,478,124) can be used. Means for properly positioning bed 4 may take any suitable form and are indicated generally at 7. The rotary member 1 is rotatably mounted on a fixed frame 8, having an aperture at least commensurate with aperture 2. Member 1 is rotated by means of a gear wheel 9a journaled in frame 8 and driven by a motor 10. The gear wheel 9a engages gear teeth, not shown, formed around the periphery of member 1. Other, non driven, gear wheels 9, also journaled in frame 8, are also provided to properly support rotary member 1 and bearings 11 are provided to restrict axial motion. A light source/photocell device 12 fixed to main frame 18 co-operates with a graticule 13 to provide pulses indicative of the progress of the rotary motion. Graticule 13 is formed around the entire circumference of member 1 and comprises a transparent substrate having opaque markings formed thereon. By interrupting the light path between light source and photocell these markings provide the desired pulses. Other means of providing suitable pulses may of course be used.

The rotatable member 1 carries a source 14 of penetrating radiation. This may be of the type in which a substantially point source 15 of X-rays 16 is scanned over an elongated anode 17 by the scanning of an incident electron beam by means not shown. The X-rays 16, which are confined to a fan-shaped spread by suitable collimator means 18, are, after passage

through the body, incident on a detector means 19. Detector means 19 will be described in greater detail hereinafter.

Also carried on member 1 is the collimator arrangement 18. This comprises in this example a plurality of thin parallel plate collimators, made of molybdenum or other suitable material, which are arranged to define the X-rays 16 into a narrow fan of X-rays directed at detector 19 and having the same angular spread for all positions of the spot 15. Other collimators, not shown, restrict the X-rays to the plane of the slice to be examined. The collimators are shown in simplified form in Figure 1 and in one practical example are plates two thousands of an inch (thou) thick, 900 thou long and at 18 thou spacing. Considering a typical dimension of X-ray spot 15 on the anode 17 of the tube 14 to be 80 thou diameter it will be apparent that the fan of X-rays is formed by four or five collimator slits so that the motion of the X-ray fan, on detector 19, in response to movement of spot 15 is substantially steady. It should be noted that the intensity distribution across the fan, produced by the collimator arrangement, should be taken into account in processing. A collimator arrangement of the dimensions given can be used to give a fan of about 2° extent if placed at a suitable distance from the source. In this example of the invention a fan of substantially 1.8° is considered.

The detector means 19 comprises a strip of individual detectors such as scintillator crystals or photodiodes, lying in the plane of the slice to be examined so as to intercept substantially all of the X-rays 16 for all positions of the spot 15. As shown in Figure 1a this strip of detectors is only irradiated over a small portion at any time. For the purposes of explanation it will be assumed that 3 cm of the strip is so irradiated at any time. The detector comprises detector elements each covering 1 mm of the strip so that thirty such elements supply data across the 3 cm of the fan. This data corresponds to thirty individual beam paths in the fan. The entire detector is typically 30 cm long including 300 detector elements. In this example the detectors are scintillator crystals co-operating with photomultipliers indicated generally at 20.

In operation the X-ray spot is scanned steadily across the anode 17 of tube 14 and correspondingly the fan of X-rays 16 scans in a plane across body 3 and surrounding materials and long detector strip 19. In this example the irradiated region of the detectors moves in the same direction as and approximately parallel to the source spot 15 as a result of the form of collimators 18 used. The outputs of the detector elements are integrated for a period in

which the irradiated region of the detectors is moved 1 mm so that each detector provides one datum for a respective beam path. For the immediately following integration interval the data are obtained for elements displaced one place in the direction of scan i.e. with an extra element at one end of the irradiated region and one less at the other. The detector elements irradiated are thus progressively changed as the scan progresses.

It can be seen that by this means the information relating to any one small region of the body is obtained by many detectors so that the effect of relative detector errors is reduced.

To irradiate the body over a sufficient number of beam paths source 14 and detector means 19 are in this example orbited about an axis 21 perpendicular to the slice of the body 3 to be examined. This may be achieved in steps between each scan of the spot 15. However, since the angle of the fan is 1.8° this will be the required orbital movement for one lateral scan and it is sufficiently small to be provided by a continuous orbital movement without significant distortion or misplacement of the beam paths.

As mentioned hereinbefore, at any time only a small proportion of the detector elements of detector means 19 are irradiated, typically thirty out of three hundred. That situation is utilised in the detector arrangement shown in Figure 2. The figure shows, for the sake of clarity, a simplified arrangement for which detector means 19 comprises twenty five detector elements, in the form of scintillation crystals, of which only five are irradiated at any time. The intensity of light emitted by the scintillators is measured by five photomultipliers 20, and 20, each of which receives light from five detector elements through individual light guides 22. The light guides are represented in the Figure by single lines. However it will be understood that each light guide in practice receives light from one entire face of a crystal, the other faces being silvered to prevent loss of light. The light guides 22 are arranged so that the photomultipliers receive light from detector elements in interlaced manner. In this example each receives light from elements spaced five positions apart. It will be seen from Figure 2 that, although each photomultiplier receives light from five detector elements, only one of these will be irradiated at any time. Thus, for the position of X-ray fan 16 shown in Figure 2, each photomultiplier receives light along the first light guide from the right, at the multiplier, and no light along the others. As the fan moves one element to the left only the light to photomultiplier 20, changes so

that light is received along the second light guide. It will be apparent that, in this manner, the twenty five detector elements can be covered by the five multipliers if the data from these multipliers is appropriately allocated in the processing used. Other numbers of detector elements and photomultipliers may be used in a similar manner.

Instead of using five different photomultipliers a five, or more, channel photomultiplier can be used. This may be of the type described in our co-pending application No. 9747/73 (Serial No. 1,470,162). This may equally well be a three hundred channel photomultiplier if desired. In that case the photomultiplier can be placed close to the detector elements with short, or no light guides so that each element would at all times supply light to one photomultiplier channel. However, since, as described above, only a small number of detector elements are irradiated at any time a grouping similar to that of Figure 2 can be effected by joining the photomultiplier channel anodes in groups internally. By this means the number of output connections required would be reduced, simplifying construction problems. As in the previous example other numbers of irradiated elements and groupings may be employed as desired.

It should be understood that Figure 2 is illustrative of a manner of organising the detector outputs. However other positions, for example of photomultipliers 20, can be adopted for convenience of construction.

As mentioned hereinbefore large numbers of detector elements are employed in a practical arrangement, typically 300 arranged in six cycles of fifty elements. Fifty detector elements, say 1 mm apart, can be irradiated by the narrow fan of X-rays, the individual fifty beam paths being narrow enough to give the desired spatial resolution within the body. This results, however, in a large quantity of output data and, since the angular resolution so obtained is unnecessarily good, some of this data may be combined to give reduced angular resolution. The arrangement in this example is that data for beam paths passing through substantially the same parts of the body should be combined. In practice this means that data for each beam in the fan is combined with data obtained from beams incident on a number of, say three, adjacent detectors and passing through the same predetermined point in the body. A time delay of τ seconds is applied between those adjacent detectors. The delay τ is equal to the time which elapses between the passage of a beam incident on one detector through the predetermined point and the passage of

18 19

70

75

80

85

90

95

100

105

110

115

120

125

130

a beam incident on the next detector through the same point. The data for the first detector is delayed τ seconds and added to that of the second and the two are delayed by a further τ seconds and added to the data for the third detector. The arrangement is assumed to be that employing continuous orbital motion thus the three beam paths for which data is combined are not strictly parallel but give a composite beam path which is narrower at the centre of the body and slightly thicker at the edges. For three beam paths this does not give significant error but allows a reduction of storage to one third of that otherwise required.

In an alternative mode of operation of apparatus such as that of Figure 1 the X-ray spot scan and collimators 18 can be arranged so that the fan effectively rotates about the body, with the region of irradiated detectors moving laterally in the opposite direction to the source spot. If the extent of anode 17 and detectors 19 is sufficient the orbital motion may be dispensed with. In that case the organisation of the data can be similar to that described in our copending application No. 4562/74 (Serial No. 1,493,594). As a further alternative the scanning X-ray source can be replaced by a conventional source such as a rotating anode tube and the scan of the fan of X-rays relative to the detectors provided solely by orbital and/or lateral scanning motions of that source.

It should be noted that, in the arrangements described, afterglow in detector elements no longer being irradiated can still be intercepted by the photomultipliers and introduce some noise into the data. For this reason scintillator crystals having low afterglow should be employed. The problem can be alleviated by the use of other detectors such as semiconductor diodes, which may be germanium photodiodes. Gas filled counters or other detectors may also be used. In those cases the grouping, if desired, may be suitable multiplexing of the output signals. Alternatively shutter means or similar may be provided to intercept the emitted light between the crystals and the associated photomultipliers.

Figure 3 shows a development, of the arrangement described, for which the orbital movement, of X-ray source 14 and detector means 19, is not required. Aperture 2 is surrounded by a ring of individual scanning X-ray tubes 17 of which the glass envelopes, indicated at 23 are arranged to adjoin. Inside the ring of tubes 14 there is provided a ring of collimators 18. X-ray tubes 14 having anodes 17 and collimators 18 are essentially similar to those described in relation to Figure 1,

tubes 14 being fixed in relation to the body in aperture 2. Outside of tubes 14 there is provided a further ring comprising a plurality of detector means 19 each of which is as described hereinbefore.

At any time one of the tubes 14 is in operation, the X-rays being formed into a fan by collimators 18 nearest to the tube and thereafter passing through the body in aperture 2 to be received at a detector means 19 opposite. It will be understood that for this purpose the ring of detector means 19 must be set in a sufficiently different plane from tubes 14 for the X-rays to reach the detectors unobstructed. This is a source of slight error in the desired data but such errors largely cancel for the data obtained from the 180° displaced detector. Collimators 18 may be arranged so that the beam passes through them after passing through the aperture 2 as well as before.

In operation the X-ray tubes are operated in sequence so that the X-ray spot on the anode orbits in effect around the body in aperture 2. The ring of collimators 18 is arranged to rotate around aperture 2 but at a relatively slower rate than the rotation of the Figure 1 arrangement. The angular velocity desired is such that the collimators move through an angle slightly less than the beam spread angle, of the fan of X-rays 16, during one revolution of the X-ray spot. In the example shown in Figure 3 the collimator is in ten sections so that, without rotation, the angle of the centre beam of the fan would change by 36° when the spot moves from one section to the next. For the 1.8° fan of the example the collimators rotate 1.8° in one spot revolution so that, when the spot returns to the same collimator section it begins to fill in the missing 36°. Thus twenty revolutions of the spot are required to fill in all missing values. The exact number used is tailored to give a suitable degree of overlap between fan beams for adjacent positions to reduce noise problems. It will be apparent that this collimator movement changes the fan position by 0.18° as it crosses each section but such a small error can be disregarded. It should be noted that any detectors not being irradiated may be switched out of the circuit by any suitable means to reduce noise problems further.

In an alternative mode of operation of the Figure 3 arrangement the fan of radiation may be of sufficient extent to encompass the entire region of interest in the body. In that case, in conjunction with larger source and detector sectors, the operation would be such that the position of the group of detectors irradiated by the fan orbits in effect about the body in the same direction as the source spot.

Figure 4 shows in simplified block

20 21

diagrammatic form an arrangement for processing the output signals derived by the arrangement of Figure 2 disregarding the steps required for combining adjacent detector outputs with appropriate delays. The five photomultipliers 20, to 20, are shown although it will be understood that there may be a greater number of photomultipliers or outputs from a single photomultiplier. The signals are amplified in amplifiers 24, to 24, and integrated and converted to digital form in converters 25, to 25. The integration period is as allowed by the progress of the scan of the X-ray source spot 15 and is controlled by signals from a scan control unit 26, which also controls the source spot 15. Scan control unit 26 also receives signals from photodetector unit 12, related to the progress of the orbital scan, so that the scan of source spot 15 can be properly related to the orbital movement. The data are provided to appropriate locates in a store 28 in response to an address selector 27. The locations in store 28 are chosen so that successive outputs from each photomultiplier are applied to storage locations representing beam paths at successive angles in the fan. After the fifth such angle, in this example, the data are applied to a new location representing a parallel beam path again at the first angle and the cycle recommenced. In this way the data are allocated to storage locations representing five sets of data each for parallel beam paths at one of the angles of beams in the fan, the allocation taking into account the group of outputs shown in Figure 2. When store 28 contains data for the complete sets of beam paths, properly sorted, this data is applied to a processing unit 29 for processing, for example, as described in co-pending application No. 19528/73 (Serial No. 1,471,531) or in British Patent Specification No. 1,283,915. The processing derives absorption values for individual elements of a matrix of elements notionally delineated in the planar slice being examined. The values are then provided as signals applied to corresponding elements of a representation on a display unit 30. Unit 30 may be a cathode ray tube, line printer or other suitable output device. Alternatively it may be applied to permanent storage, not shown, for future display.

The apparatus described hereinbefore is intended to acquire all the required data in a very short time, possibly as short as one hundredth of a second for the arrangement of Figure 3. A suitable analogue to digital converter should be employed to meet such rates of acquisition. Such a counter may operate in the known manner of converting the output of a digital counter to analogue

form and counting up or down to match that output to the input voltage. However it may be divided into a plurality of sections each to converter to digital form signals between preset threshold levels, to operate at a faster rate.

It will be appreciated that the invention is not limited to the forms described hereinbefore and that other arrangements may be devised.

Our co-pending application No. 3353/75 (Serial No. 1,540,582) discloses an alternative form of the apparatus described herein.

WHAT WE CLAIM IS:—

1. An apparatus for examining a body by means of penetrating radiation including a source means arranged to irradiate the body with a planar spread of said radiation originating from a position outside the body, detector means arranged to detect the radiation to provide output signals, relative to absorption of the radiation by the body, for processing to provide a representation of the distribution of absorption in a substantially planar section of the body and scanning means arranged to scan the planar spread of radiation in relation to the body so as to irradiate the said section along a plurality of beam paths passing through the body from a plurality of positions of the origin of the radiation wherein said detector means comprises a plurality of detector devices of which a predetermined plurality, less than the first mentioned plurality, are irradiated by the said spread at any time and wherein the scanning means is arranged to traverse the spread of radiation along the detector devices.

2. An apparatus according to Claim 1 including means arranged to move the said source means in relation to the body to provide at least part of the scanning of said spread of radiation.

3. An apparatus according to either of the preceding claims in which the said detector devices are distributed along a substantially circular path around the body and arranged to be substantially stationary relative to the body in the direction of motion of the radiation and the scanning means is arranged to move the origin of the radiation around the body along a path spaced from the path on which the detector devices are disposed to traverse the radiation, after passage through the body, along the detector devices.

4. An apparatus according to either of Claims 1 or 2 including means arranged to move the said detector means relative to the body.

5. An apparatus according to any of Claims 1, 2 or 4 in which the scanning

diagrammatic form an arrangement for processing the output signals derived by the arrangement of Figure 2 disregarding the steps required for combining adjacent detector outputs with appropriate delays. The five photomultipliers 20, to 20, are shown although it will be understood that there may be a greater number of photomultipliers or outputs from a single photomultiplier. The signals are amplified in amplifiers 24, to 24, and integrated and converted to digital form in converters 25, to 25. The integration period is as allowed by the progress of the scan of the X-ray source spot 15 and is controlled by signals from a scan control unit 26, which also controls the source spot 15. Scan control unit 26 also receives signals from photodetector unit 12, related to the progress of the orbital scan, so that the scan of source spot 15 can be properly related to the orbital movement. The data are provided to appropriate locates in a store 28 in response to an address selector 27. The locations in store 28 are chosen so that successive outputs from each photomultiplier are applied to storage locations representing beam paths at successive angles in the fan. After the fifth such angle, in this example, the data are applied to a new location representing a parallel beam path again at the first angle and the cycle recommenced. In this way the data are allocated to storage locations representing five sets of data each for parallel beam paths at one of the angles of beams in the fan, the allocation taking into account the group of outputs shown in Figure 2. When store 28 contains data for the complete sets of beam paths, properly sorted, this data is applied to a processing unit 29 for processing, for example, as described in co-pending application No. 19528/73 (Serial No. 1,471,531) or in British Patent Specification No. 1,283,915. The processing derives absorption values for individual elements of a matrix of elements notionally delineated in the planar slice being examined. The values are then provided as signals applied to corresponding elements of a representation on a display unit 30. Unit 30 may be a cathode ray tube, line printer or other suitable output device. Alternatively it may be applied to permanent storage, not shown, for future display.

The apparatus described hereinbefore is intended to acquire all the required data in a very short time, possibly as short as one hundredth of a second for the arrangement of Figure 3. A suitable analogue to digital converter should be employed to meet such rates of acquisition. Such a counter may operate in the known manner of converting the output of a digital counter to analogue

form and counting up or down to match that output to the input voltage. However it may be divided into a plurality of sections each to convert to digital form signals between preset threshold levels, to operate at a faster rate.

It will be appreciated that the invention is not limited to the forms described hereinbefore and that other arrangements may be devised.

Our co-pending application No. 3353/75 (Serial No. 1,540,582) discloses an alternative form of the apparatus described herein.

WHAT WE CLAIM IS:—

1. An apparatus for examining a body by means of penetrating radiation including a source means arranged to irradiate the body with a planar spread of said radiation originating from a position outside the body, detector means arranged to detect the radiation to provide output signals, relative to absorption of the radiation by the body, for processing to provide a representation of the distribution of absorption in a substantially planar section of the body and scanning means arranged to scan the planar spread of radiation in relation to the body so as to irradiate the said section along a plurality of beam paths passing through the body from a plurality of positions of the origin of the radiation wherein said detector means comprises a plurality of detector devices of which a predetermined plurality, less than the first mentioned plurality, are irradiated by the said spread at any time and wherein the scanning means is arranged to traverse the spread of radiation along the detector devices.

2. An apparatus according to Claim 1 including means arranged to move the said source means in relation to the body to provide at least part of the scanning of said spread of radiation.

3. An apparatus according to either of the preceding claims in which the said detector devices are distributed along a substantially circular path around the body and arranged to be substantially stationary relative to the body in the direction of motion of the radiation and the scanning means is arranged to move the origin of the radiation around the body along a path spaced from the path on which the detector devices are disposed to traverse the radiation, after passage through the body, along the detector devices.

4. An apparatus according to either of Claims 1 or 2 including means arranged to move the said detector means relative to the body.

5. An apparatus according to any of Claims 1, 2 or 4 in which the scanning



means is arranged to provide at least a lateral motion of said spread of radiation relative to the body.

6. An apparatus according to any of the preceding claims in which the scanning means is arranged to provide at least a rotational motion of said spread of radiation relative to the body.

7. An apparatus according to any of the preceding claims including collimator means arranged to restrict the number of said detector devices irradiated at any time.

8. An apparatus according to Claim 7 in which the collimator means are arranged to move in relation to the detector means to change the identity of the detector devices so irradiated.

9. An apparatus according to any of the preceding claims, wherein the detector devices are interconnected in groups in each of which not all devices are irradiated at any time so that the outputs of all devices in any group are provided as one output channel for the said processing.

10. A medical radiographic device for diagnostic examination of a substantially planar slice extending through the body of a patient, comprising:

means disposed outside the patient's body for generating penetrating radiation which propagates substantially along the plane of the slice, traverses the body and emerges therefrom after suffering absorption determined at least in part by its path through the body, said radiation traversing the body along a path determined by an initial position of the origin of said radiation relative to the body;

detecting means including a plurality of detector devices at least some of which are disposed to receive and measure the intensity of radiation which has traversed the body, for said initial position, along a plurality of beam paths which are within the plane of the slice and diverge from each other in moving away from the generating means;

means for changing the position of the origin of said radiation relative to the body so that said radiation traverses the body along a succession of other beam paths determined by successive positions of the origin of said radiation relative to the body and so that at each of said positions some of said detector devices receive and measure the intensity of radiation which has traversed the body along a corresponding further plurality of diverging beam paths the arrangement being such that for each successive position of said origin at least one of the detector devices receiving the radiation did not receive radiation at the preceding position;

and means for combining the measurements of intensity obtained for a

predetermined number of said positions of said origin to form an image of the body slice being examined, said image comprising a pattern of image elements, each corresponding to an element notionally defined in the body slice.

11. A medical radiographic device according to Claim 10 in which the detecting means comprises a stationary array of detectors disposed around the body and in which the origin of the radiation moves around the body along a path spaced from the array of detectors to traverse the radiation along the detectors.

12. A medical radiographic device for diagnostic examination of a substantially planar slice extending through the body of a patient, the device comprising:

means for defining a patient position for locating the patient's body;

a source of radiation arranged to project penetrating radiation in a substantially planar swath diverging about a mean direction to propagate through the patient position and to emerge therefrom after suffering absorption determined at least in part by material traversed by the radiation within the patient position;

a plurality of detector devices some of which are irradiated by and measure the intensity of the radiation traversing the patient position;

scanning means arranged to move the said source relative to the patient position to project the penetrating radiation therethrough diverging about a different mean direction, to irradiate some of the detector devices of which at least one was not irradiated by radiation diverging about the first mean direction, and to repeat the movement of said source for a plurality of such mean directions;

and means for combining the measurements of intensity provided by detector devices irradiated by radiation traversing the patient position in said plurality of mean directions to form an image, comprising a pattern of image elements, representing the absorption of the radiation in corresponding elements notionally defined in said slice.

13. A medical radiographic device according to Claim 11 in which the detector devices are disposed along a substantially circular path about the patient position and the scanning means is arranged to move the source around the body along a path, which does not coincide with the path on which the detectors lie, to irradiate different detectors at different times.

14. Radiographic apparatus including means for generating a fan shaped distribution of penetrating radiation and for projecting it through a substantially planar slice of the body of a patient, a plurality of



22 23

7

1,540,583

7

- 5 detector devices, substantially fixed relative to said body and disposed on a substantially circular path therearound to receive radiation projected through the body and to provide output signals indicative of its intensity after suffering attenuation therein, means for moving the origin of the radiation around the body, along a path which is spaced from the circular path on which the detectors are disposed, so as to project the radiation through the body from
- 10

a plurality of positions of said origin and means for processing the output signals provided for said plurality of positions to provide a distribution of the attenuation of the radiation in said slice.

15

15. An apparatus for examining a body substantially as herein described with reference to the accompanying drawings.

A. B. LOGAN,
Chartered Patent Agent.

Printed for Her Majesty's Stationery Office, by the Courier Press, Leamington Spa, 1979
Published by The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.

