

INTEGRATION OF MOLTEN CARBONATE FUEL CELLS IN A REFINERY  
SETTING

FIELD OF THE INVENTION

[0001] In various aspects, the invention is related to chemical production and/or power generation processes integrated with the use of molten carbonate fuel cells.

BACKGROUND OF THE INVENTION

[0002] Molten carbonate fuel cells utilize hydrogen and/or other fuels to generate electricity. The hydrogen may be provided by reforming methane or other reformable fuels in a steam reformer that is upstream of the fuel cell or within the fuel cell. Reformable fuels can encompass hydrocarbonaceous materials that can be reacted with steam and/or oxygen at elevated temperature and/or pressure to produce a gaseous product that comprises hydrogen. Alternatively or additionally, fuel can be reformed in the anode cell in a molten carbonate fuel cell, which can be operated to create conditions that are suitable for reforming fuels in the anode. Alternately or additionally, the reforming can occur both externally and internally to the fuel cell.

[0003] Traditionally, molten carbonate fuel cells are operated to maximize electricity production per unit of fuel input, which may be referred to as the fuel cell's electrical efficiency. This maximization can be based on the fuel cell alone or in conjunction with another power generation system. In order to achieve increased electrical production and to manage the heat generation, fuel utilization within a fuel cell is typically maintained at 70% to 75%.

[0004] U.S. Published Patent Application 2011/0111315 describes a system and process for operating fuel cell systems with substantial hydrogen content in the anode inlet stream. The technology in the '315 publication is concerned with providing enough fuel in the anode inlet so that sufficient fuel remains for the oxidation reaction as the fuel approaches the anode exit. To ensure adequate fuel, the '315 publication provides fuel with a high concentration of H<sub>2</sub>. The H<sub>2</sub> not utilized in the oxidation reaction is recycled to the anode for use in the next pass. On a single pass basis, the H<sub>2</sub> utilization may range from 10% to 30%. The '315 reference does not describe significant reforming within the anode, instead relying primarily on external reforming.

[0005] U.S. Published Patent Application 2005/0123810 describes a system and method for co-production of hydrogen and electrical energy. The co-production system

comprises a fuel cell and a separation unit, which is configured to receive the anode exhaust stream and separate hydrogen. A portion of the anode exhaust is also recycled to the anode inlet. The operating ranges given in the '810 publication appear to be based on a solid oxide fuel cell. Molten carbonate fuel cells are described as an alternative.

**[0006]** U.S. Published Patent Application 2003/0008183 describes a system and method for co-production of hydrogen and electrical power. A fuel cell is mentioned as a general type of chemical converter for converting a hydrocarbon-type fuel to hydrogen. The fuel cell system also includes an external reformer and a high temperature fuel cell. An embodiment of the fuel cell system is described that has an electrical efficiency of about 45% and a chemical production rate of about 25% resulting in a system coproduction efficiency of about 70%. The '183 publication does not appear to describe the electrical efficiency of the fuel cell in isolation from the system.

**[0007]** U.S. Patent 5,084,362 describes a system for integrating a fuel cell with a gasification system so that coal gas can be used as a fuel source for the anode of the fuel cell. Hydrogen generated by the fuel cell is used as an input for a gasifier that is used to generate methane from a coal gas (or other coal) input. The methane from the gasifier is then used as at least part of the input fuel to the fuel cell. Thus, at least a portion of the hydrogen generated by the fuel cell is indirectly recycled to the fuel cell anode inlet in the form of the methane generated by the gasifier.

**[0008]** An article in the Journal of Fuel Cell Science and Technology (G. Manzolini *et. al.*, *J. Fuel Cell Sci. and Tech.*, Vol. 9, Feb 2012) describes a power generation system that combines a combustion power generator with molten carbonate fuel cells. Various arrangements of fuel cells and operating parameters are described. The combustion output from the combustion generator is used in part as the input for the cathode of the fuel cell. One goal of the simulations in the Manzolini article is to use the MCFC to separate CO<sub>2</sub> from the power generator's exhaust. The simulation described in the Manzolini article establishes a maximum outlet temperature of 660° C and notes that the inlet temperature must be sufficiently cooler to account for the temperature increase across the fuel cell. The electrical efficiency (i.e. electricity generated/ fuel input) for the MCFC fuel cell in a base model case is 50%. The

electrical efficiency in a test model case, which is optimized for CO<sub>2</sub> sequestration, is also 50%.

[0009] An article by Desideri *et al.* (*Intl. J. of Hydrogen Energy*, Vol. 37, 2012) describes a method for modeling the performance of a power generation system using a fuel cell for CO<sub>2</sub> separation. Recirculation of anode exhaust to the anode inlet and the cathode exhaust to the cathode inlet are used to improve the performance of the fuel cell. The model parameters describe an MCFC electrical efficiency of 50.3%.

#### SUMMARY OF THE INVENTION

[0010] In an aspect, a method for generating hydrogen in a refinery is provided. The method includes introducing a fuel stream comprising a reformable fuel into the anode of a molten carbonate fuel cell, an internal reforming element associated with the anode, or a combination thereof; receiving one or more CO<sub>2</sub>-containing streams derived from one or more first refinery processes; introducing a cathode inlet stream comprising CO<sub>2</sub> and O<sub>2</sub> into the cathode of the fuel cell, the cathode inlet stream comprising at least a portion of the one or more CO<sub>2</sub>-containing streams; generating electricity within the molten carbonate fuel cell; withdrawing, from an anode exhaust, one or more gas streams comprising H<sub>2</sub>, H<sub>2</sub> and CO, or a combination thereof; and delivering the one or more gas streams withdrawn from the anode exhaust to one or more second refinery processes.

[0011] In an additional aspect, the withdrawing, from the anode exhaust, one or more gas streams comprising H<sub>2</sub>, H<sub>2</sub> and CO, or a combination thereof comprises: generating the anode exhaust; and separating the anode exhaust to form at least one gas stream having a CO<sub>2</sub> content greater than a CO<sub>2</sub> content of the anode exhaust, and the one or more gas streams comprising H<sub>2</sub>, H<sub>2</sub> and CO, or a combination thereof, the one or more gas stream having a CO<sub>2</sub> content less than the CO<sub>2</sub> content of the anode exhaust.

[0012] In an additional aspect, the withdrawing, from the anode exhaust, one or more gas streams comprising H<sub>2</sub>, H<sub>2</sub> and CO, or a combination thereof comprises: generating the anode exhaust; separating CO<sub>2</sub> and H<sub>2</sub>O from the anode exhaust to form a first gas stream having a first volume percent of H<sub>2</sub>; separating a second gas stream having a second volume percent of H<sub>2</sub> from the first gas stream, the second volume percent of H<sub>2</sub> being greater than the first volume percent of H<sub>2</sub>; compressing the first gas stream

to a first pressure; and compressing the second gas stream to a second pressure, the second pressure being greater than the first pressure.

[0013] In another aspect, a method for generating hydrogen in a refinery is provided. The method includes introducing a fuel stream comprising a reformable fuel into the anode of a molten carbonate fuel cell, an internal reforming element associated with the anode, or a combination thereof; introducing a cathode inlet stream comprising CO<sub>2</sub> and O<sub>2</sub> into the cathode of the fuel cell; generating electricity within the molten carbonate fuel cell; generating an anode exhaust comprising H<sub>2</sub> and CO<sub>2</sub>; separating the anode exhaust to form at least one gas stream having a CO<sub>2</sub> content greater than a CO<sub>2</sub> content of the anode exhaust, and one or more gas streams having a CO<sub>2</sub> content less than the CO<sub>2</sub> content of the anode exhaust; and delivering the one or more gas streams having a CO<sub>2</sub> content less than the CO<sub>2</sub> content of the anode exhaust to one or more second refinery processes.

[0014] This application is related to 21 other co-pending PCT applications, filed on even date herewith, and identified by the following Attorney Docket numbers and titles: 2013EM104-WO entitled “Integrated Power Generation and Carbon Capture using Fuel Cells”; 2013EM107-WO entitled “Integrated Power Generation and Carbon Capture using Fuel Cells”; 2013EM108-WO entitled “Integrated Power Generation and Carbon Capture using Fuel Cells”; 2013EM109-WO entitled “Integrated Power Generation and Carbon Capture using Fuel Cells”; 2013EM272-WO entitled “Integrated Power Generation and Chemical Production using Fuel Cells”; 2013EM273-WO entitled “Integrated Power Generation and Chemical Production using Fuel Cells at a Reduced Electrical Efficiency”; 2013EM274-WO entitled “Integrated Power Generation and Chemical Production using Fuel Cells”; 2013EM277-WO entitled “Integrated Power Generation and Chemical Production using Fuel Cells”; 2013EM278-WO entitled “Integrated Carbon Capture and Chemical Production using Fuel Cells”; 2013EM279-WO entitled “Integrated Power Generation and Chemical Production using Fuel Cells”; 2013EM285-WO entitled “Integrated Operation of Molten Carbonate Fuel Cells”; 2014EM047-WO entitled “Mitigation of NO<sub>x</sub> in Integrated Power Production”; 2014EM048-WO entitled “Integrated Power Generation using Molten Carbonate Fuel Cells”; 2014EM049-WO entitled “Integrated of Molten Carbonate Fuel Cells in Fischer-Tropsch Synthesis”; 2014EM050-WO

entitled “Integrated of Molten Carbonate Fuel Cells in Fischer-Tropsch Synthesis”; 2014EM051-WO entitled “Integrated of Molten Carbonate Fuel Cells in Fischer-Tropsch Synthesis”; 2014EM052-WO entitled “Integrated of Molten Carbonate Fuel Cells in Methanol Synthesis”; 2014EM054-WO entitled “Integrated of Molten Carbonate Fuel Cells for Synthesis of Nitrogen Compounds”; 2014EM055-WO entitled “Integrated of Molten Carbonate Fuel Cells with Fermentation Processes”; 2014EM056-WO entitled “Integrated of Molten Carbonate Fuel Cells in Iron and Steel Processing”; and 2014EM057-WO entitled “Integrated of Molten Carbonate Fuel Cells in Cement Processing”. Each of these co-pending PCT applications is hereby incorporated by reference herein in its entirety.

#### BRIEF DESCRIPTION OF THE FIGURES

[0015] FIG. 1 schematically shows an example of a configuration for molten carbonate fuel cells and associated reforming and separation stages.

[0016] FIG. 2 schematically shows another example of a configuration for molten carbonate fuel cells and associated reforming and separation stages.

[0017] FIG. 3 schematically shows an example of the operation of a molten carbonate fuel cell.

[0018] FIG. 4 schematically shows an example of a combined cycle system for generating electricity based on combustion of a carbon-based fuel.

[0019] FIG. 5 schematically shows an example of a combined cycle system for generating electricity based on combustion of a carbon-based fuel.

[0020] FIG. 6 schematically shows an example of a system for generating hydrogen and electrical power in a refinery setting.

[0021] FIG. 7 shows an example of process flows in a system for generating hydrogen and electrical power in a refinery setting.

[0022] FIG. 8 schematically shows an example of a system for generating hydrogen and electrical power in a refinery setting.

[0023] FIG. 9 shows an example of process flows in a system for generating hydrogen and electrical power in a refinery setting.

## DETAILED DESCRIPTION OF THE EMBODIMENTS

### Overview

[0024] In various aspects, the operation of molten carbonate fuel cells can be integrated with a variety of chemical and/or materials production processes. The production processes can correspond to production of an output from the molten carbonate fuel cells, or the production process can consume or provide one or more fuel cell streams.

### Integration of MCFC with Refinery Hydrogen Use and “Carbon-Free” Hydrogen

[0025] Hydrogen can be used within the refinery for a variety of processes. Most refineries both generate hydrogen in some processes (for example, gasoline reforming to produce aromatics) and use hydrogen for other processes (for example, sulfur removal from gasoline and diesel blending streams). Additionally, refineries can have a large number of boilers, furnaces and/or other systems for heating reactors that require energy. These heating and/or energy generation systems generally do not utilize hydrogen, because hydrogen can typically be more valuable than other fuel sources, and because most refineries are, on an overall basis, net importers of hydrogen. Generally, hydrogen import can be done by building on-site, and/or by accessing nearby/pipeline sources of hydrogen to bring the overall refinery into balance.

[0026] Since most refinery processes typically take place at elevated temperature and usually require heat provided by boilers of various sorts (as well as process steam), refineries generally contain large numbers of heating systems. This can result in a large number of point sources of CO<sub>2</sub> that can vary widely in size. Some, like cat cracking, can produce large amounts of CO<sub>2</sub>, while others can produce modest amounts. Each of these point sources of CO<sub>2</sub> can contribute to the overall refinery CO<sub>2</sub> production. As most integrated refineries are typically about 70-95% thermally efficient on an overall basis at converting crude oil to products, typically about 5-30% of the carbon entering the refinery in crude oil or other inputs can be exhausted (to the air) as CO<sub>2</sub>. Reduction of these emissions can improve refinery greenhouse gas emissions per unit of product produced.

[0027] In various aspects, integration of an MCFC system with a refinery hydrogen supply can reduce, minimize, or eliminate hydrogen constraints on the overall refinery operation. Additionally or alternately, the MCFC system can use, as inputs, any of a

wide variety of off-gasses and/or other streams, as long as they can be converted to “clean” light gasses and syngas mixtures. It is noted that the light gas and/or syngas mixtures can be used without much restriction on the amount of inerts (e.g.,  $N_2$ ,  $CO_2$ , and the like, and combinations thereof) present. This “input integration” can additionally or alternately be a feature in streamlining overall efficiency in refinery operation. More generally, an MCFC system can provide a single integrated solution for up to four (or potentially more) aspects of refinery operation: production of heat for process units, production of hydrogen as a reactant, collection and sequestration of carbon, and efficient utilization of off-gasses and purge streams from various processes.

[0028] In some aspects,  $H_2$  can be used as the fuel in burners in a refinery to reduce, minimize, or eliminate  $CO_2$  emission point sources. A centralized supply of  $H_2$  for both purposes can simplify overall refinery operations by reducing the number and type of fuels and reactants – only one material can be distributed for these purposes. For example, hydrogen can be used at a variety of temperatures and pressures. An MCFC system can produce hydrogen from the anode exhaust stream after (optional) separation of water and  $CO_2$ , and further (optional) purification through any conventional method, such as pressure-swing adsorption. Once purified to typical refinery requirements, such as a purity (on a dry basis) of at least about 80 vol%  $H_2$ , or at least about 90 vol%, or at least 95 vol% or at least 98 vol%, a hydrogen-containing stream can be pressurized to an appropriate pressure for process use and piped/transported to any process. The hydrogen-containing stream may be split into multiple streams where lower purity and/or lower pressure streams can be sent to some processes or burners, while higher purity and/or higher pressure streams can be sent to other processes.

[0029] The integrated system can additionally or alternately, but typically advantageously, produce electricity. The electrical production may be used to at least partially power MCFC-related systems, such as separation systems or compressors, as well as to power at least a portion (such as up to all) of the refinery electrical demand. This electricity can be produced at relatively high efficiency with little or no transmission losses. Additionally, some or all of the electricity can optionally be direct current (DC) electricity, for instance where DC power could be preferred for the operation of some systems without the normal losses in transformers/inverters. In some aspects, an MCFC system can be sized so that at least a portion (or all) of the power

needed by the refinery can be provided, or even so that excess power can be provided. Additionally or alternately, the MCFC system can be sized to a desired  $H_2$ /heat load and/or to the electrical load. Furthermore, the system can be operated over a range of conditions, allowing for variable amounts of both electrical and hydrogen demand.

**[0030]** At least a portion of the refinery processes that produce  $CO_2$  can be collected and used as some or all of the gasses for the cathode inlet, such as a majority of the  $CO_2$  production processes or all of the  $CO_2$  production processes. If necessary, these gases can be mixed with air or other oxygen containing streams to comprise a gas mixture with both  $CO_2$  and oxygen appropriate for the cathode inlet. Fuel constituents present in these streams can typically be burned with excess oxygen/air to provide preheating of the cathode inlet. The  $CO_2$  concentration of the overall cathode inlet can vary widely, and can typically be at least about 4 vol%, such as at least about 6 vol%, at least about 8 vol%, or at least about 10 vol%. If the collected streams do not contain sufficient  $CO_2$  concentrations for MCFC operations (or even if so), then  $CO_2$  produced in the separation of the anode exhaust and/or from one or more off-gas or purge streams from the separation process can be recycled to the cathode inlet. Heating for the cathode inlet streams may come from combustion of off-gases in these streams, heat exchange, and/or addition of combustible fuel components. For example, in some aspects the MCFC system can use high carbon materials, like coke or petcoke, and/or other “bottoms” from petroleum processes, to provide heat for inlet streams where the combustion products from those materials can be used as a  $CO_2$  source for the cathode.

**[0031]** Additionally or alternately, at least a portion of the  $CO_2$  for the cathode inlet stream can be provided by a combustion turbine, such as a turbine that can use methane/natural gas as a fuel. In this type of configuration,  $CO_2$  generated by processes such as catalytic cracking may not be mitigated, but  $CO_2$  generated by heaters, boilers, and/or other burners can be reduced or minimized by using  $H_2$  generated by the MCFC.

**[0032]** The anode outlet stream can contain a large concentration of carbon dioxide as well as other syngas components. Typically,  $CO_2$  can be removed from this stream efficiently to produce a  $CO_2$  product that can be used for a variety of other processes. As a significant fraction of the carbon dioxide produced from the refinery can exit from an MCFC anode, collection of  $CO_2$  can be efficient and greatly simplified. The

collection of CO<sub>2</sub> as a single point source can then be used for other operations (e.g., EOR if near oil fields, re-injection to gas wells) and/or can be captured/sequestered. The removal of a majority of the entire CO<sub>2</sub> load, such as at least about 70%, or at least about 80%, for both H<sub>2</sub> production and electricity use, can substantially lower the greenhouse gas impact of refinery operations and can improve overall refinery efficiency (conversion of crude to products) by adding a high-efficiency source of electricity, hydrogen, and heat within a single process.

**[0033]** In aspects where an MCFC system is integrated with the hydrogen delivery system in a refinery, the anode input for the MCFC system can be selected from a large variety of materials available from various refinery processes, such as light gasses pre-reformed to reduce C<sub>2</sub>+; methane; gasified heavy materials like gasified coke or bitumen; syngas; and/or any other hydrocarbonaceous material that can be cleaned of sulfur and other harmful impurities; as well as combinations thereof. Thus, the MCFC system, with proper pre-cleanup, can act as a “disposal” for all sorts of inputs which might otherwise not have an efficient or effective use in the refinery. Instead of eventually being exhausted to the atmosphere, optionally after being burned as a fuel, a predominant amount of the carbon in these “waste”, “purge”, or other undesirable streams can be effectively concentrated/captured as separated CO<sub>2</sub> by the system. The cathode input can be or comprise any refinery stream containing CO<sub>2</sub> off-gasses plus any recycle from the anode exhaust or burned fresh methane that might be used for heat exchange. Most refineries have a wide variety of processes operating at various temperatures, so appropriate refinery processes can be selected for some heat integration to manage, for example, clean-up cooling and heating. The cathode exhaust can generally be exhausted to the atmosphere. The anode exhaust can be used as is, optionally after separation of some components, and /or can undergo both separation and water-gas shift to produce a stream that is nearly all H<sub>2</sub>. The high H<sub>2</sub> content stream can be purified to a desired level for various reactive processes, while combustion H<sub>2</sub> can contain greater levels of residual CO, CO<sub>2</sub>, and so forth, as combustion of such a stream can still result in reduced emissions of carbon oxides relative to combustion of a hydrocarbonaceous fuel. CO<sub>2</sub> separated from the anode exhaust can optionally be recycled, for example, for use as an input to the cathode. Additionally or alternately, feeds to the anode can include those with large CO<sub>2</sub>

impurities such as natural gas with a large CO<sub>2</sub> content. For normal refinery operations this type of stream could increase the CO<sub>2</sub> emissions from the refinery when used for either heat or hydrogen generation. When fed to the anode of an MCFC system, however, the separation stage(s) can effectively remove this additional CO<sub>2</sub> as part of removal of other CO<sub>2</sub> in the anode exhaust.

**[0034]** An additional difficulty in capturing carbon from the disparate CO<sub>2</sub> sources in a refinery can be the low concentration of the CO<sub>2</sub> often present in the refinery streams. In general, the energy required for separation of the CO<sub>2</sub> from the gas stream is highly dependent on the concentration of CO<sub>2</sub> in the stream. For processes that generate gas streams with low CO<sub>2</sub> concentrations, such as CO<sub>2</sub> concentrations of about 10 vol% or less, substantial energy can be required to separate CO<sub>2</sub> from a stream to form a high purity CO<sub>2</sub> stream. By contrast, in some aspects, a feature of an MCFC containing system can be that CO<sub>2</sub> can be transferred from a relatively low concentration stream (such as a cathode inlet stream) to a relatively high concentration stream (such as an anode exhaust). This can reduce the energy requirements for forming a high purity CO<sub>2</sub> gas stream. As a result, an MCFC can provide substantial energy savings when attempting to form, for example, a CO<sub>2</sub>-containing stream for sequestration.

**[0035]** Output electricity generated by the MCFC directly can typically be as DC power, but can be configured to produce any convenient mix of DC and/or AC power at a variety of current and voltage settings. Typically, a power plant / input electrical for a refinery can be a common high voltage AC current (e.g. ~960V). Due to the way molten carbonate fuel cells are constructed, one can produce essentially any DC current/voltage and, with inversion, a variety of AC voltages. DC, produced locally, should not suffer transmission losses typical of long-distance power lines and should not require inverters, at considerable cost and some efficiency loss. This can provide some flexibility in designing compressors, pumps, and other components and/or can eliminate a number of grid and/or local electrical inefficiencies.

**[0036]** In addition to use within a refinery, hydrogen can be more generally useful for a wide variety of products and processes, as it produces only water vapor on combustion. However, most conventional approaches to making hydrogen require large emissions of carbon. For example, production of hydrogen from steam reforming of methane can typically produce CO<sub>2</sub> (from the carbon in the methane) and waste heat.

Production of hydrogen from electrolysis can require electricity that can typically be derived from a mixture of fossil fuel production to the electrical grid. These production systems can all result in effluent exhausts comprising CO<sub>2</sub>. The effluents, if carbon capture is required, would typically entail separate carbon capture systems at those various sources, without any convenient integration into wider refinery operations. Typically, these sources can actually be outside of the refinery gates, allowing for little or no synergistic production / consumption of the various chemical, electrical, and heat inputs and outputs.

[0037] Additionally or alternately, MCFC containing systems according to the invention can provide the means to separate CO<sub>2</sub> efficiently from the process as an integral part of the separation and hydrogen purification steps. The CO<sub>2</sub> can then be captured, and/or used for other useful processes. This can occur at high overall system efficiency – far higher than conventional means of producing net hydrogen export, especially at small scale and under variable load.

[0038] The use of a MCFC system for hydrogen production for use in subsequent processes that may generate electrical power or heat can allow for relatively low-emission production at relatively high efficiency and with low (minimum) carbon emissions. The MCFC system can dynamically respond to varying needs for hydrogen by adjusting the ratio of chemical energy production to electrical energy production and can be ideal for uses where loads and demands may not be approximately constant – varying from pure electrical production with no excess hydrogen to high hydrogen production. Furthermore, the integrated MCFC system can be scaled over a wider range of applications with relatively high efficiency than larger scale systems such as methane steam reformers.

[0039] The MCFC – hydrogen production system can have an advantage that repurposing the hydrogen for fuel value can produce lower net CO<sub>2</sub> emissions than conventional systems without carbon capture and can produce far lower emissions with use of the inherent system CO<sub>2</sub> separation. This can be valuable in a variety of applications. Hydrogen can be produced for fuel cell vehicles that can use low temperature/low pressure hydrogen. The amount of hydrogen and electricity can be varied depending on overall demand maintaining overall high system efficiency. Hydrogen for export into boilers and/or other combined heat and power systems can

allow for the constant production of electricity, e.g., in stand-alone generation, along with a variable amount of carbon-free heat via the production of hydrogen with subsequent combustion in heater / boiler and similar systems. For example, an installation could produce primarily electricity in the summer for air conditioning systems while switching to a mix of primarily chemical energy in the winter for heating operations. Other applications can include systems designed to provide on-site hydrogen such as in laboratories and other technical and manufacturing facilities where some hydrogen can be beneficial along with a need for electrical energy.

[0040] In aspects involving hydrogen production and/or electrical power generation, the anode inlet can be fed by fresh methane, another suitable hydrocarbon fuel, and/or the combination of fresh fuel and recycled CO and/or H<sub>2</sub> from the various processes. The anode outlet stream comprising H<sub>2</sub> and/or CO can provide the components to produce hydrogen. This can typically be done through some combination of reaction, separation, and purification steps. An example would be a first stage employing water-gas shift to shift as much CO as possible to H<sub>2</sub> by the reaction  $\text{H}_2\text{O} + \text{CO} = \text{H}_2 + \text{CO}_2$ , followed by a second (and subsequent) stage(s) that remove H<sub>2</sub>O and CO<sub>2</sub> from the H<sub>2</sub>, and provide a suitable purity product. Such stages can include PSA, cryogenic separation, membranes, and other known separation methods, either individually or in combination. The off-gasses from these steps can be recycled and/or used to provide heat for inlet streams. The separated CO<sub>2</sub> can be used as a recycle stream and/or can be captured and/or used for other processes. The cathode inlet can be composed of recycled CO<sub>2</sub> from the overall process and/or CO<sub>2</sub> produced by the combustion of fresh (or recycled) fuel used to provide heat to the inlet streams. The cathode effluent can typically be exhausted to the atmosphere, optionally but preferably after heat recovery to, for example, provide heat for other process streams and/or in combined cycled electrical production, though the cathode effluent could optionally but less preferably be sent for further treatment, if desired.

[0041] MCFC systems integrated into carbon-free heat and power applications can be used over a range of operating conditions ranging from fuel utilizations with lower hydrogen make (e.g., 60-70%) to lower fuel utilizations (e.g., 20-30%) for high hydrogen production. The exact operational range of an individual application may vary widely both by application and over time. The ability to adapt to this operational

range can be a desirable advantage. The number of separation stages and/or the purity achieved can depend on the ultimate application. Simple production of hydrogen for low-emissions heat can be tolerant to modest impurities in the hydrogen, as even a few percent CO<sub>2</sub> and/or CO could still result in very low overall emissions. High purification applications such as fuel cell vehicles and/or hydrogen for laboratories may require multiple steps (e.g. cryogenic separation followed by PSA) to achieve purity specifications.

[0042] As an example of providing hydrogen to multiple refinery processes, an MCFC can be operated to generate electricity and an anode exhaust that contains H<sub>2</sub>, CO<sub>2</sub>, and H<sub>2</sub>O. One or more separations can be used to separate CO<sub>2</sub> and/or H<sub>2</sub>O from the anode exhaust (or alternatively from a gas stream derived from the anode exhaust). This can result in a first gas stream having an increased volume percent of H<sub>2</sub> relative to the anode exhaust. A separation can then be performed on the first gas stream to form a second gas stream with an even higher volume percentage of H<sub>2</sub> than the first gas stream. The remaining portion of the first gas stream can then be compressed to a first pressure for use in a process with less stringent requirements for hydrogen, while the second gas stream can be compressed to a second (higher) pressure for use in a process requiring a higher pressure and/or higher purity hydrogen input.

#### Additional Fuel Cell Operation Strategies

[0043] As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell can be operated so that the amount of reforming can be selected relative to the amount of oxidation in order to achieve a desired thermal ratio for the fuel cell. As used herein, the “thermal ratio” is defined as the heat produced by exothermic reactions in a fuel cell assembly divided by the endothermic heat demand of reforming reactions occurring within the fuel cell assembly. Expressed mathematically, the thermal ratio (TH) =  $Q_{EX}/Q_{EN}$ , where  $Q_{EX}$  is the sum of heat produced by exothermic reactions and  $Q_{EN}$  is the sum of heat consumed by the endothermic reactions occurring within the fuel cell. Note that the heat produced by the exothermic reactions corresponds to any heat due to reforming reactions, water gas shift reactions, and the electrochemical reactions in the cell. The heat generated by the electrochemical reactions can be calculated based on the ideal electrochemical potential of the fuel cell reaction across the electrolyte minus the actual output voltage

of the fuel cell. For example, the ideal electrochemical potential of the reaction in a MCFC is believed to be about 1.04V based on the net reaction that occurs in the cell. During operation of the MCFC, the cell will typically have an output voltage less than 1.04 V due to various losses. For example, a common output/operating voltage can be about 0.7 V. The heat generated is equal to the electrochemical potential of the cell (i.e. ~1.04V) minus the operating voltage. For example, the heat produced by the electrochemical reactions in the cell is ~0.34 V when the output voltage of ~0.7V. Thus, in this scenario, the electrochemical reactions would produce ~0.7 V of electricity and ~0.34 V of heat energy. In such an example, the ~0.7 V of electrical energy is not included as part of  $Q_{EX}$ . In other words, heat energy is not electrical energy.

**[0044]** In various aspects, a thermal ratio can be determined for any convenient fuel cell structure, such as a fuel cell stack, an individual fuel cell within a fuel cell stack, a fuel cell stack with an integrated reforming stage, a fuel cell stack with an integrated endothermic reaction stage, or a combination thereof. The thermal ratio may also be calculated for different units within a fuel cell stack, such as an assembly of fuel cells or fuel cell stacks. For example, the thermal ratio may be calculated for a single anode within a single fuel cell, an anode section within a fuel cell stack, or an anode section within a fuel cell stack along with integrated reforming stages and/or integrated endothermic reaction stage elements in sufficiently close proximity to the anode section to be integrated from a heat integration standpoint. As used herein, “an anode section” comprises anodes within a fuel cell stack that share a common inlet or outlet manifold.

**[0045]** In various aspects of the invention, the operation of the fuel cells can be characterized based on a thermal ratio. Where fuel cells are operated to have a desired thermal ratio, a molten carbonate fuel cell can be operated to have a thermal ratio of about 1.5 or less, for example about 1.3 or less, or about 1.15 or less, or about 1.0 or less, or about 0.95 or less, or about 0.90 or less, or about 0.85 or less, or about 0.80 or less, or about 0.75 or less. Additionally or alternately, the thermal ratio can be at least about 0.25, or at least about 0.35, or at least about 0.45, or at least about 0.50. Additionally or alternately, in some aspects the fuel cell can be operated to have a temperature rise between anode input and anode output of about 40°C or less, such as about 20°C or less, or about 10°C or less. Further additionally or alternately, the fuel

cell can be operated to have an anode outlet temperature that is from about 10°C lower to about 10°C higher than the temperature of the anode inlet. Still further additionally or alternately, the fuel cell can be operated to have an anode inlet temperature that is greater than the anode outlet temperature, such as at least about 5°C greater, or at least about 10°C greater, or at least about 20°C greater, or at least about 25°C greater. Yet still further additionally or alternately, the fuel cell can be operated to have an anode inlet temperature that is greater than the anode outlet temperature by about 100°C or less, such as by about 80°C or less, or about 60°C or less, or about 50°C or less, or about 40°C or less, or about 30°C or less, or about 20°C or less.

**[0046]** As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell (such as a fuel cell assembly) can be operated with increased production of syngas (or hydrogen) while also reducing or minimizing the amount of CO<sub>2</sub> exiting the fuel cell in the cathode exhaust stream. Syngas can be a valuable input for a variety of processes. In addition to having fuel value, syngas can be used as a raw material for forming other higher value products, such as by using syngas as an input for Fischer-Tropsch synthesis and/or methanol synthesis processes. One option for making syngas can be to reform a hydrocarbon or hydrocarbon-like fuel, such as methane or natural gas. For many types of industrial processes, a syngas having a ratio of H<sub>2</sub> to CO of close to 2:1 (or even lower) can often be desirable. A water gas shift reaction can be used to reduce the H<sub>2</sub> to CO ratio in a syngas if additional CO<sub>2</sub> is available, such as is produced in the anodes.

**[0047]** One way of characterizing the overall benefit provided by integrating syngas generation with use of molten carbonate fuel cells can be based on a ratio of the net amount of syngas that exits the fuel cells in the anode exhaust relative to the amount of CO<sub>2</sub> that exits the fuel cells in the cathode exhaust. This characterization measures the effectiveness of producing power with low emissions and high efficiency (both electrical and chemical). In this description, the net amount of syngas in an anode exhaust is defined as the combined number of moles of H<sub>2</sub> and number of moles of CO present in the anode exhaust, offset by the amount of H<sub>2</sub> and CO present in the anode inlet. Because the ratio is based on the net amount of syngas in the anode exhaust, simply passing excess H<sub>2</sub> into the anode does not change the value of the ratio. However, H<sub>2</sub> and/or CO generated due to reforming in the anode and/or in an internal

reforming stage associated with the anode can lead to higher values of the ratio. Hydrogen oxidized in the anode can lower the ratio. It is noted that the water gas shift reaction can exchange  $H_2$  for  $CO$ , so the combined moles of  $H_2$  and  $CO$  represents the total potential syngas in the anode exhaust, regardless of the eventual desired ratio of  $H_2$  to  $CO$  in a syngas. The syngas content of the anode exhaust ( $H_2 + CO$ ) can then be compared with the  $CO_2$  content of the cathode exhaust. This can provide a type of efficiency value that can also account for the amount of carbon capture. This can equivalently be expressed as an equation as

$$\text{Ratio of net syngas in anode exhaust to cathode } CO_2 = \frac{\text{net moles of } (H_2 + CO)_{\text{ANODE}}}{\text{moles of } (CO_2)_{\text{CATHODE}}}$$

**[0048]** In various aspects, the ratio of net moles of syngas in the anode exhaust to the moles of  $CO_2$  in the cathode exhaust can be at least about 2.0, such as at least about 3.0, or at least about 4.0, or at least about 5.0. In some aspects, the ratio of net syngas in the anode exhaust to the amount of  $CO_2$  in the cathode exhaust can be still higher, such as at least about 10.0, or at least about 15.0, or at least about 20.0. Ratio values of about 40.0 or less, such as about 30.0 or less, or about 20.0 or less, can additionally or alternately be achieved. In aspects where the amount of  $CO_2$  at the cathode inlet is about 6.0 volume % or less, such as about 5.0 volume % or less, ratio values of at least about 1.5 may be sufficient/realistic. Such molar ratio values of net syngas in the anode exhaust to the amount of  $CO_2$  in the cathode exhaust can be greater than the values for conventionally operated fuel cells.

**[0049]** As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell (such as a fuel cell assembly) can be operated at a reduced fuel utilization value, such as a fuel utilization of about 50% or less, while also having a high  $CO_2$  utilization value, such as at least about 60%. In this type of configuration, the molten carbonate fuel cell can be effective for carbon capture, as the  $CO_2$  utilization can advantageously be sufficiently high. Rather than attempting to maximize electrical efficiency, in this type of configuration the total efficiency of the fuel cell can be improved or increased based on the combined electrical and chemical efficiency. The chemical efficiency can be based on withdrawal of a hydrogen and/or syngas stream from the anode exhaust as an output for use in other processes. Even though the electrical efficiency may be reduced relative to

some conventional configurations, making use of the chemical energy output in the anode exhaust can allow for a desirable total efficiency for the fuel cell.

**[0050]** In various aspects, the fuel utilization in the fuel cell anode can be about 50% or less, such as about 40% or less, or about 30% or less, or about 25% or less, or about 20% or less. In various aspects, in order to generate at least some electric power, the fuel utilization in the fuel cell can be at least about 5%, such as at least about 10%, or at least about 15%, or at least about 20%, or at least about 25%, or at least about 30%. Additionally or alternatively, the CO<sub>2</sub> utilization can be at least about 60%, such as at least about 65%, or at least about 70%, or at least about 75%.

**[0051]** As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell can be operated at conditions that increase or maximize syngas production, possibly at the detriment of electricity production and electrical efficiency. Instead of selecting the operating conditions of a fuel cell to improve or maximize the electrical efficiency of the fuel cell, operating conditions, possibly including an amount of reformable fuel passed into the anode, can be established to increase the chemical energy output of the fuel cell. These operating conditions can result in a lower electrical efficiency of the fuel cell. Despite the reduced electrical efficiency, optionally, but preferably, the operating conditions can lead to an increase in the total efficiency of the fuel cell, which is based on the combined electrical efficiency and chemical efficiency of the fuel cell. By increasing the ratio of reformable fuel introduced into the anode to the fuel that is actually electrochemically oxidized at the anode, the chemical energy content in the anode output can be increased.

**[0052]** In some aspects, the reformable hydrogen content of reformable fuel in the input stream delivered to the anode and/or to a reforming stage associated with the anode can be at least about 50% greater than the net amount of hydrogen reacted at the anode, such as at least about 75% greater or at least about 100% greater. Additionally or alternately, the reformable hydrogen content of fuel in the input stream delivered to the anode and/or to a reforming stage associated with the anode can be at least about 50% greater than the net amount of hydrogen reacted at the anode, such as at least about 75% greater or at least about 100% greater. In various aspects, a ratio of the reformable hydrogen content of the reformable fuel in the fuel stream relative to an

amount of hydrogen reacted in the anode can be at least about 1.5 : 1, or at least about 2.0 : 1, or at least about 2.5 : 1, or at least about 3.0 : 1. Additionally or alternately, the ratio of reformable hydrogen content of the reformable fuel in the fuel stream relative to the amount of hydrogen reacted in the anode can be about 20 : 1 or less, such as about 15 : 1 or less or about 10 : 1 or less. In one aspect, it is contemplated that less than 100% of the reformable hydrogen content in the anode inlet stream can be converted to hydrogen. For example, at least about 80% of the reformable hydrogen content in an anode inlet stream can be converted to hydrogen in the anode and/or in an associated reforming stage(s), such as at least about 85%, or at least about 90%. Additionally or alternately, the amount of reformable fuel delivered to the anode can be characterized based on the Lower Heating Value (LHV) of the reformable fuel relative to the LHV of the hydrogen oxidized in the anode. This can be referred to as a reformable fuel surplus ratio. In various aspects, the reformable fuel surplus ratio can be at least about 2.0, such as at least about 2.5, or at least about 3.0, or at least about 4.0. Additionally or alternately, the reformable fuel surplus ratio can be about 25.0 or less, such as about 20.0 or less, or about 15.0 or less, or about 10.0 or less.

**[0053]** As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell (such as a fuel cell assembly) can also be operated at conditions that can improve or optimize the combined electrical efficiency and chemical efficiency of the fuel cell. Instead of selecting conventional conditions for maximizing the electrical efficiency of a fuel cell, the operating conditions can allow for output of excess synthesis gas and/or hydrogen in the anode exhaust of the fuel cell. The synthesis gas and/or hydrogen can then be used in a variety of applications, including chemical synthesis processes and collection of hydrogen for use as a “clean” fuel. In aspects of the invention, electrical efficiency can be reduced to achieve a high overall efficiency, which includes a chemical efficiency based on the chemical energy value of syngas and/or hydrogen produced relative to the energy value of the fuel input for the fuel cell.

**[0054]** In some aspects, the operation of the fuel cells can be characterized based on electrical efficiency. Where fuel cells are operated to have a low electrical efficiency (EE), a molten carbonate fuel cell can be operated to have an electrical efficiency of about 40% or less, for example, about 35% EE or less, about 30% EE or less, about

25% EE or less, or about 20% EE or less, about 15% EE or less, or about 10% EE or less. Additionally or alternately, the EE can be at least about 5%, or at least about 10%, or at least about 15%, or at least about 20%. Further additionally or alternately, the operation of the fuel cells can be characterized based on total fuel cell efficiency (TFCE), such as a combined electrical efficiency and chemical efficiency of the fuel cell(s). Where fuel cells are operated to have a high total fuel cell efficiency, a molten carbonate fuel cell can be operated to have a TFCE (and/or combined electrical efficiency and chemical efficiency) of about 55% or more, for example, about 60% or more, or about 65% or more, or about 70% or more, or about 75% or more, or about 80% or more, or about 85% or more. It is noted that for a total fuel cell efficiency and/or combined electrical efficiency and chemical efficiency, any additional electricity generated from use of excess heat generated by the fuel cell can be excluded from the efficiency calculation.

**[0055]** In various aspects of the invention, the operation of the fuel cells can be characterized based on a desired electrical efficiency of about 40% or less and a desired total fuel cell efficiency of about 55% or more. Where fuel cells are operated to have a desired electrical efficiency and a desired total fuel cell efficiency, a molten carbonate fuel cell can be operated to have an electrical efficiency of about 40% or less with a TFCE of about 55% or more, for example, about 35% EE or less with about a TFCE of 60% or more, about 30% EE or less with about a TFCE of about 65% or more, about 25% EE or less with about a 70% TFCE or more, or about 20% EE or less with about a TFCE of 75% or more, about 15% EE or less with about a TFCE of 80% or more, or about 10% EE or less with about a TFCE of about 85% or more.

**[0056]** As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell (such as a fuel cell assembly) can be operated at conditions that can provide increased power density. The power density of a fuel cell corresponds to the actual operating voltage  $V_A$  multiplied by the current density  $I$ . For a molten carbonate fuel cell operating at a voltage  $V_A$ , the fuel cell also can tend to generate waste heat, the waste heat defined as  $(V_0 - V_A) \cdot I$  based on the differential between  $V_A$  and the ideal voltage  $V_0$  for a fuel cell providing current density  $I$ . A portion of this waste heat can be consumed by reforming of a reformable fuel within the anode of the fuel cell. The remaining portion of this waste heat can be

absorbed by the surrounding fuel cell structures and gas flows, resulting in a temperature differential across the fuel cell. Under conventional operating conditions, the power density of a fuel cell can be limited based on the amount of waste heat that the fuel cell can tolerate without compromising the integrity of the fuel cell.

**[0057]** In various aspects, the amount of waste heat that a fuel cell can tolerate can be increased by performing an effective amount of an endothermic reaction within the fuel cell. One example of an endothermic reaction includes steam reforming of a reformable fuel within a fuel cell anode and/or in an associated reforming stage, such as an integrated reforming stage in a fuel cell stack. By providing additional reformable fuel to the anode of the fuel cell (or to an integrated / associated reforming stage), additional reforming can be performed so that additional waste heat can be consumed. This can reduce the amount of temperature differential across the fuel cell, thus allowing the fuel cell to operate under an operating condition with an increased amount of waste heat. The loss of electrical efficiency can be offset by the creation of an additional product stream, such as syngas and/or  $H_2$ , that can be used for various purposes including additional electricity generation further expanding the power range of the system.

**[0058]** In various aspects, the amount of waste heat generated by a fuel cell,  $(V_0 - V_A) \cdot I$  as defined above, can be at least about  $30 \text{ mW/cm}^2$ , such as at least about  $40 \text{ mW/cm}^2$ , or at least about  $50 \text{ mW/cm}^2$ , or at least about  $60 \text{ mW/cm}^2$ , or at least about  $70 \text{ mW/cm}^2$ , or at least about  $80 \text{ mW/cm}^2$ , or at least about  $100 \text{ mW/cm}^2$ , or at least about  $120 \text{ mW/cm}^2$ , or at least about  $140 \text{ mW/cm}^2$ , or at least about  $160 \text{ mW/cm}^2$ , or at least about  $180 \text{ mW/cm}^2$ . Additionally or alternately, the amount of waste heat generated by a fuel cell can be less than about  $250 \text{ mW/cm}^2$ , such as less than about  $200 \text{ mW/cm}^2$ , or less than about  $180 \text{ mW/cm}^2$ , or less than about  $165 \text{ mW/cm}^2$ , or less than about  $150 \text{ mW/cm}^2$ .

**[0059]** Although the amount of waste heat being generated can be relatively high, such waste heat may not necessarily represent operating a fuel cell with poor efficiency. Instead, the waste heat can be generated due to operating a fuel cell at an increased power density. Part of improving the power density of a fuel cell can include operating the fuel cell at a sufficiently high current density. In various aspects, the current density generated by the fuel cell can be at least about  $150 \text{ mA/cm}^2$ , such as at least

about 160 mA/cm<sup>2</sup>, or at least about 170 mA/cm<sup>2</sup>, or at least about 180 mA/cm<sup>2</sup>, or at least about 190 mA/cm<sup>2</sup>, or at least about 200 mA/cm<sup>2</sup>, or at least about 225 mA/cm<sup>2</sup>, or at least about 250 mA/cm<sup>2</sup>. Additionally or alternately, the current density generated by the fuel cell can be about 500 mA/cm<sup>2</sup> or less, such as 450 mA/cm<sup>2</sup>, or less, or 400 mA/cm<sup>2</sup>, or less or 350 mA/cm<sup>2</sup>, or less or 300 mA/cm<sup>2</sup> or less.

**[0060]** In various aspects, to allow a fuel cell to be operated with increased power generation and increased generation of waste heat, an effective amount of an endothermic reaction (such as a reforming reaction) can be performed. Alternatively, other endothermic reactions unrelated to anode operations can be used to utilize the waste heat by interspersing “plates” or stages into the fuel cell array that are in thermal communication but not fluid communication. The effective amount of the endothermic reaction can be performed in an associated reforming stage, an integrated reforming stage, an integrated stack element for performing an endothermic reaction, or a combination thereof. The effective amount of the endothermic reaction can correspond to an amount sufficient to reduce the temperature rise from the fuel cell inlet to the fuel cell outlet to about 100°C or less, such as about 90°C or less, or about 80°C or less, or about 70°C or less, or about 60°C or less, or about 50°C or less, or about 40°C or less, or about 30°C or less. Additionally or alternately, the effective amount of the endothermic reaction can correspond to an amount sufficient to cause a temperature decrease from the fuel cell inlet to the fuel cell outlet of about 100°C or less, such as about 90°C or less, or about 80°C or less, or about 70°C or less, or about 60°C or less, or about 50°C or less, or about 40°C or less, or about 30°C or less, or about 20°C or less, or about 10°C or less. A temperature decrease from the fuel cell inlet to the fuel cell outlet can occur when the effective amount of the endothermic reaction exceeds the waste heat generated. Additionally or alternately, this can correspond to having the endothermic reaction(s) (such as a combination of reforming and another endothermic reaction) consume at least about 40% of the waste heat generated by the fuel cell, such as consuming at least about 50% of the waste heat, or at least about 60% of the waste heat, or at least about 75% of the waste heat. Further additionally or alternately, the endothermic reaction(s) can consume about 95% of the waste heat or less, such as about 90% of the waste heat or less, or about 85% of the waste heat or less.

[0061] As an addition, complement, and/or alternative to the fuel cell operating strategies described herein, a molten carbonate fuel cell (such as a fuel cell assembly) can be operated at conditions corresponding to a decreased operating voltage and a low fuel utilization. In various aspects, the fuel cell can be operated at a voltage  $V_A$  of less than about 0.7 Volts, for example less than about 0.68 V, less than about 0.67 V, less than about 0.66 V, or about 0.65 V or less. Additionally or alternatively, the fuel cell can be operated at a voltage  $V_A$  of at least about 0.60, for example at least about 0.61, at least about 0.62, or at least about 0.63. In so doing, energy that would otherwise leave the fuel cell as electrical energy at high voltage can remain within the cell as heat as the voltage is lowered. This additional heat can allow for increased endothermic reactions to occur, for example increasing the  $\text{CH}_4$  conversion to syngas.

#### Definitions

[0062] **Syngas:** In this description, syngas is defined as mixture of  $\text{H}_2$  and CO in any ratio. Optionally,  $\text{H}_2\text{O}$  and/or  $\text{CO}_2$  may be present in the syngas. Optionally, inert compounds (such as nitrogen) and residual reformable fuel compounds may be present in the syngas. If components other than  $\text{H}_2$  and CO are present in the syngas, the combined volume percentage of  $\text{H}_2$  and CO in the syngas can be at least 25 vol% relative to the total volume of the syngas, such as at least 40 vol%, or at least 50 vol%, or at least 60 vol%. Additionally or alternately, the combined volume percentage of  $\text{H}_2$  and CO in the syngas can be 100 vol% or less, such as 95 vol% or less or 90 vol% or less.

[0063] **Reformable fuel:** A reformable fuel is defined as a fuel that contains carbon-hydrogen bonds that can be reformed to generate  $\text{H}_2$ . Hydrocarbons are examples of reformable fuels, as are other hydrocarbonaceous compounds such as alcohols. Although CO and  $\text{H}_2\text{O}$  can participate in a water gas shift reaction to form hydrogen, CO is not considered a reformable fuel under this definition.

[0064] **Reformable hydrogen content:** The reformable hydrogen content of a fuel is defined as the number of  $\text{H}_2$  molecules that can be derived from a fuel by reforming the fuel and then driving the water gas shift reaction to completion to maximize  $\text{H}_2$  production. It is noted that  $\text{H}_2$  by definition has a reformable hydrogen content of 1, although  $\text{H}_2$  itself is not defined as a reformable fuel herein. Similarly, CO has a reformable hydrogen content of 1. Although CO is not strictly reformable, driving the

water gas shift reaction to completion will result in exchange of a CO for an H<sub>2</sub>. As examples of reformable hydrogen content for reformable fuels, the reformable hydrogen content of methane is 4 H<sub>2</sub> molecules while the reformable hydrogen content of ethane is 7 H<sub>2</sub> molecules. More generally, if a fuel has the composition C<sub>x</sub>H<sub>y</sub>O<sub>z</sub>, then the reformable hydrogen content of the fuel at 100% reforming and water-gas shift is  $n(\text{H}_2 \text{ max reforming}) = 2x + y/2 - z$ . Based on this definition, fuel utilization within a cell can then be expressed as  $n(\text{H}_2 \text{ ox})/n(\text{H}_2 \text{ max reforming})$ . Of course, the reformable hydrogen content of a mixture of components can be determined based on the reformable hydrogen content of the individual components. The reformable hydrogen content of compounds that contain other heteroatoms, such as oxygen, sulfur or nitrogen, can also be calculated in a similar manner.

**[0065] Oxidation Reaction:** In this discussion, the oxidation reaction within the anode of a fuel cell is defined as the reaction corresponding to oxidation of H<sub>2</sub> by reaction with CO<sub>3</sub><sup>2-</sup> to form H<sub>2</sub>O and CO<sub>2</sub>. It is noted that the reforming reaction within the anode, where a compound containing a carbon-hydrogen bond is converted into H<sub>2</sub> and CO or CO<sub>2</sub>, is excluded from this definition of the oxidation reaction in the anode. The water-gas shift reaction is similarly outside of this definition of the oxidation reaction. It is further noted that references to a combustion reaction are defined as references to reactions where H<sub>2</sub> or a compound containing carbon-hydrogen bond(s) are reacted with O<sub>2</sub> to form H<sub>2</sub>O and carbon oxides in a non-electrochemical burner, such as the combustion zone of a combustion-powered generator.

**[0066]** Aspects of the invention can adjust anode fuel parameters to achieve a desired operating range for the fuel cell. Anode fuel parameters can be characterized directly, and/or in relation to other fuel cell processes in the form of one or more ratios. For example, the anode fuel parameters can be controlled to achieve one or more ratios including a fuel utilization, a fuel cell heating value utilization, a fuel surplus ratio, a reformable fuel surplus ratio, a reformable hydrogen content fuel ratio, and combinations thereof.

**[0067] Fuel utilization:** Fuel utilization is an option for characterizing operation of the anode based on the amount of oxidized fuel relative to the reformable hydrogen content of an input stream can be used to define a fuel utilization for a fuel cell. In this

discussion, “fuel utilization” is defined as the ratio of the amount of hydrogen oxidized in the anode for production of electricity (as described above) versus the reformable hydrogen content of the anode input (including any associated reforming stages). Reformable hydrogen content has been defined above as the number of H<sub>2</sub> molecules that can be derived from a fuel by reforming the fuel and then driving the water gas shift reaction to completion to maximize H<sub>2</sub> production. For example, each methane introduced into an anode and exposed to steam reforming conditions results in generation of the equivalent of 4 H<sub>2</sub> molecules at max production. (Depending on the reforming and/or anode conditions, the reforming product can correspond to a non-water gas shifted product, where one or more of the H<sub>2</sub> molecules is present instead in the form of a CO molecule.) Thus, methane is defined as having a reformable hydrogen content of 4 H<sub>2</sub> molecules. As another example, under this definition ethane has a reformable hydrogen content of 7 H<sub>2</sub> molecules.

**[0068]** The utilization of fuel in the anode can also be characterized by defining a heating value utilization based on a ratio of the Lower Heating Value of hydrogen oxidized in the anode due to the fuel cell anode reaction relative to the Lower Heating Value of all fuel delivered to the anode and/or a reforming stage associated with the anode. The “fuel cell heating value utilization” as used herein can be computed using the flow rates and Lower Heating Value (LHV) of the fuel components entering and leaving the fuel cell anode. As such, fuel cell heating value utilization can be computed as  $(\text{LHV}(\text{anode\_in}) - \text{LHV}(\text{anode\_out})) / \text{LHV}(\text{anode\_in})$ , where LHV(anode\_in) and LHV(anode\_out) refer to the LHV of the fuel components (such as H<sub>2</sub>, CH<sub>4</sub>, and/or CO) in the anode inlet and outlet streams or flows, respectively. In this definition, the LHV of a stream or flow may be computed as a sum of values for each fuel component in the input and/or output stream. The contribution of each fuel component to the sum can correspond to the fuel component’s flow rate (e.g., mol/hr) multiplied by the fuel component’s LHV (e.g., joules/mol).

**[0069] Lower Heating Value:** The lower heating value is defined as the enthalpy of combustion of a fuel component to vapor phase, fully oxidized products (i.e., vapor phase CO<sub>2</sub> and H<sub>2</sub>O product). For example, any CO<sub>2</sub> present in an anode input stream does not contribute to the fuel content of the anode input, since CO<sub>2</sub> is already fully oxidized. For this definition, the amount of oxidation occurring in the anode due to the

anode fuel cell reaction is defined as oxidation of  $H_2$  in the anode as part of the electrochemical reaction in the anode, as defined above.

[0070] It is noted that, for the special case where the only fuel in the anode input flow is  $H_2$ , the only reaction involving a fuel component that can take place in the anode represents the conversion of  $H_2$  into  $H_2O$ . In this special case, the fuel utilization simplifies to  $(H_2\text{-rate-in} - H_2\text{-rate-out})/H_2\text{-rate-in}$ . In such a case,  $H_2$  would be the only fuel component, and so the  $H_2$  LHV would cancel out of the equation. In the more general case, the anode feed may contain, for example,  $CH_4$ ,  $H_2$ , and  $CO$  in various amounts. Because these species can typically be present in different amounts in the anode outlet, the summation as described above can be needed to determine the fuel utilization.

[0071] Alternatively or in addition to fuel utilization, the utilization for other reactants in the fuel cell can be characterized. For example, the operation of a fuel cell can additionally or alternately be characterized with regard to “ $CO_2$  utilization” and/or “oxidant” utilization. The values for  $CO_2$  utilization and/or oxidant utilization can be specified in a similar manner.

[0072] **Fuel surplus ratio:** Still another way to characterize the reactions in a molten carbonate fuel cell is by defining a utilization based on a ratio of the Lower Heating Value of all fuel delivered to the anode and/or a reforming stage associated with the anode relative to the Lower Heating Value of hydrogen oxidized in the anode due to the fuel cell anode reaction. This quantity will be referred to as a fuel surplus ratio. As such the fuel surplus ratio can be computed as  $(LHV(\text{anode\_in}) / (LHV(\text{anode\_in}) - LHV(\text{anode\_out})))$  where  $LHV(\text{anode\_in})$  and  $LHV(\text{anode\_out})$  refer to the LHV of the fuel components (such as  $H_2$ ,  $CH_4$ , and/or  $CO$ ) in the anode inlet and outlet streams or flows, respectively. In various aspects of the invention, a molten carbonate fuel cell can be operated to have a fuel surplus ratio of at least about 1.0, such as at least about 1.5, or at least about 2.0, or at least about 2.5, or at least about 3.0, or at least about 4.0. Additionally or alternately, the fuel surplus ratio can be about 25.0 or less.

[0073] It is noted that not all of the reformable fuel in the input stream for the anode may be reformed. Preferably, at least about 90% of the reformable fuel in the input stream to the anode (and/or into an associated reforming stage) can be reformed prior to exiting the anode, such as at least about 95% or at least about 98%. In some alternative

aspects, the amount of reformable fuel that is reformed can be from about 75% to about 90%, such as at least about 80%.

[0074] The above definition for fuel surplus ratio provides a method for characterizing the amount of reforming occurring within the anode and/or reforming stage(s) associated with a fuel cell relative to the amount of fuel consumed in the fuel cell anode for generation of electric power.

[0075] Optionally, the fuel surplus ratio can be modified to account for situations where fuel is recycled from the anode output to the anode input. When fuel (such as H<sub>2</sub>, CO, and/or unreformed or partially reformed hydrocarbons) is recycled from anode output to anode input, such recycled fuel components do not represent a surplus amount of reformable or reformed fuel that can be used for other purposes. Instead, such recycled fuel components merely indicate a desire to reduce fuel utilization in a fuel cell.

[0076] **Reformable fuel surplus ratio:** Calculating a reformable fuel surplus ratio is one option to account for such recycled fuel components is to narrow the definition of surplus fuel, so that only the LHV of reformable fuels is included in the input stream to the anode. As used herein the “reformable fuel surplus ratio” is defined as the Lower Heating Value of reformable fuel delivered to the anode and/or a reforming stage associated with the anode relative to the Lower Heating Value of hydrogen oxidized in the anode due to the fuel cell anode reaction. Under the definition for reformable fuel surplus ratio, the LHV of any H<sub>2</sub> or CO in the anode input is excluded. Such an LHV of reformable fuel can still be measured by characterizing the actual composition entering a fuel cell anode, so no distinction between recycled components and fresh components needs to be made. Although some non-reformed or partially reformed fuel may also be recycled, in most aspects the majority of the fuel recycled to the anode can correspond to reformed products such as H<sub>2</sub> or CO. Expressed mathematically, the reformable fuel surplus ratio ( $R_{RFS}$ ) =  $LHV_{RF} / LHV_{OH}$ , where  $LHV_{RF}$  is the Lower Heating Value (LHV) of the reformable fuel and  $LHV_{OH}$  is the Lower Heating Value (LHV) of the hydrogen oxidized in the anode. The LHV of the hydrogen oxidized in the anode may be calculated by subtracting the LHV of the anode outlet stream from the LHV of the anode inlet stream (e.g.,  $LHV(\text{anode\_in}) - LHV(\text{anode\_out})$ ). In various aspects of the invention, a molten carbonate fuel cell can be operated to have a

reformable fuel surplus ratio of at least about 0.25, such as at least about 0.5, or at least about 1.0, or at least about 1.5, or at least about 2.0, or at least about 2.5, or at least about 3.0, or at least about 4.0. Additionally or alternately, the reformable fuel surplus ratio can be about 25.0 or less. It is noted that this narrower definition based on the amount of reformable fuel delivered to the anode relative to the amount of oxidation in the anode can distinguish between two types of fuel cell operation methods that have low fuel utilization. Some fuel cells achieve low fuel utilization by recycling a substantial portion of the anode output back to the anode input. This recycle can allow any hydrogen in the anode input to be used again as an input to the anode. This can reduce the amount of reforming, as even though the fuel utilization is low for a single pass through the fuel cell, at least a portion of the unused fuel is recycled for use in a later pass. Thus, fuel cells with a wide variety of fuel utilization values may have the same ratio of reformable fuel delivered to the anode reforming stage(s) versus hydrogen oxidized in the anode reaction. In order to change the ratio of reformable fuel delivered to the anode reforming stages relative to the amount of oxidation in the anode, either an anode feed with a native content of non-reformable fuel needs to be identified, or unused fuel in the anode output needs to be withdrawn for other uses, or both.

**[0077] Reformable hydrogen surplus ratio:** Still another option for characterizing the operation of a fuel cell is based on a “reformable hydrogen surplus ratio.” The reformable fuel surplus ratio defined above is defined based on the lower heating value of reformable fuel components. The reformable hydrogen surplus ratio is defined as the reformable hydrogen content of reformable fuel delivered to the anode and/or a reforming stage associated with the anode relative to the hydrogen reacted in the anode due to the fuel cell anode reaction. As such, the “reformable hydrogen surplus ratio” can be computed as  $(\text{RFC}(\text{reformable\_anode\_in}) / (\text{RFC}(\text{reformable\_anode\_in}) - \text{RFC}(\text{anode\_out})))$ , where  $\text{RFC}(\text{reformable\_anode\_in})$  refers to the reformable hydrogen content of reformable fuels in the anode inlet streams or flows, while  $\text{RFC}(\text{anode\_out})$  refers to the reformable hydrogen content of the fuel components (such as  $\text{H}_2$ ,  $\text{CH}_4$ , and/or  $\text{CO}$ ) in the anode inlet and outlet streams or flows. The RFC can be expressed in moles/s, moles/hr, or similar. An example of a method for operating a fuel cell with a large ratio of reformable fuel delivered to the anode reforming stage(s) versus amount of oxidation in the anode can be a method where excess reforming is performed in

order to balance the generation and consumption of heat in the fuel cell. Reforming a reformable fuel to form  $H_2$  and CO is an endothermic process. This endothermic reaction can be countered by the generation of electrical current in the fuel cell, which can also produce excess heat corresponding (roughly) to the difference between the amount of heat generated by the anode oxidation reaction and the carbonate formation reaction and the energy that exits the fuel cell in the form of electric current. The excess heat per mole of hydrogen involved in the anode oxidation reaction / carbonate formation reaction can be greater than the heat absorbed to generate a mole of hydrogen by reforming. As a result, a fuel cell operated under conventional conditions can exhibit a temperature increase from inlet to outlet. Instead of this type of conventional operation, the amount of fuel reformed in the reforming stages associated with the anode can be increased. For example, additional fuel can be reformed so that the heat generated by the exothermic fuel cell reactions can be (roughly) balanced by the heat consumed in reforming, or even the heat consumed by reforming can be beyond the excess heat generated by the fuel oxidation, resulting in a temperature drop across the fuel cell. This can result in a substantial excess of hydrogen relative to the amount needed for electrical power generation. As one example, a feed to the anode inlet of a fuel cell or an associated reforming stage can be substantially composed of reformable fuel, such as a substantially pure methane feed. During conventional operation for electric power generation using such a fuel, a molten carbonate fuel cell can be operated with a fuel utilization of about 75%. This means that about 75% (or  $\frac{3}{4}$ ) of the fuel content delivered to the anode is used to form hydrogen that is then reacted in the anode with carbonate ions to form  $H_2O$  and  $CO_2$ . In conventional operation, the remaining about 25% of the fuel content can be reformed to  $H_2$  within the fuel cell (or can pass through the fuel cell unreacted for any CO or  $H_2$  in the fuel), and then combusted outside of the fuel cell to form  $H_2O$  and  $CO_2$  to provide heat for the cathode inlet to the fuel cell. The reformable hydrogen surplus ratio in this situation can be  $4/(4-1) = 4/3$ .

**[0078] Electrical efficiency:** As used herein, the term “electrical efficiency” (“EE”) is defined as the electrochemical power produced by the fuel cell divided by the rate of Lower Heating Value (“LHV”) of fuel input to the fuel cell. The fuel inputs to the fuel cell includes both fuel delivered to the anode as well as any fuel used to maintain the

temperature of the fuel cell, such as fuel delivered to a burner associated with a fuel cell. In this description, the power produced by the fuel may be described in terms of LHV(el) fuel rate.

**[0079] Electrochemical power:** As used herein, the term “electrochemical power” or LHV(el) is the power generated by the circuit connecting the cathode to the anode in the fuel cell and the transfer of carbonate ions across the fuel cell’s electrolyte. Electrochemical power excludes power produced or consumed by equipment upstream or downstream from the fuel cell. For example, electricity produced from heat in a fuel cell exhaust stream is not considered part of the electrochemical power. Similarly, power generated by a gas turbine or other equipment upstream of the fuel cell is not part of the electrochemical power generated. The “electrochemical power” does not take electrical power consumed during operation of the fuel cell into account, or any loss incurred by conversion of the direct current to alternating current. In other words, electrical power used to supply the fuel cell operation or otherwise operate the fuel cell is not subtracted from the direct current power produced by the fuel cell. As used herein, the power density is the current density multiplied by voltage. As used herein, the total fuel cell power is the power density multiplied by the fuel cell area.

**[0080] Fuel inputs:** As used herein, the term “anode fuel input,” designated as LHV(anode\_in), is the amount of fuel within the anode inlet stream. The term “fuel input”, designated as LHV(in), is the total amount of fuel delivered to the fuel cell, including both the amount of fuel within the anode inlet stream and the amount of fuel used to maintain the temperature of the fuel cell. The fuel may include both reformable and nonreformable fuels, based on the definition of a reformable fuel provided herein. Fuel input is not the same as fuel utilization.

**[0081] Total fuel cell efficiency:** As used herein, the term “total fuel cell efficiency” (“TFCE”) is defined as: the electrochemical power generated by the fuel cell, plus the rate of LHV of syngas produced by the fuel cell, divided by the rate of LHV of fuel input to the anode. In other words,  $TFCE = (LHV(el) + LHV(sg\ net))/LHV(anode\_in)$ , where LHV(anode\_in) refers to rate at which the LHV of the fuel components (such as H<sub>2</sub>, CH<sub>4</sub>, and/or CO) delivered to the anode and LHV(sg net) refers to a rate at which syngas (H<sub>2</sub>, CO) is produced in the anode, which is the difference between syngas input to the anode and syngas output from the anode. LHV(el) describes the electrochemical

power generation of the fuel cell. The total fuel cell efficiency excludes heat generated by the fuel cell that is put to beneficial use outside of the fuel cell. In operation, heat generated by the fuel cell may be put to beneficial use by downstream equipment. For example, the heat may be used to generate additional electricity or to heat water. These uses, when they occur apart from the fuel cell, are not part of the total fuel cell efficiency, as the term is used in this application. The total fuel cell efficiency is for the fuel cell operation only, and does not include power production, or consumption, upstream, or downstream, of the fuel cell.

**[0082] Chemical efficiency:** As used herein, the term “chemical efficiency”, is defined as the lower heating value of H<sub>2</sub> and CO in the anode exhaust of the fuel cell, or LHV(sg out), divided by the fuel input, or LHV(in).

**[0083]** Neither the electrical efficiency nor the total system efficiency takes the efficiency of upstream or downstream processes into consideration. For example, it may be advantageous to use turbine exhaust as a source of CO<sub>2</sub> for the fuel cell cathode. In this arrangement, the efficiency of the turbine is not considered as part of the electrical efficiency or the total fuel cell efficiency calculation. Similarly, outputs from the fuel cell may be recycled as inputs to the fuel cell. A recycle loop is not considered when calculating electrical efficiency or the total fuel cell efficiency in single pass mode.

**[0084] Syngas produced:** As used herein, the term “syngas produced” is the difference between syngas input to the anode and syngas output from the anode. Syngas may be used as an input, or fuel, for the anode, at least in part. For example, a system may include an anode recycle loop that returns syngas from the anode exhaust to the anode inlet where it is supplemented with natural gas or other suitable fuel. Syngas produced LHV (sg net) = (LHV(sg out) - LHV(sg in)), where LHV(sg in) and LHV(sg out) refer to the LHV of the syngas in the anode inlet and syngas in the anode outlet streams or flows, respectively. It is noted that at least a portion of the syngas produced by the reforming reactions within an anode can typically be utilized in the anode to produce electricity. The hydrogen utilized to produce electricity is not included in the definition of “syngas produced” because it does not exit the anode. As used herein, the term “syngas ratio” is the LHV of the net syngas produced divided by the LHV of the fuel input to the anode or LHV (sg net)/LHV(anode in). Molar flow

rates of syngas and fuel can be used instead of LHV to express a molar-based syngas ratio and a molar-based syngas produced.

**[0085] Steam to carbon ratio (S/C):** As used herein, the steam to carbon ratio (S/C) is the molar ratio of steam in a flow to reformable carbon in the flow. Carbon in the form of CO and CO<sub>2</sub> are not included as reformable carbon in this definition. The steam to carbon ratio can be measured and/or controlled at different points in the system. For example, the composition of an anode inlet stream can be manipulated to achieve a S/C that is suitable for reforming in the anode. The S/C can be given as the molar flow rate of H<sub>2</sub>O divided by the product of the molar flow rate of fuel multiplied by the number of carbon atoms in the fuel, e.g. one for methane. Thus,  $S/C = f_{H_2O} / (f_{CH_4} \times \#C)$ , where  $f_{H_2O}$  is the molar flow rate of water, where  $f_{CH_4}$  is the molar flow rate of methane (or other fuel) and #C is the number of carbons in the fuel.

**[0086] EGR ratio:** Aspects of the invention can use a turbine in partnership with a fuel cell. The combined fuel cell and turbine system may include exhaust gas recycle (“EGR”). In an EGR system, at least a portion of the exhaust gas generated by the turbine can be sent to a heat recovery generator. Another portion of the exhaust gas can be sent to the fuel cell. The EGR ratio describes the amount of exhaust gas routed to the fuel cell versus the total exhaust gas routed to either the fuel cell or heat recovery generator. As used herein, the “EGR ratio” is the flow rate for the fuel cell bound portion of the exhaust gas divided by the combined flow rate for the fuel cell bound portion and the recovery bound portion, which is sent to the heat recovery generator.

**[0087]** In various aspects of the invention, a molten carbonate fuel cell (MCFC) can be used to facilitate separation of CO<sub>2</sub> from a CO<sub>2</sub>-containing stream while also generating additional electrical power. The CO<sub>2</sub> separation can be further enhanced by taking advantage of synergies with the combustion-based power generator that can provide at least a portion of the input feed to the cathode portion of the fuel cell.

**[0088] Fuel Cell and Fuel Cell Components:** In this discussion, a fuel cell can correspond to a single cell, with an anode and a cathode separated by an electrolyte. The anode and cathode can receive input gas flows to facilitate the respective anode and cathode reactions for transporting charge across the electrolyte and generating electricity. A fuel cell stack can represent a plurality of cells in an integrated unit. Although a fuel cell stack can include multiple fuel cells, the fuel cells can typically be

connected in parallel and can function (approximately) as if they collectively represented a single fuel cell of a larger size. When an input flow is delivered to the anode or cathode of a fuel cell stack, the fuel stack can include flow channels for dividing the input flow between each of the cells in the stack and flow channels for combining the output flows from the individual cells. In this discussion, a fuel cell array can be used to refer to a plurality of fuel cells (such as a plurality of fuel cell stacks) that are arranged in series, in parallel, or in any other convenient manner (e.g., in a combination of series and parallel). A fuel cell array can include one or more stages of fuel cells and/or fuel cell stacks, where the anode/cathode output from a first stage may serve as the anode/cathode input for a second stage. It is noted that the anodes in a fuel cell array do not have to be connected in the same way as the cathodes in the array. For convenience, the input to the first anode stage of a fuel cell array may be referred to as the anode input for the array, and the input to the first cathode stage of the fuel cell array may be referred to as the cathode input to the array. Similarly, the output from the final anode/cathode stage may be referred to as the anode/cathode output from the array.

**[0089]** It should be understood that reference to use of a fuel cell herein typically denotes a “fuel cell stack” composed of individual fuel cells, and more generally refers to use of one or more fuel cell stacks in fluid communication. Individual fuel cell elements (plates) can typically be “stacked” together in a rectangular array called a “fuel cell stack”. This fuel cell stack can typically take a feed stream and distribute reactants among all of the individual fuel cell elements and can then collect the products from each of these elements. When viewed as a unit, the fuel cell stack in operation can be taken as a whole even though composed of many (often tens or hundreds) of individual fuel cell elements. These individual fuel cell elements can typically have similar voltages (as the reactant and product concentrations are similar), and the total power output can result from the summation of all of the electrical currents in all of the cell elements, when the elements are electrically connected in series. Stacks can also be arranged in a series arrangement to produce high voltages. A parallel arrangement can boost the current. If a sufficiently large volume fuel cell stack is available to process a given exhaust flow, the systems and methods described herein can be used with a single molten carbonate fuel cell stack. In other aspects of the

invention, a plurality of fuel cell stacks may be desirable or needed for a variety of reasons.

[0090] For the purposes of this invention, unless otherwise specified, the term “fuel cell” should be understood to also refer to and/or is defined as including a reference to a fuel cell stack composed of set of one or more individual fuel cell elements for which there is a single input and output, as that is the manner in which fuel cells are typically employed in practice. Similarly, the term fuel cells (plural), unless otherwise specified, should be understood to also refer to and/or is defined as including a plurality of separate fuel cell stacks. In other words, all references within this document, unless specifically noted, can refer interchangeably to the operation of a fuel cell stack as a “fuel cell”. For example, the volume of exhaust generated by a commercial scale combustion generator may be too large for processing by a fuel cell (i.e., a single stack) of conventional size. In order to process the full exhaust, a plurality of fuel cells (i.e., two or more separate fuel cells or fuel cell stacks) can be arranged in parallel, so that each fuel cell can process (roughly) an equal portion of the combustion exhaust. Although multiple fuel cells can be used, each fuel cell can typically be operated in a generally similar manner, given its (roughly) equal portion of the combustion exhaust.

[0091] **“Internal reforming” and “external reforming”:** A fuel cell or fuel cell stack may include one or more internal reforming sections. As used herein, the term “internal reforming” refers to fuel reforming occurring within the body of a fuel cell, a fuel cell stack, or otherwise within a fuel cell assembly. External reforming, which is often used in conjunction with a fuel cell, occurs in a separate piece of equipment that is located outside of the fuel cell stack. In other words, the body of the external reformer is not in direct physical contact with the body of a fuel cell or fuel cell stack. In a typical set up, the output from the external reformer can be fed to the anode inlet of a fuel cell. Unless otherwise noted specifically, the reforming described within this application is internal reforming.

[0092] Internal reforming may occur within a fuel cell anode. Internal reforming can additionally or alternately occur within an internal reforming element integrated within a fuel cell assembly. The integrated reforming element may be located between fuel cell elements within a fuel cell stack. In other words, one of the trays in the stack can be a reforming section instead of a fuel cell element. In one aspect, the flow arrangement

within a fuel cell stack directs fuel to the internal reforming elements and then into the anode portion of the fuel cells. Thus, from a flow perspective, the internal reforming elements and fuel cell elements can be arranged in series within the fuel cell stack. As used herein, the term “anode reforming” is fuel reforming that occurs within an anode. As used herein, the term “internal reforming” is reforming that occurs within an integrated reforming element and not in an anode section.

**[0093]** In some aspects, a reforming stage that is internal to a fuel cell assembly can be considered to be associated with the anode(s) in the fuel cell assembly. In some alternative aspects, for a reforming stage in a fuel cell stack that can be associated with an anode (such as associated with multiple anodes), a flow path can be available so that the output flow from the reforming stage is passed into at least one anode. This can correspond to having an initial section of a fuel cell plate not in contact with the electrolyte and instead can serve just as a reforming catalyst. Another option for an associated reforming stage can be to have a separate integrated reforming stage as one of the elements in a fuel cell stack, where the output from the integrated reforming stage can be returned to the input side of one or more of the fuel cells in the fuel cell stack.

**[0094]** From a heat integration standpoint, a characteristic height in a fuel cell stack can be the height of an individual fuel cell stack element. It is noted that the separate reforming stage and/or a separate endothermic reaction stage could have a different height in the stack than a fuel cell. In such a scenario, the height of a fuel cell element can be used as the characteristic height. In some aspects, an integrated endothermic reaction stage can be defined as a stage that is heat integrated with one or more fuel cells, so that the integrated endothermic reaction stage can use the heat from the fuel cells as a heat source for the endothermic reaction. Such an integrated endothermic reaction stage can be defined as being positioned less than 5 times the height of a stack element from any fuel cells providing heat to the integrated stage. For example, an integrated endothermic reaction stage (such as a reforming stage) can be positioned less than 5 times the height of a stack element from any fuel cells that are heat integrated, such as less than 3 times the height of a stack element. In this discussion, an integrated reforming stage and/or integrated endothermic reaction stage that represent an adjacent

stack element to a fuel cell element can be defined as being about one stack element height or less away from the adjacent fuel cell element.

**[0095]** In some aspects, a separate reforming stage that is heat integrated with a fuel cell element can correspond to a reforming stage associated with the fuel cell element. In such aspects, an integrated fuel cell element can provide at least a portion of the heat to the associated reforming stage, and the associated reforming stage can provide at least a portion of the reforming stage output to the integrated fuel cell as a fuel stream. In other aspects, a separate reforming stage can be integrated with a fuel cell for heat transfer without being associated with the fuel cell. In this type of situation, the separate reforming stage can receive heat from the fuel cell, but the decision can be made not to use the output of the reforming stage as an input to the fuel cell. Instead, the decision can be made to use the output of such a reforming stage for another purpose, such as directly adding the output to the anode exhaust stream, and/or for forming a separate output stream from the fuel cell assembly.

**[0096]** More generally, a separate stack element in a fuel cell stack can be used to perform any convenient type of endothermic reaction that can take advantage of the waste heat provided by integrated fuel cell stack elements. Instead of plates suitable for performing a reforming reaction on a hydrocarbon fuel stream, a separate stack element can have plates suitable for catalyzing another type of endothermic reaction. A manifold or other arrangement of inlet conduits in the fuel cell stack can be used to provide an appropriate input flow to each stack element. A similar manifold or other arrangement of outlet conduits can additionally or alternately be used to withdraw the output flows from each stack element. Optionally, the output flows from a endothermic reaction stage in a stack can be withdrawn from the fuel cell stack without having the output flow pass through a fuel cell anode. In such an optional aspect, the products of the exothermic reaction can therefore exit from the fuel cell stack without passing through a fuel cell anode. Examples of other types of endothermic reactions that can be performed in stack elements in a fuel cell stack can include, without limitation, ethanol dehydration to form ethylene and ethane cracking.

**[0097] Recycle:** As defined herein, recycle of a portion of a fuel cell output (such as an anode exhaust or a stream separated or withdrawn from an anode exhaust) to a fuel cell inlet can correspond to a direct or indirect recycle stream. A direct recycle of a

stream to a fuel cell inlet is defined as recycle of the stream without passing through an intermediate process, while an indirect recycle involves recycle after passing a stream through one or more intermediate processes. For example, if the anode exhaust is passed through a CO<sub>2</sub> separation stage prior to recycle, this is considered an indirect recycle of the anode exhaust. If a portion of the anode exhaust, such as an H<sub>2</sub> stream withdrawn from the anode exhaust, is passed into a gasifier for converting coal into a fuel suitable for introduction into the fuel cell, then that is also considered an indirect recycle.

#### Anode Inputs and Outputs

[0098] In various aspects of the invention, the MCFC array can be fed by a fuel received at the anode inlet that comprises, for example, both hydrogen and a hydrocarbon such as methane (or alternatively a hydrocarbonaceous or hydrocarbon-like compound that may contain heteroatoms different from C and H). Most of the methane (or other hydrocarbonaceous or hydrocarbon-like compound) fed to the anode can typically be fresh methane. In this description, a fresh fuel such as fresh methane refers to a fuel that is not recycled from another fuel cell process. For example, methane recycled from the anode outlet stream back to the anode inlet may not be considered “fresh” methane, and can instead be described as reclaimed methane. The fuel source used can be shared with other components, such as a turbine that uses a portion of the fuel source to provide a CO<sub>2</sub>-containing stream for the cathode input. The fuel source input can include water in a proportion to the fuel appropriate for reforming the hydrocarbon (or hydrocarbon-like) compound in the reforming section that generates hydrogen. For example, if methane is the fuel input for reforming to generate H<sub>2</sub>, the molar ratio of water to fuel can be from about one to one to about ten to one, such as at least about two to one. A ratio of four to one or greater is typical for external reforming, but lower values can be typical for internal reforming. To the degree that H<sub>2</sub> is a portion of the fuel source, in some optional aspects no additional water may be needed in the fuel, as the oxidation of H<sub>2</sub> at the anode can tend to produce H<sub>2</sub>O that can be used for reforming the fuel. The fuel source can also optionally contain components incidental to the fuel source (e.g., a natural gas feed can contain some content of CO<sub>2</sub> as an additional component). For example, a natural gas feed can contain CO<sub>2</sub>, N<sub>2</sub>, and/or other inert (noble) gases as additional components.

Optionally, in some aspects the fuel source may also contain CO, such as CO from a recycled portion of the anode exhaust. An additional or alternate potential source for CO in the fuel into a fuel cell assembly can be CO generated by steam reforming of a hydrocarbon fuel performed on the fuel prior to entering the fuel cell assembly.

**[0099]** More generally, a variety of types of fuel streams may be suitable for use as an input stream for the anode of a molten carbonate fuel cell. Some fuel streams can correspond to streams containing hydrocarbons and/or hydrocarbon-like compounds that may also include heteroatoms different from C and H. In this discussion, unless otherwise specified, a reference to a fuel stream containing hydrocarbons for an MCFC anode is defined to include fuel streams containing such hydrocarbon-like compounds. Examples of hydrocarbon (including hydrocarbon-like) fuel streams include natural gas, streams containing C1 – C4 carbon compounds (such as methane or ethane), and streams containing heavier C5+ hydrocarbons (including hydrocarbon-like compounds), as well as combinations thereof. Still other additional or alternate examples of potential fuel streams for use in an anode input can include biogas-type streams, such as methane produced from natural (biological) decomposition of organic material.

**[00100]** In some aspects, a molten carbonate fuel cell can be used to process an input fuel stream, such as a natural gas and/or hydrocarbon stream, with a low energy content due to the presence of diluent compounds. For example, some sources of methane and/or natural gas are sources that can include substantial amounts of either CO<sub>2</sub> or other inert molecules, such as nitrogen, argon, or helium. Due to the presence of elevated amounts of CO<sub>2</sub> and/or inerts, the energy content of a fuel stream based on the source can be reduced. Using a low energy content fuel for a combustion reaction (such as for powering a combustion-powered turbine) can pose difficulties. However, a molten carbonate fuel cell can generate power based on a low energy content fuel source with a reduced or minimal impact on the efficiency of the fuel cell. The presence of additional gas volume can require additional heat for raising the temperature of the fuel to the temperature for reforming and/or the anode reaction. Additionally, due to the equilibrium nature of the water gas shift reaction within a fuel cell anode, the presence of additional CO<sub>2</sub> can have an impact on the relative amounts of H<sub>2</sub> and CO present in the anode output. However, the inert compounds otherwise

can have only a minimal direct impact on the reforming and anode reactions. The amount of CO<sub>2</sub> and/or inert compounds in a fuel stream for a molten carbonate fuel cell, when present, can be at least about 1 vol%, such as at least about 2 vol%, or at least about 5 vol%, or at least about 10 vol%, or at least about 15 vol%, or at least about 20 vol%, or at least about 25 vol%, or at least about 30 vol%, or at least about 35 vol%, or at least about 40 vol%, or at least about 45 vol%, or at least about 50 vol %, or at least about 75 vol%. Additionally or alternately, the amount of CO<sub>2</sub> and/or inert compounds in a fuel stream for a molten carbonate fuel cell can be about 90 vol% or less, such as about 75 vol% or less, or about 60 vol% or less, or about 50 vol% or less, or about 40 vol% or less, or about 35 vol% or less.

**[00101]** Yet other examples of potential sources for an anode input stream can correspond to refinery and/or other industrial process output streams. For example, coking is a common process in many refineries for converting heavier compounds to lower boiling ranges. Coking typically produces an off-gas containing a variety of compounds that are gases at room temperature, including CO and various C1 – C4 hydrocarbons. This off-gas can be used as at least a portion of an anode input stream. Other refinery off-gas streams can additionally or alternately be suitable for inclusion in an anode input stream, such as light ends (C1 – C4) generated during cracking or other refinery processes. Still other suitable refinery streams can additionally or alternately include refinery streams containing CO or CO<sub>2</sub> that also contain H<sub>2</sub> and/or reformable fuel compounds.

**[00102]** Still other potential sources for an anode input can additionally or alternately include streams with increased water content. For example, an ethanol output stream from an ethanol plant (or another type of fermentation process) can include a substantial portion of H<sub>2</sub>O prior to final distillation. Such H<sub>2</sub>O can typically cause only minimal impact on the operation of a fuel cell. Thus, a fermentation mixture of alcohol (or other fermentation product) and water can be used as at least a portion of an anode input stream.

**[00103]** Biogas, or digester gas, is another additional or alternate potential source for an anode input. Biogas may primarily comprise methane and CO<sub>2</sub> and is typically produced by the breakdown or digestion of organic matter. Anaerobic bacteria may be

used to digest the organic matter and produce the biogas. Impurities, such as sulfur-containing compounds, may be removed from the biogas prior to use as an anode input.

**[00104]** The output stream from an MCFC anode can include H<sub>2</sub>O, CO<sub>2</sub>, CO, and H<sub>2</sub>. Optionally, the anode output stream could also have unreacted fuel (such as H<sub>2</sub> or CH<sub>4</sub>) or inert compounds in the feed as additional output components. Instead of using this output stream as a fuel source to provide heat for a reforming reaction or as a combustion fuel for heating the cell, one or more separations can be performed on the anode output stream to separate the CO<sub>2</sub> from the components with potential value as inputs to another process, such as H<sub>2</sub> or CO. The H<sub>2</sub> and/or CO can be used as a syngas for chemical synthesis, as a source of hydrogen for chemical reaction, and/or as a fuel with reduced greenhouse gas emissions.

**[00105]** In various aspects, the composition of the output stream from the anode can be impacted by several factors. Factors that can influence the anode output composition can include the composition of the input stream to the anode, the amount of current generated by the fuel cell, and/or the temperature at the exit of the anode. The temperature of at the anode exit can be relevant due to the equilibrium nature of the water gas shift reaction. In a typical anode, at least one of the plates forming the wall of the anode can be suitable for catalyzing the water gas shift reaction. As a result, if a) the composition of the anode input stream is known, b) the extent of reforming of reformable fuel in the anode input stream is known, and c) the amount of carbonate transported from the cathode to anode (corresponding to the amount of electrical current generated) is known, the composition of the anode output can be determined based on the equilibrium constant for the water gas shift reaction.

$$K_{eq} = [CO_2] [H_2] / [CO] [H_2O]$$

**[00106]** In the above equation,  $K_{eq}$  is the equilibrium constant for the reaction at a given temperature and pressure, and [X] is the partial pressure of component X. Based on the water gas shift reaction, it can be noted that an increased CO<sub>2</sub> concentration in the anode input can tend to result in additional CO formation (at the expense of H<sub>2</sub>) while an increased H<sub>2</sub>O concentration can tend to result in additional H<sub>2</sub> formation (at the expense of CO).

**[00107]** To determine the composition at the anode output, the composition of the anode input can be used as a starting point. This composition can then be modified to

reflect the extent of reforming of any reformable fuels that can occur within the anode. Such reforming can reduce the hydrocarbon content of the anode input in exchange for increased hydrogen and CO<sub>2</sub>. Next, based on the amount of electrical current generated, the amount of H<sub>2</sub> in the anode input can be reduced in exchange for additional H<sub>2</sub>O and CO<sub>2</sub>. This composition can then be adjusted based on the equilibrium constant for the water gas shift reaction to determine the exit concentrations for H<sub>2</sub>, CO, CO<sub>2</sub>, and H<sub>2</sub>O.

[00108] Table 1 shows the anode exhaust composition at different fuel utilizations for a typical type of fuel. The anode exhaust composition can reflect the combined result of the anode reforming reaction, water gas shift reaction, and the anode oxidation reaction. The output composition values in Table 1 were calculated by assuming an anode input composition with an about 2 to 1 ratio of steam (H<sub>2</sub>O) to carbon (reformable fuel). The reformable fuel was assumed to be methane, which was assumed to be 100% reformed to hydrogen. The initial CO<sub>2</sub> and H<sub>2</sub> concentrations in the anode input were assumed to be negligible, while the input N<sub>2</sub> concentration was about 0.5%. The fuel utilization U<sub>f</sub> (as defined herein) was allowed to vary from about 35% to about 70% as shown in the table. The exit temperature for the fuel cell anode was assumed to be about 650°C for purposes of determining the correct value for the equilibrium constant.

**TABLE 1 - Anode Exhaust Composition**

| U <sub>f</sub>                                                 | %      | 35%   | 40%   | 45%   | 50%   | 55%   | 60%   | 65%   | 70%   |
|----------------------------------------------------------------|--------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>Anode Exhaust Composition</b>                               |        |       |       |       |       |       |       |       |       |
| <b>H<sub>2</sub>O</b>                                          | %, wet | 32.5% | 34.1% | 35.5% | 36.7% | 37.8% | 38.9% | 39.8% | 40.5% |
| <b>CO<sub>2</sub></b>                                          | %, wet | 26.7% | 29.4% | 32.0% | 34.5% | 36.9% | 39.3% | 41.5% | 43.8% |
| <b>H<sub>2</sub></b>                                           | %, wet | 29.4% | 26.0% | 22.9% | 20.0% | 17.3% | 14.8% | 12.5% | 10.4% |
| <b>CO</b>                                                      | %, wet | 10.8% | 10.0% | 9.2%  | 8.4%  | 7.5%  | 6.7%  | 5.8%  | 4.9%  |
| <b>N<sub>2</sub></b>                                           | %, wet | 0.5%  | 0.5%  | 0.5%  | 0.4%  | 0.4%  | 0.4%  | 0.4%  | 0.4%  |
|                                                                |        |       |       |       |       |       |       |       |       |
| <b>CO<sub>2</sub></b>                                          | %, dry | 39.6% | 44.6% | 49.6% | 54.5% | 59.4% | 64.2% | 69.0% | 73.7% |
| <b>H<sub>2</sub></b>                                           | %, dry | 43.6% | 39.4% | 35.4% | 31.5% | 27.8% | 24.2% | 20.7% | 17.5% |
| <b>CO</b>                                                      | %, dry | 16.1% | 15.2% | 14.3% | 13.2% | 12.1% | 10.9% | 9.7%  | 8.2%  |
| <b>N<sub>2</sub></b>                                           | %, dry | 0.7%  | 0.7%  | 0.7%  | 0.7%  | 0.7%  | 0.7%  | 0.7%  | 0.7%  |
| <b>H<sub>2</sub>/CO</b>                                        |        | 2.7   | 2.6   | 2.5   | 2.4   | 2.3   | 2.2   | 2.1   | 2.1   |
| <b>(H<sub>2</sub>-CO<sub>2</sub>)/<br/>(CO+CO<sub>2</sub>)</b> |        | 0.07  | -0.09 | -0.22 | -0.34 | -0.44 | -0.53 | -0.61 | -0.69 |

[00109] Table 1 shows anode output compositions for a particular set of conditions and anode input composition. More generally, in various aspects the anode output can include about 10 vol% to about 50 vol%  $\text{H}_2\text{O}$ . The amount of  $\text{H}_2\text{O}$  can vary greatly, as  $\text{H}_2\text{O}$  in the anode can be produced by the anode oxidation reaction. If an excess of  $\text{H}_2\text{O}$  beyond what is needed for reforming is introduced into the anode, the excess  $\text{H}_2\text{O}$  can typically pass through largely unreacted, with the exception of  $\text{H}_2\text{O}$  consumed (or generated) due to fuel reforming and the water gas shift reaction. The  $\text{CO}_2$  concentration in the anode output can also vary widely, such as from about 20 vol% to about 50 vol%  $\text{CO}_2$ . The amount of  $\text{CO}_2$  can be influenced by both the amount of electrical current generated as well as the amount of  $\text{CO}_2$  in the anode input flow. The amount of  $\text{H}_2$  in the anode output can additionally or alternately be from about 10 vol%  $\text{H}_2$  to about 50 vol%  $\text{H}_2$ , depending on the fuel utilization in the anode. At the anode output, the amount of  $\text{CO}$  can be from about 5 vol% to about 20 vol%. It is noted that the amount of  $\text{CO}$  relative to the amount of  $\text{H}_2$  in the anode output for a given fuel cell can be determined in part by the equilibrium constant for the water gas shift reaction at the temperature and pressure present in the fuel cell. The anode output can further additionally or alternately include 5 vol% or less of various other components, such as  $\text{N}_2$ ,  $\text{CH}_4$  (or other unreacted carbon-containing fuels), and/or other components.

[00110] Optionally, one or more water gas shift reaction stages can be included after the anode output to convert  $\text{CO}$  and  $\text{H}_2\text{O}$  in the anode output into  $\text{CO}_2$  and  $\text{H}_2$ , if desired. The amount of  $\text{H}_2$  present in the anode output can be increased, for example, by using a water gas shift reactor at lower temperature to convert  $\text{H}_2\text{O}$  and  $\text{CO}$  present in the anode output into  $\text{H}_2$  and  $\text{CO}_2$ . Alternatively, the temperature can be raised and the water-gas shift reaction can be reversed, producing more  $\text{CO}$  and  $\text{H}_2\text{O}$  from  $\text{H}_2$  and  $\text{CO}_2$ . Water is an expected output of the reaction occurring at the anode, so the anode output can typically have an excess of  $\text{H}_2\text{O}$  relative to the amount of  $\text{CO}$  present in the anode output. Alternatively,  $\text{H}_2\text{O}$  can be added to the stream after the anode exit but before the water gas shift reaction.  $\text{CO}$  can be present in the anode output due to incomplete carbon conversion during reforming and/or due to the equilibrium balancing reactions between  $\text{H}_2\text{O}$ ,  $\text{CO}$ ,  $\text{H}_2$ , and  $\text{CO}_2$  (i.e., the water-gas shift equilibrium) under either reforming conditions or the conditions present during the anode reaction. A water gas shift reactor can be operated under conditions to drive the equilibrium further

in the direction of forming  $\text{CO}_2$  and  $\text{H}_2$  at the expense of  $\text{CO}$  and  $\text{H}_2\text{O}$ . Higher temperatures can tend to favor the formation of  $\text{CO}$  and  $\text{H}_2\text{O}$ . Thus, one option for operating the water gas shift reactor can be to expose the anode output stream to a suitable catalyst, such as a catalyst including iron oxide, zinc oxide, copper on zinc oxide, or the like, at a suitable temperature, e.g., between about  $190^\circ\text{C}$  to about  $210^\circ\text{C}$ . Optionally, the water-gas shift reactor can include two stages for reducing the  $\text{CO}$  concentration in an anode output stream, with a first higher temperature stage operated at a temperature from at least about  $300^\circ\text{C}$  to about  $375^\circ\text{C}$  and a second lower temperature stage operated at a temperature of about  $225^\circ\text{C}$  or less, such as from about  $180^\circ\text{C}$  to about  $210^\circ\text{C}$ . In addition to increasing the amount of  $\text{H}_2$  present in the anode output, the water-gas shift reaction can additionally or alternately increase the amount of  $\text{CO}_2$  at the expense of  $\text{CO}$ . This can exchange difficult-to-remove carbon monoxide ( $\text{CO}$ ) for carbon dioxide, which can be more readily removed by condensation (e.g., cryogenic removal), chemical reaction (such as amine removal), and/or other  $\text{CO}_2$  removal methods. Additionally or alternately, it may be desirable to increase the  $\text{CO}$  content present in the anode exhaust in order to achieve a desired ratio of  $\text{H}_2$  to  $\text{CO}$ .

[00111] After passing through the optional water gas shift reaction stage, the anode output can be passed through one or more separation stages for removal of water and/or  $\text{CO}_2$  from the anode output stream. For example, one or more  $\text{CO}_2$  output streams can be formed by performing  $\text{CO}_2$  separation on the anode output using one or more methods individually or in combination. Such methods can be used to generate  $\text{CO}_2$  output stream(s) having a  $\text{CO}_2$  content of 90 vol% or greater, such as at least 95% vol%  $\text{CO}_2$ , or at least 98 vol%  $\text{CO}_2$ . Such methods can recover about at least about 70% of the  $\text{CO}_2$  content of the anode output, such as at least about 80% of the  $\text{CO}_2$  content of the anode output, or at least about 90%. Alternatively, in some aspects it may be desirable to recover only a portion of the  $\text{CO}_2$  within an anode output stream, with the recovered portion of  $\text{CO}_2$  being about 33% to about 90% of the  $\text{CO}_2$  in the anode output, such as at least about 40%, or at least about 50%. For example, it may be desirable to retain some  $\text{CO}_2$  in the anode output flow so that a desired composition can be achieved in a subsequent water gas shift stage. Suitable separation methods may comprise use of a physical solvent (e.g., Selexol™ or Rectisol™); amines or other bases (e.g., MEA or MDEA); refrigeration (e.g., cryogenic separation); pressure swing

adsorption; vacuum swing adsorption; and combinations thereof. A cryogenic CO<sub>2</sub> separator can be an example of a suitable separator. As the anode output is cooled, the majority of the water in the anode output can be separated out as a condensed (liquid) phase. Further cooling and/or pressurizing of the water-depleted anode output flow can then separate high purity CO<sub>2</sub>, as the other remaining components in the anode output flow (such as H<sub>2</sub>, N<sub>2</sub>, CH<sub>4</sub>) do not tend to readily form condensed phases. A cryogenic CO<sub>2</sub> separator can recover between about 33% and about 90% of the CO<sub>2</sub> present in a flow, depending on the operating conditions.

**[00112]** Removal of water from the anode exhaust to form one or more water output streams can also be beneficial, whether prior to, during, or after performing CO<sub>2</sub> separation. The amount of water in the anode output can vary depending on operating conditions selected. For example, the steam-to-carbon ratio established at the anode inlet can affect the water content in the anode exhaust, with high steam-to-carbon ratios typically resulting in a large amount of water that can pass through the anode unreacted and/or reacted only due to the water gas shift equilibrium in the anode. Depending on the aspect, the water content in the anode exhaust can correspond to up to about 30% or more of the volume in the anode exhaust. Additionally or alternately, the water content can be about 80% or less of the volume of the anode exhaust. While such water can be removed by compression and/or cooling with resulting condensation, the removal of this water can require extra compressor power and/or heat exchange surface area and excessive cooling water. One beneficial way to remove a portion of this excess water can be based on use of an adsorbent bed that can capture the humidity from the moist anode effluent and can then be ‘regenerated’ using dry anode feed gas, in order to provide additional water for the anode feed. HVAC-style (heating, ventilation, and air conditioning) adsorption wheels design can be applicable, because anode exhaust and inlet can be similar in pressure, and minor leakage from one stream to the other can have minimal impact on the overall process. In embodiments where CO<sub>2</sub> removal is performed using a cryogenic process, removal of water prior to or during CO<sub>2</sub> removal may be desirable, including removal by triethyleneglycol (TEG) system and/or desiccants. By contrast, if an amine wash is used for CO<sub>2</sub> removal, water can be removed from the anode exhaust downstream from the CO<sub>2</sub> removal stage.

[00113] Alternately or in addition to a CO<sub>2</sub> output stream and/or a water output stream, the anode output can be used to form one or more product streams containing a desired chemical or fuel product. Such a product stream or streams can correspond to a syngas stream, a hydrogen stream, or both syngas product and hydrogen product streams. For example, a hydrogen product stream containing at least about 70 vol% H<sub>2</sub>, such as at least about 90 vol% H<sub>2</sub> or at least about 95 vol% H<sub>2</sub>, can be formed. Additionally or alternately, a syngas stream containing at least about 70 vol% of H<sub>2</sub> and CO combined, such as at least about 90 vol% of H<sub>2</sub> and CO can be formed. The one or more product streams can have a gas volume corresponding to at least about 75% of the combined H<sub>2</sub> and CO gas volumes in the anode output, such as at least about 85% or at least about 90% of the combined H<sub>2</sub> and CO gas volumes. It is noted that the relative amounts of H<sub>2</sub> and CO in the products streams may differ from the H<sub>2</sub> to CO ratio in the anode output based on use of water gas shift reaction stages to convert between the products.

[00114] In some aspects, it can be desirable to remove or separate a portion of the H<sub>2</sub> present in the anode output. For example, in some aspects the H<sub>2</sub> to CO ratio in the anode exhaust can be at least about 3.0 : 1. By contrast, processes that make use of syngas, such as Fischer-Tropsch synthesis, may consume H<sub>2</sub> and CO in a different ratio, such as a ratio that is closer to 2 : 1. One alternative can be to use a water gas shift reaction to modify the content of the anode output to have an H<sub>2</sub> to CO ratio closer to a desired syngas composition. Another alternative can be to use a membrane separation to remove a portion of the H<sub>2</sub> present in the anode output to achieve a desired ratio of H<sub>2</sub> and CO, or still alternately to use a combination of membrane separation and water gas shift reactions. One advantage of using a membrane separation to remove only a portion of the H<sub>2</sub> in the anode output can be that the desired separation can be performed under relatively mild conditions. Since one goal can be to produce a retentate that still has a substantial H<sub>2</sub> content, a permeate of high purity hydrogen can be generated by membrane separation without requiring severe conditions. For example, rather than having a pressure on the permeate side of the membrane of about 100 kPaa or less (such as ambient pressure), the permeate side can be at an elevated pressure relative to ambient while still having sufficient driving force to perform the membrane separation. Additionally or alternately, a sweep gas such as methane can be used to provide a driving force for the membrane separation. This can

reduce the purity of the H<sub>2</sub> permeate stream, but may be advantageous, depending on the desired use for the permeate stream.

**[00115]** In various aspects of the invention, at least a portion of the anode exhaust stream (preferably after separation of CO<sub>2</sub> and/or H<sub>2</sub>O) can be used as a feed for a process external to the fuel cell and associated reforming stages. In various aspects, the anode exhaust can have a ratio of H<sub>2</sub> to CO of about 1.5 : 1 to about 10 : 1, such as at least about 3.0 : 1, or at least about 4.0 : 1, or at least about 5.0 : 1. A syngas stream can be generated or withdrawn from the anode exhaust. The anode exhaust gas, optionally after separation of CO<sub>2</sub> and/or H<sub>2</sub>O, and optionally after performing a water gas shift reaction and/or a membrane separation to remove excess hydrogen, can correspond to a stream containing substantial portions of H<sub>2</sub> and/or CO. For a stream with a relatively low content of CO, such as a stream where the ratio of H<sub>2</sub> to CO is at least about 3 : 1, the anode exhaust can be suitable for use as an H<sub>2</sub> feed. Examples of processes that could benefit from an H<sub>2</sub> feed can include, but are not limited to, refinery processes, an ammonia synthesis plant, or a turbine in a (different) power generation system, or combinations thereof. Depending on the application, still lower CO<sub>2</sub> contents can be desirable. For a stream with an H<sub>2</sub>-to-CO ratio of less than about 2.2 to 1 and greater than about 1.9 to 1, the stream can be suitable for use as a syngas feed. Examples of processes that could benefit from a syngas feed can include, but are not limited to, a gas-to-liquids plant (such as a plant using a Fischer-Tropsch process with a non-shifting catalyst) and/or a methanol synthesis plant. The amount of the anode exhaust used as a feed for an external process can be any convenient amount. Optionally, when a portion of the anode exhaust is used as a feed for an external process, a second portion of the anode exhaust can be recycled to the anode input and/or recycled to the combustion zone for a combustion-powered generator.

**[00116]** The input streams useful for different types of Fischer-Tropsch synthesis processes can provide an example of the different types of product streams that may be desirable to generate from the anode output. For a Fischer-Tropsch synthesis reaction system that uses a shifting catalyst, such as an iron-based catalyst, the desired input stream to the reaction system can include CO<sub>2</sub> in addition to H<sub>2</sub> and CO. If a sufficient amount of CO<sub>2</sub> is not present in the input stream, a Fischer-Tropsch catalyst with water gas shift activity can consume CO in order to generate additional CO<sub>2</sub>, resulting in a

syngas that can be deficient in CO. For integration of such a Fischer-Tropsch process with an MCFC fuel cell, the separation stages for the anode output can be operated to retain a desired amount of CO<sub>2</sub> (and optionally H<sub>2</sub>O) in the syngas product. By contrast, for a Fischer-Tropsch catalyst based on a non-shifting catalyst, any CO<sub>2</sub> present in a product stream could serve as an inert component in the Fischer-Tropsch reaction system.

[00117] In an aspect where the membrane is swept with a sweep gas such as a methane sweep gas, the methane sweep gas can correspond to a methane stream used as the anode fuel or in a different low pressure process, such as a boiler, furnace, gas turbine, or other fuel-consuming device. In such an aspect, low levels of CO<sub>2</sub> permeation across the membrane can have minimal consequence. Such CO<sub>2</sub> that may permeate across the membrane can have a minimal impact on the reactions within the anode, and such CO<sub>2</sub> can remain contained in the anode product. Therefore, the CO<sub>2</sub> (if any) lost across the membrane due to permeation does not need to be transferred again across the MCFC electrolyte. This can significantly reduce the separation selectivity requirement for the hydrogen permeation membrane. This can allow, for example, use of a higher-permeability membrane having a lower selectivity, which can enable use of a lower pressure and/or reduced membrane surface area. In such an aspect of the invention, the volume of the sweep gas can be a large multiple of the volume of hydrogen in the anode exhaust, which can allow the effective hydrogen concentration on the permeate side to be maintained close to zero. The hydrogen thus separated can be incorporated into the turbine-fed methane where it can enhance the turbine combustion characteristics, as described above.

[00118] It is noted that excess H<sub>2</sub> produced in the anode can represent a fuel where the greenhouse gases have already been separated. Any CO<sub>2</sub> in the anode output can be readily separated from the anode output, such as by using an amine wash, a cryogenic CO<sub>2</sub> separator, and/or a pressure or vacuum swing absorption process. Several of the components of the anode output (H<sub>2</sub>, CO, CH<sub>4</sub>) are not easily removed, while CO<sub>2</sub> and H<sub>2</sub>O can usually be readily removed. Depending on the embodiment, at least about 90 vol% of the CO<sub>2</sub> in the anode output can be separated out to form a relatively high purity CO<sub>2</sub> output stream. Thus, any CO<sub>2</sub> generated in the anode can be efficiently separated out to form a high purity CO<sub>2</sub> output stream. After separation, the remaining

portion of the anode output can correspond primarily to components with chemical and/or fuel value, as well as reduced amounts of CO<sub>2</sub> and/or H<sub>2</sub>O. Since a substantial portion of the CO<sub>2</sub> generated by the original fuel (prior to reforming) can have been separated out, the amount of CO<sub>2</sub> generated by subsequent burning of the remaining portion of the anode output can be reduced. In particular, to the degree that the fuel in the remaining portion of the anode output is H<sub>2</sub>, no additional greenhouse gases can typically be formed by burning of this fuel.

[00119] The anode exhaust can be subjected to a variety of gas processing options, including water-gas shift and separation of the components from each other. Two general anode processing schemes are shown in FIGS. 1 and 2.

[00120] FIG. 1 schematically shows an example of a reaction system for operating a fuel cell array of molten carbonate fuel cells in conjunction with a chemical synthesis process. In FIG. 1, a fuel stream 105 is provided to a reforming stage (or stages) 110 associated with the anode 127 of a fuel cell 120, such as a fuel cell that is part of a fuel cell stack in a fuel cell array. The reforming stage 110 associated with fuel cell 120 can be internal to a fuel cell assembly. In some optional aspects, an external reforming stage (not shown) can also be used to reform a portion of the reformable fuel in an input stream prior to passing the input stream into a fuel cell assembly. Fuel stream 105 can preferably include a reformable fuel, such as methane, other hydrocarbons, and/or other hydrocarbon-like compounds such as organic compounds containing carbon-hydrogen bonds. Fuel stream 105 can also optionally contain H<sub>2</sub> and/or CO, such as H<sub>2</sub> and/or CO provided by optional anode recycle stream 185. It is noted that anode recycle stream 185 is optional, and that in many aspects no recycle stream is provided from the anode exhaust 125 back to anode 127, either directly or indirectly via combination with fuel stream 105 or reformed fuel stream 115. After reforming, the reformed fuel stream 115 can be passed into anode 127 of fuel cell 120. A CO<sub>2</sub> and O<sub>2</sub>-containing stream 119 can also be passed into cathode 129. A flow of carbonate ions 122, CO<sub>3</sub><sup>2-</sup>, from the cathode portion 129 of the fuel cell can provide the remaining reactant needed for the anode fuel cell reactions. Based on the reactions in the anode 127, the resulting anode exhaust 125 can include H<sub>2</sub>O, CO<sub>2</sub>, one or more components corresponding to incompletely reacted fuel (H<sub>2</sub>, CO, CH<sub>4</sub>, or other components corresponding to a reformable fuel), and optionally one or more additional

nonreactive components, such as  $N_2$  and/or other contaminants that are part of fuel stream 105. The anode exhaust 125 can then be passed into one or more separation stages. For example, a  $CO_2$  removal stage 140 can correspond to a cryogenic  $CO_2$  removal system, an amine wash stage for removal of acid gases such as  $CO_2$ , or another suitable type of  $CO_2$  separation stage for separating a  $CO_2$  output stream 143 from the anode exhaust. Optionally, the anode exhaust can first be passed through a water gas shift reactor 130 to convert any CO present in the anode exhaust (along with some  $H_2O$ ) into  $CO_2$  and  $H_2$  in an optionally water gas shifted anode exhaust 135. Depending on the nature of the  $CO_2$  removal stage, a water condensation or removal stage 150 may be desirable to remove a water output stream 153 from the anode exhaust. Though shown in FIG. 1 after the  $CO_2$  separation stage 140, it may optionally be located before the  $CO_2$  separation stage 140 instead. Additionally, an optional membrane separation stage 160 for separation of  $H_2$  can be used to generate a high purity permeate stream 163 of  $H_2$ . The resulting retentate stream 166 can then be used as an input to a chemical synthesis process. Stream 166 could additionally or alternately be shifted in a second water-gas shift reactor 131 to adjust the  $H_2$ , CO, and  $CO_2$  content to a different ratio, producing an output stream 168 for further use in a chemical synthesis process. In FIG. 1, anode recycle stream 185 is shown as being withdrawn from the retentate stream 166, but the anode recycle stream 185 could additionally or alternately be withdrawn from other convenient locations in or between the various separation stages. The separation stages and shift reactor(s) could additionally or alternately be configured in different orders, and/or in a parallel configuration. Finally, a stream with a reduced content of  $CO_2$  139 can be generated as an output from cathode 129. For the sake of simplicity, various stages of compression and heat addition/removal that might be useful in the process, as well as steam addition or removal, are not shown.

**[00121]** As noted above, the various types of separations performed on the anode exhaust can be performed in any convenient order. FIG. 2 shows an example of an alternative order for performing separations on an anode exhaust. In FIG. 2, anode exhaust 125 can be initially passed into separation stage 260 for removing a portion 263 of the hydrogen content from the anode exhaust 125. This can allow, for example, reduction of the  $H_2$  content of the anode exhaust to provide a retentate 266 with a ratio

of H<sub>2</sub> to CO closer to 2 : 1. The ratio of H<sub>2</sub> to CO can then be further adjusted to achieve a desired value in a water gas shift stage 230. The water gas shifted output 235 can then pass through CO<sub>2</sub> separation stage 240 and water removal stage 250 to produce an output stream 275 suitable for use as an input to a desired chemical synthesis process. Optionally, output stream 275 could be exposed to an additional water gas shift stage (not shown). A portion of output stream 275 can optionally be recycled (not shown) to the anode input. Of course, still other combinations and sequencing of separation stages can be used to generate a stream based on the anode output that has a desired composition. For the sake of simplicity, various stages of compression and heat addition/removal that might be useful in the process, as well as steam addition or removal, are not shown.

#### Cathode Inputs and Outputs

[00122] Conventionally, a molten carbonate fuel cell can be operated based on drawing a desired load while consuming some portion of the fuel in the fuel stream delivered to the anode. The voltage of the fuel cell can then be determined by the load, fuel input to the anode, air and CO<sub>2</sub> provided to the cathode, and the internal resistances of the fuel cell. The CO<sub>2</sub> to the cathode can be conventionally provided in part by using the anode exhaust as at least a part of the cathode input stream. By contrast, the present invention can use separate/different sources for the anode input and cathode input. By removing any direct link between the composition of the anode input flow and the cathode input flow, additional options become available for operating the fuel cell, such as to generate excess synthesis gas, to improve capture of carbon dioxide, and/or to improve the total efficiency (electrical plus chemical power) of the fuel cell, among others.

[00123] In a molten carbonate fuel cell, the transport of carbonate ions across the electrolyte in the fuel cell can provide a method for transporting CO<sub>2</sub> from a first flow path to a second flow path, where the transport method can allow transport from a lower concentration (the cathode) to a higher concentration (the anode), which can thus facilitate capture of CO<sub>2</sub>. Part of the selectivity of the fuel cell for CO<sub>2</sub> separation can be based on the electrochemical reactions allowing the cell to generate electrical power. For nonreactive species (such as N<sub>2</sub>) that effectively do not participate in the electrochemical reactions within the fuel cell, there can be an insignificant amount of reaction and transport from cathode to anode. By contrast, the potential (voltage)

difference between the cathode and anode can provide a strong driving force for transport of carbonate ions across the fuel cell. As a result, the transport of carbonate ions in the molten carbonate fuel cell can allow CO<sub>2</sub> to be transported from the cathode (lower CO<sub>2</sub> concentration) to the anode (higher CO<sub>2</sub> concentration) with relatively high selectivity. However, a challenge in using molten carbonate fuel cells for carbon dioxide removal can be that the fuel cells have limited ability to remove carbon dioxide from relatively dilute cathode feeds. The voltage and/or power generated by a carbonate fuel cell can start to drop rapidly as the CO<sub>2</sub> concentration falls below about 2.0 vol%. As the CO<sub>2</sub> concentration drops further, e.g., to below about 1.0 vol%, at some point the voltage across the fuel cell can become low enough that little or no further transport of carbonate may occur and the fuel cell ceases to function. Thus, at least some CO<sub>2</sub> is likely to be present in the exhaust gas from the cathode stage of a fuel cell under commercially viable operating conditions.

**[00124]** The amount of carbon dioxide delivered to the fuel cell cathode(s) can be determined based on the CO<sub>2</sub> content of a source for the cathode inlet. One example of a suitable CO<sub>2</sub>-containing stream for use as a cathode input flow can be an output or exhaust flow from a combustion source. Examples of combustion sources include, but are not limited to, sources based on combustion of natural gas, combustion of coal, and/or combustion of other hydrocarbon-type fuels (including biologically derived fuels). Additional or alternate sources can include other types of boilers, fired heaters, furnaces, and/or other types of devices that burn carbon-containing fuels in order to heat another substance (such as water or air). To a first approximation, the CO<sub>2</sub> content of the output flow from a combustion source can be a minor portion of the flow. Even for a higher CO<sub>2</sub> content exhaust flow, such as the output from a coal-fired combustion source, the CO<sub>2</sub> content from most commercial coal-fired power plants can be about 15 vol% or less. More generally, the CO<sub>2</sub> content of an output or exhaust flow from a combustion source can be at least about 1.5 vol%, or at least about 1.6 vol%, or at least about 1.7 vol%, or at least about 1.8 vol% , or at least about 1.9 vol%, or at least greater 2 vol%, or at least about 4 vol%, or at least about 5 vol%, or at least about 6 vol%, or at least about 8 vol%. Additionally or alternately, the CO<sub>2</sub> content of an output or exhaust flow from a combustion source can be about 20 vol% or less, such as about 15 vol% or less, or about 12 vol% or less, or about 10 vol % or less, or about 9

vol % or less, or about 8 vol % or less, or about 7 vol% or less, or about 6.5 vol% or less, or about 6 vol% or less, or about 5.5 vol% or less, or about 5 vol% or less, or about 4.5 vol% or less. The concentrations given above are on a dry basis. It is noted that the lower CO<sub>2</sub> content values can be present in the exhaust from some natural gas or methane combustion sources, such as generators that are part of a power generation system that may or may not include an exhaust gas recycle loop.

**[00125]** Other potential sources for a cathode input stream can additionally or alternately include sources of bio-produced CO<sub>2</sub>. This can include, for example, CO<sub>2</sub> generated during processing of bio-derived compounds, such as CO<sub>2</sub> generated during ethanol production. An additional or alternate example can include CO<sub>2</sub> generated by combustion of a bio-produced fuel, such as combustion of lignocellulose. Still other additional or alternate potential CO<sub>2</sub> sources can correspond to output or exhaust streams from various industrial processes, such as CO<sub>2</sub>-containing streams generated by plants for manufacture of steel, cement, and/or paper.

**[00126]** Yet another additional or alternate potential source of CO<sub>2</sub> can be CO<sub>2</sub>-containing streams from a fuel cell. The CO<sub>2</sub>-containing stream from a fuel cell can correspond to a cathode output stream from a different fuel cell, an anode output stream from a different fuel cell, a recycle stream from the cathode output to the cathode input of a fuel cell, and/or a recycle stream from an anode output to a cathode input of a fuel cell. For example, an MCFC operated in standalone mode under conventional conditions can generate a cathode exhaust with a CO<sub>2</sub> concentration of at least about 5 vol%. Such a CO<sub>2</sub>-containing cathode exhaust could be used as a cathode input for an MCFC operated according to an aspect of the invention. More generally, other types of fuel cells that generate a CO<sub>2</sub> output from the cathode exhaust can additionally or alternately be used, as well as other types of CO<sub>2</sub>-containing streams not generated by a “combustion” reaction and/or by a combustion-powered generator. Optionally but preferably, a CO<sub>2</sub>-containing stream from another fuel cell can be from another molten carbonate fuel cell. For example, for molten carbonate fuel cells connected in series with respect to the cathodes, the output from the cathode for a first molten carbonate fuel cell can be used as the input to the cathode for a second molten carbonate fuel cell.

**[00127]** For various types of CO<sub>2</sub>-containing streams from sources other than combustion sources, the CO<sub>2</sub> content of the stream can vary widely. The CO<sub>2</sub> content

of an input stream to a cathode can contain at least about 2 vol% of CO<sub>2</sub>, such as at least about 4 vol%, or at least about 5 vol%, or at least about 6 vol%, or at least about 8 vol%. Additionally or alternately, the CO<sub>2</sub> content of an input stream to a cathode can be about 30 vol% or less, such as about 25 vol% or less, or about 20 vol% or less, or about 15 vol% or less, or about 10 vol% or less, or about 8 vol% or less, or about 6 vol% or less, or about 4 vol% or less. For some still higher CO<sub>2</sub> content streams, the CO<sub>2</sub> content can be greater than about 30 vol%, such as a stream substantially composed of CO<sub>2</sub> with only incidental amounts of other compounds. As an example, a gas-fired turbine without exhaust gas recycle can produce an exhaust stream with a CO<sub>2</sub> content of approximately 4.2 vol%. With EGR, a gas-fired turbine can produce an exhaust stream with a CO<sub>2</sub> content of about 6-8 vol%. Stoichiometric combustion of methane can produce an exhaust stream with a CO<sub>2</sub> content of about 11 vol%. Combustion of coal can produce an exhaust stream with a CO<sub>2</sub> content of about 15–20 vol%. Fired heaters using refinery off-gas can produce an exhaust stream with a CO<sub>2</sub> content of about 12–15 vol%. A gas turbine operated on a low BTU gas without any EGR can produce an exhaust stream with a CO<sub>2</sub> content of ~12 vol%.

[00128] In addition to CO<sub>2</sub>, a cathode input stream must include O<sub>2</sub> to provide the components necessary for the cathode reaction. Some cathode input streams can be based on having air as a component. For example, a combustion exhaust stream can be formed by combusting a hydrocarbon fuel in the presence of air. Such a combustion exhaust stream, or another type of cathode input stream having an oxygen content based on inclusion of air, can have an oxygen content of about 20 vol% or less, such as about 15 vol% or less, or about 10 vol% or less. Additionally or alternately, the oxygen content of the cathode input stream can be at least about 4 vol%, such as at least about 6 vol%, or at least about 8 vol%. More generally, a cathode input stream can have a suitable content of oxygen for performing the cathode reaction. In some aspects, this can correspond to an oxygen content of about 5 vol% to about 15 vol%, such as from about 7 vol% to about 9 vol%. For many types of cathode input streams, the combined amount of CO<sub>2</sub> and O<sub>2</sub> can correspond to less than about 21 vol% of the input stream, such as less than about 15 vol% of the stream or less than about 10 vol% of the stream. An air stream containing oxygen can be combined with a CO<sub>2</sub> source that has low

oxygen content. For example, the exhaust stream generated by burning coal may include a low oxygen content that can be mixed with air to form a cathode inlet stream. [00129] In addition to  $\text{CO}_2$  and  $\text{O}_2$ , a cathode input stream can also be composed of inert/non-reactive species such as  $\text{N}_2$ ,  $\text{H}_2\text{O}$ , and other typical oxidant (air) components. For example, for a cathode input derived from an exhaust from a combustion reaction, if air is used as part of the oxidant source for the combustion reaction, the exhaust gas can include typical components of air such as  $\text{N}_2$ ,  $\text{H}_2\text{O}$ , and other compounds in minor amounts that are present in air. Depending on the nature of the fuel source for the combustion reaction, additional species present after combustion based on the fuel source may include one or more of  $\text{H}_2\text{O}$ , oxides of nitrogen ( $\text{NO}_x$ ) and/or sulfur ( $\text{SO}_x$ ), and other compounds either present in the fuel and/or that are partial or complete combustion products of compounds present in the fuel, such as  $\text{CO}$ . These species may be present in amounts that do not poison the cathode catalyst surfaces though they may reduce the overall cathode activity. Such reductions in performance may be acceptable, or species that interact with the cathode catalyst may be reduced to acceptable levels by known pollutant removal technologies.

[00130] The amount of  $\text{O}_2$  present in a cathode input stream (such as an input cathode stream based on a combustion exhaust) can advantageously be sufficient to provide the oxygen needed for the cathode reaction in the fuel cell. Thus, the volume percentage of  $\text{O}_2$  can advantageously be at least 0.5 times the amount of  $\text{CO}_2$  in the exhaust. Optionally, as necessary, additional air can be added to the cathode input to provide sufficient oxidant for the cathode reaction. When some form of air is used as the oxidant, the amount of  $\text{N}_2$  in the cathode exhaust can be at least about 78 vol%, e.g., at least about 88 vol%, and/or about 95 vol% or less. In some aspects, the cathode input stream can additionally or alternately contain compounds that are generally viewed as contaminants, such as  $\text{H}_2\text{S}$  or  $\text{NH}_3$ . In other aspects, the cathode input stream can be cleaned to reduce or minimize the content of such contaminants.

[00131] In addition to the reaction to form carbonate ions for transport across the electrolyte, the conditions in the cathode can also be suitable for conversion of nitrogen oxides into nitrate and/or nitrate ions. Hereinafter, only nitrate ions will be referred to for convenience. The resulting nitrate ions can also be transported across the electrolyte for reaction in the anode.  $\text{NO}_x$  concentrations in a cathode input stream can

typically be on the order of ppm, so this nitrate transport reaction can have a minimal impact on the amount of carbonate transported across the electrolyte. However, this method of NO<sub>x</sub> removal can be beneficial for cathode input streams based on combustion exhausts from gas turbines, as this can provide a mechanism for reducing NO<sub>x</sub> emissions. The conditions in the cathode can additionally or alternately be suitable for conversion of unburned hydrocarbons (in combination with O<sub>2</sub> in the cathode input stream) to typical combustion products, such as CO<sub>2</sub> and H<sub>2</sub>O.

**[00132]** A suitable temperature for operation of an MCFC can be between about 450°C and about 750°C, such as at least about 500°C, e.g., with an inlet temperature of about 550°C and an outlet temperature of about 625°C. Prior to entering the cathode, heat can be added to or removed from the combustion exhaust, if desired, e.g., to provide heat for other processes, such as reforming the fuel input for the anode. For example, if the source for the cathode input stream is a combustion exhaust stream, the combustion exhaust stream may have a temperature greater than a desired temperature for the cathode inlet. In such an aspect, heat can be removed from the combustion exhaust prior to use as the cathode input stream. Alternatively, the combustion exhaust could be at very low temperature, for example after a wet gas scrubber on a coal-fired boiler, in which case the combustion exhaust can be below about 100°C. Alternatively, the combustion exhaust could be from the exhaust of a gas turbine operated in combined cycle mode, in which the gas can be cooled by raising steam to run a steam turbine for additional power generation. In this case, the gas can be below about 50°C. Heat can be added to a combustion exhaust that is cooler than desired.

#### Fuel Cell Arrangement

**[00133]** In various aspects, a configuration option for a fuel cell (such as a fuel cell array containing multiple fuel cell stacks) can be to divide the CO<sub>2</sub>-containing stream between a plurality of fuel cells. Some types of sources for CO<sub>2</sub>-containing streams can generate large volumetric flow rates relative to the capacity of an individual fuel cell. For example, the CO<sub>2</sub>-containing output stream from an industrial combustion source can typically correspond to a large flow volume relative to desirable operating conditions for a single MCFC of reasonable size. Instead of processing the entire flow in a single MCFC, the flow can be divided amongst a plurality of MCFC units, usually

at least some of which can be in parallel, so that the flow rate in each unit can be within a desired flow range.

**[00134]** A second configuration option can be to utilize fuel cells in series to successively remove CO<sub>2</sub> from a flow stream. Regardless of the number of initial fuel cells to which a CO<sub>2</sub>-containing stream can be distributed to in parallel, each initial fuel cell can be followed by one or more additional cells in series to further remove additional CO<sub>2</sub>. If the desired amount of CO<sub>2</sub> in the cathode output is sufficiently low, attempting to remove CO<sub>2</sub> from a cathode input stream down to the desired level in a single fuel cell or fuel cell stage could lead to a low and/or unpredictable voltage output for the fuel cell. Rather than attempting to remove CO<sub>2</sub> to the desired level in a single fuel cell or fuel cell stage, CO<sub>2</sub> can be removed in successive cells until a desired level can be achieved. For example, each cell in a series of fuel cells can be used to remove some percentage (e.g., about 50%) of the CO<sub>2</sub> present in a fuel stream. In such an example, if three fuel cells are used in series, the CO<sub>2</sub> concentration can be reduced (e.g., to about 15% or less of the original amount present, which can correspond to reducing the CO<sub>2</sub> concentration from about 6% to about 1% or less over the course of three fuel cells in series).

**[00135]** In another configuration, the operating conditions can be selected in early fuel stages in series to provide a desired output voltage while the array of stages can be selected to achieve a desired level of carbon separation. As an example, an array of fuel cells can be used with three fuel cells in series. The first two fuel cells in series can be used to remove CO<sub>2</sub> while maintaining a desired output voltage. The final fuel cell can then be operated to remove CO<sub>2</sub> to a desired concentration but at a lower voltage.

**[00136]** In still another configuration, there can be separate connectivity for the anodes and cathodes in a fuel cell array. For example, if the fuel cell array includes fuel cathodes connected in series, the corresponding anodes can be connected in any convenient manner, not necessarily matching up with the same arrangement as their corresponding cathodes, for example. This can include, for instance, connecting the anodes in parallel, so that each anode receives the same type of fuel feed, and/or connecting the anodes in a reverse series, so that the highest fuel concentration in the anodes can correspond to those cathodes having the lowest CO<sub>2</sub> concentration.

[00137] In yet another configuration, the amount of fuel delivered to one or more anode stages and/or the amount of CO<sub>2</sub> delivered to one or more cathode stages can be controlled in order to improve the performance of the fuel cell array. For example, a fuel cell array can have a plurality of cathode stages connected in series. In an array that includes three cathode stages in series, this can mean that the output from a first cathode stage can correspond to the input for a second cathode stage, and the output from the second cathode stage can correspond to the input for a third cathode stage. In this type of configuration, the CO<sub>2</sub> concentration can decrease with each successive cathode stage. To compensate for this reduced CO<sub>2</sub> concentration, additional hydrogen and/or methane can be delivered to the anode stages corresponding to the later cathode stages. The additional hydrogen and/or methane in the anodes corresponding to the later cathode stages can at least partially offset the loss of voltage and/or current caused by the reduced CO<sub>2</sub> concentration, which can increase the voltage and thus net power produced by the fuel cell. In another example, the cathodes in a fuel cell array can be connected partially in series and partially in parallel. In this type of example, instead of passing the entire combustion output into the cathodes in the first cathode stage, at least a portion of the combustion exhaust can be passed into a later cathode stage. This can provide an increased CO<sub>2</sub> content in a later cathode stage. Still other options for using variable feeds to either anode stages or cathode stages can be used if desired.

[00138] The cathode of a fuel cell can correspond to a plurality of cathodes from an array of fuel cells, as previously described. In some aspects, a fuel cell array can be operated to improve or maximize the amount of carbon transferred from the cathode to the anode. In such aspects, for the cathode output from the final cathode(s) in an array sequence (typically at least including a series arrangement, or else the final cathode(s) and the initial cathode(s) would be the same), the output composition can include about 2.0 vol% or less of CO<sub>2</sub> (e.g., about 1.5 vol% or less or about 1.2 vol% or less) and/or at least about 0.5 vol% of CO<sub>2</sub>, or at least about 1.0 vol%, or at least about 1.2 vol% or at least about 1.5 vol%. Due to this limitation, the net efficiency of CO<sub>2</sub> removal when using molten carbonate fuel cells can be dependent on the amount of CO<sub>2</sub> in the cathode input. For cathode input streams with CO<sub>2</sub> contents of greater than about 6 vol%, such as at least about 8%, the limitation on the amount of CO<sub>2</sub> that can be removed is not severe. However, for a combustion reaction using natural gas as a fuel

and with excess air, as is typically found in a gas turbine, the amount of  $\text{CO}_2$  in the combustion exhaust may only correspond to a  $\text{CO}_2$  concentration at the cathode input of less than about 5 vol%. Use of exhaust gas recycle can allow the amount of  $\text{CO}_2$  at the cathode input to be increased to at least about 5 vol%, e.g., at least about 6 vol%. If EGR is increased when using natural gas as a fuel to produce a  $\text{CO}_2$  concentration beyond about 6 vol%, then the flammability in the combustor can be decreased and the gas turbine may become unstable. However, when  $\text{H}_2$  is added to the fuel, the flammability window can be significantly increased, allowing the amount of exhaust gas recycle to be increased further, so that concentrations of  $\text{CO}_2$  at the cathode input of at least about 7.5 vol% or at least about 8 vol% can be achieved. As an example, based on a removal limit of about 1.5 vol% at the cathode exhaust, increasing the  $\text{CO}_2$  content at the cathode input from about 5.5 vol% to about 7.5 vol% can correspond to a ~10% increase in the amount of  $\text{CO}_2$  that can be captured using a fuel cell and transported to the anode loop for eventual  $\text{CO}_2$  separation. The amount of  $\text{O}_2$  in the cathode output can additionally or alternately be reduced, typically in an amount proportional to the amount of  $\text{CO}_2$  removed, which can result in small corresponding increases in the amount(s) of the other (non-cathode-reactive) species at the cathode exit.

[00139] In other aspects, a fuel cell array can be operated to improve or maximize the energy output of the fuel cell, such as the total energy output, the electric energy output, the syngas chemical energy output, or a combination thereof. For example, molten carbonate fuel cells can be operated with an excess of reformable fuel in a variety of situations, such as for generation of a syngas stream for use in chemical synthesis plant and/or for generation of a high purity hydrogen stream. The syngas stream and/or hydrogen stream can be used as a syngas source, a hydrogen source, as a clean fuel source, and/or for any other convenient application. In such aspects, the amount of  $\text{CO}_2$  in the cathode exhaust can be related to the amount of  $\text{CO}_2$  in the cathode input stream and the  $\text{CO}_2$  utilization at the desired operating conditions for improving or maximizing the fuel cell energy output.

[00140] Additionally or alternately, depending on the operating conditions, an MCFC can lower the  $\text{CO}_2$  content of a cathode exhaust stream to about 5.0 vol% or less, e.g., about 4.0 vol% or less, or about 2.0 vol% or less, or about 1.5 vol% or less, or about

1.2 vol% or less. Additionally or alternately, the CO<sub>2</sub> content of the cathode exhaust stream can be at least about 0.9 vol%, such as at least about 1.0 vol%, or at least about 1.2 vol%, or at least about 1.5 vol%.



#### Molten Carbonate Fuel Cell Operation

[00141] In some aspects, a fuel cell may be operated in a single pass or once-through mode. In single pass mode, reformed products in the anode exhaust are not returned to the anode inlet. Thus, recycling syngas, hydrogen, or some other product from the anode output directly to the anode inlet is not done in single pass operation. More generally, in single pass operation, reformed products in the anode exhaust are also not returned indirectly to the anode inlet, such as by using reformed products to process a fuel stream subsequently introduced into the anode inlet. Optionally, CO<sub>2</sub> from the anode outlet can be recycled to the cathode inlet during operation of an MCFC in single pass mode. More generally, in some alternative aspects, recycling from the anode outlet to the cathode inlet may occur for an MCFC operating in single pass mode. Heat from the anode exhaust or output may additionally or alternately be recycled in a single pass mode. For example, the anode output flow may pass through a heat exchanger that cools the anode output and warms another stream, such as an input stream for the anode and/or the cathode. Recycling heat from anode to the fuel cell is consistent with use in single pass or once-through operation. Optionally but not preferably, constituents of the anode output may be burned to provide heat to the fuel cell during single pass mode.

[00142] FIG. 3 shows a schematic example of the operation of an MCFC for generation of electrical power. In FIG. 3, the anode portion of the fuel cell can receive fuel and steam (H<sub>2</sub>O) as inputs, with outputs of water, CO<sub>2</sub>, and optionally excess H<sub>2</sub>, CH<sub>4</sub> (or other hydrocarbons), and/or CO. The cathode portion of the fuel cell can receive CO<sub>2</sub> and some oxidant (e.g., air/O<sub>2</sub>) as inputs, with an output corresponding to a reduced amount of CO<sub>2</sub> in O<sub>2</sub>-depleted oxidant (air). Within the fuel cell, CO<sub>3</sub><sup>2-</sup> ions formed in the cathode side can be transported across the electrolyte to provide the carbonate ions needed for the reactions occurring at the anode.

[00143] Several reactions can occur within a molten carbonate fuel cell such as the example fuel cell shown in FIG. 3. The reforming reactions can be optional, and can be reduced or eliminated if sufficient H<sub>2</sub> is provided directly to the anode. The following

reactions are based on CH<sub>4</sub>, but similar reactions can occur when other fuels are used in the fuel cell.



**[00144]** Reaction (1) represents the basic hydrocarbon reforming reaction to generate H<sub>2</sub> for use in the anode of the fuel cell. The CO formed in reaction (1) can be converted to H<sub>2</sub> by the water-gas shift reaction (2). The combination of reactions (1) and (2) is shown as reaction (3). Reactions (1) and (2) can occur external to the fuel cell, and/or the reforming can be performed internal to the anode.

**[00145]** Reactions (4) and (5), at the anode and cathode respectively, represent the reactions that can result in electrical power generation within the fuel cell. Reaction (4) combines H<sub>2</sub>, either present in the feed or optionally generated by reactions (1) and/or (2), with carbonate ions to form H<sub>2</sub>O, CO<sub>2</sub>, and electrons to the circuit. Reaction (5) combines O<sub>2</sub>, CO<sub>2</sub>, and electrons from the circuit to form carbonate ions. The carbonate ions generated by reaction (5) can be transported across the electrolyte of the fuel cell to provide the carbonate ions needed for reaction (4). In combination with the transport of carbonate ions across the electrolyte, a closed current loop can then be formed by providing an electrical connection between the anode and cathode.

**[00146]** In various embodiments, a goal of operating the fuel cell can be to improve the total efficiency of the fuel cell and/or the total efficiency of the fuel cell plus an integrated chemical synthesis process. This is typically in contrast to conventional operation of a fuel cell, where the goal can be to operate the fuel cell with high electrical efficiency for using the fuel provided to the cell for generation of electrical power. As defined above, total fuel cell efficiency may be determined by dividing the electric output of the fuel cell plus the lower heating value of the fuel cell outputs by the lower heating value of the input components for the fuel cell. In other words,  $\text{TFCE} = (\text{LHV}(\text{el}) + \text{LHV}(\text{sg out}))/\text{LHV}(\text{in})$ , where LHV(in) and LHV(sg out) refer to the LHV of the fuel components (such as H<sub>2</sub>, CH<sub>4</sub>, and/or CO) delivered to the fuel cell

and syngas ( $\text{H}_2$ , CO and/or  $\text{CO}_2$ ) in the anode outlet streams or flows, respectively. This can provide a measure of the electric energy plus chemical energy generated by the fuel cell and/or the integrated chemical process. It is noted that under this definition of total efficiency, heat energy used within the fuel cell and/or used within the integrated fuel cell / chemical synthesis system can contribute to total efficiency. However, any excess heat exchanged or otherwise withdrawn from the fuel cell or integrated fuel cell / chemical synthesis system is excluded from the definition. Thus, if excess heat from the fuel cell is used, for example, to generate steam for electricity generation by a steam turbine, such excess heat is excluded from the definition of total efficiency.

**[00147]** Several operational parameters may be manipulated to operate a fuel cell with excess reformable fuel. Some parameters can be similar to those currently recommended for fuel cell operation. In some aspects, the cathode conditions and temperature inputs to the fuel cell can be similar to those recommended in the literature. For example, the desired electrical efficiency and the desired total fuel cell efficiency may be achieved at a range of fuel cell operating temperatures typical for molten carbonate fuel cells. In typical operation, the temperature can increase across the fuel cell.

**[00148]** In other aspects, the operational parameters of the fuel cell can deviate from typical conditions so that the fuel cell is operated to allow a temperature decrease from the anode inlet to the anode outlet and/or from the cathode inlet to the cathode outlet. For example, the reforming reaction to convert a hydrocarbon into  $\text{H}_2$  and CO is an endothermic reaction. If a sufficient amount of reforming is performed in a fuel cell anode relative to the amount of oxidation of hydrogen to generate electrical current, the net heat balance in the fuel cell can be endothermic. This can cause a temperature drop between the inlets and outlets of a fuel cell. During endothermic operation, the temperature drop in the fuel cell can be controlled so that the electrolyte in the fuel cell remains in a molten state.

**[00149]** Parameters that can be manipulated in a way so as to differ from those currently recommended can include the amount of fuel provided to the anode, the composition of the fuel provided to the anode, and/or the separation and capture of syngas in the anode output without significant recycling of syngas from the anode

exhaust to either the anode input or the cathode input. In some aspects, no recycle of syngas or hydrogen from the anode exhaust to either the anode input or the cathode input can be allowed to occur, either directly or indirectly. In additional or alternative aspects, a limited amount of recycle can occur. In such aspects, the amount of recycle from the anode exhaust to the anode input and/or the cathode input can be less than about 10 vol% of the anode exhaust, such as less than about 5 vol%, or less than about 1 vol%.

**[00150]** Additionally or alternately, a goal of operating a fuel cell can be to separate CO<sub>2</sub> from the output stream of a combustion reaction or another process that produces a CO<sub>2</sub> output stream, in addition to allowing generation of electric power. In such aspects, the combustion reaction(s) can be used to power one or more generators or turbines, which can provide a majority of the power generated by the combined generator/fuel cell system. Rather than operating the fuel cell to optimize power generation by the fuel cell, the system can instead be operated to improve the capture of carbon dioxide from the combustion-powered generator while reducing or minimizing the number of fuel cells required for capturing the carbon dioxide. Selecting an appropriate configuration for the input and output flows of the fuel cell, as well as selecting appropriate operating conditions for the fuel cell, can allow for a desirable combination of total efficiency and carbon capture.

**[00151]** In some embodiments, the fuel cells in a fuel cell array can be arranged so that only a single stage of fuel cells (such as fuel cell stacks) can be present. In this type of embodiment, the anode fuel utilization for the single stage can represent the anode fuel utilization for the array. Another option can be that a fuel cell array can contain multiple stages of anodes and multiple stages of cathodes, with each anode stage having a fuel utilization within the same range, such as each anode stage having a fuel utilization within 10% of a specified value, for example within 5% of a specified value. Still another option can be that each anode stage can have a fuel utilization equal to a specified value or lower than the specified value by less than an amount, such as having each anode stage be not greater than a specified value by 10% or less, for example, by 5% or less. As an illustrative example, a fuel cell array with a plurality of anode stages can have each anode stage be within about 10% of 50% fuel utilization, which would correspond to each anode stage having a fuel utilization between about 40% and about

60%. As another example, a fuel cell array with a plurality of stages can have each anode stage be not greater than 60% anode fuel utilization with the maximum deviation being about 5% less, which would correspond to each anode stage having a fuel utilization between about 55% to about 60%. In still another example, one or more stages of fuel cells in a fuel cell array can be operated at a fuel utilization from about 30% to about 50%, such as operating a plurality of fuel cell stages in the array at a fuel utilization from about 30% to about 50%. More generally, any of the above types of ranges can be paired with any of the anode fuel utilization values specified herein.

**[00152]** Still another additional or alternate option can include specifying a fuel utilization for less than all of the anode stages. For example, in some aspects of the invention fuel cells/stacks can be arranged at least partially in one or more series arrangements such that anode fuel utilization can be specified for the first anode stage in a series, the second anode stage in a series, the final anode stage in a series, or any other convenient anode stage in a series. As used herein, the “first” stage in a series corresponds to the stage (or set of stages, if the arrangement contains parallel stages as well) to which input is directly fed from the fuel source(s), with later (“second,” “third,” “final,” etc.) stages representing the stages to which the output from one or more previous stages is fed, instead of directly from the respective fuel source(s). In situations where both output from previous stages and input directly from the fuel source(s) are co-fed into a stage, there can be a “first” (set of) stage(s) and a “last” (set of) stage(s), but other stages (“second,” “third,” etc.) can be more tricky among which to establish an order (e.g., in such cases, ordinal order can be determined by concentration levels of one or more components in the composite input feed composition, such as CO<sub>2</sub> for instance, from highest concentration “first” to lowest concentration “last” with approximately similar compositional distinctions representing the same ordinal level.)

**[00153]** Yet another additional or alternate option can be to specify the anode fuel utilization corresponding to a particular cathode stage (again, where fuel cells/stacks can be arranged at least partially in one or more series arrangements). As noted above, based on the direction of the flows within the anodes and cathodes, the first cathode stage may not correspond to (be across the same fuel cell membrane from) the first anode stage. Thus, in some aspects of the invention, the anode fuel utilization can be

specified for the first cathode stage in a series, the second cathode stage in a series, the final cathode stage in a series, or any other convenient cathode stage in a series.

[00154] Yet still another additional or alternate option can be to specify an overall average of fuel utilization over all fuel cells in a fuel cell array. In various aspects, the overall average of fuel utilization for a fuel cell array can be about 65% or less, for example, about 60% or less, about 55% or less, about 50% or less, or about 45% or less (additionally or alternately, the overall average fuel utilization for a fuel cell array can be at least about 25%, for example at least about 30%, at least about 35%, or at least about 40%). Such an average fuel utilization need not necessarily constrain the fuel utilization in any single stage, so long as the array of fuel cells meets the desired fuel utilization.

#### Applications for CO<sub>2</sub> Output after Capture

[00155] In various aspects of the invention, the systems and methods described above can allow for production of carbon dioxide as a pressurized fluid. For example, the CO<sub>2</sub> generated from a cryogenic separation stage can initially correspond to a pressurized CO<sub>2</sub> liquid with a purity of at least about 90%, *e.g.*, at least about 95%, at least about 97%, at least about 98%, or at least about 99%. This pressurized CO<sub>2</sub> stream can be used, *e.g.*, for injection into wells in order to further enhance oil or gas recovery such as in secondary oil recovery. When done in proximity to a facility that encompasses a gas turbine, the overall system may benefit from additional synergies in use of electrical/mechanical power and/or through heat integration with the overall system.

[00156] Alternatively, for systems dedicated to an enhanced oil recovery (EOR) application (*i.e.*, not comingled in a pipeline system with tight compositional standards), the CO<sub>2</sub> separation requirements may be substantially relaxed. The EOR application can be sensitive to the presence of O<sub>2</sub>, so O<sub>2</sub> can be absent, in some embodiments, from a CO<sub>2</sub> stream intended for use in EOR. However, the EOR application can tend to have a low sensitivity to dissolved CO, H<sub>2</sub>, and/or CH<sub>4</sub>. Also, pipelines that transport the CO<sub>2</sub> can be sensitive to these impurities. Those dissolved gases can typically have only subtle impacts on the solubilizing ability of CO<sub>2</sub> used for EOR. Injecting gases such as CO, H<sub>2</sub>, and/or CH<sub>4</sub> as EOR gases can result in some

loss of fuel value recovery, but such gases can be otherwise compatible with EOR applications.

[00157] Additionally or alternately, a potential use for CO<sub>2</sub> as a pressurized liquid can be as a nutrient in biological processes such as algae growth/harvesting. The use of MCFCs for CO<sub>2</sub> separation can ensure that most biologically significant pollutants could be reduced to acceptably low levels, resulting in a CO<sub>2</sub>-containing stream having only minor amounts of other “contaminant” gases (such as CO, H<sub>2</sub>, N<sub>2</sub>, and the like, and combinations thereof) that are unlikely to substantially negatively affect the growth of photosynthetic organisms. This can be in stark contrast to the output streams generated by most industrial sources, which can often contain potentially highly toxic material such as heavy metals.

[00158] In this type of aspect of the invention, the CO<sub>2</sub> stream generated by separation of CO<sub>2</sub> in the anode loop can be used to produce biofuels and/or chemicals, as well as precursors thereof. Further additionally or alternately, CO<sub>2</sub> may be produced as a dense fluid, allowing for much easier pumping and transport across distances, *e.g.*, to large fields of photosynthetic organisms. Conventional emission sources can emit hot gas containing modest amounts of CO<sub>2</sub> (*e.g.*, about 4-15%) mixed with other gases and pollutants. These materials would normally need to be pumped as a dilute gas to an algae pond or biofuel “farm”. By contrast, the MCFC system according to the invention can produce a concentrated CO<sub>2</sub> stream (~60-70% by volume on a dry basis) that can be concentrated further to 95%+ (for example 96%+, 97%+, 98%+, or 99%+) and easily liquefied. This stream can then be transported easily and efficiently over long distances at relatively low cost and effectively distributed over a wide area. In these embodiments, residual heat from the combustion source/MCFC may be integrated into the overall system as well.

[00159] An alternative embodiment may apply where the CO<sub>2</sub> source/MCFC and biological/ chemical production sites are co-located. In that case, only minimal compression may be necessary (*i.e.*, to provide enough CO<sub>2</sub> pressure to use in the biological production, *e.g.*, from about 15 psig to about 150 psig). Several novel arrangements can be possible in such a case. Secondary reforming may optionally be applied to the anode exhaust to reduce CH<sub>4</sub> content, and water-gas shift may optionally additionally or alternately be present to drive any remaining CO into CO<sub>2</sub> and H<sub>2</sub>.

**[00160]** The components from an anode output stream and/or cathode output stream can be used for a variety of purposes. One option can be to use the anode output as a source of hydrogen, as described above. For an MCFC integrated with or co-located with a refinery, the hydrogen can be used as a hydrogen source for various refinery processes, such as hydroprocessing. Another option can be to additionally or alternately use hydrogen as a fuel source where the CO<sub>2</sub> from combustion has already been “captured.” Such hydrogen can be used in a refinery or other industrial setting as a fuel for a boiler, furnace, and/or fired heater, and/or the hydrogen can be used as a feed for an electric power generator, such as a turbine. Hydrogen from an MCFC fuel cell can further additionally or alternately be used as an input stream for other types of fuel cells that require hydrogen as an input, possibly including vehicles powered by fuel cells. Still another option can be to additionally or alternately use syngas generated as an output from an MCFC fuel cell as a fermentation input.

**[00161]** Another option can be to additionally or alternately use syngas generated from the anode output. Of course, syngas can be used as a fuel, although a syngas based fuel can still lead to some CO<sub>2</sub> production when burned as fuel. In other aspects, a syngas output stream can be used as an input for a chemical synthesis process. One option can be to additionally or alternately use syngas for a Fischer-Tropsch type process, and/or another process where larger hydrocarbon molecules are formed from the syngas input. Another option can be to additionally or alternately use syngas to form an intermediate product such as methanol. Methanol could be used as the final product, but in other aspects methanol generated from syngas can be used to generate larger compounds, such as gasoline, olefins, aromatics, and/or other products. It is noted that a small amount of CO<sub>2</sub> can be acceptable in the syngas feed to a methanol synthesis process, and/or to a Fischer-Tropsch process utilizing a shifting catalyst. Hydroformylation is an additional or alternate example of still another synthesis process that can make use of a syngas input.

**[00162]** It is noted that one variation on use of an MCFC to generate syngas can be to use MCFC fuel cells as part of a system for processing methane and/or natural gas withdrawn by an offshore oil platform or other production system that is a considerable distance from its ultimate market. Instead of attempting to transport the gas phase output from a well, or attempting to store the gas phase product for an extended period,

the gas phase output from a well can be used as the input to an MCFC fuel cell array. This can lead to a variety of benefits. First, the electric power generated by the fuel cell array can be used as a power source for the platform. Additionally, the syngas output from the fuel cell array can be used as an input for a Fischer-Tropsch process at the production site. This can allow for formation of liquid hydrocarbon products more easily transported by pipeline, ship, or railcar from the production site to, for example, an on-shore facility or a larger terminal.

[00163] Still other integration options can additionally or alternately include using the cathode output as a source of higher purity, heated nitrogen. The cathode input can often include a large portion of air, which means a substantial portion of nitrogen can be included in the cathode input. The fuel cell can transport CO<sub>2</sub> and O<sub>2</sub> from the cathode across the electrolyte to the anode, and the cathode outlet can have lower concentrations of CO<sub>2</sub> and O<sub>2</sub>, and thus a higher concentration of N<sub>2</sub> than found in air. With subsequent removal of the residual O<sub>2</sub> and CO<sub>2</sub>, this nitrogen output can be used as an input for production of ammonia or other nitrogen-containing chemicals, such as urea, ammonium nitrate, and/or nitric acid. It is noted that urea synthesis could additionally or alternately use CO<sub>2</sub> separate from the anode output as an input feed.

#### Integration Example: Applications for Integration with Combustion Turbines

[00164] In some aspects of the invention, a combustion source for generating power and exhausting a CO<sub>2</sub>-containing exhaust can be integrated with the operation of molten carbonate fuel cells. An example of a suitable combustion source is a gas turbine. Preferably, the gas turbine can combust natural gas, methane gas, or another hydrocarbon gas in a combined cycle mode integrated with steam generation and heat recovery for additional efficiency. Modern natural gas combined cycle efficiencies are about 60% for the largest and newest designs. The resulting CO<sub>2</sub>-containing exhaust gas stream can be produced at an elevated temperature compatible with the MCFC operation, such as 300°C – 700°C and preferably 500°C – 650°C. The gas source can optionally but preferably be cleaned of contaminants such as sulfur that can poison the MCFC before entering the turbine. Alternatively, the gas source can be a coal-fired generator, wherein the exhaust gas would typically be cleaned post-combustion due to the greater level of contaminants in the exhaust gas. In such an alternative, some heat

exchange to/from the gas may be necessary to enable clean-up at lower temperatures. In additional or alternate embodiments, the source of the CO<sub>2</sub>-containing exhaust gas can be the output from a boiler, combustor, or other heat source that burns carbon-rich fuels. In other additional or alternate embodiments, the source of the CO<sub>2</sub>-containing exhaust gas can be bio-produced CO<sub>2</sub> in combination with other sources.

**[00165]** For integration with a combustion source, some alternative configurations for processing of a fuel cell anode can be desirable. For example, an alternative configuration can be to recycle at least a portion of the exhaust from a fuel cell anode to the input of a fuel cell anode. The output stream from an MCFC anode can include H<sub>2</sub>O, CO<sub>2</sub>, optionally CO, and optionally but typically unreacted fuel (such as H<sub>2</sub> or CH<sub>4</sub>) as the primary output components. Instead of using this output stream as an external fuel stream and/or an input stream for integration with another process, one or more separations can be performed on the anode output stream in order to separate the CO<sub>2</sub> from the components with potential fuel value, such as H<sub>2</sub> or CO. The components with fuel value can then be recycled to the input of an anode.

**[00166]** This type of configuration can provide one or more benefits. First, CO<sub>2</sub> can be separated from the anode output, such as by using a cryogenic CO<sub>2</sub> separator. Several of the components of the anode output (H<sub>2</sub>, CO, CH<sub>4</sub>) are not easily condensable components, while CO<sub>2</sub> and H<sub>2</sub>O can be separated individually as condensed phases. Depending on the embodiment, at least about 90 vol% of the CO<sub>2</sub> in the anode output can be separated to form a relatively high purity CO<sub>2</sub> output stream. Alternatively, in some aspects less CO<sub>2</sub> can be removed from the anode output, so that about 50 vol% to about 90 vol% of the CO<sub>2</sub> in the anode output can be separated out, such as about 80 vol% or less or about 70 vol% or less. After separation, the remaining portion of the anode output can correspond primarily to components with fuel value, as well as reduced amounts of CO<sub>2</sub> and/or H<sub>2</sub>O. This portion of the anode output after separation can be recycled for use as part of the anode input, along with additional fuel. In this type of configuration, even though the fuel utilization in a single pass through the MCFC(s) may be low, the unused fuel can be advantageously recycled for another pass through the anode. As a result, the single-pass fuel utilization can be at a reduced level, while avoiding loss (exhaust) of unburned fuel to the environment.

[00167] Additionally or alternatively to recycling a portion of the anode exhaust to the anode input, another configuration option can be to use a portion of the anode exhaust as an input for a combustion reaction for a turbine or other combustion device, such as a boiler, furnace, and/or fired heater. The relative amounts of anode exhaust recycled to the anode input and/or as an input to the combustion device can be any convenient or desirable amount. If the anode exhaust is recycled to only one of the anode input and the combustion device, the amount of recycle can be any convenient amount, such as up to 100% of the portion of the anode exhaust remaining after any separation to remove CO<sub>2</sub> and/or H<sub>2</sub>O. When a portion of the anode exhaust is recycled to both the anode input and the combustion device, the total recycled amount by definition can be 100% or less of the remaining portion of anode exhaust. Otherwise, any convenient split of the anode exhaust can be used. In various embodiments of the invention, the amount of recycle to the anode input can be at least about 10% of the anode exhaust remaining after separations, for example at least about 25%, at least about 40%, at least about 50%, at least about 60%, at least about 75%, or at least about 90%. Additionally or alternately in those embodiments, the amount of recycle to the anode input can be about 90% or less of the anode exhaust remaining after separations, for example about 75% or less, about 60% or less, about 50% or less, about 40% or less, about 25% or less, or about 10% or less. Further additionally or alternately, in various embodiments of the invention, the amount of recycle to the combustion device can be at least about 10% of the anode exhaust remaining after separations, for example at least about 25%, at least about 40%, at least about 50%, at least about 60%, at least about 75%, or at least about 90%. Additionally or alternately in those embodiments, the amount of recycle to the combustion device can be about 90% or less of the anode exhaust remaining after separations, for example about 75% or less, about 60% or less, about 50% or less, about 40% or less, about 25% or less, or about 10% or less.

[00168] In still other alternative aspects of the invention, the fuel for a combustion device can additionally or alternately be a fuel with an elevated quantity of components that are inert and/or otherwise act as a diluent in the fuel. CO<sub>2</sub> and N<sub>2</sub> are examples of components in a natural gas feed that can be relatively inert during a combustion reaction. When the amount of inert components in a fuel feed reaches a sufficient level, the performance of a turbine or other combustion source can be impacted. The

impact can be due in part to the ability of the inert components to absorb heat, which can tend to quench the combustion reaction. Examples of fuel feeds with a sufficient level of inert components can include fuel feeds containing at least about 20 vol% CO<sub>2</sub>, or fuel feeds containing at least about 40 vol% N<sub>2</sub>, or fuel feeds containing combinations of CO<sub>2</sub> and N<sub>2</sub> that have sufficient inert heat capacity to provide similar quenching ability. (It is noted that CO<sub>2</sub> has a greater heat capacity than N<sub>2</sub>, and therefore lower concentrations of CO<sub>2</sub> can have a similar impact as higher concentrations of N<sub>2</sub>. CO<sub>2</sub> can also participate in the combustion reactions more readily than N<sub>2</sub>, and in doing so remove H<sub>2</sub> from the combustion. This consumption of H<sub>2</sub> can have a large impact on the combustion of the fuel, by reducing the flame speed and narrowing the flammability range of the air and fuel mixture.) More generally, for a fuel feed containing inert components that impact the flammability of the fuel feed, the inert components in the fuel feed can be at least about 20 vol%, such as at least about 40 vol%, or at least about 50 vol%, or at least about 60 vol%. Preferably, the amount of inert components in the fuel feed can be about 80 vol% or less.

**[00169]** When a sufficient amount of inert components are present in a fuel feed, the resulting fuel feed can be outside of the flammability window for the fuel components of the feed. In this type of situation, addition of H<sub>2</sub> from a recycled portion of the anode exhaust to the combustion zone for the generator can expand the flammability window for the combination of fuel feed and H<sub>2</sub>, which can allow, for example, a fuel feed containing at least about 20 vol% CO<sub>2</sub> or at least about 40% N<sub>2</sub> (or other combinations of CO<sub>2</sub> and N<sub>2</sub>) to be successfully combusted.

**[00170]** Relative to a total volume of fuel feed and H<sub>2</sub> delivered to a combustion zone, the amount of H<sub>2</sub> for expanding the flammability window can be at least about 5 vol% of the total volume of fuel feed plus H<sub>2</sub>, such as at least about 10 vol%, and/or about 25 vol% or less. Another option for characterizing the amount of H<sub>2</sub> to add to expand the flammability window can be based on the amount of fuel components present in the fuel feed before H<sub>2</sub> addition. Fuel components can correspond to methane, natural gas, other hydrocarbons, and/or other components conventionally viewed as fuel for a combustion-powered turbine or other generator. The amount of H<sub>2</sub> added to the fuel feed can correspond to at least about one third of the volume of fuel components (1 : 3 ratio of H<sub>2</sub> : fuel component) in the fuel feed, such as at least about half of the volume

of the fuel components (1 : 2 ratio). Additionally or alternately, the amount of H<sub>2</sub> added to the fuel feed can be roughly equal to the volume of fuel components in the fuel feed (1 : 1 ratio) or less. For example, for a feed containing about 30 vol% CH<sub>4</sub>, about 10% N<sub>2</sub>, and about 60% CO<sub>2</sub>, a sufficient amount of anode exhaust can be added to the fuel feed to achieve about a 1 : 2 ratio of H<sub>2</sub> to CH<sub>4</sub>. For an idealized anode exhaust that contained only H<sub>2</sub>, addition of H<sub>2</sub> to achieve a 1 : 2 ratio would result in a feed containing about 26 vol% CH<sub>4</sub>, 13 vol% H<sub>2</sub>, 9 vol% N<sub>2</sub>, and 52 vol% CO<sub>2</sub>.

#### Exhaust Gas Recycle

[00171] Aside from providing exhaust gas to a fuel cell array for capture and eventual separation of the CO<sub>2</sub>, an additional or alternate potential use for exhaust gas can include recycle back to the combustion reaction to increase the CO<sub>2</sub> content. When hydrogen is available for addition to the combustion reaction, such as hydrogen from the anode exhaust of the fuel cell array, further benefits can be gained from using recycled exhaust gas to increase the CO<sub>2</sub> content within the combustion reaction.

[00172] In various aspects of the invention, the exhaust gas recycle loop of a power generation system can receive a first portion of the exhaust gas from combustion, while the fuel cell array can receive a second portion. The amount of exhaust gas from combustion recycled to the combustion zone of the power generation system can be any convenient amount, such as at least about 15% (by volume), for example at least about 25%, at least about 35%, at least about 45%, or at least about 50%. Additionally or alternately, the amount of combustion exhaust gas recirculated to the combustion zone can be about 65% (by volume) or less, e.g., about 60% or less, about 55% or less, about 50% or less, or about 45% or less.

[00173] In one or more aspects of the invention, a mixture of an oxidant (such as air and/or oxygen-enriched air) and fuel can be combusted and (simultaneously) mixed with a stream of recycled exhaust gas. The stream of recycled exhaust gas, which can generally include products of combustion such as CO<sub>2</sub>, can be used as a diluent to control, adjust, or otherwise moderate the temperature of combustion and of the exhaust that can enter the succeeding expander. As a result of using oxygen-enriched air, the recycled exhaust gas can have an increased CO<sub>2</sub> content, thereby allowing the expander to operate at even higher expansion ratios for the same inlet and discharge temperatures, thereby enabling significantly increased power production.

**[00174]** A gas turbine system can represent one example of a power generation system where recycled exhaust gas can be used to enhance the performance of the system. The gas turbine system can have a first/main compressor coupled to an expander via a shaft. The shaft can be any mechanical, electrical, or other power coupling, thereby allowing a portion of the mechanical energy generated by the expander to drive the main compressor. The gas turbine system can also include a combustion chamber configured to combust a mixture of a fuel and an oxidant. In various aspects of the invention, the fuel can include any suitable hydrocarbon gas/liquid, such as syngas, natural gas, methane, ethane, propane, butane, naphtha diesel, kerosene, aviation fuel, coal derived fuel, bio-fuel, oxygenated hydrocarbon feedstock, or any combinations thereof. The oxidant can, in some embodiments, be derived from a second or inlet compressor fluidly coupled to the combustion chamber and adapted to compress a feed oxidant. In one or more embodiments of the invention, the feed oxidant can include atmospheric air and/or enriched air. When the oxidant includes enriched air alone or a mixture of atmospheric air and enriched air, the enriched air can be compressed by the inlet compressor (in the mixture, either before or after being mixed with the atmospheric air). The enriched air and/or the air-enriched air mixture can have an overall oxygen concentration of at least about 25 volume %, e.g., at least about 30 volume %, at least about 35 volume %, at least about 40 volume %, at least about 45 volume %, or at least about 50 volume %. Additionally or alternately, the enriched air and/or the air-enriched air mixture can have an overall oxygen concentration of about 80 volume % or less, such as about 70 volume % or less.

**[00175]** The enriched air can be derived from any one or more of several sources. For example, the enriched air can be derived from such separation technologies as membrane separation, pressure swing adsorption, temperature swing adsorption, nitrogen plant-byproduct streams, and/or combinations thereof. The enriched air can additionally or alternately be derived from an air separation unit (ASU), such as a cryogenic ASU, for producing nitrogen for pressure maintenance or other purposes. In certain embodiments of the invention, the reject stream from such an ASU can be rich in oxygen, having an overall oxygen content from about 50 volume % to about 70 volume %, can be used as at least a portion of the enriched air and subsequently diluted, if needed, with unprocessed atmospheric air to obtain the desired oxygen concentration.

[00176] In addition to the fuel and oxidant, the combustion chamber can optionally also receive a compressed recycle exhaust gas, such as an exhaust gas recirculation primarily having CO<sub>2</sub> and nitrogen components. The compressed recycle exhaust gas can be derived from the main compressor, for instance, and adapted to help facilitate combustion of the oxidant and fuel, e.g., by moderating the temperature of the combustion products. As can be appreciated, recirculating the exhaust gas can serve to increase CO<sub>2</sub> concentration.

[00177] An exhaust gas directed to the inlet of the expander can be generated as a product of combustion reaction. The exhaust gas can have a heightened CO<sub>2</sub> content based, at least in part, on the introduction of recycled exhaust gas into the combustion reaction. As the exhaust gas expands through the expander, it can generate mechanical power to drive the main compressor, to drive an electrical generator, and/or to power other facilities.

[00178] The power generation system can, in many embodiments, also include an exhaust gas recirculation (EGR) system. In one or more aspects of the invention, the EGR system can include a heat recovery steam generator (HRSG) and/or another similar device fluidly coupled to a steam gas turbine. In at least one embodiment, the combination of the HRSG and the steam gas turbine can be characterized as a power-producing closed Rankine cycle. In combination with the gas turbine system, the HRSG and the steam gas turbine can form part of a combined-cycle power generating plant, such as a natural gas combined-cycle (NGCC) plant. The gaseous exhaust can be introduced to the HRSG in order to generate steam and a cooled exhaust gas. The HRSG can include various units for separating and/or condensing water out of the exhaust stream, transferring heat to form steam, and/or modifying the pressure of streams to a desired level. In certain embodiments, the steam can be sent to the steam gas turbine to generate additional electrical power.

[00179] After passing through the HRSG and optional removal of at least some H<sub>2</sub>O, the CO<sub>2</sub>-containing exhaust stream can, in some embodiments, be recycled for use as an input to the combustion reaction. As noted above, the exhaust stream can be compressed (or decompressed) to match the desired reaction pressure within the vessel for the combustion reaction.

#### Example of Integrated System

[00180] FIG. 4 schematically shows an example of an integrated system including introduction of both CO<sub>2</sub>-containing recycled exhaust gas and H<sub>2</sub> or CO from the fuel cell anode exhaust into the combustion reaction for powering a turbine. In FIG. 4, the turbine can include a compressor 402, a shaft 404, an expander 406, and a combustion zone 415. An oxygen source 411 (such as air and/or oxygen-enriched air) can be combined with recycled exhaust gas 498 and compressed in compressor 402 prior to entering combustion zone 415. A fuel 412, such as CH<sub>4</sub>, and optionally a stream containing H<sub>2</sub> or CO 187 can be delivered to the combustion zone. The fuel and oxidant can be reacted in zone 415 and optionally but preferably passed through expander 406 to generate electric power. The exhaust gas from expander 106 can be used to form two streams, e.g., a CO<sub>2</sub>-containing stream 422 (that can be used as an input feed for fuel cell array 425) and another CO<sub>2</sub>-containing stream 492 (that can be used as the input for a heat recovery and steam generator system 490, which can, for example, enable additional electricity to be generated using steam turbines 494). After passing through heat recovery system 490, including optional removal of a portion of H<sub>2</sub>O from the CO<sub>2</sub>-containing stream, the output stream 498 can be recycled for compression in compressor 402 or a second compressor that is not shown. The proportion of the exhaust from expander 406 used for CO<sub>2</sub>-containing stream 492 can be determined based on the desired amount of CO<sub>2</sub> for addition to combustion zone 415.

[00181] As used herein, the EGR ratio is the flow rate for the fuel cell bound portion of the exhaust gas divided by the combined flow rate for the fuel cell bound portion and the recovery bound portion, which is sent to the heat recovery generator. For example, the EGR ratio for flows shown in FIG. 4 is the flow rate of stream 422 divided by the combined flow rate of streams 422 and 492.

[00182] The CO<sub>2</sub>-containing stream 422 can be passed into a cathode portion (not shown) of a molten carbonate fuel cell array 425. Based on the reactions within fuel cell array 425, CO<sub>2</sub> can be separated from stream 422 and transported to the anode portion (not shown) of the fuel cell array 425. This can result in a cathode output stream 424 depleted in CO<sub>2</sub>. The cathode output stream 424 can then be passed into a heat recovery (and optional steam generator) system 450 for generation of heat exchange and/or additional generation of electricity using steam turbines 454 (which

may optionally be the same as the aforementioned steam turbines 494). After passing through heat recovery and steam generator system 450, the resulting flue gas stream 456 can be exhausted to the environment and/or passed through another type of carbon capture technology, such as an amine scrubber.

**[00183]** After transport of CO<sub>2</sub> from the cathode side to the anode side of fuel cell array 425, the anode output 435 can optionally be passed into a water gas shift reactor 470. Water gas shift reactor 470 can be used to generate additional H<sub>2</sub> and CO<sub>2</sub> at the expense of CO (and H<sub>2</sub>O) present in the anode output 435. The output from the optional water gas shift reactor 470 can then be passed into one or more separation stages 440, such as a cold box or a cryogenic separator. This can allow for separation of an H<sub>2</sub>O stream 447 and CO<sub>2</sub> stream 449 from the remaining portion of the anode output. The remaining portion of the anode output 485 can include unreacted H<sub>2</sub> generated by reforming but not consumed in fuel cell array 425. A first portion 445 of the H<sub>2</sub>-containing stream 485 can be recycled to the input for the anode(s) in fuel cell array 425. A second portion 487 of stream 485 can be used as an input for combustion zone 415. A third portion 465 can be used as is for another purpose and/or treated for subsequent further use. Although FIG. 4 and the description herein schematically details up to three portions, it is contemplated that only one of these three portions can be exploited, only two can be exploited, or all three can be exploited according to the invention.

**[00184]** In FIG. 4, the exhaust for the exhaust gas recycle loop is provided by a first heat recovery and steam generator system 490, while a second heat recovery and steam generator system 450 can be used to capture excess heat from the cathode output of the fuel cell array 425. FIG. 5 shows an alternative embodiment where the exhaust gas recycle loop is provided by the same heat recovery steam generator used for processing the fuel cell array output. In FIG. 5, recycled exhaust gas 598 is provided by heat recovery and steam generator system 550 as a portion of the flue gas stream 556. This can eliminate the separate heat recovery and steam generator system associated with the turbine.

**[00185]** In various embodiments of the invention, the process can be approached as starting with a combustion reaction for powering a turbine, an internal combustion engine, or another system where heat and/or pressure generated by a combustion

reaction can be converted into another form of power. The fuel for the combustion reaction can comprise or be hydrogen, a hydrocarbon, and/or any other compound containing carbon that can be oxidized (combusted) to release energy. Except for when the fuel contains only hydrogen, the composition of the exhaust gas from the combustion reaction can have a range of CO<sub>2</sub> contents, depending on the nature of the reaction (e.g., from at least about 2 vol% to about 25 vol% or less). Thus, in certain embodiments where the fuel is carbonaceous, the CO<sub>2</sub> content of the exhaust gas can be at least about 2 vol%, for example at least about 4 vol%, at least about 5 vol%, at least about 6 vol%, at least about 8 vol%, or at least about 10 vol%. Additionally or alternately in such carbonaceous fuel embodiments, the CO<sub>2</sub> content can be about 25 vol% or less, for example about 20 vol% or less, about 15 vol% or less, about 10 vol% or less, about 7 vol% or less, or about 5 vol% or less. Exhaust gases with lower relative CO<sub>2</sub> contents (for carbonaceous fuels) can correspond to exhaust gases from combustion reactions on fuels such as natural gas with lean (excess air) combustion. Higher relative CO<sub>2</sub> content exhaust gases (for carbonaceous fuels) can correspond to optimized natural gas combustion reactions, such as those with exhaust gas recycle, and/or combustion of fuels such as coal.

[00186] In some aspects of the invention, the fuel for the combustion reaction can contain at least about 90 volume % of compounds containing five carbons or less, e.g., at least about 95 volume %. In such aspects, the CO<sub>2</sub> content of the exhaust gas can be at least about 4 vol%, for example at least about 5 vol%, at least about 6 vol%, at least about 7 vol%, or at least about 7.5 vol%. Additionally or alternately, the CO<sub>2</sub> content of the exhaust gas can be about 13 vol% or less, e.g., about 12 vol% or less, about 10 vol% or less, about 9 vol% or less, about 8 vol% or less, about 7 vol% or less, or about 6 vol% or less. The CO<sub>2</sub> content of the exhaust gas can represent a range of values depending on the configuration of the combustion-powered generator. Recycle of an exhaust gas can be beneficial for achieving a CO<sub>2</sub> content of at least about 6 vol%, while addition of hydrogen to the combustion reaction can allow for further increases in CO<sub>2</sub> content to achieve a CO<sub>2</sub> content of at least about 7.5 vol%.

#### Alternative Configuration – High Severity NO<sub>x</sub> Turbine

[00187] Gas turbines can be limited in their operation by several factors. One typical limitation can be that the maximum temperature in the combustion zone can be

controlled below certain limits to achieve sufficiently low concentrations of nitrogen oxides (NO<sub>x</sub>) in order to satisfy regulatory emission limits. Regulatory emission limits can require a combustion exhaust to have a NO<sub>x</sub> content of about 20 vppm or less, and possible 10 vppm or less, when the combustion exhaust is allowed to exit to the environment.

**[00188]** NO<sub>x</sub> formation in natural gas-fired combustion turbines can be a function of temperature and residence time. Reactions that result in formation of NO<sub>x</sub> can be of reduced and/or minimal importance below a flame temperature of about 1500°F, but NO<sub>x</sub> production can increase rapidly as the temperature increases beyond this point. In a gas turbine, initial combustion products can be mixed with extra air to cool the mixture to a temperature around 1200°F, and temperature can be limited by the metallurgy of the expander blades. Early gas turbines typically executed the combustion in diffusion flames that had stoichiometric zones with temperatures well above 1500°F, resulting in higher NO<sub>x</sub> concentrations. More recently, the current generation of 'Dry Low Nox' (DLN) burners can use special pre-mixed burners to burn natural gas at cooler lean (less fuel than stoichiometric) conditions. For example, more of the dilution air can be mixed in to the initial flame, and less can be mixed in later to bring the temperature down to the ~1200°F turbine-expander inlet temperature. The disadvantages for DLN burners can include poor performance at turndown, higher maintenance, narrow ranges of operation, and poor fuel flexibility. The latter can be a concern, as DLN burners can be more difficult to apply to fuels of varying quality (or difficult to apply at all to liquid fuels). For low BTU fuels, such as fuels containing a high content of CO<sub>2</sub>, DLN burners are typically not used and instead diffusion burners can be used. In addition, gas turbine efficiency can be increased by using a higher turbine-expander inlet temperature. However, because there can be a limited amount of dilution air, and this amount can decrease with increased turbine-expander inlet temperature, the DLN burner can become less effective at maintaining low NO<sub>x</sub> as the efficiency of the gas turbine improves.

**[00189]** In various aspects of the invention, a system integrating a gas turbine with a fuel cell for carbon capture can allow use of higher combustion zone temperatures while reducing and/or minimizing additional NO<sub>x</sub> emissions, as well as enabling DLN-like NO<sub>x</sub> savings via use of turbine fuels that are not presently compatible with DLN

burners. In such aspects, the turbine can be run at higher power (i.e., higher temperature) resulting in higher NO<sub>x</sub> emissions, but also higher power output and potentially higher efficiency. In some aspects of the invention, the amount of NO<sub>x</sub> in the combustion exhaust can be at least about 20 vppm, such as at least about 30 vppm, or at least about 40 vppm. Additionally or alternately, the amount of NO<sub>x</sub> in the combustion exhaust can be about 1000 vppm or less, such as about 500 vppm or less, or about 250 vppm or less, or about 150 vppm or less, or about 100 vppm or less. In order to reduce the NO<sub>x</sub> levels to levels required by regulation, the resulting NO<sub>x</sub> can be equilibrated via thermal NO<sub>x</sub> destruction (reduction of NO<sub>x</sub> levels to equilibrium levels in the exhaust stream) through one of several mechanisms, such as simple thermal destruction in the gas phase; catalyzed destruction from the nickel cathode catalyst in the fuel cell array; and/or assisted thermal destruction prior to the fuel cell by injection of small amounts of ammonia, urea, or other reductant. This can be assisted by introduction of hydrogen derived from the anode exhaust. Further reduction of NO<sub>x</sub> in the cathode of the fuel cell can be achieved via electrochemical destruction wherein the NO<sub>x</sub> can react at the cathode surface and can be destroyed. This can result in some nitrogen transport across the membrane electrolyte to the anode, where it may form ammonia or other reduced nitrogen compounds. With respect to NO<sub>x</sub> reduction methods involving an MCFC, the expected NO<sub>x</sub> reduction from a fuel cell / fuel cell array can be about 80% or less of the NO<sub>x</sub> in the input to the fuel cell cathode, such as about 70% or less, and/or at least about 5%. It is noted that sulfidic corrosion can also limit temperatures and affect turbine blade metallurgy in conventional systems. However, the sulfur restrictions of the MCFC system can typically require reduced fuel sulfur levels that reduce or minimize concerns related to sulfidic corrosion. Operating the MCFC array at low fuel utilization can further mitigate such concerns, such as in aspects where a portion of the fuel for the combustion reaction corresponds to hydrogen from the anode exhaust.

#### Additional Embodiments

**[00190]** Embodiment 1. A method for generating hydrogen in a refinery, the method comprising: introducing a fuel stream comprising a reformable fuel into an anode of a molten carbonate fuel cell, an internal reforming element associated with the anode, or a combination thereof; introducing a cathode inlet stream comprising CO<sub>2</sub> and O<sub>2</sub> into

a cathode of the molten carbonate fuel cell; generating electricity within the molten carbonate fuel cell; generating an anode exhaust comprising  $H_2$  and  $CO_2$ ; performing a separation (e.g., using a membrane) on the anode exhaust to form a  $CO_2$ -rich gas stream having a  $CO_2$  content greater than a  $CO_2$  content of the anode exhaust, and a  $CO_2$ -depleted gas stream having a  $CO_2$  content less than the  $CO_2$  content of the anode exhaust, which  $CO_2$ -depleted gas stream optionally comprises an  $H_2$ -rich gas stream and a syngas stream; and delivering the  $CO_2$ -depleted gas stream to one or more second refinery processes.

**[00191]** Embodiment 2. The method of embodiment 1, wherein the cathode inlet stream comprises one or more  $CO_2$ -containing streams derived directly or indirectly from one or more first refinery processes.

**[00192]** Embodiment 3. The method of embodiment 1 or 2, wherein the molten carbonate fuel cell is operated at a thermal ratio from about 0.25 to about 1.5 (e.g., from about 0.25 to about 1.3, from about 0.25 to about 1.15, from about 0.25 to about 1.0, from about 0.25 to about 0.85, or from about 0.25 to about 0.75).

**[00193]** Embodiment 4. The method of any of the above embodiments, further comprising separating  $H_2O$  from at least one of the anode exhaust, the  $CO_2$ -depleted stream, and the  $CO_2$ -rich stream in one or more separation stages.

**[00194]** Embodiment 5. The method of any of the above embodiments, wherein an amount of the reformable fuel introduced into the anode, the internal reforming element associated with the anode, or the combination thereof, provides a reformable fuel surplus ratio of at least about 1.5 (e.g., at least about 2.0, at least about 2.5 or at least about 3.0).

**[00195]** Embodiment 6. The method of any of the above embodiments, wherein a ratio of net moles of syngas in the anode exhaust to moles of  $CO_2$  in a cathode exhaust is at least about 2.0 (e.g., at least about 3.0, at least about 4.0, at least about 5.0, at least about 10.0, or at least about 20.0), and optionally is about 40.0 or less (e.g., about 30.0 or less or about 20.0 or less).

**[00196]** Embodiment 7. The method of any of the above embodiments, wherein a fuel utilization in the anode is about 50% or less (e.g., about 45% or less, about 40% or less, about 35% or less, about 30% or less, about 25% or less, or about 20% or less) and a

CO<sub>2</sub> utilization in the cathode is at least about 60% (e.g., at least about 65%, at least about 70%, or at least about 75%).

[00197] Embodiment 8. The method of any of the above embodiments, wherein the molten carbonate fuel cell is operated at a first operating condition to generate electrical power and at least about 50 mW/cm<sup>2</sup> (e.g., at least about 80 mW/cm<sup>2</sup> or at least 100 mW/cm<sup>2</sup>) of waste heat, the first operating condition providing a current density of at least about 150 mA/cm<sup>2</sup>, and wherein an effective amount of an endothermic reaction is performed to maintain a temperature differential between an anode inlet and an anode outlet of about 100°C or less (e.g., about 80°C or less or about 60°C or less).

[00198] Embodiment 9. The method of embodiment 8, wherein performing the endothermic reaction consumes at least about 40% (e.g., at least about 50%, at least about 60%, or at least about 75%) of the waste heat.

[00199] Embodiment 10. The method of any of the above embodiments, wherein an electrical efficiency for the molten carbonate fuel cell is between about 10% and about 40% (e.g., between about 10% and about 35%, between about 10% and about 30%, between about 10% and about 25%, or between about 10% and about 20%) and a total fuel cell efficiency for the molten carbonate fuel cell is at least about 55% (e.g., at least about 60%, at least about 65%, at least about 70%, at least about 75%, or at least about 80%).

[00200] Embodiment 11. The method of any of the above embodiments, wherein one or more of the following are satisfied: at least one process in the one or more first refinery processes is a process in the one or more second refinery processes; the fuel stream is derived from one or more third refinery processes; and the anode exhaust has a molar ratio of H<sub>2</sub> to CO of at least about 3.0:1, and has a CO<sub>2</sub> content of at least about 10 vol%.

[00201] Embodiment 12. The method of any of the above embodiments, wherein at least a portion of the fuel stream passes through a pre-reforming stage prior to being introduced into the anode.

[00202] Embodiment 13. The method of any of the above embodiments, wherein at least a portion of the fuel stream passes through a desulfurization stage prior to being introduced into the anode.

[00203] Embodiment 14. The method of any of the above embodiments, further comprising modifying an  $H_2$  content of one or more of the anode exhaust, the  $CO_2$ -rich gas stream, and the a  $CO_2$ -depleted gas stream using a water gas shift process.

[00204] Embodiment 15. The method of any of the above embodiments, wherein the  $CO_2$ -depleted gas stream is further separated into a first  $H_2$ -rich stream having a first  $H_2$  purity and a second  $H_2$ -rich stream having a second  $H_2$  purity, wherein the second  $H_2$ -rich stream is compressed to a pressure greater than the first  $H_2$ -rich stream.

#### Example – Integration of MCFC with Refinery Hydrogen Supply

[00205] In the following example, calculations were performed for a configuration where an MCFC system was used as a source of hydrogen for supplying various burners, boilers, and/or other units that use combustion of a fuel as a source of energy. While the following examples focus on supplying hydrogen to combustion reactions, the hydrogen generated by the MCFC could additionally or alternately be used to supply one or more processes (such as a plurality of processes) where hydrogen can be used for a purpose other than combustion. For example, the hydrogen generated by the MCFC could be used in one or more hydroprocessing reactors within a refinery.

[00206] In the following example, the  $CO_2$  for the cathode was calculated based on using an external source of  $CO_2$ . This choice was made for convenience in demonstrating the energy benefits of using an MCFC for reducing  $CO_2$  emissions in comparison with attempting to capture  $CO_2$  via another method, such as using conventional amine washes for each potential point source of carbon. For comparison purposes, a typical expected energy cost for using an amine wash based on using monoethanolamine (MEA) to capture  $CO_2$  from relatively dilute  $CO_2$  streams (such as streams with approximately 10 vol% or less  $CO_2$ ) was approximated to be about 3 GJ/ton  $CO_2$ . A substantial portion of this energy cost can be avoided by using an MCFC to concentrate  $CO_2$  in an anode exhaust stream. It is noted that, in embodiments where  $CO_2$  is collected from various point sources within a refinery for use as part of the cathode input, some additional energy cost may be required to deliver the  $CO_2$  streams to the MCFC. However, those costs can be at least approximately or roughly offset (if not exceeded) by the additional energy inefficiencies required for a conventional configuration where a separate amine wash would need to incur similar

costs for delivery of CO<sub>2</sub> to a central amine wash, and/or by the additional energy inefficiencies that would be incurred by having a separate amine wash for each point source of CO<sub>2</sub>.

[00207] The following configuration examples provide two alternatives for operating an MCFC to provide hydrogen for consumption in a refinery. In the calculations for the first configuration, a gas turbine was used to generate electricity and to provide a source of CO<sub>2</sub> for the cathode input. In the calculations for the second configuration, additional methane was burned to provide the heat and CO<sub>2</sub> for operating the fuel cell. In both configurations, the anode exhaust was processed in one or more separation stages to separate CO<sub>2</sub> (such as for sequestration) from H<sub>2</sub> (used for fuel in the refinery).

[00208] In these examples, calculations were performed for supplying the heat requirements of a typical refinery that can process about 500 kbd of crude oil. A refinery with a refining capacity of about 500 kbd can use about 118 Mscf/d (or roughly  $3.34 \times 10^6$  m<sup>3</sup> per day) of natural gas to the heating system, which can produce roughly 118 Mscf/d of CO<sub>2</sub> emissions from combustion, if no capture/sequestration mechanism is used. The following examples integrate a MCFC process with a refinery gas fired heater system in a roughly 500 kbd system to provide distributed heating with low CO<sub>2</sub> emissions.

[00209] FIG. 6 schematically shows an example of a system for integrated processing with a combustion gas turbine, MCFC system, and refinery wide fired heaters that burn H<sub>2</sub>. The system in FIG. 6 is configured such that the turbine can generate the CO<sub>2</sub> feed required in the cathode to produce enough H<sub>2</sub> in the MCFC system to run the refinery heating system. Air 601 and methane 602 were fed to a combustion gas turbine 650 and burned to produce a hot cathode feed 603. The excess heat in hot cathode feed 603 was used to pre-heat the anode methane feed 604, which can then be fed 605 to the cathode of MCFC 640. Anode methane feed 604 and steam 606 were fed to the anode of MCFC 640. The MCFC can produce a low CO<sub>2</sub> content cathode exhaust 607 at high temperature. Depending on the aspect, the MCFC can be operated at a low fuel utilization (e.g., of about 25% to about 60%, such as a fuel utilization of at least about 30%, or at least about 40%, or about 50% or less, or about 40% or less). Additionally or alternately, the MCFC can be operated at a more conventional fuel utilization (e.g.,

of about 70% or greater, though conventional fuel utilization can typically be between 70% and 75%), but this can be less preferable, as the amount of potential H<sub>2</sub> that capable of being recovered from the anode exhaust can be reduced. Heat can be recovered from cathode exhaust 607 in a HRSG (Heat Recovery Steam Generation system) before the cathode exhaust is emitted to the atmosphere (or further processed). The anode exhaust 608 can be cooled in a HRSG and/or can be shifted in a water gas shift reaction stage 660. The shifted gas 609, mostly H<sub>2</sub> and CO<sub>2</sub>, can go through a separation unit 670 to produce a CO<sub>2</sub> stream 610 and a H<sub>2</sub> stream 611. The CO<sub>2</sub> stream 610 can be compressed and sold for use and/or sequestered. H<sub>2</sub> stream 611 can be distributed to the refinery heaters as the heating fuel. Each sub-stream of H<sub>2</sub> stream 611 can be burned with oxidant (air) 612 in burners 680 that can be located at one or more locations in the refinery to provide heat with substantially no CO<sub>2</sub> emissions. For a configuration similar to FIG. 6, FIG. 7 shows representative values for the flow volumes within the configuration.

**[00210]** Figure 8 schematically shows another example of a system for integrated processing with an MCFC system and a refinery fired heaters with methane and hydrogen burners. This system was configured such that the methane burners can generate the CO<sub>2</sub> feed required in the cathode to produce enough H<sub>2</sub> in the MCFC system to run the remaining hydrogen burners. Methane 801 and oxidant (air) 802 can be distributed to the methane burners 890. The off-gas 803 can be collected from the methane burners and sent to a feed pre-heater 845. Methane 804, oxidant (air) 805, and off-gas 803 can be burned in pre-heater 845 to produce a hot cathode feed 806. The excess heat in 806 can be used to pre-heat the anode (methane) feed 807 and fed to the cathode at 808. The pre-heated methane 809 and steam 810 were fed to the anode. The MCFC 850 can produce a low CO<sub>2</sub> content cathode exhaust 811 at relatively high temperature. Heat can be recovered from cathode exhaust 811 in a HRSG, e.g., before it is emitted to the atmosphere or sent for further treatment (not shown). The anode exhaust 812 can be cooled in a HRSG and shifted in 860. The shifted gas 813, mostly H<sub>2</sub> and CO<sub>2</sub>, can go through a separation unit 870 to produce a CO<sub>2</sub> stream 814 and a H<sub>2</sub> stream 815. H<sub>2</sub> stream 815 can be distributed to the hydrogen burners 880. Each sub-stream can be burned with oxidant (air) 816 in burners 880 that can be located at one or more locations in the refinery to provide heat with substantially no CO<sub>2</sub>

emissions. For a configuration similar to FIG. 8, FIG. 9 shows representative values for the flow volumes within the configuration.

[00211] Based on configurations similar to FIGS 6 and 8, and based on process flow similar to FIGS 7 and 9, the relative net power production was calculated for sequestering carbon for a refinery integrated with an MCFC. This was compared with a calculation for the net power production for a conventional refinery system where amine wash systems were used for carbon capture for each point source. As noted above, it has been determined that using a representative amine wash (e.g., with MEA) to capture CO<sub>2</sub> from a typical dilute refinery stream (such as streams containing about 2 vol% to about 8 vol% CO<sub>2</sub>) can require about 3 GJ/ton CO<sub>2</sub>. Table 2 shows the comparison for the inventive configurations similar to FIGS 6 and 8 (which can result in CO<sub>2</sub> streams such as stream 610 or stream 814) relative to a conventional amine wash method. For the comparison in Table 2, the % CO<sub>2</sub> emission reduction represents the percentage of carbon that passes through the anode of the MCFC. Based on the calculated values shown in Table 2, use of an MCFC to provide H<sub>2</sub> for refinery burners and to centrally separate CO<sub>2</sub> can result in additional available power being generated. This can notably be in contrast to the substantial power requirements for separating CO<sub>2</sub> using a conventional configuration.

**Table 2 – Carbon Capture and Net Power Generation**

|                                       | Configuration 1 | Configuration 2 |
|---------------------------------------|-----------------|-----------------|
| % CO <sub>2</sub> emissions reduction | 55.98%          | 86%             |
| Net power with MCFC power [MW]        | 110             | 36              |
| Net power with MEA capture [MW]       | -115            | -180            |

[00212] Although the present invention has been described in terms of specific embodiments, it is not so limited. Suitable alterations/modifications for operation under specific conditions should be apparent to those skilled in the art. It is therefore intended that the following claims be interpreted as covering all such alterations/modifications that fall within the true spirit/scope of the invention.

## CLAIMS:

1. A method for generating hydrogen in a refinery, the method comprising:
  - introducing a fuel stream comprising a reformable fuel into an anode of a molten carbonate fuel cell, an internal reforming element associated with the anode, or a combination thereof;
  - introducing a cathode inlet stream comprising CO<sub>2</sub> and O<sub>2</sub> into a cathode of the molten carbonate fuel cell;
  - generating electricity within the molten carbonate fuel cell;
  - generating an anode exhaust comprising H<sub>2</sub> and CO<sub>2</sub>;
  - performing a separation on the anode exhaust to form a CO<sub>2</sub>-rich gas stream having a CO<sub>2</sub> content greater than a CO<sub>2</sub> content of the anode exhaust, and a CO<sub>2</sub>-depleted gas stream comprising hydrogen and having a CO<sub>2</sub> content less than the CO<sub>2</sub> content of the anode exhaust; and
  - delivering the CO<sub>2</sub>-depleted gas stream to one or more second refinery processes,
  - wherein the molten carbonate fuel cell is operated (i) such that a CO<sub>2</sub> utilization in the cathode is at least about 60% and either (ii) so as to achieve a thermal ratio from about 0.25 to about 1.15, or (iii) such that an amount of the reformable fuel introduced into the anode, the internal reforming element associated with the anode, or the combination thereof, provides a reformable fuel surplus ratio of at least about 1.5, or (iv) both (ii) and (iii).
2. The method of claim 1, wherein the cathode inlet stream comprises one or more CO<sub>2</sub>-containing streams derived directly or indirectly from one or more first refinery processes.
3. The method of claim 1, further comprising separating H<sub>2</sub>O from at least one of the anode exhaust, the CO<sub>2</sub>-depleted stream, and the CO<sub>2</sub>-rich stream in one or more separation stages.
4. The method of claim 1, wherein a ratio of net moles of syngas in the anode exhaust to moles of CO<sub>2</sub> in a cathode exhaust is at least about 2.0.

5. The method of claim 1, wherein a fuel utilization in the anode is about 50% or less and/or wherein an amount of the reformable fuel introduced into the anode, the internal reforming element associated with the anode, or the combination thereof, provides a reformable fuel surplus ratio of at least about 2.0 and/or wherein the molten carbonate fuel cell is operated at a thermal ratio from about 0.25 to about 1.0.
6. The method of claim 1, wherein the molten carbonate fuel cell is operated to generate electrical power at a current density of at least about 150 mA/cm<sup>2</sup> and at least about 80 mW/cm<sup>2</sup> of waste heat, the method further comprising performing an effective amount of an endothermic reaction to maintain a temperature differential between an anode inlet and an anode outlet of about 100°C or less.
7. The method of claim 6, wherein performing the endothermic reaction consumes at least about 40% of the waste heat.
8. The method of claim 1, wherein an electrical efficiency for the molten carbonate fuel cell is between about 10% and about 40% and/or a total fuel cell efficiency for the molten carbonate fuel cell is at least about 55%.
9. The method of claim 1, wherein the CO<sub>2</sub>-depleted gas stream comprises an H<sub>2</sub>-rich gas stream and a syngas stream, each of which having a CO<sub>2</sub> content less than the CO<sub>2</sub> content of the anode exhaust.
10. The method of claim 2, wherein at least one process in the one or more first refinery processes is a process in the one or more second refinery processes.
11. The method of claim 2, wherein the fuel stream is derived from one or more third refinery processes.
12. The method of claim 11, wherein at least a portion of the fuel stream passes through a pre-reforming stage prior to being introduced into the anode.

13. The method of claim 11, wherein at least a portion of the fuel stream passes through a desulfurization stage prior to being introduced into the anode.
14. The method of claim 9, further comprising separating H<sub>2</sub>O from one or more of the anode exhaust, the CO<sub>2</sub>-rich gas stream, and the a CO<sub>2</sub>-depleted gas stream.
15. The method of claim 2, wherein the anode exhaust has a molar ratio of H<sub>2</sub> to CO of at least about 3.0:1, and has a CO<sub>2</sub> content of at least about 10 vol %.
16. The method of claim 2, further comprising modifying an H<sub>2</sub> content of one or more of the anode exhaust, the CO<sub>2</sub>-rich gas stream, and the a CO<sub>2</sub>-depleted gas stream using a water gas shift process.
17. The method of claim 2, wherein the separating of the anode exhaust comprises using a membrane.
18. The method of claim 1, wherein the CO<sub>2</sub>-depleted gas stream is further separated into a first H<sub>2</sub>-rich stream having a first H<sub>2</sub> purity and a second H<sub>2</sub>-rich stream having a second H<sub>2</sub> purity, wherein the second H<sub>2</sub>-rich stream is compressed to a pressure greater than the first H<sub>2</sub>-rich stream.
19. The method of claim 1, wherein at least one of the one or more second refinery processes involves using hydrogen as a reactant and/or as a combustant.