


✓		1	22
✓	1	23	24
✓		24	25
✓		27	-

Liquid crystal aligning films and liquid crystal display devices

The present invention relates to a liquid crystal aligning film and a liquid crystal display device. More specifically, it relates to a liquid crystal aligning film having a polybenzylimide skeleton and to a liquid display device prepared by using this film.

A twisted nematic (which will hereafter be abbreviated as TN) mode is one in which the aligned direction of a nematic liquid crystal provided between a pair of upper and lower electrode substrates has been twisted 90° on the surfaces of the substrates. It has been used extensively. There is another mode in which the aligned direction of a nematic liquid crystal is twisted from 180° to 300° and it is known as a super nematic mode (which will hereafter be abbreviated as STN). Furthermore, in recent years, in order to perform a matrix display or a color display by means of liquid crystals, many developments have been made regarding an active type twisted nematic mode using a majority of picture element electrodes and MIM (metal - insulating phase - metal) elements or TFT (field effect type thin film transistor) elements for their

This Sheet Has Been Replaced



ON-OFF operation.


The common problems for all these modes are that when the same image is displayed for a long time and then a transfer to a new image is made, the previous image remains
5 as an after image. In particular, the improvement in the after image is very important in order to obtain a high quality liquid crystal display device.

It is considered that the causes of the after image may be due to a potential difference, that is to say: since
10 a DC component is added to a liquid crystal display device, electric double layers due to the impure ionic components contained in the liquid crystal are produced on the interfaces of the liquid crystal aligning film. The offsetting of electric charges is given between the upper
15 and lower substrates and such a potential difference as to keep the condition stable is created. Since DC components cannot be removed, particularly from the TFT elements due to the characteristics of the elements, these problems of after image are easily highlighted more than
20 those in TN and STN and look serious. Furthermore, a higher voltage holding ratio is required for preventing the flickering of the image in the TFT mode.

As for an aligning film used in such liquid crystal display devices, organic type films, such as polyimides
25 and polyamides, are mainly used. For example, Japanese patent application laid-open No. Sho 51-65960 discloses a liquid crystal display device having a liquid crystal



aligning film using a polyimide resin constituted of the repeated unit represented by:



There was, however, a problem in that an after image
5 is easily caused in such a device using a polyimide aligning
film obtained by using such a polyether compound.

SUMMARY OF THE INVENTION

It is, accordingly, a primary object of the present
invention to solve the above problem of the prior art and
10 to obtain a liquid crystal aligning film and a liquid
crystal display device where a good liquid crystal alignment
property can be obtained and an after image is reduced
by the rubbing treatment of the thin film consisting of
organics.

15 The present inventors have considered that the after
image may be produced since the electric charges due to
impurities as ions are offset on the surface of the aligning
film, resulting in their stabilization, and made research
and development to eliminate the after image. As a result,
20 the present inventors have found that the generation of
an after image has a correlation with the superficial
polarity of the aligning film.


Then, the present inventors developed an aligning
film having the following structure so as to prevent the
25 after image from occurring by lessening the superficial



polarity of the polymer.


Specifically, the ratio of polar components was reduced by transforming a bond including a polar atom or groups as represented by -O- or -SO₂- contained in the polymer
 5 into a carbon bond, and by relatively reducing the ratio of imide groups by way of increasing the molecular weight of the amine.

Namely, a first invention of this application is a liquid crystal aligning film containing a polymer, as the
 10 main component, having in its principal chain a skeleton represented by the general formula (1):




wherein X and Y each represent the same or different hydrogen atoms, an alkyl group having from 1 to 3 carbon
 15 atoms, fluorine atom, a chlorine atom or a trifluoromethyl group, these substituent positions being at the ortho-position or the meta-position.

Then, a second invention of this application is a liquid crystal aligning film containing a polyimide, as
 20 the main component, having a structural unit represented by the general formula (2):




wherein X and Y each represent the same or different hydrogen atoms, an alkyl group having from 1 to 3 carbon atoms, a fluorine atom, a chlorine atom or a trifluoromethyl group, these substituent positions being at the ortho-
 5 position or the meta-position, and R represents a tetravalent aromatic or aliphatic group or a composite group having both tetravalent aromatic and aliphatic properties.

A third invention of this application is a liquid
 10 crystal aligning film containing polyimide, as the main component, prepared by heating polyamic acid prepared by reacting, in a solvent, tetracarboxylic acid dianhydride represented by the general formula (3):



15 wherein R represents a tetravalent aromatic or aliphatic group, or a composite group having both tetravalent aromatic and aliphatic properties, with a diamino compound represented by the general formula (4):



20 wherein X and Y each represent the same or different hydrogen atoms, an alkyl group having from 1 to 3 carbon atoms, a fluorine atom, a chlorine atom or trifluoromethyl group, these substituent positions being at the ortho-



position or the meta-position.

Furthermore, a fourth invention of this application is a liquid crystal display device using the liquid crystal aligning film described above.

5 Some specific examples of diamine compounds used in the invention can be listed as follows:

1,1-bis[4-(4'-aminobenzyl)phenyl]methane;

1,1-bis[4-(4'-amino-3-methylbenzyl)phenyl]methane;

1,1-bis[4-(4'-amino-3-ethylbenzyl)phenyl]methane;

10 1,1-bis[4-(4'-amino-3-propylbenzyl)phenyl]methane;

1,1-bis[4-(4'-amino-3-fluorobenzyl)phenyl]methane;

1,1-bis[4-(4'-amino-3-chlorobenzyl)phenyl]methane;

1,1-bis[4-(4'-amino-3-trifluoromethylchlorobenzyl)phenyl]methane;

15 1,1-bis[4-(4'-aminobenzyl)-3-methylphenyl]methane;

1,1-bis[4-(4'-aminobenzyl)-3-ethylphenyl]methane;

1,1-bis[4-(4'-aminobenzyl)-3-propylphenyl]methane;

1,1-bis[4-(4'-aminobenzyl)-3-fluorophenyl]methane;

1,1-bis[4-(4'-aminobenzyl)-3-chlorophenyl]methane; and


20 1,1-bis[4-(4'-aminobenzyl)-3-trifluoromethylphenyl]methane.

As for tetracarboxylic acid dianhydride used in the invention, either of an aromatic type, an aliphatic type and a composite type having both aromatic and aliphatic properties, may be used. There are no restrictions, but
25 specifically illustrated, there are listed as follows:
pyromellitic acid dianhydride; biphenyltetracarboxylic acid dianhydride; benzophenonetetracarboxylic acid




- dianhydride; naphthalenetetracarboxylic acid dianhydride;
 bis(dicarboxyphenyl)ether dianhydride;
 bis(dicarboxyphenyl)sulfone dianhydride;
 bis(dicarboxyphenyl)methane dianhydride;
 5 cyclobutanetetracarboxylic acid dianhydride;
 cyclopentanetetracarboxylic acid dianhydride;
 cyclohexanetetracarboxylic acid dianhydride;
 dicyclohexanetetracarboxylic acid dianhydride;
 dicyclopentanetetracarboxylic acid dianhydride;
 10 bis(dicarboxycyclohexyl)ether dianhydride;
 bis(dicarboxycyclohexyl)sulfone dianhydride;
 bis(dicarboxycyclohexyl)methane dianhydride;
 5-(2,5-dioxotetrahydro-3-furanyl)-3-methyl-3-cyclohexene-
 1,2-dicarboxylic anhydride;
 15 1,3,3a,4,5,9b-hexahydro-5-(tetrahydro-2,5-dioxo-3-furanyl)-
 naphto[1,2-c]furane-1,3-dione, etc.


- In the liquid crystal aligning film of the invention,
 aminosilicone compounds or diaminosilicone compounds can
 be introduced so as to improve the adhesion to a substrate.
 20 As for a specific example of a liquid crystal aligning
 film in which the above silicon compounds are introduced,
 there are provided a liquid crystal aligning film containing
 from 0.1 to 50 mol %, preferably from 0.1 to 20 mol % of
 the total polyimide structural unit represented by the
 25 formula (7):



in the film is replaced by a structural unit represented by the formula (5):




and/or the formula (6):




wherein, in the formulas (5) and (6), Z represents an alkylene or phenylene group having from 1 to 3 carbon atoms; R^2 represents an alkyl group having from 1 to six carbon atoms; R represents a tetravalent aromatic or aliphatic group of a composite group having both tetravalent aromatic and aliphatic properties; and m represents an integer from 0 to 4.

As for a specific example of introduced aminosilicone compounds, the following compounds can be listed. In the first place, as for an aminosilicone compound for producing a structural unit represented by the general formula (5), the following compounds can be listed:





This Sheet Has Been Replaced







In the case of introducing these aminosilicone
 compounds into polybenzylimide type polymers, 50 mol %
 or less, preferably 20 mol % or less of diamino compounds
 represented by the general formula (4) can be replaced
 with aminosilicone compounds and used.

As for a diaminosilicone compound for producing a
 structural unit represented by the general formula (6),
 the following compounds can be listed.



This Sheet Has Been Replaced





In the formulas m represents an integer from 0 to 4. In the case of introducing these diaminosilicone compound into a polybenzylimide type polymer, 50 mol % or less, preferably 20 mol % or less, of a diamino compound represented by the above general formula (4) can be replaced with a diaminosilicone compound.

For mounting the liquid crystal aligning film of the invention on a substrate, since a polyimide compound is, in general, insoluble in solvents, a polyamic acid, which can be obtained from the condensation of a diamino compound and tetracarboxylic acid dianhydride as a precursor of this polyimide compound, is dissolved and coated on the substrate. For example, the polyamic acid is dissolved in a solvent, such as *N*-methyl-2-pyrrolidone (NMP), dimethylacetamide (DMAC), dimethylformamide (DMF), dimethylsulfoxide (DMSO), butyl cellosolve or ethylcarbitol, to prepare a 0.1 to 30 wt.%, preferably 1 to 10 wt.% solution, which is coated on the substrate by brushing, immersing, rotational coating, spraying or printing to give a coated film. The coated film is then heat-treated at 50 to 150°C,



preferably at 80 to 120°C, and subjected to a dehydrating ring formation reaction to give a liquid crystal aligning film consisting of a polybenzylimide type polymer film.

In the case the adhesion of the polymer film to the substrate is not good, the surface of the substrate may be treated in advance with a silane coupling reagent, followed by forming a polymer film on it, thereby the above situation can be improved. Next, the coated surface is rubbed in a certain direction with a cloth to give a liquid crystal aligning film.

Normally, electrodes, for example, transparent electrodes such as ITO, are formed on this substrate. For preventing the alkali elution from the substrate, an undersheet film, such as an insulating film, polarized disk, or color filter, may be coated on the electrodes. Furthermore, an overcoat film, such as an insulating film, color filter film or light transmission preventing film, may be formed on the electrodes. The prior art liquid crystal display device constitution can be applied to these electrodes, undercoatings, overcoatings and the other components within a cell.

After preparing a cell using the above substrates and injecting liquid crystal between the substrates, the injection inlet is sealed. Otherwise, after liquid crystal is sprayed on the substrate, the substrate is overlapped on another and the resulting substrates may be sealed so as not to leak the liquid crystal. Normal nematic liquid



crystals, dichroic liquid crystals and various other liquid crystals can be used as the liquid crystal to be injected.

The aligning film containing a polybenzylimide type polymer as the main component in the invention, acts so
5 as to reduce the after image. This reason is not clear, but since the ratio of polar components in the polymer is small, it may be considered that it becomes hard to absorb and retain ionic impurities.

The liquid crystal display device of the invention
10 is characterized by an alignment controlling film with reduced after image, and its voltage holding ratio is high as well. As a matter of course, the alignment of the liquid crystal is good, and it is also possible to bring about the pretilt angle in the same degree as that of a poly-
15 etherimide type polyimide of the prior art. Further, the present invention is applicable to a ferroelectric liquid crystal aligning films.

BRIEF DESCRIPTION OF THE DRAWINGS

Further objects and advantages of the present invention
20 will be apparent from the following description, reference being had to the accompanying drawings wherein preferred embodiments of the present invention are clearly shown.

In the drawings:

Fig. 1 is a view showing a C-V hysteresis curve; and

25 Fig. 2 is a circuit diagram for measuring a voltage holding ratio.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

This Sheet Has Been Replaced



Referring now to preferred embodiments, a detailed description of the invention will be given below. While the embodiment of the present invention, as herein described, constitutes a preferred form, it is to be understood that other form might be adopted.

In each preferred embodiment, the degree of the after image was measured by a C-V curve method. The C-V curve method is carried out by applying the triangle wave (frequency: 0.0036 Hz) of a voltage $V=\pm 10$ V to a liquid crystal cell, and then overlapping an alternating current at 25 mV and 1 KHz on this. The varying capacities, C, are then recorded. When the voltage is swept to the positive side, the capacity increases. When the voltage is swept toward the negative side, the capacity decreases to give a minimum value. Further, when the voltage is swept to the negative side less than 0, the capacity increases again, and next, when the voltage is swept toward the positive side, the capacity decreases again. The resulting wave form after several cycles are shown in Fig. 1. At this time, when the off-setting of electric charges is produced on the interfaces of the liquid crystal aligning film and stabilized, the voltage draws a hysteresis curve at both positive and negative sides. The residual electric charges are determined by drawing 2 tangents to the C-V curve at both positive and negative sides, obtaining the cross points ($\alpha_1 - \alpha_4$) where these lines cross the line of capacity, C_0 , at the time of $V=0$. The voltage differences



between two points for the positive side and between two points for the negative side are examined, and then by getting the average value thereof, the residual electric charge is determined. If the film thickness of the cell and the thickness of the aligning film are equal, this value becomes a parameter for stabilizing the off-setting of electric charges. Namely, the smaller the size of hysteresis in the aligning film, the less the after image.

The measurement of a voltage holding ratio percentage was carried out using a circuit as shown in Fig. 2(I). In the circuit, a rectangular wave V_s of gate pulse width 6.9 μs , frequency 60 Hz, and wave height ± 4.5 V, is applied on a source and the resulting voltage drain, V_D , is monitored. It is apparent from Fig. 2(II) that when a positive voltage pulse, V_{S1} , is applied at this point, the voltage shows a positive value during the period of time before the next negative pulse, V_{S2} , is applied. Therefore, the area (slanting line portion) enclosed by $V=0$ and monitored voltage V_D (positive value) is integrated. Such a measurement is repeated four times to obtain the average value. Setting the area, in the case that the voltage is not reduced, as 100%, a relative value of the area to this is calculated and the calculated value is defined as the voltage holding ratio (%).

Furthermore, the measurement of the pretilt angle was done by a crystal rotation method.

Example 1

This Sheet Has Been Replaced



Dehydrated and refined N-methyl-2-pyrrolidone (50 ml) was put in a four neck flask of 200 ml attached with a stirrer, a thermometer, a condenser and a nitrogen-replacing apparatus. Then, 1,1-bis[4-(4'-aminobenzyl)-phenyl]methane (7.43 g) was added and the mixture was stirred and dissolved. The resulting solution was cooled to 13°C, and pyromellitic acid dianhydride (4.36 g) was added to the solution at one time and allowed to react with the solution while simultaneously stirring and cooling. After 1 hour, 0.11 g of para-aminophenyltrimethoxysilane was added to the solution and allowed to react with it at 20°C for 1 hour while stirring. Then, the reaction solution was diluted with N-methyl-2-pyrrolidone (NMP) (58 ml) to give a clear solution of 10 wt.% polyamic acid. The viscosity of this solution at 25°C was 1893 cps.

This solution was diluted in a mixture solution of butyl cellosolve and NMP (1:1) to give a 3 wt.% solution, which was coated on a clear glass substrate mounted with ITO electrodes on one surface thereof by a rotational coating method (spinner method). The rotational condition was 5000 rpm for 15 seconds. After coating, the coated substrate was dried at 100°C for 10 min., and then, its temperature was gradually increased up to 200°C for 1 hour within an oven. It was further heat treated at 200°C for 90 min. to give polybenzylimide having an approximate film thickness of 600 Å. The coated surfaces of two substrates on which this polybenzylimide film had been formed were



treated by rubbing, respectively, to give their liquid crystal aligning films, which were incorporated in a liquid crystal cell having a cell thickness of $6\ \mu$ so that their rubbing directions may be in parallel with each other and face with each other, and in which Liquid Crystal F301 for TFT use (Chisso Corporation product and its commercial name) was sealed. After sealing, an isotropic transformation treatment was applied to it at 120°C for 30 min., and it was gradually cooled to a room temperature to give a liquid crystal display device. Furthermore, a liquid crystal cell having a cell thickness of $20\ \mu$ enclosing a Merk & Co., Inc. product, Liquid Crystal ZLI-1132, was prepared, following the similar procedure described, above and applied to the measurement of the pretilt angle. The alignment property of this liquid crystal was good and the pretilt angle of this liquid crystal was 3.6° . The residual electric charge of this cell was 0.07 at 25°C , and its voltage holding ratio was 97.5%.

20 Example 2

Dehydrated and refined N-methyl-2-pyrrolidone (50 ml) was put in a four-neck flask of 200 ml attached with a stirrer, a thermometer, a condenser and a nitrogen-replacing apparatus. Then, 1,1-bis[4-(4'-aminobenzyl)-phenyl]methane (7.43 g) was added and the mixture was stirred and dissolved. The resulting solution was cooled to 13°C , and methylcyclobutanetetracarboxylic acid



dianhydride (3.92 g) was added to the solution at one time and allowed to react with the solution while simultaneously stirring and cooling. After 1 hour, para-aminophenyltrimethoxysilane (0.11 g) was added to the solution and allowed to react with it at 20°C for 1 hour, while stirring. Then, the reaction solution was diluted with N-methyl-2-pyrrolidone (NMP) (58 ml) to give a clear solution of 10 wt.% polyamic acid. The viscosity of this solution at 25°C was 97.5 cps.

This solution was diluted in a mixture solution of butyl cellosolve and NMP (7:3) to give a 3 wt.% solution, which was coated on a clear glass substrate mounted with ITO electrodes on one surface thereof by a rotational coating method (spinner method). The rotational condition was 3000 rpm for 15 sec. After coating, the coated substrate was dried at 100°C for 10 min., and then, its temperature was gradually increased up to 200°C for 1 hour within an oven. It was further heat treated at 200°C for 90 min. to give polybenzylimide having an approximate film thickness of 600 Å. The coated surfaces of two substrates on which this polybenzylimide film had been formed were treated by rubbing, to give their liquid crystal aligning films, which were incorporated in a liquid crystal cell having a cell thickness of 6 μ so that their rubbing directions may be in parallel with each other and face with each other, and in which Liquid Crystal FB01 for TFT use (Chisso Corporation product and its commercial name)



was sealed.

After sealing, an isotropic transformation treatment was applied at 120°C for 30 min. and it was gradually cooled to a room temperature to give a liquid crystal display device. Furthermore, a liquid crystal cell having a cell thickness of 20 μ enclosing a Merk & Co., Inc. product, Liquid Crystal ZLI-1132, was prepared, following the similar procedure described above, and applied to the measurement of the pretilt angle.

The alignment property of this liquid crystal was good and the pretilt angle of this liquid crystal was 1.5°. The residual electric charge of this cell was 0.5 at 25°C, and its voltage holding ratio was 97.3%.

Comparative example 1

A mixture of 2,2-bis[4-(4'-aminophenoxy)phenyl]propane (8.06 g), pyromellitic acid dianhydride (4.36 g) and para-aminophenyltrimethoxysilane (0.11 g), was polymerized to give a polyamic acid solution.

This solution was diluted with a mixture solution of butyl cellosolve and NMP (1:1) to give a 3 wt.% solution, which was coated on a clear glass substrate mounted with ITO electrodes on one surface thereof by a rotational coating method (spinner method). The rotational condition was 3000 rpm for 15 sec. After coating, the coated substrate was dried at 100°C for 10 min., and then, its temperature was gradually increased up to 200°C for 1 hour within an oven. It was further heat treated at 200°C for

This Sheet Has Been Replaced



90 min. to give polyetherimide having an approximate film thickness of 600 Å. The coated surfaces of two substrates on which this polyetherimide film had been formed were treated by rubbing, respectively, to give their liquid crystal aligning films, which were incorporated in a liquid crystal cell having a cell thickness of 6 μ so that their rubbing directions may be in parallel with each other and face with each other, and in which Liquid Crystal FB01 for TFT use (Chisso Corporation product and its commercial name) was sealed. After sealing, an isotropic transformation treatment was applied to it at 120°C for 30 min., and it was gradually cooled to a room temperature to give a liquid crystal display device. Furthermore, a liquid crystal cell having a cell thickness of 20 μ enclosing a Merk & Co., Inc. product, Liquid Crystal ZLI-1132, was prepared, following the similar procedure described above, and applied to the measurement of the pretilt angle.

The alignment property of this liquid crystal was good and the pretilt angle of this liquid crystal was 3.7°. However, the residual electric charge of this cell was 0.20 at 25°C, and its voltage holding ratio was 90.0%.

Comparative example 2

A mixture of 2,2-bis[4-(4'-aminophenoxy)phenyl]propane (8.06 g), methylcyclobutanetetracarboxylic acid dianhydride (3.92 g) and para-aminophenyltrimethoxysilane (0.11 g), was polymerized to give a polyamic acid solution.



This solution was diluted with a mixture solution of butyl cellosolve and NMP (7:3) to give a 3 wt.% solution, which was coated on a clear glass substrate mounted with ITO electrodes on one surface thereof by a rotational coating method (spinner method). The rotational condition was 5000 rpm for 15 sec. After coating, the coated substrate was dried at 100°C for 10 min., and then, its temperature was gradually increased up to 200°C for 1 hour within an oven. It was further heat treated at 200°C for 90 min. to give polyetherimide having an approximate film thickness of 600 Å. The coated surfaces of two substrates on which this polyetherimide film had been formed were treated by rubbing, respectively, to give their liquid crystal aligning films, which were incorporated in a liquid crystal cell having a cell thickness of 6 μ so that their rubbing directions may be in parallel with each other and face with each other, and in which Liquid Crystal FB01 for TFT use (Chisso Corporation product and its commercial name) was sealed. After sealing, an isotropic transformation treatment was applied to it at 120°C for 30 min. and it was gradually cooled to a room temperature to give a liquid crystal display device. Furthermore, a liquid crystal cell having a cell thickness of 20 μ enclosing a Merk & Co., Inc. product, Liquid Crystal ZLI-1132, was prepared, following the similar procedure described above, and applied to the measurement of the pretilt angle.

This Sheet Has Been Replaced



The alignment property of this liquid crystal was good and the pretilt angle of this liquid crystal was 1.5° . However, the residual electric charge of this cell was 0.15 at 25°C , and its voltage holding ratio was 89.0%.

5 Comparative example 3

A mixture of 4,4'-diaminophenylether (3.46 g), pyromellitic acid dianhydride (4.36 g) and para-aminophenyltrimethoxysilane (0.11 g), was polymerized to give a polyamic acid solution.

10 This solution was diluted with a mixture solution of butyl cellosolve and NMP (1:1) to give a 3 wt.% solution, which was coated on a clear glass substrate mounted with ITO electrodes on one surface thereof by a rotational coating method (spinner method). The rotational condition
15 was 3000 rpm for 15 sec. After coating, the coated substrate was dried at 100°C for 10 min., and then, its temperature was gradually increased up to 200°C for 1 hour within an oven. It was further heat treated at 200°C for 90 min. to give polyetherimide having an approximate film
20 thickness of 600 Å. The coated surfaces of two substrates on which this polyetherimide film had been formed were treated by rubbing, respectively, to give their liquid crystal aligning films, which were incorporated in a liquid crystal cell having a cell thickness of $6\ \mu$ so that their
25 rubbing directions may be in parallel with each other and face with each other, and in which Liquid Crystal FB01 for TFT use (Chisso Corporation product and its commercial



name) was sealed. After sealing, an isotropic transformation treatment was applied to it at 120°C for 30 min. and it was gradually cooled to a room temperature to give a liquid crystal display device. Furthermore, a liquid crystal cell having a cell thickness of 20 μ enclosing a Merk & Co., Inc. product, Liquid Crystal ZLI-1132, was prepared, following the similar procedure described above, and applied to the measurement of the pretilt angle.

10 The alignment property of this liquid crystal was good and the pretilt angle of this liquid crystal was 0.5°. However, the residual electric charge of this cell was 0.90 at 25°C, and its voltage holding ratio was 78.0%.

15 In accordance with the first through third inventions of the present application, since the absorption of impurities can be decreased by reducing the polar components contained in the polymer, liquid crystal aligning films having reduced after image can be prepared. The liquid crystal display devices prepared by using these films have 20 reduced after image and which enables them to carry out good and stable displays. The aligning films of the invention contribute to the improvement in their voltage holding ratios also.






M&C FOLIO: 799P68233

WANGDOC:17511


CLAIMS:

1. A liquid crystal aligning film containing a polymer having repeating units of the formula:



wherein X and Y are the same or are different and each is a hydrogen, chlorine or fluorine atom or an alkyl group having from 1 to 3 carbon atoms, or a trifluoromethyl group, which may be substituted at the ortho- or meta-positions.

2. A liquid crystal aligning film containing a polyimide having repeating units of the formula:




This Sheet Has Been Replaced






wherein X and Y have the meanings defined in claim 1, and R is a tetravalent aromatic group, a tetravalent aliphatic group or a composite group having both tetravalent aromatic and aliphatic properties.

3. A liquid crystal aligning film containing a polyimide prepared by heating the polyamic acid obtained by reacting, in a solvent, a tetracarboxylic acid dianhydride of the formula:



(wherein R has the meaning defined in claim 2) with a diamino compound of the formula:




(wherein X and Y have the meanings defined in claim 1).


4. A liquid crystal aligning film according to claim 2, wherein the polyimide also contains repeating units of formulae (2) in which the polyimide structural unit of formula:

This Sheet Has Been Replaced






is replaced by structural units of the formulae:



and/or



wherein Z is an alkylene group having from 1 to 3 carbon atoms a phenylene group or a phenylene-alkylene group in which the alkylene group has 1 to 3 carbon atoms; R^2 is an alkyl group having from 1 to 6 carbon atoms; R has the meaning defined in claim 1; and m is 0 or an integer from 1 to 4.

This Sheet Has Been Replaced





5. A liquid crystal aligning film according to claim 4, wherein from 0.1 to 50 mol % of the total polyimide structural units in the film are replaced by structural units of the formulae (5) and/or (6).

6. A liquid crystal display device using a liquid crystal aligning films according to any one of the preceding claims.

This Sheet Has Been Replaced

