

Device for dispensing adhesive on a substrate

FIELD OF THE INVENTION

[0001] The invention relates to a device for dispensing adhesive on a substrate.

BACKGROUND OF THE INVENTION

[0002] Such devices are used as a dispensing station in a semiconductor mounting apparatus in order to apply adhesive such as epoxy to the chip mounting surfaces of a substrate. Subsequently, the substrates are transported to a bonding station where the semiconductor chips are placed. From US 6129040 and EP 1432013 devices for the application of adhesive to a substrate are known, which contain a writing head with a dispensing nozzle which is movable in three spatial directions X, Y and Z. From CH 705475 a method is known which uses a camera for recognizing the position of the substrate location prior to the application of the adhesive and for the quality control after the application of the adhesive, which coordinates the application of the adhesive with the movement of the writing head in order to obtain high throughput. From US 2003044534 a device is known which comprises a writing head with a dispensing nozzle with two outlet openings. From US 7977231 a device is known which comprises two dispensing nozzles which are independently movable from each other in at least one direction. Furthermore, semiconductor mounting apparatuses are known which contain two complete dispensing stations with one dispensing nozzle each.

[0003] Dispensing stations with only one dispensing nozzle come with the disadvantage that they are often slower than the following bonding station, because the waiting time which is required until the adhesive applied to the substrate has detached from the dispensing nozzle limits the throughput. The dispensing stations known from the state of the art with two dispensing nozzles come with various disadvantages, namely lack of flexibility and/or high constructional complexity.

SUMMARY OF THE INVENTION

[0004] The invention is based on the object of developing a device for the application of adhesive which allows applying adhesive in a simple way and at high speed to substrates with an uneven number of substrate places per row or column and easily applying the adhesive a second time to a substrate when a dispensing error is recognized.

A device in accordance with the invention for applying adhesive to a substrate comprises a writing head that is movable in three spatial directions. A first dispensing nozzle and at least one second dispensing nozzle can be fixed in such a way to the writing head that the tip of the first dispensing nozzle is fixed and the tip of the at least one second dispensing nozzle is movable in a direction extending substantially perpendicularly to a surface of the substrate. An actuator with a pin is fastened to the writing head. The

device can be operated in two operating modes and is set up to perform the following steps for the change from the one operating mode into the other operating mode:

- lifting of the writing head;
- extending or retracting the pin, and
- lowering the writing head to a predetermined working altitude, wherein in the retracted state of the pin the tips of the dispensing nozzles reach a substantially similar altitude above the substrate, and wherein in the extended state of the pin the tip of the at least one second dispensing nozzle reaches a higher altitude above the substrate than the tip of the first dispensing nozzle.

The device preferably comprises four struts which are connected to each other by flexure hinges. The at least one second dispensing nozzle can be fixed to one of said struts. The flexure hinges allow a movement of the tip of the at least one second dispensing nozzle in the aforementioned direction, which extends substantially perpendicularly to the surface of the substrate. A guide prevents a movement of the strut to which the at least one second dispensing nozzle is fixed in other directions.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

[0005] The accompanying drawings, which are incorporated into and constitute a part of this specification, illustrate one or more embodiments of the present invention and, together with the detailed description, serve to explain the principles and implementations of the invention. The figures are not to scale. In the drawings:

- Fig. 1 shows a perspective view of parts of a device in accordance with the invention for applying adhesive to a substrate;
- Fig. 2 shows the device in another perspective, and
- Figs. 3 and 4 show the device in two different operating modes.

DETAILED DESCRIPTION OF THE INVENTION

[0006] Fig. 1 shows a perspective view of a device in accordance with the invention for applying adhesive to a substrate insofar as it is required for the understanding of the invention. The device comprises a writing head 1 with a retainer 2, to which a first adhesive container 3 with a first dispensing nozzle 4 and a second adhesive container 5 with a second dispensing nozzle 6 can be fixed. In addition to Fig. 1, Fig. 2 shows the device in accordance with the invention from a different perspective. In Fig. 2, the adhesive containers and parts of the retainer 2 were omitted so that other parts of the device can be recognized with more clarity. The device comprises at least three drives (not shown) in order to move the writing head 1 in three spatial directions X, Y and Z, wherein the directions X and Y extend parallel to the surface of the substrate and the Z direction perpendicularly thereto. The adhesive containers and the respective dispensing nozzle are detachably connected to each other. The retainer 2 comprises a first

bracket 7 for fixing the first adhesive container 3, a second bracket 8 for fixing the second adhesive container 5, a first fixed frame 9, a second movable frame 10, a table 11 with a plate 12 and, optionally, a guide 13. The table 11 is fixed to the fixed frame 9, wherein the table 11 and the plate 12 are aligned in a plane-parallel way in respect to a support surface on which the substrates are placed. A first fastening part 14 is fixed to the plate 12, which fastening part is configured to fix the dispensing nozzle 4. The first fastening part 14 can be fastened displaceably in a first direction (the X direction in this case) to the plate 12 and the plates 12 can be fastened displaceably in a second direction (the Y direction in this case) to the table 11, so that the XY position of the tip of the first dispensing nozzle 4 is adjustable. A second fastening part 16 is fixed to the second frame 10, which is set up to fix the second dispensing nozzle 6. The second frame 10 is movably arranged in such a way that the second fastening part 16 is displaceable with respect to the first frame 9 and the plate 12 substantially in the Z direction. The second frame 10 consists of four struts 17 for example, which are each connected via a flexure hinge 18 to each other. The guide 13 is formed in this example by an elongated metallic strip 19, the one end of which is fixed to the plate 12 and the other end of which is fixed to the second fastening part 16, and by a leaf spring 20, the one end of which is fixed to the frame 10 and the other end of which is fixed to the writing head 1. The strip 19 and the leaf spring 20 ensure that the strut 17 of the movable frame 10 to which the second fastening part 16 is fixed can perform up and down movements, i.e. movements in the Z direction, while movements of the frame 10 in the X direction and the Y direction are not possible. As a result, fluttering of the second fastening part 16 is prevented during abrupt movements of the writing head 1. The tip of the first dispensing nozzle 4 is thus fixed to the writing head 1, whereas the tip of the second dispensing nozzle 6 is movable in a direction extending substantially perpendicularly to the surface of the substrate, which in this case is the Z direction. A pin 22 which is displaceable in the Y direction by means of an actuator 21 is fixed to the writing head 1, the object of which will be described below in closer detail. The actuator 21 and the pin 22 are not visible in Figs. 1 and 2, but in Figs. 3 and 4. Figs. 1 to 4 additionally show a small plate 23 which does not belong to the device and which illustrates the plane of the substrate surface.

[0007] The device further comprises either a first pneumatic system for supplying the first adhesive container 3 with a pressure pulse and a second pneumatic system for supplying the second adhesive container 5 with a pressure pulse, or a single pneumatic system and a valve which allow supplying both adhesive containers 3 and 5 simultaneously with a pressure pulse in a first valve position and only supplying the first dispensing nozzle 4 with a pressure pulse in a second valve position. The second adhesive container 5 is preferably supplied with negative pressure in the second valve position.

[0008] The device in accordance with the invention allows writing two adhesive patterns on two adjacent substrate places simultaneously with the two dispensing nozzles 4 and 6 in a first mode, or writing an adhesive pattern on one substrate place only with a single dispensing nozzle (namely the first

dispensing nozzle 4) in a second mode. For this purpose, the pin 22, the movable frame 10, the motorised Z axis of the writing head 1 and the pneumatic system (or the pneumatic systems) cooperate in the manner as described below. Fig. 3 shows the device in mode 1, and Fig. 4 shows the device in mode 2. The writing head 1 is lifted at first to a Z position z_1 during the change from one mode to the other mode.

[0009] Subsequently, for the operation in mode 1,

- the pin 22 is moved to a retracted position;
- the writing head is lowered to a predetermined Z position z_2 with $z_2 < z_1$, which corresponds to the desired working altitude of the tips of the dispensing nozzles 4 and 6 above the substrate;

or in mode 2

- the pin 22 is moved to an extended position;
- the writing head 1 is lowered to the predetermined Z position z_2 .

When the writing head 1 is lowered in mode 2, the movable frame 10 comes to rest on the pin 22 before it has reached the Z position z_2 . When the writing head 1 is then situated at the Z position z_2 , the tip of the first dispensing nozzle 4 is at the desired working altitude above the substrate, whereas the tip of the second dispensing nozzle 6 is situated at a higher altitude.

[0010] In mode 1, the writing head 1 is moved along a predetermined path, and the two adhesive containers 3 and 5 are supplied with a pressure pulse simultaneously and synchronously, whereas in mode 2 the writing head 1 is moved along a predetermined path and only the first adhesive container 3 is supplied with a pressure pulse.

[0011] The device can be extended easily in order to write several adhesive patterns 2 on adjacent substrate places with three, four or more adhesive containers and dispensing nozzles simultaneously in the first mode, and to write only one adhesive pattern in the second mode with a single dispensing nozzle.

[0012] The invention was described by reference to an embodiment. It is obvious to the person skilled in the art that the mechanical configuration of the device can also be realized in other ways in order to enable the operation of the device in the two operating modes.

CLAIMS

1. Device for dispensing adhesive on a substrate, comprising a writing head (1) movable in three spatial directions, wherein a first dispensing nozzle (4) and at least one second dispensing nozzle (6) can be fixed to the writing head (1) in such a way that the tip of the first dispensing nozzle (4) is fixed and the tip of the at least one second dispensing nozzle (6) is movable in a direction extending substantially perpendicularly to a surface of the substrate, wherein an actuator (21) with a pin (22) is fixed to the writing head (1), and wherein the device can be operated in two operating modes and is configured to perform the following steps for the change from the one operating mode to the other operating mode:
 - lifting of the writing head (1),
 - retracting or extending the pin (22), and
 - lowering of the writing head (1) to a predetermined working altitude, wherein the tips of the dispensing nozzles (4, 6) reach a substantially similar altitude above the substrate in the retracted state of the pin (22), and wherein the tip of the at least one second dispensing nozzle (6) reaches a higher altitude above the substrate than the tip of the first dispensing nozzle (4) in the extended state of the pin (22).
2. Device according to claim 1, wherein the device comprises four struts (17) which are connected to each other via flexure hinges (18), wherein the at least one second dispensing nozzle (6) is fixed to one of said struts (17), wherein the flexure hinges (18) enable a movement of the tip of the at least one second dispensing nozzle (6) in the said direction which extends substantially perpendicularly to the surface of the substrate, and wherein a guide (13) prevents a movement of the strut (17) to which the at least one second dispensing nozzle (6) is fixed in other directions.