

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 December 2010 (29.12.2010)

PCT

(10) International Publication Number
WO 2010/151514 A1

(51) International Patent Classification:

C10M 141/08 (2006.01) *C10N 30/10* (2006.01)
C10M 163/00 (2006.01) *C10N 40/20* (2006.01)
C10N 10/04 (2006.01)

(21) International Application Number:

PCT/US2010/039401

(22) International Filing Date:

22 June 2010 (22.06.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/220,626 26 June 2009 (26.06.2009) US

(71) Applicant (for all designated States except US): **THE LUBRIZOL CORPORATION** [US/US]; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JONES, Craig** [GB/GB]; P.O. Box 88, Belper Derby DE56 1QN (GB). **ADAMCZEWSKA, Jola, Z.** [GB/GB]; P.O. Box 88, Belper Derby DE56 1QN (GB). **DAVIES, Mark, C.** [GB/GB]; P.O. Box 88, Belper, Derby DE56 1QN (GB).

(74) Agents: **SHOLD, David, M.** et al.; THE LUBRIZOL CORPORATION, Patent Dept./022B, 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:

— with international search report (Art. 21(3))

(54) Title: ENGINE OIL FORMULATIONS FOR BIODIESEL FUELS

(57) Abstract: Oxidative degradation may be reduced in a lubricant composition which contains an oil of lubricating viscosity and at least about 1 percent by weight of a C1-C3 alkyl ester of a carboxylic acid of about 12 to about 24 carbon atoms, by including within the lubricant composition a sulfonate detergent in an amount sufficient to provide at least about 0.2 percent by weight sulfonate soap to the lubricant composition, wherein the weight ratio of sulfonate soap to phenate soap in the lubricant composition is at least about 0.35:1.



WO 2010/151514 A1