

- 1 -

CONNECTION STRUCTURE OF COAXIAL CABLE TO ELECTRIC
CIRCUIT SUBSTRATE

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

 The present invention relates to a structure
of connecting a coaxial cable to an electric circuit
substrate and a structure of connecting a coaxial
10 cable to an electric circuit substrate preferably
applied to an electric device testing apparatus for
testing a semiconductor integrated circuit element and
other variety of electric devices (hereinafter, also
simply referred to as an IC).

15 2. Description of the Related Art

 An electronic devices testing apparatus called a
"handler" conveys a large number of ICs held on a tray
to inside of a testing apparatus where the ICs are
pressed against socket terminals connected to a test
20 head, then the IC testing unit (tester) is made to
perform a test. When the test is ended, the ICs are
conveyed out from the test procedure and reloaded on
trays in accordance with results of the tests so as to
classify them into categories of good ICs and
25 defective ones.

- 2 -

Here, a socket board 505 (an electric circuit substrate) of the test heads is connected to a coaxial cable 506 shown in Fig. 5. In the related art, a coaxial cable was connected to a socket board by soldering a core wire 506a of the coaxial cable 506 to the socket board 505 and a jumper cable J soldered to the socket board 505 and a shield 506b of the coaxial cable 506 were twisted together and soldered. By connecting a large number of such coaxial cables 506 to the socket board 505, sending and receiving of test signals is performed between the tester and the test head at the time of pressing ICs against socket terminals.

In the above connection structure of a coaxial cable to a socket board in the related art, however, since the core wire 506a constituting a signal line and the jumper cable J constituting an earth line were connected one to one, a space S between the core wire 506a and the jumper cable J needs to be at least 2 to 3 mm, so there was a disadvantage that a packaging density of the coaxial cable 506 could not be made higher.

Also, since an earth line was configured by connecting the jumper cable J and the shield 506b, the earth line inevitably became long, consequently, there

- 3 -

was a disadvantage that inductance of a high frequency range increased and frequency characteristics declined.

Furthermore, there was a disadvantage that consistency of impedance of a signal was poor since exposing portions of an insulation body 506c of the core wire was large and not covered by the shield 506b.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a connection structure of a coaxial cable to an electric circuit substrate which can heighten a packaging density of coaxial cables and has excellent electric characteristics.

In accordance with an aspect of the invention, there is provided a connection structure of a coaxial cable to an electric circuit substrate, comprising a cable block connected to a ground line of the electric circuit substrate and a coaxial cable wherein the ground line is connected to said cable block, said cable block has a concave portion in accordance with an outward form of said coaxial cable, and the ground line of said coaxial is connected to said concave portion

In this connection structure, since a ground line of a coaxial cable is connected to a ground line of an electric circuit substrate via a cable block connected to the ground line of the electric circuit substrate,

- 4 -

a plurality of coaxial cables can be grounded by one cable block. Accordingly, an area occupied by the ground line of the electric circuit substrate becomes smaller and a higher packaging density of coaxial
5 cables becomes attainable. Also, since the ground line of the coaxial cable is directly connected to the cable block, the length of the ground line becomes shorter and frequency characteristics improves. Furthermore, by directly connecting the ground line of
10 the coaxial cable to the cable block, the core wire is covered by the ground line to the end of the coaxial cable, as a result, consistency of impedance of signals becomes preferable.

It is not particularly limited in the above
15 invention, but the cable block preferably has a concave portion in accordance with an outward form of the coaxial cable, and the ground line of the coaxial cable is connected to the concave portion.

By setting an outward form of the coaxial cable in
20 a concave portion of the cable block at the time of connecting the ground line of the coaxial cable to the cable block, a position of the core wire of the coaxial cable can be made accurate.

Also, it is not particularly limited in the above
25 invention, but the core wire of the above coaxial

- 5 -

cable is preferably connected to a land of a signal line of the above electric circuit substrate.

By connecting the core wire of the coaxial cable to the land of the signal line, connection bias becomes small and a capacity can be made small.

Particularly, as explained above, since the position of the core wire of the coaxial cable is accurately determined by setting the ground line of the coaxial cable in the concave portion in the cable block, relative position with respect to the land of the signal line can be also made accurate.

Also, it is not particularly limited in the above invention, but preferably, the above cable block is formed a conductive material layer, for example, a copper plating layer on a surface of the substrate.

By making a plating layer by a conductive material having a large heat capacity, a temperature rising speed at the time of soldering

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and features of the present invention will be explained in more detail below with reference to the attached drawings, wherein:

Fig. 1 is a view from a side of an electric device

- 6 -

testing apparatus being applied a connection structure of the present invention;

Fig. 2 is a detailed sectional view of a test head in Fig. 1;

5 Fig. 3 is a sectional view along the line III-III in Fig. 2;

Fig. 4A is a sectional view of an embodiment of the connection structure of the present invention;

10 Fig. 4B is a view along the B-direction in Fig. 4A;

Fig. 4C is a sectional view of another embodiment of a cable block; and

Fig. 5 is a view from a side of a connection structure of the related art.

15

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in Fig. 1, an electric device testing apparatus being applied the present invention is comprised of, for example, a handler 1 for handling
20 ICs to be tested, a test head 5 which electrically contacts the ICs to be tested, and a tester 6 for sending a test signal to the test head 5 and conducting a test on the ICs to be tested. The electric device testing apparatus tests (inspects)
25 whether or not ICs suitably operate in a state when

- 7 -

high temperature or low temperature stress is applied on the ICs and sorts the ICs in accordance with the test results.

As shown in Fig. 2 and Fig. 3, in the test head 5, a base board 502 is mounted on the test head body 501 via a connector 502a and a spacing frame 503 is provided on the base board 502 via a space column 502b capable of slightly moving up and down in a Z-axis direction.

On the spacing frame 503 is provided a socket board 505 via a socket board spacer 504, and further thereon is provided a sub-socket board 511 via a sub-socket board spacer 513.

Between the base board 502 and the socket board 505 is connected by a plurality of coaxial cables 506 and between the socket board 505 and the sub-socket board 511 is connected by a relay terminal 512.

Note that Fig. 2 is a sectional view of seeing the test head 5 to an X-axis direction, wherein only two sets of socket boards 505 and sub-socket boards 511 are shown in a Y-axis direction, however, an actual test head 5 of 4 lines and 16 rows is provided with four sets of socket boards 505 and sub-socket boards 511 in the Y-axis direction.

Also, Fig. 3 is a sectional view of seeing the

- 8 -

test head 5 to the Y-axis direction, wherein only one set of socket board 505 and sub-socket board 511 are shown in the X-axis direction, however, an actual test head 5 of 4 lines and 16 rows is provided with eight
5 sets of socket boards 505 and sub-socket boards 511 in the X-axis direction.

An IC socket terminal 510 and a socket guide 514 in accordance with need are provided on the respective sub-socket boards 511. The IC socket terminal 510
10 comprises a plurality of contact pins for contacting input/output terminals of the ICs to be tested and connected to lands, etc. formed on an upper surface of the sub-socket board 511. Also, the socket guide 514 is a guide for determining positions of the ICs to be
15 tested at the time of bringing the ICs to be tested contact the contact pins of the IC socket terminal 510 and may be omitted.

Figures 4A to 4C are views of embodiments of a connection structure of a coaxial cable to an electric
20 circuit substrate of the present invention, wherein Fig. 4A is a general sectional view, Fig. 4B is a B perspective view in Fig. 4A, and Fig. 4C is a sectional view of another embodiment of a cable block. Figure 4A is an enlarged sectional view of a IV
25 portion in Fig. 3.

- 9 -

In the present embodiment, a coaxial cable wherein a core wire 506a and a shield 506b are provided over an insulation body 506c is connected to a socket board 505 as an electric circuit substrate, and a large
5 number of coaxial cables 506 are connected to the socket board 505 of an actual test head 5 as shown in Fig. 2 and Fig. 3., but only two coaxial cables 506 are shown in Fig. 4A to explain a connection structure of the present embodiment.

10 The socket board 505 is constituted by stacking a large number of wiring pattern layers on which a wiring pattern including a signal line and a ground line is formed, the reference number 505a in Fig. 4A indicates a wiring pattern layer including a signal
15 line and 505c an insulation layer.

In the present embodiment, there is provided a cable block 515 electrically connected to the ground line 505b. The cable block 515 can be comprised of a copper block and can be connected to the ground line
20 505b by peeling a part of the insulation layer 505c on its backside surface (the lower surface in the figure) and soldering thereto.

At this time, the overall cable block 515 can be comprised of a copper material, but considering heat
25 conductivity at the time of soldering, it is

- 10 -

preferable to be formed by plating with copper on the whole surface of a substrate made by glass, epoxy or polytetrafluoroethylene (PTFE), etc. Furthermore, if one main surface of the ground line side connected to the copper plated cable block or the cable block side of copper plating is formed a soldering plating layer, excellent heat conductivity is obtained and soldering becomes remarkably easier. This example is shown in Fig. 4C. The reference number 515b indicates a substrate made by glass, epoxy or PTFE, etc., 515c indicates the copper plating layer and 515d indicates the soldering plating layer.

The cable block 515 is formed a concave portion 515a in accordance with an outward form of the shield 506b of the coaxial cable 506 at an interval of the coaxial cable 506 to be mounted. A depth of the concave portion 515a is not limited, but it bears a function of determining a position of the core wire 506a by being set the shield 506b of the coaxial cable 506 in the concave portion 515a, thus, it is made to be a suitable depth therefor. In the present embodiment, it is made to be a semicircular shape.

Also, the concave portion 515a is connected to the shield 506b of the coaxial cable 506 by soldering.

Also, in the present embodiment, the core wire

- 11 -

506a is connected by soldering to lands of a signal line formed on the backside surface of the socket board 505 (detailed illustration is omitted). By connecting the core wire 506a of the coaxial cable 506 to the lands of the signal line in this way, a connection via-hole (transit through-hole) becomes small and electrostatic capacitance between a signal and a ground can be made smaller. In addition to this, since the shield 506b of the coaxial cable 506 is directly connected to the cable block 515, the portion where the insulation body 506c is exposed can be made as short as possible and the core wire 506a is covered with the shield 506b to the end of the coaxial cable 506, as a result, consistency of impedance of a signal becomes preferable.

Furthermore, since the shields 506b of a plurality of coaxial cables 506 can be grounded by one cable block 515 in the present embodiment, an area occupied by the ground line 505b of the socket board 505 becomes smaller and a higher packaging density of the coaxial cables 506 can be attained. Also, since the shield 506b of the coaxial cable 506 is directly connected to the cable block 515, a length of the ground line becomes shorter and electric characteristics becomes preferable.

- 12 -

Note that the embodiments explained above were described to facilitate the understanding of the present invention and not to limit the present invention. Accordingly, elements disclosed in the
5 above embodiments include all design modifications and equivalents belonging to the technical field of the present invention.

- 13 -

CLAIMS

1. A connection structure of a coaxial cable to an electric circuit substrate, comprising a cable
5 block connected to a ground line of the electric circuit substrate and a coaxial cable

wherein the ground line is connected to said cable block, said cable block has a concave portion in accordance with an outward form of said coaxial cable,
10 and the ground line of said coaxial cable is connected to said concave portion.

2. A connection structure of a coaxial cable to an electric circuit substrate as set forth in claim 1,
15 wherein a core wire of said coaxial cable is connected to a land of a signal line of said electric circuit substrate.

3. A connection structure of a coaxial cable to
20 an electric circuit substrate as set forth in claim 1 or 2, wherein said cable block is provided by partially buried in said electric circuit substrate so as to be connected to the ground line provided to an inner layer of the electric circuit substrate.

25

4. A connection structure of a coaxial cable to an electric circuit substrate as set forth in any one of the preceding claims, wherein said cable block is

- 14 -

formed on its substrate surface a conductive material layer.

5. A connection structure of a coaxial cable to
5 an electric circuit substrate as set forth in claim 4,
wherein said conductive material is copper.

6. A connection structure of a coaxial cable to
an electric circuit substrate as set forth in any one
10 of the preceding claims, wherein the ground lines of
said electric circuit substrate and said cable block
are soldered.

7. A connection structure of a coaxial cable to
15 an electric circuit substrate as set forth in any one
of the preceding claim s, wherein said cable block and
the ground line of said coaxial cable are soldered.

- 15 -

CONNECTION STRUCTURE OF COAXIAL CABLE TO ELECTRIC
CIRCUIT SUBSTRATE

5

ABSTRACT OF THE DISCLOSURE

A connection structure of a coaxial cable to an
electric circuit substrate, comprising a cable block
10 connected to a ground line of the electric circuit
substrate and a coaxial cable whose shield is
connected to the cable block.

Fig. 4A