



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/56	A1	(11) International Publication Number: WO 97/27691 (43) International Publication Date: 31 July 1997 (31.07.97)
(21) International Application Number: PCT/SE97/00118 (22) International Filing Date: 24 January 1997 (24.01.97) (30) Priority Data: 9600279-5 25 January 1996 (25.01.96) SE (71) Applicant (for all designated States except US): TELEFON-AKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): ENEROTH, Lars, Göran, Vilhelm [SE/SE]; Scheffers gränd 13, S-135 61 Tyresö (SE). NÄSMAN, Karl, Anders [SE/SE]; Södra Långgatan 34, S-171 49 Solna (SE). PETERSEN, Lars-Göran [SE/SE]; Hökbursvägen 5, S-147 42 Tumba (SE). (74) Agents: BJELLMAN, Lennart et al.; Dr. Ludwig Brann Patentbyrå AB, P.O. Box 1344, S-751 43 Uppsala (SE).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	
(54) Title: A METHOD OF INDICATING MINI CELL SIZE (57) Abstract The invention relates to a method of changing the size of mini cells belonging to an individual connection during an ongoing connection. A control mini cell is used for this purpose. The control mini cell is transported either in a separate connection or in the same individual connection the mini cell size of which it shall change. Depending on system design the control mini cell is handled either at the control plane by the operation and maintenance system of the telecommunication network or it is handled at the traffic plane by transmission equipments.		