

(19) World Intellectual Property
Organization
International Bureau



WIPO | PCT



(10) International Publication Number

WO 2020/085997 A8

(43) International Publication Date
30 April 2020 (30.04.2020)

(51) International Patent Classification:

H04W 72/04 (2009.01) H04W 74/00 (2009.01)
H04W 52/02 (2006.01)

Singapore 469332 (SG). **URABE, Yoshio**; c/o Panasonic Corporation, 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(21) International Application Number:

PCT/SG2019/050403

(74) Agent: SPRUSON & FERGUSON (ASIA) PTE LTD;

P.O. Box 1531, Robinson Road Post Office, Singapore 903031 (SG).

(22) International Filing Date:

15 August 2019 (15.08.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

10201809503R 26 October 2018 (26.10.2018) SG

(71) Applicant: **PANASONIC INTELLECTUAL PROPERTY CORPORATION OF AMERICA** [US/US]; 20000 Mariner Avenue, Suite 200, Torrance, California 90503 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(72) Inventors: **CHITRAKAR, Rojan**; c/o Panasonic R&D Center Singapore, 202 Bedok South Avenue 1, #02-11, Singapore 469332 (SG). **HUANG, Lei**; c/o Panasonic R&D Center Singapore, 202 Bedok South Avenue 1, #02-11,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,

(54) Title: COMMUNICATION APPARATUS AND COMMUNICATION METHOD FOR MULTI-BAND TRANSMISSION




Figure 3

(57) Abstract: A multi-band communication device includes: one or more transceiver circuitries, each of which in operation transmits and receives data on a plurality of channels in different frequency bands; and a band configuration circuitry operative to change a configuration of any one of the transceiver circuitries based on configuration information received from a multi-band Access Point (AP). The configuration information specifies one of the frequency bands as a Primary band and the other frequency bands as Secondary band(s). The transceiver circuitry operating on the Primary band is used as a default circuitry for communication with the AP.

[Continued on next page]

TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

Published:

— *with international search report (Art. 21(3))*
— *in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE*

(48) Date of publication of this corrected version:

18 February 2021 (18.02.2021)

(15) Information about Correction:

see Notice of 18 February 2021 (18.02.2021)