

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 June 2002 (13.06.2002)

PCT

(10) International Publication Number
WO 02/047361 A3

(51) International Patent Classification⁷: **H04B 7/005**

(21) International Application Number: PCT/US01/46969

(22) International Filing Date: 4 December 2001 (04.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/251,537	5 December 2000 (05.12.2000)	US
09/738,016	15 December 2000 (15.12.2000)	US
09/755,207	5 January 2001 (05.01.2001)	US

(71) Applicant: **QUALCOMM INCORPORATED** [US/US];
5775 Morhouse Drive, San Diego, CA 92121-1714 (US).

(72) Inventors: **CHEN, Tao**; 8826 La Cartera, San Diego, CA 92129 (US). **WANG, Jun**; 13203 Winstanley Way, San Diego, CA 92130 (US).


(74) Agents: **WADSWORTH, Philip, R.** et al.; Qualcomm Incorporated, 5775 Morehouse Drive, San Diego, CA 92121-1714 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR POWER LEVEL ADJUSTMENT IN A WIRELESS COMMUNICATION SYSTEM



(57) Abstract: A method and apparatus for transmitter re-initialization in a wireless communication system 810). When the communication link between a mobile station (38) and a base station (32) is in trouble, the mobile station and the infrastructure prearrange potential rescue base stations (34). The mobile station 838) disables the transmitter during the rescue process. On recovery the transmit power level of the transmitter is incremented for transmission of the pilot strength measurement message until a hand-off direction message is received. The transmit power level is incremented to a maximum value.

WO 02/047361 A3



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

30 October 2003