

What is claimed is:

1. A sliced assembly type container, characterized that the sliced assembly type container is in consistent with ISO requirements about a general cargo container, and
5 comprises a bottom finished module, two lateral finished modules, two door finished modules respectively hinged to door ends of lateral bodies of the two lateral finished modules, a top finished module, and a front finished module, and

the bottom finished module comprises: a bottom body; two bottom lateral connecting parts, respectively disposed on both sides of the bottom body, to fixedly
10 connect the two lateral finished modules, each of the bottom lateral connecting parts comprises a lateral connecting element, a first corner connecting element at the door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a bottom front connecting part, disposed at a front end of the bottom body, to connect the front finished module;

15 the lateral finished module comprises: a lateral body; lateral bottom connecting parts, disposed on a bottom side of the lateral body, to fixedly connect the bottom finished module, each of the lateral bottom connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral
20 connecting element; lateral top connecting parts, disposed on a top side of the lateral body, to fixedly connect the top finished module, each of the lateral top connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a lateral front connecting part, disposed at a front
25 end of the lateral body, to connect the front finished module;

the top finished module comprises: a top body; two top lateral connecting parts, respectively disposed on both sides of the top body, to fixedly connect the two lateral finished modules, each of the top lateral connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting
5 element, and a second corner connecting element at a front end of the lateral connecting element; and a top front connecting part, disposed at the front end of the top body, to connect the front finished module;

the front finished module comprises: a front body; a front bottom connecting part, disposed on a bottom side of the front body, to connect the bottom finished module; two
10 front lateral connecting parts, respectively disposed on both sides of the front body, to connect the two lateral finished modules; and a front top connecting part, disposed on a top side of the front body, to connect the top finished module;

wherein between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are
15 totally four pairs of the lateral connecting elements being able to be fixedly connected together via a connecting piece and/or a structural adhesive; between the bottom finished module and the front finished module, between the top finished module and the front finished module, as well as between the two lateral finished modules and the front finished module, there are totally four pairs of side connections being able to be fixedly
20 connected together via a connecting piece and/or a structural adhesive; between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are totally eight pairs of the corner connection elements being able to be fixedly connected together via a connecting piece; and sealing process is performed on coupled portions between the modules of the sliced
25 assembly type container.

2. The sliced assembly type container according to claim 1, characterized that the sliced assembly type container is in consistent with requirements about container in CSC and/or UIC.

5

3. The sliced assembly type container according to claim 1, characterized that the sliced assembly type container is in consistent with requirements about a container in TIR.

10

4. The sliced assembly type container according to claim 1, characterized that the door finished module and the lateral finished module are one integrated finished module; or, the door finished modules and the lateral finished module are two finished modules separated from each other.

15

5. The sliced assembly type container according to claim 1, characterized that the bottom body comprises two sets of door end bottom corner parts, bottom longitudinal beams and front end bottom corner parts, respectively disposed on both sides thereof, a front end bottom beam connected between the two front end bottom corner fittings, a doorsill connected between of the two door end bottom corner fittings, bottom crossbeams each connected between the two bottom longitudinal beams, and a floor; the first corner connecting element of the bottom lateral connecting parts is disposed on a top of the door end bottom corner par, the second corner connecting element is disposed on a top of the front end bottom corner fitting, and the lateral connecting elements are disposed on a top of the bottom longitudinal beam; the lateral body comprises a lateral wall, a front end corner pillar connected to a front end of the lateral wall, and a door end

20

25

corner pillar connected to a door end of the lateral wall; the first corner connecting element of the lateral bottom connecting part is disposed on a bottom of the door end corner pillar, the second corner connecting element is disposed on a bottom of the front end corner pillar, the lateral connecting elements are disposed on a bottom of the lateral wall; and wherein the corresponding lateral connecting elements are able to be fixedly connected together via a connecting piece.

6. The sliced assembly type container according to claim 5, characterized that one of the two first corner connecting element comprises a vertically extending protrusion; the other of the two first corner connecting elements comprises a receiving cavity correspondingly for insertion of the protrusion; and the two first corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation with the protrusion and the receiving cavity.

7. The sliced assembly type container according to claim 6, characterized that a connection structure of the two first corner connecting elements is selected from any one of the plug-in structures below:

a first plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a upwardly protruding protrusion, and a first connecting hole and first mounting holes around the first connecting hole are horizontally disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at a bottom of the door end corner pillar, and a second connecting hole and second mounting holes surrounding the second connecting hole are horizontally disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece comprises a connecting pin

and a fastener, the connecting pin is disposed to penetrate through the first and second connecting holes and has a locking effect and has third mounting holes disposed therein, and the fastener is disposed to penetrate into the first to third mounting holes;

5 a second plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, and a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting pieces are
10 disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a third plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the first corner connecting element of the lateral bottom
15 connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, and a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the door end corner pillar comprises a first corner pillar part, a second corner pillar part and a reinforcing part, which all are welded together, the reinforcing part is correspondingly welded in the
20 bottom of the first corner pillar part/the second corner pillar part and located between the first corner pillar part and the second corner pillar part, the connecting hole in the bottom of the door end corner pillar comprises holes formed in the first corner pillar part, the reinforcing part and the second corner pillar part, respectively; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having a
25 locking effect may be selected;

a fourth plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises an upwardly protruding protrusion, and two connecting holes and a mounting hole positioned on a side of each of the connecting holes and communicating with the connecting holes are disposed in the protrusion; the first corner
5 connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, and two connecting holes and a mounting hole positioned on a side of each of the connecting holes and communicating with the connecting holes are horizontally disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece comprises
10 two connecting pins and a fastener, the connecting pins are correspondingly disposed to penetrate into the connecting holes and have locking effect, and the fastener is correspondingly disposed to penetrate into the mounting holes;

a fifth plug-in structure: the first corner connecting element of the bottom lateral connecting parts comprises a upwardly protruding protrusion, and a connecting hole is
15 disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece comprises a bolt having a locking effect and a tail cone and being correspondingly disposed to penetrate
20 into the connecting holes.

a sixth plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a connecting block having a downwardly depressed receiving cavity, the connecting block has a horizontally traversing connecting hole disposed therein; the first corner connecting element of the lateral bottom connecting part
25 comprises a downwardly protruding protrusion, and a connecting hole is disposed in the

protrusion to horizontally pass therethrough; the connecting piece is disposed to penerate into the connecting holes, and the connecting piece having locking effect may be selected;

5 a seventh plug-in structure: the first corner connecting element of the bottom lateral connecting parts comprises a vertically extending protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into the receiving cavity;

10 an eighth plug-in structure: the first corner connecting element of the lateral bottom connecting part comprises a vertically extending protrusion; the first corner connecting element of the bottom lateral connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into the receiving cavity.

15 8. The sliced assembly type container according to claim 7, characterized that the connecting piece having locking effect is a rivet.

20 9. The sliced assembly type container according to claim 7, characterized that the protrusion is a special-shaped protrusion, and the the filler is a glue, a high strength resin or a special cement in the seventh plug-in structure and/or the eighth plug-in structure.

25 10. The sliced assembly type container according to claim 5, characterized that the first corner connecting element of the bottom lateral connecting parts comprises a first overlapping piece; the first corner connecting element of the lateral bottom connecting

part comprises a second overlapping piece, and the two first corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation with the two overlapping pieces.

5 11. The sliced assembly type container according to claim 10, characterized that a connection structure of the two first corner connecting element is selected from any of the overlapped structures below:

10 a first overlapped structure: the first overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the second overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the connecting piece is selected to be a fastener correspondingly to penetrate into the connecting holes;

15 a second overlapped structure: the first overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

20 a third overlapped structure: the first overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; wherein one of the two overlapping pieces has an overlapping surface with a clasp slot depressed therein, and the other of the two overlapping pieces has an overlapping surface with a clasp block protruded therein, the clasp block is in cooperation with the clasp slot; the connecting piece is disposed to penetrate into the connecting holes, and the connecting
25 piece having locking effect may be selected.

12. The sliced assembly type container according to claim 11, characterized that the connecting piece having locking effect is a rivet.

5 13. The sliced assembly type container according to claim 5, characterized that the second corner connecting element of the bottom lateral connecting part comprises a first overlapping piece; the second corner connecting element of the lateral bottom connecting part comprises a second overlapping piece, the two second corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation
10 with the two overlapping pieces.

14. The sliced assembly type container according to claim 13, characterized that a connection structure of the two second corner connecting element is selected from any of the overlapped structures below:

15 a first overlapped structure: the first overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the second overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the connecting piece is chosen to be a fastener correspondingly to penetrate into the connecting holes;

20 a second overlapped structure: the first overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

25 a third overlapped structure: the first overlapping piece has a vertically overlapping

surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; wherein one of the two overlapping pieces has an overlapping surface with a clasp slot depressed therein, and the other of the two overlapping pieces has an overlapping surface with a clasp block protruded therein, the clasp block is in cooperation with the clasp slot; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a fourth overlapped structure: the first overlapping piece comprises a first part having a vertically overlapping surface with a connecting hole disposed therein, and a second part having a horizontally overlapping surface with a connecting hole disposed therein; the second overlapping piece comprises a first part having a vertically overlapping surface with a connecting hole disposed therein, and a second part having a horizontally overlapping surface with a connecting hole disposed therein; the connecting pieces are disposed to horizontally penetrate into the connecting holes and disposed to vertically penetrate into the connecting holes, wherein the connecting piece disposed to horizontally penetrate into the connecting holes is selected to be a connecting piece having locking effect, and the connecting piece disposed to vertically penetrate into the connecting holes is a fastener.

15. The sliced assembly type container according to claim 14, characterized that in any of the overlapped structures, the first overlapping piece has a shape of L; and the second overlapping piece has a shape of L.

16. The sliced assembly type container according to claim 14, characterized that the connecting piece having locking effect is a rivet.

17. The sliced assembly type container according to claim 5, characterized that one of the two second corner connecting elements comprises a vertically extending protrusion; the other of the two second corner connecting elements comprises a receiving cavity for insertion of the protrusion; the two second corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation with the two overlapping pieces.

18. The sliced assembly type container according to claim 17, characterized that a connection structure of the two second corner connecting element is selected from any one of the plug-in structures below:

a first plug-in structure: the second corner connecting element of the bottom lateral connecting part comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the second corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of front end corner pillar, the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a second plug-in structure: the second corner connecting element of the bottom lateral connecting part comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the second corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the front end corner pillar, a connecting hole is disposed in the protrusion in the bottom of the front end corner pillar at a position corresponding to the receiving cavity; the front end corner pillar comprises a first corner pillar part, a second corner pillar part and a reinforcing part, which all are welded together, the reinforcing part is correspondingly welded in the

bottom of the first corner pillar part/the second corner pillar part and located between the first corner pillar part and the second corner pillar part, the connecting hole in the bottom of the front end corner pillar comprises holes formed in the first corner pillar part, the reinforcing part and the second corner pillar part, respectively; the connecting
5 piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a third plug-in structure: the second corner connecting element of the bottom lateral connecting part comprises a connecting block having a downwardly depressed receiving cavity, the connecting block has a connecting hole disposed therein; the
10 second corner connecting element of the lateral bottom connecting part comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected.

a fourth plug-in structure: the second corner connecting element of the bottom
15 lateral connecting part comprises a vertically extending protrusion; the second corner connecting element of the lateral bottom connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into the receiving cavity;

a fifth plug-in structure: the second corner connecting element of the lateral bottom
20 connecting part comprises a vertically extending protrusion; the second corner connecting element of the bottom lateral connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into the receiving cavity.

25 19. The sliced assembly type container according to claim 18, characterized that the

connecting piece having locking effect is a rivet.

20. The sliced assembly type container according to claim 18, characterized that in the fourth plug-in structure and/or fifth plug-in structure, the protrusion may be is
5 special-shaped protrusion, the filler is selected from a glue, a high strength resin or a special cement.

21. The sliced assembly type container according to claim 3, characterized that the first corner connecting element of the bottom lateral connecting parts comprises a
10 upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at a bottom of the door end corner pillar, a connecting hole is disposed in the the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece to fixedly connecting the two first corner
15 connecting elements is disposed correspondingly penetrate into the connecting holes, and the connecting piece having locking effect may be selected; the second corner connecting element of the bottom lateral connecting part comprises a first overlapping piece, the second corner connecting element of the lateral bottom connecting part comprises a second overlapping piece, the connecting piece to fixedly connecting the
20 two second corner connecting elements is disposed correspondingly penetrate into the connecting holes, and if the two overlapping pieces are horizontally overlapped, the connecting piece is a fastener, if the two overlapping pieces are vertically overlapped, then the connecting piece having locking effect may be selected.

25 22. The sliced assembly type container according to claim 21, characterized that the

connecting piece having locking effect is a rivet.

23. The sliced assembly type container according to claim 5, characterized that the lateral connecting element of the bottom lateral connecting part comprises a first
5 abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall;

the lateral connecting element of the lateral bottom connecting part comprises a second abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall;

10 the connecting piece to fixedly connect the corresponding two lateral connecting elements is a fastener disposed correspondingly penetrate into the two connecting holes.

24. The sliced assembly type container according to claim 23, characterized that the second abutting wall has an outer side edge protruding downwardly from an outer side
15 thereof, and the outer side edge is positioned corresponding to an outer side of the first abutting wall;

or, the second abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is positioned corresponding to an outer side of the first abutting wall, further, the second abutting wall has an inner side edge
20 protruding downwardly from an inner side thereof, and the inner side edge is positioned corresponding to an inner side of the first abutting wall.

25. The sliced assembly type container according to claim 5, characterized that the lateral connecting element of the bottom lateral connecting part comprises a first
25 abutting wall extending vertically, and a connecting hole is disposed in the abutting

wall;

the lateral connecting element of the lateral bottom connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall;

5 the second abutting wall is correspondingly positioned on an outer side of the first abutting wall, or, the first abutting wall is correspondingly positioned on an outer side of the second abutting wall;

the connecting piece to fixedly connect the corresponding two lateral connecting elements is a fastener disposed correspondingly to penetrate into the two connecting
10 holes.

26. The sliced assembly type container according to claim 1, characterized that the top body comprises two sets of door end top corner parts, top longitudinal beams, and front end top corner parts positioned on both sides thereof, the front end top beam
15 connected between two of the front end top corner parts, an lintel connected between the two door end top corner parts, and the top plate;

the first corner connecting element of the top lateral connecting part is disposed on the bottom of the door end top corner part of the top body, the second corner connecting element is disposed on the bottom of the front end top corner part, the lateral connecting
20 element is disposed on the bottom of the top longitudinal beam;

the first corner connecting element of the lateral top connecting part is disposed on the top of a door end corner pillar of the lateral body, the second corner connecting element is disposed on the top of the front end corner pillar, the lateral connecting element is disposed on the top of the lateral wall; and

25 the corresponding lateral connecting elements are able to be fixedly connected

together via a connecting piece.

27. The sliced assembly type container according to claim 26, characterized that the connection structure of the first corner connecting element of the top lateral connecting parts and the corresponding first corner connecting element of the lateral top connecting part is as same as the connection structure of the first corner connecting element of the bottom lateral connecting part and the first corner connecting element of the lateral bottom connecting part;

the connection structure of the second corner connecting element of the top lateral connecting part and the corresponding second corner connecting element of the lateral top connecting part is as same as connection structure of the second corner connecting element of the bottom lateral connecting part and the second corner connecting element of the lateral bottom connecting part.

28. The sliced assembly type container according to claim 26, characterized that the lateral connecting element of the top lateral connecting parts comprises first abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall; the lateral connecting element of the lateral top connecting part comprises a second abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall; the connecting piece to fixedly connect the corresponding two lateral connecting elements is a fastener disposed correspondingly to penetrate into the two connecting holes.

29. The sliced assembly type container according to claim 28, characterized that the first abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is correspondingly positioned on an outer side of the

second abutting wall; or, the first abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is correspondingly positioned on an outer side of the second abutting wall, the first abutting wall has an inner side edge protruding downwardly from an inner side thereof, and the inner side edge is correspondingly positioned on an inner side of the second abutting wall.

30. The sliced assembly type container according to claim 28, characterized that the second abutting wall has an inner side edge protruding from an inner side thereof, and the inner side edge is correspondingly positioned on an inner side of the first abutting wall; or, the second abutting wall has an inner side edge protruding from an inner side thereof, and the inner side edge is correspondingly positioned on an inner side of the first abutting wall, further, the first abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is correspondingly positioned on an outer side of the second abutting wall.

31. The sliced assembly type container according to claim 28, characterized that the top finished module further comprises a reinforcing plate welded on the top longitudinal beams, a top of the reinforcing plate abuts against the top longitudinal beam, and a bottom of the reinforcing plate abuts against the first abutting wall.

32. The sliced assembly type container according to claim 26, characterized that the lateral connecting element of the top lateral connecting part comprises a first abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; the lateral connecting element of the lateral top connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall;

wherein the second abutting wall is correspondingly positioned on an inner side of the first abutting wall, or, the first abutting wall is correspondingly positioned on an inner side of the second abutting wall; the connecting piece to fixedly connect the corresponding two lateral connecting elements is a fastener disposed correspondingly to penetrate into the two connecting holes.

33. The sliced assembly type container according to claim 1, characterized that the bottom body comprises a front end bottom beam connected between the two front end bottom corner fittings, a doorsill connected between the two door end bottom corner fittings, a crossbeam connected between the two bottom longitudinal beams, and a floor; the bottom front connecting part is disposed on the front end bottom beam of the bottom body; the front bottom connecting part and the bottom front connecting part are fixedly connected together via a connecting piece.

34. The sliced assembly type container according to claim 33, characterized that the front bottom connecting part comprises a first abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall; the bottom front connecting part comprises a second abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall; the connecting piece for fixing the corresponding two side connections is a fastener correspondingly disposed to penetrate into the two connecting holes.

35. The sliced assembly type container according to claim 34, characterized that the first abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is correspondingly positioned on an outer side of the

second abutting wall; and/or, the first abutting wall has an inner side edge protruding downwardly from an inner side thereof, and the inner side edge is correspondingly positioned on an inner side of the second abutting wall.

5 36. The sliced assembly type container according to claim 1, characterized that the top body comprises two sets of door end top corner parts, top longitudinal beams, and front end top corner parts on both sides, a front end top beam connected between two of the front end top corner fittings, a lintel connected between the two door end top corner fittings, and a top plate; the top front connecting part is disposed on the front end top
10 beam of the top body; and the front top connecting part and the top front connecting part are fixedly connected together via a connecting piece.

 37. The sliced assembly type container according to claim 36, characterized that the front top connecting part comprises a first abutting wall extending vertically, and a
15 connecting hole is disposed in the abutting wall; the top front connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; wherein the second abutting wall is positioned on an outer side of the first abutting wall, or, the first abutting wall is positioned on an outer side of the second abutting wall; the connecting piece for fixing the corresponding two side connections is
20 a fastener correspondingly disposed to penetrate into the two connecting holes.

 38. The sliced assembly type container according to claim 1, characterized that the lateral body comprises a lateral wall, a front end corner pillar connected to a front end of the lateral wall, and a door end corner pillar connected to a door end of the lateral wall;
25 the lateral front connecting part is disposed on the front end corner pillar of the lateral

body; the front lateral connecting part and the lateral front connecting part are fixedly connected together via a connecting piece.

39. The sliced assembly type container according to claim 38, characterized that the
5 front lateral connecting part comprises a first abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; the lateral front connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; wherein the second abutting wall is positioned on an outer side of the first abutting wall, or, the first abutting wall is positioned on an outer side of the
10 second abutting wall; the connecting piece for fixing the corresponding two side connections is a fastener correspondingly disposed to penetrate into the two connecting holes.

40. The sliced assembly type container according to claim 38, characterized that the
15 front lateral connecting part comprises a first abutting wall extending vertically; the lateral front connecting part of the lateral finished module comprises a second abutting wall extending vertically; the connecting piece for fixing the two corresponding side connections has a shape of H, and comprises a first clasp slot for clamping the first abutting wall and a second clasp slot for clamping the second abutting wall.

20
41. A sliced assembly type container, characterized that the sliced assembly type container is consistent with requirements about a general cargo container in ISO and comprises a bottom finished module, two lateral finished modules, two door finished modules, top finished a module, and a front finished module, the two door finished
25 modules are respectively hinged to a door end of lateral bodies of the two lateral

finished modules, wherein:

the bottom finished module comprises: bottom body; two bottom lateral connecting parts, respectively disposed on both sides of the bottom body, to fixedly connect the two lateral finished modules, each of the bottom lateral connecting parts
5 comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a bottom front connecting part, disposed at a front end of the bottom body, to connect the front finished module;

the lateral finished module comprises: a lateral body; lateral bottom connecting
10 parts, disposed on a bottom side of the lateral body, to fixedly connect the bottom finished module, each of the lateral bottom connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; lateral top connecting parts, disposed on a top side of the lateral
15 body, to fixedly connect the top finished module, each of the lateral top connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a lateral front connecting part, disposed at a front end of the lateral body, to connect the front finished module;

the top finished module comprises: a top body; two top lateral connecting parts, respectively disposed on both sides of the top body, to fixedly connect the two lateral finished modules, each of the top lateral connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting
20 element; and a top front connecting part, disposed at a front end of the top body, to
25

connect the front finished module;

the front finished module comprises: a front body; a front bottom connecting part, disposed on a bottom side of the front body, to connect the bottom finished module; two front lateral connecting parts, respectively disposed on both sides of the front body, to connect the two lateral finished modules; and a front top connecting part, disposed on a top side of the front body, to connect the top finished module;

wherein between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are four pairs of the lateral connecting elements each being able to be fixedly connected together via a connecting piece and/or a structural adhesive; between the bottom finished module and the front finished module, between the top finished module and the front finished module, as well as between the two lateral finished modules and the front finished module, there are totally four pairs of side connections each being able to be fixedly connected together via a connecting piece and/or a structural adhesive; between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, at least one of total eight pairs of the corner connection elements is able to be fixedly connected together via welding and the rest of them are able to be fixedly connected together via a connecting piece and/or welding; and sealing process is performed on coupled portions between the modules of the sliced assembly type container.

42. A sliced assembly type container, characterized that the sliced assembly type container is in consistent with requirements about a general cargo container in ISO and comprises a bottom finished module, two lateral finished modules, two door finished modules, top finished a module, and a front finished module, the two door finished

modules are respectively hinged to a door end of lateral bodies of the two lateral finished modules, wherein:

the bottom finished module comprises: bottom body; two bottom lateral connecting parts, respectively disposed on both sides of the bottom body, to fixedly connect the two lateral finished modules, each of the bottom lateral connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a bottom front connecting part, disposed at a front end of the bottom body, to connect the front finished module,

the lateral finished modules comprises: a lateral body; lateral bottom connecting parts, disposed on a bottom side of the lateral body, to fixedly connect the bottom finished module, each of the lateral bottom connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; lateral top connecting parts, disposed on a top side of the lateral body, to fixedly connect the top finished module, each of the lateral top connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a lateral front connecting part, disposed at a front end of the lateral body, to connect the front finished module;

the top finished module comprises: a top body; two top lateral connecting parts, respectively disposed on bosides of the top body, to fixedly connect the two lateral finished modules, each of the top lateral connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting

element; and a top front connecting part, disposed at a front end of the top body, to connect the front finished module;

the front finished module comprises: a front body; a front bottom connecting part, disposed on a bottom side of the front body, to connect the bottom finished module; two
5 front lateral connecting parts, respectively disposed on both sides of the front body, to connect the two lateral finished modules; and a front top connecting part, disposed on a top side of the front body, to connect the top finished module;

wherein between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are four
10 pairs of the lateral connecting elements each being able to be fixedly connected together via a connecting piece and/or a structural adhesive; the front finished module is hinged to one module of the two lateral finished modules, the bottom finished module, and the top finished module, and the front finished module is being able to be fixedly connected to each of the rest modules of the two lateral finished modules, the bottom finished
15 module, and the top finished module via a connecting piece and/or a structural adhesive; between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are totally eight pairs of the corner connection elements each being able to be fixedly connected together via a connecting piece; and sealing process is performed on coupled portions between the
20 modules of the sliced assembly type container.

43. The sliced assembly type container according to claim 42, characterized that one of the front finished module, the two lateral finished modules, the bottom finished module, and the top finished module is able to be a coupled finished module; or, the
25 front finished module and the other finished modules are finished modules separated

from each other.

44. The sliced assembly type container according to any of claims 1-43,
characterized that sealing is able to be performed on coupled portions between the
5 modules of the sliced assembly type container by applying a glue, an adhesive tape or
adhesive sheet.

45. A method for manufacturing the sliced assembly type container of any of
claims 1-43, characterized that the method comprises:

10 a manufacturing process of finished modules for separately manufacturing the
bottom finished module, the two lateral finished modules, the two door finished modules,
the top finished module, and the front finished module; and

an assembling process of the container for assembling the finished modules
together, the assembling process is based on the bottom finished module, and the
15 assembling process comprises sealing coupled portions between the modules by
applying a glue, an adhesive tape or adhesive sheet;

wherein the two door finished modules are able to be coupled to the two lateral
finished modules during the manufacturing process of finished modules in advance, or
assembled with the two lateral finished modules during the assembling process of the
20 container.

46. The method for manufacturing the sliced assembly type container according to
claim 45, characterized that both manufacturing process of finished modules and the
assembling process of the container are able to be completed in amanufacturing site site.

47. The method for manufacturing the sliced assembly type container according to claim 45, characterized that the manufacturing process of finished modules is able to be completed at manufacturing site, and the assembling process of the container is able to be completed at delivery site.

5

48. The method for manufacturing the sliced assembly type container according to claim 45, characterized that it further comprises, between the manufacturing process of finished modules and the assembling process of the container, stacking the manufactured finished modules.

10

49. A method for stacking and transporting the sliced assembly type container of any of 1-43, characterized that the method comprises the following steps: arranging the bottom finished module at bottom; respectively stacking the front finished module, the two lateral finished modules, and the two door finished modules on the bottom finished module; stacking the top finished module at the top, and packing the finished modules together to form a stacking and transporting basic unit.

15

50. The method for stacking and transporting the sliced assembly type container according to claim 49, characterized that the method further comprises: stacking a plurality of the transporting basic units together to form a stacking and transporting unit.

20

51. A bottom finished module for a sliced assembly type container, characterized that the sliced assembly type container is in consistent with requirements about a common cargo container in ISO; the bottom finished module comprises: a bottom body; two bottom lateral connecting parts, respectively disposed on both sides of the bottom body, to fixedly connect the two lateral finished modules, each of the bottom lateral

25

connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a bottom front connecting part, disposed at a front end of the bottom body, to connect the front finished module;

5 wherein the bottom body comprises two sets of door end bottom corner parts, bottom longitudinal beams and front end bottom corner parts on both sides thereof, a front end bottom beam connected between the two front end bottom corner parts, a doorsill connected between the two door end bottom corner parts, bottom crossbeams each connected between two of the bottom longitudinal beams, and a floor; the first corner

10 connecting element is disposed on a top of the door end bottom corner parts, the second corner connecting element is disposed on a top of the front end bottom corner part, the lateral connecting element is disposed on a top of the bottom longitudinal beam; the lateral connecting element of the bottom lateral connecting part is disposed on the front end bottom beam of the bottom body.

15

52. The bottom finished module according claim 51, characterized that the first corner connecting element comprises a plug-in structure including a vertically extending protrusion or receiving cavity.

20

53. The bottom finished module according claim 52, characterized that a structure of the first corner connecting element is selected from any one of the plug-in structures below:

a first plug-in structure: the first corner connecting element comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion and

25 surrounding the connecting hole mounting hole;

a second plug-in structure: the first corner connecting element comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion;

a third plug-in structure: the first corner connecting element comprises upwardly protruding protrusion, and two connecting holes and a mounting hole positioned on a side of each of the connecting holes and communicating with the connecting holes are disposed in the protrusion;

a fourth plug-in structure: the first corner connecting element comprises a connecting block having a downwardly depressed receiving cavity, the connecting block has a connecting hole disposed therein to traverse the receiving cavity.

54. The bottom finished module according claim 51, characterized that the first corner connecting element comprises an overlapped structure.

55. The bottom finished module according claim 54, characterized that the structure of the first corner connecting element is selected from any of the overlapped structures below:

a first overlapped structure: the first corner connecting element has a horizontal overlapping surface, and a connecting hole traversing the overlapping surface is disposed therein;

a second overlapped structure: the first corner connecting element has a vertical overlapping surface, and a connecting hole traversing the overlapping surface is disposed therein;

a third overlapped structure: the first corner connecting element has a vertical overlapping surface with a depressed clasp slot or a protruded clasp block disposed in the overlapping surface, and a connecting hole traversing the overlapping surface is

disposed in a peripheral of the clasp slot/clasp block.

56. The bottom finished module according claim 51, characterized that the second corner connecting element comprises an overlapped structure.

5

57. The bottom finished module according claim 56, characterized that the second corner connecting element has a structure selected from any of the overlapped structures below:

10 a first overlapped structure: the second corner connecting element has a horizontal overlapping surface, and has a connecting hole disposed therein to traverse the overlapping surface;

a second overlapped structure: the second corner connecting element has a vertical overlapping surface, and has a connecting hole disposed therein to traverse the overlapping surface;

15 a third overlapped structure: the second corner connecting element has a vertical overlapping surface with a depressed clasp slot or a protruded clasp block disposed in the overlapping surface, and a connecting hole traversing the overlapping surface is disposed in a peripheral of the clasp slot/clasp block;

20 a fourth overlapped structure: the second corner connecting element comprises a first part having a vertical overlapping surface and a second part having a horizontal overlapping surface, a connecting hole traversing the vertical overlapping surface is disposed in the first part, and a connecting hole traversing the horizontal overlapping surface is disposed in the second part.

25 58. The bottom finished module according claim 57, characterized that in any of

the overlapped structures, the second corner connecting element has a shape of L.

59. The bottom finished module according claim 51, characterized that the second corner connecting element comprises a plug-in structure including the vertically
5 extending protrusion or the receiving cavity.

60. The bottom finished module according claim 59, characterized that a connection structure of the second corner connecting element is selected from any one of the plug-in structures below:

10 a first plug-in structure: the second corner connecting element comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion;

a second plug-in structure: the second corner connecting element comprises a connecting block having a downwardly depressed receiving cavity, a connecting hole traversing the receiving cavity is disposed in the connecting block.

15 61. The bottom finished module according claim 51, characterized that the first corner connecting element comprises an upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the second corner connecting element has a horizontal overlapping surface or a vertically overlapping surface, and a connecting
20 hole is disposed to pass through the overlapping surface.

62. The bottom finished module according claim 51, characterized that the lateral connecting element of the bottom lateral connecting part comprises a horizontally extending abutting wall, and a connecting hole is disposed in the abutting wall; or, the
25 bottom lateral connecting part comprises a vertically extending abutting wall, and a

connecting hole is disposed in the abutting wall.

63. A top finished module for a sliced assembly type container, characterized that the sliced assembly type container is in consistent with requirements about a general cargo container in ISO; the top finished module comprises: a top body; two top lateral
5 connecting parts, respectively disposed on bosides of the top body, to fixedly connect the two lateral finished modules, each of the top lateral connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral
10 connecting element; and a top front connecting part, disposed at a front end of the top body, to connect the front finished module; the top body comprises two sets of door end top corner parts, top longitudinal beams, and front end top corner parts on both sides, a front end top beam connected between the two front end top corner parts, a lintel connected between the two door end top corner parts, and a top plate; the first corner
15 connecting element is disposed on a bottom of the door end top corner part of the top body, the second corner connecting element is disposed on a bottom of the front end top corner part, the lateral connecting element is disposed on a bottom of the top longitudinal beam; the top front connecting part is disposed on the front end top beam of the top body.

20 64. The top finished module according to claim 63, characterized that the first corner connecting element comprises a plug-in structure including a vertically extending protrusion or a receiving cavity.

25 65. The top finished module according to claim 64, characterized that the structure

of the first corner connecting element is selected from any one of the plug-in structures below:

a first plug-in structure: the first corner connecting element comprises a downwardly protruding protrusion, and a connecting hole and mounting holes around the connection hole are disposed in the protrusion;

a second plug-in structure: the first corner connecting element comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion;

a third plug-in structure: the first corner connecting element comprises a downwardly protruding protrusion, and two connecting holes and a mounting hole positioned on a side of each of the connecting holes and communicating with the connecting holes are disposed in the protrusion;

a fourth plug-in structure: the first corner connecting element comprises a connecting block having a receiving cavity depressed towards the top, and a connecting hole traversing the receiving cavity is disposed in the connecting block.

66. The top finished module according to claim 63, characterized that the first corner connecting element comprises an overlapped structure.

67. The top finished module according to claim 66, characterized that the structure of the first corner connecting element is selected from any of the overlapped structures below:

a first overlapped structure: the first corner connecting element has a horizontally overlapping surface, and a connecting hole traversing the overlapping surface is disposed therein;

a second overlapped structure: the first corner connecting element has a vertically

overlapping surface, and a connecting hole traversing the overlapping surface is disposed therein;

a third overlapped structure: the first corner connecting element has a vertically overlapping surface with a depressed clasp slot or a protruded clasp block disposed in the overlapping surface, and a connecting hole traversing the overlapping surface is disposed in a peripheral of the clasp slot/clasp block.

68. The top finished module according to claim 63, characterized that the second corner connecting element comprises an overlapped structure.

69. The top finished module according to claim 68, characterized that the second corner connecting element has a structure selected from any of the overlapped structures below:

a first overlapped structure: the second corner connecting element has a horizontal overlapping surface, and has a connecting hole disposed therein to traverse the overlapping surface;

a second overlapped structure: the second corner connecting element has a vertical overlapping surface, and has a connecting hole disposed therein to traverse the overlapping surface;

a third overlapped structure: the second corner connecting element has a vertical overlapping surface with a depressed clasp slot or a protruded clasp block disposed in the overlapping surface, and a connecting hole traversing the overlapping surface is disposed in a peripheral of the clasp slot/clasp block;

a fourth overlapped structure: the second corner connecting element comprises a first part having a vertically overlapping surface and a second part having a horizontally

overlapping surface, a connecting hole traversing the vertically overlapping surface is disposed in the first part, and a connecting hole traversing the horizontally overlapping surface is disposed in the second part.

5 70. The top finished module according to claim 69, characterized that in any of the overlapped structures, the second corner connecting element has a shape of L.

71. The top finished module according to claim 63, characterized that the second corner connecting element comprises a plug-in structure including a vertically extending
10 protrusion or a receiving cavity.

72. The top finished module according to claim 63, characterized that a connection structure of the second corner connecting element is selected from any one of the plug-in structures below:

15 a first plug-in structure: the second corner connecting element comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion;

 a second plug-in structure: the second corner connecting element comprises a connecting block having a receiving cavity depressed towards the top, a connecting hole traversing the receiving cavity is disposed in the connecting block.

20

73. The top finished module according to claim 63, characterized that the first corner connecting element comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the second corner connecting element has a horizontally overlapping surface or a vertically overlapping surface, and a connecting

25 hole traversing the overlapping surface is disposed therein.

74. The top finished module according to claim 63, characterized that the lateral connecting element of the top lateral connecting part comprises a horizontally extending abutting wall, and a connecting hole is disposed in the abutting wall.

5

75. The top finished module according to claim 74, characterized that the abutting wall may have an outer side edge protruding downwardly at an outer side thereof; or, the abutting wall may have an outer side edge protruding downwardly at an outer side thereof, the abutting wall may have a protruding downward inner side edge at an inner side thereof.

10

76. The top finished module according to claim 74, characterized that the top finished module further comprises a reinforcing plate welded on the top longitudinal beams, and the reinforcing plate has a top abutting against the top longitudinal beams and a bottom abutting against the abutting wall.

15

77. The top finished module according to claim 63, characterized that the lateral connecting element of the top lateral connecting parts comprises a vertically extending abutting wall, and a connecting hole is disposed in the abutting wall.

20

78. The top finished module according to claim 63, characterized that the top front connecting part comprises a vertically extending abutting wall, and a connecting hole is disposed in the abutting wall.

25

79. A lateral finished module for a sliced assembly type container, characterized

that the sliced assembly type container is in consistent with requirements about a general cargo container in ISO; the lateral finished module comprises: a lateral body; lateral bottom connecting parts, disposed on a bottom side of the lateral body, to fixedly connect the bottom finished module, each of the lateral bottom connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; lateral top connecting parts, disposed on a top side of the lateral body, to fixedly connect the top finished module, each of the lateral top connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a lateral front connecting part, disposed at a front end of the lateral body, to connect the front finished module; wherein the first corner connecting element disposed on the bottom of the door end corner pillar, the second corner connecting element is disposed on a bottom of the front end corner pillar, the lateral connecting element is disposed on a bottom of the lateral wall; the lateral front connecting part is disposed on the front end corner pillar of the lateral body.

80. The lateral finished module according to claim 79, characterized that the first corner connecting element of the lateral bottom connecting part comprises a plug-in structure including a vertically extending protrusion or a receiving cavity.

81. The lateral finished module according to claim 80, characterized that the structure of the first corner connecting element is selected from any one of the plug-in structures below:

a first plug-in structure: the first corner connecting element comprises a receiving cavity formed at a bottom of the door end corner pillar, and a connecting hole and a mounting hole surrounding the connecting hole are horizontally disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity;

5 a second plug-in structure: the first corner connecting element comprises a receiving cavity formed at a bottom of the door end corner pillar, and a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity;

10 a third plug-in structure: the first corner connecting element comprises a receiving cavity formed at a bottom of the door end corner pillar, and a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the door end corner pillar comprises a first corner pillar part, a second corner pillar part and a reinforcing part, which all are welded together, the reinforcing part is correspondingly welded in a bottom of the first corner pillar part/the second corner pillar part and located between the first corner pillar part and the second corner pillar part, the connecting hole in the bottom of the door end corner pillar comprises holes formed in the first corner pillar part, the reinforcing part and the second corner pillar part, respectively;

15 a fourth plug-in structure: the first corner connecting element comprises a receiving cavity formed at a bottom of the door end corner pillar, and two connecting holes and a mounting hole positioned on a side of each of the connecting holes and communicating with the connecting holes are horizontally disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity;

20 a fifth plug-in structure: the first corner connecting element comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion

25

to horizontally pass therethrough.

82. The lateral finished module according to claim 79, characterized that the first corner connecting element of the lateral bottom connecting part comprises an overlapped structure.

83. The lateral finished module according to claim 82, characterized that the structure of the first corner connecting element is selected from any of the overlapped structures below:

a first overlapped structure: the first corner connecting element has a horizontal overlapping surface, and a connecting hole is disposed to traverse the overlapping surface;

a second overlapped structure: the first corner connecting element has a vertically overlapping surface, and a connecting hole is disposed to traverse the overlapping surface;

a third overlapped structure: the first corner connecting element has a vertically overlapping surface, the overlapping surface has a clasp slot or a clasp block depressed therein, and a connecting hole is disposed in a peripheral of the clasp slot/clasp block to traverse the overlapping surface.

84. The lateral finished module according to claim 79, characterized that the second corner connecting element of the lateral bottom connecting part comprises an overlapped structure.

85. The lateral finished module according to claim 84, characterized that the second

corner connecting element has a structure selected from any of the overlapped structures below:

a first overlapped structure: the second corner connecting element has a horizontally overlapping surface, and a connecting hole traversing the overlapping surface is disposed therein;

a second overlapped structure: the second corner connecting element has a vertically overlapping surface, and a connecting hole traversing the overlapping surface is disposed therein;

a third overlapped structure: the second corner connecting element has a vertically overlapping surface with a clasp slot or a protruding clasp block depressed in the overlapping surface, and a connecting hole traversing the overlapping surface is disposed in a peripheral of the clasp slot/clasp block;

a fourth overlapped structure: the second corner connecting element comprises a first part having a vertically overlapping surface and a second part having a horizontally overlapping surface, a connecting hole is disposed in the first part to traverse the vertical overlapping surface, and a connecting hole disposed in the second part to traverse the horizontally overlapping surface.

86. The lateral finished module according to claim 85, characterized that in any of the overlapped structures, the second corner connecting element has a shape of L.

87. The lateral finished module according to claim 79, characterized that the second corner connecting element of the lateral bottom connecting part comprises a plug-in structure, including a vertically extending protrusion or a receiving cavity.

88. The lateral finished module according to claim 87, characterized that the second corner connecting element has a structure selected from any one of the plug-in structures below:

5 a first plug-in structure: the second corner connecting element comprises a receiving cavity formed in a bottom of the front end corner pillar, a connecting hole is disposed in the protrusion in the bottom of the front end corner pillar at a position corresponding to the receiving cavity;

10 a second plug-in structure: the second corner connecting element comprises a receiving cavity formed in a bottom of the front end corner pillar, a connecting hole is disposed in the protrusion in the bottom of the front end corner pillar at a position corresponding to the receiving cavity; the front end corner pillar comprises a first corner pillar part, a second corner pillar part and a reinforcing part, which all are welded together, the reinforcing part is correspondingly welded in a bottom of the first corner pillar part/the second corner pillar part and located between the first corner pillar part and the second corner pillar part, the connecting hole in the bottom of the front end corner pillar comprises holes formed in the first corner pillar part, the reinforcing part and the second corner pillar part, respectively;

15 a third plug-in structure: the second corner connecting element comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion.

20 89. The lateral finished module according to claim 79, characterized that the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at a bottom of the door end corner pillar, a connecting hole is disposed in the the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the second corner connecting element of the lateral bottom connecting part has a

25

horizontally overlapping surface or a vertically overlapping surface, and a connecting hole is disposed to pass through the overlapping surface.

90. The lateral finished module according to claim 79, characterized that the structure of the first corner connecting element of the lateral top connecting part is as same as the structure of the first corner connecting element of the lateral bottom connecting part; the structure of the second corner connecting element of the lateral top connecting part is as same as the structure of the second corner connecting element of the lateral bottom connecting part.

91. The lateral finished module according to claim 79, characterized that the structure of the second corner connecting element of the lateral top connecting part is as same as the structure of the first corner connecting element of the lateral bottom connecting part.

92. The lateral finished module according to claim 79, characterized that the lateral connecting element of the lateral bottom connecting part comprises a horizontally extending abutting wall, and a connecting hole is disposed in the abutting wall.

93. The lateral finished module according to claim 92, characterized that the abutting wall may have an outer side edge protruding downwardly at an outer side thereof; or the abutting wall may have an outer side edge protruding downwardly at an outer side thereof, the abutting wall may have an inner side edge protruding downwardly at an inner side thereof.

94. The lateral finished module according to claim 79, characterized that the lateral connecting element of the lateral top connecting part comprises a horizontally extending abutting wall, and a connecting hole is disposed in the abutting wall.

5 95. The lateral finished module according to claim 94, characterized that the abutting wall may have a inner side edge protruding upwardly at an inner side thereof.

96. The lateral finished module according to claim 79, characterized that the lateral front connecting part comprises a vertically extending abutting wall with a connecting
10 hole disposed therein.

97. The lateral finished module according to any of claim 79-96, characterized that the lateral finished module further comprises door finished modules hinged to a door end of the lateral body.

15 98. A front finished module for a sliced assembly type container, characterized that the sliced assembly type container is in consistent with requirements about a general cargo container in ISO; the front finished module comprises: a front body; a front bottom connecting part, disposed on a bottom side of the front body, to connect the
20 bottom finished module; two front lateral connecting parts, respectively disposed on both sides of the front body, to connect the two lateral finished modules; and a front top connecting part, disposed on a top side of the front body, to connect the top finished module.

25 99. The front finished module according to claim 98, characterized that the front

bottom connecting part comprises a horizontally extending abutting wall, and a connecting hole is disposed in the abutting wall.

100. The front finished module according to claim 99, characterized that the
5 abutting wall may have an outer side edge protruding downwardly on an outer side thereof; and/or, the abutting wall may have an inner side edge protruding downwardly at an inner side thereof.

101. The front finished module according to claim 98, characterized that the front
10 top connecting part comprises a vertically extending abutting wall, and a connecting hole is disposed in the abutting wall.

102. The front finished module according to claim 98, characterized that the front
lateral connecting part comprises a vertically extending abutting wall, and a connecting
15 hole may be disposed in the vertically extending abutting wall.

CLAIMS:

1. A sliced assembly type container, characterized in that the sliced assembly type container is in consistent with ISO requirements about a general cargo container, and
5 comprises a bottom finished module, two lateral finished modules, two door finished modules respectively hinged to door ends of lateral bodies of the two lateral finished modules, a top finished module, and a front finished module, and

the bottom finished module comprises: a bottom body, comprising two sets of door end bottom corner fittings, bottom longitudinal beams and front end bottom corner
10 fittings, respectively disposed on both sides thereof; two bottom lateral connecting parts, respectively disposed on both sides of the bottom body, to fixedly connect the two lateral finished modules, each of the bottom lateral connecting parts comprises a lateral connecting element, a first corner connecting element at the door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral
15 connecting element; and a bottom front connecting part, disposed at a front end of the bottom body, to connect the front finished module;

the lateral finished module comprises: a lateral body, comprising a lateral wall, a front end corner pillar connected to a front end of the lateral wall, and a door end corner pillar connected to a door end of the lateral wall; lateral bottom connecting parts,
20 disposed on a bottom side of the lateral body, to fixedly connect the bottom finished module, each of the lateral bottom connecting parts comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; lateral top connecting parts, disposed on a top side of the lateral body, to
25 fixedly connect the top finished module, each of the lateral top connecting parts

comprises a lateral connecting element, a first corner connecting element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a lateral front connecting part, disposed at a front end of the lateral body, to connect the front finished module;

5 the top finished module comprises: a top body, comprising two sets of door end top corner fittings, top longitudinal beams, and front end top corner fittings positioned on both sides thereof; two top lateral connecting parts, respectively disposed on both sides of the top body, to fixedly connect the two lateral finished modules, each of the top lateral connecting parts comprises a lateral connecting element, a first corner connecting
10 element at a door end of the lateral connecting element, and a second corner connecting element at a front end of the lateral connecting element; and a top front connecting part, disposed at the front end of the top body, to connect the front finished module;

 the front finished module comprises: a front body; a front bottom connecting part, disposed on a bottom side of the front body, to connect the bottom finished module; two
15 front lateral connecting parts, respectively disposed on both sides of the front body, to connect the two lateral finished modules; and a front top connecting part, disposed on a top side of the front body, to connect the top finished module;

 wherein between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are
20 totally four pairs of the lateral connecting elements being able to be fixedly connected together via a connecting piece and/or a structural adhesive, and the connecting piece has locking effect to be able to produce force in a vertical direction and in a horizontal direction.

 characterized in that

25 2. The sliced assembly type container according to claim 1, characterized in that

the door finished module and the lateral finished module are one integrated finished module; or, the door finished modules and the lateral finished module are two finished modules separated from each other.

5 3. The sliced assembly type container according to claim 1, characterized in that the bottom body further comprises a front end bottom beam connected between the two front end bottom corner fittings, a doorsill connected between of the two door end bottom corner fittings, bottom crossbeams each connected between the two bottom longitudinal beams, and a floor; the first corner connecting element of the bottom lateral
10 connecting parts is disposed on a top of the door end bottom corner par, the second corner connecting element is disposed on a top of the front end bottom corner fitting, and the lateral connecting elements are disposed on a top of the bottom longitudinal beam; the first corner connecting element of the lateral bottom connecting part is disposed on a bottom of the door end corner pillar, the second corner connecting
15 element is disposed on a bottom of the front end corner pillar, the lateral connecting elements are disposed on a bottom of the lateral wall; and wherein the corresponding lateral connecting elements are able to be fixedly connected together via a connecting piece.

20 4. The sliced assembly type container according to claim3, characterized in that one of the two first corner connecting element comprises a vertically extending protrusion; the other of the two first corner connecting elements comprises a receiving cavity correspondingly for insertion of the protrusion; and the two first corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation
25 with the protrusion and the receiving cavity.

5. The sliced assembly type container according to claim 4, characterized in that a connection structure of the two first corner connecting elements is selected from any one of the plug-in structures below:

5 a first plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a upwardly protruding protrusion, and a first connecting hole and first mounting holes around the first connecting hole are horizontally disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at a bottom of the door end corner pillar, and a
10 second connecting hole and second mounting holes surrounding the second connecting hole are horizontally disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece comprises a connecting pin and a fastener, the connecting pin is disposed to penetrate through the first and second connecting holes and has a locking effect and has third mounting holes disposed therein,
15 and the fastener is disposed to penetrate into the first to third mounting holes;

 a second plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end
20 corner pillar, and a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting pieces are disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

 a third plug-in structure: the first corner connecting element of the bottom lateral
25 connecting part comprises a upwardly protruding protrusion, and a connecting hole is

disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, and a connecting hole is disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the door end corner pillar
5 comprises a first corner pillar part, a second corner pillar part and a reinforcing part, which all are welded together, the reinforcing part is correspondingly welded in the bottom of the first corner pillar part/the second corner pillar part and located between the first corner pillar part and the second corner pillar part, the connecting hole in the bottom of the door end corner pillar comprises holes formed in the first corner pillar part,
10 the reinforcing part and the second corner pillar part, respectively; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having a locking effect may be selected;

a fourth plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises an upwardly protruding protrusion, and two connecting holes
15 and a mounting hole positioned on a side of each of the connecting holes and communicating with the connecting holes are disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, and two connecting holes and a mounting hole positioned on a side of each of the connecting holes and communicating
20 with the connecting holes are horizontally disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece comprises two connecting pins and a fastener, the connecting pins are correspondingly disposed to penetrate into the connecting holes and have locking effect, and the fastener is correspondingly disposed to penetrate into the mounting holes;

25 a fifth plug-in structure: the first corner connecting element of the bottom lateral

connecting parts comprises a upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the door end corner pillar, a connecting hole is disposed in the bottom of the door end corner pillar at
5 a position corresponding to the receiving cavity; the connecting piece comprises a bolt having a locking effect and a tail cone and being correspondingly disposed to penetrate into the connecting holes.

a sixth plug-in structure: the first corner connecting element of the bottom lateral connecting part comprises a connecting block having a downwardly depressed receiving
10 cavity, the connecting block has a horizontally traversing connecting hole disposed therein; the first corner connecting element of the lateral bottom connecting part comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion to horizontally pass therethrough; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may
15 be selected;

a seventh plug-in structure: the first corner connecting element of the bottom lateral connecting parts comprises a vertically extending protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into
20 the receiving cavity;

an eighth plug-in structure: the first corner connecting element of the lateral bottom connecting part comprises a vertically extending protrusion; the first corner connecting element of the bottom lateral connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into
25 the receiving cavity.

6. The sliced assembly type container according to claim 5, characterized in that the connecting piece having locking effect is a rivet.

5 7. The sliced assembly type container according to claim 3, characterized in that the first corner connecting element of the bottom lateral connecting parts comprises a first overlapping piece; the first corner connecting element of the lateral bottom connecting part comprises a second overlapping piece, and the two first corner connecting elements are able to be fixedly connected together by a connecting piece in
10 cooperation with the two overlapping pieces.

8. The sliced assembly type container according to claim 7, characterized in that a connection structure of the two first corner connecting element is selected from any of the overlapped structures below:

15 a first overlapped structure: the first overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the second overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the connecting piece is selected to be a fastener correspondingly to penetrate into the connecting holes;

20 a second overlapped structure: the first overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

25 a third overlapped structure: the first overlapping piece has a vertically overlapping

surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; wherein one of the two overlapping pieces has an overlapping surface with a clasp slot depressed therein, and the other of the two overlapping pieces has an overlapping surface with a clasp block protruded therein, the clasp block is in cooperation with the clasp slot; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected.

9. The sliced assembly type container according to claim 8, characterized in that the connecting piece having locking effect is a rivet.

10. The sliced assembly type container according to claim 3, characterized in that the second corner connecting element of the bottom lateral connecting part comprises a first overlapping piece; the second corner connecting element of the lateral bottom connecting part comprises a second overlapping piece, the two second corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation with the two overlapping pieces.

11. The sliced assembly type container according to claim 10, characterized in that a connection structure of the two second corner connecting element is selected from any of the overlapped structures below:

a first overlapped structure: the first overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the second overlapping piece has a horizontally overlapping surface with a connecting hole disposed therein; the connecting piece is chosen to be a fastener correspondingly to penetrate into the

connecting holes;

a second overlapped structure: the first overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a third overlapped structure: the first overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; the second overlapping piece has a vertically overlapping surface with a connecting hole disposed therein; wherein one of the two overlapping pieces has an overlapping surface with a clasp slot depressed therein, and the other of the two overlapping pieces has an overlapping surface with a clasp block protruded therein, the clasp block is in cooperation with the clasp slot; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a fourth overlapped structure: the first overlapping piece comprises a first part having a vertically overlapping surface with a connecting hole disposed therein, and a second part having a horizontally overlapping surface with a connecting hole disposed therein; the second overlapping piece comprises a first part having a vertically overlapping surface with a connecting hole disposed therein, and a second part having a horizontally overlapping surface with a connecting hole disposed therein; the connecting pieces are disposed to horizontally penetrate into the connecting holes and disposed to vertically penetrate into the connecting holes, wherein the connecting piece disposed to horizontally penetrate into the connecting holes is selected to be a connecting piece having locking effect, and the connecting piece disposed to vertically penetrate into the connecting holes is a fastener.

12. The sliced assembly type container according to claim 11, characterized in that in any of the overlapped structures, the first overlapping piece has a shape of L; and the second overlapping piece has a shape of L.

5

13. The sliced assembly type container according to claim 11, characterized in that the connecting piece having locking effect is a rivet.

14. The sliced assembly type container according to claim 3, characterized in that
10 one of the two second corner connecting elements comprises a vertically extending protrusion; the other of the two second corner connecting elements comprises a receiving cavity for insertion of the protrusion; the two second corner connecting elements are able to be fixedly connected together by a connecting piece in cooperation with the two overlapping pieces.

15

15. The sliced assembly type container according to claim 14, characterized in that a connection structure of the two second corner connecting element is selected from any one of the plug-in structures below:

a first plug-in structure: the second corner connecting element of the bottom lateral
20 connecting part comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the second corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of front end corner pillar, the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

25 a second plug-in structure: the second corner connecting element of the bottom

lateral connecting part comprises upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the second corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at the bottom of the front end corner pillar, a connecting hole is disposed in the protrusion in the bottom of the front end corner pillar at a position corresponding to the receiving cavity; the front end corner pillar comprises a first corner pillar part, a second corner pillar part and a reinforcing part, which all are welded together, the reinforcing part is correspondingly welded in the bottom of the first corner pillar part/the second corner pillar part and located between the first corner pillar part and the second corner pillar part, the connecting hole in the bottom of the front end corner pillar comprises holes formed in the first corner pillar part, the reinforcing part and the second corner pillar part, respectively; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected;

a third plug-in structure: the second corner connecting element of the bottom lateral connecting part comprises a connecting block having a downwardly depressed receiving cavity, the connecting block has a connecting hole disposed therein; the second corner connecting element of the lateral bottom connecting part comprises a downwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the connecting piece is disposed to penetrate into the connecting holes, and the connecting piece having locking effect may be selected.

a fourth plug-in structure: the second corner connecting element of the bottom lateral connecting part comprises a vertically extending protrusion; the second corner connecting element of the lateral bottom connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler injected into the receiving cavity;

a fifth plug-in structure: the second corner connecting element of the lateral bottom connecting part comprises a vertically extending protrusion; the second corner connecting element of the bottom lateral connecting part comprises a receiving cavity for insertion of the protrusion; the connecting piece is formed by solidification of a filler
5 injected into the receiving cavity.

16. The sliced assembly type container according to claim 15, characterized in that the connecting piece having locking effect is a rivet.

10 17. The sliced assembly type container according to claim 3, characterized in that the first corner connecting element of the bottom lateral connecting parts comprises a upwardly protruding protrusion, and a connecting hole is disposed in the protrusion; the first corner connecting element of the lateral bottom connecting part comprises a receiving cavity formed at a bottom of the door end corner pillar, a connecting hole is
15 disposed in the bottom of the door end corner pillar at a position corresponding to the receiving cavity; the connecting piece to fixedly connecting the two first corner connecting elements is disposed correspondingly penetrate into the connecting holes, and the connecting piece having locking effect may be selected; the second corner connecting element of the bottom lateral connecting part comprises a first overlapping
20 piece, the second corner connecting element of the lateral bottom connecting part comprises a second overlapping piece, the connecting piece to fixedly connecting the two second corner connecting elements is disposed correspondingly penetrate into the connecting holes, and if the two overlapping pieces are horizontally overlapped, the connecting piece is a fastener, if the two overlapping pieces are vertically overlapped,
25 then the connecting piece having locking effect may be selected.

18. The sliced assembly type container according to claim 17, characterized in that the connecting piece having locking effect is a rivet.

5 19. The sliced assembly type container according to claim 3, characterized in that the lateral connecting element of the bottom lateral connecting part comprises a first abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall;

the lateral connecting element of the lateral bottom connecting part comprises a
10 second abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall;

the connecting piece to fixedly connect the corresponding two lateral connecting elements is a fastener disposed correspondingly to penetrate into the two connecting holes.

15 20. The sliced assembly type container according to claim 19, characterized in that the second abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is positioned corresponding to an outer side of the first abutting wall;

20 or, the second abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is positioned corresponding to an outer side of the first abutting wall, further, the second abutting wall has an inner side edge protruding downwardly from an inner side thereof, and the inner side edge is positioned corresponding to an inner side of the first abutting wall.

21. The sliced assembly type container according to claim 3, characterized in that the lateral connecting element of the bottom lateral connecting part comprises a first abutting wall extending vertically, and a connecting hole is disposed in the abutting wall;

5 the lateral connecting element of the lateral bottom connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall;

the second abutting wall is correspondingly positioned on an outer side of the first abutting wall, or, the first abutting wall is correspondingly positioned on an outer side of
10 the second abutting wall;

the connecting piece to fixedly connect the corresponding two lateral connecting elements is a fastener disposed correspondingly to penetrate into the two connecting holes.

15 22. The sliced assembly type container according to claim 1, characterized in that the bottom body further comprises a front end bottom beam connected between the two front end bottom corner fittings, a doorsill connected between the two door end bottom corner fittings, a crossbeam connected between the two bottom longitudinal beams, and a floor; the bottom front connecting part is disposed on the front end bottom beam of the
20 bottom body; the front bottom connecting part and the bottom front connecting part are fixedly connected together via a connecting piece.

23. The sliced assembly type container according to claim 22, characterized in that the front bottom connecting part comprises a first abutting wall extending horizontally,
25 and a connecting hole is disposed in the abutting wall; the bottom front connecting part

comprises a second abutting wall extending horizontally, and a connecting hole is disposed in the abutting wall; the connecting piece for fixing the corresponding two side connections is a fastener correspondingly disposed to penetrate into the two connecting holes.

5

24. The sliced assembly type container according to claim 23, characterized in that the first abutting wall has an outer side edge protruding downwardly from an outer side thereof, and the outer side edge is correspondingly positioned on an outer side of the second abutting wall; and/or, the first abutting wall has an inner side edge protruding
10 downwardly from an inner side thereof, and the inner side edge is correspondingly positioned on an inner side of the second abutting wall.

25. The sliced assembly type container according to claim 1, characterized in that the top body further comprises a front end top beam connected between two of the front
15 end top corner fittings, a lintel connected between the two door end top corner fittings, and a top plate; the top front connecting part is disposed on the front end top beam of the top body; and the front top connecting part and the top front connecting part are fixedly connected together via a connecting piece.

20 26. The sliced assembly type container according to claim 25, characterized in that the front top connecting part comprises a first abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; the top front connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; wherein the second abutting wall is positioned on an outer side of the first
25 abutting wall, or, the first abutting wall is positioned on an outer side of the second

abutting wall; the connecting piece for fixing the corresponding two side connections is a fastener correspondingly disposed to penetrate into the two connecting holes.

27. The sliced assembly type container according to claim 1, characterized in that the lateral front connecting part of the lateral finished module is disposed on the front end corner pillar of the lateral body; the front lateral connecting part and the lateral front connecting part are fixedly connected together via a connecting piece.

28. The sliced assembly type container according to claim 27, characterized in that the front lateral connecting part comprises a first abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; the lateral front connecting part comprises a second abutting wall extending vertically, and a connecting hole is disposed in the abutting wall; wherein the second abutting wall is positioned on an outer side of the first abutting wall, or, the first abutting wall is positioned on an outer side of the second abutting wall; the connecting piece for fixing the corresponding two side connections is a fastener correspondingly disposed to penetrate into the two connecting holes.

29. The sliced assembly type container according to claim 27, characterized in that the front lateral connecting part comprises a first abutting wall extending vertically; the lateral front connecting part of the lateral finished module comprises a second abutting wall extending vertically; the connecting piece for fixing the two corresponding side connections has a shape of H, and comprises a first clasp slot for clamping the first abutting wall and a second clasp slot for clamping the second abutting wall.

30. The sliced assembly type container according to claim 1, characterized in that between the bottom finished module and the front finished module, between the top finished module and the front finished module, as well as between the two lateral finished modules and the front finished module, there are totally four pairs of side connections each being able to be fixedly connected together via a connecting piece and/or a structural adhesive, and the connecting piece has locking effect to be able to produce force in a vertical direction and in a horizontal direction;

between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are totally eight pairs of the corner connection elements being able to be fixedly connected together via a connecting piece, and the connecting piece has locking effect to be able to produce force in a vertical direction and in a horizontal direction;

or, between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, at least one of total eight pairs of the corner connection elements is able to be fixedly connected together via welding and the rest of them are able to be fixedly connected together via a connecting piece and/or welding.

31. The sliced assembly type container according to claim 1, characterized in that the front finished module is hinged to one module of the two lateral finished modules, the bottom finished module, and the top finished module, and the front finished module is being able to be fixedly connected to each of the rest modules of the two lateral finished modules, the bottom finished module, and the top finished module via a connecting piece and/or a structural adhesive, and the connecting piece has locking effect to be able to produce force in a vertical direction and in a horizontal direction;

between the bottom finished module and the lateral finished modules as well as between the lateral finished modules and the top finished module, there are totally eight pairs of the corner connection elements each being able to be fixedly connected together via a connecting piece, and the connecting piece has locking effect to be able to produce
5 force in a vertical direction and in a horizontal direction.

32. The sliced assembly type container according to claim 31, characterized in that one of the front finished module, the two lateral finished modules, the bottom finished module, and the top finished module is able to be a coupled finished module; or, the
10 front finished module and the other finished modules are finished modules separated from each other.

33. The sliced assembly type container according to claim 1, characterized in that sealing is able to be performed on coupled portions between the modules of the sliced
15 assembly type container by applying a glue, an adhesive tape or adhesive sheet.

34. A method for manufacturing the sliced assembly type container, characterized in that the method comprises:

a manufacturing process of finished modules for separately manufacturing the
20 bottom finished module, the two lateral finished modules, the two door finished modules, the top finished module, and the front finished module; and

an assembling process of the container for assembling the finished modules together, comprising:

locating the bottom finished module at first;

25 mounting the two lateral finished modules on both sides of the bottom

finished module via the connecting pieces;

mounting the front finished module to the bottom finished module via the connecting pieces;

5 mounting the top finished module to two lateral finished modules via the connecting pieces; and

sealing coupled portions between the modules by applying a glue, an adhesive tape or adhesive sheet;

10 wherein the connecting piece has locking effect to be able to produce force in a vertical direction and in a horizontal direction; the two door finished modules are able to be coupled to the two lateral finished modules during the manufacturing process of finished modules in advance, or assembled with the two lateral finished modules during the assembling process of the container.