

BEARER PROCESSING METHOD AND SYSTEM, AND RELATED APPARATUS

TECHNICAL FIELD

The present invention relates to the field of communications technologies, and in
5 particular, to a bearer processing method and system, and a related apparatus.

BACKGROUND

In an evolved packet core (Evolved Packet Core, EPC), a general packet radio
service (General Packet Radio Service, GPRS) tunneling protocol (GPRS tunneling
protocol, GTP) bearer provides an end-to-end data service for a user.

10 In an end-to-end data service implementation process, service data flows
(Service Data Flow, SDF) with different quality of service (Quality of Service, QoS)
attributes are aggregated in different bearers. Based on QoS attributes of the different
bearers, a network provides differentiated services for the user.

Currently, in a bearer processing process, if QoS of a bearer cannot meet a
15 service requirement, user equipment (User Equipment, UE) sends requested QoS
information to a packet data network gateway (Packet Data Network Gateway,
P-GW). The QoS information may be information such as a QoS class identifier (QoS
Class Identifier, QCI) or an allocation/retention priority (Allocation and Retention
Priority, ARP). Based on the QoS information provided by the UE, the P-GW
20 manages the bearer, for example, creating a bearer, updating the bearer, or deleting the
bearer, so that QoS of the bearer meets the service requirement.

In the foregoing bearer processing process, the UE initiates a resource request
procedure. That is, the UE needs to have a capability of identifying a service data
flow. If the UE cannot identify the service flow, the bearer processing process cannot
25 be implemented.

SUMMARY

Embodiments of the present invention provide a bearer processing method and system, and a related apparatus, so as to resolve a problem that bearer processing is limited to a UE capability of identifying a service flow.

5 According to a first aspect, the present invention provides a bearer processing system, including a gateway user plane GW-U and a gateway control plane GW-C, where

the GW-U is configured to: receive a data packet and match the data packet with a rule, and send bearer processing indication information to the GW-C if a rule
10 matching result of the data packet meets a trigger condition for bearer processing, where the bearer processing indication information is used to trigger the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to the data packet; and

the GW-C is configured to: receive the bearer processing indication information
15 sent by the GW-U, determine, according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet, and perform bearer processing according to the QoS information of the data service corresponding to the data packet.

In the present invention, the GW-U matches the received data packet with the
20 rule, and sends the bearer processing indication information to the GW-C if the matching result meets the trigger condition for bearer processing, so as to trigger the GW-C to perform bearer processing. That is, load interaction is implemented between the GW-C and the GW-U without a UE capability of identifying a service flow, thereby resolving a problem that bearer processing is limited to a difference between
25 UE capabilities of identifying a service flow.

With reference to the first aspect, in a first implementation, the rule is a correspondence between the data service and the QoS information, and the rule is locally configured by the GW-U or obtained by the GW-U from the GW-C; the GW-U finds, from the rule, QoS information required for the data service corresponding to
30 the data packet; and if the QoS information required for the data service is inconsistent with QoS information of a current bearer that is currently used for transmitting the data service, the trigger condition for bearer processing is met.

In the present invention, that the QoS information required for the data service is

inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service includes at least one of the following cases: an allocation/retention priority ARP required for the data service is inconsistent with an ARP of the current bearer that is currently used for transmitting the data service, or a QoS class identifier QCI required for the data service is inconsistent with a QoS QCI of the current bearer that is currently used for transmitting the data service.

In the present invention, the bearer processing indication information sent by the GW-U may include the QoS information required for the data service, so that the GW-C can directly obtain the QoS information.

In the present invention, if each correspondence that is between a data service and QoS information and that is in the rule is corresponding to a rule identifier, the bearer processing indication information sent by the GW-U includes a rule identifier of a correspondence matching the data packet. Correspondingly, the GW-C may determine, according to the rule identifier, the QoS information of the data service corresponding to the data packet.

With reference to the first aspect, in a second implementation, the GW-C is further configured to send a subscription event to the GW-U, where the subscription event includes type information of a data service on which bearer processing needs to be performed; and the trigger condition is that the data packet matches the type information.

In the present invention, that the GW-C determines, according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet may be implemented in the following manner:

determining, by the GW-C according to the bearer processing indication information, a data service type corresponding to the data packet; and allocating QoS according to the data service type, or receiving QoS that is sent by another network element device and that is allocated according to the data service type, where the another network element device is a network element device that is in an evolved packet core EPC and that is different from the GW-U and the GW-C.

In the present invention, the bearer processing indication information sent by the GW-U may include an application identifier, and the application identifier is used to identify a data service type matching the data packet, so that the GW-C determines the data service type according to the application identifier, and determines corresponding QoS.

In the present invention, if the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed is corresponding to an event identifier, the bearer processing indication information sent by the GW-U may include an event identifier corresponding to type
5 information description matching the data packet. Correspondingly, the GW-C may determine, according to the event identifier, the type information description that is of the data service and that is corresponding to the event identifier, and determine, according to the type information description that is of the data service and that is corresponding to the event identifier, the data service type corresponding to the data
10 packet.

With reference to the first aspect of the present invention or any one of the foregoing implementations of the first aspect, the GW-U may further send packet feature information of the data packet to the GW-C, where the packet feature information is used by the GW-C to bind the data service corresponding to the data
15 packet to a bearer; and the GW-C receives the packet feature information that is of the data packet and that is sent by the GW-U, and binds, according to the packet feature information, the data service corresponding to the data packet to the bearer.

In the present invention, the packet feature information is packet filtering information, and the packet filtering information includes some or all items of a
20 service quintet of the data packet.

With reference to the first aspect of the present invention or any one of the foregoing implementations of the first aspect, the GW-C may further send rule update indication information to the GW-U, where the rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing
25 manner corresponding to the modified rule. The GW-U receives the rule update indication information sent by the GW-C, updates the rule according to the rule update indication information, and deletes a data service processing result associated with the modified rule, where the data service processing result is a result obtained by processing, by the GW-U, a data service corresponding to a data packet that meets the
30 trigger condition for bearer processing.

With reference to the first aspect of the present invention or any one of the foregoing implementations of the first aspect, the GW-C may further send a traffic query request to the GW-U, where the traffic query request is used to instruct the GW-U to collect statistics about traffic of a specified bearer; receive a statistical result

obtained by collecting, by the GW-U, statistics about the traffic of the specified bearer according to the traffic query request; and delete the specified bearer if it is determined, according to the statistical result, that accumulated traffic data of the specified bearer does not change at a specified time interval. Correspondingly, the
5 GW-U receives the traffic query request sent by the GW-C, collects statistics about the traffic of the specified bearer according to the traffic query request, and sends the statistical result to the GW-C.

With reference to the first aspect of the present invention or any one of the foregoing implementations of the first aspect, the GW-U may further send
10 end-of-data-service indication information to the GW-C. The GW-C receives the end-of-data-service indication information sent by the GW-U, and removes a data service indicated by the end-of-data-service indication information from a traffic flow template TFT of a bearer.

Specifically, in the present invention, the GW-U may further send QoS
15 information of a deleted service flow to the GW-C. The GW-C receives the QoS information of the deleted service flow, and updates QoS information of a running bearer.

According to a second aspect, a gateway user plane GW-U is provided, including:

20 a receiving unit, configured to receive a data packet;
a processing unit, configured to: match the data packet received by the receiving unit with a rule, and control a sending unit to send bearer processing indication information to a gateway control plane GW-C if a rule matching result of the data packet meets a trigger condition for bearer processing, where the bearer processing
25 indication information is used to trigger the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to the data packet; and

the sending unit, configured to send the bearer processing indication information to the GW-C.

30 In the present invention, the GW-U receives the data packet and matches the received data packet with the rule, and sends the bearer processing indication information to the GW-C if the matching result meets the trigger condition for bearer processing, so as to trigger the GW-C to perform bearer processing, thereby resolving a problem that bearer processing is limited to a difference between UE capabilities of

identifying a service flow.

With reference to the second aspect, in a first implementation, the rule is a correspondence between the data service and the QoS information, and the rule is locally configured by the GW-U or obtained by the GW-U from the GW-C; and

5 the processing unit finds, from the rule, QoS information required for the data service corresponding to the data packet, and determines that the trigger condition is that the QoS information required for the data service is inconsistent with QoS information of a current bearer that is currently used for transmitting the data service.

10 In the present invention, that the QoS information required for the data service is inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service includes at least one of the following cases: an allocation/retention priority ARP required for the data service is inconsistent with an ARP of the current bearer that is currently used for transmitting the data service, or a QoS class identifier QCI required for the data service is inconsistent with a QoS QCI
15 of the current bearer that is currently used for transmitting the data service.

 In the present invention, the bearer processing indication information sent by the sending unit may include the QoS information required for the data service. Alternatively, if each correspondence that is between a data service and QoS information and that is in the rule is corresponding to a rule identifier, the bearer
20 processing indication information may include a rule identifier of a correspondence matching the data packet.

 With reference to the second aspect, in a second implementation, the rule is a subscription event obtained by the GW-U from the GW-C, and the subscription event includes type information description of a data service on which bearer processing
25 needs to be performed; and the trigger condition is that the data packet matches the type information description.

 In the present invention, the bearer processing indication information sent by the sending unit may include an application identifier, and the application identifier is used to identify a data service type matching the data packet; or

30 if the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed is corresponding to an event identifier, the bearer processing indication information sent by the sending unit may include an event identifier corresponding to type information description matching the data packet.

With reference to the second aspect or any one of the foregoing implementations of the second aspect, in a third implementation, the sending unit is further configured to send packet feature information of the data packet to the GW-C, where the packet feature information is used by the GW-C to bind the data service corresponding to the data packet to a bearer.

The packet feature information is packet filtering information, and the packet filtering information includes some or all items of a service quintet of the data packet.

With reference to the second aspect or any one of the foregoing implementations of the second aspect, in a fourth implementation, the receiving unit is further configured to receive rule update indication information sent by the GW-C, where the rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing manner corresponding to the modified rule.

The processing unit is further configured to: update the rule according to the rule update indication information, and delete a data service processing result associated with the modified rule, where the data service processing result is a result obtained by processing, by the GW-U, a data service corresponding to a data packet that meets the trigger condition for bearer processing.

With reference to the second aspect or any one of the foregoing implementations of the second aspect, in a fifth implementation, the receiving unit is further configured to receive a traffic query request sent by the GW-C, where the traffic query request is used to instruct the GW-U to collect statistics about traffic of a specified bearer.

The processing unit is further configured to: collect statistics about the traffic of the specified bearer according to the traffic query request, and send a statistical result to the GW-C.

With reference to the second aspect or any one of the foregoing implementations of the second aspect, in a sixth implementation, the sending unit is further configured to send end-of-data-service indication information to the GW-C.

According to a third aspect, the present invention provides a gateway control plane GW-C, including:

a receiving unit, configured to receive bearer processing indication information sent by a gateway user plane GW-U, where the bearer processing indication information is used to instruct the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to a data packet; and

a processing unit, configured to: determine, according to the bearer processing indication information received by the receiving unit, the QoS information of the data service corresponding to the data packet, and perform bearer processing according to the QoS information of the data service corresponding to the data packet.

5 The performing bearer processing according to the QoS information of the data service corresponding to the data packet may be implemented in the following manner:

 determining whether QoS information of all bearers in an evolved packet core EPC includes QoS information consistent with the QoS information of the data service corresponding to the data packet; and if the QoS information of all the bearers in the evolved packet core includes the QoS information consistent with the QoS information of the data service corresponding to the data packet, updating a bearer corresponding to the QoS information that is consistent with the QoS information of the data service corresponding to the data packet, where QoS information of an updated bearer is consistent with the QoS information of the data service corresponding to the data packet; or if the QoS information of all the bearers in the evolved packet core does not include the QoS information consistent with the QoS information of the data service corresponding to the data packet, creating a dedicated bearer, where QoS information of the dedicated bearer is consistent with the QoS information of the data service corresponding to the data packet.

10
15
20

 In the present invention, the GW-C receives the bearer processing indication information sent by the GW-U, and performs bearer processing, thereby implementing bearer processing between the GW-U and the GW-C, and resolving a problem that bearer processing is limited to a difference between UE capabilities of identifying a service flow.

25

 With reference to the third aspect, in a first implementation, in the present invention, the bearer processing indication information received by the GW-C may include QoS information required for the data service corresponding to the data packet, or a rule identifier of a correspondence matching the data packet.

30 With reference to the third aspect, in a second implementation, the GW-C further includes a sending unit, and the sending unit is configured to send a subscription event to the GW-U, where the subscription event includes type information description of a data service on which bearer processing needs to be performed.

 The determining, according to the bearer processing indication information, the

QoS information of the data service corresponding to the data packet includes:
determining, by the GW-C according to the bearer processing indication information,
a data service type corresponding to the data packet; and allocating, by the GW-C,
QoS according to the data service type; or receiving, by the GW-C, QoS that is sent
5 by another network element device and that is allocated according to the data service
type, where the another network element device is a network element device that is in
the evolved packet core EPC and that is different from the GW-U and the GW-C.

In the present invention, the bearer processing indication information received by
the GW-C includes an application identifier, and the application identifier is used to
10 identify a data service type matching the data packet. Therefore, the GW-C may
determine the data service type of the data packet according to the application
identifier included in the bearer processing indication information.

In the present invention, if the type information description that is in the
subscription event and that is of the data service on which bearer processing needs to
15 be performed is corresponding to an event identifier, the bearer processing indication
information may include an event identifier corresponding to type information
description matching the data packet. Correspondingly, the determining, by the GW-C
according to the bearer processing indication information, a data service type
corresponding to the data packet may be implemented in the following manner:

20 determining, by the GW-C according to the event identifier, the type information
description that is of the data service and that is corresponding to the event identifier,
and determining, according to the type information description that is of the data
service and that is corresponding to the event identifier, the data service type
corresponding to the data packet.

25 With reference to the third aspect or any one of the foregoing implementations of
the third aspect, in a third implementation, the receiving unit is further configured to
receive packet feature information that is of the data packet and that is sent by the
GW-U. The processing unit is further configured to bind, according to the packet
feature information, the data service corresponding to the data packet to a bearer.

30 The packet feature information is packet filtering information, and the packet
filtering information includes some or all items of a service quintet of the data packet.

With reference to the third aspect or any one of the foregoing implementations of
the third aspect, in a fourth implementation, the GW-C includes the sending unit, and
the sending unit is configured to send rule update indication information to the GW-U.

The rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing manner corresponding to the modified rule.

5 With reference to the third aspect or any one of the foregoing implementations of the third aspect, in a fourth implementation, the GW-C includes the sending unit, and the sending unit is configured to send a traffic query request to the GW-U, where the traffic query request is used to instruct the GW-U to collect statistics about traffic of a specified bearer.

10 The receiving unit is further configured to receive a statistical result obtained by collecting, by the GW-U, statistics about the traffic of the specified bearer according to the traffic query request.

The processing unit is further configured to delete the specified bearer if it is determined, according to the statistical result, that accumulated traffic data of the specified bearer does not change at a specified time interval.

15 With reference to the third aspect or any one of the foregoing implementations of the third aspect, in a fifth implementation, the receiving unit is further configured to receive end-of-data-service indication information sent by the GW-U.

20 The processing unit is further configured to remove a data service indicated by the end-of-data-service indication information from a traffic flow template TFT of a bearer.

With reference to the fifth implementation of the third aspect, in a sixth implementation, the receiving unit is further configured to receive QoS information of the deleted service flow, and the processing unit is further configured to update QoS information of a running bearer.

25 According to a fourth aspect, a bearer processing method is provided, including: receiving, by a gateway user plane GW-U, a data packet; and matching, by the GW-U, the data packet with a rule; and sending, by the GW-U, bearer processing indication information to a gateway control plane GW-C if a rule matching result of the data packet meets a trigger condition for bearer processing, where

30

the bearer processing indication information is used to trigger the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to the data packet.

In the present invention, the GW-U matches the received data packet with the

rule, and sends the bearer processing indication information to the GW-C if the matching result meets the trigger condition for bearer processing, so as to trigger the GW-C to perform bearer processing. That is, load interaction is implemented between the GW-C and the GW-U without a UE capability of identifying a service flow, thereby resolving a problem that bearer processing is limited to a difference between UE capabilities of identifying a service flow.

With reference to the fourth aspect, in a first implementation, the rule is a correspondence between the data service and the QoS information, and the rule is locally configured by the GW-U or obtained by the GW-U from the GW-C;

the matching, by the GW-U, the data packet with a rule includes:

finding, by the GW-U from the rule, QoS information required for the data service corresponding to the data packet; and

the trigger condition is that the QoS information required for the data service is inconsistent with QoS information of a current bearer that is currently used for transmitting the data service.

With reference to the first implementation of the fourth aspect, in a second implementation, that the QoS information required for the data service is inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service includes at least one of the following cases: an allocation/retention priority ARP required for the data service is inconsistent with an ARP of the current bearer that is currently used for transmitting the data service, or a QoS class identifier QCI required for the data service is inconsistent with a QoS QCI of the current bearer that is currently used for transmitting the data service.

With reference to the first or the second implementation of the fourth aspect, in a third implementation, the bearer processing indication information includes the QoS information required for the data service.

With reference to the first or the second implementation of the fourth aspect, in a fourth implementation, each correspondence that is between a data service and QoS information and that is in the rule is corresponding to a rule identifier, and the bearer processing indication information includes a rule identifier of a correspondence matching the data packet.

With reference to the fourth aspect, in a fifth implementation, the rule is a subscription event obtained by the GW-U from the GW-C, and the subscription event includes type information description of a data service on which bearer processing

needs to be performed; and

the trigger condition is that the data packet matches the type information description.

5 With reference to the fifth implementation of the fourth aspect, in a sixth implementation, the bearer processing indication information includes an application identifier, and the application identifier is used to identify a data service type matching the data packet.

10 With reference to the fifth implementation of the fourth aspect, in a seventh implementation, the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed is corresponding to an event identifier; and

the bearer processing indication information includes an event identifier corresponding to type information description matching the data packet.

15 With reference to the fourth aspect or any one of the foregoing implementations of the fourth aspect, in an eighth implementation, the method further includes:

sending, by the GW-U, packet feature information of the data packet to the GW-C, where the packet feature information is used by the GW-C to bind the data service corresponding to the data packet to a bearer.

20 With reference to the eighth implementation of the fourth aspect, in a ninth implementation, the packet feature information is packet filtering information, and the packet filtering information includes some or all items of a service quintet of the data packet.

With reference to the fourth aspect or any one of the foregoing implementations of the fourth aspect, in a tenth implementation, the method further includes:

25 receiving, by the GW-U, rule update indication information sent by the GW-C, where the rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing manner corresponding to the modified rule; and

30 updating, by the GW-U, the rule according to the rule update indication information, and deleting a data service processing result associated with the modified rule, where

the data service processing result is a result obtained by processing, by the GW-U, a data service corresponding to a data packet that meets the trigger condition for bearer processing.

With reference to the fourth aspect or any one of the foregoing implementations of the fourth aspect, in an eleventh implementation, the method further includes:

receiving, by the GW-U, a traffic query request sent by the GW-C, where the traffic query request is used to instruct the GW-U to collect statistics about traffic of a specified bearer; and

collecting, by the GW-U, statistics about the traffic of the specified bearer according to the traffic query request, and sending a statistical result to the GW-C.

With reference to the fourth aspect or any one of the foregoing implementations of the fourth aspect, in a twelfth implementation, the method further includes:

sending, by the GW-U, end-of-data-service indication information to the GW-C.

According to a fifth aspect, the present invention provides a bearer processing method, including:

receiving, by a gateway control plane GW-C, bearer processing indication information sent by a gateway user plane GW-U, where the bearer processing indication information is used to instruct the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to a data packet;

determining, by the GW-C according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet;

and

performing, by the GW-C, bearer processing according to the QoS information of the data service corresponding to the data packet.

In the present invention, the GW-C receives the bearer processing indication information sent by the GW-U, and performs bearer processing, so as to implement bearer processing by means of interaction between the GW-C and the GW-U, and resolve a problem that bearer processing is limited to a difference between UE capabilities of identifying a service flow.

With reference to the fifth aspect, in a first implementation, the performing, by the GW-C, bearer processing according to the QoS information of the data service corresponding to the data packet includes:

determining, by the GW-C, whether QoS information of all bearers in an evolved packet core EPC includes QoS information consistent with the QoS information of the data service corresponding to the data packet; and

if the QoS information of all the bearers in the evolved packet core includes the

QoS information consistent with the QoS information of the data service corresponding to the data packet, updating a bearer corresponding to the QoS information that is consistent with the QoS information of the data service corresponding to the data packet, where QoS information of an updated bearer is
5 consistent with the QoS information of the data service corresponding to the data packet; or if the QoS information of all the bearers in the evolved packet core does not include the QoS information consistent with the QoS information of the data service corresponding to the data packet, creating a dedicated bearer, where QoS information of the dedicated bearer is consistent with the QoS information of the data service
10 corresponding to the data packet.

With reference to the fifth aspect or the first implementation of the fifth aspect, in a second implementation, the bearer processing indication information includes QoS information required for the data service corresponding to the data packet.

With reference to the fifth aspect or the first implementation of the fifth aspect,
15 in a third implementation, each correspondence that is between a data service and QoS information and that is in the rule is corresponding to a rule identifier, and the bearer processing indication information includes a rule identifier of a correspondence matching the data packet; and

the determining, by the GW-C according to the bearer processing indication
20 information, the QoS information of the data service corresponding to the data packet includes:

determining, by the GW-C according to the rule identifier, the QoS information of the data service corresponding to the data packet.

With reference to the fifth aspect or the first implementation of the fifth aspect,
25 in a fourth implementation, the method further includes:

sending, by the GW-C, a subscription event to the GW-U, where the subscription event includes type information description of a data service on which bearer processing needs to be performed; and

the determining, by the GW-C according to the bearer processing indication
30 information, the QoS information of the data service corresponding to the data packet includes:

determining, by the GW-C according to the bearer processing indication information, a data service type corresponding to the data packet; and

allocating, by the GW-C, QoS according to the data service type; or receiving, by

the GW-C, QoS that is sent by another network element device and that is allocated according to the data service type, where

the another network element device is a network element device that is in the evolved packet core EPC and that is different from the GW-U and the GW-C.

5 With reference to the fourth implementation of the fifth aspect, in a fifth implementation, the bearer processing indication information includes an application identifier, and the application identifier is used to identify a data service type matching the data packet.

10 With reference to the fourth implementation of the fifth aspect, in a sixth implementation, the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed is corresponding to an event identifier;

the bearer processing indication information includes an event identifier corresponding to type information description matching the data packet; and

15 the determining, by the GW-C according to the bearer processing indication information, a data service type corresponding to the data packet includes:

determining, by the GW-C according to the event identifier, the type information description that is of the data service and that is corresponding to the event identifier; and

20 determining, by the GW-C according to the type information description that is of the data service and that is corresponding to the event identifier, the data service type corresponding to the data packet.

With reference to the fifth aspect or any one of the foregoing implementations of the fifth aspect, in a seventh implementation, the method further includes:

25 receiving, by the GW-C, packet feature information that is of the data packet and that is sent by the GW-U; and

binding, by the GW-C according to the packet feature information, the data service corresponding to the data packet to a bearer.

30 With reference to the seventh implementation of the fifth aspect, in an eighth implementation, the packet feature information is packet filtering information, and the packet filtering information includes some or all items of a service quintet of the data packet.

With reference to the fifth aspect or any one of the foregoing implementations of the fifth aspect, in a ninth implementation, the method further includes:

sending, by the GW-C, rule update indication information to the GW-U.

With reference to the ninth implementation of the fifth aspect, in a tenth implementation, the rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing manner corresponding to the modified rule.

With reference to the fifth aspect or any one of the foregoing implementations of the fifth aspect, in an eleventh implementation, the method further includes:

sending, by the GW-C, a traffic query request to the GW-U, where the traffic query request is used to instruct the GW-U to collect statistics about traffic of a specified bearer;

receiving, by the GW-C, a statistical result obtained by collecting, by the GW-U, statistics about the traffic of the specified bearer according to the traffic query request; and

deleting, by the GW-C, the specified bearer if it is determined, according to the statistical result, that accumulated traffic data of the specified bearer does not change at a specified time interval.

With reference to the fifth aspect or any one of the foregoing implementations of the fifth aspect, in a twelfth implementation, the method further includes:

receiving, by the GW-C, end-of-data-service indication information sent by the GW-U; and

removing, by the GW-C, a data service indicated by the end-of-data-service indication information from a traffic flow template TFT of a bearer.

With reference to the twelfth implementation of the fifth aspect, in a thirteenth implementation, the method further includes:

receiving, by the GW-C, QoS information of the deleted service flow, and updating QoS information of a running bearer.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a diagram of a distributed gateway network architecture;

FIG. 2 is a schematic structural diagram of a GW-U according to an embodiment of the present invention;

FIG. 3A and FIG. 3B are schematic structural diagrams of a GW-C according to an embodiment of the present invention;

FIG. 4 is a schematic structural diagram of a bearer processing system according to an embodiment of the present invention;

FIG. 5 is a flowchart for implementing a bearer processing method according to an embodiment of the present invention;

5 FIG. 6 is a schematic flowchart for implementing a bearer processing method according to an embodiment of the present invention;

FIG. 7 is another schematic flowchart for implementing a bearer processing method according to an embodiment of the present invention;

10 FIG. 8 is a flowchart for implementing a bearer processing method in a rule update case according to an embodiment of the present invention;

FIG. 9 is a flowchart for implementing bearer delete or update that is triggered after a data service ends according to an embodiment of the present invention; and

15 FIG. 10 is another flowchart for implementing bearer delete or update that is triggered after a data service ends according to an embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

The following clearly describes the technical solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention.

20 The "multiple" in the embodiments of the present invention means at least two. The term "and/or" describes an association relationship for describing associated objects and represents that three relationships may exist. For example, A and/or B may represent the following three cases: Only A exists, both A and B exist, and only B exists. The character "/" generally indicates an "or" relationship between the
25 associated objects.

A distributed gateway (Distributed Gateway, DGW) network architecture shown in FIG. 1 may be applied to a bearer processing method provided in the embodiments of the present invention. A gateway device in the DGW network architecture shown in FIG. 1 includes a distributed gateway control plane (Gateway Control Plane) and a
30 distributed gateway user plane (Gateway User Plane). The distributed gateway control plane implements a function of the gateway control plane, and is referred to as a GW-C for short below. The distributed gateway user plane implements a function of

the gateway user plane, and is referred to as a GW-U for short below.

The GW-C is a signaling control anchor, communicates with an access controller (Access Controller, AC), a mobility management entity (Mobility Management Entity, MME), a policy and charging rules function (Policy and Charging Rules Function, PCRF), a lawful interception gateway (Lawful Interception Gateway, LIG), an online charging system (Online Charging System, OCS), an offline charging system (Offline Charging System, OFCS), or the like, and may further define a processing action performed by the GW-U on a data packet. The GW-U is a processing anchor of a user data packet, communicates with an access point (Access Point, AP), an evolved NodeB (evolved NodeB, eNodeB), or the like, and may implement local data exchange.

In the embodiments of the present invention, there is a communications interface between the GW-C and the GW-U. In the embodiments of the present invention, a name of the interface between the GW-C and the GW-U may be defined as S18. Certainly, another interface name is not limited. The GW-U may obtain a data packet of a data service. In the embodiments of the present invention, the GW-U determines whether the received data packet meets a condition for bearer processing. If the data packet meets the condition for bearer processing, the GW-U sends bearer processing indication information to the GW-C by using the S18 interface. The GW-C performs bearer processing according to the bearer processing indication information.

In the present invention, a process of implementing bearer processing by means of interaction between the GW-C and the GW-U is described in detail below.

The present invention provides a GW-U. FIG. 2 is a schematic structural diagram of the GW-U according to the present invention. In FIG. 2, a reference sign 100 is used to represent the GW-U. As shown in FIG. 2, the GW-U provided in the present invention includes a receiving unit 101, a processing unit 102, and a sending unit 103.

The receiving unit 101 is configured to receive a data packet.

The processing unit 102 is configured to: match the data packet received by the receiving unit 101 with a rule, and control the sending unit 103 to send bearer processing indication information to a GW-C if a rule matching result of the data packet meets a trigger condition for bearer processing, where the bearer processing indication information is used to trigger the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to the data packet.

The sending unit 103 is configured to send the bearer processing indication information to the GW-C.

In an implementation of the present invention, the rule may be a correspondence between the data service and the QoS information, and the rule is locally configured
5 by the GW-U or obtained by the GW-U from the GW-C.

The processing unit 102 finds, from the rule, QoS information required for the data service corresponding to the data packet, and determines that the trigger condition is that the QoS information required for the data service is inconsistent with QoS information of a current bearer that is currently used for transmitting the data
10 service.

In the present invention, that the QoS information required for the data service is inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service includes at least one of the following cases: an allocation/retention priority ARP required for the data service is inconsistent with an
15 ARP of the current bearer that is currently used for transmitting the data service, or a QoS class identifier QCI required for the data service is inconsistent with a QoS QCI of the current bearer that is currently used for transmitting the data service.

In the present invention, the bearer processing indication information sent by the sending unit 103 may include the QoS information required for the data service.
20 Alternatively, if each correspondence that is between a data service and QoS information and that is in the rule is corresponding to a rule identifier, the bearer processing indication information may include a rule identifier of a correspondence matching the data packet.

In another implementation of the present invention, the rule is a subscription
25 event obtained by the GW-U from the GW-C, the subscription event includes type information description of a data service on which bearer processing needs to be performed, and the trigger condition is that the data packet matches the type information description.

In the present invention, the bearer processing indication information sent by the
30 sending unit 103 may include an application identifier, and the application identifier is used to identify a data service type matching the data packet. Alternatively, if the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed is corresponding to an event identifier, the bearer processing indication information sent by the sending unit 103

may include an event identifier corresponding to type information description matching the data packet.

In the present invention, the sending unit 103 is further configured to send packet feature information of the data packet to the GW-C, where the packet feature
5 information is used by the GW-C to bind the data service corresponding to the data packet to a bearer.

The packet feature information is packet filtering information, and the packet filtering information includes some or all items of a service quintet of the data packet.

In the present invention, the receiving unit 101 is further configured to receive
10 rule update indication information sent by the GW-C, where the rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing manner corresponding to the modified rule.

The processing unit 102 is further configured to: update the rule according to the rule update indication information, and delete a data service processing result
15 associated with the modified rule, where the data service processing result is a result obtained by processing, by the GW-U, a data service corresponding to a data packet that meets the trigger condition for bearer processing.

In the present invention, the receiving unit 101 is further configured to receive a traffic query request sent by the GW-C, where the traffic query request is used to
20 instruct the GW-U to collect statistics about traffic of a specified bearer.

The processing unit 102 is further configured to: collect statistics about the traffic of the specified bearer according to the traffic query request, and send a statistical result to the GW-C.

In the present invention, the sending unit 103 is further configured to send
25 end-of-data-service indication information to the GW-C.

It should be noted that, in a specific implementation process, the receiving unit 101 in the GW-U may be a receiver, the processing unit 102 may be a processor, and the sending unit 103 may be a transmitter. The receiver, the processor, and the transmitter may be connected by using a bus.

30 The receiver and the transmitter may be communications interfaces, and the like.

The processor may be a general purpose processor, including a central processing unit (Central Processing Unit, CPU for short), a network processor (Network Processor, NP for short), and the like, or may be a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field programmable gate array

(FPGA), another programmable logic device, or the like.

When the processor is a CPU, the GW-U may further include a memory that is configured to store a program. Specifically, the program may include program code, and the program code includes a computer operation instruction. The memory may include a random access memory (random access memory, RAM for short), or may further include a nonvolatile memory (non-volatile memory) such as at least one magnetic disk storage. The processor executes the program code stored in the memory, so as to implement the foregoing functions of the GW-U.

For details that are not described in this embodiment, refer to method description shown in FIG. 5 to FIG. 10. Details are not described herein.

In the present invention, the GW-U matches the received data packet with the rule, and sends the bearer processing indication information to the GW-C if the matching result meets the trigger condition for bearer processing, so as to trigger the GW-C to perform bearer processing, thereby resolving a problem that bearer processing is limited to a difference between UE capabilities of identifying a service flow.

The present invention provides a GW-C. FIG. 3A is a schematic structural diagram of the GW-C according to an embodiment of the present invention. In FIG. 3A, a reference sign 200 is used to represent the GW-C. As shown in FIG. 3A, the GW-C provided in the present invention includes a receiving unit 201 and a processing unit 202.

The receiving unit 201 receives bearer processing indication information sent by a GW-U, where the bearer processing indication information is used to instruct the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to a data packet.

The processing unit 202 determines, according to the bearer processing indication information received by the receiving unit 201, the QoS information of the data service corresponding to the data packet, and performs bearer processing according to the QoS information of the data service corresponding to the data packet.

The performing bearer processing according to the QoS information of the data service corresponding to the data packet may be implemented in the following manner:

determining whether QoS information of all bearers in an evolved packet core EPC includes QoS information consistent with the QoS information of the data

service corresponding to the data packet; and if the QoS information of all the bearers in the evolved packet core includes the QoS information consistent with the QoS information of the data service corresponding to the data packet, updating a bearer corresponding to the QoS information that is consistent with the QoS information of the data service corresponding to the data packet, where QoS information of an updated bearer is consistent with the QoS information of the data service corresponding to the data packet; or if the QoS information of all the bearers in the evolved packet core does not include the QoS information consistent with the QoS information of the data service corresponding to the data packet, creating a dedicated bearer, where QoS information of the dedicated bearer is consistent with the QoS information of the data service corresponding to the data packet.

In the present invention, the bearer processing indication information received by the GW-C may include QoS information required for the data service corresponding to the data packet or a rule identifier of a correspondence matching the data packet.

The GW-C further includes a sending unit 203. As shown in FIG. 3B, the sending unit 203 is configured to send a subscription event to the GW-U, where the subscription event includes type information description of a data service on which bearer processing needs to be performed.

The determining, according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet includes: determining, by the GW-C according to the bearer processing indication information, a data service type corresponding to the data packet; and allocating, by the GW-C, QoS according to the data service type; or receiving, by the GW-C, QoS that is sent by another network element device and that is allocated according to the data service type, where the another network element device is a network element device that is in the evolved packet core EPC and that is different from the GW-U and the GW-C.

In the present invention, the bearer processing indication information received by the GW-C includes an application identifier, and the application identifier is used to identify a data service type matching the data packet. Therefore, the GW-C may determine the data service type of the data packet according to the application identifier included in the bearer processing indication information.

In the present invention, if the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed is corresponding to an event identifier, the bearer processing indication

information may include an event identifier corresponding to type information description matching the data packet. Correspondingly, the determining, by the GW-C according to the bearer processing indication information, a data service type corresponding to the data packet may be implemented in the following manner:

5 determining, by the GW-C according to the event identifier, the type information description that is of the data service and that is corresponding to the event identifier, and determining, according to the type information description that is of the data service and that is corresponding to the event identifier, the data service type corresponding to the data packet.

10 In the present invention, the receiving unit 201 is further configured to receive packet feature information that is of the data packet and that is sent by the GW-U. The processing unit 202 is further configured to bind, according to the packet feature information, the data service corresponding to the data packet to a bearer.

15 The packet feature information is packet filtering information, and the packet filtering information includes some or all items of a service quintet of the data packet.

 In the present invention, the GW-C includes the sending unit 203. The sending unit 203 is configured to send rule update indication information to the GW-U.

20 The rule update indication information includes modified rule content, a modified rule identifier, and a bearer processing manner corresponding to the modified rule.

 With reference to the third aspect or any one of the foregoing implementations of the third aspect, in a fourth implementation, the GW-C includes the sending unit 203. The sending unit 203 is configured to send a traffic query request to the GW-U, where the traffic query request is used to instruct the GW-U to collect statistics about traffic
25 of a specified bearer.

 The receiving unit 201 is further configured to receive a statistical result obtained by collecting, by the GW-U, statistics about the traffic of the specified bearer according to the traffic query request.

30 The processing unit 202 is further configured to delete the specified bearer if it is determined, according to the statistical result, that accumulated traffic data of the specified bearer does not change at a specified time interval.

 In the present invention, the receiving unit 201 is further configured to receive end-of-data-service indication information sent by the GW-U.

 The processing unit 202 is further configured to remove a data service indicated

by the end-of-data-service indication information from a traffic flow template TFT of a bearer.

In the present invention, the receiving unit 201 is further configured to receive QoS information of the deleted service flow. The processing unit 202 is further
5 configured to update QoS information of a running bearer.

It should be noted that, in a specific implementation process, the receiving unit 201 in the GW-C may be a receiver, the processing unit 202 may be a processor, and the sending unit 203 may be a transmitter. The receiver, the processor, and the transmitter may be connected by using a bus.

10 The receiver and the transmitter may be communications interfaces, and the like.

The processor may be a general purpose processor, including a central processing unit (Central Processing Unit, CPU for short), a network processor (Network Processor, NP for short), and the like, or may be a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field programmable gate array
15 (FPGA), another programmable logic device, or the like.

When the processor is a CPU, the GW-C may further include a memory that is configured to store a program. Specifically, the program may include program code, and the program code includes a computer operation instruction. The memory may include a random access memory (random access memory, RAM for short), or may
20 further include a nonvolatile memory (non-volatile memory) such as at least one magnetic disk storage. The processor executes the program code stored in the memory, so as to implement the foregoing functions of the GW-C.

For details that are not described in this embodiment, refer to method description shown in FIG. 5 to FIG. 10. Details are not described herein.

25 The GW-C provided in the present invention receives the bearer processing indication information sent by the GW-U, and performs bearer processing according to the bearer processing indication information, thereby resolving a problem that bearer processing is limited to a difference between UE capabilities of identifying a service flow.

30 The present invention further provides a bearer processing system. As shown in FIG. 4, the bearer processing system provided in the present invention includes a GW-C and a GW-U. The GW-U is configured to: receive a data packet and match the data packet with a rule, and send bearer processing indication information to the GW-C if a rule matching result of the data packet meets a trigger condition for bearer

processing, where the bearer processing indication information is used to trigger the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to the data packet. The GW-C is configured to: receive the bearer processing indication information sent by the GW-U, determine, according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet, and perform bearer processing according to the QoS information of the data service corresponding to the data packet.

The GW-U in the bearer processing system provided in the present invention has a structure shown in FIG. 2, and may perform corresponding GW-U method functions in FIG. 5 to FIG. 10. The GW-C has a structure shown in FIG. 3, and may perform corresponding GW-C method functions in FIG. 5 to FIG. 10. Therefore, for details about the GW-C and the GW-U that are not described in the present invention, refer to related accompanying drawings and embodiment description. Details are not described herein.

The bearer processing method provided in the embodiments of the present invention is described in detail in the following embodiment of the present invention.

FIG. 5 is a flowchart for implementing a bearer processing method according to an embodiment of the present invention. As shown in FIG. 5, the method includes the following steps.

S101. A GW-U receives a data packet.

In this embodiment of the present invention, the data packet received by the GW-U may be an uplink data packet or a downlink data packet.

S102. The GW-U matches the received data packet with a rule.

In this embodiment of the present invention, the rule matched by the GW-U with the data packet may be locally configured by the GW-U or may be sent by a GW-C to the GW-U.

The rule in this embodiment of the present invention may be a correspondence between a data service and QoS information. For example, a rule description manner shown in the following Table 1 may be used.

Table 1

Rule 1	Data service 1	QoS 1
Rule 2	Data service 2	QoS 2

	Data service 3	QoS 3
Rule 3	Data service 4	QoS 4
Rule 4	Data service 5	QoS 4

In Table 1, the rule 1, the rule 2, and the rule 3 may be understood as rule identifiers such as rule names or identities (ID). The data service 1, the data service 2, the data service 3, the data service 4, and the data service 5 may be understood as different data services. The QoS 1, the QoS 2, the QoS 3, and the QoS 4 may be understood as different QoS values. For example, a rule name is a first matching rule, a corresponding data service is a voice service, and QoS values required for the voice service are: a priority of 7, a packet delay budget of 100, and a packet error loss rate of 10-6.

In this embodiment of the present invention, one rule may include correspondences between QoS and one or more data services. For example, the rule 1 includes a correspondence between the data service 1 and the QoS 1, and the rule 2 includes a correspondence between the data service 2 and the QoS 2 and a correspondence between the data service 3 and the QoS 3. In this embodiment of the present invention, there may be a one-to-one mapping relationship between a data service and QoS. For example, QoS required for the data service 1 is the QoS 1. There may be further a many-to-one mapping relationship between a data service and QoS. For example, QoS required for the data service 4 is the QoS 4, and QoS required for the data service 5 is the QoS 4.

The GW-U finds, from the rule, QoS information required for a data service corresponding to the data packet, and determines whether the QoS information required for the data service is consistent with QoS information of a current bearer that is currently used for transmitting the data service. If the QoS information required for the data service is inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service, a trigger condition for bearer processing is met.

Specifically, in this embodiment of the present invention, if an ARP included in the QoS information required for the data service is inconsistent with an ARP included in the QoS information of the current bearer that is currently used for transmitting the data service, and/or if a QCI included in the QoS information

required for the data service is inconsistent with a QCI included in the QoS information of the current bearer that is currently used for transmitting the data service, it may be determined that the QoS information required for the data service is inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service.

The rule in this embodiment of the present invention may be further a subscription event sent by the GW-C to the GW-U. The subscription event includes type information description of a data service on which bearer processing needs to be performed. For example, a manner shown in the following Table 2 may be used.

Table 2

Event 1	Type information description 1 of a data service	Application identifier 1
	Type information description 2 of a data service	Application identifier 2
Event 2	Type information description 3 of a data service	Application identifier 3
Event 3	Type information description 4 of a data service	Application identifier 4

In Table 2, the event 1, the event 2, and the event 3 may be understood as event identifiers such as event names or IDs. The event identifiers may be understood as the rule identifiers in Table 1 in the foregoing embodiment. The type information description of the data service may be understood as information such as a data packet feature that is used to match the data packet. The type information description of the data service may be understood as the data service in Table 1 in the foregoing embodiment. The application identifier is used to identify a data service type that is corresponding to type information description of a data service matching the application identifier. For example, the application identifier 1 is used to identify a data service type corresponding to the type information description 1 of the data service.

The GW-U determines whether the received data packet matches the type information description that is in the subscription event and that is of the data service. If the received data packet matches the type information description, the trigger condition for bearer processing is met.

S103. The GW-U sends bearer processing indication information to a GW-C if a rule matching result of the data packet meets a trigger condition for bearer processing,

so as to trigger the GW-C to perform bearer processing according to quality of service QoS information of a data service corresponding to the data packet.

In this embodiment of the present invention, the bearer processing indication information sent by the GW-U to the GW-C is used to trigger the GW-C to perform
5 bearer processing according to the quality of service QoS information of the data service corresponding to the data packet.

Specifically, in this embodiment of the present invention, the bearer processing indication information may include different content according to different rules. For example, if the rule is locally configured by the GW-U, the bearer processing
10 indication information may include the QoS information required for the data service. Alternatively, if the rule is obtained by the GW-U from the GW-C, the bearer processing indication information may include a rule identifier matching the data packet. The rule identifier may be a rule name matching the data packet.

It should be noted that if the rule is obtained by the GW-U from the GW-C, the
15 rule identifier sent by the GW-U to the GW-C is a rule identifier delivered by the GW-C to the GW-U or negotiated by the GW-C and the GW-U.

In the present invention, if the rule is the subscription event sent by the GW-C to the GW-U, the bearer processing indication information may include an application identifier. The application identifier is used to identify a data service type matching
20 the data packet. Alternatively, the bearer processing indication information may include an event identifier. The event identifier is used to identify an event identifier corresponding to type information description that is of the data service and that matches the data packet.

Optionally, in this embodiment of the present invention, the bearer processing
25 indication information sent by the GW-U to the GW-C may include packet feature information of the data packet, so as to bind a newly created dedicated bearer or an updated bearer to the data packet received by the GW-U. For example, in this embodiment of the present invention, the packet feature information may be packet filtering (packet filter) information. The packet filter information includes some or all
30 items of a service quintet of the data packet.

In this embodiment of the present invention, the GW-U may send the packet filter information when deep packet inspection is performed on the data packet.

S104. The GW-C receives the bearer processing indication information sent by the GW-U, and determines, according to the bearer processing indication information

sent by the GW-U, the QoS information of the data service corresponding to the data packet.

Specifically, in this embodiment of the present invention, if the bearer processing indication information includes QoS information of the data packet, the GW-C may
5 directly obtain the QoS information of the data packet. Alternatively, if the bearer processing indication information includes a rule identifier of a correspondence matching the data packet, the GW-C may obtain QoS information of the data packet by parsing the rule identifier.

In this embodiment of the present invention, if the rule is the subscription event
10 sent by the GW-C to the GW-U, the GW-C determines, according to the bearer processing indication information sent by the GW-U, the data service type corresponding to the data packet. The GW-C allocates QoS according to the data service type, or receives QoS that is sent by another network element device and that is allocated according to the data service type. The another network element device is
15 a network element device that is in an evolved packet core (Evolved Packet Core, EPC) and that is different from the GW-U and the GW-C, for example, a PCRF.

In this embodiment of the present invention, if the bearer processing indication information includes an application identifier, a data service type matching the data packet may be directly determined according to the application identifier.

20 Type information description that is in the subscription event and that is of each data service on which bearer processing needs to be performed is corresponding to an event identifier such as an event name or a rule name. If the bearer processing indication information includes an event identifier, the GW-C determines, according to the event identifier, type information description that is corresponding to the event
25 identifier and that is of a data service on which bearer processing needs to be performed, and determines, according to the type information description that is corresponding to the event identifier and that is of the data service on which bearer processing needs to be performed, the data service type corresponding to the data packet.

30 S105. The GW-C performs bearer processing according to the QoS information of the data service corresponding to the data packet.

In this embodiment of the present invention, the GW-C determines the QoS information of the data service corresponding to the data packet. Then, the GW-C determines whether QoS information of all bearers in the EPC includes QoS

information consistent with the QoS information of the data service corresponding to the data packet.

If the QoS information of all the bearers in the EPC includes the QoS information consistent with the QoS information of the data service corresponding to the data packet, for example, the EPC includes an ARP and/or a QCI consistent with an ARP and/or a QCI of the data service corresponding to the data packet, the GW-C updates a bearer corresponding to the QoS information that is consistent with the QoS information of the data service corresponding to the data packet.

Alternatively, if the EPC does not include the QoS information consistent with the QoS information of the data service corresponding to the data packet, the GW-C creates a dedicated bearer. QoS information of the dedicated bearer is consistent with the QoS information of the data service corresponding to the data packet.

Optionally, in the present invention, the GW-C may receive the packet feature information sent by the GW-U. If the GW-C needs to create a new dedicated bearer, the GW-C generates a new traffic flow template (Traffic Flow Template, TFT) according to the packet feature information. Alternatively, if the GW-C needs to update an original bearer, the GW-C updates TFT information according to the packet feature information, so as to bind the data packet to the bearer.

According to the bearer processing method provided in this embodiment of the present invention, the GW-U matches the received data packet with the rule, and sends the bearer processing indication information to the GW-C if the matching result meets the trigger condition for bearer processing, so as to trigger the GW-C to perform bearer processing, thereby resolving a problem that bearer processing is limited to a difference between UE capabilities of identifying a service flow.

The bearer processing method in the foregoing embodiment is described in detail in the following embodiment of the present invention with reference to actual application.

In an embodiment of the present invention, an application scenario in which a GW-U matches a data packet with a local rule, and determines whether bearer processing needs to be performed on a data service corresponding to the data packet is used as an example for description. FIG. 6 is a schematic flowchart for implementing a bearer processing method according to this embodiment of the present invention. As shown in FIG. 6, the method includes the following steps.

S201. The GW-U receives an uplink data packet or a downlink data packet, and

matches the received data packet with a rule.

In this embodiment of the present invention, the rule matched by the GW-U with the data packet may be locally configured by the GW-U or may be sent by a GW-C to the GW-U.

5 In this embodiment of the present invention, the rule is a correspondence between a data service and QoS information. For example, the rule may be the rule shown in Table 1 in the foregoing embodiment. The GW-U first matches the received data packet with a data service in the rule, and obtains corresponding QoS information. The GW-U compares the found QoS information with QoS information
10 of a current bearer that is currently used for transmitting the data service, to determine whether QoS information required for the data service is consistent with the QoS information of the current bearer that is currently used for transmitting the data service. If the found QoS information is inconsistent with the QoS information of the current bearer, for example, at least one of a found ARP or QCI is inconsistent with at
15 least one of an ARP or a QCI of the current bearer, the GW-U may determine that the QoS information required for the data service is inconsistent with the QoS information of the current bearer that is currently used for transmitting the data service, and a trigger condition for bearer processing is met.

S202. The GW-U sends bearer processing indication information to a GW-C.

20 In this embodiment of the present invention, the bearer processing indication information sent by the GW-U to the GW-C is used to trigger the GW-C to perform bearer processing according to the QoS information of the data service corresponding to the data packet.

In this embodiment of the present invention, the bearer processing indication
25 information sent by the GW-U to the GW-C includes information that can enable the GW-C to obtain the QoS information required for the data service corresponding to the data packet. For example, the bearer processing indication information directly includes the QoS information required for the data service, or may certainly include a rule identifier of a correspondence matching the data packet, for example, a rule
30 name.

S203. The GW-C sends a create bearer request or an update bearer request to an MME.

In this embodiment of the present invention, the GW-C obtains, according to the bearer processing indication information sent by the GW-U, the QoS information

required for the data service, and compares the QoS information required for the data service with QoS information of all bearers in an EPC. For example, the GW-C compares a QCI in the QoS information required for the data service with QCIs of all the bearers in the EPC. If the QoS information of all the bearers in the EPC does not include QoS information consistent with the QoS information required for the data service, the GW-C sends the create bearer request to the MME, so as to create a dedicated bearer for the data service. Alternatively, if the EPC includes a bearer corresponding to QoS information that is consistent with the QoS information required for the data service, the GW-C sends the update bearer request to the MME, so as to add the data service to the bearer.

In this embodiment of the present invention, to bind a newly created dedicated bearer or an updated bearer to the data packet received by the GW-U, the bearer processing indication information sent by the GW-U to the GW-C may include packet feature information of the data packet, and the GW-C creates the new dedicated bearer or binds the data packet to an existing bearer according to the packet feature information. For specific implementation, refer to related descriptions in the foregoing embodiment. Details are not described herein again.

S204. The MME sends the create bearer request or the update bearer request to an eNodeB, and sends a session management request, and the eNodeB sends the session management request to user equipment (User Equipment, UE).

S205. The eNodeB sends a radio resource control (Radio Resource Control, RRC) connection reconfiguration message to the UE.

S206. The UE feeds back an RRC connection reconfiguration complete message to the eNodeB.

S207. The eNodeB sends a create bearer response message or an update bearer response message to the MME.

S208. The UE sends a session management response message to the eNodeB, and the eNodeB sends the session management response message to the MME.

S209. The MME sends the create bearer response message or the update bearer response message to the GW-C.

S210. The GW-C sends a session management request message to the GW-U, and controls the GW-U to update a corresponding user session, and the GW-U completes session update, and returns the session management response message to the GW-C.

In this embodiment of the present invention, the GW-U matches the received data packet with the rule, finds, from the rule, QoS information corresponding to a data service type, and determines whether the QoS information required for the data service is consistent with the QoS information of the current bearer that is currently used for transmitting the data service. If the QoS information required for the data service is inconsistent with the QoS information of the current bearer, the GW-U sends the bearer processing indication information to the GW-C. The GW-C performs bearer processing according to the bearer processing indication information, to complete bearer processing by means of interaction between the GW-U and the GW-C, and avoid a problem that bearer processing cannot be completed because of a UE capability difference.

In another embodiment of the present invention, an example in which a GW-C sends a subscription event to a GW-U, and the GW-C obtains a data service type corresponding to a data packet, and determines whether bearer processing needs to be performed on a data service corresponding to the data packet is used for description. The subscription event includes type information description of a data service on which bearer processing needs to be performed. FIG. 7 is a schematic flowchart for implementing a bearer processing method according to another embodiment of the present invention. As shown in FIG. 7, the method includes the following steps.

S301. The GW-C sends a subscription event to the GW-U.

In this embodiment of the present invention, the subscription event sent by the GW-C to the GW-U includes type information description of a data service on which bearer processing needs to be performed. In this embodiment of the present invention, the subscription event sent by the GW-C to the GW-U may be locally configured by the GW-C or may be triggered by another network element device. The another network element device is a network element device that is in an evolved packet core (Evolved Packet Core, EPC) and that is different from the GW-U and the GW-C, for example, a PCRF. The subscription event is generated by means of triggering of the another network element device. For example, the type information description that is in the subscription event and that is of the data service on which bearer processing needs to be performed may be generated based on a dynamic policy and charging control (Policy and Charging Control, PCC) rule or an application detection and control (Application Detection and Control, ADC) rule sent by the PCRF.

S302. The GW-U receives an uplink data packet or a downlink data packet, and

determines whether the data packet matches type information description that is in the subscription event and that is of a data service.

In this embodiment of the present invention, the GW-U determines whether the received uplink data packet or downlink data packet matches the type information description that is in the subscription event and that is of the data service. The GW-U may determine whether a data packet feature of the uplink data packet or the downlink data packet meets a requirement for a data service type described in the subscription event. If the data packet feature meets the requirement for the data service type described in the subscription event, the GW-U may determine that the data packet matches the type information description that is in the subscription event and that is of the data service. That is, a data service type corresponding to the received data packet is consistent with the data service type described in the subscription event. Then, the GW-U sends bearer processing indication information to the GW-C.

S303. The GW-C receives bearer processing indication information sent by the GW-U, and determines a data service type corresponding to the data packet.

In this embodiment of the present invention, the bearer processing indication information sent by the GW-U includes information that enables the GW-C to determine the data service type of the data packet received by the GW-U. For example, the bearer processing indication information includes an application identifier, and the application identifier is used to identify a data service type matching the data packet. The GW-C determines the data service type of the data packet according to the application identifier. In another example, the bearer processing indication information includes an event identifier. The event identifier is used to identify type information description that is of a data service and that matches the data packet. The GW-C determines, according to the event identifier, the type information description that is of the data service and that is corresponding to the event identifier. The GW-C determines, according to the type information description that is of the data service and that is corresponding to the event identifier, the data service type corresponding to the data packet.

S304. The GW-C determines QoS required for a data service corresponding to the data packet.

In this embodiment of the present invention, if the subscription event is locally configured by the GW-C, the GW-C allocates QoS according to the data service type.

Alternatively, in this embodiment of the present invention, if the subscription event is triggered by the another network element device, the GW-C sends the bearer processing indication information to the another network element device, and receives QoS that is sent by the another network element device and that is allocated according to the data service type. In this embodiment of the present invention, the another network element device may be a network element device that is in the EPC and that is different from the GW-U and the GW-C, for example, the PCRF. For example, the GW-C may send an IP-connectivity access network (connectivity access network IP, IP-CAN) session modification request message to the PCRF. The PCRF determines and allocates the QoS according to the data service type of the data packet, and feeds back an IP-CAN session modification reply to the GW-C.

S305. The GW-C performs bearer processing according to QoS information of the data service corresponding to the data packet.

In this embodiment of the present invention, the GW-C determines whether QoS information of all bearers in the EPC includes QoS information consistent with the QoS information of the data service corresponding to the data packet. If the QoS information of all the bearers in the EPC includes the QoS information consistent with the QoS information of the data service corresponding to the data packet, the GW-C updates a bearer corresponding to the QoS information that is consistent with the QoS information of the data service corresponding to the data packet. QoS information of an updated bearer is consistent with the QoS information of the data service corresponding to the data packet. Alternatively, if the QoS information of all the bearers in the EPC does not include the QoS information consistent with the QoS information of the data service corresponding to the data packet, the GW-C creates a dedicated bearer. QoS information of the dedicated bearer is consistent with the QoS information of the data service corresponding to the data packet.

S306. The GW-C triggers a procedure for creating or updating a dedicated bearer, and updates a user bearer of the GW-U and processing logic related to the user bearer. For a specific implementation procedure, refer to related descriptions in the foregoing embodiment. Details are not described herein again.

In this embodiment of the present invention, the GW-C sends the subscription event to the GW-U. The subscription event includes the type information description of the data service on which bearer processing needs to be performed. The GW-U matches the received data packet with a rule according to the subscription event. If the

data packet feature of the data packet matches the type information description of the data service on which bearer processing needs to be performed, the GW-U sends the bearer processing indication information to the GW-C. The GW-C determines, according to the bearer processing indication information, the data service type that is corresponding to the data packet received by the GW-U, and determines QoS information of the data service type. The GW-C determines whether bearer processing needs to be performed, and performs bearer processing if bearer processing needs to be performed.

Optionally, in this embodiment of the present invention, the GW-C may further receive packet feature information that is of the data packet and that is sent by the GW-U, so as to bind, according to the packet feature information, the data service corresponding to the data packet to a bearer. The packet feature information may be packet filter information. The packet filter information includes some or all items of a service quintet of the data packet.

Further, if a matching rule is modified, a GW-U needs to update the rule and perform corresponding processing. In this embodiment of the present invention, an example in which a rule stored in a GW-C is modified is used for description. The rule stored in the GW-C may be modified by means of triggering of another network element device. For example, a PCRF modifies the stored rule by using an IP-CAN session modification message, or the GW-C may locally modify the stored rule in a statically predefined manner. In this embodiment of the present invention, an example in which the PCRF modifies the stored rule by using the IP-CAN session modification message is used below for description. As shown in FIG. 8, the following steps are included.

S401. The PCRF sends an IP-CAN session modification message to the GW-C, where the IP-CAN session modification message is used to instruct a rule to be updated.

S402. The GW-C sends rule update indication information to the GW-U, and synchronously updates a locally stored rule.

In this embodiment of the present invention, the rule update indication information sent by the GW-C to the GW-U includes a rule identifier and a rule processing method. The rule processing method includes: adding, modifying, or deleting a rule. If a rule is to be added or modified, the rule update indication information further includes new rule content.

In this embodiment of the present invention, the rule update indication information sent by the GW-C to the GW-U may be a session management request.

S403. The GW-U receives the rule update indication information sent by the GW-C, updates the rule according to the rule update indication information, and
5 deletes a data service processing result associated with the modified rule.

In this embodiment of the present invention, the data service processing result is a result obtained by processing, by the GW-U, a data service corresponding to a data packet that meets a trigger condition for bearer processing. The data service processing result may be a flow table or a flow object. A subsequent data packet
10 corresponding to the same data service may be directly matched with the data service processing result. If the data packet can match the data service processing result, the data packet does not need to be matched with the rule. Alternatively, if the data packet and the data service processing result cannot match, the data packet needs to be matched with the rule.

15 S404. The GW-U sends a session management response to the GW-C.

In this embodiment of the present invention, the GW-U updates the rule according to the rule update indication information sent by the GW-C, and deletes the data service processing result associated with the modified rule, so that a related data service can be matched with a rule again. That is, if the rule is modified, the related
20 data service can be matched with a new rule, and creation or update of a bearer is triggered.

S405. A data packet triggers a dedicated bearer to be processed.

In this embodiment of the present invention, a GW-C may send a traffic query request to a GW-U, so as to monitor a traffic status of a bearer, determine whether a
25 data service ends, and trigger the bearer to be deleted or updated. As shown in FIG. 9, the following steps are included.

S501. The GW-C sends a traffic query request to the GW-U.

In this embodiment of the present invention, the traffic query request sent by the GW-C to the GW-U is used to instruct the GW-U to collect statistics about traffic of a
30 specified bearer.

Specifically, in this embodiment of the present invention, the traffic query request sent by the GW-C may be indication information used for obtaining statistics about traffic in a timely manner, and the like, or may be indication information that includes a name type of a traffic statistics query request message of the bearer.

Further, the traffic query request may further include a bearer identifier, for example, a bearer object ID, so as to collect statistics about the traffic of the specified bearer.

In this embodiment of the present invention, the GW-C may send the traffic query request to the GW-U at regular time intervals.

5 S502. The GW-U receives the traffic query request, collects statistics about traffic of a specified bearer according to the traffic query request, and sends a statistical result to the GW-C.

S503. The GW-C triggers, according to the statistical result, a procedure for deleting a dedicated bearer.

10 In this embodiment of the present invention, the GW-C may determine, according to the statistical result, whether the traffic of the specified bearer changes at a specified time interval. If the traffic does not change at the specified time interval, it is determined that the specified bearer does not transmit data at the specified time interval, and a trigger condition for deleting the dedicated bearer is met. The GW-C
15 initiates the procedure for deleting the dedicated bearer. For the procedure initiated by the GW-C for deleting the dedicated bearer, refer to an existing procedure. This is not limited in the present invention.

It should be noted that the procedure initiated by the GW-C for deleting the dedicated bearer relates to network elements such as an MME, an eNodeB, and UE.

20 In FIG. 9, some of the network elements are omitted.

S504. The GW-C interacts with the GW-U, and deletes processing logic related to the specified bearer.

In this embodiment of the present invention, the GW-C regularly sends the traffic query request to the GW-U. The GW-U collects statistics about the traffic of the
25 specified bearer according to the traffic query request, and sends the statistical result to the GW-C. The GW-C determines a traffic change status of the specified bearer according to the statistical result, and deletes a corresponding dedicated bearer if the traffic does not change at the specified time interval.

In this embodiment of the present invention, if a GW-U determines that a data
30 service ends, the GW-U may further interact with a GW-C, so as to delete or update a bearer. As shown in FIG. 10, the following steps are included.

S601. The GW-U detects a data service status, and determines that a data service ends.

In this embodiment of the present invention, the GW-U may determine whether

the data service ends by detecting a service flow (a service data flow filter or an application detection filter) traffic feature, a data service packet feature, or the like. For example, if no traffic is generated at a specified time interval, the GW-U determines that the data service ends. If the GW-U detects a data packet feature
5 indicating that the data service ends, for example, the GW-U detects an end-of-Transmission Control Protocol (Transmission Control Protocol, TCP) packet, the GW-U may determine that the data service ends.

S602. The GW-U sends end-of-data-service indication information to the GW-C.

In this embodiment of the present invention, the GW-U may send the
10 end-of-data-service indication information to the GW-C according to reporting indication information sent by the GW-C to the GW-U. The reporting indication information is used to instruct the GW-U to send the end-of-data-service indication information to the GW-C if the GW-U detects that the data service ends. The reporting indication information may be included in a rule or a subscription event sent by the
15 GW-C to the GW-U.

In this embodiment of the present invention, the GW-U may further locally determine whether the end-of-data-service indication information needs to be sent to the GW-C. For example, if a bearer in which the data service is located is an assured bandwidth (Guaranteed Bit Rate, GBR) bearer, and the bearer includes another
20 service different from the data service, the GW-U sends the end-of-data-service indication information to the GW-C if the GW-U detects that the data service ends.

Further, in this embodiment of the present invention, the end-of-data-service indication information includes data service description information. The data service description information may be specific service flow feature information such as
25 packet filter, service data flow filter (Service Data Flow Filter), or application detection filter (Application Detection Filter). The data service description information may be further an identifier of a rule or a subscription event to which the data service is bound. The GW-C obtains the service flow feature information according to the identifier.

30 Further, in this embodiment of the present invention, the GW-U may include, in the end-of-data-service indication information, a bearer identifier of the bearer in which the data service is located, so that the GW-C determines corresponding bearer information according to the bearer identifier, and initiates bearer update to the bearer.

S603. The GW-C removes a data service indicated by the end-of-data-service

indication information from a traffic flow template TFT of a bearer.

In this embodiment of the present invention, the GW-C deletes the data service indicated by the end-of-data-service indication information from the bearer. That is, the GW-C initiates a procedure for updating the bearer, so as to remove service flow
5 feature information of the data service from the TFT, and generate new TFT information.

S604. The GW-C interacts with the GW-U, to update the bearer and processing logic related to the bearer.

Further, for the GBR bearer, the end-of-data-service indication information sent
10 by the GW-U to the GW-C further includes QoS information of a deleted service flow. The QoS information of the deleted service flow is mainly bandwidth information. The GW-C obtains new QoS information of the bearer according to current QoS information of the bearer and the QoS information of the deleted service flow. The new QoS information is mainly bearer bandwidth information in the QoS information
15 of the bearer.

In this embodiment of the present invention, the GW-U sends the end-of-data-service indication information to the GW-C, so that the GW-C determines a bearer for which a data service ends, and triggers the corresponding bearer to be updated.

20 The foregoing descriptions are merely example implementations of the present invention, but are not intended to limit the protection scope of the present invention. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in the present invention shall fall within the protection scope of the present invention. Therefore, the protection scope of the present
25 invention shall be subject to the protection scope of the claims.

CLAIMS

What is claimed is:

1. A bearer processing system comprising:

5 a gateway user plane (GW-U) comprising:

a first receiver configured to receive a data packet, a first processor and a first memory for storing a first program to be executed in the first processor, the first program comprising instructions that when executed cause the first processor to:

match the data packet with a rule, and

10 determine that a rule matching result of the data packet meets a trigger condition for bearer processing, wherein the rule is a subscription event obtained by the GW-U from a gateway control plane (GW-C), the subscription event comprises type information description of a data service on which bearer processing needs to be performed, and the trigger condition comprises that the data packet matches the type information
15 description;

a first transmitter configured to send bearer processing indication information to the GW-C in response to determining that the rule matching result of the data packet meets the trigger condition for bearer processing, wherein the bearer processing indication information is used to trigger the GW-C to perform bearer processing according to quality
20 of service (QoS) information of a data service corresponding to the data packet; and

the GW-C comprising:

a second receiver configured to receive the bearer processing indication information from the GW-U,

a second processor and a second memory for storing a second program to be
25 executed in the second processor, the second program comprising instructions that when executed cause the second processor to

determine, according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet, and perform bearer processing according to the QoS information of the data service corresponding to the data packet.

5 2. The bearer processing system according to claim 1, wherein the rule further comprises a correspondence between the data service and the QoS information;

wherein the trigger condition further comprises that QoS information required for the data service is inconsistent with QoS information of a current bearer that is currently used for transmitting the data service; and

10 wherein the first program comprises further instructions that cause the first processor to match the data packet with the rule by finding, from the rule, the QoS information required for the data service corresponding to the data packet.

3. The bearer processing system according to claim 2, wherein the QoS information required for the data service is inconsistent with the QoS information of the current bearer
15 in response to determining that:

an allocation/retention priority (ARP) required for the data service is inconsistent with an ARP of the current bearer that is currently used for transmitting the data service, or
a QoS class identifier (QCI) required for the data service is inconsistent with a QCI of the current bearer that is currently used for transmitting the data service.

20 4. The bearer processing system according to claim 2, wherein the bearer processing indication information comprises the QoS information required for the data service.

5. The bearer processing system according to claim 2, wherein each correspondence that is between a data service and QoS information and that is in the rule is corresponding to a rule identifier, and the bearer processing indication information comprises a rule identifier of a correspondence matching the data packet; and

5 wherein the second program causes the second processor to determine the QoS information of the data service corresponding to the data packet by causing the second processor to determine, according to the rule identifier, the QoS information of the data service corresponding to the data packet.

6. The bearer processing system according to claim 1, wherein the GW-C further
10 comprises a second transmitter configured to send a subscription event to the GW-U; and

 wherein the second program causes the second processor to determine the QoS information of the data service corresponding to the data packet by causing the second processor to

 determine, according to the bearer processing indication information, a data
15 service type corresponding to the data packet; and

 allocate, QoS according to the data service type; or receive, by the GW-C from another network element device, QoS that is allocated according to the data service type, wherein the another network element device is a network element device that is in an evolved packet core (EPC) and that is different from the GW-U and the GW-C.

20 7. The bearer processing system according to claim 6, wherein the bearer processing indication information comprises an application identifier, and the application identifier is used to identify a data service type matching the data packet.

8. The bearer processing system according to claim 6, wherein the type information description that is in the subscription event and that is of the data service on which bearer

processing needs to be performed is corresponding to an event identifier, and the bearer processing indication information comprises an event identifier corresponding to type information description matching the data packet; and

wherein the second program causes the second processor to determine the data service type corresponding to the data packet by causing the second processor to:

determine, according to the event identifier, the type information description that is of the data service and that is corresponding to the event identifier; and

determine, according to the type information description, the data service type corresponding to the data packet.

9. The bearer processing system according to claim 1, wherein the first transmitter is further configured to:

send packet feature information of the data packet to the GW-C, wherein the packet feature information is used by the GW-C to bind the data service corresponding to the data packet to a bearer; and

wherein the second program comprises further instructions that cause the second processor to:

receive the packet feature information that is of the data packet from the GW-U, and bind, according to the packet feature information, the data service corresponding to the data packet to the bearer.

10. The bearer processing system according to claim 9, wherein the packet feature information is packet filtering information, and the packet filtering information comprises items of a service quintet of the data packet.

11. The bearer processing system according to claim 1, wherein the second program comprises further instructions that cause the second processor to send rule update

indication information to the GW-U, wherein the rule update indication information comprises content of a modified rule, a rule identifier of the modified rule, and a bearer processing manner corresponding to the modified rule; and

5 wherein the first program comprises further instructions that cause the first processor to: receive the rule update indication information from the GW-C, update the rule according to the rule update indication information, and delete a data service processing result associated with the modified rule, wherein the data service processing result is a result obtained by processing, by the GW-U, a data service corresponding to a data packet that meets the trigger condition for bearer processing.

10 12. The bearer processing system according to claim 1,

wherein the second program comprises further instructions that cause the second processor to:

send a traffic query request to the GW-U, wherein the traffic query request is used to instruct the GW-U to collect statistics about traffic of a specified bearer;

15 receive a statistical result obtained by collecting, by the GW-U, statistics about the traffic of the specified bearer according to the traffic query request; and

delete the specified bearer if it is determined, according to the statistical result, that accumulated traffic data of the specified bearer does not change at a specified time interval; and

20 wherein the first program comprises further instructions that cause the first processor to:

receive the traffic query request from the GW-C, collect statistics about the traffic of the specified bearer according to the traffic query request, and send the statistical result to the GW-C.

13. A gateway user plane (GW-U) comprising:
- a receiver configured to receive a data packet;
 - a transmitter;
 - a processor; and
- 5 a memory storing a program to be executed in the processor, the program comprising instructions for matching the data packet with a rule, and
- controlling the transmitter to send bearer processing indication information to a gateway control plane (GW-C) in response to determining that a rule matching result of the data packet meets a trigger condition for bearer processing;
- 10 wherein the bearer processing indication information is used to trigger the GW-C to perform bearer processing according to quality of service (QoS) information of a data service corresponding to the data packet, wherein the transmitter is configured to send the bearer processing indication information to the GW-C; and
- wherein the rule is a subscription event transmitted to the GW-U from the GW-C,
- 15 the subscription event comprises type information description of a data service on which bearer processing needs to be performed, and the trigger condition comprises that the data packet matches the type information description.
14. The GW-U according to claim 13, wherein the rule is a correspondence between the data service and the QoS information; and
- 20 wherein the program comprises further instructions that when executed cause the processor to
- find, from the rule, QoS information required for the data service corresponding to the data packet, and
- determine that the trigger condition further comprises that the QoS information

required for the data service is inconsistent with QoS information of a current bearer that is currently used for transmitting the data service.

15. The GW-U according to claim 14, wherein the bearer processing indication information comprises the QoS information required for the data service, or a rule identifier
5 of a correspondence matching the data packet.

16. The GW-U according to claim 13,
wherein the bearer processing indication information comprises an application identifier, and the application identifier is used to identify a data service type matching the data packet; or

10 wherein the bearer processing indication information comprises an event identifier corresponding to type information description matching the data packet.

17. A gateway control plane (GW-C), comprising:

a receiver configured to receive bearer processing indication information from a gateway user plane (GW-U), wherein the bearer processing indication information is used
15 to instruct the GW-C to perform bearer processing according to quality of service (QoS) information of a data service corresponding to a data packet;

a processor; and

a memory storing a program to be executed in the processor, the program comprising instructions for:

20 determining, according to the bearer processing indication information, the QoS information of the data service corresponding to the data packet, and

performing bearer processing according to the QoS information of the data service corresponding to the data packet; and

a transmitter configured to transmit a rule to the GW-U, wherein the rule is a

subscription event, the subscription event comprises type information description of a data service on which bearer processing needs to be performed.

18. The GW-C according to claim 17, wherein the program comprises further instructions that when executed cause the processor to:

5 determine whether QoS information of all bearers in an evolved packet core EPC comprises QoS information consistent with the QoS information of the data service corresponding to the data packet; and

 in response to determining that the QoS information of all the bearers in the evolved packet core comprises the QoS information consistent with the QoS information of the data
10 service corresponding to the data packet, update a bearer corresponding to the QoS information that is consistent with the QoS information of the data service corresponding to the data packet, wherein QoS information of an updated bearer is consistent with the QoS information of the data service corresponding to the data packet; or

 in response to determining that the QoS information of all the bearers in the
15 evolved packet core does not comprise the QoS information consistent with the QoS information of the data service corresponding to the data packet, create a dedicated bearer, wherein QoS information of the dedicated bearer is consistent with the QoS information of the data service corresponding to the data packet.

19. The GW-C according to claim 17, wherein
20 the program comprises further instructions that when executed cause the processor to:

 determine, according to the bearer processing indication information, a data service type corresponding to the data packet; and

 allocate, QoS according to the data service type; or the receiver is configured to

receive from another network element device, QoS that is allocated according to the data service type, wherein the another network element device is a network element device that is in an evolved packet core (EPC) and that is different from the GW-U and the GW-C.